



- (51) International Patent Classification:
A61B 34/20 (2016.01) A61B 90/00 (2016.01)
A61B 34/30 (2016.01)
- (21) International Application Number:
PCT/US2016/021205
- (22) International Filing Date:
7 March 2016 (07.03.2016)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
62/128,857 5 March 2015 (05.03.2015) US
- (71) Applicant: **THINK SURGICAL, INC.** [US/US]; 47320 Mission Falls, Fremont, California 94539 (US).
- (72) Inventors: **BONNY, Daniel Patrick**; 47320 Mission Falls Court, Fremont, California 94539 (US). **ZUHARS, Joel**; 47320 Mission Falls Court, Fremont, California 94539 (US). **NETRAVALI, Nathan A.**; 452 Fernando Avenue, Palo Alto, California 94306 (US).
- (74) Agent: **GOLDSTEIN, Avery N., PH.D.**; Blue Filament Law PLLC, 450 N. Old Woodward Avenue, First Floor, Birmingham, Michigan 48009 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: METHODS FOR LOCATING AND TRACKING A TOOL AXIS





FIG. 1

(57) Abstract: A calibration device is provided having a body with an exterior surface configured for placement about a tool such that the body rotates about a tool axis. One or more fiducial marker is positioned on the exterior surface and in communication with a tracking system. A fixed fiducial marker array is provided that is also in communication with the tracking system. A calibration tool defines the tool axis relative to the fiducial marker array. A surgical system is also provided with a tracking module that calculates a center point of the rotation or a normal vector to the circular path to define a tool axis orientation. A method of using the surgical system and defining a tool axis relative to a fiducial marker array is provided. A system for defining a robot link orientation or tracking a tool a medical procedure and a fiducial marker array are provided.



- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

METHODS FOR LOCATING AND TRACKING A TOOL AXIS

RELATED APPLICATIONS

[0001] This application claims priority benefit of US Provisional Application Serial Number
5 62/128,857 filed 5 March 2015; the contents of which are hereby incorporated by reference.

FIELD OF THE INVENTION

[0002] The present invention generally relates to the field of computer-aided surgical
systems, and more specifically to a new and useful device and method for calibrating a tool
10 relative to a tracking system.

BACKGROUND OF THE INVENTION

[0003] Computer-assisted surgical systems are widely used to aid surgeons in performing a
variety of medical procedures. One such example is the ROBODOC™ Surgical System (Think
Surgical™, Fremont, CA) that assists a surgeon in preparing the femoral canal in total hip
15 arthroplasty (THA). In order to prepare the canal with submillimeter accuracy, both the tool
center point (TCP) and the center axis of the tool must be accurately calibrated with respect to a
robotic coordinate frame as well as any other tracking system coordinate frame. The tracking
system may also be used to locate and track other objects in the operating room such as the
anatomy of interest or other medical devices. Therefore the relationships between all of the
20 tracked objects may be coalesced to improve or aid in a medical procedure in a dynamic manner.

[0004] Tracking systems typically include multiple receivers that detect energy from a set of
passive or active fiducial markers. In order to define the relationship between the tool
orientation and tip position relative to an array of tracked fiducial markers, a calibration
procedure must be performed. There are many different methods of calibrating an array of
25 fiducial markers relative to a tool tip position and orientation, however the processes are usually
time-consuming, costly and/or not accurate enough for a particular surgical procedure.

[0005] One existing method of calibration is to manufacture the array at a precise position and orientation on the tool followed by a factory calibration step. However, the method requires precise placement of the array on every tool that may be used in a surgical setting, increasing overall costs. An alternative method is to calibrate the tool relative to the array within the operating room. A digitizer either mechanically or optically tracked is manually positioned to collect a number of points on the tool to define the geometric relationship between the tool and the array. However, when calibrating an optically-tracked cutting tool using single measurements, tracking systems are insufficiently accurate to be used as a calibration device based on the inherent error of the system. Additionally, the digitizing process is laborious for the user and increases overall operating time.

[0006] Once the relationship between the fiducial marker array and the tool are known, the position and orientation of the tool may be accurately tracked during a procedure. However, another problem with traditional tracking systems is an inherent error in locating each of the fiducial markers in three-dimensional space during tracking, which may affect tracking accuracy. The errors may be a function of the triangulation, sampling times, manufacturing errors in the geometric relationship between fiducial markers, and the fact that the markers are stationary with respect to one another. Considering the need for very precise surgical procedures, any method that can improve the accuracy of the tracking system is highly desirable.

[0007] Thus there is a need in the art for a calibration device that can quickly and accurately define a tool tip position and orientation relative to a tracking array in computer-assisted surgical systems and other robotic applications that require a high level of precision. There is a further need to improve the accuracy of the tracking to improve the results of a surgical procedure and the reliability of the surgical system, or for other robotic applications.

SUMMARY OF THE INVENTION

[0008] A calibration device is provided that has a body with an exterior surface. The body is configured for placement about a tool having a tool axis such that the body rotates about the tool

axis. At least one fiducial marker is positioned on an exterior surface of the body and is in communication with a tracking system. A fixed fiducial marker array is provided that is also in communication with the tracking system. A calibration tool defines the tool axis relative to the fiducial marker array.

5 [0009] A surgical system is also provided that includes a tool and a tracking module. A fiducial marker array is fixed to the tool and in communication with the tracking module. A calibration device includes a body with at least one fiducial marker positioned on the body, where the body is configured for placement about the tool such that the body rotates about a tool axis. In response to the rotation of the body one or more circular paths are generated by the at least one fiducial marker that are tracked by the tracking module, and the tracking module
10 calculates at least one of a center point of the rotation or a normal vector to the circular path to define a tool axis orientation relative to the fiducial marker array fixed to said tool and to said tracking module. A method of using the surgical system includes the calculation of average of the normal vectors to the circular paths traced by two or more rotated fiducial markers, the average of the normal vectors between the center points of the circular paths traced by the two or
15 more rotated fiducial markers, or the average of the two aforementioned options.

[0010] A method for defining a tool axis relative to a fiducial marker array is provided that includes the fixation of a fiducial marker array to a surgical tool. A calibration device with at least one fiducial marker is attached on the tool. A calibration device is attached about the tools
20 axis. The rotation of said at least one fiducial marker is tracked with a tracking module. A normal vector and a center point are calculated from one or more circular paths traced by the fiducial marker rotation to define the tool axis orientation relative to the fiducial marker array.

[0011] A system for defining a robot link orientation is also provided that includes a distal link and a proximal link attached to the distal link. A tracking module and a set of fiducial
25 markers are placed on the distal link such that three fiducial markers from the set of fiducial

markers are visible to the tracking module such that a processor can define a first coordinate system on the distal link.

[0012] A system for tracking a tool to aid in a medical procedure is also providing that includes a surgical tool equipped with a tracking module. A rotating body coincident about an axis of the tool is provided. The rotating body includes at least one fiducial marker such that the tracking module records a position of the at least one fiducial marker as the at least one fiducial marker rotates about the tool axis.

[0013] A fiducial marker array for tracking an object in the context of surgical robot is provided that includes a rigid body and at least one fiducial marker in communication with a tracking module that rotates creating a circular path on a region of the rigid body whereby the at least one fiducial marker is offset a distance from the center of rotation of the fiducial marker.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The present invention is further detailed with respect to the following drawings that are intended to show certain aspects of the present invention, but should not be construed as a limit on the practice of the present invention.

[0015] FIG. 1 illustrates the main components of the system in accordance with embodiments of the invention in the context of a surgical table or operating room;

[0016] FIGs. 2A, 2B, and 2C depict a calibration device and method for defining a tool axis orientation relative to a fiducial marker array in accordance with embodiments of the invention;

[0017] FIG. 3 depicts a calibration device capable of clipping onto a tool in accordance with embodiments of the invention;

[0018] FIGs. 4A and 4B are a cross-section views of a calibration device defining a tool tip center point relative to fiducial marker array in accordance with embodiments of the invention;

[0019] FIGs. 5A and 5B illustrate a method for determining a link axis and link rotation angle of a robot in accordance with embodiments of the invention;

[0020] FIG. 6 depicts a rotating fiducial marker incorporated with a tool for tracking in accordance with embodiments of the invention; and

[0021] FIGs. 7A and 7B depict rotating fiducial markers on a fiducial marker array to improve tracking accuracy in accordance with embodiments of the invention.

5

DETAILED DESCRIPTION OF THE INVENTION

[0022] The present invention has utility as a system and process to accurately and efficiently define a position and orientation of a tool relative to a fiducial marker array, which will aid in a medical procedure. The following description of various embodiments of the invention is not
10 intended to limit the invention to these specific embodiments, but rather to enable any person skilled in the art to make and use this invention through exemplary aspects thereof.

[0023] It is to be understood that in instances where a range of values are provided that the range is intended to encompass not only the end point values of the range but also intermediate values of the range as explicitly being included within the range and varying by the last
15 significant figure of the range. By way of example, a recited range from 1 to 4 is intended to include 1-2, 1-3, 2-4, 3-4, and 1-4.

[0024] As used herein, a fiducial marker refers to a point of reference detectable by a tracking system and may be, for example, an active transmitter, such as a light emitting diode (LED) or electromagnetic emitter; or a passive reflector, such as a plastic sphere with a retro-reflective
20 film. In specific embodiments, the use of a particular type of fiducial marker is defined as such for those applicable embodiments. A fiducial marker array is an arrangement of two or more fiducial markers in a known geometric relationship in/on a rigid body of any geometric shape; an arrangement of three fiducial markers may be used to resolve all six degrees of freedom (6-DOF) of the rigid body, unless otherwise specified.

25 [0025] The term 'tool' can be any instrument capable of performing work on an external object. These illustratively include a probe, drill, cutter, burr, or saw blade; as well as any

assembly used to house and/or operate the tissue contacting instrument (e.g. a cutter coupled to a drill and assembled in a housing, where the housing may be attached to the distal end of a robotic manipulator arm).

[0026] As used herein, the term ‘communication’ is to refer to the sending and/or receiving of data and/or energy either through a wireless or electrical connection.

[0027] Disclosed herein is the use of a tracking system. The tracking system includes at least one receiver to detect energy either emitted or reflected from a fiducial marker, where the receiver is coupled to a tracking module having a processor for processing a position and/or orientation (POSE) of a fiducial marker or fiducial marker array. The tracking module can generate a tool position based on the relationship between the fiducial marker array and the tool, where the relationship is determined using the calibration techniques described herein. In particular embodiments, the calibration technique uses a calibration device in communication with the tracking module to provide at least one reference point for determining the tool’s position. The detectable energy can be for example but not limited to optical, electromagnetic, infrared, ultraviolet, magnetic, fiber optic, ultrasound and targeted visible light. An example of an optical tracking system is the Polaris Spectra® Optical Tracking System (NDI Medical). Also referenced herein are computer-assisted surgical systems, which are to be considered synonymous with computer-aided surgical systems, robotic surgical systems, navigation assisted surgical systems, image-guided surgical systems and the like.

[0028] As reference will be made to the ROBODOC™ Surgical System, it should be appreciated that any autonomous, haptic, or semi-autonomous robotic system either for medical or industrial applications can benefit from the device and methods disclosed herein. Examples of computer-assisted surgical systems that may benefit from the invention disclosed herein include for example the ROBODOC™ Surgical System (Think Surgical, Inc.), NavioPFS™ System (Blue Belt Technologies, Inc.), The RIO® Robotic System (Mako Surgical Corp.) a navigated freehand saw (TRAK Surgical), 4 degree of freedom saw, an articulating hand-held

system with at least one degree of freedom, an articulating hand-held drilling system disclosed in provisional application 62/054,009 and incorporated herein by reference in its entirety, or any other computer-controlled device that requires tracking.

[0029] Embodiments of the present invention describe a system, device and methods to
5 define a tool axis orientation and tool center point relative to a fiducial marker array to accurately track a tool to aid in a medical procedure. FIG. 1 depicts a high-level overview of a surgical system 101 to perform a computer-assisted surgery. Generally, a computer-assisted surgical system 103 includes a user interface 107 and tool 105, and is positioned to aid in a medical procedure on a patient 109. The user interface 107 may be a monitor to display user
10 instructions such as, operating parameters, procedural workflow, the robotic state, functioning errors, guide commands, and a real-time view of a tool modifying tissue. The user interface 107 is also in certain embodiments a heads-up display unit (HUD), GoogleTM glasses, an external monitor, and/or a smart watch which may be electrically or wirelessly in communication with the robotic system. For example, a HUD is illustratively wirelessly connected to the robotic
15 system via Bluetooth, TCP/IP, visible light communication, WLAN, or combination thereof. The robotic system and/or user interface may receive input from the user through the use of a controller device like a joystick, mobile phone, or by touching the monitor, or combination thereof. Such inputs may include for example guide commands, selecting various prompts given throughout a procedural workflow, selecting a certain medical procedure, designating the
20 position of other external components/devices, aiding in registration of anatomy, configuring an optical tracking module, and combinations thereof. The surgical system 101 includes a tracking system 110 having detectors 112 coupled to a tracking module 111 to detect fiducial markers (203, 213 of FIG. 2) and track fiducial marker arrays (211 of FIG. 2) that may be positioned on the anatomy of interest, on the base of the surgical system 103, on the tool 105, on
25 the calibration device 201, as well as on any other medical devices or reference locations to ensure the tool/s are accurately executing the procedure. Prior to surgery, a fiducial marker

array is positioned and fixed with respect to the tool 105. The tool 105 is then calibrated using the methods described below so the tracking module 111 knows the exact location of the tool axis orientation and tool center point.

[0030] An inventive embodiment of a device to quickly and more accurately calibrate a tool axis orientation relative to a fiducial marker array and tracking system is shown in FIGs. 2A-2C. FIG. 2A depicts a calibration device 201 in the shape of a hollow cylindrical sleeve that includes at least one fiducial marker 203. The fiducial marker 203 being either passive or active. The calibration device 201 may include two or more fiducial markers 203 positioned along the axis of the sleeve 201 as depicted in FIG. 2C. In another embodiment, with respect to FIG. 3, the calibration device 301 includes two or more attachment points or clips 311 capable of clipping onto a tool axis 307. A rigid member 303 assembled to the two or more attachment points or clips 311 has at least one fiducial marker 305 placed thereon, where the rigid member 303 is capable of rotating about the tool axis 307. The attachment clips 311 may come in varying diameters and may be modularly assembled to the rigid member 303. For example, clips 311 with different diameters may be assembled to the rigid member 303 at point 309, to accommodate tools of varying diameter. In a specific inventive embodiment, the attachment clips 311 loosely grasp the tool 105 to allow the entire calibration device 301 to freely rotate about the tool axis 307. In another specific embodiment, the attachment clips 311 include a bearing such that the clips may firmly grasp the tool and a bearing mechanism between the clip 311 and the rigid member 303 allows for the rigid member 303 to freely rotate about the attachment clips 311 and tool axis 307.

[0031] In specific embodiments, in order to define the tool axis 217 relative to the fiducial marker array 211, a fiducial marker array 211 includes a set of fiducial markers 213 in a known geometric relationship to resolve 6 degrees of freedom, where the fiducial marker array 211 is rigidly fixed to a tool 105. The tool 105 being attached to a distal end, link and or joint 205 of a computer controlled device. In a specific embodiment, the fiducial marker array 211 is

incorporated and packaged with the tool 105, while in other embodiments the fiducial marker array is a separate entity, packaged separately, and is assembled and fixed to the tool 105 by a user in the operating room. The tool 105 may further have a working end with a tool tip surface and tool center point 207 to perform work on a workpiece. The calibration device is then placed
5 on and/or clipped to the tool 105. The calibration device 201 may rotate freely (arrow 215) about the tool 105 but, in certain embodiments, cannot translate along the tool. In a specific embodiment, the calibration device 201 may be placed on the tool 105 such that gravity keeps the device against the end of the tool to prevent translation. The tool 105 and/or calibration device 201 may have a connection such as a rotary coupling to ensure translation does not occur.
10 Additionally, the system may easily detect if the calibration device 201 has translated along the tool axis 217 during calibration and notify the user via a monitor, or audible alert for example.

[0032] In specific embodiments, the rotation may be done manually by a user who places the calibration device sleeve 201 on the tool 105 and rotates the calibration device 201 as the tracking system records the position of the fiducial marker 203 as it rotates. The calibration
15 device 201 may have a handle, a grip, or an extruding portion that allows the user to easily rotate the calibration device 201 about the tool 105. In a specific embodiment, the calibration device 201 may automatically rotate about the tool 105. The calibration device 201 may have a connection on the proximal end that interacts with the tool 105. For example, the proximal end of the calibration device 201 may have a set of threads that screw into a portion of the tool 105
20 that is in communication with components such as motors, gears, actuators, rotary coupling, or any other conventional mechanical device that allows the calibration device 201 to automatically rotate about the tool 105. In a specific embodiment, the components to rotate the calibration device may include the same and/or similar elements used to operate the working end of the tool 105. Alternatively, the calibration device 201 includes a driver to automatically rotate itself
25 about the tool 105. For example, the calibration device 201 may include multiple concentric

sleeves wherein a first innermost sleeve remains stationary on the tool 105 and a second sleeve encompassing the first sleeve has a driver to rotate a fiducial marker 203 about the tool 105.

[0033] As the fiducial marker 203 rotates about the tool 105, the tracking system records the markers position throughout rotation. The fiducial marker 203 traces concentric circles of equal number to the number of fiducial markers. For example, one fiducial marker will trace a single concentric circle, while multiple fiducials as shown in FIG. 2B will trace multiple concentric circles along the axis of the calibration device 201. The tracking module 111 fits a circle to the positions recorded during rotation. The circle may be fitted to the data using algorithms such as a least squares methods including, but not limited to Gauss-Newton, Levenberg-Marquardt, Newton, variable projection, and orthogonal distance regression, Mahalanobis distance, or a combination thereof. It should be noted that only an arc of points is needed to model the data. The fitted circle has a center 219 on the tool axis and a normal vector 221, where the normal vector 221 represents the orientation of the tool axis 217. Therefore, the orientation of the tool axis can be defined relative to the fiducial marker array 211 based on the POSE of the fiducial marker array 211 with respect to the calculated normal vector 221.

[0034] In inventive embodiments where multiple fiducial markers 203 are used, then each circle will have a normal vector where the orientation of the tool axis 217 may be calculated by one or a combination of the following:

- i. The average of each of the tool vectors
- ii. The average of the vectors from one circle center to another
- iii. The average of i. and ii.

Thus by using multiple fiducial markers 203, the accuracy in defining the true orientation of the tool axis relative to the fiducial marker array 211 increases. As only one fiducial marker 203 is necessary to obtain the tool axis orientation relative to the fiducial marker array 211, multiple fiducial markers increases the accuracy of the calibration. Furthermore, by increasing the

spacing between the fiducial markers along the tool axis 217 the accuracy of the calibration is improved when using the circle centers, where more information along a greater portion of the tool is captured. One primary advantage of the calibration devices described herein is there is no need to manufacture a precise geometric relationship between two or more of the fiducial markers 203 on the calibration device 201. Likewise, the tracking system does not need to resolve a full 6-DOF of the calibration device to accurately calibrate the tool to the tracking system (i.e. only one marker is technically needed to locate the tool axis orientation). In current systems, a precise geometric relationship between three or more fiducial markers is needed to accurately calibrate a tool. This increases manufacturing costs due to the required tolerances and can induce tracking errors where slight deviations in the geometric relationships occur during manufacturing.

[0035] In a specific embodiment, the processor may fit a cylindrical model to the calibration data. If a cylindrical model is used, then the calibration device may translate along the tool axis 217 where the tool axis 217 orientation may still be calculated. However, when using a cylindrical model, a subsequent step is needed to locate the tool center point as described below.

[0036] When fitting a circular or cylindrical model to the data, the algorithm may also account for the distribution of recorded positions as the fiducial marker 203 rotates about the tool 105. More data points may be collected in one position compared to another depending on the rotation speed or even how the user performs the calibration procedure. If more data points are collected during a particular part of the rotation compared to another, the circular or cylindrical model may be weighted towards the clustered region affecting the normal vectors and/or center points. Therefore, the algorithm may adjust the data such that an even distribution of points about the tool axis 217 is used to fit the circle or cylinder.

[0037] In a specific embodiment, one end of the calibration device 201 includes an abutment surface 401 as depicted in FIG. 4A. FIG. 4A is a cross-section view of the calibration device 201 placed about the axis of tool 105. One or more fiducial markers 203 are spaced a known

distance 'd' from the abutment surface 401. When the calibration device 201 is placed over and/or clipped about the axis of the tool 105, the abutment surface 401 is coincident with the tool tip surface. If multiple fiducial markers 203 are used, then each of the fiducial markers 203 may be spaced at a known distance from the abutment surface 401. Although, only one of the
5 fiducial markers 203 is required to have a known distance 'd' from the abutment surface 401, such as the most proximal or distal fiducial marker on the calibration device 201. In this embodiment, both the orientation of the tool axis 217 and the tool center point 207 of the working end may be defined relative to the fiducial marker array 211. The abutment surface 401 may be in full contact with the tool tip surface as shown in FIG. 4A or only a portion of the tool
10 tip surface may be in contact with the abutment surface 401 as shown in FIG. 4B.

[0038] The fiducial marker array 211 capable of resolving 6 degrees of freedom is rigidly fixed to the tool 105. The calibration device 201 with the abutment surface 401 is placed on the tool 105 such that the abutment surface 401 is coincident with the tool tip surface. The calibration device 201 is rotated about the tool 105 and the tracking module calculates the
15 normal vector 221 and tool axis orientation 217 using fitted circles as described above. The known distance from one or all fiducial markers on the sleeve to the abutment surface 401 is used to compute a plane that defines the end of the tool vector. For example, a plane is defined in space by the circle(s) traced by the fiducial marker(s) 203 at the position of the fiducial marker. By translating the circular plane the known distance from the fiducial marker(s) 203 to
20 the abutment surface, a plane can be defined at the tool tip surface. The intersection of the plane defined at the tool tip surface and the normal vector calculated from the traced circular paths defines the tool tip center point 207 on the tool axis 217. Thus both the tool tip center point 207 of the working end of the tool and the orientation of the tool axis are defined relative to the fiducial marker array 211.

[0039] In a specific inventive embodiment, the tool center point 207 at the working end may be defined using a digitizer. Instead of having an abutment surface 401 on the calibration device

201, a plane at the tool tip surface is defined by digitizing a number of points on the tip of the tool. A digitizer generally includes a probe that is either mechanically or optically tracked to collect points in space relative to a coordinate system. The digitizer may be coupled to a robotic system as described in U.S. Pat. No. 6,033,415 which is incorporated by reference herein in its entirety. If the digitizer is coupled to the robotic system, a processor of the robotic system may perform the following calculations and communicate this information to the tracking module. If the digitizer is optically tracked, the tracking module may directly perform the following calculations. In this specific method embodiment, the orientation of the tool axis 217 relative to the fiducial marker array 211 can be determined using the embodiments described above. The tool tip center point 217 is determined by digitizing several points on the end of the tool 105, and a plane is best-fit to the digitized points using a processor or the tracking module. The tool tip center point position 207 is the intersection of the tool axis 217 defined by the calculated normal vector 221 to the traced circles, and the plane that is both perpendicular to the tool axis and best-fits the digitized points. Thus both the tool tip center point position 207 and the tool axis 217 are defined relative to the fiducial marker array 211.

[0040] The use of the calibration device 201 may further be used to check the calibration of a robotic computer-assisted surgical system. After performing any of the methods described in the previous embodiments, the robot may be actuated to move where the robot thinks the tool axis 217 is in robot coordinates. The calibration device 201 is then rotated with the tracking system recording the positions of fiducial marker(s) 203. A processor may fit a circle to the recorded positions of the fiducial marker. If the diameters of the circles fit to the traced paths, the centers of the circles fit to the traced paths, and the normal vectors of the circles fit to the traced paths all match within a specified tolerance those same parameters collected when the robot was originally calibrated then the calibration is valid. Likewise, if the diameters do not match, the centers do not match, the normal vectors do not match, or if the traced paths are not circular,

then the calibration is invalid. This procedure may similarly be used to check the calibration of the entire robot.

[0041] Embodiments of the present invention also describe a method to locate a joint axis using a fiducial marker array. With respect to FIG. 5A, a link 501 distal to the target joint axis contains several fiducial markers 503 in sufficient number such that at least three fiducial markers 503 on the link are visible to the optical tracking system no matter the rotation angle of the link 501. The several fiducial markers 503 on the link 501 may be considered a fiducial marker array. The fiducial markers 503 are spaced such that 1) a coordinate system 507 may be established on the link 501 using only three visible fiducial markers 503 and 2) the known nominal geometry of the fiducial markers 503 may be used to establish the same coordinate system given any three visible fiducials. As the link 501 is rotated about its axis of rotation, the optical tracking system tracks the visible fiducials. Because, the link 501 has a constant axis of rotation, each fiducial traces a circular path about the axis of rotation. A processor may fit circles to the traced fiducial markers and calculate an approximate center 509 of the link axis. The average of the centers defines the position of the link axis in space. The processor may additionally calculate a normal vector to the fitted circle. The average of the normal vectors defines the orientation 511 of the link axis. In a specific embodiment, because at least three fiducials 503 are visible at all times, a fixed coordinate system may be established on the flange. Any two arbitrary points in space which are both fixed to the fiducial marker coordinate system 507 and fixed in global coordinate throughout rotation define the axis of rotation of the joint. Embodiments of the method find points that are on the instantaneous rotation axis of the object (the robot link). While there are an infinite number of points that are on the axis of rotation, only two need to be found to define the axis. The two points are both a) constant in the local link coordinate system and b) constant in the global coordinates assuming that proximal links are not being actuated.

[0042] With respect to FIG. 5B, a second set of fiducial markers 513 may be placed just proximal of the distal link 501 to determine an absolute rotation angle between the two links. In one embodiment, the axis of rotation of the distal link is rotated relative to the proximal link to locate the axis of rotation as described in previous embodiments. Located on the proximal link, a similar set of fiducial markers 513 are positioned but with a different geometry such that the fiducials can be distinguished from the set of fiducial markers 503 on the distal link. The fiducial markers are spaced such that 1) a unique coordinate system 515 may be established on the flange using any three visible fiducials and 2) the known nominal geometry of the fiducial marker array may be used to establish the same coordinate system given any three visible fiducial markers. The angle between the two links may be determined by computing the relative rotation (i.e., projection angles) between the two coordinate systems about the axis of rotation of the link 501. The concept may be used for example to aid in calibrating a robot or used as an extra encoder. If fiducial marker arrays are positioned as described between and/or on each of the links, then the optical tracking system may define the position and orientation of the robot in any configuration. Therefore, a robot may be programmed to perform a calibration procedure where the optical tracking system may be used to measure the actual robot position and orientation compared to the programmed positions and orientations. In an alternative embodiment, any two arbitrary points in space which are constant in both the fiducial marker coordinate system 507 and the fiducial marker coordinate system of the proximal link 515 throughout rotation define the axis of rotation of the joint.

[0043] Embodiments of the present invention also describe a system and method for tracking a tool using fiducial markers which rotate about a fixed axis as well as a more accurate method of registering a fiducial marker array with its corresponding nominal model. With respect to FIG. 6, a rotating object 601, with the axis of rotation of the rotating object aligned such that it is coincident with the axis of the tool 105, is fixed to the tool. At least one fiducial marker 603 is attached or incorporated with the rotating object. The rotating object rotates at a high velocity.

The fiducial marker(s) are tracked by an optical tracking system which records multiple positions of the fiducial marker(s) such that a circular path is traced. In a specific embodiment, the optical receivers of the tracking module 111 are cameras where the circular path is traced throughout a series of camera frames. In a specific embodiment, the cameras may use a longer
5 shutter speed such that the one or more fiducial markers trace one or more circular paths in a single frame.

[0044] A calibration device 201 may be used to define the orientation 217 of the tool axis and/or the tool center point 207 of the working end relative to the rotating fiducial markers 603 using any of the methods describe previously. If the sampling rate of the camera and the rotation
10 rate of the fiducial marker(s) 603 are large, then the tool axis and tool tip position may be tracked using only the rotating fiducial marker(s) 603.

[0045] In a specific inventive embodiment, with the system including a rotating fiducial marker 603, a second marker array is attached to the tool with fiducial markers arranged in a geometry that is sufficient to resolve all six degrees of freedom of the tool. Although this
15 marker array would not be used to track the tool axis and tool tip, the marker array may be used to track the overall geometry of the tool for other functions such as collision avoidance. In another embodiment, one or more fiducial markers are fixed to the tool rather than a full array sufficient to resolve all six degrees of freedom. Since knowing the tool axis and tool tip position resolves the movement of the system in five degrees of freedom, the one or more fixed fiducial
20 markers can resolve the last degree of freedom (i.e., rotation about the tool axis).

[0046] In a specific embodiment of the present invention rotating fiducial markers on a fiducial marker array are utilized for improving the accuracy of tracking. With respect to FIGs. 7A and 7B, two fiducial marker array configurations 701 and 713 are shown. FIG. 7A depicts a fiducial marker array consisting of rotating bodies 705 with at least one fiducial marker 703
25 attached or incorporated therewith. Each rotational mechanism has zero mechanical play, such that each fiducial marker rotates 703 with constant radius with a center of rotation 709 that does

not move on the marker array. In a specific embodiment, the tracking system 110 receivers are cameras. The tracking system 110 tracks using a camera shutter speed such that the shutter is open long enough to capture a substantial portion of each fiducial marker(s) circular travel 707, with a full rotation being ideal. For example, if the fiducial markers were rotating at 10,000 revolutions per minute (rpm), then a shutter speed of 0.006 seconds would capture a full rotation, while a shutter speed of 0.003 seconds would capture half a rotation. A processor then fits a circle in three dimensions to each circular path, and the center 709 and normal vectors 711 are computed for each circular path. A nominal model, consisting of nominal centers and normal vectors for each fiducial marker, may be registered to the computed centers and normal vectors, thus registering the marker array to a nominal model during tracking.

[0047] Similarly, FIG. 7B illustrates a different configuration of a marker array 713 where at least one fiducial marker 703 rotates about a center of rotation 709. In this embodiment, the fiducial marker is capable of rotating on its own rather than on a rotating platform. As before, the center 709 and normal vectors 711 may be calculated and registered to a nominal model consisting of nominal centers and normal vectors for each fiducial marker during tracking. This method results in increased accuracy as well as a more accurate registration as the exact center and normal vectors are computed and used for tracking and registration. It should also be appreciated that with this configuration only two fiducial markers are necessary to resolve 6 degrees of freedom. At least one rotating fiducial marker 703 and a second fiducial marker (not shown) fixed to the fiducial marker array 701 or 713. Additionally, by adding rotating fiducial markers, redundant tracking in multiple degrees of freedom is possible with a minimal amount of fiducial markers.

Other Embodiments

[0048] While at least one exemplary embodiment has been presented in the foregoing detailed description, it should be appreciated that a vast number of variations exist. It should also

be appreciated that the exemplary embodiment or exemplary embodiments are only examples, and are not intended to limit the scope, applicability, or configuration of the described embodiments in any way. Rather, the foregoing detailed description will provide those skilled in the art with a convenient road map for implementing the exemplary embodiment or exemplary
5 embodiments. It should be understood that various changes can be made in the function and arrangement of elements without departing from the scope as set forth in the appended claims and the legal equivalents thereof.

CLAIMS

1. A calibration device comprising:
 - a body with an exterior surface, said body configured for placement about a tool having a tool axis such that said body rotates about the tool axis;
 - 5 at least one fiducial marker positioned on an exterior surface of said body, where said at least one fiducial marker is in communication with a tracking system;
 - a fixed fiducial marker array in communication with said tracking system; and
 - wherein said calibration tool defines said tool axis relative to said fiducial marker array.
- 10 2. The calibration device of claim 1 wherein said body is a hollow cylindrical sleeve.
3. The calibration device of claim 1 further comprising two or more fiducial markers offset axially along a longitudinal axis of said hollow cylindrical sleeve.
- 15 4. The calibration device of claim 2 wherein said at least one fiducial marker is positioned at a known distance from a first end of said hollow cylindrical sleeve.
5. The calibration device of claim 2 wherein said sleeve further comprises a first end
20 with an abutment surface, and where a position of the at least one fiducial marker is a known distance from said abutment surface.
6. The calibration device of any one of claims 1 to 5 wherein said body further comprises two or more attachment points or clips joined with a rigid member; and
25 wherein said at least one fiducial marker is positioned on said rigid member.

7. A surgical system comprising:

a tool having a tool axis;

a tracking module;

a fiducial marker array fixed to said tool and in communication with said tracking

5 module; and

a calibration device comprising a body with at least one fiducial marker positioned on said body, where said body is configured for placement about said tool such that said body rotates about the tool axis; and

wherein in response to the rotation of said body one or more circular paths are generated
10 by said at least one fiducial marker that are tracked by said tracking module, and said tracking module calculates at least one of a center point of the rotation or a normal vector to the circular path to define a tool axis orientation relative to the fiducial marker array fixed to said tool and to said tracking module.

15 8. The surgical system of claim 7 wherein said calibration device is a hollow cylindrical sleeve with two or more fiducial markers offset axially along a longitudinal axis of said hollow cylindrical sleeve.

9. A method of using the surgical system of any one of claims 7 or 8 for defining a
20 position of a tool center point at a working end of said tool with respect to said fiducial marker array by calculating:

a) an intersection of the normal vector of the one or more circular paths traced by said at least one fiducial marker at the center point of the rotation, and

b) a plane defined by an abutment surface on said calibration device that is a known
25 distance from the fiducial marker.

10. A method of using the surgical system of any one of claims 7 or 8 for determining the tool axis orientation comprising at least one of:

- a) calculating the average of the normal vectors to the circular paths traced by two or more rotated fiducial markers
- 5 b) calculating the average of the normal vectors between the center points of the circular paths traced by the two or more rotated fiducial markers, or
- c) calculating the average of a and b.

11. A method for defining a tool axis relative to a fiducial marker array comprising:

- 10 fixing said fiducial marker array to a tool;
- attaching a calibration device with at least one fiducial marker on the tool;
- rotating said calibration device about the tools axis;
- tracking the rotation of said at least one fiducial marker with a tracking module; and
- calculating a normal vector and a center point from one or more circular paths traced by
- 15 the fiducial marker rotation to define the tool axis orientation relative to the fiducial marker array.

12. The method of claim 11 further comprising:

- collecting a set of points on a tool tip surface of said tool with a digitizer;
- 20 best-fitting a plane to the collected set of points with a processor; and
- defining the position of a tool center point at said tool tip surface relative to the fiducial marker array from 1) the intersection of the normal vector at the center point of rotation and 2) the best-fit plane.

25 13. The method of any one of claims 11 or 12 further comprising:

actuating a robot with said calibration device to a previously calibrated tool axis at a given robot position and orientation (pose);

rotating said calibration device about the tool axis;

recording the position of the fiducial marker during rotation with the tracking module;

5 fitting a circular model to the recorded positions with a processor;

calculating at least one of the circles diameter, center, or normal vector; and

comparing at least one of the circles diameter, center, or normal vector with the values stored from the previously calibrated tool axis to determine the robot calibration validity.

10 14. The method of claim 11 wherein one end of said calibration device further comprises a sleeve with an abutment surface whereby the fiducial marker on said sleeve is at a known distance from the abutment surface.

15 15. The method of claim 14 further comprising:

calculating the position of a tool center point at the working end of the tool based on 1) the intersection of the calculated normal vector to the circular paths traced by the fiducial marker at the center point of rotation and 2) a plane defined at the abutment surface.

16. A system for defining a robot link orientation comprising:

20 a distal link;

a proximal link attached to the distal link;

a tracking module; and

a set of fiducial markers placed on the distal link such that three fiducial markers from said set of fiducial markers are visible to the tracking module such that a processor can define a
25 first coordinate system on the distal link.

17. The system of claim 16 wherein the tracking module records the position of the three fiducial markers during rotation and said processor fits a circular model to the recorded positions and calculates at least one of a circle center or vector normal to the circle to define at least one of a distal link position or distal link orientation.

5

18. The system of claim 16 wherein the proximal link further comprises a second set of fiducial markers such that three secondary fiducial markers from said second set are visible to the tracking module and said processor defines a second coordinate system on the proximal link.

19. The system of claim 18 wherein said processor in communication with said tracking module calculates an angle between said proximal link and said distal link by computing a relative rotation between the first coordinate system and the second coordinate system about the axis of rotation.

20. A system for tracking a tool to aid in a medical procedure comprising:

a tool;

a tracking module; and

a rotating body coincident about an axis of said tool, said rotating body comprising at least one fiducial marker such that said tracking module records a position of the at least one fiducial marker as the at least one fiducial marker rotates about the tool axis.

21. The system of claim 20 further comprising a processor programmed to fit a circle to the recorded positions of the fiducial marker.

22. The system of claim 20 wherein the processor calculates at least one of a vector normal to the fitted circle or a center point of the fitted circle.

23. The system of any one of claims 20 to 22 wherein the tracking module records the position of the three fiducial markers during rotation and said processor fits a circular model to the recorded positions and calculates at least one of a circle center or vector normal to the
5 circle to define at least one of a distal link position or distal link orientation

24. A fiducial marker array for tracking an object comprising:
a rigid body; and
at least one fiducial marker in communication with a tracking module that rotates
10 creating a circular path on a region of the rigid body such that the at least one fiducial marker is
offset a distance from the center of rotation of the fiducial marker.

25. The fiducial marker array of claim 24 further comprising a fiducial marker fixed
to the rigid body.

15




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5B




FIG. 5A




FIG. 6




FIG. 7A




FIG. 7B

A. CLASSIFICATION OF SUBJECT MATTER**A61B 34/20(2016.01)i, A61B 34/30(2016.01)i, A61B 90/00(2016.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61B 34/20; A61B 1/00; G01B 18/00; G01C 17/38; A61B 19/00; G01C 21/20; G01C 25/00; A61B 5/06; A61B 34/30; A61B 90/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models

Japanese utility models and applications for utility models

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS(KIPO internal) & Keywords:calibration, body, tool, tool axis, rotation, fiducial marker, fiducial marker array, tracking module, calculating, normal vector, center point**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2014-0275955 A1 (GLOBUS MEDICAL, INC.) 18 September 2014 See paragraphs [0042]-[0047], [0067]-[0070]; and figures 1A-2, 10.	16, 18, 19
A		1-15, 17, 20-25
A	US 7043961 B2 (PANDEY et al.) 16 May 2006 See column 3, line 56 - column 4, line 27; column 4, line 49 - column 6, line 8; and figures 1-5.	1-25
A	US 5987960 A (MESSNER et al.) 23 November 1999 See column 4, lines 1-45; column 5, lines 17-33, 48-58; column 6, line 62 - column 9, line 13; and figures 1A-7.	1-25
A	US 5921992 A (COSTALES et al.) 13 July 1999 See column 2, line 61 - column 4, line 6; column 5, lines 6-53; and figures 1, 4.	1-25
A	US 2014-0214358 A1 (JI, YING) 31 July 2014 See paragraphs [0104]-[0110]; and figure 3.	1-25

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 July 2016 (21.07.2016)

Date of mailing of the international search report

25 July 2016 (25.07.2016)

Name and mailing address of the ISA/KR

International Application Division
Korean Intellectual Property Office
189 Cheongsa-ro, Seo-gu, Daejeon, 35208, Republic of Korea

Facsimile No. +82-42-481-8578

Authorized officer

CHO, KI YUN

Telephone No. +82-42-481-5655



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2016/021205

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2014-0275955 A1	18/09/2014	WO 2015-061638 A1	30/04/2015
US 7043961 B2	16/05/2006	CN 100491914 C CN 1511249 A EP 1364183 A1 EP 1364183 A4 EP 1364183 B1 JP 2004-529679 A JP 4153305 B2 US 2003-0209096 A1 WO 02-061371 A1	27/05/2009 07/07/2004 26/11/2003 18/06/2008 06/11/2013 30/09/2004 24/09/2008 13/11/2003 08/08/2002
US 5987960 A	23/11/1999	EP 0904735 A2 EP 0904735 A3 JP 11-188045 A JP 4201891 B2	31/03/1999 17/11/1999 13/07/1999 24/12/2008
US 5921992 A	13/07/1999	None	
US 2014-0214358 A1	31/07/2014	CA 2851747 A1 CN 103826542 A EP 2767240 A1 EP 2767240 A4 JP 2015-502186 A US 9157762 B2 WO 2013-053103 A1	18/04/2013 28/05/2014 20/08/2014 13/01/2016 22/01/2015 13/10/2015 18/04/2013