



(22) Date de dépôt/Filing Date: 2000/02/14

(41) Mise à la disp. pub./Open to Public Insp.: 2000/08/17

(45) Date de délivrance/Issue Date: 2004/10/26

(30) Priorités/Priorities: 1999/02/17 (11-39080) JP;
1999/09/01 (11-247457) JP

(51) Cl.Int.⁷/Int.Cl.⁷ H04L 29/00, G07B 5/00, H04L 9/28

(72) Inventeurs/Inventors:

TERADA, MASAYUKI, JP;
FUJIMURA, KO, JP;
KUNO, HIROSHI, JP;
HANADATE, MASAYUKI, JP


(73) Propriétaire/Owner:

NIPPON TELEGRAPH AND TELEPHONE
CORPORATION, JP

(74) Agent: SMART & BIGGAR


(54) Titre : METHODE, SYSTEME ET APPAREILLAGE DE CIRCULATION DE DONNEES ORIGINALES ET SUPPORT
LISIBLE PAR UN ORDINATEUR

(54) Title: ORIGINAL DATA CIRCULATION METHOD, SYSTEM, APPARATUS, AND COMPUTER READABLE MEDIUM



(57) Abrégé/Abstract:

An original data circulation system for storing or circulating original data which is digital information is provided. The original data circulation system includes an issuer apparatus, a user apparatus and a collector apparatus. The issuer apparatus generates



(57) Abrégé(suite)/Abstract(continued):

originality information including first information corresponding to the issuer apparatus and second information corresponding to data and sends the originality information. The user apparatus verifies the validity of the source apparatus of the originality information and stores the originality information when the validity is verified. The collector apparatus verifies the validity of the source apparatus of the originality information and processes data corresponding to the second information when the validity is verified.

ABSTRACT OF THE DISCLOSURE

An original data circulation system for storing or circulating original data which is digital information is provided. The original data
5 circulation system includes an issuer apparatus, a user apparatus and a collector apparatus. The issuer apparatus generates originality information including first information corresponding to the issuer apparatus and second information
10 corresponding to data and sends the originality information. The user apparatus verifies the validity of the source apparatus of the originality information and stores the originality information when the validity is verified. The collector
15 apparatus verifies the validity of the source apparatus of the originality information and processes data corresponding to the second information when the validity is verified.

TITLE OF THE INVENTION

ORIGINAL DATA CIRCULATION METHOD, SYSTEM,
APPARATUS, AND COMPUTER READABLE MEDIUM

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention generally relates to
an original data circulation method, system
apparatus, and computer readable medium. More
10 particularly, the present invention relates to
providing technologies for storing and distributing
data such as a digital ticket which represents a
digital right, digital contents and the like, in
which the number of valid reproductions of such data
15 needs to be smaller than a defined number.

2. Description of the Related Art

Reproductions of data or a digital ticket
which represents a digital right exceeding the
number which the data distributor intends should be
20 prevented. That is, distributed data that is
reproduced by a user illegally should be prevented.

Conventionally, such multiple use is
prevented by technologies described in the following.

A first method is that transfer histories
25 of the original data are attached to the data and
they are used to check whether the data is already
used or not at the time of request for exercising
the right. If the right is already used up, the
service provider (or collector) of the data refuses
30 accepting the right represented by the data.

A second method is to store the data in a
tamper-proof device such that the data cannot be
accessed except via the tamper-proof device. When
the data is used up, the data is deleted from the
35 tamper-proof device.

According to the above-mentioned first
method, a special device such as the tamper-proof

78230-3

-2-

device is not necessary. However, a problem comes up when the data is circulated. More specifically, validity of the data can be checked only when the right is exercised according to the first method.

5 Therefore, there is a problem that the validity of the data can not be judged while the data is circulating.

According to the above-mentioned second method, uniqueness of the data can be protected by
10 using the tamper-proof device. In addition, methods which are described in published PCT application W095/30211 published on 95-11-09 can be used together with the above-mentioned second method, in which a plurality of
15 tamper-proof devices are connected via secure communication routes which are protected by cryptography. The data is exchanged via the communication routes such that the data can be circulated while preventing reproduction of the data.
20 However, the technology has the following two problems since the data needs to be stored in the tamper-proof device.

First, it becomes impossible to view the description of the data. Therefore, there is a
25 constraint that all checks such as a check of the validity period of the description should be left to the tamper-proof device.

In addition, since the tamper-proof device should not only have a storing part of the data but
30 also carry out all processing necessary for handling the data, a large storage capacity and a high processing throughput are required for the tamper-proof device. Especially, an IC card which is generally used for the tamper-proof device does not
35 have enough storage capacity or processing throughput.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an original data circulation method, a system, an apparatus and a computer readable medium in which it is ensured that the number of valid reproductions of data is maintained below a specified number. In addition, the tamper-proof device does not necessarily perform all verifications other than the verification on reproducing such that processing load such as processing throughput or memory capacity can be decreased.

The above object of the present invention is achieved by an original data circulation system for storing or circulating original data which is digital information, the system comprising:

an apparatus including: means for generating first information corresponding to an issuer apparatus for issuing data; means for sending the first information; and means for sending second information corresponding to the data; and

an apparatus including: means for verifying validity of the first information which is received; means for verifying that an issuing apparatus corresponding to valid first information is valid; and means for determining that data corresponding to the second information is valid when the issuer apparatus is valid.

The first information may be, for example, after-mentioned H(PkI) or the like. The second information may be a hash value of data or a hash value of data with a signature. The issuer apparatus is determined to be valid, for example, when the source apparatus of the first information and an apparatus corresponding to the first information are the same. Since a tamper-proof apparatus and the like performs an authentication

process using the first information, the above-mentioned problem is solved and the processing load can be decreased.

5 The above object of the present invention is also achieved by a data storing method of storing digital information which has a value, comprising the steps of:

generating third information which is digital information with a signature signed by an
10 issuer apparatus for the digital information;
generating, by the issuer apparatus, fourth information, the fourth information being a manifest corresponding to the digital information;
verifying, by an user apparatus, identity
15 of the issuer apparatus by using the third information and the fourth information; and
preventing reproduction of the digital information.

The fourth information may be, for example,
20 a hash value of the data with the signature. The hash value is the manifest which corresponds to originality information. The originality information is information which represents genuineness of the right of data. In other words,
25 the originality information represents the authenticity or originality of data.

According to the above-mentioned invention, data and the signature of the data are stored and a manifest which is information in one-to-one
30 correspondence with the data and the signature. In addition, the signer who generates the signature is identified and it is verified that the signer is the same as the party which intends to store the manifest. Thus, the number of manifests which the
35 signer intends are stored in the data storing system.

The data storing method may further comprise the steps of:

verifying identity of the issuer apparatus
by storing the fourth information in a tamper-proof
device; and

5 preventing reproduction of the digital
information.

Accordingly, the data can be stored in an
apparatus other than the data storing system since
the tamper-proof device is used.

The above object of the present invention
10 is also achieved by a data storing system for
storing digital information which has a value,
comprising:

an issuer apparatus for generating third
information which is digital information with a
15 signature and generating the fourth information
which is a manifest corresponding to the digital
information; and

a user apparatus for verifying identity of
the issuer apparatus by using the third information
20 and the fourth information; and

preventing reproduction of the digital
information.

The above object of the present invention
is also achieved by a user apparatus for using
25 digital information in a data storing system for
storing digital information which has a value,
comprising:

first storing means for storing and
extracting digital information with a signature;

30 second storing means for storing and
extracting a manifest corresponding to digital
information;

first authentication means for verifying
that the manifest is valid; and

35 first control means for storing the
manifest in the second storing means only when the
first authentication means verifies that the

manifest is valid.

Accordingly, by determining that the data is valid only when the manifest corresponding to the data is stored in the data storing system, having
5 valid data exceeding the number of manifests that exist can be avoided.

The above object of the present invention is also achieved by an issuer apparatus for issuing digital information in a data storing system for
10 storing digital information which has a value, the issuer apparatus comprising:

accredited information generation means for generating accredited information which includes a set of information representing an accredited
15 object trusted by the signer of the digital information;

signature means for providing a signature to the digital information and to the accredited information;

20 manifest generation means for generating the manifest;

means for sending the digital information and the accredited information to a user apparatus;

means for receiving session information
25 which includes a verification key of the user apparatus and a serial number; and

means for sending information including the manifest and the session information by using a verification key and a signature function of the
30 issuer apparatus.

Accordingly, there is an accredited object trusted by the signer of the data and a signature signed by the issuer apparatus. It is verified that the signer of the manifest is included in the
35 accredited objects or in the signers trusted by the accredited object. In addition, it is verified that the signer of the accredited information and the

-7-

signer of the data are the same. Accordingly, the manifest can be transmitted only via a route trusted by the signer of the data. At the time, the tamper-proof capability is assured by using the tamper-proof apparatus.

The above object of the present invention is also achieved by a collector apparatus for exercising a right of digital information in a data storing system for storing digital information which has a value, the collector apparatus comprising:

means for receiving digital information with a signature of the issuer and accredited information with the signature from a user apparatus;

means for generating session information which has uniqueness in the data storing system and sending the session information to the user apparatus;

means for receiving information including the manifest and the session information from the user apparatus; and

means for verifying that the session information, the manifest and the accredited information are valid.

Accordingly, by generating and storing the session information, it becomes possible to avoid the manifest being stored in a plurality of storing parts without using an encrypted route. In addition, it becomes possible to send a plurality of manifests to a storing part in parallel.

The above-mentioned inventions will be described in the first embodiment in detail. In addition, the following inventions will be described in the second embodiment in detail.

The above object of the present invention is also achieved by an original data circulation method in an original data circulation system for

-8-

storing or circulating original data which is digital information, the method comprising:

5 a sending step of sending, by a first apparatus, originality information, the originality information including fifth information which corresponds to an apparatus and sixth information which is data or information corresponding to the data; and

10 an identifying step of identifying, by a second apparatus, the source apparatus of the originality information;

a first authentication step of determining that the originally information is valid when the source apparatus is authenticated; and

15 a second authentication step of determining that the originality information is valid only when the source apparatus and an apparatus corresponding to the fifth information of the originality information are the same.

20 The above object of the present invention is also achieved by an original data circulation system for storing or circulating original data which is digital information, the system comprising:

25 a first apparatus which includes sending means for sending originality information, the originality information including fifth information which corresponds to an apparatus and sixth information which is data or information corresponding to the data; and

30 a second apparatus which includes: identifying means for identifying a source apparatus of the originality information;

35 a first authentication means for determining that the originally information is valid when the source apparatus is authenticated; and

a second authentication means for determining the originality information is valid

only when the source apparatus and an apparatus corresponding to the fifth information of the originality information are the same.

The above-mentioned originality
5 information will be called token in the second embodiment. The fifth information may be, for example, a hash value of a verification key (public key) of an apparatus. The sixth information may be, for example, a hash value of the data. According to
10 the above-mentioned invention, since the second authentication means determines that the originality information is valid only when the source apparatus and an apparatus corresponding to the first information are the same, the conventional problem
15 can be solved. In addition, since it is not necessary to circulate the signature, the processing load can be further decreased.

The above object of the present invention is also achieved by an issuer apparatus in an
20 original data circulation system for storing or circulating original data which is digital information, the issuer apparatus comprising:

originality information generation means
for generating originality information which
25 includes fifth information corresponding to the issuer apparatus and sixth information corresponding to data or information corresponding to the data;
and

originality information sending means for
30 sending the originality information.

The above object of the present invention is also achieved by a user apparatus in an original data circulation system for storing or circulating original data which is digital information, the user
35 apparatus comprising:

originality information sending means for sending originality information which includes fifth

-10-

information corresponding an apparatus and sixth
information corresponding to data or information
corresponding to the data;

identifying means for identifying a source
5 apparatus of the originality information which is
sent from an apparatus;

authentication means for determining that
the originality information is valid when the source
apparatus is authenticated or when the apparatus
10 corresponding to the fifth information and the
source apparatus are the same; and

storing means for storing the originality
information when the authentication means determines
that the originality information is valid.

15 The above object of the present invention
is also achieved by a collector apparatus in an
original data circulation system for storing or
circulating original data which is digital
information, the collector apparatus comprising:

20 identifying means for identifying a source
apparatus of originality information;

authentication means for authenticating
the source apparatus; and

data processing means for performing a
25 process corresponding to the data or data
corresponding to the sixth information when the
authentication means determines that the originality
information which is sent to the collector apparatus
is valid.

30 In the present invention, since accredited
information which represents a trusted third party
may be used, the originality information can be
circulated between trusted parties.

The above object of the present invention
35 is also achieved by an original data circulation
system for storing or circulating original data
which is digital information, the original data

-11-

circulation system comprising:

an issuer apparatus including:

first originality information generation

means for generating originality information which

5 includes fifth information corresponding to the
issuer apparatus and sixth information corresponding
to data or information corresponding to the data;
and

first originality information sending

10 means for sending the originality information;

a user apparatus including:

first originality information sending

means for sending originality information which

includes fifth information corresponding to an
15 apparatus and sixth information corresponding to
data or information corresponding to the data;

first identifying means for identifying a
source apparatus of the originality information
which is sent from an apparatus;

20 first authentication means for determining
that the originality information is valid when the
source apparatus is authenticated or when the
apparatus corresponding to the fifth information and
the source apparatus is the same; and

25 storing means for storing the originality
information when the first authentication means
determines that the originality information is
valid; and

a collector apparatus including:

30 sixth identifying means for identifying a
source apparatus of originality information;

sixth authentication means for
authenticating the source apparatus; and

35 data processing means for performing a
process corresponding to the data or data
corresponding to the sixth information when the
second authentication means determines that the

78230-3

-12-

originality information which is sent to the collector apparatus is valid.

Accordingly, it becomes possible to issue a ticket, transfer the ticket, consume and present the ticket
5 in the above apparatuses.

Another broad aspect provides an original data circulation method in an original data circulation system for storing or circulating original data which is digital information, the method comprising: a sending step of
10 sending, by a first apparatus, originality information to a second apparatus, the originality information including a fingerprint corresponding to a source apparatus of the original data and second information corresponding to the original data, and an authentication step of identifying an
15 authenticating, by the second apparatus, the source apparatus, verifying whether the source apparatus is the same as an apparatus corresponding to the fingerprint, and determining that the originality information is valid if the source apparatus is the same as an apparatus corresponding
20 to the fingerprint.

Another broad aspect provides an original data circulation system for storing or circulating original data which is digital information, the system comprising: a first apparatus which includes sending means for sending
25 originality information, the originality information including a fingerprint corresponding to a source apparatus of the original data and second information corresponding to the original data; and a second apparatus which includes authentication means for identifying and authenticating the
30 source apparatus of the original data, and means for verifying whether the source apparatus is the same as an

78230-3

-12a-

apparatus corresponding to the fingerprint, and determining that the originality information is valid if the source apparatus is the same as an apparatus corresponding to the fingerprint.

5 Another broad aspect provides an original data circulation system for storing or circulating original data which is digital information, the original data circulation system comprising: an issuer apparatus which includes means for generating originality information and sending the
10 originality information, the originality information including a fingerprint corresponding to the issuer apparatus and second information corresponding to the original data; a user apparatus which includes means for verifying validity of a source apparatus of the originality
15 information and means for storing the originality information when the validity is verified; and a collector apparatus which includes means for verifying validity of a source apparatus of the originality information and data processing means for performing a process on the original
20 data if the validity is verified.

 Another broad aspect provides an original data circulation system for storing or circulating original data which is digital information, the original data circulation system comprising: an issuer apparatus including: first
25 originality information generation means for generating originality information which includes a fingerprint corresponding to the issuer apparatus and second information corresponding to the original data; and first originality information sending means for sending the originality
30 information; a user apparatus including: first originality information sending means for sending the originality information; first identifying means for identifying a source apparatus of the originality information; fist

78230-3

-12b-

authentication means for determining that the originality
information is valid if the source apparatus is
authenticated and an apparatus corresponding to the
fingerprint and the source apparatus are the same; and
5 storing means for storing the originality information when
the first authentication means determines that the
originality information is valid; and a collector apparatus
including: second identifying means for identifying a
source apparatus of originality information; second
10 authentication means for authenticating the source
apparatus; and data processing means for performing a
process corresponding to the original data if the second
authentication means determines that the originality
information which is sent to the collector apparatus is
15 valid.

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features and advantages of the
present invention will become more apparent from the
following detailed description when read in conjunction with
20 the accompanying drawings, in which:

Fig. 1 is a diagram for describing a principle
according to a first embodiment of the present invention;

Fig. 2 is a block diagram of a data storing system
according to the first embodiment of the present invention;

25 Fig. 3 is a block diagram of an issuer apparatus
of the data storing system according to the first embodiment
of the present invention;

Fig. 4 is a block diagram of a user apparatus of
the data storing system according to the first embodiment of
30 the present invention;

78230-3

-12c-

Fig. 5 is a block diagram of a collector apparatus of the data storing system according to the first embodiment of the present invention;

Fig. 6 is a block diagram of a connection
5 apparatus of the data storing system according to the first embodiment of the present invention;

Fig. 7 is a sequence chart showing a ticket issuing process in the data storing system according to the first embodiment of the present invention;

10 Fig. 8 is a sequence chart showing a ticket transferring process in the data storing system according to the first embodiment of the present invention;

Fig.9 is a sequence chart showing a ticket transferring process in the data storing system according to the first embodiment of the present invention;

5 Fig.10 is a sequence chart showing a ticket consuming process in the data storing system according to the first embodiment of the present invention;

10 Fig.11 is a diagram for describing a principle according to a second embodiment of the present invention;

Figs.12A and 12B are block diagrams of a data storing system in an original data circulation system according to the second embodiment of the present invention;

15 Fig.13 is a block diagram of an issuer apparatus of the original data circulation system according to the second embodiment of the present invention;

20 Fig.14 is a block diagram of a user apparatus of the original data circulation system according to the second embodiment of the present invention;

25 Fig.15 is a block diagram of a collector apparatus of the original data circulation system according to the second embodiment of the present invention;

30 Fig.16 is a block diagram of a connection apparatus of the original data circulation system according to the second embodiment of the present invention;

35 Fig.17 is a sequence chart showing a ticket issuing process in the original data circulation system according to the second embodiment of the present invention;

Fig.18 is a sequence chart showing a ticket transferring process in the original data

-14-

circulation system according to the second embodiment of the present invention;

Fig.19 is a sequence chart showing a ticket transferring process in the original data circulation system according to the second
5 embodiment of the present invention;

Fig.20 is a sequence chart showing a ticket consuming process in the original data circulation system according to the second
10 embodiment of the present invention;

Fig.21 is a block diagram showing a configuration of a computer.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

15 (First Embodiment)

First, a data storing system as an original data circulation system of the present invention will be described.

Fig.1 is a diagram for describing a
20 principle of the present invention. In the data storing system of the present invention, an issuer apparatus of digital information generates first information by adding a digital signature to the digital information in step 1. The issuer apparatus
25 generates second information which is a manifest corresponding to the digital information and adds the second information to the first information in step 2. A user apparatus checks the identity of the issuer apparatus by using the first information and
30 the second information such that the unauthorized reproduction of the digital information can be prevented in step 3.

In the first embodiment, a digital ticket that is a digital representation of a right to claim
35 services or goods, are used as an example of digital information to be circulated.

Fig.2 shows a block diagram of the data

-15-

storing system. As shown in the figure, an issuer issues a digital ticket. Then, the user transfers the digital ticket to another user. When a user who receives the digital ticket uses the digital ticket,
5 a verifier verifies validity of the digital ticket.

In the figure, the issuer of the digital ticket has an issuer apparatus 1 and the user who receives the digital ticket has a user apparatus 2. When issuing a digital ticket, a communication
10 channel between the issuer apparatus 1 and the user apparatus 2 is established via a connection apparatus 4. The communication channel may exist only during the period from the issuing start time to the issuing end time.

15 When transferring the digital ticket, a communication channel is established between the user apparatuses 2 via the communication apparatus 4 in the same way as when issuing the digital ticket. Then, the digital ticket is transferred between the
20 user apparatuses 2. A collector of the digital tickets has a collector apparatus 3. When collecting the digital tickets, a communication channel is established between the user apparatus 2 and the collector apparatus 3 via the communication
25 apparatus 4 in the same way as when issuing the digital ticket. Then, the digital ticket is sent to the collector apparatus 3.

As mentioned above, the data storing system of the present invention includes one or a
30 plurality of issuer apparatuses, one or a plurality of user apparatuses 2 and one or a plurality of collector apparatuses 3 which apparatuses are connected by connection apparatuses 4 which provide temporal communication channels.

35 In the following, each of the apparatuses which are included in the data storing system will be described. Before the description, meanings of

formulas which will be used for the description will be described.

$x \parallel y$ means concatenation of x and y . H means a unidirectional hash function. The hash function has the property that determining x from y which satisfies $y=H(x)$ is difficult. MD5 of RSA is known as a hash function.

S_{pk} is a signature function which generates a digital signature which can be verified by a verification function V_{pk} . The verification function V_{pk} has the property of $V_{pk}(x \parallel S_{pk}(x))=1$, $V_{pk}(x \parallel \text{other})=0$ ($\text{other} \neq S_{pk}(x)$). That is, the verification function V_{pk} can verify that information x has a signature signed by the signature function S_{pk} . In addition, the verification function V_{pk} can verify that the digital signature $S_{pk}(x)$ is a correct signature signed by S_{pk} for x .

Pk is a verification key and has the property that V_{pk} can be formed by providing the verification key Pk to a verifier V . Especially, a verification key $Pk2 \parallel S_{pk1}(Pk2)$ is called as a key certificate of $Pk2$ by $Pk1$.

ESIGN of Nippon Telegraph and Telephone Corporation is known as a digital signature method which realizes the above-mentioned S_{pk} and V_{pk} .

Fig.3 shows an issuer apparatus according to an embodiment of the present invention.

The issuer apparatus 1 shown in the figure includes a control part 11, a signature part 12, a data generation part 13, a manifest generation part 14 and an accredited information generation part 15.

The control part 11 has a verification key PkI and controls the issuer apparatus 1 to circulate a digital ticket securely. PkI is a verification key corresponding to a signature function S_{pkI} provided in the signature part 12. A detailed description on the control part 11 will be given

-17-

later.

The signature part 12 includes the signature function S_{PKI} . Each issuer apparatus has a different signature function S_{PKI} . The signature
 5 function S_{PKI} is concealed by the signature part 12.

The data generation part 13 generates data m on the basis of information generated in the issuer apparatus 1 or information given from the outside. According to the data storing system of
 10 the present invention, there is no restriction for the contents of the data m . Therefore, digital information representing rights of general tickets such as a concert ticket, program data, music data and image data can be used as the data m .

15 In addition, m can be formed as relation to other data or as data including relation to other data by obtaining $H(m_0)$ in which m_0 is provided from the outside. Accordingly, data amount sent to an after-mentioned tamper-proof device 28 can be
 20 decreased when issuing a digital ticket.

The manifest generation part 14 has the unidirectional hash function H and generates a manifest $c_{(m, PKI)} = H(m \parallel S_{PKI}(m))$ of data with a signature $m \parallel S_{PKI}(m)$.

25 The accredited information generation part 15 generates accredited information $t = (t_I, t_c)$. In the accredited information $t = (t_I, t_c)$, $t_I = PKI$, $t_c = \{H(PkC_1), H(PkC_2), \dots, H(PkC_n)\}$. Here, PKI is a verification key held by the control part 11, and
 30 PkC_i is a verification key for verifying a signature signed by an after-mentioned third party which is "trusted" by the issuer.

Fig.4 is a user apparatus 2 according to an embodiment of the present invention. The user
 35 apparatus 2 includes a control part 21, a storing part 22 and the tamper-proof device 28 which has a control part 23, an authentication part 24, a

-18-

signature part 25, a number generation part 26 and a storing part 27. The tamper-proof device 28 protects functions and contents of the parts from tampering. Even the user of the tamper-proof device 5 28 can not tamper with the tamper-proof device 28. An IC card or a server which is stringently managed by a third party via a network can be used as the tamper-proof device 28.

The control part 21 and the control part 10 23 in the tamper-proof device 28 control the user apparatus 2 for circulating a digital ticket securely. The detailed description of the control part 21 will be described later.

The storing part 22 stores a set M_u of 15 data with a signature which is held by the user and a set T_u of accredited information with a signature signed by an issuer. The sets can be updated by the control part 21.

The control part 23 has verification keys 20 PkU and PkC , and a key certificate $PkU \parallel S_{PkC}(PkU)$. Here, the verification key PkU corresponds to S_{PkU} in the signature part 25. S_{PkC} is a signature function concealed by a third party which assures security of the tamper-proof device 28. The third party may be 25 an IC card manufacturer, a tamper-proof server administrator or the like. That is, tamper-proof capability of the tamper-proof device 28 which includes the signature function S_{PkU} is assured by the third party which has the signature function S_{PkC} . 30 A detailed description of the control part 23 will be given later. PkC is a verification key of S_{PkC} .

A storing part 22 of another user apparatus and/or a storing part 34 of an after-mentioned collector apparatus 3 can be used with the 35 storing part 22 or instead of the storing part 22. In such a case, since data m and after-mentioned accredited information (t_1, t_2, t_3) can be shared by

-19-

the user apparatuses and the collector apparatuses, the data m and the accredited information (t_1 , t_2 , t_3) are not necessarily sent between the apparatuses.

The authentication part 24 includes a
 5 verifier V . The signature part 25 includes the signature function S_{PKU} . Each of the user apparatuses have different S_{PKU} . S_{PKU} is concealed by the signature part 25.

The number generation part 26 stores a
 10 next number r_v . When the number generation part 26 is required to issue a number, the number generation part 26 issues a current number r_v and increments r_v .

The storing part 27 stores a set of manifests $C_v=\{c_1, c_2, \dots, c_n\}$ and a set of numbers
 15 $R_v=\{r_1, r_2, \dots, r_m\}$. These sets can be updated by the control part 21.

Fig.5 is a block diagram of the collector apparatus 3 according to an embodiment of the present invention. The collector apparatus 3
 20 includes a control part 31, an authentication part 32, a number generation part 33 and a storing part 34.

The control part 31 has a verification key PkV and controls the collector apparatus 3 for
 25 circulating the digital ticket securely. The detailed description of the operation of the control part 31 will be given later.

The authentication part 32 includes a verifier V .

30 The number generation part 33 stores a next number r_v . When the number generation part 33 is required to issue a number, the number generation part 33 issues a current number r_v and increments r_v .

The storing part 34 stores a set of
 35 numbers $R_v=\{r_1, r_2, \dots, r_m\}$. The set can be updated by the control part 31.

Fig.6 is a block diagram of the connection

-20-

apparatus 4 according to an embodiment of the present invention.

The connection apparatus 4 includes a communication part 41. The communication part 41 provides a temporal or permanent communication channel between the issuer apparatus 1, the user apparatus 2 and the collector apparatus 3, or between the user apparatuses. A terminal with an IC card slot at a kiosk, a plurality of PCs which are connected via network or the like can be used as the connection apparatus 4.

A method for circulating the digital ticket securely by using the above-mentioned apparatuses will be described in the following.

Basic concepts of the circulation method are shown below.

- The digital ticket is represented by data with a signature by an issuer $m \parallel S_{PKI}(m)$. Contents of a right which is given to an owner of the digital ticket by the issuer are described in m . Otherwise, m includes a relation to data in which contents of the right are described.

- Tampering with the digital ticket can be prevented by using the signature function S_{PKI} of the issuer of the digital ticket.

- Reproduction of the digital ticket is not prohibited.

- A manifest $c_{(m, PKI)}$ can be generated from the digital ticket. The manifest is substantially in a one-to-one correspondence with the digital ticket.

- The manifest becomes valid by being stored in the storing part 27 of the tamper-proof device 28 trusted by the issuer.

- The tamper-proof device trusted by the issuer is a device in which the tamper-proof capability is insured by a party trusted by the

-21-

issuer. The party trusted by the issuer is defined by an accredited information t_i .

- A valid manifest can be newly generated only by the issuer of the corresponding digital
5 ticket.

- It is prohibited to generate one or a plurality of valid manifests from a valid manifest. That is, the user is prohibited from generating a manifest of a digital ticket which is signed by
10 others.

In the following, the circulation method of a digital ticket will be described for each of the cases of (1) Issuing a digital ticket, (2) Transferring a digital ticket and (3) Consuming a
15 digital ticket. In the following description, communication between the apparatuses is carried out via the communication part 41 of the connection apparatus 4.

(1) Issuing a digital ticket

20 The process for issuing a digital ticket from the issuer apparatus 1 to the user apparatus 2 via the connection apparatus 4 is shown below. Fig.7 is a sequence chart of the process according to an embodiment of the present invention.

25 Step 101) The control part 11 obtains m and $S_{PKI}(m)$ according to the following procedure to generate a digital ticket $m \parallel S_{PKI}(m)$ which is data with a signature.

(a) The data generation part 13 generates data
30 m .

(b) m is given to the signature part 12 such that the signature part 12 generates $S_{PKI}(m)$.

Step 102) The control part 11 provides the digital ticket $m \parallel S_{PKI}(m)$ to the manifest generation
35 part 14 such that the manifest generation part 14 generates a manifest $c_{(m, PKI)}$.

Step 103) The control part 11 obtains

-22-

accredited information t and a signature function $S_{PKI}(t)$ according to the following procedure and generates accredited information with a signature $t \parallel S_{PKI}(t)$.

5 (a) The accredited information generation part 15 generates the accredited information t . The configuration of t was described before.

 (b) The accredited information t is provided to the signature part 12 such that the signature
10 part 12 generates the signature $S_{PKI}(t)$.

 Step 104) The control part 11 sends the digital ticket $m \parallel S_{PKI}(m)$ and the accredited information with a signature $t \parallel S_{PKI}(t)$ to the control part 21.

15 In step 101, when m which is generated by the data generation part 13 is a relation to other data, for example, $m = H(m_0)$, or when m includes the relation, the related data (m_0) is sent as necessary, which is the same as the cases of after-
20 mentioned transferring and consuming.

 Step 105) The control part 21 of the user apparatus 2 adds the digital ticket $m \parallel S_{PKI}(m)$ in the set M_u , adds the accredited information with the signature $t \parallel S_{PKI}(t)$ in the set T_u and stores them in
25 the storing part 22.

 When data related to m is sent, the relation is verified. If the verification fails, the process is interrupted and the issuer apparatus is notified of it. This is the same as in the case
30 of after-mentioned transferring and consuming.

 Step 106) The control part 21 requests to generate session information (s_1, s_2) to the control part 23.

 The control part 23 generates the session
35 information (s_1, s_2) according to the following procedure and sends it to the control part 21.

 (a) The control part 23 obtains a number r_u

-23-

generated by the number generation part 26.

(b) The number r_u is added to a number set R_u in the storing part 27.

(c) The session information $(s_1, s_2) = (H(PkU), r_u)$ is generated. Here, PkU is a verification key held by the control part 21.

Step 107) The control part 21 sends the session information (s_1, s_2) to the control part 11.

Step 108) The control part 11 obtains a manifest issuing format $e_I = (e_1, e_2, e_3, e_4, e_5)$ by using S_{PkI} in the signature part 12 and the verification key PkI retained by the control part 11. Each element in e_I is shown below.

$e_1 = C_{(m, PkI)}$
 $e_2 = s_1$
 $e_3 = s_2$
 $e_4 = S_{PkI}(C_{(m, PkI)} \parallel s_1 \parallel s_2)$
 $e_5 = PkI$

Step 109) The control part 11 sends the manifest issuing format e_I to the control part 21.

Step 110) The control part 21 sends the digital ticket $m \parallel S_{PkI}(m)$ and the manifest issuing format e_I to the control part 23 and requests to store the manifest in e_I .

Step 111) The control part 23 verifies that following conditions are satisfied by using the authentication part 24. If the verification fails, the process after that is interrupted and the control part 23 notifies the control part 11 of the process interruption via the control part 21.

$e_2 = H(PkU) \quad (1)$
 $e_3 \in R_u \quad (2)$
 $V_{e_5}(m \parallel S_{PkI}(m)) = 1 \quad (3)$
 $V_{e_5}(e_1 \parallel e_2 \parallel e_3 \parallel e_4) = 1 \quad (4)$
 $e_1 = H(m \parallel S_{PkI}(m)) \quad (5)$

The above-mentioned formulas (1) and (2) mean verification of validity of the session

-24-

information. According to the verification, fraud can be prevented. Such fraud may be, for example, storing a manifest issuing format destined to other user apparatus 2 or reproducing a manifest by reusing the manifest issuing format. The formulas (3) and (4) means verification of validity of the signature of the manifest issuing format. According to the verification, the occurrence of a manifest other than one which is included in the manifest issuing format and which has a signature signed by the issuer is stored can be prevented. The formula (5) means verification of correspondence between the manifest and the digital ticket. According to the verification, the occurrence of a manifest which does not correspond to the digital ticket, such as one corresponding to other digital ticket, can be prevented.

Step 112) The control part 23 deletes $e_3 (=r_v)$ from the number set R_v in the storing part 27.

Step 113) The control part 23 adds $e_1 (=c_{(m, PKI)})$ to a manifest set C_v in the storing part 27.

Step 114) The control part 23 sends e_1 to the control part 21 to notify of a normal end.

(2) Transferring a digital ticket

The digital ticket transferring process from the user apparatus 2a to the user apparatus 2b via the connection apparatus 4 will be described in the following.

Fig.8 and Fig.9 are sequence charts showing the digital ticket transferring process according to an embodiment of the present invention.

Step 201) The control part 21a extracts the digital ticket $m \parallel S_{PKI}(m)$ which is an object to be transferred from a set M_{Ua} of data with a signature retained by the storing part 22a.

Step 202) The control part 21a extracts the accredited information $t \parallel S_{PKI}(t)$ with a

-25-

signature by the issuer of $m \parallel S_{PKI}(m)$ from T_{Ua} included in the storing part 22a.

Step 203) The control part 21a sends $m \parallel S_{PKI}(m)$ and $t \parallel S_{PKI}(t)$ to the control part 21b.

5 Step 204) The control part 21b stores $m \parallel S_{PKI}(m)$ in a set M_{Ub} of data with the signature in the storing part 22b and stores $t \parallel S_{PKI}(t)$ in an accredited information set T_{Ub} in the storing part 22b.

10 Step 205) The control part 21b requests the control part 23b to generate session information (s_1, s_2) .

The control part 23b generates the session information (s_1, s_2) according to the following
15 procedure and sends it to the control part 21b.

(a) The control part 23 obtains a number r_{Ub} generated by the number generation part 26b.

(b) The number r_{Ub} is added to a number set R_{Ub} in the storing part 27b.

20 (c) The session information $(s_1, s_2) = (H(PkUb), r_{Ub})$ is generated. Here, $PkUb$ is a verification key held by the control part 21b.

Step 206) The control part 21b sends the session information (s_1, s_2) to the control part 21a.

25 Step 207) The control part 21a sends (s_1, s_2) and a hash value $H(m \parallel S_{PKI}(m))$ of the digital ticket to be transferred to the control part 23a.

Step 208) The control part 23a verifies that following formula is satisfied for a set of
30 manifest C_{Ua} of manifests which is stored in the storing part 27a.

$$H(m \parallel S_{PKI}(m)) \in C_{Ua} \quad (6)$$

When the verification fails, the process after that is interrupted and the control part 21a
35 is notified of the failure.

The above formula (6) means verification that the manifest $c_{(m, PKI)} = H(m \parallel S_{PKI}(m))$ which

-26-

corresponds to the digital ticket to be transferred is stored in the storing part 27a.

Step 209) The control part 23a obtains a manifest sending format $e_c = (e_1, e_2, e_3, e_4, e_5, e_6, e_7)$ by using S_{PkUa} which is included in the signature part 25a and verification keys $PkUa$, $PkCa$, and a key certificate $PkUa \parallel S_{PkCa}(PkUa)$ which are included in the control part 11. Each element of e_c is shown below.

10 $e_1 = C_{(m, PkI)}$
 $e_2 = s_1$
 $e_3 = s_2$
 $e_4 = S_{PkUa}(C_{(m, PkI)} \parallel s_1 \parallel s_2)$
 $e_5 = PkUa$
15 $e_6 = S_{PkCa}(PkUa)$
 $e_7 = PkCa$

Step 210) The control part 23a deletes $C_{(m, PkI)}$ from the set C_{Ua} of manifest.

Step 211) The control part 23a sends e_c to
20 the control part 21a.

Step 212) The control part 21a sends e_c to the control part 21b. The control part 21b verifies e_1 in the sent e_c whether $e_1 = H(m \parallel S_{PkI}(m))$ is satisfied.

Step 213) The control part 21b sends e_c , t
25 $\parallel S_{PkI}(t)$ and $m \parallel S_{PkI}(m)$ to the control part 23b and requests to store the manifest in e_c .

Step 214) The control part 23b verifies that all formulas below are satisfied by using the an authentication part 24b. If the verification
30 fails, the process is interrupted and the control part 21b is notified of the interruption.

$$e_2 = H(PkUb) \quad (7)$$

$$e_3 \in R_{Ub} \quad (8)$$

$$V_{e5}(e_1 \parallel e_2 \parallel e_3 \parallel e_4, e_5) = 1 \quad (9)$$

35 $V_{e7}(e_5 \parallel e_6) = 1 \quad (10)$

$$H(e_7) \in t_c \quad (11)$$

$$V_{tI}(m \parallel S_{PkI}(m)) = 1 \quad (12)$$

-27-

$$V_{tI}(t \parallel S_{PKI}(t)) = 1 \quad (13)$$

The above formulas (7) and (8) mean verification of validity of the session information. Using the verification, fraud such as storing a
 5 manifest sending format on another user apparatus, reproducing a manifest by reusing the manifest sending format or the like is prevented.

The formula (9) means verification for identifying the signer of the manifest sending
 10 format. The formula (10) means verification of the key certificate of the signer. The formula (11) means verification that the signer of the key certificate is trusted by the issuer as an accredited object in the accredited information.
 15 According to the above verification, it is verified that the tamper-proof capability of the source of the manifest sending format is assured by a party trusted by the issuer.

The formulas (12) and (13) mean
 20 verification of validity of the signature signed on the accredited information. According to the verification, it is verified that the accredited information is properly signed by the signer of the digital ticket.

25 Step 215) The control part 23b deletes e_3 ($= r_{ub}$) from the number set R_{ub} in the storing part 27b.

Step 216) The control part 23b adds e_1 ($= c_{(m, PKI)}$) to the manifest set C_{ub} in the storing
 30 part 27b.

Step 217) The control part 23b notifies the control part 21b of the normal completion of the process.

(3) Consuming the digital ticket
 35 The digital ticket consuming process from the user apparatus 2 to the collector apparatus 3 via the connection apparatus 4 will be described in

the following.

Fig.10 is a sequence chart of the ticket consuming process according to an embodiment of the present invention.

5 Step 301) The control part 21 extracts a digital ticket $m \parallel S_{PKI}(m)$ to be consumed from the signed data set M_U which is included in the storing part 22.

10 Step 302) The control part 21 extracts the accredited information $t \parallel S_{PKI}(t)$ signed by the issuer of $m \parallel S_{PKI}(m)$ from the signed accredited information set T_U included in the storing part 22.

 Step 303) The control part 21 sends $m \parallel S_{PKI}(m)$ and $t \parallel S_{PKI}(t)$ to the control part 31.

15 Step 304) The control part 31 generates session information (s_1, s_2) according to the following procedure.

 (a) The control part 23 obtains a number r_v from the number generation part 33.

20 (b) The number r_v is added to a number set R_v in the storing part 34.

 (c) The session information $(s_1, s_2) = (H(PkV), r_v)$ is generated. Here, PkV is a verification key held by the control part 31.

25 Step 305) The control part 31 sends the session information (s_1, s_2) to the control part 21.

 Step 306) The control part 21 sends (s_1, s_2) and a hash value $H(m \parallel S_{PKI}(m))$ of the digital ticket to be consumed to the control part 23.

30 Step 307) The control part 23 verifies that a following formula is satisfied for a set of manifests C_U which is stored in the storing part 27.

$$H(m \parallel S_{PKI}(m)) \in C_U \quad (15)$$

35 When the verification fails, the process after that is interrupted and the control part 21 is notified of the failure.

 The above formula (15) means verification

-29-

that the manifest $c_{(m, PkI)} = H(m \parallel S_{PkI}(m))$ which corresponds to the digital ticket to be consumed is stored in the storing part 27.

Step 308) The control part 23 obtains a
 5 manifest sending format $e_c = (e_1, e_2, e_3, e_4, e_5, e_6, e_7)$
 by using the signature function S_{PkU} which is
 included in the signature part 25 and verification
 keys PkU, PkC , and a key certificate $PkU \parallel S_{PkC}(PkU)$
 which are included in the control part 21. Each
 10 element of e_c is shown below.

$$e_1 = c_{(m, PkI)}$$

$$e_2 = s_1$$

$$e_3 = s_2$$

$$e_4 = S_{PkU}(c_{(m, PkI)} \parallel s_1 \parallel s_2)$$

$$15 \quad e_5 = PkU$$

$$e_6 = S_{PkC}(PkU)$$

$$e_7 = PkC$$

Step 309) The control part 23 deletes $c_{(m, PkI)}$ from the manifest set C_U .

20 Step 310) The control part 23 sends e_c to the control part 21.

Step 311) The control part 21 sends e_c to the control part 31.

25 Step 312) The control part 31 verifies that all formulas below are satisfied by using the authentication part 32. If the verification fails, the process is interrupted and the control part 21 is notified of the interruption.

$$30 \quad e_2 = H(PkV) \quad (16)$$

$$e_3 \in R_v \quad (17)$$

$$V_{e_5}(e_1 \parallel e_2 \parallel e_3 \parallel e_4, e_5) = 1 \quad (18)$$

$$V_{e_7}(e_5 \parallel e_6) = 1 \quad (19)$$

$$H(e_7) \in t_c \quad (20)$$

$$V_{tI}(m \parallel S_{PkI}(m)) = 1 \quad (21)$$

$$35 \quad V_{tI}(t \parallel S_{PkI}(t)) = 1 \quad (22)$$

The above formulas (16) and (17) mean verification of validity of the session information.

-30-

Using the verification, fraud such as storing a manifest sending format on another collector apparatus, reproducing a manifest by reusing the manifest sending format or the like is prevented.

5 The formula (18) means verification for identifying the signer of the manifest sending format. The formula (19) means verification of the key certificate of the signer. The formula (20) means verification that the signer of the key
10 certificate is trusted by the issuer as an accredited object in the accredited information. According to the above verification, it is verified that the tamper-proof capability of the source of the manifest sending format is assured by a party
15 trusted by the issuer.

 The formulas (21) and (22) mean verification of the validity of the signature for the accredited information. According to the verification, it is verified that the accredited
20 information is properly signed by the signer of the digital ticket.

 Step 313) The control part 31 deletes e_3 ($= r_v$) from R_v in the storing part 34.

 Step 314) The control part 31 verifies
25 that all formulas below are satisfied. If the verification fails, the control part 21 is notified of process interruption. If the verification succeeds, a service corresponding to m is provided to the consumer.

30
$$e_1 = H(m \parallel S_{PKI}(m)) \quad (23)$$

 The above formula (23) means verification that a manifest corresponding to the consumed digital ticket has been sent. According to the verification, it is verified that a valid digital
35 ticket has been consumed.

 Each element of the issuer apparatus 1, the user apparatus 2 or the collector apparatus 3

-31-

can be constructed by a program. The program can be stored in a disk unit connected to a computer which may be used as the issuer apparatus, the user apparatus or the collector apparatus. The program
5 can be also stored in a transportable computer readable medium such as a floppy disk, a CD-ROM or the like. The program may be installed from the computer readable medium to a computer such that the present invention is realized by the computer.

10 As mentioned above, according to the first embodiment of the present invention, since only manifests of the number which the signer intends to store are stored in the manifest storing part in the data storing system, the occurrence of a manifest
15 newly stored by a person other than the signer can be prevented. In addition, it can be prevented that valid data exceeding the number of the manifests may exist. Further, it becomes possible that the manifests can be transmitted only via routes which
20 are trusted by the signer.

By using the digital ticket as data in the data storing system of the present invention, the number of valid reproductions of the digital ticket can be maintained at less than a constant number
25 without storing the digital tickets in the tamper-proof device.

In addition, by using a program as data of the present invention and by using the manifest as a license of the program, illegal copying and use of
30 the program can be prevented.

Further, by using music data or image data as data of the present invention, illegal copying and use of the music data or image data can be prevented. Furthermore, by "consuming" ((3) in the
35 embodiment) the data each time when the data is used, the system of the present invention can be used for billing per use in a billing system (for example, a

-32-

pay per view billing system).

(Second Embodiment)

In the following, a second embodiment of the present invention will be described.

5 According to the above mentioned first embodiment, only data which represents originality (manifest) is stored in the tamper-proof apparatus and it is ensured that the number of valid reproductions of data is maintained below a pre-set
10 constant number. Therefore, the tamper-proof device does not necessarily perform verifications other than the verification on reproducing. The verifications include a verification of validity of description. Thus, processing load such as
15 processing speed and memory capacity can be decreased. The above-mentioned invention has remarkable effects in comparison with the conventional technology. However, there are two main problems described below as to the matter of
20 practicality.

 First, when generating the data representing originality or authenticity or genuineness, it is necessary to send data and the signature to the tamper-proof device in order to
25 verify the data and the signature. On the other hand, the transmitting speed of an IC card is about 9600 bps (ISO-7816), which is relatively low. Therefore, when the size of the data is large, the time for generating the data representing
30 originality may be remarkably increased.

 In addition, according to the above-mentioned first embodiment, the data representing originality is generated from data and the signature, and it is necessary to verify the data representing
35 originality by using the data and the signature when consuming the data. Therefore, it becomes necessary to circulate not only the data but also the

-33-

signature. Therefore, the memory capacity necessary for the system and the processing time for circulation may be increased.

5 In the second embodiment, an original data circulation system will be described. According to the system, the processing load for generating data representing originality (which will be called a token) and circulating the data is decreased.

10 Fig.11 is a block diagram for explaining the principle of the second embodiment of the present invention.

The original data circulation for storing and circulating original data which is digital information includes an issuer apparatus 50, a user
15 apparatus 60 and a collector apparatus 70.

The issuer apparatus includes a first originality information generation part 51, and a first originality information sending part 52. The first originality information generation part 51
20 generates originality information. The first originality information sending part 52 sends the originality information. Here, the originality information is information which represents genuineness of the right of issued data. In other
25 words, the originality information represents the authenticity or originality of issued data.

The user apparatus 60 includes a second originality information sending part 61, a first identifying part 62, a first authentication part 63
30 and a storing part 64.

The second originality information sending part 61 receives originality information which is formed by fifth information corresponding to an apparatus and by sixth information which is data or
35 which corresponds to the data. The first identifying part 62 identifies a source apparatus of the originality information when the originality

-34-

information is received from another apparatus.
When the source apparatus is authenticated, the
first authentication part 63 determines that the
originality information is valid only when the
5 source apparatus and information corresponding to
first information of the originality information are
the same. The storing part 64 stores the
originality information when the originality
information is determined as valid by the first
10 authentication part 63.

The collector apparatus 70 includes a
second identifying part 71, a second authentication
part 72 and a data processing part 73.

The second identifying part 71 identifies
15 a source apparatus which sends originality
information. The second authentication part 72
authenticates the source apparatus. The data
processing part 73 carries out processing for the
originality information data or data corresponding
20 to the second information.

Figs.12A and 12B show the configurations
of the data storing system in the original data
circulation system.

In the figure, the issuer of the digital
25 ticket has an issuer apparatus 100 and the user who
receives the digital ticket has a user apparatus 200.
When issuing a digital ticket, a communication
channel between the issuer apparatus 100 and the
user apparatus 200 is established via a connection
30 apparatus 400. The issuer apparatus 100 sends the
digital ticket which is validated in the issuer
apparatus 100 to the user apparatus 200.

The above-mentioned apparatuses can be
configured as shown in Figs.12A and 12B. Fig.12A
35 shows a representative configuration when an IC card
is used for the user apparatus 200 and an IC card
reader is used for the connection apparatus 400.

-35-

Fig.12B shows a representative configuration when a tamper-proof device such as an IC card or a PC which is kept in a safe place is used as the user apparatus and a network is used for the connection
5 apparatus 400. The configurations shown in Figs.12A and 12B can be mixed.

The above-mentioned communication channel may exist only during the period from the issuing start time to the issuing end time, which applies to
10 the cases of "transferring", "consuming" and "presenting".

When transferring the digital ticket, a communication channel is established between the user apparatuses 200 via the communication apparatus
15 400 in the same way as when issuing the digital ticket. Then, the digital ticket is transferred between the user apparatuses 200.

A collector of the digital tickets has a collector apparatus 300. When consuming the digital
20 tickets, a communication channel is established between the user apparatus 200 and the collector apparatus 300 via the communication apparatus 400 in the same way as when issuing the digital ticket. Then, a valid digital ticket is transferred to the
25 collector apparatus 300.

When presenting the digital tickets, a communication channel is established between the user apparatuses 200 or between the user apparatus
30 200 and the collector apparatus 300 via the communication apparatus 400 such that the user apparatus 200 presents a certificate that the user apparatus 200 has a valid digital ticket to another user apparatus or to the collector apparatus 300.

As mentioned above, the data storing
35 system of the present invention includes one or a plurality of issuer apparatuses 100, one or a plurality of user apparatuses 200 and one or a

-36-

plurality of collector apparatuses 300 which apparatuses are connected by connection apparatuses 400 which provide temporal communication channels.

5 In the following, the embodiment of the present invention will be described with reference to figures.

Each apparatus which forms the above-mentioned data storing system will be described by using Figs.13-16. The meaning of formulas used for
10 descriptions below are almost the same as those used in the first embodiment. Especially, a combination ($Pk2, S_{Pk1}(Pk2)$) of a digital signature $S_{Pk1}(Pk2)$ of $Pk2$ by a verification key $Pk2$ and S_{Pk1} is called as a key certificate of $Pk2$ by $Pk1$. $H(Pk)$ is called as a
15 hash value of Pk .

Fig.13 shows an issuer apparatus according to an embodiment of the present invention.

The issuer apparatus 100 shown in the figure includes a control part 110, a signature part
20 120, a data generation part 130, a token generation part 140 and an accredited information generation part 150.

The control part 110 has a verification key PkI and enables the issuer apparatus 100 to
25 circulate a digital ticket securely. PkI is a verification key corresponding to a signature function S_{PkI} provided in the signature part 120. The hash value of it $H(PkI)$ is used as an identifier for identifying the issuer. A detailed description
30 of the control part 110 will be given later.

The signature part 120 includes a signature function S_{PkI} . S_{PkI} is different for each issuer apparatus 100 and concealed by the signature part 120.

35 The data generation part 130 generates data m on the basis of information generated in the issuer apparatus 100 or information given from

-37-

outside. According to the data storing system of the present invention, there is no restriction on the contents of the data m . Therefore, digital information representing rights of general tickets
 5 such as a concert ticket, program data, music data and image data can be used as the data m .

The token generation part 140 has the unidirectional hash function H and generates a token $(c_1, c_2) = (H(m), H(PkI))$ from data m and a
 10 verification key PkI . c_2 is token issuer information which is a hash value that identifies the issuer of the token. Hash of data m is used as c_1 here; however, an identifier for identifying m can also be used as c_1 .

15 The accredited information generation part 150 generates accredited information (t_1, t_2, t_3) . (t_1, t_2, t_3) that can be formed as shown below by using the signature part 120.

$$\begin{aligned} t_1 &= \{H(PkA_1), H(PkA_2), \dots, H(PkA_n)\} \\ 20 \quad t_2 &= S_{PkI}(H(PkA_1) \parallel H(PkA_2) \parallel \dots \parallel H(PkA_n)) \\ t_3 &= PkI \end{aligned}$$

Here, $H(PkA_i)$ is a hash value for identifying an after-mentioned third party who is "trusted" by the issuer.

25 The accredited information can also be formed (t'_1, t'_2, t'_3, t'_4) as shown below.

$$\begin{aligned} t'_1 &= \{H(PkA_1), H(PkA_2), \dots, H(PkA_n)\} \\ t'_2 &= H(m) \\ t'_3 &= S_{PkI}(H(PkA_1) \parallel H(PkA_2) \parallel \dots \parallel H(PkA_n) \parallel H(m)) \\ 30 \quad t'_4 &= PkI \end{aligned}$$

In this case, $H(PkA_i)$ is a hash value for identifying a third party trusted by the issuer for circulating data m .

In addition, a third party may issue
 35 accredited information such that the above-mentioned accredited information can be constructed recursively.

Further, the accredited information may be stored beforehand in a control part of the tamper-proof device of the user apparatus or a control part of the collector apparatus instead of being generated by each issuer. In this case, the signature is not necessary and the accredited information can be constituted as (t''_1, t''_2) or only t''_1 as shown below.

$$t''_1 = \{H(PkA_1), H(PkA_2), \dots, H(PkA_n)\}$$

$$t''_2 = H(m)$$

In such a case, $H(PkA_1)$ is a hash value for identifying a third party trusted by a third party which made the control part for circulating the data m .

In the following, the accredited information is assumed as (t_1, t_2, t_3) . However, any of the above-mentioned accredited information can be used.

Fig.14 is a user apparatus 200 according to an embodiment of the present invention.

The user apparatus 200 includes a control part 210, a storing part 220 and the tamper-proof device 280 which has a control part 230, an authentication part 240, a signature part 250, a number generation part 260 and a storing part 270. The tamper-proof device 280 protects functions and contents of each part from tampering. Even the user of the tamper-proof device 280 can not tamper with the tamper-proof device 280. An IC card or a server which is stringently managed by a third party via a network can be used as the tamper-proof device 280.

The control part 210 includes issuer information $I_u = \{H(PkI_1), H(PkI_2), \dots, H(PkI_n)\}$. The control part 210 and the control part 230 in the tamper-proof device 280 control the user apparatus 200 for circulating a digital ticket securely. I_u is a set representing an issuer trusted by a user

and can be updated by the user at any time. The control part 210 determines that only the token issued by an issuer included in I_u is valid. The detailed description of the control part 210 will be described later.

In addition, I_u can be realized as $I_u(m_i) = \{H(PkI_{i1}), H(PkI_{i2}), \dots, H(PkI_{in})\}$. That is, sets of issuer information are managed from one data to another data.

The storing part 220 stores a set M_u of data which is held by a user and a set T_u of accredited information. The sets can be updated by the control part 210.

The control part 230 has verification keys PkU , PkA , and a key certificate (PkU , $S_{PkA}(PkU)$). The control part 230 controls the user apparatus for circulating the digital ticket securely. Here, the verification key PkU corresponds to S_{PkU} in the signature part 250. Hash data of it $H(PkU)$ is used as an identifier for identifying the user apparatus. S_{PkA} is a signature function concealed by a third party which assures safety of the tamper-proof device 280. The third party may be an IC card manufacturer, a tamper-proof server administrator or the like. That is, tamper-proof capability of the tamper-proof device 280 which includes the signature function S_{PkU} is assured by the third party who has the signature function S_{PkA} . A detailed description of the control part 230 will be given later. PkA is a verification key of S_{PkA} .

The authentication part 240 includes a verifier V .

The signature part 250 includes the signature function S_{PkU} . Each of the user apparatuses have different S_{PkU} . S_{PkU} is concealed by the signature part 250.

The number generation part 260 stores a

next number r_v . When the number generation part 260 is required to issue a number, the number generation part 260 issues a current number r_v and increments r_v . Here, r_v is a positive number.

5 The storing part 270 stores a set of tokens C_v and a set of numbers R_v . These sets can be updated by the control part 230.

Fig.15 is a block diagram of the collector apparatus according to an embodiment of the present invention. The collector apparatus 300 includes a control part 310, an authentication part 320, a number generation part 330 and a storing part 340.

10 The control part 310 has a verification key PkE and issuer information $I_E = \{H(PkI_1), H(PkI_2), \dots, H(PkI_n)\}$, and controls the collector apparatus 300 for circulating the digital ticket securely. I_E is a set representing an issuer trusted by the collector and can be updated by the issuer at any time. The control part 310 determines that only the token issued by an issuer included in I_E is valid and provides a service for consumption of only the digital ticket with the valid token. The detailed description of the operation of the control part 310 will be given later.

25 In addition, in the same way as I_v in the control part 210, I_E can be realized as $I_E(m_i) = \{H(PkI_{i1}), H(PkI_{i2}), \dots, H(PkI_{in})\}$. That is, sets of issuer information are managed from one data to another data.

30 The authentication part 320 includes a verifier V .

 The number generation part 330 stores a next number r_E . When the number generation part 330 is required to issue a number, the number generation part 330 issues a current number r_E and increments r_E . r_E is a positive number.

 The storing part 340 stores a set of

numbers R_e . The set can be updated by the control part 310.

Fig.16 is a block diagram of the connection apparatus 400 according to an embodiment of the present invention.

The connection apparatus 400 includes a communication part 410. The communication part 410 provides a temporal or permanent communication channel between the issuer apparatus 100, the user apparatus 200 and the collector apparatus 300, or between the user apparatuses. A terminal with an IC card slot at a kiosk, a plurality of PCs which are connected via network or the like can be used as the connection apparatus 400.

A method for circulating the digital ticket securely by using the above-mentioned apparatuses will be described in the following.

In the following, the circulation method of a digital ticket will be described for each of the cases of (1) Issuing a digital ticket, (2) Transferring a digital ticket and (3) Consuming a digital ticket. In the following description, communication between the apparatuses is carried out via the communication part 410 in the connection apparatus 400.

(1) Issuing a digital ticket

Fig.17 is a sequence chart of the process according to an embodiment of the present invention. In the figure, the connection apparatus 400 existing between the issuer apparatus 100 and the user apparatus 200 is not shown.

Step 1101) The control part 110 of the issuer apparatus 100 obtains data m from the data generation part 130. The data m is the digital ticket describing right information.

Step 1102) The control part 110 of the issuer apparatus 100 provides the data m and PkI to

-42-

the token generation part 140 such that the token generation part 140 generates a token $(c_1, c_2) = (H(m), H(PkI))$.

Step 1103) The control part 110 obtains
 5 accredited information (t_1, t_2, t_3) from the accredited information generation part 150. The configuration of the accredited information is shown before.

Step 1104) The control part 110 sends m
 10 and (t_1, t_2, t_3) to the control part 210 in the user apparatus 200.

Step 1105) The control part 210 of the user apparatus 200 adds m in M_v of the storing part 220, adds (t_1, t_2, t_3) in T_v of the storing part 220
 15 and stores them in the storing part 220.

Step 1106) The control part 210 requests control part 230 to generate session information (s_1, s_2) .

The control part 230 generates the session
 20 information (s_1, s_2) according to the following procedure and sends it to the control part 210.

(a) The control part 230 obtains a number r_v generated by the number generation part 260 in the tamper-proof device 280.

25 (b) The number r_v is added to a number set R_v in the storing part 270.

(c) The session information $(s_1, s_2) = (H(PkU), r_v)$ is generated. Here, PkU is a verification key held by the control part 210.

30 Step 1107) The control part 210 sends the session information (s_1, s_2) to the control part 110 of the issuer apparatus 100.

Step 1108) The control part 110 of the issuer apparatus 100 obtains a token exchange format
 35 $e = (e_1, e_2, e_3, e_4, e_5, e_6, e_7, e_8)$ by using S_{PkI} in the signature part 120 and the verification key PkI retained by the control part 110. Each element in e

-43-

is shown below. When issuing the digital ticket, since e_7 and e_8 are dummy data, each of e_7 and e_8 can take any value.

5 $e_1 = c_1$
 $e_2 = c_2$
 $e_3 = s_1$
 $e_4 = s_2$
 $e_5 = S_{PKI}(c_1 \parallel c_2 \parallel c_3 \parallel c_4)$
 $e_6 = PKI$
 10 $e_7 = \text{any}$
 $e_8 = \text{any}$

Step 1109) The control part 110 sends e to the control part 210 of the user apparatus 200.

15 Step 1110) The control part 210 sends e to the control part 230 and requests control part 230 to store the token in e .

20 Step 1111) The control part 230 in the tamper-proof device 280 verifies that following formulas are satisfied by using the authentication part 240. If the verification fails, the process after that is interrupted and the control part 230 notifies the control part 110 in the issuer device 100 of the process interruption via the control part 210.

25 $e_3 = H(PkU)$ (1)
 $e_4 \in R_U$ (2)
 $V_{e_6}(e_1 \parallel e_2 \parallel e_3 \parallel e_4, e_5) = 1$ (3)
 $e_2 = H(e_6)$ (4)

30 The above-mentioned formulas (1) and (2) mean verification of validity of the session information. Using the verification, fraud can be prevented. Such fraud may be, for example, storing a token exchange format in an other user apparatus 200 or reproducing a token by reusing the token
 35 exchange format.

The formula (3) means verification of validity of the signature of the token exchange

format. According to the verification, tampering with the token exchange format can be prevented.

The formula (4) means verification of the validity of the token issuer information. According to the verification, storing token issued by an issuer other than the signer of the token can be prevented.

Step 1112) The control part 230 in the tamper-proof device 280 of the user apparatus 200 deletes $e_4(=r_v)$ from the number set R_v in the storing part 270.

Step 1113) The control part 230 adds (e_1, e_2) to C_v in the storing part 270.

Step 1114) The control part 230 sends (e_1, e_2) to the control part 210 to notify of a normal end.

Step 1115) The control part 210 verifies that following formulas are satisfied. If the verification fails, the process is interrupted and the control part 230 notifies the control part 110 in the issuer apparatus 100 of the process interruption.

$$e_1 = H(m) \quad (5)$$

$$e_2 \in I_v \quad (6)$$

The formulas (5) and (6) mean verification that the sent token corresponds to the subject digital ticket and was issued by a proper issuer. According to the verification, it is verified that the issued ticket is valid.

(2) Transferring a digital ticket

The digital ticket transferring process from the user apparatus 200a to the user apparatus 200b via the connection apparatus 400 will be described in the following.

Fig.18 and Fig.19 are sequence charts showing the digital ticket transferring process according to an embodiment of the present invention.

In the figures, the connection apparatus 400 existing between the two user apparatuses 200a and 200b is not shown. "a" is added to the name of each element of the user apparatus 200a and "b" is added to the name of each element of the user apparatus 200b.

Step 2201) The control part 210a extracts the digital ticket m which is an object to be transferred from a set M_{va} retained by the storing part 220a.

Step 2202) The control part 210a of the user apparatus 200a extracts the accredited information (t_1, t_2, t_3) generated by the issuer of m from T_{va} included in the storing part 220a.

Step 2203) The control part 210a sends m and (t_1, t_2, t_3) to the control part 210b of the user apparatus 200b.

Step 2204) The control part 210b stores m in a set M_{vb} in the storing part 220b and stores (t_1, t_2, t_3) in an accredited information set T_{vb} in the storing part 220b.

Step 2205) The control part 210b requests to generate session information (s_1, s_2) to the control part 230b in the tamper-proof device 280b.

The control part 230b generates the session information (s_1, s_2) according to the following procedure and sends it to the control part 210b.

(a) The control part 230b obtains a number r_{vb} generated by the number generation part 260b in the tamper-proof device 280b.

(b) The number r_{vb} is added to a number set R_{vb} in the storing part 270b in the tamper-proof device 280b.

(c) The session information $(s_1, s_2) = (H(PkUb), r_{vb})$ is generated. Here, $PkUb$ is a verification key held by the control part 210b.

-46-

Step 2206) The control part 210b sends the session information (s_1, s_2) to the control part 210a of the user apparatus 200. In addition, issuer information I_{ub} may be sent with the session information (s_1, s_2) . By providing notification of the issuer information beforehand, generating and sending a token exchange format which does not satisfy formula (16) or (26) can be prevented.

Step 2207) The control part 210a sends (s_1, s_2) and a hash value $H(m)$ of the digital ticket to be transferred to the control part 230a.

Step 2208) The control part 230a in the tamper-proof device 280a verifies that following formulas are satisfied for C_{ua} which is stored in the storing part 270a.

$$\exists c_2((H(m), c_2) \in C_{ua}), \quad c_2 \in I_{ub} \quad (7)$$

When and if the verification fails, the process after that is interrupted and the control part 210a is notified of the failure.

The above formula (7) means verification that the token $(H(m), c_2)$ which corresponds to the digital ticket m to be transferred is stored in the storing part 270a.

Step 2209) The control part 230a of the tamper-proof device 280a obtains a token exchange format $e=(e_1, e_2, e_3, e_4, e_5, e_6, e_7, e_8)$ by using S_{PkUa} which is included in the signature part 250a and verification keys $PkUa, PkAa$, and a key certificate $(PkUa, S_{PkAa}(PkUa))$ which is included in the control part 210a of the user apparatus 200a. Each element of e is shown below.

$e_1 = H(m)$
 $e_2 = c_2$
 $e_3 = s_1$
 $e_4 = s_2$
 $e_5 = S_{PkUa}(H(m) \parallel c_2 \parallel s_1 \parallel s_2)$
 $e_6 = PkUa$

-47-

$$e_7 = S_{PkAa}(PkUa)$$

$$e_8 = PkAa$$

Step 2210) The control part 230a deletes $(H(m), c_2)$ from the set C_{Ua} if s_2 is positive.

5 Step 2211) The control part 230a sends e to the control part 210a.

Step 2212) The control part 210a sends e to the control part 210b of the user apparatus 200b.

10 Step 2213) The control part 210b sends e and the accredited information t to the control part 230b in the tamper-proof device 280b. The control part 210b requests to store the token in e .

15 Step 2214) The control part 230b verifies that all formulas below are satisfied by using the an authentication part 240b. If the verification fails, the process is interrupted and the control part 210b is notified of the interruption.

$$e_3 = H(PkUb) \quad (8)$$

$$e_4 \in R_{Ub} \quad (9)$$

$$20 \quad V_{e6}(e_1 \parallel e_2 \parallel e_3 \parallel e_4, e_5) = 1 \quad (10)$$

$$V_{e8}(e_6, e_7) = 1 \quad (11)$$

$$H(e_8) \in t_1 \quad (12)$$

$$V_{t3}(t_1, t_2) = 1 \quad (13)$$

$$e_2 = H(t_3) \quad (14)$$

25 The above formulas (8) and (9) mean verification of validity of the session information. According to the verification, fraud such as storing a token exchange format in a user apparatus other than the user apparatus 200b, reproducing a token by reusing the token exchange format or the like is prevented.

35 The formula (10) means verification for the validity of the signer of the token exchange format. According to this verification, tampering of the token exchange format can be prevented.

The formula (11) means verification of the key certificate of the signer. The formula (12)

-48-

means verification that the signer of the key certificate is included in the accredited objects in the accredited information. The formula (13) means verification of the validity of the accredited information. The formula (14) means verification that the signer of the accredited information is the same as the issuer of the token. According to the above verification, it is verified that the tamper-proof capability of the source of the token exchange format is assured by a party trusted by the issuer.

Step 2215) The control part 230b deletes $e_4 (=r_{ub})$ from the number set R_{ub} in the storing part 270b.

Step 2216) The control part 230b adds (e_1, e_2) to the set C_{ub} in the storing part 270b.

Step 2217) The control part 230b notifies the control part 210b of the normal completion of the process.

Step 2218) The control part 210b verifies that all formulas below are satisfied. If the verification fails, the process is interrupted and the control part 210a is notified of the interruption. If the verification succeeds, the control part 210a is notified of the normal completion of the process.

$$e_1 = H(m) \quad (15)$$

$$e_2 \in I_{ub} \quad (16)$$

The formulas (15) and (16) mean verification that the sent token corresponds to the subject digital ticket and was issued by a proper issuer. According to the verification, it is verified that the transferred ticket is valid.

When the issuer information is managed data by data in the control part 210b, $e_2 \in I_{ub}(m)$ is substituted for the formula (16).

(3) Consuming the digital ticket

The digital ticket consuming process from

the user apparatus 200 to the collector apparatus 300 via the connection apparatus 400 will be described in the following.

Fig.20 is a sequence chart of the ticket consuming process according to an embodiment of the present invention. In the figure, the connection apparatus 400 existing between the user apparatus 200 and the collector apparatus 300 is not shown.

Step 3301) The control part 210 extracts a digital ticket m to be consumed from M_v which is included in the storing part 220.

Step 3302) The control part 210 extracts the accredited information (t_1, t_2, t_3) generated by the issuer of m from T_v included in the storing part 220.

Step 3303) The control part 210 sends m and (t_1, t_2, t_3) to the control part 310 of the issuer apparatus 300.

Step 3304) The control part 310 generates session information (s_1, s_2) according to the following procedure.

(a) The control part 310 obtains a number r_e from the number generation part 330.

(b) The number r_e is added to a number set R_e in the storing part 340.

(c) The session information $(s_1, s_2) = (H(PkE), r_e)$ is generated. Here, PkE is a verification key held by the control part 310.

Step 3305) The control part 310 sends the session information (s_1, s_2) to the control part 210 of the user apparatus 200.

Step 3306) The control part 210 sends (s_1, s_2) and a hash value $H(m)$ of the digital ticket to be consumed to the control part 230 of the tamper-proof apparatus 280.

Step 3307) The control part 230 verifies that following formulas are satisfied for C_v which

-50-

is stored in the storing part 270.

$$\exists c_2((H(m), c_2) \in C_v) \quad (17)$$

When and if the verification fails, the process after that is interrupted and the control part 210 is notified of the failure.

The above formula (17) means verification that the token $(H(m), c_2)$ which corresponds to the digital ticket m to be consumed is stored in the storing part 270 of the tamper-proof device 280.

Step 3308) The control part 230 obtains a token exchange format $e=(e_1, e_2, e_3, e_4, e_5, e_6, e_7, e_8)$ by using the signature function S_{PkU} which is included in the signature part 250 and verification keys PkU, PkA , and a key certificate($PkU, S_{PkA}(PkU)$) which are included in the control part 210. Each element of e is shown below.

$$e_1=H(m)$$

$$e_2=C_2$$

$$e_3=S_1$$

$$e_4=S_2$$

$$e_5= S_{PkU}(H(m) \parallel c_2 \parallel s_1 \parallel s_2)$$

$$e_6= PkU$$

$$e_7= S_{PkA}(PkU)$$

$$e_8= PkA$$

Step 3309) The control part 230 of the tamper-proof device 280 deletes $(H(m), c_2)$ from C_v when s_2 is positive.

Step 3310) The control part 230 sends e to the control part 210.

Step 3311) The control part 210 sends e to the control part 310 of the collector apparatus 300.

Step 3312) The control part 310 verifies that all formulas below are satisfied by using the authentication part 320. If the verification fails, the process is interrupted and the control part 210 of the user apparatus 200 is notified of the interruption.

-51-

$$e_3 = H(PkE) \quad (18)$$

$$e_4 \in R_E \quad (19)$$

$$V_{e6}(e_1 \parallel e_2 \parallel e_3 \parallel e_4, e_5) = 1 \quad (20)$$

$$V_{e8}(e_6, e_7) = 1 \quad (21)$$

$$5 \quad H(e_8) \in t_1 \quad (22)$$

$$V_{t3}(t_1, t_2) = 1 \quad (23)$$

$$e_2 = H(t_3) \quad (24)$$

The above formulas (18) and (19) mean verification of validity of the session information.

10 According to the verification, fraud such as storing a token exchange format to a collector apparatus other than the collector apparatus 300, reproducing a token by reusing the token exchange format or the like is prevented.

15 The formula (20) means verification for the validity of the signer of the token exchange format. According to this verification, tampering of the token exchange format can be prevented.

The formula (21) means verification of the
20 key certificate of the signer. The formula (22) means verification that the signer of the key certificate is included in the accredited objects in the accredited information. The formula (23) means verification of the validity of the accredited
25 information. The formula (24) means verification that the signer of the accredited information is the same as the issuer of the token. According to the above verification, it is verified that the tamper-proof capability of the source of the token exchange
30 format is assured by a party trusted by the issuer.

Step 3313) The control part 310 of the collector apparatus 300 deletes $e_4 (=r_E)$ from R_E in the storing part 340.

Step 3314) The control part 310 verifies
35 that all formulas below are satisfied. If the verification fails, the control part 210 of the user apparatus 200 is notified of the process

-52-

interruption. If the verification succeeds, a service corresponding to m is provided to the consumer.

$$e_1 = H(m) \quad (25)$$

5 $e_2 \in I_E \quad (26)$

The formulas (25) and (26) means verification that the sent token corresponds to the subject digital ticket and was issued by a proper issuer. According to the verification, it is
10 verified that the consumed ticket is valid.

When the issuer information is managed data by data in the control part 310, $e_2 \in I_E(m)$ is substituted for the formula (26).

(4) Presenting the digital ticket

15 Presentation of the digital ticket can be realized by modifying the process of the ticket consumption as follows.

- The control part 310 generates $(s_1, s_2) = (H(PkE), -r_E)$ in (c) of the step 3304.

20 - A formula $-e_4 \in R_E$ is substituted for the formula (19) in the step 3312.

According to the above-mentioned modification, since s_2 becomes negative, $(H(m), c_2)$ is not deleted from C_v in step 3309. That is, it
25 becomes possible to verify that the user apparatus has a valid digital ticket at the time of the presentation while the valid digital ticket remains in the user apparatus. Thus, the inspection of the digital tickets becomes possible.

30 In the above descriptions (1)-(4), the sent token exchange format is not explicitly stored. On the other hand, storing the token exchange format in the storing part 220 produces an effect. That is, the user apparatus can send the history of the token
35 exchange format when sending m . As a result, it becomes possible to identify a fraudulent apparatus when fraud (double spending) is found. The fraud

-53-

may be, for example, that the tamper-proof device 28 is cracked.

(5) Returning the digital ticket

The collector can return the digital
5 ticket which has been consumed or presented to the issuer. Then, the issuer can pay a value to the collector. Accordingly, a value such as a fee can be paid to the issuer who has collected or inspected a digital ticket while preventing double-billing.

10 In the following, the process for returning will be described.

The issuer apparatus 100 further includes a part (a storing part 160) for storing the token exchange format e and a part for storing or
15 obtaining data m corresponding to the returned ticket and accredited information (t_1, t_2, t_3) .

The process for returning the digital ticket which is consumed or presented at the issuer apparatus 300 will be describe.

20 Step 5501) The issuer apparatus 300 sends the token exchange format e which is consumed or presented to the issuer apparatus 100.

Step 5502) The control part 100 of the issuer apparatus 100 verifies that a formula $e_2 =$
25 $H(PkI)$ is satisfied in which e_2 is included in e . When and if the verification fails, the issuer apparatus is notified of the failure and the process is interrupted. According to the verification, it is verified that e corresponds to the digital ticket
30 which is issued by the issuer apparatus 100 itself.

Step 5503) The control part 110 verifies that the formulas (20)-(22) are satisfied for e . When the accredited information (t_1, t_2, t_3) is obtained via an unreliable route (for example, via
35 the issuer), the formulas (23) and (24) are also verified. In this case, when verifying the formula (24), PkI is substituted for t_3 . When the

-54-

verification fails, the issuer apparatus 300 is notified of the failure and the process is interrupted. According to the verification, it is verified that e is circulated via a valid
5 circulation route.

Step 5504) The control part 110 verifies that the tamper-proof capability of e_3 is not assured by any third party which is trusted by t_1 in which e_3 is included in e when e_4 is positive.
10 Accordingly, it is verified that the valid token is not stored, that is, the right of the ticket is properly terminated due to consumption.

Step 5505) The control part 110 stores e in the storing part 160. If e has been already
15 stored in the storing part 160, the issuer apparatus 300 is notified of the failure and the process is interrupted.

Step 5506) The issuer provides a value according to the returned digital ticket to the
20 issuer.

(6) Book of tickets

A book of tickets can be realized by adding number information or time information to the token of the token exchange format. The number
25 information is assumed to be the number of the ticket.

Accordingly, when a plurality of digital tickets issued by the same issuer and having the same contents are issued, the digital tickets can be
30 treated properly and a plurality of same tokens can be sent effectively.

Specifically, by modifying the above-mentioned embodiments, the book of tickets can be realized.

- 35
- Number information c_3 is added to the token.
 - Number information e_n is added to the token exchange format.

-55-

- In the process of issuing the digital ticket, the number of tickets is specified as N when the token is generated (step 1102).

5 - In the process of transferring/consuming the digital ticket, when the step 2207 or the step 3306 is performed, the number of the digital tickets to be transferred/consumed is specified as n .

10 - In the process of transferring/consuming the digital ticket, when it is verified that the token is stored in step 2208 or step 3307, it is verified that the number of the tickets is adequate. That is, it is verified that C_v includes (c_1, c_2, c_3) in which $c_1 = H(m) \cap c_3 \geq n$ is satisfied.

15 - When the token exchange format is generated in step 1108, step 2209 or step 3308, $e_n = n$ is added and n is added and concatenated to the object to be signed in e_s such that $c_1 \parallel c_2 \parallel s_1 \parallel s_2 \parallel n$ is obtained.

20 - In the process of transferring/consuming, when deleting the token (when s_2 is positive in step 2210 or step 3309), $(H(m), c_2, c_3)$ is deleted from C_v only when $c_3 = n$ is satisfied. When $c_3 < n$, $(H(m), c_2, c_3)$ in C_v is updated to $(H(m), c_2, c_3 - n)$.

25 - When verifying the token exchange format in step 1111, step 2214 or step 3312, e_n is added and concatenated to the object to be verified in the signature verification by e_s (the formulas (3), (10) and (20)) such that $e_1 \parallel e_2 \parallel e_3 \parallel e_4 \parallel e_n$ is obtained.

30 - In the process of issuing/transferring the digital ticket, when storing the token in step 1113 or step 2216, if C_v already includes a token (c_1, c_2, c_3) in which $e_1 = c_1$ and $e_2 = c_2$ are satisfied, the token (c_1, c_2, c_3) in C_v is updated to $(c_1, c_2, c_3 + e_n)$.

35 - In the process of consuming/returning the digital ticket, the service or the value may be provided a plurality of times according to e_n .

(7) Retransmission control

-56-

The token can be retransmitted while preventing reproduction after abnormal conditions such as unintentional disconnection of a route are encountered. In the following, the process for the retransmission will be described. Specifically, the following procedures are added to some steps in the above-mentioned embodiments.

- The control part 110 or 230 retains the token exchange format e generated in step 1108, step 2209 or step 3308.

- The control part 210 or 310 notifies the control part 110 or 210 which sent the digital ticket of (s_1, s_2) when acknowledgment of receipt is sent in normal completion in step 1115, step 2218, or in providing a service in step 3314.

- The control part 110, 210 deletes the token exchange format corresponding to (s_1, s_2) after the acknowledgment of receipt is received.

When carrying out retransmission, some steps of the above-mentioned embodiment are modified as shown below.

- When the session information is obtained in step 1106, 2205 or 3304, the session information is not newly generated. Instead, the session information (s_1, s_2) stored in the storing part 220 or 340 is used.

- In step 1108, steps 2208-2210, and steps 3307-3309, if the control part 110 or 210 has e in which $(e_3=s_1) \cap (e_4=s_2)$ is satisfied, e is not newly generated and the retained e is used.

(8) Variations of issuing

Since the issue of the digital ticket can be assumed to be ticket (token) generation and transferring the ticket logically, the digital ticket can be issued by using the ticket transferring process described below for example. The amount of processing necessary for the process

-57-

increases as compared with the ticket issuing process described above, since the verification process of the ticket transferring is more complex than that of the ticket issuing.

5 (8-1) Use of self-certificate

According to the after mentioned process, the verification process of the token exchange format by the control part 230 is different between ticket issuing (step 1111) and ticket transferring
10 (step 2214). Implementation cost can be decreased by unifying the verification process as one in step 2214.

The control part 110 includes a key certificate (PkI , $S_{PkI}(PkI)$) by itself. As
15 described below, by modifying the ticket issuing process, the process of the control part 230 which is in the receiving side can be unified.

- The issuer apparatus includes the self hash value $H(PkI)$ in the accredited object t_1 by the
20 issuer when the accredited information generation part 150 generates the accredited information in step 1103.

- $e_7 = S_{PkI}(PkI)$ and $e_8 = PkI$ are used when the token exchange format e is generated in step
25 1108.

- The formulas (8)-(14) are used instead of the formulas (1)-(4) when the token exchange format e is verified in step 1111. U is substituted for U_b .

30 (8-2) Issuing the digital ticket by a user apparatus

As mentioned below, the user apparatus can issue the digital ticket by having a capability of generating a token issued by the user apparatus.

35 The process will be described in the following. In the description, it is assumed that data m is already generated.

-58-

- The control part 210 provides a hash value $H(m)$ of data m which corresponds to the digital ticket and the accredited object $t_1 = \{H(PkA_1), H(PkA_2), \dots, H(PkA_i)\}$ to the control part
 5 230.

- The control part 230 stores $(H(m), H(PkU))$ in the storing part 270 by using the verification key PkU .

The control part 230 generates $t_2 = S_{PkU}(H(PkA_1) \parallel H(PkA_2) \parallel \dots \parallel H(PkA_i))$ by using the
 10 signature part 250.

- The control part 230 returns $(t_1, t_2, t_3 = PkU)$ to the control part 210. The control part 210 stores (t_1, t_2, t_3) in the storing part 220.
 15 After that, the digital ticket is sent.

The above-mentioned examples of returning the tickets, the book of the tickets, retransmission control, and variations of issuing can be applied to the first embodiment.

20 Each element of the issuer apparatus 100, the user apparatus 200 or the collector apparatus 300 can be constructed by a program. The program can be stored in a disk unit connected to a computer which may be used as the issuer apparatus, the user
 25 apparatus or the collector apparatus. The program can be also stored in a transportable computer readable medium such as a floppy disk, a CD-ROM or the like. The program may be installed from the computer readable medium to a computer such that the
 30 present invention is realized by the computer.

Fig.21 is a block diagram showing a hardware configuration of such a computer. As shown in Fig.21, the computer system includes a CPU 500 by which a process of a program is executed, a memory
 35 501 for temporarily storing data and a program, an external storage unit 502 for storing data and a program to be loaded into the memory 501, a display

-59-

503 for displaying data, a keyboard 504 for inputting data or commands, and a communication processing unit 505 which enables the computer system to communicate with other computers via a network. The program is installed in the external storage unit 502 then loaded into memory 501 and executed by the CPU 500.

As mentioned above, according to the second embodiment of the present invention, the token can be transmitted only via routes which are trusted by the issuer and the user or the collector identified by the issuer. Thus, the occurrence of the token corresponding to the data being newly stored in the token storing part by a person other than the issuer indicated by the token issuer information in the token can be prevented. In addition, the occurrence of the token being reproduced to a plurality of the token storing parts while the token is transferred can be prevented.

In addition, by regarding data with the token issued by a specific issuer as original, it becomes possible to restrict the number issuances of the original data by the issuer.

Further, by using an information identifier such as an URL which exists in an network as data, an access right of the information which can not be reproduced and can be transferred can be provided.

Further, by using a ticket with the correct contents or by using an identifier of the ticket, only the ticket that has a valid token can be regarded as a valid ticket and a user or a collector can refuse a ticket other than the valid ticket. Thus, fraudulent use (for example, double spending and illegal reproduction) of the ticket can be prevented.

Furthermore, by using a program as data of

-60-

the present invention and by using the token issued by a specific issuer as a license of the program, illegal copying and use of the program can be prevented. In this case, the program execution
5 apparatus can refuse to execute a program other than the program with the token.

Further, by using music data or image data as data of the present invention, illegal copying and use of the music data or image data, in which
10 the token issued by a specific issuer is used as an appreciation right can be prevented. A display apparatus of the data or a playback apparatus can refuse to display or playback data other than the data with the token.

15 The present invention is not limited to the specifically disclosed embodiments, and variations and modifications may be made without departing from the scope of the invention.

20

25

30

35

78230-3

-61-

CLAIMS:

1. An original data circulation
5 method in an original data circulation system for
storing or circulating original data which is
digital information, the method comprising:
a sending step of sending, by a first
10 apparatus, originality information to a second
apparatus, the originality information including a
fingerprint corresponding to a source apparatus of
the original data and second information
corresponding to the original data, and
an authentication step of identifying and
15 authenticating, by the second apparatus, the source
apparatus, verifying whether the source apparatus is
the same as an apparatus corresponding to the
fingerprint, and determining that the originality
information is valid if the source apparatus is the
20 same as an apparatus corresponding to the
fingerprint.

25
2. The original data circulation
method as claimed in claim 1, wherein the source
apparatus conceals a secret key, and the fingerprint
is a hash value generated by applying a
30 unidirectional function to a public key of the
source apparatus; and
the second apparatus authenticates the
source apparatus by verifying that the source
apparatus has a private key corresponding to the
35 fingerprint.

78230-3

-62-

3. The original data circulation method as claimed in claim 1, wherein the sending
5 step includes a step of sending a third party certificate to the second apparatus, the third party certificate being a certificate representing that the second apparatus is authenticated by a third party; and
10 the second apparatus authenticates the first apparatus by verifying that the third party certificate authenticates the first apparatus and that a certifier in the third party certificate is included in third parties stored in the second
15 apparatus.

20 4. The original data circulation method as claimed in claim 1, wherein the first apparatus conceals a private key of the first apparatus; and
in the step of sending, the first
25 apparatus sends, to the second apparatus, a public key certificate and a first signature corresponding to the private key, wherein the public key certificate is generated by adding, to a public key corresponding to the private key, a second signature
30 of a third party which trusts the first apparatus; and

in the authentication step, the second apparatus verifies the first signature by using the public key included in the public key certificate,
35 and verifies whether a hash value of a public key of the third party is included in fingerprints of third parties stored in the second apparatus.

78230-3

-63-

5 5. The original data circulation
method as claimed in claim 1, wherein the second
apparatus includes accreditation information that
indicate one or a plurality of source apparatuses
trusted by the second apparatus, and
10 in the authentication step, the second
apparatus verifies whether the fingerprint of the
source apparatus of the original data is included in
the accreditation information.

15

 6. An original data circulation
system for storing or circulating original data
20 which is digital information, the system comprising:
 a first apparatus which includes sending
means for sending originality information, the
originality information including a fingerprint
corresponding to a source apparatus of the original
25 data and second information corresponding to the
original data; and
 a second apparatus which includes
authentication means for identifying and
authenticating the source apparatus of the original
30 data, and means for verifying whether the source
apparatus is the same as an apparatus corresponding
to the fingerprint, and determining that the
originality information is valid if the source
apparatus is the same as an apparatus corresponding
35 to the fingerprint.

78230-3

-64-

7. The original data circulation system as claimed in claim 6, wherein the source apparatus conceals a secret key, and the fingerprint is a hash value generated by applying a unidirectional function to a public key of the source apparatus;

the second apparatus authenticates the source apparatus by verifying that the source apparatus has a private key corresponding to the fingerprint.

15

8. The original data circulation system as claimed in claim 6, wherein the sending means includes means for sending a third party certificate to the second apparatus, the third party certificate being a certificate representing that the second apparatus is authenticated by a third party; and

the second apparatus authenticates the first apparatus by verifying that the third party certificate authenticates the first apparatus and that a certifier in the third party certificate is included in third parties stored in the second apparatus.

30

9. The original data circulation system as claimed in claim 6, wherein the first apparatus conceals a private key of the first apparatus; and

35

78230-3

-65-

the first apparatus sends, to the second apparatus, a public key certificate and a first signature corresponding to the private key, wherein the public key certificate is generated by adding,
5 to a public key corresponding to the private key, a second signature of a third party which trusts the first apparatus; and

the second apparatus verifies the first signature by using the public key included in the
10 public key certificate, and verifies whether a hash value of a public key of the third party is included in fingerprints of third parties stored in the second apparatus.

15

10. The original data circulation system as claimed in claim 6, wherein the second
20 apparatus includes means for storing or obtaining accreditation information that indicate one or a plurality of source apparatuses trusted by the second apparatus; and

the second apparatus verifies whether the
25 fingerprint of the source apparatus of the original data is included in the accreditation information.

30

11. An original data circulation system for storing or circulating original data which is digital information, the original data circulation system comprising:

35 an issuer apparatus which includes means for generating originality information and sending the originality information, the originality

78230-3

-66-

information including a fingerprint corresponding to the issuer apparatus and second information corresponding to the original data;

5 a user apparatus which includes means for verifying validity of a source apparatus of the originality information and means for storing the originality information when the validity is verified; and

10 a collector apparatus which includes means for verifying validity of a source apparatus of the originality information and data processing means for performing a process on the original data if the validity is verified.

15

12. An original data circulation system for storing or circulating original data which is digital information, the original data circulation system comprising:

an issuer apparatus including:
first originality information generation means for generating originality information which includes a fingerprint corresponding to the issuer apparatus and second information corresponding to the original data; and

first originality information sending means for sending the originality information;

30 a user apparatus including:
first originality information sending means for sending the originality information;
first identifying means for identifying a source apparatus of the originality information;

35 first authentication means for determining that the originality information is valid if the source apparatus is authenticated and an apparatus

78230-3

-67-

corresponding to the fingerprint and the source apparatus are the same; and

storing means for storing the originality information when the first authentication means
5 determines that the originality information is valid; and

a collector apparatus including:

second identifying means for identifying a source apparatus of originality information;

10 second authentication means for authenticating the source apparatus; and

data processing means for performing a process corresponding to the original data if the second authentication means determines that the
15 originality information which is sent to the collector apparatus is valid.

20

13. The original data circulation system as claimed in claim 11, the collector apparatus further comprising means for sending, to the issuer apparatus, the originality information
25 received from the user apparatus;

the issuer apparatus further comprising:
means for verifying that the originality information is generated by the issuer apparatus;

30 means for verifying that the originality information is sent via a valid route;

means for verifying that the original data corresponding to the second information has been processed by the data processing means; and

35 means for providing a value according to the original data to the collector apparatus.

78230-3

-68-

14. The original data circulation system as claimed in claim 11, the issuer apparatus
5 further comprising means for adding a usable number of the original data as count information to the originality information;

the user apparatus further comprising means for verifying the count information;

10 the collector apparatus further comprising means for verifying the count information;

wherein the user apparatus can use the data the usable number of times.

15

15. The original data circulation system as claimed in claim 11, wherein the user
20 apparatus sends session information which has uniqueness in the data circulation system when the user apparatus sends the originality information;

the user apparatus which sends the originality information stores the originality
25 information and the session information; and

another user apparatus which receives the session information sends the session information to the user apparatus of the sending side when the
another user apparatus receives the originality
30 information; and

the user apparatus of the sending side deletes the originality information and the session information.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

TO ISSUER APPARATUS 1, USER APPARATUS 2, COLLECTOR APPARATUS 3




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14




FIG. 15




FIG. 16

TO ISSUER APPARATUS 1, USER APPARATUS 2, COLLECTOR APPARATUS 3




FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21



ISSUER APPARATUS

USER APPARAUS

GENERATE TICKET IN CONTROL
PART

S 101

GENERATE MANIFEST IN MANIFEST
GENERATION PART

S 102

GENERATE ACCREDITED
INFORMATION WITH SIGNATURE

S 103

TICKET AND ACCREDITED INFORMATION WITH
SIGNATURE

S 104

STORE TICKET AND ACCREDITED
INFORMATION WITH SIGNATURE

S 105

GENERATE SESSION INFORMATION

SESSION INFORMATION

S 106

OBTAINS MANIFEST ISSUING
FORMAT BY USING VERIFICATION
KEY

S 108

MANIFEST ISSUING FORMAT

S 109

REQUEST TO STORE MANIFEST

S 110

VERIFY SESSION INFORMATION AND
SIGNATURE

S 111

DELETE $e_3 (=r_U)$ FROM
NUMBER SET

S 112

ADD MANIFEST TO MANIFEST SET

S 113

SEND MANIFEST FROM CONTROL
PART 23 TO CONTROL PART 21

S 114