

12

EUROPEAN PATENT APPLICATION

21 Application number: 85300778.9

51 Int. Cl.⁴: **B 65 G 11/02**
B 65 B 67/08

22 Date of filing: 06.02.85

30 Priority: 08.02.84 GB 8403314
01.08.84 US 636771

71 Applicant: **MOBIL OIL CORPORATION**
150 East 42nd Street
New York New York 10017(US)

43 Date of publication of application:
02.10.85 Bulletin 85/40

72 Inventor: **van Cleef Lambert, James**
1776 Lake Road
Webster New York 14580(US)


84 Designated Contracting States:
AT BE CH DE FR IT LI LU NL SE

72 Inventor: **Rice, William Estus**
23 Chelsea Way
Fairport New York 14450(US)

74 Representative: **West, Alan Harry**
Mobil Court 3 Clements Inn
London WC2A 2EB(GB)

54 Apparatus for dispensing plastics stretch film.

57 An apparatus for stretching a plastic film around a package includes two handles 15, 17 secured to the core 11 of the plastic film 12, one handle 15 effectively extending the core and having a braking cover for effecting tension control. The other handle 17 includes a U-shaped member to provide a second grip 19 parallel to, but displaced from the axial centerline of the core. The plastic film 12 is configured between the two handles 15, 17 for rotation about the centerline axis of its core.



F-2682

APPARATUS FOR DISPENSING PLASTICS STRETCH FILM

This invention relates to apparatus for dispensing plastics stretch film and in particular for manually wrapping plastics stretch film around a package, for example a loaded pallet.

There exist many apparatus for wrapping a plastic film around a package. For example, U. S. Patent No. 4,179,081 discloses apparatus for manually dispensing plastics stretch film in which the film is contained on a core having extended ends. A pair of flexible hand grips are rotatably mounted on the ends of the core whereby control of the tension on the film during dispensing can be achieved by manually squeezing the hand grips to effect a braking action on the core. While this apparatus provides a satisfactory manual dispenser for stretch film, it suffers from the disadvantage that it is difficult, in view of the projecting ends of the core, to wrap film around a package near the ground-engaging surface of the package. An object of the present invention is therefore to obviate or minimize this problem.

Accordingly, the invention resides in one aspect in apparatus for dispensing plastic film having a core comprising:

a first handle extending along the axial centerline of the core and fixed to the core for simultaneous rotation therewith;

a flexible handgrip covering said first handle and configured for slideable rotation on said first handle; and

a second generally U-shaped handle with two members, a first member having a centerline coincident with said centerline of said core and a second member having a centerline parallel to said centerline of said core, said first member being mounted in said core to remain stationary while permitting axial rotation of said core and said second member arranged to provide a handgrip.

In a further aspect, the invention resides in apparatus for manually dispensing plastics stretch film comprising a hollow core for receiving a roll of the film, the core being of a length such that it projects from one end, but not both ends, of the film in use; a flexible hand grip rotatably mounted on said one end of the core to permit control of the tension on the film during manual dispensing of the film; and a generally U-shaped handle separate from the core and having one limb rotatably mounted in the other end of the core, the other limb of the handle being generally parallel, with, but spaced from, the axis of the core and extending towards said one end of the core.

The accompanying drawing is a sectional view of a plastic film dispenser according to one example of the invention.

Referring to the drawing, the apparatus includes a hollow core 11 around which is wound a roll of plastics stretch film 12. The length of the core 11 exceeds the width of the film 12 so that one end 13 of the core 11 extends from the adjacent edge of the roll of stretch film. The other end 14 of the core is, however, arranged so as to lie flush with the adjacent edge of the film.

Rotatably mounted on the extending end 13 of the core 11 is a flexible hand grip 15 conveniently in the form of a cup-shaped PVC member. If desired, the external surface of the hand grip 15 may be provided with axially extending ribs [not shown] to facilitate gripping thereof.

Mounted in the other end 14 of the core 11 is one limb 16 of a generally U-shaped handle 17, conveniently molded in polyethylene or other suitable thermoplastics material. The limb 16 of the handle 17 is generally in the form of a hollow cylinder which, at least at its free end, is normally of increased external diameter as compared to the internal diameter of the core. The limb 16 is, however, formed with an axially extending slot 18 so that, by resiliently deforming the limb 16 so as to close the slot 18, the limb 16 can be inserted

into the end 14 of the core 11. In use, therefore, the limb 16 is urged by its own resilience against the internal surface of the core 11 so that the handle 17 is releasably retained by the core but at the same time the core is free to rotate relative to the handle.

The other limb 19 of the handle 17 is also in the form of a hollow cylinder whose axis is parallel with, but spaced from, the axis of the core 11 and which extends towards the end 13 of the core. The limb 19 is conveniently formed with external, axially extending ribs to facilitate gripping of the handle 17 and is joined to the limb 16 by a base member 21 in the form of a shallow trough strengthened by internal ribs 22. It is to be appreciated that by arranging that the limbs 16, 19 are hollow and the base member 21 is in the form of a trough minimizes the amount of material required to mold the handle 17. In this way the cost of the handle 17 is minimized so that the entire assembly of the handle 17, core 11 and hand grip 5 can be thrown away after the roll of film 12 has been used up.

When the apparatus described above is used to wrap the film 12 around a package, such as a loaded pallet, the operator grips the limb 19 of the handle 17 and the hand grip 15. Then, by squeezing the hand grip 15, the operator can adjust the tension on the film 12 to stretch the film during wrapping. In addition, since the film 12 extends up to the other end 14 of the core 11 and the handle 17 projects therefrom only by the height of the shallow base member 21, the film 12 can be readily wrapped adjacent the ground-engaging surface of the package.

Claims:


1. An apparatus for dispensing plastic film having a core comprising:

a first handle extending along the axial centerline of the core and fixed to the core for simultaneous rotation therewith;

a flexible handgrip covering said first handle and configured for slideable rotation on said first handle; and

a second generally U-shaped handle with two members, a first member having a centerline coincident with said centerline of said core and a second member having a centerline parallel to said centerline of said core, said first member being mounted in said core to remain stationary while permitting axial rotation of said core and said second member arranged to provide a handgrip.

2. Apparatus for manually dispensing plastics stretch film comprising a hollow core for receiving a roll of the film, the core being of a length such that it projects from one end, but not both ends, of the film in use; a flexible hand grip rotatably mounted on said one end of the core to permit control of the tension on the film during manual dispensing of the film; and a generally U-shaped handle separate from the core and having one limb rotatably mounted in the other end of the core, the other limb of the handle being generally parallel, with, but spaced from, the axis of the core and extending towards said one end of the core.





European Patent
Office

EUROPEAN SEARCH REPORT

0156468

Application number

EP 85 30 0778

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
D, Y	DE-A-2 923 643 (PARRY) * Whole document *	1, 2	B 65 B 11/02 B 65 B 67/08
Y	US-A-4 102 513 (GUARD) * Whole document *	1, 2	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			B 65 B
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 10-05-1985	Examiner CLAEYS H.C.M.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			