



(86) Date de dépôt PCT/PCT Filing Date: 2012/05/09
(87) Date publication PCT/PCT Publication Date: 2012/11/15
(85) Entrée phase nationale/National Entry: 2014/11/06
(86) N° demande PCT/PCT Application No.: US 2012/037103
(87) N° publication PCT/PCT Publication No.: 2012/154841
(30) Priorités/Priorities: 2011/05/09 (US61/484,126);
2012/03/27 (US61/616,234)

(51) Cl.Int./Int.Cl. *G06T 7/00* (2006.01),
G06F 17/10 (2006.01), *G06F 19/00* (2011.01)
(71) Demandeur/Applicant:
MCVEY, CATHERINE GRACE, US
(72) Inventeur/Inventor:
MCVEY, CATHERINE GRACE, US
(74) Agent: BORDEN LADNER GERVAIS LLP

(54) Titre : ANALYSE D'IMAGE PERMETTANT DE DETERMINER DES CARACTERISTIQUES D'UN ANIMAL ET D'UN
ETRE HUMAIN
(54) Title: IMAGE ANALYSIS FOR DETERMINING CHARACTERISTICS OF ANIMALS AND HUMANS

Facial Descriptor Name: Degree of Facial Inflexion

Anatomical Region of Face: AB01_FacialProfile

General Description:

Describes the degree of structural concavity/convexity of the *True Line of the Face*. Differentiate between a concave "dished", convex "roman", or straight bone structure.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$$

finds the angle for $\angle BAC$, denoted here as θ

$$d = \sin(\theta) * \overline{AC}$$

finds the height of triangle $\triangle ABC$, the distance of facial inflexion

$$M_{AB} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of line $\overline{AB}$

$$Q_x = \left(\frac{C_y - A_y}{M_{AB}} \right) + A_x$$

finds the x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C

$$s = Q_x - C_x$$

finds a value for which s is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face

$$s' = \frac{s}{|s|}$$

finds s' here defined as the Constant of Concavity with magnitude 1 indicating direction of inflexion via sign (+)

$$DoFI = s' * \left(\frac{d}{\overline{AB}} \right)$$

finds the Degree of Facial Inflexion; here defined as the degree of perpendicular deviation of the Upper Profile of the skull from the True Line of the Face relative to the overall length of the face.





Fig. 1A

(57) **Abrégé/Abstract:**

Systems and methods are disclosed for predicting one or more characteristics of a animal by applying computational methods to image(s) of the animal to generate one or more metrics indicative of the characteristics. Embodiments determine predictors of



(57) Abrégé(suite)/Abstract(continued):

characteristics by creating a sample library of animals of a particular type, determining facial descriptor measurements for each animal, determining relationships between facial descriptor measurements and additional library data, and selecting predictors from these relationships. Other embodiments predict characteristics of animals not in the library and, optionally, categorize animals for particular discipline, training, management, care, etc. based on the characteristics. Other embodiments predict characteristics and determine strategies for group(s) of animals using predicted characteristics of individual animals. Embodiments are broadly applicable to domesticated animals including dogs, cats, cattle, oxen, llamas, sheep, goats, camels, geese, horses, chickens, turkeys, and pigs. Other embodiments predict certain characteristics of humans, including certain cognitive or developmental disorders.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



WIPO | PCT



(10) International Publication Number
WO 2012/154841 A8

(43) International Publication Date
15 November 2012 (15.11.2012)

(51) International Patent Classification:

G06T 7/00 (2006.01) **G06F 17/10** (2006.01)
G06F 19/00 (2011.01)

(21) International Application Number:

PCT/US2012/037103

(22) International Filing Date:

9 May 2012 (09.05.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/484,126 9 May 2011 (09.05.2011) US
61/616,234 27 March 2012 (27.03.2012) US

(72) Inventor; and

(71) Applicant : **MCVEY, Catherine, Grace** [US/US]; 1031
Hanford Road, Graham, NC 27253 (US).

(74) Agent: **NOTO, Aldo**; Andrews Kurth LLP, 1350 I Street,
N.W. Suite 1100, Washington, DC 20005 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMAGE ANALYSIS FOR DETERMINING CHARACTERISTICS OF ANIMAL AND HUMANS

Facial Descriptor Name: Degree of Facial Inflection

Anatomical Region of Face: AR01_FacialProfile

General Description:

Describes the degree of structural concavity/convexity of the *True Line of the Face*. Differentiate between a concave "dished", convex "roman", or straight bone structure.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 \times \overline{AB} \times \overline{AC}} \right)$$

finds the angle for $\angle BAC$, denoted here as θ

$$d = \sin(\theta) \times \overline{AC}$$

finds the height of triangle $\triangle ABC$, the distance of facial inflection

$$M_{AB} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of line $\overline{AB}$

$$Q_x = \left(\frac{C_y - A_y}{M_{AB}} \right) + A_x$$

finds the x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C

$$a = Q_x - C_x$$

finds a value for which a is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face

$$\sigma_3 = \frac{a}{|a|}$$

finds σ_3 , here defined as the Constant of Concavity with magnitude 1 indicating direction of inflection via Sign ($\pm$)

$$DoFI = \sigma_3 \times \left(\frac{d}{\overline{AB}} \right)$$


finds the **Degree of Facial Inflection**, here defined as the degree of perpendicular deviation of the Upper Profile of the skull from the *True Line of the Face* relative to the overall length of the face.

Fig. 1A

(57) Abstract: Systems and methods are disclosed for predicting one or more characteristics of a animal by applying computational methods to image(s) of the animal to generate one or more metrics indicative of the characteristics. Embodiments determine predictors of characteristics by creating a sample library of animals of a particular type, determining facial descriptor measurements for each animal, determining relationships between facial descriptor measurements and additional library data, and selecting predictors from these relationships. Other embodiments predict characteristics of animals not in the library and, optionally, categorize animals for particular discipline, training, management, care, etc. based on the characteristics. Other embodiments predict characteristics and determine strategies for group(s) of animals using predicted characteristics of individual animals. Embodiments are broadly applicable to domesticated animals including dogs, cats, cattle, oxen, llamas, sheep, goats, camels, geese, horses, chickens, turkeys, and pigs. Other embodiments predict certain characteristics of humans, including certain cognitive or developmental disorders.



WO 2012/154841 A8

WO 2012/154841 A8



Published:

- *with international search report (Art. 21(3))*
- *with information concerning incorporation by reference of missing parts and/or elements (Rule 20.6)*

(48) Date of publication of this corrected version:

3 April 2014

(15) Information about Correction:

see Notice of 3 April 2014

(88) Date of publication of the international search report:

4 April 2013

IMAGE ANALYSIS FOR DETERMINING CHARACTERISTICS OF ANIMALS AND HUMANS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the priority of U.S. Provisional Application Serial No. 61/484,126, entitled “Image Analysis for Determining Characteristics of Animals,” which was filed May 9, 2011 and is incorporated herein by reference. This application also claims the priority of U.S. Provisional Application Serial No. 61/616,234, entitled “Image Analysis for Determining Characteristics of Animals,” which was filed March 27, 2012 and is incorporated herein by reference.

10 TECHNICAL FIELD

[0002] The disclosure herein relates to the objective determination of a characteristic of an animal or human by applying computational methods to one or more images of the animal or human to generate one or more metrics indicative of the characteristic of interest. It also relates to the pairing of animals and humans that are better suited to work together.

BACKGROUND

[0003] Animal domestication can be thought of as developing a mutually useful relationship between animals and humans. Over the past 12,000 years, humans have learned to control their access to food and other necessities of life by changing the behaviors and natures of wild animals. All of today’s domesticated animals – including dogs, cats, cattle, oxen, llamas, sheep, goats, camels, geese, horses, chickens, turkeys, and pigs – started out as wild animals but were changed over the centuries and millennia into animals that are tamer, quieter, and generally more cognitively suited to a lifestyle of coexistence with humans. Today people benefit from domesticated animal in many ways including keeping cattle in pens for access to milk and meat and for pulling plows, training dogs to be guardians and companions, teaching horses to adapt to the plow or take a rider, and changing the lean, nasty wild boar into the fat, friendly pig.

[0004] When individuals are looking to breed animals, they look for certain traits in purebred stock that are valued for a particular purpose, or may intend to use some type of crossbreeding to produce a new type of stock with different, and, it is presumed, superior abilities in a given area of endeavor. For example, to breed chickens, a typical

breeder intends to receive eggs, meat, and new, young birds for further reproduction. Thus, the breeder has to study different breeds and types of chickens and analyze what can be expected from a certain set of characteristics before he or she starts breeding them. On the other hand, purebred breeding aims to establish and maintain stable traits that animals will pass to the next generation. By "breeding the best to the best," employing a certain degree of inbreeding, considerable culling, and selection for "superior" qualities, one could develop a bloodline superior in certain respects to the original base stock.

[0005] As first noted by Charles Darwin, domesticated animals are known to share a common set of physical characteristics, sometimes referred to as the domestication phenotype. C. Darwin, *THE VARIATION OF ANIMALS AND PLANTS UNDER DOMESTICATION* (2nd ed.) (New York: D. Appleton & Co., 1883). They are often smaller, with floppier ears and curlier tails than their untamed ancestors. Their coats are sometimes spotted while their wild ancestors' coats are solid. One long-term study demonstrating this phenomenon has been ongoing since 1958 at the Institute of Cytology and Genetics in Novosibirsk, Russia. In this study, scientists have successfully demonstrated that, through careful selective breeding for tamability, wild Siberian silver foxes acquire both the behavioral and appearance traits of domesticated dogs. See, e.g., L. Trut, *Early Canid Domestication: The Fox Farm Experiment*, 87 *AMERICAN SCIENTIST* 160-69 (Mar.-Apr. 1999). This highly conserved combination of psychological and morphological changes during the process of domestication is seen to varying degrees across a remarkably wide range of species, from horses, dogs, pigs, and cows to some non-mammals like chickens and even a few fish. However, in no other species has this relationship between behavior and anatomical features been more widely noted than in the horse.

[0006] The partnership between human and horse is among the earliest bonds formed between mankind and the animal world. Archeological findings estimate that horses have been domesticated for approximately 5,500 years, and throughout this extended relationship these two cohabitating species have certainly left a mark on one another. Few major civilizations exist in pre-modern history that did not make use of the horse's strength and speed for survival and economic prosperity. As a result of this dependence, centuries of selective breeding have seen mankind gradually reshape the horse from the form of its wild forbearers into the athletic and reliable working partner that we know

today. The value that early breeders placed on physical attributes such as size, color, and build varied greatly by region largely as a product of differing climates, terrains, and lifestyles. However, all early horsemen placed special emphasis on breeding for horses cognitively capable of thriving in a human environment and working relationship. It was from this early focus on behavioral characteristics in the development of the domesticated horse that the practice of relating physiological aspects of the equine face to aspects personality was first derived. From the earliest mentions in the ancient Bedouin breeding books of 300 B.C., to the extensive facial analysis techniques of the Gypsy tribes of eighteenth-century Russia, nearly every major equestrian culture in history has recognized a relationship between physiological features of the equine face and innate traits of personality. Even amongst the many technological and scientific advancements of the modern era, today's multi-billion dollar horse industry has still held fast to many of its long-standing traditions and customs, including the use of facial analysis techniques to predict equine personality and trainability.

[0007] Relationships also exist in humans between physiological feature sets (i.e., phenotypes) and certain cognitive functions and/or personality traits. During progressive stages of human embryonic growth, development of the brain and face remains intimately connected through both genetic signaling and biomechanical/biochemical mechanisms. The face develops from populations of cells originating from the early neural crest, with cells from the neural tube gradually shifting to form the prominences of the face. Differentiation of these early cells is closely regulated through intricate genetic signaling mechanisms, with the brain essentially serving as the platform on which the face grows. As these two structures continue to grow and develop during the later embryonic stages, their phenotypes remain closely linked as complex genetic hierarchies regulate patterns of cross talk between molecules, cells, and tissues.

SUMMARY

[0008] Embodiments comprise a method for measuring an animal to determine one or more characteristics of the animal, comprising receiving one or more digital images representing said animal, storing the images in a computer memory, adding a plurality of reference points to the stored digital images, and computing one or more metrics relating to the characteristic of the animal using the reference points. Other

embodiments comprise a method for determining a characteristic of an animal based on a set of metrics related to the animal, comprising selecting one or more metrics from the set of metrics, calculating a combined metric using the selected metrics, and determining the characteristic of the animal based on the value of the combined metric.

5 Other embodiments comprise computer systems that implement one or more of the above methods.

[0009] Other embodiments comprise methods and systems that can be used to predict certain characteristics of humans, including certain human cognitive or developmental disorders. The methods include measurements of facial features and the use of such
10 measurements in computations. Other embodiments pair humans and animals based on characteristics and/or various types of suitability, for example suitability to work or perform a certain task together.

[0010] Other embodiments include a method for predicting a characteristic of a type of animal comprising, for each of a plurality of individual animals of the type, storing
15 one or more digital images representing the individual animal in a memory operably connected to a digital computer; annotating the one or more digital images with a plurality of reference points; associating at least one other data value about the individual animal with the one or more digital images representing the individual animal; computing, with the digital computer, one or more metrics using the plurality of
20 reference points. The method further comprises selecting a combination of the one or more metrics for predicting the characteristic of the animal. In some embodiments, the selecting step further comprises determining one or more relationships between the one or more metrics and the at least one other data value for the plurality of individual animals and the combination is selected based on the one or more relationships. Other
25 embodiments comprise systems and computer-readable media embodying these methods.

[0011] Other embodiments include a method for determining a characteristic of an animal based on one or more metrics related to the animal, comprising storing one or more digital images representing the animal in a memory operably connected to a
30 digital computer; annotating the one or more digital images with a plurality of reference points; computing, with the digital computer, the one or more metrics using the plurality of reference points; and predicting the characteristic of the animal based on the one or more metrics. In some embodiments, the predicting step further comprises computing a

combined metric based on a predetermined function of the one or more metrics and predicting the characteristic based on the combined metric. Other embodiments comprise systems and computer-readable media embodying these methods.

5 [0012] Other embodiments include a method for predicting one or more characteristics of a group of animals of the same type comprising, for each of the individual animals within the group, storing one or more digital images representing the individual animal in a memory operably connected to a digital computer; annotating the one or more digital images with a plurality of reference points; computing, with the digital computer, one or more metrics using the plurality of reference points; and
10 predicting one or more characteristics of the individual animal based on the one or more metrics. The method further comprises predicting the one or more characteristics of the group of animals based on the predicted one or more characteristics of the individual animals comprising the group. Some embodiments further comprise determining a strategy for maintaining or managing the group of animals based on the predicted one
15 or more characteristics of the group of animals. Some embodiments further comprise computing one or more combined metrics, each based on a predetermined function of the one or more metrics, and predicting the one or more characteristics of the individual animal based on the one or more combined metrics. Other embodiments comprise systems and computer-readable media embodying these methods.

20 [0013] Other embodiments include a method for determining a characteristic of a human or animal subject, comprising calculating two or more ratios based upon metrics related to a subject's head, wherein distances or angles between reference points on the subject's head are used; predicting, using a computer and computations, a characteristic of the subject wherein the two or more ratios are used and wherein data about a group
25 of subjects are referenced; and providing the predicted characteristic to an output device. Other embodiments comprise systems and computer-readable media embodying these methods.

[0014] Other embodiments include a method for determining a characteristic of a person based on one or more metrics related to the person, comprising storing one or
30 more digital images representing the person in a memory operably connected to a digital computer; annotating the one or more digital images with a plurality of reference points; computing, with the digital computer, the one or more metrics using the plurality of reference points; and predicting the characteristic of the person based on the one or

more metrics. Other embodiments comprise systems and computer-readable media embodying these methods.

[0015] Other embodiments include a method for choosing a combination of a person and an animal for a particular task, comprising computing one or more metrics related to the person; computing one or more metrics related to each of a plurality of animals; computing a combination characteristic related to the combination of the person with each of the plurality of animals, based on at least a portion of the one or more metrics related to the person and at least a portion of the one or more metrics related to each of the plurality of animals; and determining the combination of the person and one of the plurality of animals based on the computed combination characteristics. Other embodiments comprise systems and computer-readable media embodying these methods.

[0016] Other embodiments include a method for choosing a combination of a person and an animal for a particular task, comprising computing one or more metrics related to the animal; computing one or more metrics related to each of a plurality of persons; computing a combination characteristic related to the combination of the animal with each of the plurality of persons, based on at least a portion of the one or more metrics related to the animal and at least a portion of the one or more metrics related to each of the plurality of persons; and determining the combination of the animal and one of the plurality of persons based on the computed combination characteristics. Other embodiments comprise systems and computer-readable media embodying these methods.

DESCRIPTION OF THE DRAWINGS

[0017] The detailed description will refer to the following drawings, wherein like numerals refer to like elements, and wherein:

Fig. 1A shows facial description measurement AR01_Degree of Facial Inflexion;

Fig. 1B shows facial description measurement AR01_Degree of Nose Rounding;

Fig. 1C shows facial description measurement AR01_Face Thickness Proportion;

Fig. 1D shows facial description measurement AR01_Forehead Slope Proportion;

Fig. 1E shows facial description measurement AR01_Forehead Height Proportion;

Fig. 1F shows facial description measurement AR01_Forehead Length Proportion;

Fig. 1G shows facial description measurement AR01_Nose Length Proportion;

- Fig. 1H shows facial description measurement AR01_Nose Roundness Proportion;
 Fig. 1J shows facial description measurement AR01_Nostril Position Proportion;
 Fig. 1K shows facial description measurement AR01_Degree of Eye Orbital Protrusion;
 Fig. 2 shows facial description measurement AR02_Degree of Facial Protuberance;
 5 Fig. 3A shows facial description measurement AR03_Jowl Protuberance Proportion;
 Fig. 3B shows facial description measurement AR03_Jowl Roundness Proportion;
 Fig. 3C shows facial description measurement AR03_Jowl-to-Underline Proportion;
 Fig. 4A shows facial description measurement AR04_Forehead Height Angle
 Fig. 4B shows facial description measurement AR04_Full Angle Face;
 10 Fig. 4C shows facial description measurement AR04_Mouth Inflexion Angle;
 Fig. 4D shows facial description measurement AR04_Muzzle Roundness Proportion;
 Fig. 4E shows facial description measurement AR04_Muzzle Size Proportion;
 Fig. 4F shows facial description measurement AR04_Muzzle Slope Angle;
 Fig. 5A shows facial description measurement AR05_Chin Firmness Proportion;
 15 Fig. 5B shows facial description measurement AR05_Chin Fullness Proportion;
 Fig. 5C shows facial description measurement AR05_Chin Length Angle;
 Fig. 5D shows facial description measurement AR05_Chin Thickness Angle;
 Fig. 5E shows facial description measurement AR05_Chin Width-to-Height Proportion;
 Fig. 5F shows facial description measurement AR05_Lip Length Proportion;
 20 Fig. 6A shows facial description measurement AR06_Lip Protuberance Proportion;
 Fig. 6B shows facial description measurement AR06_Mouth Length Proportion;
 Fig. 7A shows facial description measurement AR07_Degree of Nostril Flutedness;
 Fig. 7B shows facial description measurement AR07_Degree of Nostril Roundness;
 Fig. 7C shows facial description measurement AR07_Inner Nostril Convergence
 25 Proportion;
 Fig. 7D shows facial description measurement AR07_Nose Width-to-Height Proportion;
 Fig. 7E shows facial description measurement AR07_Nostril Length Proportion;
 Fig. 7F shows facial description measurement AR07_Nostril Width Proportion;
 Fig. 8 shows facial description measurement AR08_Degree of Lip Inflexion;
 30 Fig. 9A shows facial description measurement AR09_Degree of Ear Flare;
 Fig. 9B shows facial description measurement AR09_Ear Inflexion Proportion;
 Fig. 9C shows facial description measurement AR09_Ear Roundness Proportion;
 Fig. 9D shows facial description measurement AR09_Ear Width-to-Breadth Proportion;

- Fig. 10A shows facial description measurement AR10_Ear Rotation Proportion;
- Fig. 10B shows facial description measurement AR10_Ear Set Angle;
- Fig. 11A shows facial description measurement AR11_Eye Height Proportion;
- Fig. 11B shows facial description measurement AR11_Eye Extrema Intersect Angle;
- 5 Fig. 11C shows facial description measurement AR11_Eye Height-to-Length Proportion;
- Fig. 11D shows facial description measurement AR11_Eye Height Proportion;
- Fig. 11E shows facial description measurement AR11_Eye Orbital Lateral Protuberance Proportion;
- Fig. 11F shows facial description measurement AR11_Eye Protuberance Proportion;
- 10 Fig. 11G shows facial description measurement AR11_Eye Roundness Proportion;
- Fig. 11H shows facial description measurement AR11_Eye Size Proportion;
- Fig. 11J shows facial description measurement AR11_Eye Size Proportion_{Length};
- Fig. 11K shows facial description measurement AR11_Lower Minima Point Proportion Eye;
- 15 Fig. 11L shows facial description measurement AR11_Top Eye Angle;
- Fig. 11M shows facial description measurement AR11_Upper Maxima Point Proportion Eye;
- Fig. 12 shows facial description measurement AR12_Forehead Width Angle;
- Fig. 13A shows facial description measurement AR13_Cheek-to-Zygomatic Height
- 20 Ratio;
- Fig. 13B shows facial description measurement AR13_Zygomatic Ridge Angles;
- Fig. 14 shows various relationships between genes, hormones, behavior, and facial features of an animal;
- Fig. 15 shows a method for determining a predictor of a characteristic of an animal
- 25 according to an embodiment of the present disclosure;
- Fig. 16 shows a method for determining a characteristic of an animal according to another embodiment of the present disclosure;
- Fig. 17 shows a method for determining a maintenance or management strategy for one or more animals according to another embodiment of the present disclosure;
- 30 Fig. 18 shows an exemplary application of an embodiment of the present disclosure in categorizing horses into one of three different equestrian events;
- Fig. 19 shows an exemplary application of an embodiment of the present disclosure in predicting the performance of horses in a particular equestrian event;

Fig. 20 shows an exemplary hierarchical system of the features of the equine facial profile;

Fig. 21 shows an exemplary receiver operating characteristic (ROC) curve;

Fig. 22 shows a system that can be used to implement any of the methods of the present disclosure;

Fig. 23A shows facial descriptor measurement Eye Extreme Intersect Angle, θ ;

Fig. 23B shows facial descriptor measurement Eye Depth Proportion, A/B ;

Fig. 23C shows facial descriptor measurement Eye Height Proportion, A/B ;

Fig. 23D shows facial descriptor measurement Eye Length-to-Height Proportion, $(B+C)/A$;

Fig. 23E shows facial descriptor measurement Lower Eye Angle, θ ;

Fig. 23F shows facial descriptor measurement Upper Eye Angle, θ ;

Fig. 24 shows facial descriptor measurement Mid-Face Width Proportion, $(A+B)/C$;

Fig. 25 shows facial descriptor measurement Upper Eyelid Proportion, $A/(A+B)$;

Fig. 26 shows facial descriptor measurement Palpebral Angle, θ ;

Fig. 27 shows facial descriptor measurement Eye Roundness Proportion, A/B ;

Fig. 28 shows facial descriptor measurement Philtrum Definition Proportion, A/B ;

Fig. 29A shows facial descriptor measurement Upper Lip Thickness Proportion, A/B ;

Fig. 29B shows facial descriptor measurement Lower Lip Thickness Proportion, A/B ;

Fig. 30 shows facial descriptor measurement Philtrum Length Proportion, A/B ; and

Fig. 31 shows a method for determining which animal among a plurality of animals is the best match for a particular human engaged in a particular task, according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0018] Various methods for using metrics associated with the physical form of an animal or human (including facial measurements) to predict a characteristic including behavior or suitability are described. While a greater number of examples are shown or described with respect to horses, pigs and humans, the methods apply equally to other

mammals and non-mammals. Also, the methods described are used for the grouping, pairing or matching of mammals and non-mammals.

5 [0019] Methods for analyzing equine facial characteristics vary across the horse industry, and most are cherished as highly guarded trade secrets typically only passed down from aging trainers to their selected successors. To date there have been no formal scientific studies carried out on this topic, and only one published text exists which delineates one of these behavioral evaluation methods, namely "Getting in TTouch: Understand and Influence Your Horse's Personality" by Linda Tellington-Jones (North Pomfret: Trafalgar Square Publishing, 1995). As a result, this valuable
10 but purely non-quantitative method remains obscure, highly subjective, and inaccessible to many individuals in the equestrian industry.

[0020] Within the equestrian industry there are many different styles of riding recognized as distinct riding disciplines. The riding discipline that a horse is trained for is the earliest and arguably the most important training decision of a horse's competitive
15 career. Disciplines differ widely in the conformational characteristics that they favor and the physical demands that they place on the equine athlete. However, just as in human athletes, horses must also be cognitively well suited to the varying mentalities required within differing equestrian sports to succeed at the top levels of competition.

[0021] Due to the relationship in horses between facial features and temperament, in
20 the experiments patterns of facial features were discerned between horses that excel in cognitive distinct riding disciplines. The embodiments include an effective computer model of the equine face quantitatively reflecting this pattern, allowing the riding discipline of a horse to be predicted computationally with a high degree of accuracy. Similarly, models derived from computationally determined facial measurements can be
25 used to predict a horse's performance (e.g., win percentile) within a given riding discipline based on its relative cognitive suitability to that training style.

[0022] Moreover, the need for a computational system for analyzing facial characteristics to determine behavior and performance traits affected by the innate nature of an animal extends well beyond equine applications. For example, in addition
30 to being companions, humans use dogs in many specialized ways such as police dogs, bomb-sniffing dogs, seeing-eye/service dogs, herding dogs, hunting dogs, cadaver dogs, therapeutic dogs, etc. Each of these specialized uses requires significant training. Like horses, dogs must be cognitively suited to the rigors of a particular specialization

and it is imperative that this be determined as soon as possible due to the significant investment required for training. Dogs with behavioral traits making them suitable for particular specializations should have corresponding discernible facial features, much like the Russian foxes discussed above. An effective model of the canine face quantitatively reflects this pattern, enabling a highly-accurate, computational prediction of the suitability of a dog for a particular specialization.

[0023] Similar needs also exist with respect to animals raised to produce food or other materials for human consumption. For example, there is extensive debate in the swine production industry over the use of gestation crates versus gestation pens. Gestation crates are individual enclosures that allow the animal only enough room to stand up and lie down. In intensive swine production systems, such crates are the traditional housing option for sows during gestation. Many farmers contend that these crates enable them to provide sows with individualized care. Nevertheless, concerns from pork consumers over the mental and emotional welfare of sows living in these types of enclosures have placed considerable pressure on the swine production industry to adopt group housing such as gestation pens. The European Union has mandated that all gestation crates must be phased out of swine production systems by 2015. Although there is no corresponding regulation in the U. S., recently U. S. swine producers have faced significant market pressure from large buyers to begin phasing out gestation crates in favor of gestations pens. One of the industry's largest customers – a well-known fast-food chain – recently called for its suppliers to shift toward gestation pens, and other large customers are likely to enact similar requirements. The ultimate source of this U. S. market pressure is consumer concerns about swine welfare.

[0024] While the switch from crates to pens will provide sows with significant physical and emotional benefits, it is not without costs and risks. As a species, pigs are extremely aggressive animals that fight to establish and maintain social hierarchies. As farmers increasingly house their sows as groups in gestation pens, they will encounter new problems related to fights among these naturally aggressive animals. These fights can cause serious injury – including miscarriage – or even death to the sows involved, which is extremely undesirable to swine farmers.

[0025] To avoid such outcomes, what is needed is a method that reliably predicts aggression-related personality characteristics of individual sows and to what extent certain individuals will cohabitate in a gestation pens without harming each other. As

discussed above with reference to horses, a solution to this problem is to use swine facial features to predict aspects of swine personality that correlate with aggression. Once these are known, an individual's aggression-related personality traits can be used to predict the outcome of that individual interacting socially with another individual.

5 These predicted pair-wise outcomes can be used to predict the level or incidence of aggression among a larger group cohabitating in a gestation pen. By doing so, one can allocate groups of sows to individual gestation pens based on minimizing risk of aggression-related injuries to the individuals.

10 [0026] A reliable method to predict aggression-related personality characteristics of individual sows also would allow hog farmers to breed less aggressive animals through their selection of replacement gilts, thereby reversing the trend of increasingly aggressive and unmanageable hogs created through excessive breeding for weight gain. Such a method also may allow farmers to implement intelligent and humane animal management strategies. For example, sows predicted to be excessively aggressive can
15 be placed in gestation crates while the rest of the population can be placed in more open gestation pens.

[0027] Similarly, there is a need to reduce the incidence of "mash deaths" among pig litters. Such deaths are among the leading cause of litter losses in lactation-age piglets (0-3 weeks). They occur when a piglet is unable to move out of the way of its mother as
20 she lies down, and becomes asphyxiated under her greater body weight. Evidence suggests that mash deaths are much more common in pigs raised in large-scale production systems compared to farm-raised pigs, due in part to the confined living conditions and restricted fields of vision that farrowing crates place on sows as they nurse their litters.

25 [0028] Nevertheless, a sow's insufficient reactivity also contributes to the greater incidence of mash deaths in large-scale production systems. As wild animals, sows instinctively rose to their feet quickly whenever they heard distress cries or felt a piglet struggling beneath them. Domesticated sows appear to have lost this protective mothering reflex. Many experts believe that this loss of mothering instinct is part of
30 the degradation of behavioral traits among high-performance pig lines due to heavy over-breeding for traits such as lean weight gain and weaning weights. If mash deaths are due to a loss of genetic potential for mothering, then the associated endocrine changes will also produce observable and quantifiable changes to facial morphology.

[0029] In such case, the anatomical structures of a sow's face are used to develop a computational model for predicting the expected number of mash deaths that the sow would incur per litter. The predicted behavioral outcomes are used to determine various management and/or maintenance strategies for high-risk sows, including increased supervision, larger pens, moving piglets off to reduce litter size, etc. Farmers could also use this model to select young female pigs ("gilts") as replacements for their maintenance rotation by taking into consideration which ones would make the most productive mothers. This would allow them to avoid the monetary loss of feeding a gilt to farrowing age only to have her prove unsuitable as a mother. It would also allow farmers to improve the mothering ability of their herd over time by selective breeding.

[0030] There exists a similar need to identify the existence of mothering-related behavioral traits in sheep. Many of the births by ewes are twins. However, certain ewes will not accept the second-born twin under any circumstances. In such cases, the anatomical structures of an ewe's face is used to develop a computational model to predict that individual's behavioral traits associated with mothering capacity, including willingness to accept all offspring. The predicted behavioral traits are used to determine various management solutions and/or maintenance strategies including identifying ewes with higher rejection rate potentials. These animals would benefit from being brought into confined birthing pens prior to parturition to allow for a more efficient imprinting process than would occur in open range-management situations. These computational models also could be used to predict ewes with highest capacities for accepting lambs; these ewes would then become candidates for receiving grafted lambs who could not be imprinted onto their original mother. These results benefit both animals and farmers.

[0031] Similar needs exist for identifying traits such as behavioral traits of animals used for purposes of recreation, training, work, etc. For example, there has been much concern about the welfare of horses and cattle used in rodeos, in particular the ones that buck aggressively while attempting to throw off a rider. While many of these animals are naturally aggressive, a certain amount of this behavior is due to the use of devices such as straps, electric prods, etc. that increase aggression but that many consider to be inhumane. Accordingly, it would be beneficial to use a computational model based on the facial structures of a horse or bull to measure or estimate a prospective rodeo animal's natural level of aggressive behavior. By selecting only the animals whose

innate characteristics make them most suitable, rodeos could avoid the need for these controversial devices.

5 [0032] Consequently, one of the objects of the disclosure is to revolutionize, with the use of modern imaging and computing technology, the processes of ancient equine behavioral evaluation systems. Another object of the disclosure is to bring objectivity to an animal facial analysis process by utilizing mathematical techniques to quantify the relevant physiological facial features of animals such as horses, donkeys, cattle, oxen, llamas, sheep, goats, dogs, camels, geese, chickens, turkeys, cats, ferrets, and pigs. Another object is establish a set of measurements that provides a quantitative model for a type of animal that is effective for determining a characteristic of a particular animal of that type, such as the most suitable riding discipline or expected performance within a particular riding discipline for a horse. Another object is to provide a computational method for determining and evaluating a characteristic of a particular horse based on the model of the equine face. Yet another object is to provide a user-friendly system that embodies this computational method and is based on readily-available digital computing and imaging technology. Moreover, another object is to improve the efficacy of animal management and training by providing a computationally-efficient, accurate, and objective technique for predicting an animal's innate personality characteristics that affect the results of activities in which the animal may participate, such as a race or event.

20 [0033] The biological mechanism relied upon in the disclosed embodiments was first proposed in the ground-breaking 1999 Russian study entitled "Early Canid Domestication: The Fox Farm Experiment." Using an extensive breeding program of wild silver foxes, this study showed that selective breeding can be used to alter the innate personality traits or characteristics of a line of domesticated animals. More particularly, this study demonstrated that endocrine or hormone changes cause both the personality trait changes and a predictable suite of morphological changes, most predominantly in the structures of the face.

25 [0034] As illustrated graphically in Fig. 14, the innate personality of an animal originates in its genetic composition. Genes dictate the basal levels of neurologically active hormones that control the behavior of an animal, such serotonin which inhibits aggression. Genes also dictate the timing of the release of these hormones, such as corticosteroids (stress response) that control the windows of postnatal cognitive and

30

social development in young animals. The cognitive framework of an animal is determined from a combination of these innate personality traits provided by this genetically controlled endocrine makeup – the so-called “nature effect” – and the stimuli and experiences that the animal was subject to during development – the so-called “nurture effect.” When viewed in the context of the animal’s current environment, this cognitive framework dictates its behavioral performance, which may be defined in such terms as cognitive suitability to a specific task, success in performing a specific task, likelihood of displaying a specific type or pattern of behavioral responses, or, when compared against the personality types of its conspecifics, performance of an individual in group situations.

[0035] As mentioned above, variation in the basal levels of neurologically active hormones and their release windows during development account not only for differences in innate personality among animals of the same species, but also for variability in morphology, particularly of the face. This direct correlation between the facial structure and endocrine composition of an animal subsequently allows for quantifiable features of an animal’s face to be correlated with and used as a proxy for predicting variability in the innate behavior of individual animals as a function of their neurochemical makeup. Variations in facial structure may also be used to predict the behavior and performance of an animal as a result of the variations in the degree of functionality that they allow, in terms such as field of vision, auditory acquisition, oxygen intake, feed intake, etc.

[0036] Various facial recognition and image matching techniques will mathematically model the equine face and allow the prediction of behavior and performance. While these embodiments are effective, the processes and techniques of facial recognition and image matching are generally computationally intensive. Therefore, trigonometric modeling is used by some embodiments. Combinations of facial/shape recognition, image matching and trigonometric modeling may be used to predict behavior and performance.

[0037] For example, equine facial features may be quantified based on thirteen independent anatomical regions. Within each region an individual horse can possess one of a plurality of discrete facial classification. The distinctions between these classifications, however, vary by anatomical region. Classifications in less structurally diverse regions can be described by a single structural feature, which can in turn be

modeled with a single continuous measure. Classifications in anatomical regions with high structural complexity, however, show hierarchical relationships dependent on multiple structural features that must be modeled with multiple measured variables to distinguish between classifications. The first step in developing a mathematical model of the equine face was to identify the anatomical regions that show hierarchical relationships and determine the individual structural features that distinguish between classifications in these more complex systems. Fig. 17 shows an exemplary hierarchical system of equine facial profile features.

[0038] Based upon the identified continuous traits and hierarchical system, the identified structural features of relevance can be described using length measure and angles. Accordingly, a trigonometric model can be used to accurately characterize the equine face in lieu of more computationally expensive facial recognition and image matching techniques. Figs. 1 through 13 illustrate the trigonometric model for each of the thirteen independent anatomical regions, denoted AR01 through AR13, respectively. Certain anatomical regions comprise multiple facial descriptor measurements. For example, AR01 (Facial Profile) comprises ten different facial descriptor measurements, denoted AR01_Degree of Facial Inflexion, AR01_Degree of Nose Rounding, AR01_Face Thickness Proportion, AR01_Forehead Slope Proportion, AR01_Forehead Height Proportion, AR01_Forehead Length Proportion, AR01_Nose Length Proportion, AR01_Nose Roundness Proportion, AR01_Nostril Position Proportion, and AR01_Degree of Eye Orbital Protrusion, as illustrated in Figs. 1A through 1K, respectively. In total, the thirteen anatomical regions AR01 through AR13 comprise fifty-six (56) facial descriptor measurements as illustrated in Figs. 1 through 13. The corresponding mathematical descriptions for each of these measurements are provided below.

Descriptor Name: Degree of Nose Rounding
AR01_FacialProfile

Anatomical Region of Face:

Describes the degree to which the boney structures of the nose rounds away from the true line of the face. Partially differentiates between “Roman” and “Moose” noses.

$M_{ac} = \frac{(A_y - C_y)}{(A_x - C_x)}$	<i>finds the slope of line $\overline{AC}$</i>
$N_x = B_x - (A_x - B_x)$	<i>finds the x-coordinate for “imaginary” point N sufficiently far to the left of point B to complete the triangle</i>
$N_y = M_{ac} * (N_x - C_x) + C_y$	<i>finds the y-coordinate of imaginary point N</i>

$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}, \quad \overline{BN} = \sqrt{(B_x - N_x)^2 + (B_y - N_y)^2},$ $\overline{CN} = \sqrt{(C_x - N_x)^2 + (C_y - N_y)^2}, \quad \overline{BC} = \sqrt{(B_x - C_x)^2 + (B_y - C_y)^2}$ <i>finds distance values for all sides of triangle</i>	
$\theta = \cos^{-1} \left(\frac{\overline{BN}^2 - \overline{BC}^2 - \overline{CN}^2}{-2 * \overline{BC} * \overline{CN}} \right)$ <i>finds the angle for $\angle BCN$, denoted here as θ</i>	
$\overline{BL} = \sin(\theta) * \overline{BC}$ <i>finds the height of triangle $\triangle CBN$ (perpendicular displacement of Upper Nose Point from Upper Profile of Face)</i>	
$M_{bi} = -(M_{ac})^{-1}$ <i>finds the slope of the slope perpendicular to the line of the upper face</i>	
$L_x = \frac{(M_{bi} * B_x - M_{ac} * A_x + A_y - B_y)}{(M_{bi} - M_{ac})}$ <i>finds the x-coordinate of the intersection point between the line of the upper face and its perpendicular bisector inclusive of point B</i>	
$\sigma_* = \left(\frac{L_x - B_x}{ L_x - B_x } \right)$ <i>finds the constant of nostril position with magnitude 1 indicating direction of position relative to the upper line of the face via sign ($\pm$)</i>	
$DoNR = \sigma_* * \left(\frac{d}{\overline{AB}} \right)$ <i>finds the Degree of Nostril Rounding, here defined as the degree to which the Upper Nostril Point rounds away from the True Line of the Face relative to the overall length of the face</i>	

Descriptor Name: Forehead Length Proportion
AR01_FacialProfile

Anatomical Region of Face:

Describes the length of the horse’s forehead relative to the overall length of the head.

$M_{ubb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$ <i>finds the slope of the True Line of the Head</i>	
$M_p = -(M_{ubb})^{-1}$ <i>finds the slope perpendicular to the True Line of the Head</i>	
$R_x = \frac{(M_{ubb} * U_x - M_p * F_x + F_y - U_y)}{(M_{ubb} - M_p)}, \quad R_y = M_{ubb} * (R_x - U_x) + U_y$ <i>finds the x and y-coordinates of intersect point R</i>	
$Q_x = \frac{(M_p * E_x - M_{ubb} * U_x + U_y - E_y)}{(M_p - M_{ubb})}$ <i>finds the x-coordinate of perpendicular intercept point Q</i>	
$Q_y = M_{ubb} * (Q_x - U_x) + U_y$ <i>finds the y-coordinate of perpendicular intercept point Q</i>	
$\overline{UR} = \sqrt{(U_x - R_x)^2 + (U_y - R_y)^2}, \quad \overline{QR} = \sqrt{(R_x - Q_x)^2 + (R_y - Q_y)^2}$ <i>finds the length of lines $\overline{UR}$ and $\overline{QR}$</i>	
$FLP = \frac{\overline{QR}}{\overline{UQ}}$ <i>finds the Forehead Length Proportion, here defined the perpendicular length of the forehead relative to the overall length of the head</i>	

5

Descriptor Name: Face Thickness Proportion
AR01_FacialProfile

Anatomical Region of Face:

Describes the overall depth of the overall depth of the jaw relative to the perpendicular height of the face.
Identifies a horse that is wide from the mid-nose bone to the jaw.

$M_{ubb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$ <i>finds the slope of the True Line of the Head</i>	
---	--

$M_p = -(M_p)^{-1}$	<i>finds the slope perpendicular to the True Line of the Head</i>
$Qn_x = \frac{(M_{ubb} * U_x - M_p * N_x + N_y - U_y)}{(M_{ubb} - M_p)}$, $Qn_y = M_{ubb} * (QN_x - U_x) + U_y$	<i>finds the x and y-coordinates of perpendicular intersect point Q_N</i>
$Qc_x = \frac{(M_{ubb} * U_x - M_p * C_x + C_y - U_y)}{(M_{ubb} - M_p)}$, $Qc_y = M_{ubb} * (Qc_x - U_x) + U_y$	<i>finds the x and y-coordinates of perpendicular intersect point Q_C</i>
$\overline{NQn} = \sqrt{(N_x - Qn_x)^2 + (N_y - Qn_y)^2}$, $\overline{CQc} = \sqrt{(C_x - Qc_x)^2 + (C_y - Qc_y)^2}$, $FTP = \frac{CQc}{NQn}$	<i>finds the Face Thickness Proportion, here defined as the ratio between perpendicular height of the face and the perpendicular thickness of the jaw</i>

Descriptor Name: Nostril Position Proportion
AR01_FacialProfile

Anatomical Region of Face:

Describes the angle at which the nose is set onto the face. Partially differentiates between a Roman Nose and Roman Head. Partially identifies a “Moose” nose.

$M_{ac} = \frac{(A_y - C_y)}{(A_x - C_x)}$	<i>finds the slope of line</i>
$N_x = B_x - (A_x - B_x)$	<i>finds the x-coordinate for “imaginary” point N sufficiently far to the left of point B to complete the triangle</i>
$N_y = M_{ac} * (N_x - C_x) + C_y$	<i>finds the y-coordinate of imaginary point N</i>
$\overline{BN} = \sqrt{(B_x - N_x)^2 + (B_y - N_y)^2}$, $\overline{CN} = \sqrt{(C_x - N_x)^2 + (C_y - N_y)^2}$, $\overline{BC} = \sqrt{(B_x - C_x)^2 + (B_y - C_y)^2}$	<i>finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{BN}^2 - \overline{BC}^2 - \overline{CN}^2}{-2 * \overline{BC} * \overline{CN}} \right)$	<i>finds the angle for $\angle BCN$, denoted here as θ</i>
$\overline{BL} = \sin(\theta) * \overline{BC}$	<i>finds the height of triangle $\triangle CBN$, defined here as the distance of displacement of the nose from the line of the upper face</i>
$M_{bl} = -(M_{ac})^{-1}$	<i>finds the slope of the slope perpendicular to the line of the upper face</i>
$L_x = \frac{(M_{bl} * B_x - M_{ac} * A_x + A_y - B_y)}{(M_{bl} - M_{ac})}$	<i>finds the x-coordinate of the intersection point between the line of the upper face and its perpendicular bisector inclusive of point B</i>
$\sigma_* = \left(\frac{L_x - B_x}{ L_x - B_x } \right)$	<i>finds the constant of nostril position with magnitude 1 indicating direction of position relative to the upper line of the face via sign ($\pm$)</i>
$NPP = \sigma_* * \left(\frac{\overline{BL}}{\overline{AB}} \right)$	<i>finds the Nostril Position Proportion, here defined as the degree to which the position of the nose varies from the upper line of the face relative to the overall size of the face.</i>

5

Descriptor Name: Forehead Slope Proportion

Anatomical Region of Face: AR01_FacialProfile

Describes the slope of the forehead moving into the poll relative to the **True Line of the Head**.

$M_{abb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$	<i>finds the slope of line $\overline{Ubb}$</i>
$M_p = -(M_{abb})^{-1}$	<i>finds the slopes of lines $\overline{EQ}$ and $\overline{FR}$ perpendicular to line $\overline{Ubb}$</i>

$Q_x = \frac{(M_p * E_x - M_{abb} * U_x + U_y - E_y)}{(M_p - M_{abb})}$	finds the x-coordinate of perpendicular intercept point Q
$Q_y = M_{abb} * (Q_x - U_x) + U_y$	finds the y-coordinate of perpendicular intercept point Q
$R_x = \frac{(M_p * F_x - M_{abb} * U_x + U_y - F_y)}{(M_p - M_{abb})}$	finds the x-coordinate of perpendicular intercept point R
$R_y = M_{abb} * (R_x - U_x) + U_y$	finds the y-coordinate of perpendicular intercept point R
$\overline{EQ} = \sqrt{(E_x - Q_x)^2 + (E_y - Q_y)^2}, \quad \overline{FR} = \sqrt{(F_x - R_x)^2 + (F_y - R_y)^2}$	finds the legths of lines $\overline{EQ}$ and $\overline{FR}$
$FSP = \frac{\overline{FR}}{\overline{EQ}}$	finds the Forehead Slop Proportion , here defined as the ratio of perpendicular forehead height from the True Line of the Head at the roastal and caudal-most points of the forehead

Descriptor Name: Forehead Height Proportion**Anatomical Region of Face:**AR01_FacialProfileDescribes the perpendicular height of the forehead above the **True Line of the Face**.

$M_{AB} = \frac{(B_y - A_y)}{(B_x - A_x)}$	finds the slope of line $\overline{AB}$
$N_x = A_x + (A_x - B_x)$	finds the x-coordinate for "imaginary" point N sufficiently far to the right of point A to complete the triangle
$N_y = M_{AB} * (N_x - A_x) + A_y$	finds the y-coordinate of imaginary point N
$\overline{BN} = \sqrt{(B_x - N_x)^2 + (B_y - N_y)^2}, \quad \overline{EN} = \sqrt{(E_x - N_x)^2 + (E_y - N_y)^2},$ $\overline{BE} = \sqrt{(B_x - E_x)^2 + (B_y - E_y)^2}$	finds distance values for all sides of triangle
$\theta = \cos^{-1} \left(\frac{\overline{BE}^2 - \overline{BN}^2 - \overline{EN}^2}{-2 * \overline{BN} * \overline{EN}} \right)$	finds the angle for $\angle BNE$, denoted here as θ
$\overline{DL} = \sin(\theta) * \overline{EN}$	finds the height of triangle $\triangle CDN$ (perpendicular displacement of Forehead from True Line of Face)
$M_{EL} = -(M_{AB})^{-1}$	finds the slope of line $\overline{EL}$
$L_x = \frac{(M_{EL} * E_x - M_{AB} * A_x + A_y - E_y)}{(M_{EL} - M_{AB})}$	finds the x-coordinate of the perpendicular intersection point L
$\sigma_* = \left(\frac{L_x - E_x}{ L_x - E_x } \right)$	finds the constant of forehead position with magnitude 1 indicating direction of position relative the true line of the face via sign ($\pm$)
$FHP = \sigma_* * \left(\frac{\overline{DL}}{\overline{AB}} \right)$	finds the Forehead Height Proportion , here defined as the perpendicular displacement of the Upper Eye Orbital Point of the forehead from the True Line of the Face , relative to the length of the face.

5

Descriptor Name: Degree of Facial Inflexion**Anatomical Region of Face:** AR01_FacialProfileDescribes the degree of structural concavity/convexity of the **True Line of the Face**. Differentiates between a concave "dished", convex "roman", or straight bone structure.

$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}, \quad \overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}, \quad \overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$	finds distance values for all sides of triangle
--	---

$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$	<i>finds the angle for $\angle BAC$, denoted here as θ</i>
	<i>finds height of triangle $\triangle ABC$, the distance of facial inflexion</i>
$d = \sin(\theta) * \overline{AC}$	
$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$	<i>finds slope of line $\overline{AB}$</i>
$Q_x = \left(\frac{C_y - A_y}{M_{ab}} \right) + A_x$	<i>finds x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C</i>
$\sigma = Q_x - C_x$	<i>finds a value for which σ is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face</i>
$\sigma_* = \frac{\sigma}{ \sigma }$	<i>finds σ_* here defined of the Constant of Concavity with magnitude 1 indicating direction of inflexion via sign ($\pm$)</i>
$DoFI = \sigma_* * \left(\frac{d}{\overline{AB}} \right)$	<i>finds Degree of Facial Inflexion, here defined as the degree of perpendicular deviation of the Upper Profile of the skull from the True Line of the Face relative to overall length of face.</i>

Descriptor Name: Nose Roundness Proportion **Anatomical Region of Face:** AR01_FacialProfile

Describes the degree of roundness of the nasal bone as it results from the accretion of bone above the **True Line of the Nose**. Identifies convex “Moose” and “Roman” profiles.

$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}, \quad \overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2},$ $\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$	<i>finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$	<i>finds the angle for $\angle BAC$, denoted here as θ</i>
$d = \sin(\theta) * \overline{AC}$	<i>finds the height of triangle $\triangle ABC$ (distance of nostril rounding)</i>
$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$	<i>finds the slope of line $\overline{AB}$</i>
$Q_x = \left(\frac{C_y - A_y}{M_{ab}} \right) + A_x$	<i>finds the x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C</i>
$\sigma = Q_x - C_x$	<i>finds a value for which σ is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face</i>
$\sigma_* = \frac{\sigma}{ \sigma }$	<i>finds σ_* here defined of the Constant of Concavity with magnitude 1 indicating direction of inflexion/convection via sign ($\pm$)</i>
$NRP = \sigma_* * \left(\frac{d}{\overline{AB}} \right)$	<i>finds the Nose Roundness Proportion, here defined as the degree of perpendicular deviation of the Upper Profile of the skull above the True Line of the Nose relative to the length of the nose.</i>

Descriptor Name: Nose Length Proportion **Anatomical Region of Face:** AR01_FacialProfile

Describes the perpendicular length of a horse’s nose relative to the overall length of the face.

$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$	<i>finds the slope of the True Line of the Face</i>
$M_p = -(M_{ab})^{-1}$	<i>finds the slope perpendicular to the True Line of the Face</i>
$Q_x = \frac{(M_p * C_x - M_{ab} * A_x + A_y - C_y)}{(M_p - M_{ab})}$	<i>finds the x-coordinate of perpendicular intercept point Q</i>
$Q_y = M_{ab} * (Q_x - A_x) + A_y$	<i>finds the y-coordinate of perpendicular intercept point Q</i>
$\overline{AB} = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}, \overline{BQ} = \sqrt{(B_x - Q_x)^2 + (B_y - Q_y)^2}$ <i>finds the length of lines $\overline{AB}$ and $\overline{BQ}$</i>	
$NLP = \frac{\overline{BQ}}{\overline{AB}}$	<i>finds the Nose Length Proportion, here defined the perpendicular length of the nose relative to the overall length of the face</i>

Descriptor Name: Degree of Facial Protuberance **Anatomical Region of Face:** AR02_Protruberances

5 Describes the degree of prominence/enlargement of the sinus cavities above the eyes (“Jibbah”) as they protrude from the underlying boney structure of the **True Line of the Face**.

$M_{Bc} = \frac{(B_y - C_y)}{(B_x - C_x)}$	<i>finds the slope of line $\overline{BC}$</i>
$N_x = C_x + (A_x - B_x)$	<i>finds the x-coordinate for “imaginary” point N sufficiently far to the right of point D to complete the triangle</i>
$N_y = M_{Bc} * (N_x - C_x) + C_y$	<i>finds the y-coordinate of imaginary point N</i>
$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}, \overline{CN} = \sqrt{(C_x - N_x)^2 + (C_y - N_y)^2},$ $\overline{DN} = \sqrt{(D_x - N_x)^2 + (D_y - N_y)^2}, \overline{CD} = \sqrt{(D_x - C_x)^2 + (D_y - C_y)^2},$ $\theta = \cos^{-1} \left(\frac{\overline{CD}^2 - \overline{CN}^2 - \overline{ND}^2}{-2 * CN * ND} \right)$ <i>finds distance values for all sides of triangle</i>	
<i>finds the angle for $\angle CND$, denoted here as θ</i>	
$\overline{DL} = \sin(\theta) * \overline{DN}$	<i>finds the height of triangle $\triangle CDN$ (perpendicular displacement of Sinus from True Line of the Nose)</i>
$DoFP = \frac{d}{\overline{AB}}$	<i>finds the Degree of Facial Protuberance, here defined as the perpendicular displacement of the Sinus Protuberance Point from the True Line of the Nose, relative to the length of the upper portion of the face.</i>

Descriptor Name: Jowl-to-Underline Proportion **Anatomical Region of Face:** AR03_JowlSize

Describes the magnitude of the lateral length of the jowl relative to the length of the of the jaw bone. Partially differentiates between a large and small jowl.

$\overline{MN} = \sqrt{(M_x - B_x)^2 + (M_y - N_y)^2}$	<i>Finds the length of the underline of the jaw</i>
--	---

$\overline{NO} = \sqrt{(N_x - O_x)^2 + (N_y - O_y)^2}$	Finds the lateral length across the jowl
$JtUP = \overline{NO} / \overline{MN}$	Finds Jowl-to-Underline Proportion , here defined as the magnitude of the lateral length of the jowl relative to the length of jaw bone

Descriptor Name: Degree of Eye Orbital Protrusion **Anatomical Region of Face:** AR01_Facial Profile

Describes the longitudinal placement of the eye orbital on the top of the skull as it is positioned in correlation with the sinus cavities. Partially identifies protruding sinus cavities.

$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$	finds the slope of line $\overline{AB}$
$m_p = -(m_{ab})^{-1}$	Finds the slope perpendicular to the line $\overline{AB}$
$Q_x = \frac{m_{ab} * A_x - m_p * C_x + C_y - A_y}{m_{ab} \quad m_p}$	finds x-coordinate of the intersection point between line $\overline{AB}$ and its perpendicular bisector inclusive of point C
$Q_y = m_{ab}(Q_x - A_x) + A_y$	finds the y-coordinate of intersect point "Q"
$P_x = \frac{m_{ab} * A_x - m_p * D_x + D_y - A_y}{m_{ab} \quad m_p}$	finds the x-coordinate of intersection point between line $\overline{AB}$ and perpendicular bisector inclusive of point D
$P_y = m_{ab}(P_x - A_x) + A_y$	finds y-coordinate of intersect point "P"
$\overline{CQ} = \sqrt{(C_x - Q_x)^2 + (C_y - Q_y)^2}$	finds the distance of displacement of the base point of the eye orbital from line $\overline{AB}$
$\overline{DP} = \sqrt{(D_x - P_x)^2 + (D_y - P_y)^2}$	finds the distance of displacement of the tallest point of the eye orbital from line $\overline{AB}$
$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$	finds the overall length of the face
$DcEOP = \frac{DP - CQ}{\overline{AB}}$	finds Degree of Eye Orbital Protrusion , defined here as distance of protrusion of the maxima point of the eye orbital its base on the skull relative to overall length of face

5 **Descriptor Name:** Jowl Protuberance Proportion **Anatomical Region of Face:** AR03_JowlSize

Describes the degree to which the minima point of the jowl protrudes from the underline of the jaw. Identifies shallow jowls. Partially differentiates between large and small jowls.

$m_{mn} = \frac{M_y - N_y}{M_x - N_x}$	Finds the slope of the underline of the jaw
$Q_x = N_x + 2(N_x - M_x)$	Finds x-coordinate for imaginary point "q", sufficiently far to the right of point N to complete a triangle on the line fit to the underline of the jaw
$Q_y = m_{mn}(Q_x - M_x) + M_y$	Finds the y-coordinate corresponding to imaginary point "q"
$\overline{NP} = \sqrt{(N_x - P_x)^2 + (N_y - P_y)^2}, \quad \overline{PQ} = \sqrt{(P_x - Q_x)^2 + (P_y - Q_y)^2},$ $\overline{NQ} = \sqrt{(N_x - Q_x)^2 + (N_y - Q_y)^2}$	Finds distance values for all sides of triangle
$\theta = \cos^{-1} \left(\frac{\overline{PQ}^2 - \overline{NQ}^2 - \overline{NP}^2}{-2 * \overline{NQ} * \overline{NP}} \right)$	Finds the angle measure $\angle NQP$, denoted here as θ
$d = \sin \theta * \overline{NP}$	Finds the perpendicular distance from the line fit to the underline of the jaw to the minima point of the jowl
$\overline{MN} = \sqrt{(M_x - N_x)^2 + (M_y - N_y)^2}$	Finds the length of the underline of the jaw

$JPP = d / \overline{MN}$	<i>Finds the Jowl Protuberance Proportion, which here describes the length of protuberance of the jowl from the line of the jowl relative to the full length of the underline of the jaw</i>
---------------------------	---

Descriptor Name: Jowl Roundness Proportion**Anatomical Region of Face:** AR03_JowlSize

5

Describes degree of jowl rounding along the underline of the jowl as described by the ratio of the perpendicular distance of the **Mid Jowl Point** from the **True Line of the Jowl** and the overall length of the jowl.

$\overline{MN} = \sqrt{(M_x - N_x)^2 + (M_y - N_y)^2}$	$\overline{MK} = \sqrt{(M_x - K_x)^2 + (M_y - K_y)^2}$
$\overline{NK} = \sqrt{(N_x - K_x)^2 + (N_y - K_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{NK}^2 - \overline{MN}^2 - \overline{MK}^2}{-2 * \overline{MN} * \overline{MK}} \right)$	<i>finds the angle for $\angle NMK$, denoted here as θ</i>
$d = \sin(\theta) * \overline{MK}$	<i>finds the perpendicular depth of the jowl</i>
$JRP = \frac{d}{\overline{MN}}$	<i>finds the Jowl Roundness Proportion, here defined as the perpendicular distance of rounding of the underline of the jowl from the True Line of the Jowl relative to the overall length of the jowl</i>

Descriptor Name: Muzzle Size Proportion**Anatomical Region of Face:** AR04_MuzzleShape

Describes the overall size of the muzzle in terms of perpendicular height relative to overall length of the face

$M_{ubh} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$	<i>finds the slope of the True Line of the Head</i>
$M_{pu} = -(M_{ubh})^{-1}$	<i>finds the slope perpendicular to the True Line of the Head</i>
$R_x = \frac{(M_{ubh} * H_x - M_{pu} * F_x + F_y - H_y)}{(M_{ubh} - M_{pu})}$	$R_y = M_{ubh} * (R_x - U_x) + U_y$ <i>finds the x and y-coordinates of intersect point R</i>
$M_{gh} = \frac{(G_y - H_y)}{(G_x - H_x)}$	<i>finds the slope of the True Line of the Chin</i>
$M_{pb} = -(M_{gh})^{-1}$	<i>finds the slope perpendicular to the True Line of the Chin</i>
$Q_x = \frac{(M_{gh} * G_x - M_{pb} * B_x + B_y - G_y)}{(M_{gh} - M_{pb})}$	$Q_y = M_{gh} * (Q_x - G_x) + G_y$ <i>finds the x and y-coordinates of intersect point Q</i>
$\overline{BQ} = \sqrt{(B_x - Q_x)^2 + (B_y - Q_y)^2}, \overline{UR} = \sqrt{(U_x - R_x)^2 + (U_y - R_y)^2}$ <i>finds the distance values for lines $\overline{BQ}$ and $\overline{UR}$</i>	
$MSP = \frac{\overline{BQ}}{\overline{UR}}$	<i>finds the Muzzle Size Proportion, here defined as the perpendicular height of the muzzle relative to the overall length of the face</i>

Descriptor Name: Mouth Inflexion Angle**Anatomical Region of Face:** AR04_MuzzleShape

10

Describes the degree of inflexion/angulation taken by the lower portion of the muzzle as it contracts inwards from the **Distal Muzzle Point** to the **Distal Point of the Mouth**.

$$\overline{BS} = \sqrt{(B_x - S_x)^2 + (B_y - S_y)^2}, \overline{BT} = \sqrt{(T_x - B_x)^2 + (T_y - B_y)^2},$$

$\overline{ST} = \sqrt{(T_x - S_x)^2 + (T_y - S_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{DT}^2 - \overline{DS}^2 - \overline{ST}^2}{-2 * \overline{DS} * \overline{ST}} \right)$	<i>Finds angle value for Muzzle Slope Angle ($\angle ABC$), denoted here as θ</i>

Descriptor Name: Full Angle Face**Anatomical Region of Face:** AR04_MuzzleShape

Describes both the magnitude and rate of change of the thickness of the face. Gives an indication of the relationship between the jowl region of the face and the muzzle. Identifies a “teacup muzzle”.

$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$	<i>Finds the slope of the True Line of Face</i>
$m_{cd} = \frac{D_y - C_y}{D_x - C_x}$	<i>Finds the slope of line fitted to underline of jaw</i>
$Q_x = \frac{m_{ab} * A_x - m_{cd} * C_x + C_y - A_y}{m_{ab} - m_{cd}}$	<i>Finds the x-coordinate of the point “Q” where the rue line of the face and the line fitted to the underline of the jaw intersect</i>
$Q_y = m_{ab}(Q_x - A_x) + A_y$	<i>Finds the y-coordinate for intersect point “Q”</i>
$AC = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$, $AQ = \sqrt{(A_x - Q_x)^2 + (A_y - Q_y)^2}$, $CQ = \sqrt{(C_x - Q_x)^2 + (C_y - Q_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$FAF = \theta = \cos^{-1} \left(\frac{AC^2 - AQ^2 - CQ^2}{-2 * AQ * CQ} \right)$	<i>Finds the angle measure for Full Angle Face ($\angle AQC$), here defined as the intersect angle of the upper and lower lines of the face (True Line of the Face & True Line of the Jaw)</i>

5 **Descriptor Name:** Muzzle Roundness Proportion **Anatomical Region of Face:** AR04_MuzzleShape

Describes the degree of inflexion/angulation taken by the lower portion of the muzzle as it contracts inwards from the **Distal Muzzle Point** to the **Distal Point of the Mouth**.

$\overline{ST} = \sqrt{(T_x - S_x)^2 + (T_y - S_y)^2}$, $\overline{SU} = \sqrt{(U_x - S_x)^2 + (U_y - S_y)^2}$, $\overline{UT} = \sqrt{(T_x - U_x)^2 + (T_y - U_y)^2}$	<i>finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{UT}^2 - \overline{SU}^2 - \overline{ST}^2}{-2 * \overline{SU} * \overline{ST}} \right)$	<i>finds the angle for $\angle UST$, denoted here as θ</i>
$\bar{d} = \sin(\theta) * EN$	<i>finds the height of triangle ΔSTU</i>
$MRP = \frac{d}{\overline{UT}}$	<i>finds the Muzzle Roundness Proportion, here defined as the perpendicular displacement of the Distal Muzzle Point from the line of the muzzle formed by the Lower Nostril Point and Distal Mouth Point.</i>

Descriptor Name: Forehead Height Angle**Anatomical Region of Face:** AR04_MuzzleShape

Describes the angle of rise of the forehead along the topline of the face from the **True Line of the Head**.

$m_{be} = \frac{B_y - E_y}{B_x - E_x}$	<i>Finds the slope of the True Line of Face</i>
$m_{ubb} = \frac{U_y - bb_y}{U_x - bb_x}$	<i>Finds the slope of line fitted to underline of jaw</i>
$Q_x = \frac{m_{be} * B_x - m_{ubb} * U_x + U_y - B_y}{m_{be} - m_{ubb}}$	<i>Finds the x-coordinate of the point "Q" where the true line of the face and the line fitted to the underline of the jaw intersect</i>
$Q_y = m_{be}(Q_x - B_x) + B_y$	<i>Finds the y-coordinate for intersect point "Q"</i>
$\overline{EQ} = \sqrt{(E_x - Q_x)^2 + (E_y - Q_y)^2}, \quad \overline{Ebb} = \sqrt{(E_x - bb_x)^2 + (E_y - bb_y)^2},$ $\overline{Qbb} = \sqrt{(Q_x - bb_x)^2 + (Q_y - bb_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$FAF = \theta = \cos^{-1} \left(\frac{\overline{Ebb}^2 - \overline{EQ}^2 - \overline{Qbb}^2}{-2 * \overline{EQ} * \overline{Qbb}} \right)$	<i>Finds the angle measure for Forehead Height Angle ($\angle EQB$),</i> <i>here defined as the intersect angle of the topline of the face and the True Line of the Head</i>

Descriptor Name: Muzzle Slope Angle**Anatomical Region of Face:** AR04_MuzzleShape

Describes the degree of slope/angulation taken by the top line of the muzzle and upper lip. Identifies a "moose" nose. Partially differentiates between a round and square muzzle.

$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}, \quad \overline{BS} = \sqrt{(B_x - S_x)^2 + (B_y - S_y)^2},$ $\overline{CS} = \sqrt{(C_x - S_x)^2 + (C_y - S_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{BS}^2 - \overline{BC}^2 - \overline{CS}^2}{-2 * \overline{BC} * \overline{CS}} \right)$	<i>Finds angle value for Muzzle Slope Angle ($\angle ABC$), denoted</i> <i>here as θ</i>

5 **Descriptor Name:** Zygomatic Ridge Angles
AR13_ZygomaticProces

Anatomical Region of Face:

Describes the angle of the **Zygomatic Ridge**, from the point of the **Zygomatic Process Point** to the **Distal Cheek Point**, relative to the upper and lower lines of the face.

$m_{yz} = \frac{Z_y - Y_y}{Z_x - Y_x}$	<i>Finds the slope of the Zygomatic Ridge</i>
$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$	<i>finds the slope of the True Line of the Face</i>
$m_{mn} = \frac{M_y - N_y}{M_x - N_x}$	<i>Finds the slope of the Line of the Jaw</i>
$R_x = \frac{m_{ab} * A_x - m_{yz} * Z_x + Z_y - A_y}{m_{ab} - m_{yz}}$	$R_y = m_{ab}(R_x - A_x) + A_y$ <i>finds the x-coordinate and y-coordinate of intersect point R</i>
$Q_x = \frac{m_{mn} * N_x - m_{yz} * Z_x + Z_y - N_y}{m_{mn} - m_{yz}}$	$Q_y = m_{mn}(Q_x - N_x) + N_y$ <i>finds the x-coordinate and y-coordinate of intersect point Q</i>

$\overline{BR} = \sqrt{(B_x - R_x)^2 + (B_y - R_y)^2} \quad \overline{NQ} = \sqrt{(N_x - Q_x)^2 + (N_y - Q_y)^2}$ $\overline{BY} = \sqrt{(B_x - Y_x)^2 + (B_y - Y_y)^2} \quad \overline{NY} = \sqrt{(N_x - Y_x)^2 + (N_y - Y_y)^2}$ $\overline{RY} = \sqrt{(R_x - Y_x)^2 + (R_y - Y_y)^2} \quad \overline{QY} = \sqrt{(Q_x - Y_x)^2 + (Q_y - Y_y)^2}$ <i>finds the distance values for all legs of the triangles</i>	
$ZRAU = \theta_U = \cos^{-1} \left(\frac{\overline{BY}^2 - \overline{RB}^2 - \overline{RY}^2}{-2 * \overline{RB} * \overline{RY}} \right)$	<i>finds the Zygomatic Ridge Angle_{Upper}, here defined as the angle of the Zygomatic Ridge bone as it relates to the True Line of the Face</i>
$ZRAL = \theta_L = \cos^{-1} \left(\frac{\overline{NY}^2 - \overline{QY}^2 - \overline{QN}^2}{-2 * \overline{QY} * \overline{QN}} \right)$	<i>finds the Zygomatic Ridge Angle_{lower}, here defined as the angle of the Zygomatic Ridge bone as it relates to the Line of the Jaw</i>

Descriptor Name: Top Eye Angle
AR11_EyeShape

Anatomical Region of Face:

5 Describes degree of angulation in the bone structure of the upper portion of the eye orbital. Differentiates between hard and soft eyes. Partially identifies triangularly-shaped eyes.

$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2} \quad \overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$ $\overline{bbcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$ <i>Finds distance values for all sides of triangle</i>	
$\theta = \cos^{-1} \left(\frac{\overline{Abb}^2 - \overline{Acc}^2 - \overline{bbcc}^2}{-2 * \overline{Acc} * \overline{bbcc}} \right)$ θ <i>Finds angle value for Top Eye Angle ($\angle ACB$), denoted here as</i>	

Descriptor Name: Eye Size Proportion_{Length}
AR11_EyeShape

Anatomical Region of Face:

Describes the size of the eye orbital in terms of length relative to the scale of the face as a whole.

$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$	<i>Finds the length of the True Line of the Face</i>
$\overline{Abb} = \sqrt{(A_x - bb_x)^2 + (A_y - bb_y)^2}$	<i>Finds the lateral distance of the eye</i>
$ESP_L = \overline{Abb} / \overline{AB}$	<i>Finds the Eye Size Proportion_{Height} measure, which measures the size of the eye normalized against the conserved distance of the True Line of the Face</i>

10 **Descriptor Name:** Eye Protuberance Proportion
AR11_EyeShape

Anatomical Region of Face:

Describes the overall portion of the eye visible from a frontal view in terms of lateral protrusion distance relative to the overall width of the forehead, which effects the range of a horse's frontal vision when set up into the bridle.

$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$	<i>finds the slope of the True Line of the Forehead</i>
$M_p = -(M_{ab})^{-1}$	<i>finds the slope perpendicular to the True Line of the Forehead</i>
$Q_{lx} = \frac{(M_p * C_x - M_{ab} * A_x + A_y - C_y)}{(M_p - M_{ab})}$	<i>finds the x-coordinate of perpendicular intercept point Q_L</i>
$Q_{ly} = M_{ab} * (Q_{lx} - A_x) + A_y$	<i>finds the y-coordinate of perpendicular intercept point Q_L</i>
$Q_{rx} = \frac{(M_p * D_x - M_{ab} * A_x + A_y - D_y)}{(M_p - M_{ab})}$	<i>finds the x-coordinate of perpendicular intercept point Q_L</i>
$Q_{ry} = M_{ab} * (Q_{rx} - A_x) + A_y$	<i>finds the y-coordinate of perpendicular intercept point Q_L</i>
$\overline{AB} = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}$	<i>finds the overall distance across the forehead</i>
$\overline{AQ_l} = \sqrt{(A_x - Q_{lx})^2 + (A_y - Q_{ly})^2}$	<i>finds the maximal lateral distance of eye protrusion of the left eye</i>
$\overline{BQ_r} = \sqrt{(A_x - Q_{rx})^2 + (A_y - Q_{ry})^2}$	<i>finds the maximal lateral distance of eye protrusion of the right eye</i>
$EFP = \frac{\overline{AQ_l} + \overline{BQ_r}}{2 * \overline{AB}}$	<i>finds the Eye Protuberance Proportion, here defined as the average distance of lateral protrusion of the eye relative to the overall distance across the forehead</i>

Descriptor Name: Eye Height Proportion
AR11_EyeShape

Anatomical Region of Face:

- 5 Describes the perpendicular height of the eye above the midline of the eye relative to the eyes overall length.

$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$	$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$
$\overline{bcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{Abb}^2 - \overline{bcc}^2}{-2 * \overline{Abb} * \overline{bcc}} \right)$	<i>finds the angle for $\angle ABC$, denoted here as θ</i>
$d = \sin(\theta) * \overline{bcc}$	<i>finds the perpendicular height of the eye</i>
$EHP = \frac{d}{\overline{Abb}}$	<i>finds the Eye Height Proportion, here defined as the ratio of the perpendicular height of the eye and the overall length of the eye</i>

Descriptor Name: Eye Size Proportion_{Height}

Anatomical Region of Face: AR11_EyeShape

Describes the size of the eye orbital in terms of length relative to the scale of the face as a whole.

$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$	<i>Finds the length of the True Line of the Face</i>
$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}, \overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2},$ $\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}, \overline{bcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2},$ $\overline{bdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$	<i>Finds distance values for all sides of triangle</i>

$\theta_U = \cos^{-1} \left(\frac{Acc^2 - Abb^2 - bbcc^2}{-2 * Abb * Bcc} \right),$	$d_U = \sin(\theta) * \overline{bbdd}$
<i>finds the perpendicular height of the eye</i>	
$\theta_L = \cos^{-1} \left(\frac{Add^2 - Abb^2 - bdd^2}{-2 * Abb * bdd} \right),$	$d_L = \sin(\theta) * \overline{bbdd}$
<i>finds the perpendicular depth of the eye</i>	
$ESP_H = \frac{d_U + d_L}{AB}$	<i>finds Eye Size Proportion_{Height}, which measures the cumulative perpendicular height of the eye relative to the length of the True Line of the Face</i>

Descriptor Name: Upper Maxima Point Proportion Eye
AR11_EyeShape

Anatomical Region of Face:

- 5 Describes the location of the highest point of the eye orbital relative to the lateral extrema of the eye. Identifies triangular-shaped eyes.

$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$	$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$
$\overline{bcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{Acc^2 - Abb^2 - bbcc^2}{2 * Abb * Bcc} \right)$	<i>Finds the angle measure $\angle ABC$, denoted here as θ</i>
$d = \cos \theta * \overline{bcc}$	<i>Finds the distance between the right extrema point of the eye and the perpendicular intersect point of the upper maxima point of the eye</i>
$UMPP = d / \overline{Abb}$	<i>Finds the Upper Maxima Point Proportion of the Eye, which is here defined as the proportion of the lateral distance across the eye located behind the perpendicular intersect of the upper maxima point of the eye</i>

Descriptor Name: Eye Roundness Proportion
AR11_EyeShape

Anatomical Region of Face:

- 10 Describes the perpendicular height of deviation of the **Upper Media Eye Point** from the **Caudal Line of the Eye** relative to the overall length of the backside of the eye.

$\overline{bcc} = \sqrt{(bb_x - cc_x)^2 + (bb_y - cc_y)^2}$	$\overline{bee} = \sqrt{(bb_x - ee_x)^2 + (bb_y - ee_y)^2}$
$\overline{cee} = \sqrt{(cc_x - ee_x)^2 + (cc_y - ee_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{bee}^2 - \overline{bcc}^2 - \overline{cee}^2}{-2 * \overline{bcc} * \overline{cee}} \right)$	<i>finds the angle for $\angle BCE$, denoted here as θ</i>
$d = \sin(\theta) * \overline{cee}$	<i>finds the perpendicular roundness height of the eye</i>
$ERP = \frac{d}{\overline{bcc}}$	<i>finds the Eye Roundness Proportion, here defined as the perpendicular deviation height of the Upper Media Eye Point relative to the overall length of the Caudal Line of the Eye</i>

Descriptor Name: Lower Minima Point Proportion Eye Shape

Anatomical Region of Face: AR11_Eye

Describes the location of the lowest point of the eye orbital relative to the lateral extrema of the eye. Identifies “almond”-shaped eyes.

$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$	$\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}$
$\overline{bbdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$	<i>Finds the angle measure $\angle ABD$, denoted here as θ</i>
$d = \cos \theta * \overline{bbdd}$	<i>Finds the distance between the right extrema point of the eye and the perpendicular intersect point of the lower minima point of the eye</i>
$UMPP = d / \overline{Abb}$	<i>Finds the Lower Minima Point Proportion of the Eye, which is here defined as the proportion of the lateral distance across the eye located behind the perpendicular intersect of the lower minima point of the eye</i>

5 **Descriptor Name:** Eye Height-to-Length Proportion
AR11_EyeShape

Anatomical Region of Face:

Describes the cumulative perpendicular height of the eye relative to the overall length of the eye.

$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$	$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$
$\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}$	$\overline{bbcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$
$\overline{bbdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta_U = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{Abb}^2 - \overline{bbcc}^2}{-2 * \overline{Abb} * \overline{bbcc}} \right)$	$d_U = \sin(\theta) * \overline{bbdd}$
<i>finds the perpendicular height of the eye</i>	
$\theta_L = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$	$d_L = \sin(\theta) * \overline{bbdd}$
<i>finds the perpendicular depth of the eye</i>	
$EHtLP = \frac{d_U + d_L}{\overline{Abb}}$	<i>finds the Eye Height-to-Length Proportion, here defined as the ratio of the cumulative perpendicular height of to the horizontal length of the eye</i>

10 **Descriptor Name:** Eye Height Proportion
AR11_EyeShape

Anatomical Region of Face:

Describes the perpendicular height of the eye above the midline of the eye relative to the eyes overall length.

$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$, $\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}$, $\overline{bbdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$, <i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$ <i>finds the angle for $\angle ABD$, denoted here as θ</i>

$d = \sin(\theta) * \overline{bbdd}$	<i>finds the perpendicular depth of the eye</i>
$EDP = \frac{d}{\overline{Abb}}$	<i>finds the Eye Depth Proportion, here defined as the ratio of the perpendicular depth of the eye and the overall length of the eye</i>

Descriptor Name: Eye Orbital Lateral Protuberance Proportion

Anatomical Region of Face: AR11_EyeShape

Describes the degree to which the lateral-most point of the boney portion of the eye orbital extends beyond the line of the cheek, which effects the range of a horses caudal and ventral vision when set up into the bridle.

5

$M_{eh} = \frac{(E_y - H_y)}{(E_x - H_x)}$	<i>finds the slope of the Line of the Cheek</i>
$M_p = -(M_{eh})^{-1}$	<i>finds the slope perpendicular to the Line of the Cheek</i>
$Q_x = \frac{(M_p * G_x - M_{eh} * E_x + E_y - G_y)}{(M_p - M_{eh})}$	<i>finds the x-coordinate of perpendicular intercept point Q</i>
$Q_y = M_{eh} * (Q_x - E_x) + E_y$	<i>finds the y-coordinate of perpendicular intercept point Q</i>
$\overline{GQ} = \sqrt{(G_x - Q_x)^2 + (G_y - Q_y)^2}$	<i>finds the distance of eye orbital protrusion</i>
$\overline{EF} = \sqrt{(E_x - F_x)^2 + (E_y - F_y)^2}$	<i>finds the maximal lateral thickness of the cheeks</i>
$EOLPP = \frac{\overline{GQ}}{\overline{EF}}$	<i>finds the Eye Orbital Lateral Protuberance Proportion, here defined as the overall perpendicular distance of eye orbital displacement from the line of the cheek relative to the overall measure of cheek thickness</i>

Descriptor Name: Eye Extrema Intersect Angle

Anatomical Region of Face: AR11_EyeShape

Describes the angle at which the upper and lower extreme points of the eye are set against one another in relation to the **True Line of the Eye**.

$M_{Abb} = \frac{(A_y - bb_y)}{(A_x - bb_x)}$	<i>finds the slope of line $\overline{Abb}$</i>
$M_{ccdd} = \frac{(cc_y - dd_y)}{(cc_x - dd_x)}$	<i>finds the slope of line $\overline{ccdd}$</i>
$Q_x = \frac{(M_{Abb} * A_x - M_{ccdd} * cc_x + cc_y - A_y)}{(M_{Abb} - M_{ccdd})}$	<i>finds the x-coordinate of the intersect point Q</i>
$Q_y = M_{Abb} * (Q_x - A_x) + A_y$	<i>finds the y-coordinate of imaginary point Q</i>
$\overline{AQ} = \sqrt{(Q_x - A_x)^2 + (Q_y - A_y)^2}$	$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$
$Qcc = \sqrt{(cc_x - Q_x)^2 + (cc_y - Q_y)^2}$	<i>finds distance values for all sides of triangle</i>
$EXIA = \theta = \cos^{-1} \left(\frac{Acc^2 - AQ^2 - Qcc^2}{-2 * AQ * Qcc} \right)$	<i>finds the Eye Extrema Intersect Angle, here defined as angle θ</i>

Descriptor Name: Forehead Width Angle**Anatomical Region of Face:** AR12_ForeheadWidth

Describes the degree to which the forehead widens beyond the nares (central line of the skull).

$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$	<i>Finds the slope of the True Line of the Forehead, here defined as the line between the inner extrema points of the eyes</i>
$m_p = -(m_{ab})^{-1}$	<i>Finds the slope perpendicular to the True Line of the Forehead</i>
$R_x = \frac{m_{ab} * A_x - m_p * C_x + C_y - A_y}{m_{ab} - m_p}$	<i>Finds the x-coordinate of the intersection point between the true line of the face and its perpendicular bisector inclusive of point C</i>
$R_y = m_{ab}(R_x - A_x) + A_y$	<i>Finds the y-coordinate of intersect point "R"</i>
$S_x = \frac{m_{ab} * A_x - m_p * D_x + D_y - A_y}{m_{ab} - m_p}$	<i>Finds the x-coordinate of the intersection point between the true line of the forehead and its perpendicular bisector inclusive of point D</i>
$S_y = m_{ab}(S_x - A_x) + A_y$	<i>Finds the y-coordinate of intersect point "S"</i>
$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}, \quad \overline{AR} = \sqrt{(A_x - R_x)^2 + (A_y - R_y)^2},$ $\overline{BD} = \sqrt{(D_x - B_x)^2 + (D_y - B_y)^2}, \quad \overline{BS} = \sqrt{(B_x - S_x)^2 + (B_y - S_y)^2}$	<i>Finds distance values for all sides of triangles</i>
$\theta_R = \sin^{-1}\left(\frac{\overline{AR}}{\overline{AC}}\right)$	<i>Finds the angle measure $\angle ACR$ of forehead protuberance for the left side of the face</i>
$\theta_S = \sin^{-1}\left(\frac{\overline{BS}}{\overline{BD}}\right)$	<i>Finds the angle measure $\angle BDS$ of forehead protuberance for the right side of the face</i>
$FWA = (\theta_R + \theta_S)/2$	<i>Finds the Forehead Width Angle, the average of the two angles of deviation of the extrema points of the eyes from the center line of the face</i>

Descriptor Name: Cheek-to-Zygomatic Height Ratio **Anatomical Region of Face:**

AR13_ZygomaticProcess

- 5 Describes the ratio of Cheek and Zygomatic Process height in terms of distance from the topline of the face.

$m_{yz} = \frac{Z_y - Y_y}{Z_x - Y_x}$	<i>finds the slope of the Zygomatic Ridge</i>
$m_{ab} = \frac{A_y - B_y}{A_x - B_x}$	<i>finds the slope of the True Line of the Face</i>
$m_{yz} = \frac{Z_y - Y_y}{Z_x - Y_x}$	<i>finds the slope of the Line of the Forehead</i>
$m_p = -(m_p)^{-1}$	<i>finds the slope perpendicular to the Zygomatic Ridge</i>
$Q_x = \frac{m_{of} * E_x - m_p * Z_x + Z_y - E_y}{m_{of} - m_p}$	$Q_y = m_{of}(Q_x - E_x) + E_y$ <i>finds the x-coordinate and y-coordinate of intersect point Q</i>

$R_x = \frac{m_{ab} * A_x - m_p * Y_x + Y_y - A_y}{m_{ab} - m_p}$	$R_y = m_{ab}(R_x - A_x) + A_y$
<i>finds the x-coordinate and y-coordinate of intersect point R</i>	
$\overline{RY} = \sqrt{(R_x - Y_x)^2 + (R_y - Y_y)^2}$	<i>finds the height of line RY, here defined as the height of the cheek</i>
$\overline{QZ} = \sqrt{(Q_x - Z_x)^2 + (Q_y - Z_y)^2}$	<i>finds the height of line RY, here defined as the height of the Zygomatic Process</i>
$ctZHP = \overline{RY} / \overline{QZ}$	<i>finds the Cheek-to-Zygomatic Height Proportion, here defined as the ratio between the distance from the Distal Cheek Point to the True Line of the Face and the distance from the Zygomatic Process Point and the Line of the Forehead</i>

Descriptor Name: Ear Inflexion Proportion
AR09_EarShape

Anatomical Region of Face:

Describes the degree to which the inner line of the ear curves inward between the upper-most point of the ear and the medial pinna point.

$M_{np} = \frac{(N_y - P_y)}{(N_x - P_x)}$	<i>finds the slope of line $\overline{NP}$</i>
$M_p = -(M_{np})^{-1}$	<i>finds the slope perpendicular to line $\overline{NP}$</i>
$Q_x = \frac{(M_p * J_x - M_{np} * N_x + N_y - J_y)}{(M_p - M_{np})}$	<i>finds the x-coordinate of perpendicular intercept point Q</i>
$Q_y = M_{np} * (Q_x - P_x) + P_y$	<i>finds the y-coordinate of perpendicular intercept point Q</i>
$\overline{QJ} = \sqrt{(J_x - Q_x)^2 + (J_y - Q_y)^2}$	<i>finds the distance of eye orbital protrusion</i>
$\overline{PN} = \sqrt{(P_x - N_x)^2 + (P_y - N_y)^2}$	<i>finds the maximal lateral thickness of the cheeks</i>
$EIP = \frac{\overline{QJ}}{\overline{PN}}$	<i>finds the Ear Inflexion Proportion, here defined as the perpendicular distance of inflexion relative to the overall distance of concavity along the inner line of the ear</i>

- 5 **Descriptor Name:** Ear Width-to-Breadth Proportion
AR09_EarShape

Anatomical Region of Face:

Describes the overall width of the broadest section of the ear relative to its overall length.

$M_x = 0.5(K_x - J_x) + J_x, M_y = J_y = K_y$	<i>finds the upper mid-ear point</i>
$\overline{LM} = \sqrt{(L_x - M_x)^2 + (L_y - M_y)^2}$	<i>finds the length of the ear</i>
$\overline{NH} = \sqrt{(N_x - H_x)^2 + (N_y - H_y)^2}$	<i>finds the width of the ear</i>
$EIP = \frac{\overline{NH}}{\overline{LM}}$	<i>finds the Ear Width-to-Breadth Proportion, here defined as the width of the ear at its broadest point relative to its overall length</i>

Descriptor Name: Degree of Ear Flare
AR09_EarShape

Anatomical Region of Face:

- 10 Describes degree to which the medial portion of the inner ear flares inward beyond the base structure of the ear.

$M_x = 0.5(K_x - J_x) + J_x$ $M_y = J_y = K_y$	<i>finds the upper mid-ear point</i>
---	--------------------------------------

$m_{jt} = \frac{J_y - T_y}{J_x - T_x}$	<i>finds the slope of line $\overline{JT}$</i>
$M_p = -(M_{jt})^{-1}$	<i>finds the slope perpendicular to line $\overline{JT}$</i>
$Q_x = \frac{(M_p * N_x - M_{jt} * J_x + J_y - N_y)}{(M_p - M_{jt})}$	$Q_y = M_{ad} * (Q_x - A_x) + A_y$ <i>finds the x and y-coordinates of perpendicular intersect point Q</i>
$\overline{NQ} = \sqrt{(N_x - Q_x)^2 + (N_y - Q_y)^2}$	<i>finds the perpendicular distance of flaring</i>
$\overline{LM} = \sqrt{(I_x - M_x)^2 + (I_y - M_y)^2}$	<i>finds the overall length of the ear</i>
$DoEF = \frac{\overline{NQ}}{\overline{LM}}$	<i>finds the Degree of Ear Flare, here defined as the degree of perpendicular rise of the medial portion of the inner ear relative to the overall length of the ear</i>

Descriptor Name: Chin Width-to-Height Proportion
AR05_ChinShape

Anatomical Region of Face:

Describes the ratio of the coverall length of the chin to its height at its minimal-most point.

$GH = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}, \quad GI = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2},$ $\overline{HI} = \sqrt{(H_x - I_x)^2 + (H_y - I_y)^2}$	<i>Finds distance values for all sides of the triangle</i>
$\theta = \cos^{-1}\left(\frac{\overline{HI}^2 - \overline{GI}^2 - \overline{GH}^2}{-2 * \overline{GI} * \overline{GH}}\right)$	<i>finds the angle for $\angle HGI$, denoted here as θ</i>
$\overline{QI} = \sin(\theta) * \overline{GI}$	<i>finds the height of triangle ΔGHI (perpendicular height of the chin)</i>
$CWtHP = \frac{\overline{QI}}{\overline{GH}}$	<i>finds the Chin Width-to-Height Proportion, here defined as the ratio of the length of the chin to its maximal perpendicular height</i>

5

Descriptor Name: Chin Length Angle
AR05_ChinShape

Anatomical Region of Face:

Describes the overall length of the chin relative to the degree to which it protrudes from the underside of the jowl bone. Differentiates between a long and short chin. Partially identifies a thin chin.

$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}, \quad \overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2},$ $\overline{HI} = \sqrt{(H_x - I_x)^2 + (H_y - I_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1}\left(\frac{\overline{GH}^2 - \overline{GI}^2 - \overline{HI}^2}{-2 * \overline{GI} * \overline{HI}}\right)$	<i>Finds angle value for Chin Length Angle ($\angle ACB$), denoted as θ</i>

10

Descriptor Name: Chin Firmness Proportion
AR05_ChinShape

Anatomical Region of Face:

Describes the overall tightness of the chin, as reflected closeness of the Chin Maxima Point to the Caudal Chin Point relative to the overall length of the chin

$M_{gh} = \frac{(G_y - H_y)}{(G_x - H_x)}$	<i>finds the slope of line $\overline{GH}$</i>
--	---

$M_{qi} = -(M_{gi})^{-1}$	<i>finds the slope of line $\overline{QI}$, perpendicular to line $\overline{GH}$</i>
$Q_x = \frac{(M_{gh} * G_x - M_{qi} * I_x + I_y - G_y)}{(M_{gh} - M_{qi})}$	<i>finds the x-coordinate of the perpendicular intersection point Q</i>
$Q_y = M_{gh} * (Q_x - G_x) + G_y$	<i>finds the y-coordinate of intersect point Q</i>
$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}, \quad \overline{GQ} = \sqrt{(G_x - Q_x)^2 + (G_y - Q_y)^2}$	
<i>Finds distance values for lines $\overline{GH}$ and $\overline{GQ}$</i>	
$CFP = \frac{\overline{GQ}}{\overline{GH}}$	<i>finds the Chin Firmness Proportion, here defined as the distance at which the Chin Minima Point is located from the front of the chin</i>

Descriptor Name: Chin Thickness Angle
AR05_ChinShape

Anatomical Region of Face:

Describes the position of the minima point of chin relative to the point where the chin first becomes distinguishable from the lip. Differentiates between a relaxed and tight chin.

$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}, \quad \overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2},$ $\overline{HI} = \sqrt{(H_x - I_x)^2 + (H_y - I_y)^2}$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{HI}^2 - \overline{GI}^2 - \overline{GH}^2}{-2 * \overline{GI} * \overline{GH}} \right)$	<i>Finds the angle value for Chin Thickness Angle ($\angle BAC$), denoted here as θ</i>

5

Descriptor Name: Lip Length Proportion
AR05_ChinShape

Anatomical Region of Face:

Describes the length of overhand of the lower lip as it compares to the overall length of the chin.

$M_{gh} = \frac{(G_y - H_y)}{(G_x - H_x)}$	<i>finds the slope of line $\overline{GH}$</i>
$M_{kq} = -(M_{gh})^{-1}$	<i>finds the slope of line $\overline{KQ}$, perpendicular to line $\overline{GH}$</i>
$Q_x = \frac{(M_{gh} * G_x - M_{kq} * K_x + K_y - G_y)}{(M_{gh} - M_{kq})}$	<i>finds the x-coordinate of the perpendicular intersection point Q</i>
$Q_y = M_{gh} * (Q_x - G_x) + G_y$	<i>finds the y-coordinate of intersect point Q</i>
$\overline{HQ} = \sqrt{(H_x - Q_x)^2 + (H_y - Q_y)^2}, \quad \overline{GQ} = \sqrt{(G_x - Q_x)^2 + (G_y - Q_y)^2}$	
<i>Finds distance values for lines $\overline{HQ}$ and $\overline{GQ}$</i>	
$LLP = \frac{\overline{GQ}}{\overline{HQ}}$	<i>finds the Lip Length Proportion, here defined as the length of overhang of the lower lip relative to the overall length of the chin</i>

10

Descriptor Name: Chin Fullness Proportion
AR05_ChinShape

Anatomical Region of Face:

Describes the fullness/roundness of the chin as the perpendicular deviation of the profile of the chin from the front line of the chin relative to the overall length of the front line of the chin.

$\overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2}, \quad \overline{GJ} = \sqrt{(G_x - J_x)^2 + (G_y - J_y)^2},$

$\overline{JI} = \sqrt{(J_x - I_x)^2 + (J_y - I_y)^2}$	Finds distance values for all sides of the triangle
$\theta = \cos^{-1}\left(\frac{\overline{JI}^2 - \overline{GI}^2 - \overline{GJ}^2}{-2 * \overline{GI} * \overline{GJ}}\right)$	finds the angle for $\angle GJI$, denoted here as θ
$\overline{QJ} = \sin(\theta) * \overline{GI}$	finds the height of triangle ΔGJI (perpendicular thickness height of the chin)
$CWtHP = \frac{\overline{QJ}}{\overline{GI}}$	finds the Chin Fullness Proportion , here defined as the perpendicular deviation of the Mid-Chin Point from the front line of the chin relative to the overall length of the front line of the chin

Descriptor Name: Mouth Length Proportion
AR06_MouthLength

Anatomical Region of Face:

5 Describes the length of the mouth relative to the overall length of the head

$M_{ubb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$	finds the slope of the True Line of the Head
$M_{pu} = -(M_{ubb})^{-1}$	finds the slope perpendicular to the True Line of the Head
$R_x = \frac{(M_{ubb} * U_x - M_{pu} * F_x + F_y - U_y)}{(M_{ubb} - M_{pu})}$	$R_y = M_{ubb} * (R_x - U_x) + U_y$ finds the x and y-coordinates of intersect point R
$\overline{JT} = \sqrt{(J_x - T_x)^2 + (J_y - T_y)^2}$	finds the length of the mouth
$\overline{UR} = \sqrt{(U_x - R_x)^2 + (U_y - R_y)^2}$	finds the full length of the head
$MLP = \frac{\overline{JT}}{\overline{UR}}$	finds the Mouth Length Proportion , here defined as the length of the mouth relative to the overall length of the head

Descriptor Name: Lip Protuberance Proportion

Anatomical Region of Face: AR06_MouthLength

Describes the degree to which the lower lip protrudes beyond the distal-most point of the mouth.

$m_{jt} = \frac{J_y - T_y}{J_x - T_x}$	finds the slope of the line of the mouth
$m_p = -(m_{jt})^{-1}$	Finds the slope perpendicular to the line of the mouth
$Q_x = \frac{m_{jt} * T_x - m_p * K_x + K_y - T_y}{m_{jt} - m_p}$	finds the x-coordinate of perpendicular intersect point Q
$Q_y = m_{jt}(Q_x - T_x) + T_y$	finds the y-coordinate of intersect point "Q"
$\overline{TQ} = \sqrt{(T_x - Q_x)^2 + (T_y - Q_y)^2}$	finds the total length of the lower lip
$\overline{TQ} = \sqrt{(T_x - Q_x)^2 + (T_y - Q_y)^2}$	finds the distance which the distal-most point of the lower lip protrudes beyond the distal-most point of the mouth

$\sigma_s = \left(\frac{Q_x - T_x}{ Q_x - T_x } \right)$	<i>finds the constant of lip position with magnitude 1 indicating the position of the lip beyond or behind the distal-most point of the mouth</i>
$LPP = \sigma_s * \left(\frac{TQ}{JQ} \right)$	<i>finds the Lip Protuberance Proportion, which here defines the position of the distal-most point of the lower lip relative to the distal most point of the mouth</i>

Descriptor Name: Nostril Length Proportion**Anatomical Region of Face:** AR07_NostrilShape

Describes the lateral length across the nostril relative to the overall length of the upper lip.

$\overline{BU} = \sqrt{(B_x - U_x)^2 + (B_y - U_y)^2}$	<i>Finds the length of the nostril</i>
$\overline{UT} = \sqrt{(U_x - T_x)^2 + (U_y - T_x)^2}$	<i>Finds the length of the upper lip</i>
$NWP = \overline{BU} / \overline{UT}$	<i>Finds the Nostril Length Proportion, here defined as the lateral length of the nostril relative to the overall length of the upper lip</i>

Descriptor Name: Degree of Nostril Flutendess**Anatomical Region of Face:** AR07_NostrilShape

5 Describes the degree to which excess skin along the inside of the nostril extends and curls around the inner line of the nostril.

$M_{xs} = \frac{(X_y - S_y)}{(X_x - S_x)}$	<i>finds the slope of the Line of the Inner Nostril</i>
$M_p = -(M_{xs})^{-1}$	<i>finds the slope perpendicular to the Line of the Inner Nostril</i>
$Q_x = \frac{(M_{xs} * S_x - M_p * Z_x + Z_y - S_y)}{(M_{xs} - M_u)}$	$Q_y = M_{ty} * (Q_x - T_x) + T_y$ <i>finds the x and y-coordinates of intersect point Q</i>
$\overline{XS} = \sqrt{(X_x - S_x)^2 + (X_y - S_y)^2}$	<i>finds the overall length of the nostril</i>
$\overline{ZQ} = \sqrt{(Z_x - Q_x)^2 + (Z_y - Q_y)^2}$	<i>finds the perpendicular distance of rise of the fleshy skin flap of the inner nostril from the Line of the Inner Nostril</i>
$DoNF = \frac{\overline{ZQ}}{\overline{XS}}$	<i>finds the Degree of Nostril Flutedness, here defined as the distance of inflexion of the skin of the inner nostril from the Line of the Inner Nostril (the flute of the nose) relative to the overall length of the nostril</i>

Descriptor Name: Nose Width-to-Height Proportion**Anatomical Region of Face:** AR07_NostrilShape

Describes the perpendicular height of the nose relative to the overall breadth of the nose.

$M_{xy} = \frac{(X_y - Y_y)}{(X_x - Y_x)}$	<i>finds the slope of the Upper Line of the Nostril</i>
$M_p = -(M_{xy})^{-1}$	<i>finds the slope perpendicular to the Upper Line of the Nostril</i>
$Q_x = \frac{(M_{xy} * Y_x - M_p * S_x + S_y - Y_y)}{(M_{xy} - M_u)}$	$Q_y = M_{xy} * (Q_x - X_x) + X_y$ <i>finds the x and y-coordinates of intersect point Q</i>

$\overline{XY} = \sqrt{(X_x - V_x)^2 + (X_y - V_y)^2}$	<i>finds the overall breadth of the nostril</i>
$\overline{QS} = \sqrt{(S_x - Q_x)^2 + (S_y - Q_y)^2}$	<i>finds the perpendicular height of the nose</i>
$DWtHP = \frac{\overline{QS}}{\overline{XY}}$	<i>finds the Nose Width-to-Height Proportion, here defined as the ratio between the perpendicular height of the nostrils and the overall breadth of the nose</i>

Descriptor Name: Degree of Nostril Roundness **Anatomical Region of Face:** AR07_NostrilShape

Describes the perpendicular height of the outer edge of the nostril above the line of the inner nostril. Identifies horses with large and/or flared nostrils.

$M_{ty} = \frac{(T_y - Y_y)}{(T_x - Y_x)}$	<i>finds the slope of the Line of the Inner Nostril</i>
$M_p = -(M_{ty})^{-1}$	<i>finds the slope perpendicular to the Line of the Inner Nostril</i>
$Q_x = \frac{(M_{ty} * T_x - M_p * V_x + V_y - T_y)}{(M_{ty} - M_u)}$	$Q_y = M_{ty} * (Q_x - T_x) + T_y$ <i>finds the x and y-coordinates of intersect point Q</i>
$\overline{TY} = \sqrt{(T_x - Y_x)^2 + (T_y - Y_y)^2}$	<i>finds the overall length of the nostril</i>
$\overline{VQ} = \sqrt{(V_x - Q_x)^2 + (V_y - Q_y)^2}$	<i>finds the perpendicular width of the nostril at its widest point</i>
$DoNR = \frac{\overline{VQ}}{\overline{TY}}$	<i>finds the Degree of Nostril Roundness, here defined as the perpendicular width of the nostril at its widest point relative to the overall length of the nostril</i>

5 **Descriptor Name:** Inner-Nostril Convergence Proportion **Anatomical Region of Face:** AR07_NostrilShape

Describes the horizontal positions of the upper and lower medial points of the nostrils relative to one another as they align with the mid-line of the face. Differentiated between horses with flat vertically aligned nostrils and horses with highly curved angled nostrils.

$\overline{ST} = \sqrt{(S_x - T_x)^2 + (S_y - T_y)^2}$	<i>Finds lateral distance across the upper bridge of the nose</i>
$\overline{XY} = \sqrt{(X_x - Y_x)^2 + (X_y - Y_x)^2}$	<i>Finds lateral distance across the lower bridge of the nose</i>
$INCP = \overline{ST} / \overline{XY}$	<i>Finds the Inner-Nostril Convergence Proportion, as the ratio between the lateral distance between the upper and lower portions of the bridge of the nose</i>

10 **Descriptor Name:** Nostril Width Proportion **Anatomical Region of Face:** AR07_NostrilShape

Describes the proportion of the lateral distance of the muzzle that is inclusive of nostril area. Reflects the relative size/expansiveness of the nostrils relative to the size of the entire muzzle. Differentiates between large and narrow nostrils.

$\overline{ST} = \sqrt{(S_x - T_x)^2 + (S_y - T_y)^2}$	<i>Finds lateral distance across muzzle non-inclusive of nostril area</i>
--	---

$\overline{UV} = \sqrt{(U_x - V_x)^2 + (U_y - V_x)^2}$	<i>Finds total lateral distance across the muzzle</i>
$NWP = \overline{ST} / \overline{UV}$	<i>Finds the Nostril Width Proportion, here defined as the lateral distance of the bridge of the nose relative to the overall distance across the muzzle inclusive of nostrils</i>

Descriptor Name: Degree of Lip Inflexion
AR08_LipShape

Anatomical Region of Face:

Describes degree of inflexion/curvature of upper lip. Differentiates between flat and “heart-shaped” upper lip.

$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}, \quad \overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2},$	
$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2},$	<i>Finds distance values for all sides of triangle</i>
$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$	<i>Finds the angle measure for $\angle BAC$, denoted here as θ</i>
$d = \sin \theta * \overline{AC}$	<i>Finds the distance “d” of inflexion</i>
$DoLP = d / \overline{AB}$	<i>Finds Degree of Lip Inflexion, which is here defined to the distance of medial inflexion of the lip relative to the overall width of the lips</i>

5 **Descriptor Name:** Ear Roundness Proportion
AR09_EarShape

Anatomical Region of Face:

Describes the degree to which the tip of the ear curves inward away from the midline of the ear. This measure distinguishes between curvatures at the top of the ear due to concavity at the tip and curvature due to actual rounding of the ear structure.

$M_x = 0.5(K_x - I_x) + I_x, \quad M_y = I_y = K_y$	<i>finds the upper mid-ear point</i>
$m_{ml} = \frac{M_y - L_y}{M_x - L_x}$	<i>finds the slope of the Midline of the Ear</i>
$M_p = -(M_{ml})^{-1}$	<i>finds the slope perpendicular to the Midline of the Ear</i>
$Q_x = \frac{(M_p * P_x - M_{ml} * L_x + L_y - P_y)}{(M_p - M_{ml})}, \quad Q_y = M_{ab} * (Q_x - A_x) + A_y$	<i>finds the x and y-coordinates of intersect point Q</i>
$\overline{PQ} = \sqrt{(P_x - Q_x)^2 + (P_y - Q_y)^2}$	<i>finds the perpendicular distance of rounding at the tip of the ear</i>
$\overline{LM} = \sqrt{(L_x - M_x)^2 + (L_y - M_y)^2}$	<i>finds the overall length of the ear</i>
$ERP = \frac{\overline{PQ}}{\overline{LN}}$	<i>finds the Ear Roundness Proportion, here defined as the perpendicular distance of inward curvature of the tip of the ear from the midline of the ear, relative to the overall length of the ear</i>

10

Descriptor Name: Ear Rotation Proportion
AR10_EarPosition

Anatomical Region of Face:

Describes the degree of rotation of the ear as it is naturally set onto the forehead. Ears that are set wider apart and therefore farther down the poll are rotated laterally and show from the frontal view lesser pinna area. This measure reflects the proportion of area located at the base of the ear visually identified as pinna, differentiating between horses with wide and narrow set ears.

15

$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$	<i>Finds the slope of the True Line of the Forehead, here defined as the line between the inner extrema points of the eyes</i>
$m_p = -(m_{ab})^{-1}$	<i>Finds the slope perpendicular to the True Line of the Forehead</i>
$N_x = \frac{m_{ab} * A_x - m_p * C_x + C_y - A_y}{m_{ab} - m_p} \quad P_x = \frac{m_{ab} * A_x - m_p * D_x + D_y - A_y}{m_{ab} - m_p}$ $Q_x = \frac{m_{ab} * A_x - m_p * E_x + E_y - A_y}{m_{ab} - m_p}$	
<i>Finds the x-coordinates of the intersection points between the true line of the forehead and its perpendicular bisector inclusive of pint C, D, and E respectively</i>	
$N_y = m_{ch}(N_x - A_x) + A_y \quad P_y = m_{ch}(P_x - A_x) + A_y$ $Q_y = m_{ch}(Q_x - A_x) + A_y$	
<i>Find the y-coordinated corresponding to intersect points N, P, and Q</i>	
$\overline{NP} = \sqrt{(P_x - N_x)^2 + (P_y - N_y)^2}$	<i>Finds the distance across the base of the ear non-inclusive of pinna</i>
$\overline{NQ} = \sqrt{(Q_x - N_x)^2 + (Q_y - N_y)^2}$	<i>Finds the total distance across the base of the ear</i>
$ERP = \overline{NP} / \overline{NQ}$	<i>Finds the Ear Rotation Proportion, here defined as the proportion of the base of the ear non-inclusive of pinna as a indication of degree of rotation and wideness of set</i>

Descriptor Name: Ear Set Angle
AR10_EarPosition

Anatomical Region of Face:

5 Describes the angle at which the ears are positioned onto the top of the skull, reflecting the natural position of the ears when the horse is in an emotionally neutral state of mind. Differentiates between wide, narrow, and vertically places ears.

10 When the anatomical reference points are manually selected, the most appropriate to use must be chosen based on how clearly the anatomical reference point can be seen and by which ear shows the highest degree of forward rotation.. The point on the inside curvature of the ear should be at the medial-most point of the curve, and the point of the outside curvature of the ear should be traced over so that the horizontal cross-hairs remain aligned horizontally with the inner ear point.

$M_x = 0.5(K_x - J_x) + J_x$ $M_y = J_y = K_y$	<i>finds the upper mid-ear point</i>
$m_{mi} = \frac{M_y - L_y}{M_x - L_x}$	<i>finds the slope of the Midline of the Ear</i>
$Q_x = \frac{(M_{ab} * A_x - M_{mi} * L_x + L_y - A_y)}{(M_{ab} - M_{mi})}$ $Q_y = M_{ab} * (Q_x - A_x) + A_y$	<i>finds the x and y-coordinates of intersect point Q</i>
$\overline{AB} = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}, \overline{AM} = \sqrt{(M_x - A_x)^2 + (M_y - A_y)^2},$ $\overline{MQ} = \sqrt{(M_x - Q_x)^2 + (M_y - Q_y)^2}$	<i>Finds the lengths of all sides of the triangle</i>
$ESA = \theta = \cos^{-1} \left(\frac{\overline{AM}^2 - \overline{AB}^2 - \overline{MQ}^2}{-2 * \overline{AB} * \overline{MQ}} \right)$	<i>Finds the Ear Set Angle, defined here as the angle at which the midline of the ear meets the True Line of the Face</i>

[0039] Nevertheless, these anatomical regions and measurements are exemplary rather than exhaustive, as others could be added to or removed from the set within the spirit and scope of the disclosure. Moreover, although Figs. 1 through 13 show

anatomical regions of the equine face, embodiments may be applied to other equine anatomical regions or to anatomical regions of other domesticated animals, such as donkeys, cattle, oxen, llamas, sheep, goats, dogs, camels, geese, chickens, turkeys, cats, and pigs.

5 [0040] Fig. 15 shows an embodiment in the form of a method for determining a predictor of a characteristic of a particular type of animal. As used herein, “type” refers to breed, species, sub-species, or any other relevant genetic similarity. In step 1500, a sample library is created for the type of animal of interest. This step comprises obtaining one or more digital images of an anatomical region for each of a plurality of
10 animals of interest, e.g., an equine face. The image may be obtained in various ways, such as from a memory card of a digital camera, by downloading via File Transfer Protocol (FTP), via email, etc. Once obtained, the images are stored in a memory operably connected to a digital computer, such as memory that is either locally or remotely accessible by the computer, including an attached hard drive, removable flash
15 drive, network drive, RAID (redundant array of independent disks) drive, removable memory card, etc.

[0041] Step 1500 also comprises obtaining additional data related to the characteristic of the particular type of animal and storing it in the same or a different memory operably connected to the digital computer. As used herein, “data” may refer to
20 performance records, vital statistics, and/or any other quantitative information that is related in some way to the characteristic of interest. While qualitative data may also be used, in many embodiments the qualitative data is converted into quantitative data for easier use by the system. The additional data may pertain to individual animals in the sample library, groups of animals in the sample library, or more generally the type of
25 animal. The additional data is stored in a manner and location by which it can be associated with the sample library images, such as in a relational database accessible by the digital computer.

[0042] In an exemplary embodiment, the animal of interest is an Arabian horse and the characteristic of interest is whether the animal is best suited for the English Pleasure
30 (EP), Western Pleasure (WP), or Working Western (WW) riding discipline. For this purpose, a sample library of digital images of Arabian horses may be collected, together with additional data relating to their known riding disciplines. The number of horses in the sample library may be chosen based on availability and desired statistical accuracy

of the predictor, as readily understood by persons of ordinary skill in the art. In the exemplary embodiment, the sample library comprises 81 Arabian horses, each with annotated images and information about their riding discipline.

5 [0043] In step 1502, a plurality of reference points are added to the one or more stored images of a particular animal in the sample library. This may be accomplished in an automated fashion or manually, for example by use of a program with a graphical user interface (GUI) running on the digital computer. For example, the one or more images can be processed by MATLAB, an advanced mathematical analysis program sold by The Mathworks, Inc., of Natick, Massachusetts (<http://www.mathworks.com>).
10 MATLAB provides advanced image processing features and flexible options for definition of large numbers of variables, specifically matrices. Reference points are added to each of the images by using the MATLAB "GInput" command, which provides an interactive selection GUI. In some embodiments, reference points are manually selected on the image. One such embodiment is the exemplary equestrian
15 embodiment, in which Figs. 1 through 13 were manually annotated with reference points (e.g., points A, B, and C in Fig. 1A). In other embodiments, reference points may be added automatically by MATLAB or another software application based on a generic model of the animal's face. Once the reference points are entered onto an image, MATLAB maps their pixel locations within the image to numerical coordinates
20 within the corresponding matrix to facilitate further computation.

[0044] In step 1504, one or more facial descriptor measurements (FDMs) related to the characteristic of interest are computed from the set of reference points that were added to the one or more digital images of the animal. In the exemplary equestrian embodiment, the facial descriptor measurements may be computed using distance
25 measurements and trigonometric functions as illustrated in Figs. 1-13. Because length distance measurements are based on coordinate positions within the pixel matrix, the absolute distance values may be sensitive to factors such as camera resolution, artifacts of one or more compressions of the image, and cropping applied to isolate the face. To overcome such factors, the length measurements may be normalized to structural
30 reference lengths that are effectively constant among animals of the same type and subject to the same set of factors. For example, in Fig. 1A, the facial inflection distance, d , is normalized by the overall length of the facial profile, AB. However, it is apparent to one of ordinary skill that the facial descriptor measurements may be based

upon absolute or non-normalized length measurements if the factors described above were not present or were not a concern. In other embodiments, one or more of the facial descriptor measurements may be based on an angular measurement or an area measurement. The facial descriptor measurements may be based on non-trigonometric calculations, such integral calculus calculations, or a combination of trigonometric and non-trigonometric calculations.

[0045] In some embodiments, one or more of the digital images of the animal are three-dimensional images. Such images may be created by combining multiple two-dimensional images of the animal using stereophotogrammetry or other methods known to persons of ordinary skill in the art. In such embodiments, one or more of the facial descriptor measurements may be based on a three-dimensional measurement, such as an absolute volume, a volumetric ratio, a solid angle, or a combination thereof.

[0046] As shown in Fig. 15, steps 1502 and 1504 are repeated for each animal in the sample library. Once complete, in step 1508, a relationship is determined between a particular facial descriptor measurement and the additional data related to the characteristic of interest using all animals in the sample library. For example, the relationship can be determined from the mathematical correlation between the facial descriptor measurement and additional data for all animals in the sample library. The correlation may be normalized or scaled as necessary to make it meaningful for further computation or interpretation. Other measures can be used to determine the effectiveness of a facial descriptor measurement in the model. For example, in categorical models (e.g., those used to predict riding discipline), ROC curve analysis may be used to select indicator of categorical potential, as described further below. Multi-dimensional, Euclidean distance analysis also may be used to separate two groups categorically. Other methods for determining a relationship based on appropriate statistical models are apparent to persons of ordinary skill in the art. In the exemplary equestrian embodiment, the relationship is based on the correlation between the facial descriptor measurement and the known riding discipline. As illustrated in Fig. 15, step 1506 is repeated for each facial descriptor measurement.

[0047] In step 1512, one or more of the facial descriptor measurements are selected to be used as predictors of the characteristic of interest. Any number of facial descriptor measurements – up to and including the entire set – may be selected. If there are multiple characteristics of interest, then a separate selection may be made for each

characteristic. The selection may be made in various ways, depending on the available information and the characteristic of interest. Moreover, in step 1512, the combination of the selected facial descriptor measurements that optimizes the predictor is also determined. For example, an optimal linear combination of the selected subset of facial descriptor measurements is determined using statistical analysis techniques. In the spirit of the disclosure, however, a non-linear combination of the entire set, or a selected subset, of the facial descriptor measurements also may be determined from the sample library. If multiple characteristics are of interest, then an optimal combination for each characteristic may be selected.

- 5
- 10 **[0048]** In the exemplary equestrian embodiment, facial descriptor measurements may be selected for predicting whether an Arabian horse is best suited for the English Pleasure (EP), Western Pleasure (WP), or Working Western (WW) riding discipline. Based on the categorical power of the facial descriptor measurements, ROC (receiver operating characteristic) analysis can be used to select facial descriptor measurement(s)
- 15 that best categorizes the sample of horses into their actual riding disciplines. Fig. 21 shows an exemplary ROC curve, where the false positive rate is shown on the horizontal axis and the true positive rate is shown on the vertical axis. The ROC curve shown in Fig. 21 has an area of 0.801; a ROC curve area greater than 0.65 indicates that a particular facial descriptor measurement is useful for prediction or categorization.
- 20 **[0049]** In the subset selection of the exemplary embodiment, two sets of ROC curves were generated: one containing binomial separations (A vs. B) and the other single discipline isolations from the full population (A vs. B+C). The discipline combination among the isolation curves with the highest separation values was selected for use in the first tier of the classification model. The remaining two groups were then separated
- 25 binomially in the second tier of the model. For each classification level of the model, the two individual facial descriptor measurements with the highest ROC scores were selected at the optimization variables. The strongest set of isolation ROC curves chosen to comprise the first tier of the model was the WW separation using descriptor values for AR03_Jowl Protuberance Proportion (ROC area = 0.819) and AR03_Jowl-to-
- 30 Underline Proportion (ROC area = 0.817) as optimization variables. The second tier of the model separated binomially the EP and WP groups, utilizing descriptor values for AR10_Ear Rotation Proportion (ROC area = 0.863) and AR11_Eye Size Proportion (ROC area = 0.755).

[0050] At each tier of the model, the z-scores (also commonly known as standard scores or z-values) of the facial descriptor measurements selected as the optimization variables were linearly combined. Coefficients for these variables, in addition to the cutoff value itself, were then optimized on a training set consisting of eleven randomly selected horses in the sample library from each of the three riding disciplines. The optimization resulted in linear equations capable of producing discipline descriptor values that would accurately categorize the highest possible number of horses into their known disciplines. The optimized linear equations and cutoff were then used on the remaining 48 horses in the 81-horse sample library to validate the accuracy of the model. Fig. 18 shows the results of subset selection process as applied to the 81-horse sample library, resulting in selection of a linear combination of two of the facial descriptor measurements. The described method of selecting an optimal linear combination of the selected facial descriptor measurements is merely exemplary. In an alternate embodiment, the linear combination coefficients may be selected using the entire sample library. In the same manner, a non-linear combination of the selected facial descriptor measurements may be selected using optimization techniques including, but not limited to, Newton's Method and Lagrange's Method.

[0051] According to the embodiment illustrated by Fig. 16, the selected subset and combination of facial descriptor measurements then can be used to predict a characteristic of an animal based on the facial descriptor measurements for that animal. In other words, the subset and combination selected based on the sample library can be applied to other animals of the same type to determine the characteristic for those animals. In step 1600, digital images and additional data is obtained and stored for an animal of interest, in the same manner as described above with reference to the sample library (i.e., step 1500 of Fig. 15). In step 1602, reference points consistent with those of the images in the sample library are added to the images of the animal of interest. In step 1604, facial descriptor measurements are calculated for the animal of interest. In the exemplary equestrian embodiment, the reference points and facial descriptor measurements are illustrated by Figs. 1 through 13.

[0052] In step 1606, the subset and combination selected in step 1512 is applied to the facial descriptor measurements of the animal to predict the characteristic of interest. By way of example, the subset and combination shown in Fig. 18 is applied to the facial descriptor measurements of an Arabian horse to determine whether that animal is best

suited for EP, WP, or WW riding discipline. In step 1608, the sample library optionally may be augmented by adding the image(s), additional data, and facial descriptor measurements for this animal. Subsequently, the method of Fig. 15 can be repeated using the augmented sample library, and the resulting predictor can be applied to additional animals of the same type in accordance with the method of Fig. 16.

[0053] Using the method illustrated by Fig. 15, facial descriptor measurements also may be selected for use in determining the performance of a particular horse in a desired riding discipline. Few accurate measures of performance exist within the equestrian industry. One exemplary measure of competitive performance is win percentile scores, here defined as the percentage of horses that a given horse was able to beat at point qualifying competition in a given season out of the total number of horses shown against. For each of the 81 horses, win percentiles were calculated for every season with the best win percentile retained. In one embodiment, selection of the subset of facial descriptor measurements is done by finding r-squared values representing the correlation between win percentiles and each of the facial descriptor measures for each discipline. For each riding discipline, the four descriptor values with the highest correlations were selected to be used to determine the performance characteristic for that discipline. However, the choice of four descriptor measurements is merely exemplary; fewer or more descriptor measurements may be selected.

[0054] In addition, for each riding discipline of interest, an optimal combination of the selected facial descriptor measurements is determined for that riding discipline. In some embodiments, the selected facial descriptor measurements may be combined linearly or non-linearly. In other embodiments, functions of the selected facial descriptor measurements may be combined linearly or non-linearly. In the exemplary equestrian embodiment described above, the z-scores of the facial descriptor measurements are combined linearly. The z-score for a particular facial descriptor measurement of an individual horse may be calculated using the mean and standard deviation of that facial descriptor measurement for all horses in the same library. More generally, the linear combination coefficients may be determined by applying multiple regression statistical techniques to the four selected facial predictor measurements for all horses in the sample library, all horses in the sample library that participate in a particular discipline, or a subset of horses from the sample library that participate in a particular discipline. The selected subset and combination of facial descriptor

measurements are used to calculate a characteristic, also called a “performance model,” indicative of the performance of horses of the same breed in the particular equestrian event. Fig. 19 shows an exemplary performance model for the WW event comprising a linear combination of the z-scores of facial descriptor measurements AR03_Jowl
5 Protuberance Proportion, AR04_Full Angle Face, AR09_Degree of Ear Flare, and AR11_Eye Size Proportion. This performance model for the particular event, e.g., WW, can be applied to other horses outside of the sample library to predict the performance in that event based upon the selected facial descriptor measurements.

[0055] While embodiments have been described above in relation to categorizing and
10 predicting the performance of horses in equestrian show events, embodiments also may be used to categorize and determine equestrian performance in racing events. This application is very important for a variety of reasons. First, due to the large investment in time and resources required to train a race horse, it is desirable to minimize the risk of investment by careful choice of which horses to train for racing. Second, once
15 trained for racing, these horses are poorly suited to other non-racing activities (e.g., dressage, show jumping, pleasure riding etc.), and require a significant investment of time and skill to retrain to a new use off the track. Horses that are trained but eventually found to be unsuitable for racing often are euthanized or sold for slaughter, which could be avoided by more careful preliminary selection of training candidates.

[0056] The methods described above with reference to Figs. 15 and 16 may be
20 applied to racing horses in several different ways. First, as a threshold test, embodiments may determine a particular horse’s suitability for racing. By analyzing features of the facial region, such as the ones described above, a potential buyer of a yearling race prospect can determine whether the cognitive and/or behavioral suitability
25 of that horse for a racing justifies the purchase price and the necessary follow-on investment in training. Second, for those horses that are determined to be suitable for racing, embodiments also may determine which of the racing formats (i.e., distances) is most suited to that horse. For instance, embodiments may be used to determine whether the horse is best suited for sprints, middle-distance races, or longer-distance races such
30 as a mile or more. Since each type of event entails a different but expensive training regimen, it is imperative to direct the racing-capable horse to the most suitable event. By ensuring that horses are placed only into races of distances which they are cognitively suited to handle, such information would allow owners to avoid placing

unnecessary strain on their racing prospects that may ultimately lead to costly injuries and even breakdowns. Third, embodiments also may be applied to estimate the performance of a particular horse in a particular event. All three of these applications may be used individually or in combination.

5 [0057] In some embodiments, the facial analysis methods described above with reference to Figs. 15 and 16 may be applied to each horse in the field of a particular race to predict the outcome of the race based on mental or other suitability of the horses to particular racing conditions or situations. For example, in maiden horses races, where natural speed of the individual horses is not so great a factor as their lack of
10 racing experience, the disclosed facial analysis methods may be used to predict the horse most likely to win based on ability to adapt to the unfamiliar stress and distractions of a race day environment. The disclosed facial analysis methods may also be used to identify horses likely to place highly in races due to an innate “will to win”. It is a widely accepted idea within the horse racing industry that thoroughbred
15 racehorses run for different for different reasons. Most run simply because they are told, some run out of the pure joy of doing what they were bred to do, but true champions run because they come to understand the meaning of victory and thirst for the praise and attention of the winner’s circle. In the final furlongs of long-distance, classic-format races, where all horses suffer from the exhaustion of considerable lactic
20 acid build up, the courage to rally back and claim the win is especially important in determining the outcome of the race. In the same manner, the disclosed facial analysis methods may be used to predict horses unlikely to place highly in races due to an innate unwillingness to run at the front of or beyond the pack due either to an inherent lack of confidence, submissive nature, or general inability to overcome herd mentality in the
25 simulated fight-or-flight scenario of a race environment.

[0058] Embodiments of the disclosed facial analysis methods may also be used to predict the performance of a racehorse and their subsequent placing in a specific race based their response to variable racing conditions. Some horses become nervous and tire quickly in high-traffic races with considerable bumping, and would therefore likely
30 run poorly in large or closely matched fields. Similarly, some especially sensitive horses loose heart quickly when running at the back of a large pack where dirt from the other horses hooves is kicked up into their face, indicating that these horses will likely not place well in races with large fields where their chances of breaking at the front is

greatly reduced or under muddy track conditions. When the innate responsiveness of an individual horse to such racing conditions – as predicted by the disclosed facial analysis methods – is taken into consideration with the their previous performances under standard racing conditions (i.e., racing history) and the predicted performances of the other horses in the field, the movements of horses within the field during the race and their final placing can be predicted by employing the disclosed facial analysis methods. Thus, the methods can be used to predict the performance of an individual horse in a particular race. Various conditions or factors can be accounted for by the method, or simply the distance of the race may be used.

5 [0059] While the methods to predict the outcome of a race are described with respect to horses, the same method may be deployed with other animals that compete or race, for example, dogs or camels.

[0060] In other embodiments, the methods described above with reference to Figs. 15 and 16 may be used to predict non-performance-related characteristics for a particular breed of horse such as temperament, human interaction, cognitive ability, suitability for a particular task, load-bearing ability, pain tolerance, and/or desirability for breeding. For example, embodiments may determine whether a horse is suitable for use in a therapeutic riding program for children and/or adults with disabilities. In the same manner, embodiments may be applied to aid in matching a particular horse with a particular human disability. For example, embodiments may be used to predict that a particular horse is best suited for persons with cognitive disabilities and that another horse is best suited for persons with physical (non-cognitive) disabilities.

20 [0061] By way of example, embodiments may predict from facial features whether a horse will be cognitively suited to a challenging career as a therapy horse. Most therapeutic riding (also known as “hippotherapy”) programs are characterized by limited resources and volunteer experience that often severely restrict the amount of training that can be invested into new therapy horses. For a horse to be successful in such a program, they must have an innate tolerance for the challenging circumstances such as the often colorful and often loud training tools and the discomfort of the claustrophobic and cumbersome riding apparatuses standardly used in therapeutic riding sessions. Such horses must also be incredibly patient and tolerant of the fast, unpredictable, and at times even painful movements of their riders both in the saddle and on the ground.

[0062] By using the method described above with reference to Fig. 15, a facial analysis model capable of accurately assessing whether an individual horse innately possesses such characteristics may be developed via statistical analysis of common facial structures readily identified within populations of well suited working therapy mounts. By applying such a model as described above with reference to Fig. 16, therapeutic riding programs can predict which horses would be suitable for working under these challenging conditions, drastically reducing the time and resources that they must invest selecting new therapy mounts.

[0063] In other embodiments, a facial analysis model can be developed and applied, as described above with reference to Figs. 15 and 16, to match riders of varying physical and cognitive disabilities to the most appropriate mount. As experience has shown, many therapy horses prove best suited to a specific type of rider. For example, larger and/or older persons suffering from physical disabilities that limit their motor control on the horse, or which can lead to uncontrolled cramping, often work best with calmer and somewhat aloof mounts that are capable of ignoring the discomfort of their rider's limitations. Alternatively younger and/or smaller persons, or those suffering from cognitive disabilities, often benefit from more sensitive and engaged horses that are able to readily pick up on their fears and respond appropriately to comfort them and build confidence. A facial analysis model capable of accurately predicting such characteristics as sensitivity and engagement that readily distinguish between horses best suited to physically or cognitively disabled riders, thereby allowing therapeutic riding programs to more easily match new clients to the most appropriate horse and avoid the strain of poor pairings felt by both riders and horses.

[0064] By way of example, facial images of a statistically significant number of working therapy horses that have proven well suited for riders with cognitive disabilities are analyzed to determine desired characteristic physical features, as described above with reference to Fig. 15. This establishes a model for predicting a candidate horse's suitability for this particular therapeutic riding task. Subsequently, new candidate horses may be measured and their suitability for use as a therapeutic horse for riders with cognitive disabilities may be predicted using the method described above with reference to Fig. 16. Investment in therapeutic horse training can be directed to those horses that are predicted to be suitable in this manner.

[0065] Embodiments may also be used as a preventative measure in horses against the development maintenance-based vices. The competitive lifestyles of high-performance show and racehorses are typified by high-concentrate diets, extended periods of stall confinement, and excessive stress. By nature, horses are adapted both mentally and physiologically to highly mobile lifestyles consisting primarily of long periods of time obtaining and digesting high-fiber, forage-based diets. When subjected to the unnatural conditions such as 24-hour stall confinement and limited activities that occupy their time, many horses develop undesirable behaviors such as cribbing, weaving, and stall walking. These behaviors ultimately may be destructive both to facilities and to the horse's health. Some horses are by nature at a higher risk of developing these vices as a function of their innate personalities. Once developed, these undesirable behaviors are difficult to change. The methods described above with reference to Figs. 15 and 16 could be used to predict horses likely to exhibit these behaviors, so that preventative maintenance solutions could be employed before these behavioral patterns become established.

[0066] Since the domestication phenotype is common across many species of animals, embodiments, including those described above, are applicable to a broad range of animals, both mammals and non-mammals, such as donkeys, cattle, oxen, llamas, sheep, goats, turkey, geese, dogs, foxes, cats, ferrets, camels, geese, chickens, pigs, fish, etc. For example, embodiments may be used to predict a characteristic, such as mothering ability, of a sow based upon the anatomical structures of the sow's face. One suitable metric of mothering ability is the expected number of mash deaths that a sow would incur per litter of piglets. Initially, one or more digital images of a sow's face (e.g., front, profile, and/or top views) are obtained and stored in a memory operably connected to a digital computer. Additional data may be associated with the images, such as mash death statistics, which may be obtained from farrowing records regularly kept for hog farms. This step may be repeated as necessary based upon the number of sows in a group of interest.

[0067] Next, for each sow of interest, a plurality of reference points are added to the one or more stored images in a manner such as described above with reference Figs. 15 and 16. Using these reference points, a plurality of facial measurements are determined from the one or more stored digital images for each sow of interest. The plurality of facial measurements may be – but are not necessarily – similar to the ones

for horses discussed above with reference to Figs. 1 through 13. Relationships between each of the facial descriptor measurements and the additional data of the sample library are then determined. Using these relationships, facial descriptor measurements are selected and an optimal combination of the selected facial descriptor measurements is determined, based on being most predictive of the actual mash death statistics of the sows in the sample library. Statistical techniques such as those described above with reference to Figs. 18-21 may be used in the subset selection, or any other appropriate techniques known to persons skilled in the art may be used.

[0068] The selected facial descriptor measurements and the optimal combination then can be applied to determine the mothering ability characteristic of a particular sow based on the facial descriptor measurements for that animal, in the manner described above with reference to Fig. 16. In other words, the combination of measurements selected based on the sample library may be applied to sows of interest outside the sample library to predict the mothering ability of those animals. As this embodiment is applied to new sows, the sample library can be augmented by adding the images, additional data, and facial descriptor measurements for these animals. Selection of facial descriptor measurements and their optimal combination then can be carried out using the augmented sample library, in the same manner as described above and illustrated in Fig. 16.

[0069] In this manner, using facial descriptor measurements, an embodiment can be used to predict animal characteristics such as number or percentage of mash deaths per litter that a sow would be naturally inclined to incur. Furthermore, other embodiments utilize these predicted characteristics to determine management and/or maintenance strategies to use for individual high-risk sows. These strategies may include increasing supervision, using larger pens, moving piglets off a sow to reduce litter size, etc. Selection of one or more of these strategies may be based on a sow's predicted mash death rate and, optionally, one or more environmental factors such as farrowing crate dimensions, etc. and/or one or more other factors such as the sow's age, size, weight, and average litter size.

[0070] In some embodiments, other non-facial measurements or metrics that relate to influences on the behavioral development of an animal during the key imprinting windows of early life may also be used in combination with the facial measurements in the analysis. For example, and without limitation, such non-facial measurements or

metrics may include birth weight, sow weaning weight, litter weight percentile, gender composition of litter, age, litter number, nursery pen weight percentile, finishing pen weight percentile, gestation weight percentile, and leg length. In other embodiments, the predicted mothering behavior may be used to select gilts as replacements for a maintenance rotation, allowing swine farmers to avoid the financial loss of feeding gilts to farrowing age only to have them prove unsuitable as mothers.

[0071] Other embodiments may be used to determine maintenance and/or management strategies for one or more animals, as illustrated in Fig. 17. In step 1700, one or more optimal combinations of facial descriptor measurements are selected for predicting one or more characteristics of interest for a particular type of animal. Step 1700 may be carried out according to the method described above with reference Fig. 15, or in other ways within the scope of the present embodiment. The one or more characteristics of interest preferably are related to the maintenance and/or management strategies under consideration. As discussed above, step 1700 may include generation of a sample library for a particular type of animal comprising digital images, additional data, and a plurality of facial descriptor measurements. The facial measurements may be – but are not necessarily – similar to the ones for horses discussed above with reference to Figs. 1 through 13. Non-facial physical measurements may also be used with the method.

[0072] In step 1702, digital images and additional data for a particular animal of interest are obtained and stored, in the same manner as described above with reference to the sample library (e.g., step 1500 of Fig. 15). In step 1704, reference points consistent with those added to the images in the sample library are added to the images of the animal of interest. In step 1706, facial descriptor measurements consistent with those in the sample library are calculated for the animal of interest. In step 1708, the one or more optimal combinations determined in step 1700 are applied to the facial descriptor measurements of the individual animal to predict the characteristic of interest, in a manner such as described above with reference to Fig. 16. Steps 1702 through 1708 are repeated for each individual animal included in the maintenance and/or management strategy. In step 1712, the predicted characteristics of interest for the individual animals are used to predict one or more characteristics for the group of animals. Finally, in step 1714, the predicted group characteristics and/or predicted individual characteristics are used to determine a maintenance and/or management

strategy for the group of animals. Other factors and information may be used in either or both of steps 1712 and 1714, including factors related to individual animals, factors related to the group of animals, and/or factors related to the environment of the animals.

[0073] By way of example, the embodiment illustrated by Fig. 17 may be used to

5 predict aggression-related characteristics of individual sows and to what extent certain combinations of sows will cohabitate in a gestation pen without harming each other. Step 1700 may include selecting facial descriptor measurements and an optimal combination of the selected facial descriptor measurements that is most predictive of characteristics related to fighting in a gestation pen. Example characteristics include
10 food aggression, territoriality, dominance in novel environments, etc. Statistical techniques such as those described above with reference to Figs. 18-21 may be used to select the facial descriptor measurements and their optimal combination(s). Other appropriate statistical techniques known to persons skilled in the art also may be used. To the extent that characteristics related to fighting in a gestation are independent or not
15 fully correlated with each other, multiple subsets of facial descriptor measurements and/or multiple optimal combinations may be selected to predict the respective characteristics.

[0074] The selected facial descriptor measurements and optimal combination then can be applied to predict or estimate an individual sow's natural aggression/dominance level
20 in each relevant personality characteristic. Information other than the facial descriptor measurements may be incorporated into this prediction or estimate, including the masculinity ratio of the sow's lactation litter, which indicates the level of testosterone that the sow was exposed to during conception, and weight rank of the sow within its lactation litter.

25 [0075] Furthermore, in some embodiments, this prediction or estimate of a sow's aggression-related characteristics may be used to predict the outcome of that sow's social interactions with one or more other sows in a gestation pen, or an overall level of aggressive behavior in a gestation pen. For example, observations about the number of gestation pen fights and the predicted aggression-related characteristics for sows of
30 interest may be used to determine a weighted model for gestation pen aggression that is independent of the composition of animals within a pen. Alternately, these observations and predictions of aggression-related characteristics may be used to

predict or estimate the number of fights a particular sow would engage in a gestation pen with a particular composition of animals.

[0076] More specifically, observations and predictions of aggression-related characteristics may be used to segment the sows of interest into multiple aggression levels or categories, such as I (“Dominant Aggressive”) II (“Subordinate Defensive”), and III (“Submissive Evasive”),. After sows of interest are categorized accordingly, a group characteristic such as the frequency of social aggression can be computed based on the number of animals of each category in the pen. A group characteristic such as the frequency of social aggression among sows cohabitating in a gestation pen also can be predicted by first averaging each of the selected facial descriptor measurements across all individuals comprising the group and then computing an optimized linear combination of the group averages.

[0077] By further example, a group characteristic such as aggression level can be predicted according to the method illustrated in Fig. 17 as follows. First, the optimal combination of facial descriptor measurements determined in step 1700 can be utilized according to steps 1702 through 1710 to predict the social aggressiveness of individual sows in the group. Next, the set of predicted social aggression levels can be combined optimally to form a predictor of the level of social aggression within the group. In other words, the predicted social aggression level for the i th sow in the group can be expressed as $SA_i = a_1 \cdot F_1 + a_2 \cdot F_2 + \dots + a_M \cdot F_M$, where $F_1 \dots F_M$ are the selected facial descriptor measurements and $a_1 \dots a_M$ are the optimal linear combining coefficients. Likewise, if the group comprises N individual sows, the predicted group social aggression can be expressed as $GSA = b_1 \cdot SA_1 + b_2 \cdot SA_2 + \dots + b_N \cdot SA_N$, where $b_1 \dots b_N$ are the optimal linear combining coefficients for the group. Furthermore, in the combined group model, the individual sows may be ordered in a variety of ways. For example, the predicted individual aggression levels $SA_1 \dots SA_N$ may be rearranged in descending numerical order $SA'_1 \dots SA'_N$, with SA'_1 corresponding to the most aggressive sow. In such case, each optimal coefficient b_i may be selected, at least in part, based on the position within the group. This would allow, for example, coefficients b_i to be selected to emphasize the characteristics of the most aggressive and/or submissive animals in the group.

[0078] Group dynamics and group characteristics such as aggression level among a group of sows in a gestation pen can be predicted in various other ways known to

persons skilled in the art. For example, methods may be employed that are analogous to the Hartree–Fock equation, which is commonly used to predict the behavior of the electrons in an atom. Alternately, a computational method based on a NETLOGO model can be used. An advantage of this approach is that factors other than the aggression-related behavior traits predicted from the facial descriptor measurements can be incorporated. Such factors may include the estimated activity level and the resulting number of interaction between animals in a pen, as well as environmental factors such as crowding.

[0079] While the group dynamics and group characteristics have been described with references to pigs, the same or similar methods and systems can be applied to various other animals. In some embodiments, the disclosed methods may be used to determine appropriate pasture assignments on horse boarding facilities, where pasture injuries can at best be aesthetically unpleasing in show horses and at worst permanently crippling and costly. In other embodiments, the disclosed methods may be used to identify which dogs are behaviorally suited to group-pen housing in kennel situations, and those that need individual enclosures to minimize fighting.

[0080] Persons of ordinary skill in the art would understand that any of these computational methods may be embodied in various combinations of hardware and software. For instance, the computations may be carried out by a specialized or general-purpose digital computer, such as a laptop, desktop, tablet, smartphone, workstation, etc. Moreover, this hardware may be programmed to carry out such computations in various ways, such as by programs written in human-readable languages such as C, C++, etc. and compiled into machine-readable code for execution.

Alternately, the methods may be expressed in the particular language of a specialized computational software package, such as Matlab, which are further interpreted and/or compiled into machine-readable code. In the same manner, computerized selections may be carried out by accessing one or more electronically stored database(s) comprising information about the animal of interest; other animals of the same type, species, or breed; environmental factors; and other relevant information.

[0081] For example, Fig. 22 shows various hardware and software embodiments of a system according to embodiments of the present disclosure. Various hardware devices – such as digital camera 2204, smartphone 2206, cellular phone 2208, tablet computer 2210, and laptop computer 2212 – may be used to capture a digital image of an animal

of interest, such as the exemplary horse 2202. The image-capturing device may then store the image in a memory operably connected to a digital computer. This may be carried out in various ways as illustrated in Fig. 22. For example, the image capturing device may transmit the image through network 2216 via wireless access point 2214 to
5 digital computer 2220, which may be a desktop computer, server, workstation, or the like. Moreover, wireless access point 2214 may be a cellular base station, wireless LAN access point, Bluetooth access point, or any other wireless connection known to persons of ordinary skill in the art. Likewise, network 2216 may be a local- or wide-area, public or private network, or any combination thereof, including an intranet and/or
10 the Internet.

[0082] In other embodiments, the image capturing device transfers the captured digital image to digital computer 2220 through a wired connection 2222, such as a Universal Serial Bus (USB) connection. In yet other embodiments, the captured image(s) may be transferred by removing a memory card from the image capturing
15 device and inserting it into memory card reader 2224 of digital computer 2220, which may copy the captured images to other memory accessible by or operably connected to digital computer 2220. Also within the spirit and scope of the present disclosure, the image capturing device may transfer the image, via methods described above or otherwise well known in the art, to devices other than digital computer 2220, such as
20 tablet computer 2210. In such embodiments, further processing according to the methods describe above will occur, for example, in tablet computer 2210 rather than in digital computer 2220. Similarly, the image capturing device may transfer the image to network storage unit 2226 that is accessible via network 2216, e.g., cloud storage.
Network storage unit 2226 may be configured to be accessible by some or all of the
25 other devices shown in Fig. 22.

[0083] In other embodiments, further processing according to the methods described above also may take place in the image capturing device itself. For example, tablet computer 2210 may be used to capture images of animals of interest, store the images in memory accessible or operably connected to it (including, for example, network storage
30 unit 2226), and then execute one or more software applications embodying one or more methods described above. Specific measurements or processed data from the image capturing device may also be communicated to a central computer or central location.

[0084] Although embodiments described above are related to predicting characteristics of animals, other embodiments within the scope of the present disclosure may be used to predict certain characteristics of humans via methods employing facial descriptor measurements. During progressive stages of human embryonic growth, development of the brain and face remains intimately connected through both genetic signaling and biomechanical/biochemical mechanisms. The face develops from populations of cells originating from the early neural crest, with cells from the neural tube gradually shifting to form the prominences of the face. Differentiation of these early cells is closely regulated through intricate genetic signaling mechanisms, with the brain essentially serving as the platform on which the face grows. As these two structures continue to grow and develop during the later embryonic stages, their phenotypes remain closely linked as complex genetic hierarchies regulate patterns of cross talk between molecules, cells, and tissues.

[0085] The close relationship between the functional development of the brain and structures of the face has been clearly documented for a number of developmental disorders. Among the most well known of these disorders is Fetal Alcohol Syndrome (FAS), which is the direct result of exposure of the fetus to alcohol during pregnancy. FAS has been shown to result in both an easily identifiable phenotype (i.e., collection of minor facial abnormalities such as small eyes, smooth philtrum, thin upper lip) and developmental damage to the central nervous system that is often permanent (e.g., speech delays, learning disabilities, poor reasoning skills, poor memory, attention deficit disorders, and low IQ). Figs. 23 through 30 show a set of fifteen (15) human facial descriptor measurements that can be used to identify the phenotype associated with FAS. For example, Figs. 23A through 23F show various facial descriptor measurements related to the eye, while Figs. 28 and 30 show various facial descriptor measurements related to the philtrum. Nevertheless, this set of human facial descriptor measurements is merely exemplary, and the person of ordinary skill will recognize that fewer than the entire set may be used to predict FAS. Furthermore, this set of human facial descriptor measurements is not exhaustive and others may be incorporated, such as with the set of fifty-six equine facial descriptor measurements shown in Figs. 1 through 13. In some embodiments, two, three, or more of the facial descriptor measurements are used in combination to predict a trait, characteristic, or syndrome such as FAS.

[0086] While examples are shown primarily with facial measurements, other head measurements and physical measurements may be used alone, without facial measurements, or in combination with facial measurements. For example, measurements of the head or crown may be used in conjunction with facial features to predict syndromes or traits.

[0087] By way of further example, Down syndrome is another prenatal developmental disorder causing mental/social delays that yields an easily identifiable phenotype including a host of distinctive facial features such as small chin and/or mouth, round face, and rounded almond-shaped eyes. Recent studies have even been able to identify measurable trends in facial features that distinguish between children diagnosed with Autism Spectrum Disorders (ASD) and those of typical development. The facial descriptor measurements shown in Figs. 23 through 30 may also be used to identify the phenotype associated with Down syndrome. However, as with FAS described above, this set of facial descriptor measurements is merely exemplary, and may be reduced or augmented for predicting Down syndrome or other human functional development disorders within the spirit and scope of the present disclosure.

[0088] Given these established relationships between human facial structures and cognitive development, any of the computationally inexpensive, two-dimensional, locally-normalized facial evaluation systems described provides a non-invasive analysis tool for use in multiple clinical applications. For example, embodiments of the facial analysis methods and systems disclosed herein will diagnose children with specific cognitive development disorders based on the degree of divergence between their facial features and those of the overall typical population with respect to the phenotype for a disorder. Such a diagnosis tool is faster and less invasive than the standard cognitive testing procedures currently employed, and may allow for earlier diagnosis and interventions. More computationally expensive embodiments or variations may also be used for diagnosis.

[0089] In the same manner, embodiments of the facial analysis methods and systems disclosed herein can be used for predicting cognitive disorders that vary in degree of severity (e.g., FAS and Down Syndrome) or which present as a spectrum of disorders (e.g., ASD,). Such embodiments utilize metrics such as continuously-valued, facial descriptor measurements to produce multivariate models capable of predicting severity or types of symptoms displayed. For example, a facial analysis model derived using

methods described herein could be used to statistically predict a child's score on the Childhood Autism Rating Scale (CARS). CARS is a diagnostic standard that uses behavioral observations and testing to differentiate between Autism and other types developmental disorders and to quantify the severity of the disorder along a scale.

5 [0090] By way of further example, a facial analysis model derived using methods described herein can be used to predict which category, class, and/or subclass of a particular cognitive disorder that a particular individual falls within. For example, a model based on a plurality of facial measurements will predict whether a particular individual is better diagnosed with classic autism or with Asperger's syndrome. This
10 predicted classification could be used by itself, or in conjunction with other qualitative and/or quantitative diagnostic methods, to develop of the most appropriate and effective plan for early therapeutic intervention and treatment.

[0091] Embodiments of the facial analysis methods and systems disclosed herein also can be used for predicting or inferring certain characteristics of human individuals that
15 do not have cognitive or developmental disorders. For example, a model based on a plurality of facial measurements may be used in the manner described above with reference to Figs. 15 and 16 to predict a particular individual's innate personality such as aggression and competitiveness. One or more of the facial descriptor measurements shown in Figs. 23 through 30 may also be used for this purpose. As described above,
20 however, this set of facial descriptor measurements is merely exemplary and may be reduced or augmented as necessary within the spirit and scope of the present disclosure. Furthermore, multivariate analysis of a plurality of facial measurements statistically normalized against like measurements of a standard population of individuals can be used to predict other variable aspects of innate personality such as aggression,
25 dominance, conscientiousness, compassion, extroversion, IQ, etc. Insight into such personality traits of an individual could be used as an inference tool to predict various aspects of behavior and performance such as learning styles, athletic performance, business decisions, etc.

[0092] For example, facial and other physical measurements of successful left-handed
30 baseball pitchers can be made and compared with measurements of a standard population. Digital images and reference points may be used to ease the burden of the measurement process. Ratios, angles, or nominal measurements may be used instead of or in addition to actual measurements. A number of metrics may then be analyzed to

find those metrics which show the greatest correlation or significance in determining statistically whether a person is more likely than another to be a successful left-handed pitcher. Once the more significant metrics are identified, the system may simply rely on those metrics to predict a person's strength or likelihood to succeed as a left-handed pitcher. A baseball scout may use the system as a tool to assist in choosing one left-handed pitching prospect over another by scoring both candidates. Those skilled in the art will recognize numerous applications of the methods and techniques described throughout the specification to humans.

[0093] In other embodiments of the methods and systems disclosed herein, facial analysis of both animals and humans can be used to pair a person (i.e., a human being) with a particular animal based on the degree that their personalities complement each other. For example, a model based on a plurality of facial measurements could be developed and applied in the manner described above with reference to Figs. 15 and 16 to predict the personality characteristics of a variety of horses that are available for clients of a therapeutic riding program. When a new client enrolls with the program, facial analysis is also used to predict the client's relevant characteristics, e.g., self-awareness. With this information, the program could then find the horse with facial features that correspond to characteristics that are necessary to accommodate this client, e.g., high pain tolerance levels and high responsiveness needed since the client is likely to lose their balance frequently. By the same token, if a facial analysis program indicated that a new autistic client is easily frustrated and likely to act out, then it could pair that client to a horse with facial features that indicate high tolerance levels that allow them to deal with the loud noises and fast movements, as well as some degree of stubbornness to stay on task even when the client is not doing what they are supposed to be doing.

[0094] Additionally, these embodiments can be used in a wide variety of applications to identify or predict the optimum or most appropriate combination of a human and animal. For example, for a particular type of event or race, horses may be paired with their most appropriate riders – or vice versa – thereby optimizing the competitive performance of the pair. Moreover, in training environments, horses may be matched with the most appropriate trainer to improve communication and cohesiveness and increase learning potential. By the same token, young riders may be matched to the horse that will best accommodate their needs. Similarly, embodiments may be used in

non-equine applications such as to match seeing-eye dogs to the best owners or drug/bomb dogs to the best suited handlers based on the unique personalities of animal and human.

[0095] A method according to this embodiment is shown in Fig. 31. In this method, it is assumed that facial descriptor measurements were previously computed for the set of animals of interest, e.g., the horses available in a therapeutic riding program, and matched to a single human of interest. However, a person of ordinary skill will easily recognize that the facial descriptor measurements could be pre-computed for a set of humans, e.g., clients at a therapeutic riding program, and matched to an animal of interest, e.g., a new horse. In block 3100, digital images and additional data is obtained and stored for a human, such as in the manner described previously with reference to the sample library (i.e., block 1500 of Fig. 15). In block 3102, reference points consistent with those of the images in the sample library are added to the images of the human. In block 3104, facial descriptor measurements are calculated for the human. For example, the reference points and facial descriptor measurements may be those shown in Figs. 23 through 30, augmented by additional facial descriptor measurements as necessary.

[0096] In block 3106, a combination of one or more of the facial descriptor measurements of the human and one or more of the facial descriptor measurements of a particular animal of interest (e.g., a horse) are used to predict the relevant characteristics of that particular human-animal combination. Block 3108 determines whether or not to repeat block 3106 for another animal of interest. After determining the relevant characteristics for each particular human-animal combination, in block 3110 the animal providing the best match to the human is selected based on the relevant characteristics of human-animal combination. Persons of ordinary skill will recognize that Fig. 31 may be adapted to other embodiments by combining facial descriptor measurements for an individual animal with previously computed facial descriptor measurements for a plurality of humans to select the best combination.

[0097] To find suitable pairings of animals and humans, any of the embodiments described above may be used to determine characteristics of the animal and any of the embodiments described may be used for determining characteristics of humans. Other physical metrics in addition to facial features may be used. The results of the animal characteristics and human characteristics are analyzed for suitability, best fit or a match.

[0098] Moreover, the terms and descriptions used herein are set forth by way of illustration only and are not meant as limitations. Those skilled in the art will recognize that many variations are possible within the spirit and scope of the disclosure as defined in the following claims, and their equivalents, in which all terms are to be understood in
5 their broadest possible sense unless otherwise indicated.

What is Claimed is:

1. A method for predicting a characteristic of a type of animal, comprising:
for each of a plurality of individual animals of the type,
storing one or more digital images representing the individual animal in a
5 memory operably connected to a digital computer;
annotating the one or more digital images with a plurality of reference
points;
associating at least one other data value about the individual animal with
the one or more digital images representing the individual animal;
10 computing, with the digital computer, one or more metrics using the
plurality of reference points; and
selecting a combination of the one or more metrics for predicting the characteristic
of the animal.
2. The method of claim 1, wherein:
15 the selecting step further comprises determining one or more relationships
between the one or more metrics and the at least one other data value for the plurality of
individual animals; and
the combination is selected based on the one or more relationships.
3. The method of claim 1 wherein the animal is one of: a horse, a donkey, a
20 cow, an ox, a llama, a sheep, a goat, a dog, a camel, a goose, a chicken, a turkey, a ferret,
a cat, and a pig.
4. The method of claim 1, wherein the one or more metrics comprise at least
one metric selected from a head measurement group comprising:
AR01_Degree of Facial Inflexion;
25 AR01_Degree of Nose Rounding;
AR01_Face Thickness Proportion;
AR01_Forehead Slope Proportion;
AR01_Forehead Height Proportion;
AR01_Forehead Length Proportion;
30 AR01_Nose Length Proportion;
AR01_Nose Roundness Proportion;
AR01_Nostril Position Proportion;
AR02_Degree of Facial Protuberance;

- AR03_Jowl Protuberance Proportion;
- AR03_Jowl Roundness Proportion;
- AR03_Jowl-to-Underline Proportion;
- AR04_Forehead Height Angle
- 5 AR04_Full Angle Face;
- AR04_Mouth Inflexion Angle;
- AR04_Muzzle Roundness Proportion;
- AR04_Muzzle Size Proportion;
- AR04_Muzzle Slope Angle;
- 10 AR05_Chin Firmness Proportion;
- AR05_Chin Fullness Proportion;
- AR05_Chin Length Angle;
- AR05_Chin Thickness Angle;
- AR05_Chin Width-to-Height Proportion;
- 15 AR05_Lip Length Proportion;
- AR06_Lip Protuberance Proportion;
- AR06_Mouth Length Proportion;
- AR07_Degree of Nostril Flutedness;
- AR07_Degree of Nostril Roundness;
- 20 AR07_Inner Nostril Convergence Proportion;
- AR07_Nose Width-to-Height Proportion;
- AR07_Nostril Length Proportion;
- AR07_Nostril Width Proportion;
- AR08_Degree of Lip Inflexion;
- 25 AR09_Degree of Ear Flare;
- AR09_Ear Inflexion Proportion;
- AR09_Ear Roundness Proportion;
- AR09_Ear Width-to-Breadth Proportion;
- AR10_Ear Rotation Proportion;
- 30 AR10_Ear Set Angle;
- AR11_Eye Height Proportion;
- AR11_Eye Extrema Intersect Angle;
- AR11_Eye Height-to-Length Proportion;

- AR11_Eye Height Proportion;
 AR11_Eye Orbital Lateral Protuberance Proportion;
 AR11_Eye Protuberance Proportion;
 AR11_Eye Roundness Proportion;
 5 AR11_Eye Size Proportion;
 AR11_Eye Size Proportion_{Length};
 AR11_Lower Minima Point Proportion Eye;
 AR11_Top Eye Angle;
 AR11_Upper Maxima Point Proportion Eye;
 10 AR12_Forehead Width Angle;
 AR13_Cheek-to-Zygomatic Height Proportion; and
 AR13_Zygomatic Ridge Angles.
5. The method of claim 4, wherein the one or more metrics comprise at least two metrics selected from the head measurement group.
- 15 6. The method of claim 1, wherein each of the one or more metrics is one of the following types: absolute distance, normalized distance, angle, area, absolute volume, volumetric ratio, and solid angle.
7. The method of claim 1, wherein the annotating step comprises entering using a graphical user interface.
- 20 8. The method of claim 1, wherein the annotating step comprises populating automatically based on a stored profile relating to the type of the animal.
9. The method of claim 1, wherein the one or more characteristics are one or more of: temperament, cognitive ability, performance, suitability for a particular task or event, aggressiveness, social interaction in groups, mothering ability, and desirability for
 25 breeding.
10. The method of claim 1, wherein at least one of the one or more digital images is a three-dimensional image.
11. A method for determining a characteristic of an animal based on one or more metrics related to the animal, comprising:
 30 storing one or more digital images representing the animal in a memory operably connected to a digital computer;
 annotating the one or more digital images with a plurality of reference points;

computing, with the digital computer, the one or more metrics using the plurality of reference points; and

predicting the characteristic of the animal based on the one or more metrics.

12. The method of claim 11, wherein the predicting step further comprises:
5 computing a combined metric based on a predetermined function of the one or more metrics; and

predicting the characteristic based on the combined metric.

13. The method of claim 12, wherein the combined metric is calculated using a non-linear combination of the one or more individual metrics.

10 14. The method of claim 13, wherein the non-linear combination is determined using one of Newton's Method and Lagrange's Method.

15. The method of claim 12, wherein the predetermined function is determined from one or more metrics relating to a plurality of other animals of the same type as the animal.

15 16. The method of claim 11, wherein the characteristic relates to one or more of a) the discipline or type of event most suitable for the animal, and b) the expected performance of the animal in a particular discipline or type of event.

17. The method of claim 11, wherein the predicting step is performed using a computer.

20 18. The method of claim 11, wherein the animal is one of: a horse, a donkey, a cow, an ox, a llama, a sheep, a goat, a dog, a camel, a goose, a chicken, a turkey, a cat, and a pig.

19. The method of claim 11, wherein predicting the characteristic of the animal is further based on at least one of: a) additional information related to the animal;
25 and b) information related to the environment in which the animal will be kept.

20. A method for predicting one or more characteristics of a group of animals of the same type, comprising:

for each of the individual animals comprising the group,

30 storing one or more digital images representing the individual animal in a memory operably connected to a digital computer;

annotating the one or more digital images with a plurality of reference points;

computing, with the digital computer, one or more metrics using the plurality of reference points;

predicting one or more characteristics of the individual animal based on the one or more metrics; and

5 predicting the one or more characteristics of the group of animals based on the predicted one or more characteristics of the individual animals comprising the group.

21. The method of claim 20, further comprising determining a strategy for maintaining or managing the group of animals based on the predicted one or more
10 characteristics of the group of animals.

22. The method of claim 20, wherein predicting one or more characteristics of the individual animal further comprises:

 computing one or more combined metrics, each based on a predetermined function of the one or more metrics; and

15 predicting the one or more characteristics of the individual animal based on the one or more combined metrics.

23. The method of claim 22, wherein the predetermined function is determined from the one or more metrics related to a plurality of animals of the same type as the individual animals comprising the group.

20 24. The method of claim 20, wherein predicting one or more characteristics of the group of animals further comprises:

 computing one or more group combined metrics, each based on a predetermined function of the predicted one or more characteristics of the individual animals comprising the group; and

25 predicting the one or more characteristics of the group of animals based on the one or more group combined metrics.

25. The method of claim 20, wherein predicting one or more characteristics of the group of animals further comprises:

30 for each of the one or more metrics, computing an average for the individual animals comprising the group; and

 computing one or more group combined metrics, each based on a predetermined function of the computed averages of the one or more metrics; and

predicting the one or more characteristics of the group of animals based on the one or more group combined metrics.

26. The method of claim 20 wherein the type of animal is one of: a horse, a donkey, a cow, an ox, a llama, a sheep, a goat, a dog, a camel, a goose, a chicken, a turkey, a cat, and a pig.

27. The method of claim 20 wherein predicting the one or more characteristics of the group of animals is further based on at least one of: a) estimated number of interaction between the individual animals comprising the group of animals; and b) information related to the environment in which the group of animals will be kept.

28. A system for predicting relative performance of a first horse in a race with one or more other horses, comprising:

a memory for storing one or more measurements of the first horse;

a computer adapted to:

calculate a performance indicator for the first horse using the one or more stored measurements; and

compare the performance indicator with an existing indicator, wherein the existing indicator reflects performance of at least one of the one or more other horses; and

an output device that displays a prediction of the first horse's relative performance in the race.

29. A method for calculating a rating for use in a rating system for horses comprising:

receiving measurements, wherein the measurements represent facial features of a horse;

calculating, with a processor, one or more indicators using the received measurements;

determining an alphanumeric rating using the one or more indicators.

30. The method of claim 29, wherein the alphanumeric rating is indicative of one or more of job suitability, riding discipline, racing distance, and expected performance.

31. A method for predicting a characteristic of a type of animal for an individual animal of the type, comprising:

measuring, using a computer, two or more metrics from reference points on a digital image representing the individual animal of the type;

calculating, using a computer, a resultant using the two or more measured metrics and a mathematical formula;

5 predicting, using a computer, a behavioral or performance characteristic of the individual animal using the resultant from the calculated mathematical formula for the individual animal of the type and data about a group of the type of animal; and

presenting the predicted behavioral or performance characteristic of the individual animal.

10 32. The method of claim 31 wherein the data about the group of the type of animal is calculated using the mathematical formula.

33. The method of claim 32 further comprising:
obtaining the digital image representing the individual animal of the type; and
assigning the reference points on the obtained digital image.

15 34. A computer readable medium comprising a set of instructions, which, when executed on a computing device causes the computing device to:

store one or more digital images representing an animal in a memory operably connected to the computing device;

20 annotate the one or more digital images with a plurality of reference points;
compute the one or more metrics using the plurality of reference points; and
predict the characteristic of the animal based on the one or more metrics.

35. The computer readable medium of claim 34, wherein the instructions that cause the computing device to predict the characteristic of the animal further cause the computing device to:

25 compute a combined metric based on a predetermined function of the one or more metrics; and

predict the characteristic based on the combined metric.

36. A computer readable medium comprising a set of instructions, which, when executed on a computing device causes the computing device to:

30 for each of a plurality of individual animals of a type of animal,

store one or more digital images representing the individual animal in a memory operably connected to the computing device;

annotate the one or more digital images with a plurality of reference points;

associate at least one other data value about the individual animal with the one or more digital images representing the individual animal;

5 compute one or more metrics using the plurality of reference points; and
select a combination of the one or more metrics for predicting a characteristic of the type of animal.

37. The computer readable medium of claim 36, wherein the instructions that cause the computing device to select a combination of the one or more metrics further
10 cause the computing device to:

 determine one or more relationships between the one or more metrics and the at least one other data value for the plurality of individual animals; and
select the combination based on the one or more relationships.

38. An apparatus for predicting a characteristic of a type of animal,
15 comprising:

 a memory wherein one or more digital images representing an animal are stored;
a processor, operably connected to the memory, adapted for:

 annotating the one or more digital images with a plurality of reference points;

20 computing the one or more metrics using the plurality of reference points;
and

 predicting the characteristic of the animal based on the one or more metrics.

39. The apparatus of claim 38, wherein the processor is further adapted to:
25 compute a combined metric based on a predetermined function of the one or more metrics; and

 predict the characteristic based on the combined metric.

40. A system for determining a characteristic of an animal based on one or more metrics related to the animal, comprising:

30 a memory wherein one or more digital images representing each of a plurality of individual animals of a type of animal are stored;

 a processor, operably connected to the memory, adapted for:

annotating the one or more digital images representing each of a plurality of individual animals with a plurality of reference points;

associating at least one other data value about each of the individual animals with the one or more digital images representing the respective individual animal;

computing one or more metrics for each of the plurality of individual animals using the plurality of reference points annotated on the one or more digital images representing the respective individual animal; and

selecting a combination of the one or more metrics for predicting a characteristic of the type of animal.

41. The system of claim 40, wherein the processor is further adapted to:

for each of the plurality of individual animals, determine one or more relationships between the one or more metrics and the at least one other data value for the respective individual animal; and

select the combination based on the one or more relationships.

42. The method or system of any one of the above claims wherein a human is substituted for the animal and a group of humans is substituted for the group of animals.

43. A method for determining a characteristic of a human or animal subject, comprising:

calculating two or more ratios based upon metrics related to a subject's head, wherein distances or angles between reference points on the subject's head are used;

predicting, using a computer and computations, a characteristic of the subject wherein the two or more ratios are used and wherein data about a group of subjects are referenced; and

providing the predicted characteristic to an output device.

44. A method for determining a characteristic of a person based on one or more metrics related to the person, comprising:

storing one or more digital images representing the person in a memory operably connected to a digital computer;

annotating the one or more digital images with a plurality of reference points;

computing, with the digital computer, the one or more metrics using the plurality of reference points; and

predicting the characteristic of the person based on the one or more metrics.

45. The method of claim 44, wherein the predicting step further comprises:
computing a combined metric based on a predetermined function of the one or
more metrics; and
predicting the characteristic based on the combined metric.

5 46. The method of claim 45, wherein the predetermined function is determined
from one or more metrics relating to a plurality of other persons having the same
characteristic.

47. The method of claim 46, wherein the characteristic relates to a
developmental disorder.

10 48. The method of claim 47 wherein the characteristic is a rating on the
childhood autism rating scale.

49. The method of claim 46, wherein the characteristic relates to athletic
performance.

15 50. The method of claim 44 wherein the metrics comprise at least one of ratios
or angles.

51. The method of claim 44, wherein the predicting step further comprises:
computing a combined metric based on a predetermined function of the one or
more metrics; and
20 predicting the characteristic based on the combined metric.

52. The method of claim 50, wherein the combined metric is calculated using
a non-linear combination of the one or more individual metrics.

53. The method of claim 51, wherein the non-linear combination is determined
using one of Newton's Method and Lagrange's Method.

25 54. The method of claim 51, wherein the predetermined function is determined
from one or more metrics relating to a plurality of other humans.

55. The method claim 54 wherein the predetermined function uses the two
most significant metrics.

30 56. The method of claim 44, wherein the characteristic relates to one or more
of a) type of sporting event most suitable for the human, and b) the expected
performance of the human in a particular position on a sports team.

57. The method of claim 44, wherein the predicting step is performed using a computer.

58. The method of claim 44, wherein the human is physically or mentally disabled.

5 59. The method of claim 44, wherein predicting the characteristic of the human is further based on at least one of: a) additional information related to the human; and b) information related to training the human has completed.

60. The method of claim 44 wherein the one or more digital images representing the person are digital images of the person's face and wherein the step of
10 annotating with a plurality of reference points comprises assigning reference points to locations on the person's face and wherein the locations include eyes.

61. The method of claim 44 wherein the one or more metrics comprises two or more of the following: Eye Extreme Intersect Angle, Eye Depth Proportion, Eye Height Proportion, Eye Length-to-Height Proportion, Lower Eye Angle, Upper Eye Angle, Mid-
15 Face Width Proportion, Upper Eyelid Proportion, Palpebral Angle, Eye Roundness Proportion, Philtrum Definition Proportion, Upper Lip Thickness Proportion, Lower Lip Thickness Proportion, and Philtrum Length Proportion.

62. The method of claim 44 further comprising the step of communicating to a display device and displaying on the display device the predicted characteristic.

20 63. A system for determining a characteristic of a person based on two or more metrics related to the person, comprising:

a memory, wherein one or more digital images representing the person are stored;

a processor, operably connected to the memory, adapted for :

accessing the one or more digital images from the memory;

25 annotating the accessed one or more digital images with a plurality of reference points;

calculating the two or more metrics using the plurality of reference points;

predicting the characteristic of the person based on the two or more

metrics; and

30 communicating the predicted characteristic of the person.

64. A method for choosing a combination of a person and an animal for a particular task, comprising:

computing, using a digital computer, one or more metrics related to the person;

computing, using a digital computer, one or more metrics related to each of a plurality of animals;

5 computing, using a digital computer, a combination characteristic related to the combination of the person with each of the plurality of animals, based on at least a portion of the one or more metrics related to the person and at least a portion of the one or more metrics related to each of the plurality of animals; and

determining the combination of the person and one of the plurality of animals based on the computed combination characteristics.

65. A method for choosing a combination of a person and an animal for a particular task, comprising:

10 computing, using a digital computer, one or more metrics related to the animal;
computing, using a digital computer, one or more metrics related to each of a plurality of persons;

15 computing, using a digital computer, a combination characteristic related to the combination of the animal with each of the plurality of persons, based on at least a portion of the one or more metrics related to the animal and at least a portion of the one or more metrics related to each of the plurality of persons; and

determining the combination of the animal and one of the plurality of persons based on the computed combination characteristics.

1 / 65

Facial Descriptor Name: Degree of Facial InflexionAnatomical Region of Face: AR01_FacialProfileGeneral Description:

Describes the degree of structural concavity/convexity of the *True Line of the Face*. Differentiate between a concave "dished", convex "roman", or straight bone structure.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$$

finds the angle for $\angle BAC$, denoted here as θ

$$d = \sin(\theta) * \overline{AC}$$

finds the height of triangle $\triangle ABC$, the distance of facial inflexion

$$M_{AB} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of line $\overline{AB}$

$$Q_x = \left(\frac{C_y - A_y}{M_{AB}} \right) + A_x$$

finds the x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C

$$\sigma = Q_x - C_x$$

finds a value for which σ is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face

$$\sigma_s = \frac{\sigma}{|\sigma|}$$

finds σ_s here defined of the Constant of Concavity with magnitude 1 indicating direction of inflexion via sign (+)

$$DoFI = \sigma_s * \left(\frac{d}{\overline{AB}} \right)$$

*finds the **Degree of Facial Inflexion**, here defined as the degree of perpendicular deviation of the Upper Profile of the skull from the **True Line of the Face** relative to the overall length of the face.*




Fig. 1A

2 / 65

Facial Descriptor Name: Degree of Nose RoundingAnatomical Region of Face: AR01_FacialProfileGeneral Description:

Describes the degree to which the boney structures of the nose rounds away from the true line of the face. Partially differentiates between "Roman" and "Moose" noses.

Mathematical Proof

$$M_{uc} = \frac{(A_y - C_y)}{(A_x - C_x)}$$

finds the slope of line AC

$$N_x = B_x - (A_x - B_x)$$

finds the x-coordinate for "imaginary" point N sufficiently far to the left of point B to complete the triangle

$$N_y = M_{uc} * (N_x - C_x) + C_y$$

finds the y-coordinate of imaginary point N

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{BN} = \sqrt{(B_x - N_x)^2 + (B_y - N_y)^2}$$

$$\overline{CN} = \sqrt{(C_x - N_x)^2 + (C_y - N_y)^2}$$

$$\overline{BC} = \sqrt{(B_x - C_x)^2 + (B_y - C_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BN}^2 - \overline{BC}^2 - \overline{CN}^2}{-2 * \overline{BC} * \overline{CN}} \right)$$

finds the angle for $\angle BCN$, denoted here as θ

$$\overline{BL} = \sin(\theta) * \overline{BC}$$

finds the height of triangle $\triangle BCN$ (perpendicular displacement of Upper Nose Point from Upper Profile of Face)

$$M_{bl} = -(M_{uc})^{-1}$$

finds the slope of the slope perpendicular to the line of the upper face

$$L_x = \frac{(M_{bl} * B_x - M_{uc} * A_x + A_y - B_y)}{(M_{bl} - M_{uc})}$$

finds the x-coordinate of the intersection point between the line of the upper face and its perpendicular bisector inclusive of point B

$$\sigma_x = \left(\frac{L_x - B_x}{|L_x - B_x|} \right)$$

finds the constant of nostril position with magnitude 1 indicating direction of position relative to the upper line of the face via sign ($\pm$)

$$DoNR = \sigma_x * \left(\frac{d}{\overline{AB}} \right)$$

*finds the **Degree of Nostril Rounding**, here defined as the degree to which the **Upper Nostril Point** rounds away from the **True Line of the Face** relative to the overall length of the face*




Fig. 1B

3 / 65

Facial Descriptor Name: Face Thickness Proportion**Anatomical Region of Face:** AR01_FacialProfile**General Description:**

Describes the overall depth of the overall depth of the jaw relative to the perpendicular height of the face. Identifies a horse that is wide from the mid-nose bone to the jaw.

Mathematical Proof:

$$M_{abb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$$

finds the slope of the *True Line of the Head*

$$M_p = -(M_{abb})^{-1}$$

finds the slope perpendicular to the *True Line of the Head*

$$Qn_x = \frac{(M_{abb} * U_x - M_p * N_x + N_y - U_y)}{(M_{abb} - M_p)}$$

$$Qn_y = M_{abb} * (Qn_x - U_x) + U_y$$

finds the x and y-coordinates of perpendicular intersect point Q_n

$$Qc_x = \frac{(M_{abb} * U_x - M_p * C_x + C_y - U_y)}{(M_{abb} - M_p)}$$

$$Qc_y = M_{abb} * (Qc_x - U_x) + U_y$$

finds the x and y-coordinates of perpendicular intersect point Q_c

$$\overline{NQn} = \sqrt{(N_x - Qn_x)^2 + (N_y - Qn_y)^2}$$

$$\overline{CQc} = \sqrt{(C_x - Qc_x)^2 + (C_y - Qc_y)^2}$$

$$FTP = \frac{\overline{CQc}}{\overline{NQn}}$$

finds the **Face Thickness Proportion**, here defined as the ratio between perpendicular height of the face and the perpendicular thickness of the jaw




Fig. 1C

4 / 65

Facial Descriptor Name: Forehead Slope ProportionAnatomical Region of Face: AR01_FacialProfileGeneral Description:Describes the slope of the forehead moving into the poll relative to the **True Line of the Head**.Mathematical Proof

$$M_{abb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$$

finds the slope of line $\overline{Ubb}$

$$M_p = -(M_{abb})^{-1}$$

finds the slopes of lines $\overline{EQ}$ and $\overline{FR}$ perpendicular to line $\overline{Ubb}$

$$Q_x = \frac{(M_p * E_y - M_{abb} * U_x + U_y - E_y)}{(M_p - M_{abb})}$$

finds the x-coordinate of perpendicular intercept point Q

$$Q_y = M_{abb} * (Q_x - U_x) + U_y$$

finds the y-coordinate of perpendicular intercept point Q

$$R_x = \frac{(M_p * F_y - M_{abb} * U_x + U_y - F_y)}{(M_p - M_{abb})}$$

finds the x-coordinate of perpendicular intercept point R

$$R_y = M_{abb} * (R_x - U_x) + U_y$$

finds the y-coordinate of perpendicular intercept point R

$$\overline{EQ} = \sqrt{(E_x - Q_x)^2 + (E_y - Q_y)^2}$$

$$\overline{FR} = \sqrt{(F_x - R_x)^2 + (F_y - R_y)^2}$$

finds the lengths of lines $\overline{EQ}$ and $\overline{FR}$

$$FSP = \frac{\overline{FR}}{\overline{EQ}}$$


finds the **Forehead Slope Proportion**, here defined as the ratio of perpendicular forehead height from the **True Line of the Head** at the rostral and caudal-most points of the forehead

Fig. 1D

5 / 65

Facial Descriptor Name: Forehead Height Proportion**Anatomical Region of Face:** AR01_FacialProfile**General Description:**Describes the perpendicular height of the forehead above the **True Line of the Face**.**Mathematical Proof:**

$$M_{AB} = \frac{(B_y - A_y)}{(B_x - A_x)}$$

finds the slope of line $\overline{AB}$

$$N_x = A_x + (A_x - B_x)$$

finds the x-coordinate for "imaginary" point N sufficiently far to the right of point A to complete the triangle

$$N_y = M_{AB} * (N_x - A_x) + A_y$$

finds the y-coordinate of imaginary point N

$$\overline{BN} = \sqrt{(B_x - N_x)^2 + (B_y - N_y)^2}$$

$$\overline{EN} = \sqrt{(E_x - N_x)^2 + (E_y - N_y)^2}$$

$$\overline{BE} = \sqrt{(B_x - E_x)^2 + (B_y - E_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BE}^2 - \overline{BN}^2 - \overline{EN}^2}{-2 * \overline{BN} * \overline{EN}} \right)$$

finds the angle for $\angle BNE$, denoted here as θ

$$\overline{DL} = \sin(\theta) * \overline{EN}$$

finds the height of triangle $\triangle CDN$ (perpendicular displacement of Forehead from True Line of Face)

$$M_{EL} = -(M_{AB})^{-1}$$

finds the slope of line $\overline{EL}$


$$L_x = \frac{(M_{EL} * E_x - M_{AB} * A_x + A_y - E_y)}{(M_{EL} - M_{AB})}$$

finds the x-coordinate of the perpendicular intersection point L

$$\sigma_x = \left(\frac{L_x - E_x}{|L_x - E_x|} \right)$$

finds the constant of forehead position with magnitude 1 indicating direction of position relative the **true line of the face** via sign ($\pm$)

$$FHP = \sigma_x * \left(\frac{\overline{DL}}{\overline{AB}} \right)$$

finds the **Forehead Height Proportion**, here defined as the perpendicular displacement of the **Upper Eye Orbital Point** of the forehead from the **True Line of the Face**, relative to the length of the face.**Fig. 1E**

6 / 65

Facial Descriptor Name: Forehead Length ProportionAnatomical Region of Face: AR01_FacialProfileGeneral Description:

Describes the length of the horse's forehead relative to the overall length of the head

Mathematical Proof

$$M_{abb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$$

finds the slope of the **True Line of the Head**

$$M_p = -(M_{abb})^{-1}$$

finds the slope perpendicular to the **True Line of the Head**

$$R_x = \frac{(M_{abb} * U_x - M_p * E_x + E_y - U_y)}{(M_{abb} - M_p)}$$

$$R_y = M_{abb} * (R_x - U_x) + U_y$$

finds the x and y-coordinates of intersect point R

$$Q_x = \frac{(M_p * E_x - M_{abb} * U_x + U_y - E_y)}{(M_p - M_{abb})}$$

finds the x-coordinate of perpendicular intercept point Q

$$Q_y = M_{abb} * (Q_x - U_x) + U_y$$


finds the y-coordinate of perpendicular intercept point Q

$$\overline{UR} = \sqrt{(U_x - R_x)^2 + (U_y - R_y)^2}$$

$$\overline{QR} = \sqrt{(R_x - Q_x)^2 + (R_y - Q_y)^2}$$

finds the length of lines $\overline{UR}$ and $\overline{QR}$

$$FLP = \frac{\overline{QR}}{\overline{UR}}$$

finds the **Forehead Length Proportion**, here defined the perpendicular length of the forehead relative to the overall length of the head**Fig. 1F**

7 / 65

Facial Descriptor Name: Nose Length ProportionAnatomical Region of Face: AR01_FacialProfileGeneral Description:

Describes the perpendicular length of a horse's nose relative to the overall length of the face.

Mathematical Proof

$$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of the *True Line of the Face*

$$M_p = -(M_{ab})^{-1}$$

finds the slope perpendicular to the *True Line of the Face*

$$Q_x = \frac{(M_p * C_x - M_{ab} * A_x + A_y - C_y)}{(M_p - M_{ab})}$$

finds the x-coordinate of perpendicular intercept point Q

$$Q_y = M_{ab} * (Q_x - A_x) + A_y$$

finds the y-coordinate of perpendicular intercept point Q

$$\overline{AB} = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}$$

$$\overline{BQ} = \sqrt{(B_x - Q_x)^2 + (B_y - Q_y)^2}$$

finds the length of lines $\overline{AB}$ and $\overline{BQ}$

$$NLP = \frac{\overline{BQ}}{\overline{AB}}$$


finds the **Nose Length Proportion**, here defined the perpendicular length of the nose relative to the overall length of the face

Fig. 1G

8 / 65

Facial Descriptor Name: Nose Roundness Proportion**Anatomical Region of Face:** AR01_FacialProfile**General Description:**

Describes the degree of roundness of the nasal bone as it results from the accretion of bone above the **True Line of the Nose**. Identifies convex "Moose" and "Roman" profiles.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$$

finds the angle for $\angle BAC$, denoted here as θ

$$d = \sin(\theta) * \overline{AC}$$

finds the height of triangle $\triangle ABC$ (distance of nostril rounding)

$$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of line $\overline{AB}$

$$Q_x = \left(\frac{C_y - A_y}{M_{ab}} \right) + A_x$$

finds the x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C

$$\sigma = Q_x - C_x$$


finds a value for which σ is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face

$$\sigma_s = \frac{\sigma}{|\sigma|}$$

finds σ_s , here defined of the Constant of Concavity with magnitude 1 indicating direction of inflexion/convection via sign ($\pm$)

$$NRP = \sigma_s * \left(\frac{d}{\overline{AB}} \right)$$

*finds the **Nose Roundness Proportion**, here defined as the degree of perpendicular deviation of the Upper Profile of the skull above the **True Line of the Nose** relative to the length of the nose.*

**Fig. 1H**

9 / 65

Facial Descriptor Name: Nostril Position ProportionAnatomical Region of Face: ARO1_FacialProfileGeneral Description:

Describes the angle at which the nose is set onto the face. Partially differentiates between a Roman Nose and Roman Head. Partially identifies a "Moose" nose.

Mathematical Proof

$$M_{ac} = \frac{(A_y - C_y)}{(A_x - C_x)}$$

finds the slope of line $\overline{AC}$

$$N_x = B_x - (A_x - B_x)$$

finds the x-coordinate for "imaginary" point N sufficiently far to the left of point B to complete the triangle

$$N_y = M_{ac} * (N_x - C_x) + C_y$$

finds the y-coordinate of imaginary point N

$$\overline{BN} = \sqrt{(B_x - N_x)^2 + (B_y - N_y)^2}$$

$$\overline{CN} = \sqrt{(C_x - N_x)^2 + (C_y - N_y)^2}$$

$$\overline{BC} = \sqrt{(B_x - C_x)^2 + (B_y - C_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BN}^2 - \overline{BC}^2 - \overline{CN}^2}{-2 * \overline{BC} * \overline{CN}} \right)$$

finds the angle for $\angle BCN$, denoted here as θ

$$\overline{BL} = \sin(\theta) * \overline{BC}$$

finds the height of triangle $\triangle BCN$, defined here as the distance of displacement of the nose from the line of the upper face

$$M_{bl} = -(M_{ac})^{-1}$$

finds the slope of the slope perpendicular to the line of the upper face

$$L_x = \frac{(M_{bl} * B_x - M_{ac} * A_x + A_y - B_y)}{(M_{bl} - M_{ac})}$$

finds the x-coordinate of the intersection point between the line of the upper face and its perpendicular bisector inclusive of point B

$$\sigma_x = \left(\frac{L_x - B_x}{|L_x - B_x|} \right)$$

finds the constant of nostril position with magnitude 1 indicating direction of position relative to the upper line of the face via sign ($\pm$)

$$NPP = \sigma_x * \left(\frac{\overline{BL}}{\overline{AB}} \right)$$

*finds the **Nostril Position Proportion**, here defined as the degree to which the position of the nose varies from the upper line of the face relative to the overall size of the face.*




Fig. 1J

10 / 65

Facial Descriptor Name: Degree of Eye Orbital ProtrusionAnatomical Region of Face: AR01_FacialProfileGeneral Description:

Describes the longitudinal placement of the eye orbital on the top of the skull as it is positioned in correlation with the sinus cavities. Partially identifies protruding sinus cavities

Mathematical Proof:

$$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$$

finds the slope of line $\overline{AB}$

$$m_p = -(m_{ab})^{-1}$$

Finds the slope perpendicular to the line $\overline{AB}$

$$Q_x = \frac{m_{ab} * A_x - m_p * C_x + C_y - A_y}{m_{ab} - m_p}$$

finds the x-coordinate of the intersection point between line $\overline{AB}$ and its perpendicular bisector inclusive of point C

$$Q_y = m_{ab}(Q_x - A_x) + A_y$$

finds the y-coordinate of intersect point "Q"

$$P_x = \frac{m_{ab} * A_x - m_p * D_x + D_y - A_y}{m_{ab} - m_p}$$

finds the x-coordinate of intersection point between line $\overline{AB}$ and its perpendicular bisector inclusive of point D

$$P_y = m_{ab}(P_x - A_x) + A_y$$

finds the y-coordinate of intersect point "P"

$$\overline{CQ} = \sqrt{(C_x - Q_x)^2 + (C_y - Q_y)^2}$$

finds the distance of displacement of the base point of the eye orbital from line $\overline{AB}$

$$\overline{DP} = \sqrt{(D_x - P_x)^2 + (D_y - P_y)^2}$$

finds the distance of displacement of the tallest point of the eye orbital from line $\overline{AB}$

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

finds the overall length of the face

$$DoEOP = \frac{\overline{DP} - \overline{CQ}}{\overline{AB}}$$

*finds the **Degree of Eye Orbital Protrusion**, defined here as the distance of protrusion of the maxima point of the eye orbital its base on the skull relative to the overall length of the face*




Fig. 1K

11 / 65

Facial Descriptor Name: Degree of Facial Protuberance**Anatomical Region of Face:** ARO2_Protruberances**General Description:**

Describes the degree of prominence/enlargement of the sinus cavities above the eyes ("Jibbah") as they protrude from the underlying boney structure of the **True Line of the Face**.

Mathematical Proof:

$$M_{BC} = \frac{(B_y - C_y)}{(B_x - C_x)}$$

finds the slope of line BC

$$N_x = C_x + (A_x - B_x)$$

finds the x-coordinate for "imaginary" point N sufficiently far to the right of point D to complete the triangle

$$N_y = M_{BC} * (N_x - C_x) + C_y$$

finds the y-coordinate of imaginary point N

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{CN} = \sqrt{(C_x - N_x)^2 + (C_y - N_y)^2}$$

$$\overline{DN} = \sqrt{(D_x - N_x)^2 + (D_y - N_y)^2}$$

$$\overline{CD} = \sqrt{(D_x - C_x)^2 + (D_y - C_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{CD}^2 - \overline{CN}^2 - \overline{ND}^2}{-2 * \overline{CN} * \overline{ND}} \right)$$


finds the angle for $\angle CND$, denoted here as θ

$$\overline{DL} = \sin(\theta) * \overline{DN}$$

finds the height of triangle $\triangle CDN$ (perpendicular displacement of Sinus from True Line of the Nose)

$$DoFP = \frac{d}{\overline{AB}}$$

*finds the **Degree of Facial Protuberance**, here defined as the perpendicular displacement of the **Sinus Protuberance Point** from the **True Line of the Nose**, relative to the length of the upper portion of the face.*

**Fig. 2**

12 / 65

Facial Descriptor Name: Jowl Protuberance ProportionAnatomical Region of Face: AR03_JowlSizeGeneral Description:

Describes the degree to which the minima point of the jowl protrudes from the underline of the jaw. Identifies shallow jowls. Partially differentiates between large and small jowls.

Mathematical Proof:

$$m_{\min} = \frac{M_x - N_x}{M_y - N_y}$$

Finds the slope of the underline of the jaw

$$Q_x = N_x + 2(N_x - M_x)$$

Finds x-coordinate for imaginary point "q", sufficiently far to the right of point N to complete a triangle on the line fit to the underline of the jaw

$$Q_y = m_{\min}(Q_x - M_x) + M_y$$

Finds the y-coordinate corresponding to imaginary point "q"

$$\overline{NP} = \sqrt{(N_x - P_x)^2 + (N_y - P_y)^2}$$

$$\overline{PQ} = \sqrt{(P_x - Q_x)^2 + (P_y - Q_y)^2}$$

$$\overline{NQ} = \sqrt{(N_x - Q_x)^2 + (N_y - Q_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{PQ}^2 - \overline{NQ}^2 - \overline{NP}^2}{-2 * \overline{NQ} * \overline{NP}} \right)$$

Finds the angle measure $\angle NQP$, denoted here as θ

$$d = \sin \theta * \overline{NP}$$

Finds the perpendicular distance from the line fit to the underline of the jaw to the minima point of the jowl

$$\overline{MN} = \sqrt{(M_x - N_x)^2 + (M_y - N_y)^2}$$

Finds the length of the underline of the jaw

$$JPP = d / \overline{MN}$$

*Finds the **Jowl Protuberance Proportion**, which here describes the length of protuberance of the jowl from the line of the jowl relative to the full length of the underline of the jaw*




Fig. 3A

13 / 65

Facial Descriptor Name: Jowl Roundness Proportion**Anatomical Region of Face:** AR03_JowlSize**General Description:**

Describes the degree of jowl rounding along the underline of the jowl as described by the ratio of the perpendicular distance of the **Mid Jowl Point** from the **True Line of the Jowl** and the overall length of the jowl.

Mathematical Proof:

$$\overline{MN} = \sqrt{(M_x - N_x)^2 + (M_y - N_y)^2}$$

$$\overline{MK} = \sqrt{(M_x - K_x)^2 + (M_y - K_y)^2}$$

$$\overline{NK} = \sqrt{(N_x - K_x)^2 + (N_y - K_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{NK}^2 - \overline{MN}^2 - \overline{MK}^2}{-2 * \overline{MN} * \overline{MK}} \right)$$


finds the angle for $\angle NMK$, denoted here as θ

$$d = \sin(\theta) * \overline{MK}$$

finds the perpendicular depth of the jowl

$$JRP = \frac{d}{\overline{MN}}$$

*finds the **Jowl Roundness Proportion**, here defined as the perpendicular distance of rounding of the underline of the jowl from the **True Line of the Jowl** relative to the overall length of the jowl*

**Fig. 3B**

14 / 65

Facial Descriptor Name: Jowl-to-Underline ProportionAnatomical Region of Face: AR03_JowlSizeGeneral Description:

Describes the magnitude of the lateral length of the jowl relative to the length of the of the jaw bone. Partially differentiates between a large and small jowl.

Mathematical Proof:

$$\overline{MN} = \sqrt{(M_x - B_x)^2 + (M_y - N_y)^2}$$

Finds the length of the underline of the jaw

$$\overline{NO} = \sqrt{(N_x - O_x)^2 + (N_y - O_y)^2}$$

Finds the lateral length across the jowl

$$JtUP = \overline{NO} / \overline{MN}$$

*Finds the **Jowl-to-Underline Proportion**,
here defined at the magnitude of the
lateral length of the jowl relative to
the length of jaw bone*




Fig. 3C

15 / 65

Facial Descriptor Name: Forehead Height AngleAnatomical Region of Face: A804_MuzzleShapeGeneral Description:

Describes the angle of rise of the forehead along the topline of the face from the True Line of the Head.

Mathematical Proof:

$$m_{be} = \frac{B_y - E_y}{B_x - E_x}$$

Finds the slope of the True Line of Face

$$m_{ubb} = \frac{U_y - bb_y}{U_x - bb_x}$$

Finds the slope of line fitted to underline of jaw

$$Q_x = \frac{m_{be} * B_x - m_{ubb} * U_x + U_y - B_y}{m_{be} - m_{ubb}}$$

Finds the x-coordinate of the point "Q" where the true line of the face and the line fitted to the underline of the jaw intersect

$$Q_y = m_{be}(Q_x - B_x) + B_y$$

Finds the y-coordinate for intersect point "Q"

$$\overline{EQ} = \sqrt{(E_x - Q_x)^2 + (E_y - Q_y)^2}$$

$$\overline{Ebb} = \sqrt{(E_x - bb_x)^2 + (E_y - bb_y)^2}$$

$$\overline{Qbb} = \sqrt{(Q_x - bb_x)^2 + (Q_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$FAF = \theta = \cos^{-1} \left(\frac{\overline{Ebb}^2 - \overline{EQ}^2 - \overline{Qbb}^2}{-2 * \overline{EQ} * \overline{Qbb}} \right)$$


Finds the angle measure for Forehead Height Angle ($\angle EQB$), here defined as the intersect angle of the topline of the face and the True Line of the Head

Fig. 4A

16 / 65

Facial Descriptor Name: Full Angle FaceAnatomical Region of Face: AR04_MuzzleShapeGeneral Description:

Describes both the magnitude and rate of change of the thickness of the face. Gives an indication of the relationship between the jaw region of the face and the muzzle. Identifies a "teacup muzzle".

Mathematical Proof:

$$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$$

Finds the slope of the True Line of Face

$$m_{cd} = \frac{D_y - C_y}{D_x - C_x}$$

Finds the slope of line fitted to underline of jaw

$$Q_x = \frac{m_{ab} * A_x - m_{cd} * C_x + C_y - A_y}{m_{ab} - m_{cd}}$$

Finds the x-coordinate of the point "Q" where the true line of the face and the line fitted to the underline of the jaw intersect

$$Q_y = m_{ab}(Q_x - A_x) + A_y$$

Finds the y-coordinate for intersect point "Q"

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{AQ} = \sqrt{(A_x - Q_x)^2 + (A_y - Q_y)^2}$$

$$\overline{CQ} = \sqrt{(C_x - Q_x)^2 + (C_y - Q_y)^2}$$

Finds distance values for all sides of triangle

$$FAF = \theta = \cos^{-1} \left(\frac{\overline{AC}^2 - \overline{AQ}^2 - \overline{CQ}^2}{-2 * \overline{AQ} * \overline{CQ}} \right)$$

Finds the angle measure for Full Angle Face ($\angle AQC$), here defined as the intersect angle of the upper and lower lines of the face (True Line of the Face & True Line of the Jaw)




Fig. 4B

17 / 65

Facial Descriptor Name: Mouth Inflexion AngleAnatomical Region of Face: AR04_MuzzleShapeGeneral Description:

Describes the degree of inflexion/angulation taken by the lower portion of the muzzle as it contracts inwards from the **Distal Muzzle Point** to the **Distal Point of the Mouth**.

Mathematical Proof:

$$\overline{BS} = \sqrt{(B_x - S_x)^2 + (B_y - S_y)^2}$$

$$\overline{BT} = \sqrt{(T_x - B_x)^2 + (T_y - B_y)^2}$$

$$\overline{ST} = \sqrt{(T_x - S_x)^2 + (T_y - S_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BT}^2 - \overline{BS}^2 - \overline{ST}^2}{-2 * \overline{BS} * \overline{ST}} \right)$$

*Finds angle value for Muzzle Slope Angle ($\angle ABC$),
denoted here as θ*




Fig. 4C

18 / 65

Facial Descriptor Name: Muzzle Roundness ProportionAnatomical Region of Face: AR04_MuzzleShapeGeneral Description:

Describes the degree of inflexion/angulation taken by the lower portion of the muzzle as it contracts inwards from the **Distal Muzzle Point** to the **Distal Point of the Mouth**.

Mathematical Proof:

$$\overline{ST} = \sqrt{(T_x - S_x)^2 + (T_y - S_y)^2}$$

$$\overline{SU} = \sqrt{(U_x - S_x)^2 + (U_y - S_y)^2}$$

$$\overline{UT} = \sqrt{(T_x - U_x)^2 + (T_y - U_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{UT^2 - \overline{SU}^2 - \overline{ST}^2}{-2 * \overline{SU} * \overline{ST}} \right)$$

finds the angle for $\angle UST$, denoted here as θ

$$\bar{d} = \sin(\theta) * \overline{EN}$$

finds the height of triangle ΔSTU

$$MRP = \frac{\bar{d}}{\overline{UT}}$$

*finds the **Muzzle Roundness Proportion**, here defined as the perpendicular displacement of the **Distal Muzzle Point** from the line of the muzzle formed by the **Lower Nostril Point** and **Distal Mouth Point**.*




Fig. 4D

19 / 65

Facial Descriptor Name: Muzzle Size ProportionAnatomical Region of Face: AR04_MuzzleShapeGeneral Description:

Describes the overall size of the muzzle in terms of perpendicular height relative to the overall length of the face

Mathematical Proof:

$$M_{uob} = \frac{(U_y - hb_y)}{(U_x - hb_x)}$$

finds the slope of the True Line of the Head

$$M_{pu} = -(M_{uob})^{-1}$$

finds the slope perpendicular to the True Line of the Head

$$R_x = \frac{(M_{uob} * U_x - M_{pu} * F_x + F_y - U_y)}{(M_{uob} - M_{pu})}$$

$$R_y = M_{uob} * (R_x - U_x) + U_y$$

finds the x and y-coordinates of intersect point R

$$M_{gh} = \frac{(G_y - H_y)}{(G_x - H_x)}$$

finds the slope of the True Line of the Chin

$$M_{ph} = -(M_{gh})^{-1}$$

finds the slope perpendicular to the True Line of the Chin

$$Q_x = \frac{(M_{gh} * G_x - M_{ph} * R_x + R_y - G_y)}{(M_{gh} - M_{ph})}$$

$$Q_y = M_{gh} * (Q_x - G_x) + G_y$$

finds the x and y-coordinates of intersect point Q

$$\overline{BQ} = \sqrt{(B_x - Q_x)^2 + (B_y - Q_y)^2}$$

$$\overline{UR} = \sqrt{(U_x - R_x)^2 + (U_y - R_y)^2}$$

finds the distance values for lines $\overline{BQ}$ and $\overline{UR}$

$$MSP = \frac{\overline{BQ}}{\overline{UR}}$$

finds the Muzzle Size Proportion, here defined as the perpendicular height of the muzzle relative to the overall length of the face




Fig. 4E

20 / 65

Facial Descriptor Name: Muzzle Slope AngleAnatomical Region of Face: AR04_MuzzleShapeGeneral Description:

Describes the degree of slope/angulation taken by the top line of the muzzle and upper lip. Identifies a "moose" nose. Partially differentiates between a round and square muzzle.

Mathematical Proof:

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

$$\overline{BS} = \sqrt{(B_x - S_x)^2 + (B_y - S_y)^2}$$

$$\overline{CS} = \sqrt{(C_x - S_x)^2 + (C_y - S_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BS}^2 - \overline{BC}^2 - \overline{CS}^2}{-2 * \overline{BC} * \overline{CS}} \right)$$

*Finds angle value for **Muzzle Slope Angle** ($\angle ABC$), denoted here as θ*




Fig. 4F

21 / 65

Facial Descriptor Name: Chin Firmness ProportionAnatomical Region of Face: AR05_ChinShapeGeneral Description:

Describes the overall tightness of the chin, as reflected closeness of the Chin Maxima Point to the Caudal Chin Point relative to the overall length of the chin

Mathematical Proof:

$$M_{GH} = \frac{(G_y - H_y)}{(G_x - H_x)}$$

finds the slope of line GH

$$M_{QI} = -(M_{GH})^{-1}$$

finds the slope of line QI, perpendicular to line GH

$$Q_x = \frac{(M_{GH} * G_x - M_{QI} * I_x + I_y - G_y)}{(M_{GH} - M_{QI})}$$

finds the x-coordinate of the perpendicular intersection point Q

$$Q_y = M_{GH} * (Q_x - G_x) + G_y$$

finds the y-coordinate of intersect point Q

$$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}$$

$$\overline{GQ} = \sqrt{(G_x - Q_x)^2 + (G_y - Q_y)^2}$$

Finds distance values for lines GH and GQ

$$CFP = \frac{\overline{GQ}}{\overline{GH}}$$

finds the Chin Firmness Proportion, here defined as the distance at which the Chin Minima Point is located from the front of the chin




Fig. 5A

22 / 65

Facial Descriptor Name: Chin Fullness ProportionAnatomical Region of Face: AR05__ChinShapeGeneral Description:

Describes the fullness/roundness of the chin as the perpendicular deviation of the profile of the chin from the front line of the chin relative to the overall length of the front line of the chin.

Mathematical Proof:

$$\overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2}$$

$$\overline{GJ} = \sqrt{(G_x - J_x)^2 + (G_y - J_y)^2}$$

$$\overline{JI} = \sqrt{(J_x - I_x)^2 + (J_y - I_y)^2}$$

Finds distance values for all sides of the triangle

$$\theta = \cos^{-1} \left(\frac{\overline{JI}^2 - \overline{GI}^2 - \overline{GJ}^2}{-2 * \overline{GI} * \overline{GJ}} \right)$$

finds the angle for $\angle GJI$, denoted here as θ

$$\overline{QJ} = \sin(\theta) * \overline{GJ}$$

finds the height of triangle ΔGJI
(perpendicular thickness height of the chin)

$$CWtHP = \frac{\overline{QJ}}{\overline{GI}}$$

finds the Chin Fullness Proportion, here defined as the perpendicular deviation of the Mid-Chin Point from the front line of the chin relative to the overall length of the front line of the chin




Fig. 5B

23 / 65

Facial Descriptor Name: Chin Length AngleAnatomical Region of Face: AR05_ChinShapeGeneral Description:

Describes the overall length of the chin relative to the degree to which it protrudes from the underside of the jaw bone. Differentiates between a long and short chin. Partially identifies a thin chin.

Mathematical Proof:

$$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}$$

$$\overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2}$$

$$\overline{HI} = \sqrt{(H_x - I_x)^2 + (H_y - I_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{GH}^2 - \overline{GI}^2 - \overline{HI}^2}{-2 * \overline{GI} * \overline{HI}} \right)$$

*Finds the angle value for **Chin Length Angle**
($\angle ACB$), denoted here as θ*




Fig. 5C

24 / 65

Facial Descriptor Name: Chin Thickness AngleAnatomical Region of Face: AR05_ChinShapeGeneral Description:

Describes the position of the minima point of chin relative to the point where the chin first becomes distinguishable from the lip. Differentiates between a relaxed and tight chin.

Mathematical Proof:

$$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}$$

$$\overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2}$$

$$\overline{HI} = \sqrt{(H_x - I_x)^2 + (H_y - I_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{HI^2 - GI^2 - GH^2}{-2 * GI * GH} \right)$$

*Finds the angle value for **Chin Thickness***

***Angle** ($\angle BAC$), denoted here as θ*




Fig. 5D

25 / 65

Facial Descriptor Name: Chin Width-to-Height ProportionAnatomical Region of Face: AR05__ChinShapeGeneral Description:

Describes the ratio of the coverall length of the chin to its height at its minimal-most point.

Mathematical Proof:

$$\overline{GH} = \sqrt{(G_x - H_x)^2 + (G_y - H_y)^2}$$

$$\overline{GI} = \sqrt{(G_x - I_x)^2 + (G_y - I_y)^2}$$

$$\overline{HI} = \sqrt{(H_x - I_x)^2 + (H_y - I_y)^2}$$

Finds distance values for all sides of the triangle

$$\theta = \cos^{-1} \left(\frac{HI^2 - GI^2 - GH^2}{-2 * GI * GH} \right)$$

finds the angle for $\angle HGI$, denoted here as θ

$$\overline{QI} = \sin(\theta) * \overline{GI}$$

*finds the height of triangle ΔGHI
(perpendicular height of the chin)*

$$CWtHP = \frac{\overline{QI}}{\overline{GH}}$$

finds the Chin Width-to-Height Proportion, here defined as the ratio of the length of the chin to its maximal perpendicular height




Fig. 5E

26 / 65

Facial Descriptor Name: Lip Length ProportionAnatomical Region of Face: AR05_ChinShapeGeneral Description:

Describes the length of overhang of the lower lip as it compares to the overall length of the chin.

Mathematical Proof:

$$M_{gh} = \frac{(G_y - H_y)}{(G_x - H_x)}$$

finds the slope of line $\overline{GH}$

$$M_{kq} = -(M_{gh})^{-1}$$

finds the slope of line $\overline{KQ}$, perpendicular to line $\overline{GH}$

$$Q_x = \frac{(M_{gh} * G_x - M_{kq} * K_x + K_y - G_y)}{(M_{gh} - M_{kq})}$$

finds the x-coordinate of the perpendicular intersection point Q

$$Q_y = M_{gh} * (Q_x - G_x) + G_y$$

finds the y-coordinate of intersect point Q

$$\overline{HQ} = \sqrt{(H_x - Q_x)^2 + (H_y - Q_y)^2}$$

$$\overline{GQ} = \sqrt{(G_x - Q_x)^2 + (G_y - Q_y)^2}$$

Finds distance values for lines $\overline{HQ}$ and $\overline{KQ}$

$$LLP = \frac{\overline{GQ}}{\overline{HQ}}$$

finds the Lip Length Proportion, here defined as the length of overhang of the lower lip relative to the overall length of the chin




Fig. 5F

27 / 65

Facial Descriptor Name: Lip Protuberance ProportionAnatomical Region of Face: AR06_MouthLengthGeneral Description:

Describes the degree to which the lower lip protrudes beyond the distal-most point of the mouth.

Mathematical Proof:

$$m_{jt} = \frac{J_y - T_y}{J_x - T_x}$$

finds the slope of the line of the mouth

$$m_p = -(m_{jt})^{-1}$$

Finds the slope perpendicular to the line of the mouth

$$Q_x = \frac{m_{jt} * T_x - m_p * K_x + K_y - T_y}{m_{jt} - m_p}$$

finds the x-coordinate of perpendicular intersect point Q

$$Q_y = m_{jt}(Q_x - T_x) + T_y$$

finds the y-coordinate of intersect point "Q"

$$\overline{JQ} = \sqrt{(J_x - Q_x)^2 + (J_y - Q_y)^2}$$

finds the total length of the lower lip

$$\overline{TQ} = \sqrt{(T_x - Q_x)^2 + (T_y - Q_y)^2}$$

finds the distance which the distal-most point of the lower lip protrudes beyond the distal-most point of the mouth

$$\sigma_s = \left(\frac{Q_x - T_x}{|Q_x - T_x|} \right)$$

finds the constant of lip position with magnitude 1 indicating the position of the lip beyond or behind the distal-most point of the mouth

$$LPP = \sigma_s * \left(\frac{\overline{TQ}}{\overline{JQ}} \right)$$


finds the **Lip Protuberance Proportion**, which here defines the position of the distal-most point of the lower lip relative to the distal most point of the mouth

Fig. 6A

28 / 65

Facial Descriptor Name: Mouth Length ProportionAnatomical Region of Face: AR06_MouthlengthGeneral Description:

Describes the length of the mouth relative to the overall length of the head.

Mathematical Proof:

$$M_{abb} = \frac{(U_y - bb_y)}{(U_x - bb_x)}$$

finds the slope of the True Line of the Head

$$M_{pu} = -(M_{abb})^{-1}$$

finds the slope perpendicular to the True Line of the Head

$$R_x = \frac{(M_{abb} * U_x - M_{pu} * F_x + F_y - U_y)}{(M_{abb} - M_{pu})}$$

$$R_y = M_{abb} * (R_x - U_x) + U_y$$

finds the x and y-coordinates of intersect point R

$$\overline{JT} = \sqrt{(J_x - T_x)^2 + (J_y - T_y)^2}$$

finds the length of the mouth

$$\overline{UR} = \sqrt{(U_x - R_x)^2 + (U_y - R_y)^2}$$

finds the full length of the head

$$MLP = \frac{\overline{JT}}{\overline{UR}}$$


finds the Mouth Length Proportion, here defined as the length of the mouth relative to the overall length of the head

Fig. 6B

29 / 65

Facial Descriptor Name: Degree of Nostril Flutedness**Anatomical Region of Face:** AR07_NostrilShape**General Description:**

Describes the degree to which excess skin along the inside of the nostril extends and curls around the inner line of the nostril.

Mathematical Proof:

$$M_{xz} = \frac{(X_y - S_y)}{(X_x - S_x)}$$

finds the slope of the Line of the Inner Nostril

$$M_p = -(M_{xz})^{-1}$$

finds the slope perpendicular to the Line of the Inner Nostril

$$Q_x = \frac{(M_{xz} * S_x - M_p * Z_x + Z_y - S_y)}{(M_{xz} - M_p)}$$

$$Q_y = M_{xz} * (Q_x - S_x) + S_y$$

finds the x and y-coordinates of intersect point Q

$$\overline{XS} = \sqrt{(X_x - S_x)^2 + (X_y - S_y)^2}$$

finds the overall length of the nostril

$$\overline{ZQ} = \sqrt{(Z_x - Q_x)^2 + (Z_y - Q_y)^2}$$

finds the perpendicular distance of rise of the fleshy skin flap of the inner nostril from the Line of the Inner Nostril

$$DoNF = \frac{\overline{ZQ}}{\overline{XS}}$$

finds the Degree of Nostril Flutedness, here defined as the distance of inflexion of the skin of the inner nostril from the Line of the Inner Nostril (the flute of the nose) relative to the overall length of the nostril




Fig. 7A

30 / 65

Facial Descriptor Name: Degree of Nostril RoundnessAnatomical Region of Face: AR07_NostrilShapeGeneral Description:

Describes the perpendicular height of the outer edge of the nostril above the line of the inner nostril. Identifies horses with large and/or flared nostrils.

Mathematical Proof:

$$M_{TY} = \frac{(T_y - Y_y)}{(T_x - Y_x)}$$

finds the slope of the Line of the Inner Nostril

$$M_p = -(M_{TY})^{-1}$$

finds the slope perpendicular to the Line of the Inner Nostril

$$Q_x = \frac{(M_{TY} * T_x - M_p * V_x + V_y - T_y)}{(M_{TY} - M_p)}$$

$$Q_y = M_{TY} * (Q_x - T_x) + T_y$$

finds the x and y-coordinates of intersect point Q

$$\overline{TY} = \sqrt{(T_x - Y_x)^2 + (T_y - Y_y)^2}$$

finds the overall length of the nostril

$$\overline{VQ} = \sqrt{(V_x - Q_x)^2 + (V_y - Q_y)^2}$$

finds the perpendicular width of the nostril at its widest point

$$DoNR = \frac{\overline{VQ}}{\overline{TY}}$$

finds the Degree of Nostril Roundness, here defined as the perpendicular width of the nostril at its widest point relative to the overall length of the nostril




Fig. 7B

31 / 65

Facial Descriptor Name: Inner-Nostril Convergence ProportionAnatomical Region of Face: AR07_NostrilShapeGeneral Description:

Describes the horizontal positions of the upper and lower medial points of the nostrils relative to one another as they align with the mid-line of the face. Differentiated between horses with flat vertically aligned nostrils and horses with highly curved angled nostrils.

Mathematical Proof:

$$\overline{ST} = \sqrt{(S_x - T_x)^2 + (S_y - T_y)^2}$$

*Finds lateral distance across the upper
bridge of the nose*

$$\overline{XY} = \sqrt{(X_x - Y_x)^2 + (X_y - Y_y)^2}$$

*Finds lateral distance across the lower
bridge of the nose*

$$INCP = \overline{ST} / \overline{XY}$$

*Finds the **Inner-Nostril Convergence Proportion**, as the ratio between the lateral distance
between the upper and lower portions of the bridge of the nose*




Fig. 7C

32 / 65

Facial Descriptor Name: Nose Width-to-Height ProportionAnatomical Region of Face: AR07_NostrilShapeGeneral Description:

Describes the perpendicular height of the nose relative to the overall breadth of the nose.

Mathematical Proof:

$$M_{xy} = \frac{(X_y - Y_y)}{(X_x - Y_x)}$$

finds the slope of the Upper Line of the Nostril

$$M_p = -(M_{xy})^{-1}$$

finds the slope perpendicular to the Upper Line of the Nostril

$$Q_x = \frac{(M_{xy} * Y_x - M_p * S_x + S_y - Y_y)}{(M_{xy} - M_p)}$$

$$Q_y = M_{xy} * (Q_x - X_x) + Y_y$$

finds the x and y-coordinates of intersect point Q

$$\overline{XY} = \sqrt{(X_x - Y_x)^2 + (X_y - Y_y)^2}$$

finds the overall breadth of the nostril

$$\overline{QS} = \sqrt{(S_x - Q_x)^2 + (S_y - Q_y)^2}$$

finds the perpendicular height of the nose

$$DWLHP = \frac{\overline{QS}}{\overline{XY}}$$


*finds the **Nose Width-to-Height Proportion**, here defined as the ratio between the perpendicular height of the nostrils and the overall breadth of the nose*

Fig. 7D

33 / 65

Facial Descriptor Name: Nostril Length ProportionAnatomical Region of Face: AR07_NostrilShapeGeneral Description:

Describes the lateral length across the nostril relative to the overall length of the upper lip.

Mathematical Proof:


$$\overline{BU} = \sqrt{(B_x - U_x)^2 + (B_y - U_y)^2}$$

Finds the length of the nostril

$$\overline{UT} = \sqrt{(U_x - T_x)^2 + (U_y - T_x)^2}$$

Finds the length of the upper lip

$$NWP = \overline{BU} / \overline{UT}$$

*Finds the **Nostril Length Proportion**, here defined as the lateral length of the nostril relative to the overall length of the upper lip***Fig. 7E**

34 / 65

Facial Descriptor Name: Nostril Width ProportionAnatomical Region of Face: AR07_NostrilShapeGeneral Description:

Describes the proportion of the lateral distance of the muzzle that is inclusive of nostril area.
 Reflects the relative size/expansiveness of the nostrils relative to the size of the entire muzzle.
 Differentiates between large and narrow nostrils.

Mathematical Proof:

$$\overline{ST} = \sqrt{(S_x - T_x)^2 + (S_y - T_y)^2}$$


*Finds lateral distance across muzzle
 non-inclusive of nostril area*

$$\overline{UV} = \sqrt{(U_x - V_x)^2 + (U_y - V_y)^2}$$

*Finds total lateral distance across the
 muzzle*

$$NWP = \overline{ST} / \overline{UV}$$

*Finds the **Nostril Width Proportion**, here defined as the lateral distance of the bridge of the nose
 relative to the overall distance across the muzzle inclusive of nostrils*

**Fig. 7F**

35 / 65

Facial Descriptor Name: Degree of Lip InflexionAnatomical Region of Face: AR08_LipShapeGeneral Description:

Describes the degree of inflexion/curvature of the upper lip. Differentiates between a flat and "heart-shaped" upper lip.


Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

Finds distance values for all sides of triangle



$$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$$

Finds the angle measure for $\angle BAC$, denoted here as θ

$$d = \sin \theta * \overline{AC}$$

Finds the distance "d" of inflexion

$$DoLP = \frac{d}{\overline{AB}}$$

Finds Degree of Lip Inflexion, which is here defined to the distance of medial

inflexion of the lip relative to the overall width of the lips

Fig. 8

37 / 65

Facial Descriptor Name: Ear Inflexion ProportionAnatomical Region of Face: AR09_EarShapeGeneral Description:

Describes the degree to which the inner line of the ear curves inward between the upper-most point of the ear and the medial pinna point.

Mathematical Proof:

$$M_{np} = \frac{(N_y - P_y)}{(N_x - P_x)}$$

finds the slope of line $\overline{NP}$

$$M_p = -(M_{np})^{-1}$$

finds the slope perpendicular to line $\overline{NP}$

$$Q_x = \frac{(M_p * I_x - M_{np} * N_x + N_y - I_y)}{(M_p - M_{np})}$$

finds the x-coordinate of perpendicular intercept point Q

$$Q_y = M_{np} * (Q_x - P_x) + P_y$$

finds the y-coordinate of perpendicular intercept point Q

$$QJ = \sqrt{(I_x - Q_x)^2 + (I_y - Q_y)^2}$$

finds the distance of eye orbital protrusion

$$PN = \sqrt{(P_x - N_x)^2 + (P_y - N_y)^2}$$

finds the maximal lateral thickness of the cheeks

$$EIP = \frac{QJ}{PN}$$

*finds the **Ear Inflexion Proportion**, here defined as the perpendicular distance of inflexion relative to the overall distance of concavity along the inner line of the ear*




Fig. 9B

Facial Descriptor Name: Ear Roundness Proportion

Anatomical Region of Face: AR09_EarShape

General Description:

Describes the degree to which the tip of the ear curves inward away from the midline of the ear. This measure distinguishes between curvatures at the top of the ear due to concavity at the tip and curvature due to actual rounding of the ear structure.

Mathematical Proof:

$$M_2 = 0.50 M_1 - 1.0 \pm 1.0$$

$$M_2 = I_2 = I_1$$

finds the upper mid-ear point

$$B_{ml} = \frac{B_x - B_y}{B_x + B_y}$$

finds the slope of the Midline of the Ear

$$A_2 = -(\bar{A}_2)^{-1}$$

finds the slope perpendicular to the Midline of the Ear

$$Q_x = \frac{(M_p \cdot P - M_{mi} \cdot L_x + L_y - P_y)}{(M_p - M_{mi})}$$

$$Q_{\text{eff}} = Q_{\text{eq}} + (Q_{\text{e}} - Q_{\text{e}}) + Q_{\text{e}}$$

finds the x and y -coordinates of intersect point Q

$$RQ = \sqrt{(Q_1 - Q_2)^2 + (Q_3 - Q_4)^2}$$

finds the perpendicular distance of rounding at the tip of the ear

$$EF = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}$$

finds the overall length of the ear

$$EAP = \frac{QI}{R\lambda}$$

*finds the **Ear Roundness Proportion**, here defined as the perpendicular distance of inward curvature of the tip of the ear from the midline of the ear, relative to the overall length of the ear*




Fig. 9C

39 / 65

Facial Descriptor Name: Ear Width-to-Breadth ProportionAnatomical Region of Face: AR09_EarShapeGeneral Description:

Describes the overall width of the broadest section of the ear relative to its overall length.

Mathematical Proof:

$$M_x = 0.5(|K_x - I_x|) + I_x$$

$$M_y = I_y = K_y$$

finds the upper mid-ear point

$$LM = \sqrt{(L_x - M_x)^2 + (L_y - M_y)^2}$$

finds the length of the ear

$$NH = \sqrt{(N_x - H_x)^2 + (N_y - H_y)^2}$$

finds the width of the ear

$$EIP = \frac{NH}{LM}$$

*finds the **Ear Width-to-Breadth Proportion**, here defined as the width of the ear at its broadest point relative to its overall length*




Fig. 9D

40 / 65

Facial Descriptor Name: Ear Rotation ProportionAnatomical Region of Face: AR10_EarPositionGeneral Description:

Describes the degree of rotation of the ear as it is naturally set onto the forehead. Ears that are set wider apart and therefore farther down the poll are rotated laterally and show from the frontal view lesser pinna area. This measure reflects the proportion of area located at the base of the ear visually identified as pinna, differentiating between horses with wide and narrow set ears.

Mathematical Proof:

$$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$$

Finds the slope of the True Line of the Forehead, here defined as the line between the inner extrema points of the eyes

$$m_p = -(m_{ab})^{-1}$$

Finds the slope perpendicular to the True Line of the Forehead

$$N_x = \frac{m_{ab} \cdot A_x - m_p \cdot C_x + C_y - A_y}{m_{ab} - m_p} \quad P_x = \frac{m_{ab} \cdot A_x - m_p \cdot D_x + D_y - A_y}{m_{ab} - m_p}$$

$$Q_x = \frac{m_{ab} \cdot A_x - m_p \cdot E_x + E_y - A_y}{m_{ab} - m_p}$$

Finds the x-coordinates of the intersection points between the true line of the forehead and its perpendicular bisector inclusive of point C, D, and E respectively

$$N_y = m_{ab}(N_x - A_x) + A_y \quad P_y = m_{ab}(P_x - A_x) + A_y$$

$$Q_y = m_{ab}(Q_x - A_x) + A_y$$

Find the y-coordinated corresponding to intersect points N, P, and Q

$$\overline{NP} = \sqrt{(P_x - N_x)^2 + (P_y - N_y)^2}$$

Finds the distance across the base of the ear non-inclusive of pinna

$$\overline{NQ} = \sqrt{(Q_x - N_x)^2 + (Q_y - N_y)^2}$$

Finds the total distance across the base of the ear

$$ERP = \overline{NP} / \overline{NQ}$$

Finds the Ear Rotation Proportion, here defined as the proportion of the base of the ear non-inclusive of pinna as a indication of degree of rotation and wideness of set




Fig. 10A

41 / 65

Facial Descriptor Name: Ear Set AngleAnatomical Region of Face: AR10_EarPositionGeneral Description:

Describes the angle at which the ears are positioned onto the top of the skull, reflecting the natural position of the ears when the horse is in an emotionally neutral state of mind. Differentiates between wide, narrow, and vertically places ears.

Mathematical Proof:

$$M_x = 0.5(|K_x - L_x|) + L_x^*$$

$$M_y = L_y = K_y$$

finds the upper mid-ear point

$$m_{mi} = \frac{M_y - L_y}{M_x - L_x}$$

finds the slope of the Midline of the Ear

$$Q_x = \frac{(M_{ab} * A_x - M_{mi} * L_x + L_y - A_y)}{(M_{ab} - M_{mi})}$$

$$Q_y = M_{ab} * (Q_x - A_x) + A_y$$

finds the x and y-coordinates of intersect point Q

$$\overline{AB} = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}$$


$$\overline{AM} = \sqrt{(M_x - A_x)^2 + (M_y - A_y)^2}$$

$$\overline{MQ} = \sqrt{(M_x - Q_x)^2 + (M_y - Q_y)^2}$$

finds the lengths of all sides of the triangle

$$ESA = \theta = \cos^{-1} \left(\frac{\overline{AM}^2 - \overline{AB}^2 - \overline{MQ}^2}{-2 * \overline{AB} * \overline{MQ}} \right)$$

Finds the Ear Set Angle, defined here as the angle at which the midline of the ear meets the True Line of the Face



* Note – When the anatomical reference points are manually selected from the picture, the individual analyzing the photograph must choose which ear is the most appropriate to use based on how clearly the anatomical reference point can be seen and by which ear shows the highest degree of forward rotation.. The point on the inside curvature of the ear must always be at the medial-most point of the curve, and the point of the outside curvature of the ear should always be traced over so that the horizontal cross-hairs remain aligned horizontally with the inner ear point. There will be an if/else statement in the code to recognize which point (j/k) to the absolute value of the difference between the two points to get the correct x-coordinate of the M point based on which ear it is.

Fig. 10B

42 / 65

Facial Descriptor Name: Eye Height ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the perpendicular height of the eye above the midline of the eye relative to the eyes overall length.

Mathematical Proof:

$$\overline{Abb} = \sqrt{(\overline{bb}_x - A_x)^2 + (\overline{bb}_y - A_y)^2}$$

$$\overline{Add} = \sqrt{(\overline{dd}_x - A_x)^2 + (\overline{dd}_y - A_y)^2}$$

$$\overline{bbdd} = \sqrt{(\overline{dd}_x - \overline{bb}_x)^2 + (\overline{dd}_y - \overline{bb}_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$$

finds the angle for $\angle ABD$, denoted here as θ

$$d = \sin(\theta) * \overline{bbdd}$$

finds the perpendicular depth of the eye

$$EDP = \frac{d}{\overline{Abb}}$$

*finds the **Eye Depth Proportion**, here defined as the ratio of the perpendicular depth of the eye and the overall length of the eye*




Fig. 11A

43 / 65

Facial Descriptor Name: Eye Extrema Intersect AngleAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the angle at which the upper and lower extreme points of the eye are set against one another in relation to the **True Line of the Eye**.

Mathematical Proof:

$$M_{abb} = \frac{(A_y - bb_y)}{(A_x - bb_x)}$$

finds the slope of line $\overline{Abb}$

$$M_{ccdd} = \frac{(cc_y - dd_y)}{(cc_x - dd_x)}$$

finds the slope of line $\overline{ccdd}$

$$Q_x = \frac{(M_{abb} * A_x - M_{ccdd} * cc_x + cc_y - A_y)}{(M_{abb} - M_{ccdd})}$$

finds the x-coordinate of the intersect point Q

$$Q_y = M_{abb} * (Q_x - A_x) + A_y$$

finds the y-coordinate of imaginary point Q

$$\overline{AQ} = \sqrt{(Q_x - A_x)^2 + (Q_y - A_y)^2}$$

$$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$$

$$\overline{Qcc} = \sqrt{(cc_x - Q_x)^2 + (cc_y - Q_y)^2}$$

finds distance values for all sides of triangle

$$EXIA = \theta = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{AQ}^2 - \overline{Qcc}^2}{-2 * \overline{AQ} * \overline{Qcc}} \right)$$

finds the Eye Extrema Intersect Angle, here defined as angle θ




Fig. 11B

44 / 65

Facial Descriptor Name: Eye Height-to-Length ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the cumulative perpendicular height of the eye relative to the overall length of the eye.

Mathematical Proof:

$$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$$

$$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$$

$$\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}$$

$$\overline{bbcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$$

$$\overline{bbdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$\theta_y = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{Abb}^2 - \overline{bbcc}^2}{-2 * \overline{Abb} * \overline{bcc}} \right)$$

$$d_y = \sin(\theta) * \overline{bbdd}$$

finds the perpendicular height of the eye

$$\theta_L = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$$

$$d_L = \sin(\theta) * \overline{bbdd}$$

finds the perpendicular depth of the eye

$$EHtLP = \frac{d_y + d_L}{\overline{Abb}}$$

finds the **Eye Height-to-Length Proportion**, here defined as the ratio of the cumulative perpendicular height of to the horizontal length of the eye




Fig. 11C

45 / 65

Facial Descriptor Name: Eye Height ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the perpendicular height of the eye above the midline of the eye relative to the eyes overall length.

Mathematical Proof:

$$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$$

$$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$$

$$\overline{bcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$\theta_B = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{Abb}^2 - \overline{bcc}^2}{-2 * \overline{Abb} * \overline{bcc}} \right)$$

finds the angle for $\angle ABC$, denoted here as θ

$$d = \sin(\theta) * \overline{bcc}$$

finds the perpendicular height of the eye

$$EHP = \frac{d}{\overline{Abb}}$$

*finds the **Eye Height Proportion**, here defined as the ratio of the perpendicular height of the eye and the overall length of the eye*




Fig. 11D

46 / 65

Facial Descriptor Name: Eye Orbital Lateral Protuberance ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the degree to which the lateral-most point of the boney portion of the eye orbital extends beyond the line of the cheek, which effects the range of a horses caudal and ventral vision when set up into the bridle.

Mathematical Proof:

$$M_{eh} = \frac{(E_y - H_y)}{(E_x - H_x)}$$

finds the slope of the Line of the Cheek

$$M_p = -(M_{eh})^{-1}$$

finds the slope perpendicular to the Line of the Cheek

$$Q_x = \frac{(M_p * G_x - M_{eh} * E_x + E_y - G_y)}{(M_p - M_{eh})}$$

finds the x-coordinate of perpendicular intercept point Q

$$Q_y = M_{eh} * (Q_x - E_x) + E_y$$

finds the y-coordinate of perpendicular intercept point Q

$$\overline{GQ} = \sqrt{(G_x - Q_x)^2 + (G_y - Q_y)^2}$$

finds the distance of eye orbital protrusion

$$\overline{EP} = \sqrt{(E_x - P_x)^2 + (E_y - P_y)^2}$$

finds the maximal lateral thickness of the cheeks

$$EOLPP = \frac{\overline{GQ}}{\overline{EP}}$$

*finds the **Eye Orbital Lateral Protuberance Proportion**, here defined as the overall perpendicular distance of eye orbital displacement from the line of the cheek relative to the overall measure of cheek thickness*




Fig. 11E

47 / 65

Facial Descriptor Name: Eye Protuberance ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the overall portion of the eye visible from a frontal view in terms of lateral protrusion distance relative to the overall width of the forehead, which effects the range of a horse's frontal vision when set up into the bridle.

Mathematical Proof:

$$M_{ab} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of the True Line of the Forehead

$$M_p = -(M_{ab})^{-1}$$

finds the slope perpendicular to the True Line of the Forehead

$$Q_{ix} = \frac{(M_p * C_x - M_{ab} * A_x + A_y - C_y)}{(M_p - M_{ab})}$$

finds the x-coordinate of perpendicular intercept point Q_i

$$Q_{iy} = M_{ab} * (Q_{ix} - A_x) + A_y$$

finds the y-coordinate of perpendicular intercept point Q_i

$$Q_{rx} = \frac{(M_p * D_x - M_{ab} * A_x + A_y - D_y)}{(M_p - M_{ab})}$$

finds the x-coordinate of perpendicular intercept point Q_r

$$Q_{ry} = M_{ab} * (Q_{rx} - A_x) + A_y$$

finds the y-coordinate of perpendicular intercept point Q_r

$$\overline{AB} = \sqrt{(A_x - B_x)^2 + (A_y - B_y)^2}$$

finds the overall distance across the forehead

$$\overline{AQ_i} = \sqrt{(A_x - Q_{ix})^2 + (A_y - Q_{iy})^2}$$

finds the maximal lateral distance of eye protrusion of the left eye

$$\overline{BQ_r} = \sqrt{(B_x - Q_{rx})^2 + (B_y - Q_{ry})^2}$$

finds the maximal lateral distance of eye protrusion of the right eye

$$EPP = \frac{\overline{AQ_i} + \overline{BQ_r}}{2 * \overline{AB}}$$

finds the Eye Protuberance Proportion, here defined as the average distance of lateral protrusion of the eye relative to the overall distance across the forehead




Fig. 11F

48 / 65

Facial Descriptor Name: Eye Roundness ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the perpendicular height of deviation of the **Upper Media Eye Point** from the **Caudal Line of the Eye** relative to the overall length of the backside of the eye.

Mathematical Proof:

$$\overline{bbcc} = \sqrt{(bb_x - cc_x)^2 + (bb_y - cc_y)^2}$$

$$\overline{bbce} = \sqrt{(bb_x - ee_x)^2 + (bb_y - ee_y)^2}$$

$$\overline{ceee} = \sqrt{(cc_x - ee_x)^2 + (cc_y - ee_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{bbce}^2 - \overline{bbcc}^2 - \overline{ceee}^2}{-2 * \overline{bbcc} * \overline{ceee}} \right)$$

Finds the angle for $\angle BCE$, denoted here as θ

$$d = \sin(\theta) * \overline{ceee}$$

Finds the perpendicular roundness height of the eye

$$ERP = \frac{d}{\overline{bbcc}}$$

*Finds the **Eye Roundness Proportion**, here defined as the perpendicular deviation height of the **Upper Media Eye Point** relative to the overall length of the **Caudal Line of the Eye***




Fig. 11G

49 / 65

Facial Descriptor Name: Eye Size ProportionAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the size of the eye orbital in terms of length relative to the scale of the face as a whole.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

Finds the length of the True Line of the Face

$$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$$

$$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$$

$$\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}$$

$$\overline{bbcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$$

$$\overline{bbdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$\theta_0 = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{Abb}^2 - \overline{bbcc}^2}{-2 * \overline{Abb} * \overline{bbcc}} \right)$$

$$d_0 = \sin(\theta) * \overline{bbdd}$$

finds the perpendicular height of the eye

$$\theta_1 = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$$

$$d_1 = \sin(\theta) * \overline{bbdd}$$

finds the perpendicular depth of the eye

$$ESP_E = \frac{d_0 + d_1}{\overline{AB}}$$

finds Eye Size Proportion_{height}, which measures the cumulative perpendicular height of the eye relative to the length of the True Line of the Face




Fig. 11H

50 / 65

Facial Descriptor Name: Eye Size Proportion_{Length}Anatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the size of the eye orbital in terms of length relative to the scale of the face as a whole.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

*Finds the length of the **True Line of the Face***

$$\overline{Abb} = \sqrt{(A_x - bb_x)^2 + (A_y - bb_y)^2}$$

Finds the lateral distance of the eye

$$ESP_L = \overline{Abb} / \overline{AB}$$

*Finds the **Eye Size Proportion_{Height}** measure, which measures the size of the eye normalized against the conserved distance of the **True Line of the Face***




Fig. 11J

51 / 65

Facial Descriptor Name: Lower Minima Point Proportion EyeAnatomical Region of Face: AR11_Eye ShapeGeneral Description:

Describes the location of the lowest point of the eye orbital relative to the lateral extrema of the eye. Identifies "almond"-shaped eyes.

Mathematical Proof:

$$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$$

$$\overline{Add} = \sqrt{(dd_x - A_x)^2 + (dd_y - A_y)^2}$$

$$\overline{bbdd} = \sqrt{(dd_x - bb_x)^2 + (dd_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{Add}^2 - \overline{Abb}^2 - \overline{bbdd}^2}{-2 * \overline{Abb} * \overline{bbdd}} \right)$$

Finds the angle measure $\angle ABD$, denoted here as θ

$$d = \cos \theta * \overline{bbdd}$$

Finds the distance between the right extrema point of the eye and the perpendicular intersect point of the lower minima point of the eye

$$UMPP = d / \overline{Abb}$$

Finds the Lower Minima Point Proportion of the Eye, which is here defined as the proportion of the lateral distance across the eye located behind the perpendicular intersect of the lower minima point of the eye




Fig. 11K

52 / 65

Facial Descriptor Name: Top Eye AngleAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes degree of angulation in the bone structure of the upper portion of the eye orbital. Differentiates between hard and soft eyes. Partially identifies triangularly-shaped eyes.

Mathematical Proof:

$$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$$

$$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$$

$$\overline{bbcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{Abb}^2 - \overline{Acc}^2 - \overline{bbcc}^2}{-2 * \overline{Acc} * \overline{bbcc}} \right)$$

*Finds angle value for **Top Eye Angle** ($\angle ACB$),
denoted here as θ*




Fig. 11L

53 / 65

Facial Descriptor Name: Upper Maxima Point Proportion EyeAnatomical Region of Face: AR11_EyeShapeGeneral Description:

Describes the location of the highest point of the eye orbital relative to the lateral extrema of the eye. Identifies triangular-shaped eyes.

Mathematical Proof:

$$\overline{Abb} = \sqrt{(bb_x - A_x)^2 + (bb_y - A_y)^2}$$

$$\overline{Acc} = \sqrt{(cc_x - A_x)^2 + (cc_y - A_y)^2}$$

$$\overline{bcc} = \sqrt{(cc_x - bb_x)^2 + (cc_y - bb_y)^2}$$

Finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{Acc}^2 - \overline{Abb}^2 - \overline{bcc}^2}{-2 * \overline{Abb} * \overline{bcc}} \right)$$

Finds the angle measure $\angle ABC$, denoted here as θ

$$d = \cos \theta * \overline{bcc}$$

Finds the distance between the right extrema point of the eye and the perpendicular intersect point of the upper maxima point of the eye

$$UMPP = d / \overline{Abb}$$

Finds the **Upper Maxima Point Proportion of the Eye**, which is here defined as the proportion of the lateral distance across the eye located behind the perpendicular intersect of the upper maxima point of the eye




Fig. 11M

54 / 65

Facial Descriptor Name: Forehead Width AngleAnatomical Region of Face: AR12_ForeheadWidthGeneral Description:

Describes the degree to which the forehead widens beyond the nares (central line of the skull).

Mathematical Proof:

$$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$$

Finds the slope of the True Line of the Forehead, here defined as the line between the inner extrema points of the eyes

$$m_p = -(m_{ab})^{-1}$$

Finds the slope perpendicular to the True Line of the Forehead

$$R_x = \frac{m_{ab} * A_x - m_p * C_x + C_y - A_y}{m_{ab} - m_p}$$

Finds the x-coordinate of the intersection point between the true line of the face and its perpendicular bisector inclusive of point C

$$R_y = m_{ab}(R_x - A_x) + A_y$$

Finds the y-coordinate of intersect point "R"

$$S_x = \frac{m_{ab} * A_x - m_p * D_x + D_y - A_y}{m_{ab} - m_p}$$

Finds the x-coordinate of the intersection point between the true line of the forehead and its perpendicular bisector inclusive of pint D

$$S_y = m_{ab}(S_x - A_x) + A_y$$

Finds the y-coordinate of intersect point "S"

$$\overline{AC} = \sqrt{(C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{AR} = \sqrt{(A_x - R_x)^2 + (A_y - R_y)^2}$$

$$\overline{BD} = \sqrt{(D_x - B_x)^2 + (D_y - B_y)^2}$$

$$\overline{BS} = \sqrt{(B_x - S_x)^2 + (B_y - S_y)^2}$$

Finds distance values for all sides of triangles

$$\theta_R = \sin^{-1} \left(\frac{\overline{AR}}{\overline{AC}} \right)$$

Finds the angle measure $\angle ACR$ of forehead protuberance for the left side of the face

$$\theta_S = \sin^{-1} \left(\frac{\overline{BS}}{\overline{BD}} \right)$$

Finds the angle measure $\angle BDS$ of forehead protuberance for the right side of the face

$$FWA = (\theta_R + \theta_S) / 2$$

Finds the Forehead Width Angle, the overage of the two angles of deviation of the extrema points of the eyes from the center line of the face




Fig. 12

55 / 65

Facial Descriptor Name: Cheek-to-Zygomatic Height ProportionAnatomical Region of Face: AR13_ZygomaticProcessGeneral Description:

Describes the ratio of Cheek and Zygomatic Process height in terms of distance from the topline of the face.

Mathematical Proof:

$$m_{yz} = \frac{Z_y - Y_y}{Z_x - Y_x}$$

finds the slope of the Zygomatic Ridge

$$m_{ab} = \frac{A_y - B_y}{A_x - B_x}$$

finds the slope of the True Line of the Face

$$m_{ys} = \frac{Z_x - Y_x}{Z_y - Y_y}$$

finds the slope of the Line of the Forehead

$$m_p = -(m_y)^{-1}$$

finds the slope perpendicular to the Zygomatic Ridge

$$Q_x = \frac{m_{ef} * E_x - m_p * Z_x + Z_y - E_y}{m_{ef} - m_p}$$

$$Q_y = m_{ef}(Q_x - E_x) + E_y$$

finds the x-coordinate and y-coordinate of intersect point Q

$$R_x = \frac{m_{ab} * A_x - m_p * Y_x + Y_y - A_y}{m_{ab} - m_p}$$

$$R_y = m_{ab}(R_x - A_x) + A_y$$

finds the x-coordinate and y-coordinate of intersect point R

$$RY = \sqrt{(R_x - Y_x)^2 + (R_y - Y_y)^2}$$

finds the height of line RY, here defined as the height of the cheek

$$QZ = \sqrt{(Q_x - Z_x)^2 + (Q_y - Z_y)^2}$$

finds the height of line RY, here defined as the height of the Zygomatic Process

$$CLHP = RY/QZ$$

finds the Cheek-to-Zygomatic Height Proportion, here defined as the ratio between the distance from the Distal Cheek Point to the True Line of the Face and the distance from the Zygomatic Process Point and the Line of the Forehead




Fig. 13A

56 / 65

Facial Descriptor Name: Zygomatic Ridge AnglesAnatomical Region of Face: AR13_ZygomaticProcessesGeneral Description:

Describes the angle of the Zygomatic Ridge, from the point of the Zygomatic Process Point to the Distal Cheek Point, relative to the upper and lower lines of the face.

Mathematical Proof:

$$m_{yz} = \frac{Z_y - Y_y}{Z_x - Y_x}$$

finds the slope of the Zygomatic Ridge

$$m_{ab} = \frac{B_y - A_y}{B_x - A_x}$$

finds the slope of the True Line of the Face

$$m_{mn} = \frac{M_y - N_y}{M_x - N_x}$$

finds the slope of the Line of the Jaw

$$R_x = \frac{m_{ab} * A_x - m_{yz} * B_x + Z_x - A_x}{m_{ab} - m_{yz}}$$

$$R_y = m_{ab}(R_x - A_x) + A_y$$

finds the x-coordinate and y-coordinate of intersect point R

$$Q_x = \frac{m_{mn} * N_x - m_{yz} * Z_x + Z_x - N_x}{m_{mn} - m_{yz}}$$

$$Q_y = m_{mn}(Q_x - N_x) + N_y$$

finds the x-coordinate and y-coordinate of intersect point Q

$$BR = \sqrt{(B_x - R_x)^2 + (B_y - R_y)^2} \quad NQ = \sqrt{(N_x - Q_x)^2 + (N_y - Q_y)^2}$$

$$BY = \sqrt{(B_x - Y_x)^2 + (B_y - Y_y)^2} \quad NY = \sqrt{(N_x - Y_x)^2 + (N_y - Y_y)^2}$$

$$RY = \sqrt{(R_x - Y_x)^2 + (R_y - Y_y)^2} \quad QY = \sqrt{(Q_x - Y_x)^2 + (Q_y - Y_y)^2}$$

finds the distance values for all legs of the triangles

$$ZRAU = \theta_0 = \cos^{-1} \left(\frac{BY^2 - RB^2 - RY^2}{-2 * RB * RY} \right)$$

finds the Zygomatic Ridge Angle_{upper}, here defined as the angle of the Zygomatic Ridge bone as it relates to the True Line of the Face

$$ZRAL = \theta_1 = \cos^{-1} \left(\frac{NY^2 - QY^2 - QN^2}{-2 * QY * QN} \right)$$

finds the Zygomatic Ridge Angle_{lower}, here defined as the angle of the Zygomatic Ridge bone as it relates to the Line of the Jaw




Fig. 13B

57 / 65




Fig. 14

58 / 65




Fig. 15

59 / 65




Fig. 16

60 / 65




Fig. 17

61 / 65




Fig. 18




Fig. 19





Fig. 20

**Fig. 21**




Fig. 22

Facial Descriptor Name: Degree of Facial Inflexion:

Anatomical Region of Face: AR01_FacialProfile

General Description:

Describes the degree of structural concavity/convexity of the **True Line of the Face**. Differentiate between a concave "dished", convex "roman", or straight bone structure.

Mathematical Proof:

$$\overline{AB} = \sqrt{(B_x - A_x)^2 + (B_y - A_y)^2}$$

$$\overline{AC} = \sqrt{((C_x - A_x)^2 + (C_y - A_y)^2}$$

$$\overline{BC} = \sqrt{(C_x - B_x)^2 + (C_y - B_y)^2}$$

finds distance values for all sides of triangle

$$\theta = \cos^{-1} \left(\frac{\overline{BC}^2 - \overline{AB}^2 - \overline{AC}^2}{-2 * \overline{AB} * \overline{AC}} \right)$$

finds the angle for $\angle BAC$, denoted here as θ

$$d = \sin(\theta) * \overline{AC}$$

finds the height of triangle $\triangle ABC$, the distance of facial inflexion

$$M_{AB} = \frac{(A_y - B_y)}{(A_x - B_x)}$$

finds the slope of line $\overline{AB}$

$$Q_x = \left(\frac{C_y - A_y}{M_{AB}} \right) + A_x$$

finds the x-coordinate of point Q intersected by line $\overline{AB}$ and its horizontal bisector inclusive of point C

$$\sigma = Q_x - C_x$$

finds a value for which σ is either positive or negative, indicating respectively either convexity or concavity by the location of point C relative to the position of point Q on the Profile Line of the face

$$\sigma_i = \frac{\sigma}{|\sigma|}$$

finds m , here defined of the Constant of Concavity with magnitude 1 indicating direction of inflexion via sign (+)

$$DoFI = \sigma_i * \left(\frac{d}{\overline{AB}} \right)$$

*finds the Degree of Facial Inflexion; here defined as the degree of perpendicular deviation of the Upper Profile of the skull from the **True Line of the Face** relative to the overall length of the face.*




Fig. 1A