



Office de la Propriété

Intellectuelle
du Canada

Un organisme
d'Industrie Canada

Canadian
Intellectual Property
Office

An agency of
Industry Canada

CA 2477646 C 2012/11/13

(11)(21) **2 477 646**

(12) **BREVET CANADIEN**
CANADIAN PATENT

(13) **C**

(86) Date de dépôt PCT/PCT Filing Date: 2003/03/07
(87) Date publication PCT/PCT Publication Date: 2003/09/25
(45) Date de délivrance/Issue Date: 2012/11/13
(85) Entrée phase nationale/National Entry: 2004/08/20
(86) N° demande PCT/PCT Application No.: US 2003/006778
(87) N° publication PCT/PCT Publication No.: 2003/077800
(30) Priorité/Priority: 2002/03/11 (US10/095,507)

(51) Cl.Int./Int.Cl. *A61F 2/24* (2006.01)


(72) Inventeurs/Inventors:
MATHIS, MARK L., US;
NIEMINEN, GREGORY D., US

(73) Propriétaire/Owner:
CARDIAC DIMENSIONS, INC., US

(74) Agent: FETHERSTONHAUGH & CO.

(54) Titre : DISPOSITIF, ENSEMBLE ET METHODES DE REPARATION POUR VALVULE MITRALE

(54) Title: DEVICE, ASSEMBLY AND METHOD FOR MITRAL VALVE REPAIR



(57) Abrégé/Abstract:

A mitral valve therapy device (30) effects the condition of a mitral valve annulus (20) of a heart (10). The device (30) includes an elongated member (32) dimensioned to be placed in the coronary sinus (14) of the heart (10) adjacent the mitral valve annulus (20). The elongated member (32) is flexible when placed in the heart (10) in a first orientation to position the device (30) in the coronary sinus (14) adjacent the mitral valve annulus (20) and relatively inflexible when rotated into a second orientation after the device (30) is positioned in the coronary sinus (14) adjacent to the mitral valve annulus (20) to substantially straighten and increase the radius of curvature of the mitral valve annulus (20).

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
25 September 2003 (25.09.2003)

PCT

(10) International Publication Number
WO 03/077800 A1

(51) International Patent Classification⁷: A61F 2/06

(21) International Application Number: PCT/US03/06778

(22) International Filing Date: 7 March 2003 (07.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/095,507 11 March 2002 (11.03.2002) US

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US 10/095,507 (CIP)
Filed on 11 March 2002 (11.03.2002)

(71) Applicant (for all designated States except US): CAR-DIAC DIMENSIONS, INC. [US/US]; 5540 Lake Washington Blvd., Kirkland, WA 98033 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MATHIS, Mark, L. [US/US]; 10624 NE 60th St., Kirkland, WA 98033 (US). NIEMINEN, Gregory, D. [US/US]; 20206-100th Avenue NE, Bothell, WA 98011 (US).

(74) Agents: GRAY, Richard, O., Jr. et al.; Graybeal Jackson Haley LLP, 155-108th Avenue NE, Suite 350, Bellevue, WA 98004 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE, ASSEMBLY AND METHOD FOR MITRAL VALVE REPAIR



(57) Abstract: A mitral valve therapy device (30) effects the condition of a mitral valve annulus (20) of a heart (10). The device (30) includes an elongated member (32) dimensioned to be placed in the coronary sinus (14) of the heart (10) adjacent the mitral valve annulus (20). The elongated member (32) is flexible when placed in the heart (10) in a first orientation to position the device (30) in the coronary sinus (14) adjacent the mitral valve annulus (20) and relatively inflexible when rotated into a second orientation after the device (30) is positioned in the coronary sinus (14) adjacent to the mitral valve annulus (20) to substantially straighten and increase the radius of curvature of the mitral valve annulus (20).

WO 03/077800 A1

DEVICE, ASSEMBLY AND METHOD FOR MITRAL VALVE REPAIR*Field of the Invention:*

[1] The present invention generally relates to a device, assembly and method for treating dilated cardiomyopathy of a heart. The present invention more particularly relates to mitral valve annulus device, assembly, and method wherein the device is flexible when in a first orientation to conform to the coronary sinus adjacent the mitral valve annulus and relatively rigid when rotated into a second orientation to reshape the mitral valve annulus.

Background of the Invention:

[2] The human heart generally includes four valves. Of these valves, a most critical one is known as the mitral valve. The mitral valve is located in the left atrial ventricular opening between the left atrium and left ventricle. The mitral valve is intended to prevent regurgitation of blood from the left ventricle into the left atrium when the left ventricle contracts. In preventing blood regurgitation the mitral valve must be able to withstand considerable back pressure as the left ventricle contracts.

[3] The valve cusps of the mitral valve are anchored to muscular wall of the heart by delicate but strong fibrous cords in order to support the cusps during left ventricular contraction. In a healthy mitral valve, the geometry of the mitral valve ensures that the cusps overlie each other to preclude regurgitation of the blood during left ventricular contraction.

[4] The normal functioning of the mitral valve in preventing regurgitation can be impaired by dilated cardiomyopathy caused by disease or certain natural defects. For example, certain diseases may cause dilation of the mitral

valve annulus. This can result in deformation of the mitral valve geometry to cause ineffective closure of the mitral valve during left ventricular contraction. Such ineffective closure results in leakage through the mitral valve and 5 regurgitation. Diseases such as bacterial inflammations of the heart or heart failure can cause the aforementioned distortion or dilation of the mitral valve annulus. Needless to say, mitral valve regurgitation must not go uncorrected.

[5] One method of repairing a mitral valve having 10 impaired function is to completely replace the valve. This method has been found to be particularly suitable for replacing a mitral valve when one of the cusps has been severely damaged or deformed. While the replacement of the entire valve eliminates the immediate problem associated with 15 a dilated mitral valve annulus, presently available prosthetic heart valves do not possess the same durability as natural heart valves.

[6] Various other surgical procedures have been 20 developed to correct the deformation of the mitral valve annulus and thus retain the intact natural heart valve function. These surgical techniques involve repairing the shape of the dilated or deformed valve annulus. Such techniques, generally known as annuloplasty, require 25 surgically restricting the valve annulus to minimize dilation. Here, a prosthesis is typically sutured about the base of the valve leaflets to reshape the valve annulus and restrict the movement of the valve annulus during the opening and closing of the mitral valve.

[7] Many different types of prostheses have been 30 developed for use in such surgery. In general, prostheses are annular or partially annular shaped members which fit about the base of the valve annulus. The annular or partially

annular shaped members may be formed from a rigid material, such as a metal, or from a flexible material.

[8] While the prior art methods mentioned above have been able to achieve some success in treating mitral regurgitation, they have not been without problems and potential adverse consequences. For example, these procedures require open heart surgery. Such procedures are expensive, are extremely invasive requiring considerable recovery time, and pose the concomitant mortality risks associated with such procedures. Moreover, such open heart procedures are particularly stressful on patients with a comprised cardiac condition. Given these factors, such procedures are often reserved as a last resort and hence are employed late in the mitral regurgitation progression. Further, the effectiveness of such procedures is difficult to assess during the procedure and may not be known until a much later time. Hence, the ability to make adjustments to or changes in the prostheses to obtain optimum effectiveness is extremely limited. Later corrections, if made at all, require still another open heart surgery.

[9] An improved therapy to treat mitral regurgitation without resorting to open heart surgery has recently been proposed. This is rendered possible by the realization that the coronary sinus of a heart is near to and at least partially encircles the mitral valve annulus and then extends into a venous system including the great cardiac vein. As used herein, the term "coronary sinus" is meant to refer to not only the coronary sinus itself but in addition, the venous system associated with the coronary sinus including the great cardiac vein. The therapy contemplates the use of a device introduced into the coronary sinus to reshape and advantageously effect the geometry of the mitral valve annulus.

[10] The device includes a resilient member having a cross sectional dimension for being received within the coronary sinus of the heart and a longitudinal dimension having an unstressed arched configuration when placed in the coronary sinus. The device partially encircles and exerts an inward pressure on the mitral valve. The inward pressure constricts the mitral valve annulus, or at least a portion of it, to essentially restore the mitral valve geometry. This promotes effective valve sealing action and eliminates mitral regurgitation.

[11] The device may be implanted in the coronary sinus using only percutaneous techniques similar to the techniques used to implant cardiac leads such as pacemaker leads. One proposed system for implanting the device includes an elongated introducer configured for being releasably coupled to the device. The introducer is preferably flexible to permit it to advance the device into the heart and into the coronary sinus through the coronary sinus ostium. To promote guidance, an elongated sheath is first advanced into the coronary sinus. Then, the device and introducer are moved through a lumen of the sheath until the device is in position within the coronary sinus. Because the device is formed of resilient material, it conforms to the curvatures of the lumen as it is advanced through the sheath. The sheath is then partially retracted to permit the device to assume its unstressed arched configuration. Once the device is properly positioned, the introducer is then decoupled from the device and retracted through the sheath. The procedure is then completed by the retraction of the sheath. As a result, the device is left within the coronary sinus to exert the inward pressure on the mitral valve to restore mitral valve geometry.

[12] The foregoing therapy has many advantages over the traditional open heart surgery approach. Since the device,

system and method may be employed in a comparatively noninvasive procedure, mitral valve regurgitation may be treated at an early stage in the mitral regurgitation progression. Further, the device may be placed with relative 5 ease by any minimally invasive cardiologist. Still further, since the heart remains completely intact throughout the procedure, the effectiveness of the procedure may be readily determined. Moreover, should adjustments be deemed desirable, such adjustments may be made during the procedure and before 10 the patient is sent to recovery.

[13] Another approach to treat mitral regurgitation with a device in the coronary sinus is based upon the observation that the application of a localized force against a discrete portion of the mitral valve annulus can terminate mitral 15 regurgitation. This suggests that mitral regurgitation may be localized and nonuniform. Hence, the device applies a force to one or more discrete portions of the atrial wall of the coronary sinus to provide localized mitral valve annulus reshaping instead of generalized reshaping of the mitral valve 20 annulus. Such localized therapy would have all the benefits of the generalized therapy. In addition, a localized therapy device may be easier to implant and adjust.

[14] A still further approach to treat mitral regurgitation from the coronary sinus of the heart 25 contemplates a device having a first anchor configured to be positioned within and fixed to the coronary sinus of the heart adjacent the mitral valve annulus within the heart, a cable fixed to the first anchor and extending proximally from the first anchor within the heart, a second anchor configured to be positioned in and fixed in the heart proximal to the first anchor and arranged to slidably receive the cable, and a lock that locks the cable on the second anchor. When the first and 30 second anchors are fixed within the heart, the cable may be

drawn proximally and locked on the second anchor. The geometry of the mitral valve is thereby effected. This approach provides flexibility in that the second anchor may be positioned and fixed in the coronary sinus or alternatively, 5 the second anchor may be positioned and fixed in the right atrium. This approach further allows adjustments in the cable tension after implant.

[15] A still further alternative for treating mitral regurgitation contemplates a device having a first anchor 10 configured to be positioned within and anchored to the coronary sinus of the heart adjacent the mitral valve annulus within the heart. A second anchor is configured to be positioned within the heart proximal to the first anchor and adjacent the mitral valve annulus within the heart. A 15 connecting member, having a fixed length, is permanently attached to the first and second anchors. As a result, when the first and second anchors are within the heart with the first anchor anchored in the coronary sinus, the second anchor may be displaced proximally to effect the geometry of the 20 mitral valve annulus and released to maintain the effect on the mitral valve geometry. The second anchor may be configured, when deployed, to anchor against distal movement but be moveable proximally to permit the second anchor to be displaced proximally within the coronary sinus.

[16] A further approach uses staple devices for effecting 25 mitral valve annulus geometry of a heart. The staples are carried in an elongated catheter placeable in the coronary sinus of the heart adjacent the mitral valve annulus. The staples include first and second leg portions, each leg portion terminating in a tissue piercing end, and a connection portion extending between the first and second leg portions. 30 The connection portions have an initial stressed and distorted configuration to separate the first and second leg portions by

a first distance when the tissue piercing ends pierce the mitral valve annulus and a final unstressed and undistorted configuration after the tissue piercing ends pierce the mitral valve annulus to separate the first and second leg portions by 5 a second distance, the second distance being shorter than the first distance. A tool forces the staples from the catheter to cause the tissue piercing ends of the first and second leg portions to pierce the mitral valve annulus with the connection portion of the at least one staple in the initial 10 configuration. The catheter includes a tubular wall having break-away slots adjacent the staples to permit the staples to be forced from the catheter into the adjacent tissue.

[17] The present invention provides a still further approach for effecting mitral valve annulus geometry of a 15 heart.

SUMMARY OF THE INVENTION

[18] The invention provides a device that effects the condition of a mitral valve annulus of a heart. The device 20 includes an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member having a relatively low resistance to flexure in a first direction and a relatively high resistance to flexure in a second direction. The first and second 25 directions may lie in the same plane.

[18A] Various embodiments of this invention provide a device that effects the condition of a mitral valve annulus of a heart comprising an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member being flexible when placed in the heart in a first orientation to position the device in the coronary sinus adjacent the mitral valve annulus and relatively inflexible when rotated into a second orientation after the device is positioned in the coronary sinus adjacent to the mitral valve annulus.

[18B] Various embodiments of this invention provide a device that effects the condition of a mitral valve annulus of a heart comprising: an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member having a relatively low resistance to flexure in a first direction and a relatively high resistance to flexure in a second direction; an expandable anchor at a first end of the elongated member adapted to anchor the device in the coronary sinus.

[18C] Various embodiments of this invention provide a device that effects the condition of a mitral valve annulus of a heart comprising an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member having a relatively low resistance to flexure in a first direction and a relatively high resistance to flexure in a second direction, wherein the elongated member includes a first longitudinal side facing the first direction and a first plurality of notches formed in the first longitudinal side to provide the elongated member with the relatively low resistance to flexure in the first direction, and wherein the elongated member includes a second longitudinal side

facing the second direction and a second plurality of notches formed in the second longitudinal side to render the elongated member stable when flexed in the second direction.

[18D] Various embodiments of this invention provide an assembly that effects the condition of a mitral valve annulus of a heart comprising: an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent to the mitral valve annulus, the elongated member being flexible when placed in the heart in a first orientation to conform to the coronary sinus and relatively inflexible when rotated into a second orientation; and a push member configured to be releasably coupled to the elongated member that advances the elongated member into the coronary sinus adjacent to the mitral valve annulus. The elongated member of this assembly may be the elongated member of a device of this invention as described above.

[19] The elongated member may include a first longitudinal side facing the first direction and a first plurality of notches formed in the first longitudinal side to provide the elongated member with the relatively low resistance to flexure in the first direction. The elongated member may also include a second longitudinal side facing the second direction and a second plurality of notches formed in the second longitudinal side to render the elongated member

stable when flexed in the second direction. The first plurality of notches are preferably larger than the second plurality of notches.

[20] The elongated member also has first and second ends and an anchor at each end that fix the device in the coronary sinus. Preferably each anchor anchors the device against longitudinal movement and rotational movement.

[21] The invention further provides a device that effects the condition of a mitral valve annulus of a heart including an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus. The elongated member is flexible when placed in the heart in a first orientation to position the device in the coronary sinus adjacent the mitral valve annulus and relatively inflexible when rotated into a second orientation after the device is positioned in the coronary sinus adjacent to the mitral valve annulus.

[22] The elongated member has a first radius of curvature when in the first orientation and a second radius of curvature when in the second orientation. The first radius of curvature is less than the second radius of curvature.

[23] The invention still further provides a method of effecting the condition of a mitral valve annulus of a heart. The method includes the steps of providing a mitral valve annulus therapy device including an elongated member that is flexible when placed in the heart in a first orientation and relatively inflexible when rotated into a second orientation, advancing the device into the coronary sinus of the heart with the device in the first orientation until the device is adjacent the mitral valve annulus within the coronary sinus, and rotating the device into the second orientation.

[24] The method may further include the step of anchoring the device in the coronary sinus. The device is preferably anchored against at least rotational movement.

[25] The invention still further provides an assembly 5 that effects the condition of a mitral valve annulus of a heart. The assembly includes an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent to the mitral valve annulus. The elongated member is flexible when placed in the heart in a first orientation to conform to 10 the coronary sinus and relatively inflexible when rotated into a second orientation. The assembly further includes a push member configured to be releasably coupled to the elongated member that advances the elongated member into the coronary sinus adjacent to the mitral valve annulus.

[26] The push member rotates the elongated member into 15 the second orientation upon rotation of the push member. A U-joint releasably couples the elongated member to the push member.

[27] The assembly may further include a flexible catheter 20 having a lumen that receives the elongated member and push member to guide the elongated member into the coronary sinus. The elongated member may be rotated into the second orientation upon rotation of the catheter. The push member may be released from the elongated member with proximal 25 movement of the catheter.

[28] The elongated member has a first radius of curvature when in the first orientation and a second radius of curvature when in the second orientation. The first radius of curvature is less than the second radius of curvature. The elongated member also may have an anchor at each end that fix the device 30 in the coronary sinus. The anchors preferably anchor the device against both longitudinal and rotational movement.

BRIEF DESCRIPTION OF THE DRAWINGS

[29] The features of the present invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with further aspects and advantages thereof, may best be understood by making reference to the following description taken in conjunction with the accompanying drawings, in the several figures of which like reference numerals identify identical elements, and wherein:

10 [30] **FIG. 1** is a superior view of a human heart with the atria removed;

[31] **FIG. 2** is a side plan view of a mitral valve therapy device embodying the present invention;

15 [32] **FIG. 3** is a side plan view to an enlarged scale of a portion of the device of **FIG. 2**;

[33] **FIG. 4** is a partial superior view of a human heart illustrating a first step in the deployment of the mitral valve therapy device embodying the present invention;

20 [34] **FIG. 5** is a view similar to **FIG. 4** illustrating a further step in the deployment of the mitral valve therapy device;

[35] **FIG. 6** is a superior view of a human heart similar to **FIG. 4** illustrating the mitral valve therapy device deployed and anchored in the heart;

25 [36] **FIG. 7** is a partial perspective view of a coupling arrangement between the mitral valve therapy device and a deployment tool in accordance with an embodiment of the present invention; and

30 [37] **FIG. 8** is a partial perspective view illustrating the release of the coupling arrangement of **FIG. 7**.

DETAILED DESCRIPTION OF THE INVENTION

[38] Referring now to **FIG. 1**, it is a superior view of a human heart 10 with the atria removed to expose the mitral valve 12, the coronary sinus 14, the coronary artery 15, and 5 the circumflex artery 17 of the heart 10 to lend a better understanding of the present invention. Also generally shown in **FIG. 1** are the pulmonary valve 22, the aortic valve 24, and the tricuspid valve 26 of the heart 10.

[39] The mitral valve 12 includes an anterior cusp 16, a 10 posterior cusp 18 and an annulus 20. The annulus encircles the cusps 16 and 18 and maintains their spacing to provide a complete closure during a left ventricular contraction. As is well known, the coronary sinus 14 partially encircles the mitral valve 12 adjacent to the mitral valve annulus 20. As 15 is also known, the coronary sinus is part of the venus system of the heart and extends along the AV groove between the left atrium and the left ventricle. This places the coronary sinus essentially within the same plane as the mitral valve annulus making the coronary sinus available for placement of the 20 mitral valve therapy device of the present invention therein.

[40] **FIG. 2** shows a mitral valve therapy device 30 embodying the present invention. The device 30 takes the form of an elongated tubular member 32 which includes a distal anchor 34, a proximal anchor 36, a coupler 38, and a therapy 25 section 40.

[41] The anchors 34 and 36 are shown in **FIG. 2** in their predeployed configuration. As will be seen hereinafter, upon deployment of the device 30 in the coronary sinus, the anchors expand outwardly in a toggle bolt manner to anchor the device 30 in the coronary sinus against both longitudinal and rotational movement. To that end, at least the anchors 34 and 36 are formed from a material, such as Nitinol, having shape memory to implement their expansion. The rest of the device 30 may

also be formed from Nitinol or other non-rigid biocompatible materials such as stainless steel.

[42] The coupler 38 releasably couples the device to a deployment tool to be described hereinafter during the implant 5 and deployment of the device 30. The coupler forms with the deployment tool a U-joint to permit flexibility. As will also be seen hereinafter, the deployment tool includes a complementary coupler with shape memory for releasing the deployment tool from the elongated member 32.

[43] FIG. 3 shows a portion of the therapy section 40 in greater detail. The elongated member 32, within the therapy section 40, is configured to permit a first flexibility in the elongated member when bent in a first direction and a second and less flexibility in the elongated member 32 when bent in a 15 second direction. More specifically, the elongated member 32 includes a first plurality of slots or notches 42 along a side thereof and a second plurality of slots or notches 44 along an opposite side thereof. The first plurality of notches 42 render the elongated member flexible for bending in the first 20 direction as indicated by arrows 46 and the second plurality of notches 44 render the elongated member flexible for bending in the second direction as indicated by arrows 48. The first plurality of notches 42 are wider or larger than the second plurality of notches 44 so that the elongated member 32 has a 25 relatively low resistance to flexure or bending in the first direction 46 and a relatively high resistance to flexure or bending in the second direction 48.

[44] The relative resistances to flexure allow the device 30 to be readily positioned in the coronary sinus of the heart 30 and then deployed. While in a first orientation, with the first plurality of notches adjacent the mitral valve annulus, the device 30, as it is advanced into the coronary sinus, is permitted to bend and conform to the shape of the coronary

sinus. Once properly positioned in the coronary sinus adjacent the mitral valve annulus, the device may be rotated into a second orientation wherein the second plurality of notches 44 are adjacent to the mitral valve annulus. The 5 device 30 may be rotated by either rotating the deployment tool or by rotating a deployment catheter, to be described hereinafter, in which the device resides and which may be used to guide the device 30 into the proper position within the coronary sinus. Once rotated into the second orientation, the 10 elongated member 32 will substantially straighten to act upon and increase the radius of curvature of the adjacent mitral valve annulus.

[45] The second plurality of slots 44 permit slight bending of the elongated member towards the mitral valve 15 annulus to render the device stable in the second orientation. Were the device not permitted to bend slightly towards the mitral valve annulus while in the second orientation, the device could revert to the then more stable first orientation away from the mitral valve annulus. This and further aspects 20 of the present invention will be seen more fully with reference to **FIGS. 4-6** which illustrate the deployment of the device 30 in accordance with an embodiment of the present invention.

[46] **FIG. 4** illustrates an assembly 28, including the 25 device 30, for effecting the geometry of the mitral valve annulus 20. The assembly is illustrated in an initial stage of deploying the device 30. The assembly includes the device 30, a deployment catheter 50, and the deployment tool or push member 52. The distal end of the push member 52 is coupled to 30 the coupler 38 of the device 30. Both the device 30 and push member 52 are within a lumen 54 of the deployment catheter 50 which is dimensioned to permit the device 30 and push member

52 to be advanced down into the coronary sinus in which the catheter 50 is already positioned.

[47] As the device 30 is advanced into the coronary sinus and adjacent the mitral valve annulus, the device is disposed 5 in the first orientation with the first plurality of notches 42 adjacent the mitral valve annulus 20. This permits the device 30 to bend with relatively low resistance to flexure to conform to the shape of the coronary sinus with a first radius of curvature. As a result, the device 30 may be readily 10 positioned adjacent the mitral valve annulus 20.

[48] With the device 30 positioned in the coronary sinus 14 adjacent the mitral valve annulus 20 as illustrated in **FIG. 4**, the device may now be rotated into the second orientation as illustrated in **FIG. 5**. In the second orientation, the 15 second plurality of notches or slots 44 are now adjacent the mitral valve annulus. Because the second plurality of notches are relatively narrow, the higher resistance of flexure of the device in the second orientation will cause the device to substantially straighten to a second and increased radius of 20 curvature. This causes the device to act upon the geometry of the mitral valve annulus 20 by increasing its radius of curvature as illustrated in **FIG. 5** to treat and terminate mitral regurgitation, for example.

[49] The device 30 may be rotated by rotating the 25 deployment catheter 50 or by rotating the deployment tool 52 relative to the catheter 50. This permits the assembly 28 to remain intact while the effectiveness of the device placement is evaluated. Should moving the device to a slightly 30 different position be required, this may be accomplished by simply rotating the device back to the first orientation and repositioning the device with the deployment tool 52.

[50] With the device 30 positioned as shown in **FIG. 5** and its effectiveness confirmed, the device 30 may now be fully

deployed. To that end, the deployment catheter 50 is pulled proximally while the deployment tool or push member 52 is held stationary. This removes the catheter from the device 30.

[51] As illustrated in **FIG. 6**, the distal anchor 34 is released to expand in a toggle bolt like manner and anchor the device against both longitudinal and rotational movement. The distal anchor 34 is divided into a pair of sections 33 and 35 which are coupled together by a flexible coupling 37. This enables the anchor 34 to better conform to the bend in the coronary sinus at this location of the heart.

[52] Further proximal movement of the deployment catheter 50 releases the proximal anchor 36. It also expands in a toggle bolt like manner to anchor the device against both longitudinal and rotational movement.

[53] When the deployment catheter is moved proximally enough to expose the coupling 38, the coupling 38 is removed from the deployment tool. The deployment tool and the catheter may now be removed from the patient together. Hence, **FIG. 6** illustrates the device 30 fully deployed and anchored without the deployment catheter or deployment tool.

[54] **FIGS. 6** and **7** show the coupling and decoupling of the device 30 and the deployment tool or push member 52 in greater detail. In **FIG. 7** the coupler 38 is shown engaged with a complimentary coupler 58 of the deployment tool 52. The configuration of the couplers 38 and 58 form a U-joint allowing flexibility between the device 30 and the tool 52.

[55] The coupler 58 of the deployment tool 52 has shape memory for disengaging the coupler 38 of the device 30 when the catheter is moved sufficiently proximally to expose the couplers 38 and 58. This is illustrated in **FIG. 8**. Here it can be seen that the coupler 58 has sufficiently disengaged the coupler 38 of the device 30 to enable the deployment tool 52 to be removed from the patient with the fully deployed and

anchored device 30 within the heart to provide its therapeutic effect as illustrated in **FIG. 6.**

[56] While particular embodiments of the present invention have been shown and described, modifications may be 5 made. It is therefore intended in the appended claims to cover all such changes and modifications which fall within the true spirit and scope of the invention.

What is claimed:

1. A device that effects the condition of a mitral valve annulus of a heart comprising an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member having a relatively low resistance to flexure in a first direction and a relatively high resistance to flexure in a second direction, wherein the elongated member includes a first longitudinal side facing the first direction and a first plurality of notches formed in the first longitudinal side to provide the elongated member with the relatively low resistance to flexure in the first direction, and wherein the elongated member includes a second longitudinal side facing the second direction and a second plurality of notches formed in the second longitudinal side to render the elongated member stable when flexed in the second direction.

2. The device of claim 1, wherein the first and second directions lie in the same plane.

3. The device of claim 1 or 2, wherein the first plurality of notches are larger than the second plurality of notches.

4. The device of claim 1, 2 or 3, wherein the first and second longitudinal sides are opposite each other.

5. The device of any one of claims 1 to 4, wherein the elongated member has first and second ends and wherein the device includes an anchor at each end that fix the device in the coronary sinus.

6. The device of claim 5, wherein each anchor anchors the device against longitudinal movement and rotational movement.

7. A device that effects the condition of a mitral valve annulus of a heart comprising an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member being flexible when placed in the heart in a first orientation to position the device in the coronary sinus adjacent the mitral valve annulus and relatively inflexible when rotated into a second orientation after the device is positioned in the coronary sinus adjacent to the mitral valve annulus.

8. The device of claim 7, wherein the elongated member is bent to conform to the shape of the coronary sinus when in the first orientation.

9. The device of claim 7 or 8, wherein the elongated member has a first radius of curvature when in the first orientation, a second radius of curvature when in the second orientation, and wherein the first radius of curvature is less than the second radius of curvature.

10. The device of claim 7, 8 or 9, wherein the elongated member has first and second ends and wherein the device includes an anchor at each end that fix the device in the coronary sinus.

11. The device of claim 10, wherein each anchor anchors the device against longitudinal movement and rotational movement.

12. An assembly that effects the condition of a mitral valve annulus of a heart comprising:

an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent to the mitral valve annulus, the elongated member being flexible when placed in the heart in a first orientation to conform to the coronary sinus and relatively inflexible when rotated into a second orientation; and

a push member configured to be releasably coupled to the elongated member that advances the elongated member into the coronary sinus adjacent to the mitral valve annulus.

13. The assembly of claim 12, wherein the push member rotates the elongated member into the second orientation upon rotation of the push member.

14. The assembly of claim 12 or 13, further comprising a U-joint that releasably couples the elongated member to the push member.

15. The assembly of claim 12, 13 or 14, further including a flexible catheter having a lumen that receives the elongated member and push member to guide the elongated member into the coronary sinus.

16. The assembly of claim 15, wherein the elongated member is rotatable into the second orientation upon rotation of the catheter.

17. The assembly of claim 15 or 16, wherein the push member is releasable from the elongated member with proximal movement of the catheter.

18. The assembly of any one of claims 12 to 17, wherein the elongated member has a first radius of curvature when in the first orientation, a second radius of curvature when in the second orientation, and wherein the first radius of curvature is less than the second radius of curvature.

19. The assembly of any one of claims 12 to 18, wherein the elongated member has first and second ends and further includes an anchor at each end that fix the device in the coronary sinus.






20. The assembly of claim 19, wherein each anchor anchors the device against longitudinal movement and rotational movement.

21. A device that effects the condition of a mitral valve annulus of a heart comprising:

an elongated member dimensioned to be placed in the coronary sinus of the heart adjacent the mitral valve annulus, the elongated member having a relatively low resistance to flexure in a first direction and a relatively high resistance to flexure in a second direction;




an expandable anchor at a first end of the elongated member adapted to anchor the device in the coronary sinus.

22. The device of claim 21, further comprising a second expandable anchor at a second end of the elongate member adapted to anchor the device in the coronary sinus.



SUBSTITUTE SHEET (RULE 26)

2/2

FIG. 4**FIG. 5****FIG. 6****SUBSTITUTE SHEET (RULE 26)**

