



(86) Date de dépôt PCT/PCT Filing Date: 2020/01/31
(87) Date publication PCT/PCT Publication Date: 2020/08/05
(45) Date de délivrance/Issue Date: 2021/10/19
(85) Entrée phase nationale/National Entry: 2020/06/25
(86) N° demande PCT/PCT Application No.: US 2020/016060
(87) N° publication PCT/PCT Publication No.: 2020/163162
(30) Priorités/Priorities: 2019/02/05 (US62/801,092);
2020/01/29 (US16/755,744)

(51) Cl.Int./Int.Cl. *B01D 33/067* (2006.01),
B01D 33/06 (2006.01)
(72) Inventeurs/Inventors:
GRACE, TODD, US;
STUBBLEFIELD, KENT, US
(73) Propriétaire/Owner:
ANDRITZ INC., US
(74) Agent: BERESKIN & PARR LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : ENSEMBLE PLAQUE FILTRANTE REMPLACABLE POUR UN FILTRE A TAMBOUR ROTATIF
(54) Title: REPLACEABLE FILTER PLATE ASSEMBLY FOR A ROTARY DRUM FILTER

(57) **Abrégé/Abstract:**

A removable filter plate for a rotary drum filter that reduces instances of welding to secure the filter plate to the drum and obviates the need for cap strips. An exemplary filter plate assembly in accordance with this disclosure comprises a filter plate and an engagement assembly, wherein the engager of the engagement assembly is configured to extend in a lateral direction toward the leading end or the trailing end of the filter plate, wherein an extended engager having an engagement end disposed under a shelf of the adjacent top hat mounting assembly defines a closed position, and wherein a retracted engager defines an open position.

ABSTRACT OF THE DISCLOSURE

A removable filter plate for a rotary drum filter that reduces instances of welding to secure the filter plate to the drum and obviates the need for cap strips. An exemplary filter plate assembly in accordance with this disclosure comprises a filter plate and an engagement assembly, wherein the engager of the engagement assembly is configured to extend in a lateral direction toward the leading end or the trailing end of the filter plate, wherein an extended engager having an engagement end disposed under a shelf of the adjacent top hat mounting assembly defines a closed position, and wherein a retracted engager defines an open position.

REPLACEABLE FILTER PLATE ASSEMBLY FOR A ROTARY DRUM FILTER

BACKGROUND OF THE INVENTION

TECHNICAL FIELD

[0001] The present disclosure relates generally to rotary drum filters configured to filter slurries and more particularly to filter plates in rotary vacuum drum washers, thickeners, and filters used in the pulp and paper, chemical recovery, waste separation, and mining industries.

RELATED ART

[0002] Several industries utilize rotary drum filters to separate filtrate from residue on an industrial scale. A typical rotary drum filter generally comprises a cylindrical drum mounted lengthwise for rotation in a tank or vat. Operators fill the vat with a slurry. The cylindrical drum comprises several divisions (*i.e.* cylindrical sectors) arrayed around the rotational axis. These divisions' radially outward surfaces define a filter deck assembly. The filter deck assemblies in turn comprise the outer surface of the drum. In practice, operators maintain a pressure differential between the inside and the outside of the drum. That is, the drum's interior generally exists at sub-atmospheric pressure. As a given filter deck assembly on a given division rotates through the slurry, the pressure differential pulls filtrate through the filter deck assembly. This in turn allows residue to accumulate on the filter deck assembly's outer surface. This accumulated residue may be a "pulp mat," a sediment "cake," or it may be referred to by other names depending upon the slurry that the rotary drum filter separates. When a division rotates above the slurry level, the pressure differential continues to pull entrapped liquid from the accumulated residue through the filter deck assembly and thereby begins to dry the accumulated residue.

[0003] The filtrate flows through the filter deck assembly toward the rotational axis. The filtrate then flows out of a supportive trunnion into a drop leg. The filtrate flowing down through the drop leg is the primary source of the pressure differential (*i.e.* it creates the vacuum pressure).

A stationary arced valve also sits in the trunnion upstream of the drop leg. The arced valve has a first end positioned at roughly the 12 o'clock position (*i.e.* the apex of rotation when the rotary drum filter is operational) and a second end positioned between roughly the 3 o'clock position (*i.e.* halfway along a given division's downward rotational journey) and the 5 o'clock position (*i.e.* about 30 degrees upstream of the nadir of rotation). As a filter deck assembly of a given division rotates past the apex and over the arced valve, the arced valve blocks the underside of the filter deck assembly from fluidly communicating with the drum interior and the drop leg, thereby equalizing pressure (*i.e.* releasing vacuum pressure) at the outer surface of the filter deck assembly.

[0004] A doctor blade, roller, belt, or other extracting apparatus then removes the accumulated residue from the filter deck assembly on the now pressure-equalized division. Typically, additional equipment then collects this residue for further processing. The now cleaned filter deck assembly continues to rotate downward toward the slurry. As the division rotates past the end of the valve, the pressure differential returns, thereby permitting the process to repeat as the division rotates through the slurry.

[0005] While the rotary drum filter design endures, the traditional design of the filter deck assembly contributes to problems that can lead to production loss. Traditional filter deck assemblies comprise corrugated filter plates. Each filter plate spans one or more grid supports. The respective filter plate ends engage a hat-shaped mounting clip that is in turn mounted on a grid support. Installers and servicers weld at least one end of the filter plate to a mounting clip to prevent filtrate from leaking back into the vat when the filter plate rotates downwardly. These "top hat" mounting clips also have a cap strip welded on top of (*i.e.* radially outward of) each mounting clip to define a generally C-shaped recess. Each end of the filter plate rests in one of these C-shaped recesses. Installers and servicers spot weld or tungsten inert gas ("T.I.G.") weld these cap strips to the mounting clips. Installers and servicers may also weld the ends of the filter plate to the mounting clip and/or cap strip to form a secure seal and fixedly install the filter plates. The filter plates, mounting clips, and cap strips, are typically all manufactured from stainless steel.

[0006] In practice, and depending upon the application, the temperature profile of the cylindrical drum may vary significantly, at least at startup. For example, if a rotary drum filter is used to dewater a pulp slurry, the starting temperature of the pulp slurry may be in a range of 180 degrees Fahrenheit (°F) to 200 °F in a first stage vat. The filtered pulp generally cools to about

140 °F by the time the pulp is removed from the drum. Likewise, the drum divisions that start in the vat will typically have a higher average temperature than the divisions that start above the vat. As the pulp mat rotates out of the vat, washers may spray the mat with water or other fluid to displace the entrapped slurry liquid. The expansion and contraction of the stainless steel in response to temperature fluctuations can stress the deck assembly welds, particularly the welds engaging the filter plates, mounting clips, and cap strips. Even though rotation and the materials of the cylindrical drum may eventually reduce the temperature differential over time, any remaining differential will still stress the welds. Furthermore, the cyclical loading and negative pressurization of the filter plates and unloading and depressurization of the filter plates also contributes to stressing and eventual failure of the welds. If left unaddressed, excessive or prolonged periods of stress will lead to weld failure. Weld failure between adjacent filter plates permits filtrate to flow back out of the filter deck assembly and into the vat, thereby reducing the drum filter's efficiency.

[0007] Deactivating the rotary drum filter to fix these problems results in production loss. Removing the welds to repair or rebuild the rotary drum filter can be time consuming and costly. The time and monetary cost motivates some mill operators to delay shutdowns until there is a risk of imminent equipment failure. This practice results in reduced equipment production as the problems continue to develop and efficiency continues to degrade. Furthermore, it takes more time to repair or rebuild a severely damaged rotary drum filter, thereby further exacerbating production loss.

[0008] Previously, others attempted to improve installation time with the design described in U.S. Pat. No. 9,669,337 to Giasson (hereinafter, "*Giasson*"). This design requires welding, gluing, or otherwise affixing the "top hat" mounting clips to the support grids and having a "snap in" cap strip. However, the "snap in" cap strip comprises a U-shaped piece and a generally planar top piece (*i.e.* a traditional cap strip) that is welded, glued, or otherwise fixedly engaged to the U-shaped piece. Furthermore, after installation, *Giasson* recommends welding or otherwise permanently engaging the removable cap strip into place. The presence of welds to secure: the mounting clips to the support grids, the components of the cap strip to one another, and optionally, the cap strip to the mounting clip, does nothing to address the problem of weld failure in the filter deck assembly.

SUMMARY OF THE INVENTION

[0009] The problem of production loss and risk of injury to nearby operating personnel due to weld fatigue in welds between filter plates and mounting clips in a filter plate assembly of a rotary drum filter is mitigated by the use of a removable filter plate for a rotary drum filter comprising: a filter plate; an engagement mechanism engaged to the filter plate, the engagement mechanism having an open position and a locked position, wherein the locked position is configured to engage the filter plate to the rotary drum filter.

[0010] In an exemplary embodiment, a replaceable filter deck assembly for a rotary drum filter comprises: a filter plate having a leading end distally disposed from a trailing end, and an axial filter plate bisection line extending through the filter plate; an engagement assembly engaged to the filter plate, the engagement assembly comprising: an engager, and an engager holder supporting the engager, wherein the engager is configured to extend in a lateral direction beyond the leading end or the trailing end of the filter plate, wherein an extended engager defines a closed position, and wherein the engager is configured to retract in the lateral direction toward the axial filter plate bisection line, and wherein a retracted engager defines an open position.

[0011] In other exemplary embodiments, the engager may be configured to move in an axial direction, wherein the engager disposed at a first axial location defines a closed position, and wherein the engager disposed at a second axial location defines an open position. In still other exemplary embodiments, the engager may be configured to move in both a lateral and an axial direction.

[0012] It is contemplated that an advantage of the present disclosure is that a filter plate assembly in accordance with the embodiments herein will allow installers and servicers to install replacement filter plates by dropping replacement filter plates into place without having to remove cap strips or other securing mechanisms that hinder installation. As a result, replaceable filter deck assemblies in accordance with this disclosure may contribute to a reduction in down time.

[0013] Another advantage of the present disclosures is that there is no longer a need for cap strips, thereby reducing the overall welds in the filter deck assembly and potentially extending the assembly's useful life.

[0014] Another potential advantage of certain exemplary embodiments is that the mounting clips can also be eliminated. In such weld-less embodiments, it is contemplated that the need to replace filter deck assemblies due to chlorine-induced corrosion will be obviated.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The foregoing will be apparent from the following more particular description of exemplary embodiments of the disclosure, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, with emphasis instead being placed upon illustrating the disclosed embodiments.

[0016] **FIG. 1** is a perspective view of a rotary drum filter, in particular, a vacuum washer used in the pulp and paper industry.

[0017] **FIG. 2** is a detailed perspective view of a portion of the deck assembly of **FIG. 1**.

[0018] **FIG. 3A** is a bottom-up view of an exemplary removable filter plate assembly in accordance with the present disclosure.

[0019] **FIG. 3B** is a side view of the exemplary removable filter plate assembly of **FIG. 3A** showing an engagement assembly in the closed position.

[0020] **FIG. 3C** is a side view of the exemplary removable filter plate assembly of **FIG. 3A** showing an engagement assembly in the open position.

[0021] **FIG. 4A** is a perspective view of the trailing end of an exemplary removable filter plate assembly showing the top of the engagement assembly in the open position.

[0022] **FIG. 4B** is a detailed perspective view of the trailing end of an exemplary removable filter plate assembly with a portion of the filter plate removed to better show the exemplary engagement assembly in the open position. In this exemplary embodiment, the engagement assembly is a latch assembly.

[0023] **FIG. 4C** is a detailed perspective view of the trailing end of an exemplary removable filter plate assembly with a portion of the filter plate removed to better show the exemplary latch assembly of **FIG. 4A** and **4B** in the locked position.

[0024] **FIG. 4D** is a perspective view of the trailing end of an exemplary removable filter plate assembly showing the top of the latch assembly of **FIGS. 4A - 4C** in the locked position.

[0025] **FIG. 5A** is a side view of the open position of another exemplary embodiment comprising a cam latch.

[0026] **FIG. 5B** is a side view of the closed position of another exemplary embodiment comprising a cam latch.

[0027] **FIG. 6A** is a perspective view of the trailing end of an exemplary removable filter plate assembly showing the top of the engagement assembly in the open position, wherein the engagement assembly comprises a laterally rotatable knob latch.

[0028] **FIG. 6B** is a detailed perspective view of the trailing end of an exemplary removable filter plate assembly with a portion of the filter plate removed to better show the exemplary knob latch assembly of **FIG. 6A** in the open position.

[0029] **FIG. 6C** is a detailed perspective view of the trailing end of an exemplary removable filter plate assembly with a portion of the filter plate removed to better show the exemplary knob latch assembly of **FIG. 6A** and **4B** in the locked position.

[0030] **FIG. 6D** is a perspective view of the trailing end of an exemplary removable filter plate assembly showing the top of the knob latch assembly of **FIGS. 4A - 4C** in the locked position.

[0031] **FIG. 7A** is a side view of an exemplary “weld-less” engagement assembly in the open position.

[0032] **FIG 7B** is a side view of an exemplary “weld-less” engagement assembly in the closed position.

[0033] **FIG. 8** is a cross-sectional view of an exemplary “weld-less” engagement assembly depicted in **FIG. 7**.

DETAILED DESCRIPTION OF THE INVENTION

[0034] The following detailed description of the preferred embodiments is presented only for illustrative and descriptive purposes and is not intended to be exhaustive or to limit the scope and spirit of the invention. The embodiments were selected and described to best explain the principles of the invention and its practical application. One of ordinary skill in the art will recognize that

many variations can be made to the invention disclosed in this specification without departing from the scope and spirit of the invention.

[0035] Corresponding reference characters indicate corresponding parts throughout the several views. Although the drawings represent embodiments of various features and components according to the present disclosure, the drawings are not necessarily to scale and certain features may be exaggerated in order to better illustrate embodiments of the present disclosure, and such exemplifications are not to be construed as limiting the scope of the present disclosure in any manner.

[0036] References in the specification to “one embodiment”, “an embodiment”, “an exemplary embodiment”, *etc.*, indicate that the embodiment described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to affect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

[0037] Although specific terms are used in the following description for the sake of clarity, these terms are intended to refer only to the particular structure of the embodiment selected for illustration in the drawings, and are not intended to define or limit the scope of the disclosure.

[0038] The singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Numerical values should be understood to include numerical values which are the same when reduced to the same number of significant figures and numerical values which differ from the states value by less than the experimental error of conventional measurement technique of the type described in the present application to determine the value.

[0039] All ranges disclosed herein are inclusive of the recited endpoint and are independently combinable (for example, the range “from 2 grams to 10 grams” is inclusive of the endpoints, 2 grams and 10 grams, and all intermediate values.

[0040] As used herein, approximating language may be applied to modify any quantitative representation that may vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about” and “substantially,”

may not be limited to the precise values specified. The modifier “about” should also be considered as disclosing the range defined by the absolute values of the two endpoints. For example, the expression “from about 212 °F to about 1,300 °F” also discloses the range “from 212 °F to 1,300 °F.”

[0041] It should be noted that many of the terms used herein are relative terms. For example, the terms “upper” and “lower” are relative to each other in location, *i.e.* an upper component is located at a higher elevation than a lower component in a given orientation, but these terms can change if the device is flipped. The terms “inlet” and “outlet” are relative to a fluid flowing through them with respect to a given structure, *e.g.* a fluid flows through the inlet into the structure and flows through the outlet out of the structure. The terms “upstream” and “downstream” are relative to the direction in which a fluid flows through various components, *i.e.* the flow of fluids through an upstream component prior to flowing through the downstream component.

[0042] The terms “horizontal” and “vertical” are used to indicate direction relative to an absolute reference, *i.e.* ground level. However, these terms should not be construed to require structure to be absolutely parallel or absolutely perpendicular to each other. For example, a first vertical structure and a second vertical structure are not necessarily parallel to each other. The terms “top” and “bottom” or “base” are used to refer to locations/surfaces where the top is always higher than the bottom/base relative to an absolute reference, *i.e.* the surface of the Earth. The terms “upwards” and “downwards” are also relative to an absolute reference; an upwards flow is always against the gravity of the Earth.

[0043] The term “directly,” wherein used to refer to two system components, such as valves or pumps, or other control devices, or sensors (*e.g.* temperature or pressure), may be located in the path between the two named components.

[0044] **FIG. 1** depicts a typical rotary drum filter **10**. Although designs vary slightly, a typical rotary drum filter **10** comprises a cylindrical drum **12** disposed lengthwise in a vat (not depicted). Closure plates **14** bound each end **7, 9** of the drum **12**. Support ribs **21** extend generally radially outward from structures surrounding the axis of rotation **A** toward the drum’s outer circumference **C**. Multiple ring supports **19** support the filter deck assembly **20** (detailed in **FIG. 2**). A trunnion **16** extends from each end **7, 9** of the drum **12** and rotatably mounts the drum **12** to adjacent bearing and pedestal assemblies **18**. One of the trunnions **16a** is hollow and connects to a drop leg (not

depicted). During operation, the drop leg pulls air through the drum **12** and thereby draws filtrate **11** (see also **FIG. 2**) through the rotary drum filter **10** under vacuum. A number of filtrate conduits **22** disposed between the hollow trunnion **16a** and the filtrate chambers **24** (see also **FIG. 2**) allow filtrate **11** to fluidly communicate with the drop leg.

[0045] A screen **8**, typically a wire mesh (typically known as a “face wire”), cloth, synthetic textile, or plastic screen encircles the drum **12**. In operation, the vat is filled with a slurry. In **FIG. 1**, the drum **12** rotates in rotational direction **R**, which in this example, is counter-clockwise. As divisions of the drum **12** rotate through the vat, the pressure differential (*i.e.* the vacuum pressure) facilitates the accumulation of residue **6** on the screen **8**. As the drum division continues to rotate above the slurry level, filtrate **11** percolates through the filter deck assembly **20** and eventually flows through the filtrate conduits **22** into the drop leg. As the drum **12** continues to rotate, the residue **6** begins to dry and a doctor blade, belt, roller, or other device eventually scrapes the residue **6** from the screen **8** before that section of the screen **8** rotates back under the slurry to repeat the process.

[0046] When the rotary drum filter **10** is a vacuum washer used in the pulp and paper industry, the slurry is typically a mixture of pulp and water called a “pulp stock.” The residue **6** on the screen are typically known as a “pulp mat.” In mineral processing, the rotary drum filter **10** may be known as a thickener. The residue **6** is typically cakes of mineral sediment. For example, lime mud filters are typically used to recover lime from spent pulp and paper liquors. In a lime mud filter, the filtrate **11** typically comprises water and the residue **6** comprises lime mud.

[0047] **FIG. 2** is a detailed view of a portion of a filter deck assembly **20** of **FIG. 1**. The screen **8** rests atop an array of filter plates **4**. The filter plates **4** are typically corrugated filter plates **4a** having a plurality of ridges **3** and channels **5**. Corrugated filter plates **4a** are generally preferred because the corrugations increase the surface area available for holding excess filtrate **11** and thereby permit the rotary drum filter **10** to rotate at higher speeds than would typically be achievable in an identical rotary drum filter **10** having a comparatively flat filter plate (*i.e.* a filter plate that curves slightly to match the arc of the drum **12**, but that is otherwise flat). Furthermore, the corrugations easily expand and contract slightly to accommodate thermal expansion. Each filter plate **4** has a width **W** and a length **L**. The filter plate **4** has areas defining multiple drainage slots **17** disposed throughout the filter plate **4**. When the filter plate **4** is a corrugated filter plate

4a, the multiple drainage slots **17** are typically disposed in the channels **5**. The drainage slots **17** may be louvered to collect pools of filtrate **11** on the downturn.

[0048] The filter plate **4** spans one or more grid supports **30**. Adjacent grid supports **30** and the filter plate **4** define one or more filtrate chambers **24**. In operation, filtrate **11** flows through the screen **8** and through the drainage slots **17** on the upturn and part of the downturn. The filtrate **11** then flows through the filtrate chambers **24** before flowing further to the filtrate conduits **22** (**FIG. 1**) and drop leg.

[0049] The filter plate **4** further comprises a leading end **32** and a trailing end **34**. The leading end **32** is the end that first exits the slurry when the particular section of the filter plate **4** is moving upward toward the apex of rotation and the leading end **32** is likewise the first end to fall back under the level of the slurry when the section of the filter plate **4** is moving downward toward the nadir of rotation. Similarly, the trailing end **34** is distally disposed from the leading end **32**. The trailing end **34** is the second end to exit the slurry when the filter plate **4** is moving toward the apex of rotation. It will be understood that if an operator reverses the direction of rotation, the “leading ends” and the “trailing ends” designations will likewise reverse.

[0050] The respective ends **32**, **34** of the filter plates **4** engage a hat-shaped mounting clip **25** mounted on a grid support **30**. In the past, installers and servicers have welded or otherwise rigidly affixed at least one end **32** or **34** of the filter plate **4** to a mounting clip **25** to prevent filtrate **11** from leaking around leading end **32** and back out of the filter plate **4** when the filter plate **4** is on the downturn. The “top hat” mounting clips **25** also have a cap strip **27** welded or otherwise rigidly affixed to each mounting clip **25**. In practice, installers and servicers spot weld or T.I.G. weld these cap strips **27** to the mounting clips **25**. The recess **23** (*i.e.* the generally C-shaped feature) created by the body of the mounting clip **25**, a mounting clip shelf (see **371**, **373** (**FIG. 3B**), and the cap strip **27**, also secures the ends **32**, **34** of the filter plates **4** to the drum **12**. By welding the ends **32**, **34** to the mounting clip **25**, installers and operators sought to further prevent filtrate **11** from leaking around leading end **32** and back out of the filter plate **4** when the filter plate **4** is on the downturn and to ensure that the filter plate **4** was secured to the drum **12**. Preventing the filtrate from flowing back out of the filter plate **4** permitted operators to operate the rotary drum filter **10** at higher rotational velocities and thereby increase the separation rate and the residue yield over time.

[0051] Furthermore, processes that expose the welds to electronegative ions can also weaken the welds over time. For example, in bleach plants, the chlorine in bleach will attack the protective oxide layer on the stainless steel, and then attack the stainless steel itself. Because substantially all structural components of the cylindrical drum **12** are manufactured from stainless steel, all the steel in the drum **12** will be attacked. Unlike rust, chloride-induced corrosion is not bulk corrosion, that is, once the chlorine wears through the protective oxide layer, the chlorine will concentrate in that area and continue to corrode the exposed steel. The induced stresses from welding, combined with built-in mechanical stresses from manufacturing, operation (*e.g.* cyclical loading and unloading of residue, uneven load distribution of the residue, and cyclical pressurization and depressurization of the filter plates), and thermal cycling, make welds in particular a weakened initiation point for the corrosion. Once the corrosion starts, the reactive chloride ions tend to concentrate in these areas, thereby accelerating further corrosion. As a result, these welds create a greater potential for loose cap strips **27** and filter plates **4**, torn or otherwise damaged screens **8**, and doctor blades, rollers, belts, or other extracting apparatuses damaged from encountering the loose cap strips **27**.

[0052] In practice, Applicant has discovered that the rigidly affixed cap strips **27** create ongoing maintenance problems. The rigidly affixed cap strip **27** prevent a servicer from easily accessing and removing or replacing the filter plate **4**. Additionally, if the cap strips **27** have been welded to the mounting clips **25**, the environment within the rotary drum filter **10** can lead to weld fatigue and corrosion. In extreme cases, broken welds create loose cap strips **27** and filter plates **4**, which can damage the doctor blades, rollers, belts, or other devices configured to remove the residue **6** from the screen **8**. The loose cap strips **27** or filter plates **4** can likewise tear or otherwise damage the screen **8**. This permits filtrate **11** to flow both between drum divisions and back out of filter plate **4** and screen **8**, thereby reducing the overall efficiency of the system.

[0053] Rotary drum filters **10** typically operate as a closed system that is part of a much larger production operation. Tracing a yield or quality reduction to loose cap strips **27**, filter plates **4**, or damaged residue extraction devices is often time intensive, is not always readily apparent given the complexities and variables of the overall production process, and is often based upon measurements taken downstream of the rotary drum filter **10**. As such, even when measurements are taken, the data is typically desynchronized from current conditions inside the rotary drum filter

10. As such, realization of any further degradation is likewise delayed. Furthermore, even if operators do suspect minor problems with the rotary drum filter 10, operators concerned with production yields are often reluctant to interrupt the process, or divert the flow a slurry to another rotary drum filter 10 and reduce overall production capacity, to deactivate the problem rotary drum filter 10 to investigate. As such, minor initial problems with welds tend to progress to large problems with loose cap strips 27, loose filter plates 4, torn screens 8, and damaged residue extraction devices before the entire system is stopped for annual or biannual maintenance. By this time, the more damaged rotary drum filter 10 can take longer to repair, thus extending overall plant shutdowns and overall reductions in aggregate product yields.

[0054] To address these problems, Applicant presents several exemplary embodiments, combinations of which are all considered to be within the scope of in this disclosure. **FIG. 3A** depicts bottom-up view of an exemplary removable filter plate assembly 301 for a rotary drum filter 10 (**FIG. 1**) comprising: a filter plate 304 having a leading end 332 distally disposed from a trailing end 334, and an axial bisection line **BL** extending through the filter plate 304. The removable filter plate assembly 301 further comprises multiple drainage slots 317 disposed along the width **W** and length **L** of the filter plate 304. An engagement assembly 350 is affixed to the filter plate 304. In the depicted embodiment, the engagement assembly 350 is affixed to the bottom of the filter plate 304. The engagement assembly 350 comprises: an engager 352, and an engager holder 354 supporting the engager 352. The engager 352 is configured to extend in a lateral direction **LD** (**FIG. 3B**) toward the leading end 332 (see the engagement assemblies 350 disposed closer to the leading end 332 than the bisection line **BL**) or the trailing end 334 (see the engagement assemblies 350 disposed closer to the trailing end 334 than the bisection line **BL**) of the filter plate 304. In this manner, an extended engager 352z (**FIG. 3B**) defines a closed position **CP** (**FIG. 3B**). The engager 352 is further configured to retract in the lateral direction **LD** toward the axial bisection line **BL**. The retracted engager 352y defines an open position **OP** (**FIG. 3C**). **FIG. 3A** further depicts the respective ends 332, 334 resting atop respective shelves 371, 373 (**FIG. 3B**) of distally disposed mounting clips 325. A first mounting clip 325a is adjacently disposed to the leading end 332 of the filter plate 304. A second mounting clip 325b is adjacently disposed to the trailing end 334 of the filter plate 304. In this depiction, the engagement end 359 of the engager 352 is retracted and in the open position **OP**.

[0055] It will be understood that an exemplary engager **352** configured to move in a lateral direction **LD** may also be configured to move in an axial direction, radial direction, rotational direction, or a combination thereof.

[0056] As shown in **FIGS. 3A—3C**, the engager **352** extends under an adjacent mounting clip **325a** or **325b** to secure the removable filter plate assembly **301** to the drum **12** (**FIG. 1**). In the exemplary embodiment, the engagement assemblies **350** near the trailing end **334** have an engager **352** that has an engagement end **359** disposed entirely under the mounting clip **325** in the closed position **CP**. Likewise, the engagement assemblies **350** near the leading end **332** have an engager **352** that has an engagement end **359a** disposed entirely under the mounting clip **325a** in the closed position **CP**. In this manner, the exemplary removable filter plate assembly **301** can be fixedly engaged to the respective adjacent mounting clips **325a**, **325b** without the use of a cap strip **27**. As such, the exemplary removable filter plate assembly **301** can be affixed to respective adjacent mounting clips **325a**, **325b** without the need for welding either the leading end **332** or the trailing end **334** of the filter plate **304** to a cap strip **27**, thereby reducing the overall number of welds in the rotary drum filter **10**. It is contemplated that the overall reduction in the number of welds affixing the exemplary removable filter plate assembly **301** to the rotary drum filter **10** reduces the problems associated with weld fatigue. It is further contemplated that the overall reduction in the number of welds permitted by the exemplary removable filter plate assembly **301** can also facilitate faster removable and replacement of worn removable filter plate assemblies **301**, thereby contributing to an overall reduction in operational downtime during maintenance periods. It is additionally contemplated that the increased rate at which worn removable filter plate assemblies **301** can be removed and replaced may persuade operators to deactivate damaged rotary drum filters **10** more frequently in exchange for reduced downtime, faster return to optimum rotary drum filter production, and possible increased aggregate product yield attributable to more rotary drum filters **10** operating at peak production efficiency for longer periods of time than was previously possible.

[0057] As better seen in **FIGs. 3B** and **3C**, the exemplary filter plate assemblies **301** described herein may further comprise a plug seal **357** disposed at the leading end **322** of the filter plate **304**. The plug seal **357** prevents filtrate **11** from flowing around the leading end **322** of the filter plate

304 when the filter plate **304** rotates downwardly toward the nadir. An L-shaped seal retainer **363** may be disposed between the plug seal **357** and the adjacent mounting clip **325** to secure the seal.

[0058] In the depicted embodiment, each mounting clip **325** has as first shelf **371** that is disposed slightly lower than the adjacent second shelf **373** on the same mounting clip **325**. The lower first shelf **371** accommodates the seal **357** and the L-shaped seal retainer **363** that are disposed at the leading end **332** of the filter deck **304**. To accommodate the lower first shelf **371**, the engagement assembly **350** disposed closer to the leading end **322** has a notch **358** (**FIG. 3C**) in the engagement end **359a**. The notch **358** allows an upper portion of the engager **352** to rest against a side of the adjacent mounting clip **325** (*i.e.* the side of the lower first shelf **371**) and any L-shaped seal retainer **363**. The lower end of the notched engagement end **359a** is disposed under the adjacent mounting clip **325** in the closed position **CP1**. In this manner, the engagement assembly **350** disposed closer to the leading end **332** (compared to an engagement assembly **350** disposed closer to the trailing end **334**) secures the leading end **332** of the filter plate **304** to the mounting clip **325** while further securing the L-shaped seal retainer **363** between the first shelf **371** of the mounting clip **325** and the leading end **332**. The plug seal **357** occupies a space between the L-shaped seal retainer **363** and the leading end **332**. As the leading end **332** rotates downwardly, the mass of the filter plate **304** exerts a force on the plug seal **357** to press the plug seal **357** against the L-shaped seal retainer **363** to thereby prevent filtrate **11** from flowing around the leading end **332** of the filter plate **304** and back out into the vat.

[0059] Engagement assemblies **350** in accordance with this disclosure allow installers and servicers to use a removable filter plate assembly **301** with existing mounting clips **325**. Furthermore, when the respective engagers **352** are in the closed and/or locked positions, the removable filter plate assembly **301** is securely engaged to the existing mounting clips **325** without the need for welds. The only welds that might exist in the system depicted in **FIGS. 3A-3C** are welds that would secure the mounting clips **325** to the grid supports **30** (**FIG. 2**). However, such existing mounting clips **325** no longer require a cap strip **27** (**FIG. 2**) to secure the filter plate **304**. As a result, this disclosure allows installers and servicers to drop in replacement filter plate assemblies **301** without being hindered by the overlain cap strips **27**. As a result, it is contemplated that embodiments in accordance with this disclosure may reduce equipment downtime and production loss. Furthermore, by removing the cap strips **27**, and by providing an engagement

assembly **350** as described herein, it is contemplated that the exemplary embodiments described herein can minimize the welds in the overall drum surface and thereby significantly reduce the probability of partial system failure due to inconsistent weld work. Furthermore, if an owner elects to replace the mounting clips **325**, the reduction in the overall number of welds facilitates faster replacement of these mounting clips **325** over what was previously possible.

[0060] An installer may practice a method for installing a replaceable filter plate assembly **301** comprising: ensuring that the engagers **352** are in an open position **OP**, lowering the replaceable filter plate assembly **301** along a radius of the drum **12**, extending a first engager **352** disposed proximate to the leading end **332** toward the leading end **332** to define a first extended engager **352z1** in a first closed position **CP1**, extending a second engager **352** disposed proximate the trailing end **334** toward the trailing end **334** to define a second extended engager **352z2** in a second closed position **CP2**, and locking the first and second extended engagers **352z1**, **352z2**.

[0061] In other exemplary embodiments, the engager **352** may extend through the mounting clip **325**. Although in such embodiments, a servicer would likely cut holes in the existing mounting clips **325** to accommodate the extended engager **352z**. In still other exemplary embodiments, the mounting clips **325** are omitted and the engager **352** extends through the grid support **730** (**FIG. 7A** and **7B**).

[0062] In still other exemplary embodiments the engager **352** extends from the mounting clip **325** or the grid support (**730**, see **FIG. 7**) to engage the filter plate **304**. In certain exemplary embodiments, the engager **352** extending from the mounting clip **325** or grid support **730** can engage a keyed out recess in the filter plate **304** configured to receive the engager **352**. In other exemplary embodiments, the filter plate **304** can have areas defining a hole, wherein the hole is configured to receive the engagement end **359** of the engager **352** extending from the mounting clip **325** or grid support **730** toward the leading end **332** or trailing end **334** of the filter plate **304**. In other exemplary embodiments, the engager extending from the mounting clip **325** or grid support **730** can be disposed on top of the filter plate **304** to thereby secure the filter plate **304** in place. Any engagement arrangement in which the engager **352** prevents the filter plate **304** from falling off of a mounting clip **325** or grid support **730** while the filter plate **304** rotates with the drum **12** during operation is considered to be within the scope of this disclosure. Any embodiment that is configured to allow filter plates **304** to be affixed to the adjacent mounting clips **325a**, **325b**

by an engager that has a component of movement in the lateral direction and without welding the filter plate **304** to the mounting clips **325a**, **325b** is considered to be within the scope of this disclosure.

[0063] The engager **352** may be a latch (see **FIGS. 4-6**), a clamp, lever, bolt, wedge, clip, clasp, screw, and/or an insert, or a combination thereof. Any engager **352** configured to secure an end **332**, **334** of the filter plate **304** to an adjacent mounting clip **325a**, **325b** or grid support **730** is considered to be within the scope of this disclosure. If the engager **352** is a latch, a wedge, or an insert, the engager **352** can slide laterally in the engager holder **354** to move toward and away from the axial bisection line **BL** in a lateral direction **LD**. In other exemplary embodiments, the engager **352** can pivot in the engager holder **354** (**FIGS. 5A-5B** and **6A-6C**). A pivoting engager **352** will have rotational movement and is considered to be within the scope of this disclosure. It will be understood that rotational movement comprises components of lateral movement and components of axial movement (*i.e.* having a force vector parallel to the rotational axis **A**), and/or components of radial movement **RD** (**FIG. 5A**) (*i.e.* having a force vector extending radially outward from the rotational axis **A** toward the circumference **C** of the cylindrical drum **12**). Likewise, exemplary engagers **352** may have a component of radial movement or axial movement relative to the lateral direction **LD** that is not rotational movement. As such, an engager configured to extend or retract in an axial direction, a radial direction, a lateral direction, a combination of an axial direction and a radial direction, a combination of an axial direction and a lateral direction, a combination of a radial direction and a lateral direction, or a combination thereof are considered to be within the scope of this disclosure.

[0064] The engagement assembly **350** fixedly engages the filter plate **304**. In exemplary embodiments, the engagement assembly **350** may be riveted, bolted, fused, glued, clamped, or otherwise affixed to the filter plate **304**. In still other exemplary embodiments, the engagement assembly **350** may be an integral part of the filter plate **304**. As depicted, the filter plate **304** may be a corrugated filter plate **404a** (**FIG. 4A-4C**).

[0065] **FIG. 4A** is a detailed perspective view of the exemplary assembly shown in **FIGS. 3A-3C**. As **FIG. 4A** more clearly depicts, this exemplary embodiment of a replaceable filter plate assembly **401** for a rotary drum filter **10** comprises: a corrugated filter plate **404a** having alternating ridges **403** and channels **405** disposed along the length **L** (**FIG. 3A**) of the corrugated

filter plate **404a**. The corrugated filter plate **404a** has a leading end (see **332**) distally disposed from a trailing end **434** and multiple drainage slots **417** defined by areas of the corrugated filter plate **404a** and disposed along a width **W** and length **L** (see **FIG. 3A**) of the corrugated filter plate **404a**. The multiple drainage slots **417** are preferably each disposed in the channels **405** of the corrugated filter plate **404a** to drain filtrate **11** (**FIG. 2**) that accumulates in the channels **405**. The corrugated filter plate **404a** further comprises an engager slot **455** defined by areas of the corrugated filter plate **405**. Areas of a ridge **403** preferably define the engager slot **455**. An engager slot **455** in the ridge **403** minimizes the interactions of filtrate **11** (**FIG. 2**) with the engagement assembly **450** (**FIG. 4B**) and the engager **452**.

[0066] **FIG. 4B** has a portion of the corrugated filter plate **404a** cut away to depict the engagement assembly **450** more clearly. In the depicted embodiment, the engagement assembly **450** is a latch assembly **450a** comprising: a latch **452a**. The latch **452a** in turn comprises an elongate leg **451** and a handle **453**. The handle **453** extends through the engager slot **455** (**FIG. 4A**). The latch assembly **450a** further comprises a latch guide **454a**, a type of engager holder **454**. The latch **452a** is disposed in the latch guide **454a** and is configured to slide laterally along the latch guide **454a** (*i.e.* in a lateral direction **LD**). The latch guide **454a** engages the corrugated filter plate **404a**. When installed, a first mounting clip **325a** sits adjacently to the first end (see **332**) of the corrugated filter plate **404a**. A second mounting clip **425b** sits adjacently to the second end **434** in the installed position.

[0067] The handle **453** desirably has a handle profile that conforms to the profile of the ridge **403** in which the handle **453** sits. When closed (**FIG. 4C, 4D**), the matching profiles allow filtrate **11** to flow unhindered into the adjacent channels **405**, thereby minimizing the disruption to filtrate flow through the corrugated filter plate **404a**. The handle **453** may have ears **461** protruding from the handle **453**. In practice, a servicer may use a hammer or other blunt instrument to slide a latch in a closed position **CP** (**FIG. 4C, 4D**) back into the open position **OP**. In other exemplary embodiments, the ears **461** may be omitted.

[0068] **FIG. 4C** depicts the exemplary latch assembly **450a** in the closed position **CP** and the locked position **LP**. In the depicted embodiment, the elongate latch leg **451** has been extended toward the trailing end **434** of the corrugated filter plate **404a** and rests under the second shelf **473** of the adjacent top hat mounting clip **425**. To lock the extended latch **452az** in the closed position

CP to define a locked position **LP**, a plug **466** is provided. The plug **466** is inserted into the engager slot **455** (**FIG. 4D**) to block the engager slot **455**. As such, the plug **466** preferably has the same profile as the adjacent ridge **403** and the same dimensions as the engager slot **455** minus the width of the handle **453**. The plug **466** is preferably made of heat-treated rubber, plastics, or other material configured to endure the operating environment of the particular process the for which the rotary drum filter **10** is configured. The plug **446** may further comprise a key slot **476**. The key slot **476** leads to a locking mechanism configured to lock the plug **466** into place. A servicer may unlock the plug **466** by inserting the proper key (not depicted) into the key slot **476**. In other exemplary embodiments, the key slot and locking mechanism may be in the handle **453**.

[0069] **FIG. 5A** shows a side view of another exemplary embodiment, wherein the engager **552** is a lever engager **552b** in the open position **OP**. Likewise, the engagement assembly **550** is a lever engagement assembly **550b**. The lever engager **552b** comprises a cam **579** and a flat section **577**. As an installer pushes the handle **553** toward the filter plate **504**, the lever engager **552b** rotates around the pivot **567** and the cam **579** moves against the engager retainer **554**. In this manner, the force needed to push the handle **553** increases until the cam **579** rotates to the flat section **577**. At this point, the force drops off and the flat section **577** sits flush against the bottom of the engager retainer **554** and the elongate leg **551** of the lever engager **552b** presses under the second shelf **573** of the mounting clip **525** (**FIG. 5B**). The handle **553** likewise preferably sits flush in a ridge **503** of a corrugated filter plate **504a**. In this manner, the lever engager **552b** fixedly engages the exemplary filter plate assembly **501** to the drum **512**.

[0070] To open the cam lever engager **552b** again, an installer or servicer would overcome the maximum resting force of the closed lever engager **552b**. In this manner, the cam **579** would rotate off the flat section **577** onto the rounded portion (*i.e.* the portion that contacts the bottom of the engager retainer **544**). As such, unlike the embodiments depicted in **FIGS. 4A – 4D** and **6A – 6D**, the closed position **CP** of the depicted cam lever engager **552b** is also the locked position **LP**.

[0071] **FIG. 6A** is a perspective view of the trailing end **634** of an exemplary filter plate assembly **601**, wherein the engager **652** is a knob latch **652c**. In **FIG. 6A**, the knob latch **652c** is in the open position **OP**. The handle **653** preferably has the same profile as a corrugation of the corrugated filter plate **604a** to minimize obstructions to the filtrate flow. An installer or servicer

may access the handle **653** through the knob slot **655** in the corrugated filter plate **604a**. **FIG. 6A** also better illustrates the slots **617** in the channels **605** of the corrugated filter plate **604a**.

[0072] In **FIG. 6B**, a portion of the corrugated filter plate **604a** has been removed to better illustrate the engagement assembly **650**. In the depicted embodiment, the engagement assembly **650** is a knob latch engagement assembly **650c**. Similar to the embodiment depicted in **FIGS 4A – 4D**, the knob latch engagement assembly **650c** comprises a knob latch holder **654c** that fixedly engages the bottom of the corrugated filter plate **604a**. The knob latch **652c** pivots in the knob latch holder **654c**. The rotational movement **RM** of the knob latch **652c** comprises vectors in a lateral direction **LD** and vectors in an axial direction **AD**.

[0073] In **FIG. 6C**, an installer or servicer has turned the knob latch **652c** a quarter turn to place the knob latch **652c** under the adjacent mounting clip **625** to thereby engage the exemplary removable filter plate assembly **601** to the drum (see **512**). A plug **666** has been placed over the handle **653** to lock the handle **653** and by extension, the knob latch **652c**. By securing an end of the elongate leg **651** of the knob latch **652c** under the mounting clip **625**, the knob latch **652c** prevents the filter plate assembly **601** from falling into the vat when the filter plate assembly **601** is below the horizontal plane that bisects the drum (see **FIG. 1, 12**). It will be appreciated that in other exemplary embodiments, the knob latch **652c** may turn more than a quarter turn or less than a quarter turn. **FIG. 6D** shows the plug **666** securing the knob latch **652c** in the locked position **LP**. The plug **666** has the same profile as the corrugation in which the plug **666** sits.

[0074] Although **FIGS. 4 – 6** depict the engagement assembly **450, 550, and 650** disposed near the trailing end **434, 534, 634** of their respective filter plates **404, 504, 604**, it will be appreciated that engagement assemblies **450, 550, and 650** disposed near the leading end **432, 532, 632** function in substantially the same way as the engagement assemblies detailed in the descriptions of **FIGS. 4 – 6**.

[0075] **FIGS. 7A – 7B** are side views of another exemplary embodiment that obviates the need for top hat mounting clips (see **625**) and cap strips (see **27, FIG. 2**). As such, no welds are needed to engage any portion of the exemplary removable weld-less filter deck assembly **701** to the drum **712**. In embodiments where mounting clips **625** are present, the mounting clips **625** are typically welded to the tops of grid supports **730**. Like spot welds or T.I.G. welds of the cap strip **27**, the mounting clip welds corrode over time and create maintenance and accessibility problems for

servicers. By making a hole in the adjacent grid supports **730** to receive the engager **752**, exemplary removable weld-less filter plate assemblies **701** in accordance with this and related embodiments may bypass the need for welds altogether to secure the drop in removable filter plate assembly **701** to the drum **712** via the grid supports **730**.

[0076] Instead of a mounting clip **625**, operators may use a mounting support **739**. Unlike a mounting clip **625**, a mounting support **739** does not have an overhang that prevents the extended latch **752z** from sliding out of position. Furthermore, the mounting support **739** need not necessarily be welded to the grid support **730**; rather, the mounting support **739** may be clamped, glued with an adhesive, or otherwise affixed to the grip support **730** in a way that does not include welding. In certain exemplary applications, the mounting support **739** may be omitted.

[0077] In operation, the engager **752** extends through the hole in the grid support **730** to fixedly engage the exemplary filter deck assembly to the drum **712**. The engagement end **759** of each engager **752** is preferably a notched engagement end **759a**. The notched engagement ends **759a** prevent the leading and trailing ends **732**, **734** from sliding off the support grids **730**.

[0078] This weld-less removable filter deck assembly **701** preferably has engagers **752** that engage grid supports **730** that are laterally inward of the leading end **732** and the trailing end **734** of the filter plate **704**. This permits mounting supports **793** to replace top hap mounting clips (see **625**) at the grid supports adjacent to the leading end **732** and the trailing end **734** without also fashioning a hole through the lower mounting support **792** to accommodate an extended engager **752z** in a closed or locked position.

[0079] An exemplary rotary drum filter removable weld-less filter plate assembly **701** comprises: a filter plate **704** having a leading end **732** distally disposed from a trailing end **734**, an engagement assembly **750** engaged to the filter plate **704**, the engagement assembly **750** comprising: an engager **752**, and an engager holder **754** supporting the engager **752**, wherein the engager **753** is configured to move in an axial direction (see **AD**, **FIG. 6A**), a radial direction (see **RD**, **FIG. 5A**), a lateral direction **LD**, a combination of an axial direction **AD** and a radial direction **RD**, a combination of an axial direction **AD** and a lateral direction **LD**, a combination of a radial direction **RD** and a lateral direction **LD**, or a combination thereof, wherein the engager **752** extended toward a grid support **730** disposed below the filter plate **704** defines a closed position **CP**, and wherein the engager **752** retracted from the grid support **730** below the filter plate **704**

defines an open position **OP**. In exemplary embodiments, the engager **752** extends into the grid support **730** disposed below the filter plate **704**. The grid support **730** desirably has areas defining a cut-out that is configured to receive the engagement end **759** of the extended engager **752z**. In other exemplary embodiments, the grid support **730** has areas defining a hole configured to receive the engagement end **759** of the extended engager **752z**. In such embodiments, the engager **752** is configured to extend through the grid support **730**. The engagement end **759** of each engager **752** can be a notched engagement end **759a**. In certain exemplary embodiments, the engager **752** is configured to have rotational movement (see **RM**, **FIG. 6B**).

[0080] Although **FIGS. 7A** and **7B** depict an engagement assembly **750**, wherein the engager **750** is a latch **752a**, it will be understood that other exemplary weld-less embodiments, may comprise a lever engager (see **552b**) that extends laterally into a hole in an adjacent grid support (see also **FIGS. 5A** and **5B**), a knob latch engager (see **652c**) that extends into a hole in an adjacent grid support (see also **FIGS. 6A – 6D**), clamp, bolt, wedge, clip, clasp, screw, an insert, or a mechanism combination thereof configured to extend in a lateral direction **LD** from the corrugated filter plate **704a** to an adjacent grid support **730** to fixedly engage the filter plate **704a** to the grid support **730**. In other exemplary embodiment, the engager may extend in an axial direction **AD** to fixedly engage the filter plate **704a** to the grid support **730**. In other exemplary embodiment, the engager may extend in a radial direction **RD** to fixedly engage the corrugated filter plate **704a** to the grid support **730**. Engagers **752** configured to move in combinations of these directions are considered to be within the scope of this disclosure.

[0081] **FIG. 8** is a cross-sectional view of an exemplary weld-less engagement assembly **850**, wherein the engagement assembly **850** is engaged to the bottom of a corrugated filter plate filter plate **804a** comprising a series of alternating channels **805** and ridges **803**. The engager (**752**, **FIG. 7A**) extends through the gap **893** defined by the sides of the engager holder **854**. The engagement assembly **850** may be riveted, bolted, fused, glued, or otherwise affixed to the corrugated filter plate **804a**. In still other exemplary embodiments, the engagement assembly **850** may be an integral part of the corrugated filter plate **804a**.

[0082] An exemplary rotary drum filter assembly comprises: a corrugated filter plate **704a**, **804a** comprising ridges **803** and channels **805**, the corrugated filter plate **704a**, **804a** having a leading end **732** distally disposed from a trailing end **734**, and multiple drainage slots **717** defined

by areas of the corrugated filter plate **704a**, **804a** and disposed along a width **W** of the corrugated filter plate **704a**, **804a**, an engagement assembly **750**, **850** comprising: an engager **752** and an engager holder **754**, **854**, wherein the engager **752** is disposed in the engager holder **754**, **854** and is configured to move in an axial direction (see **AD**, **FIG. 6A**), a radial direction (see **RD**, **FIG. 5A**), a lateral direction **LD**, a combination of an axial direction **AD** and a radial direction **RD**, a combination of an axial direction **AD** and a lateral direction **LD**, a combination of a radial direction **RD** and a lateral direction **LD**, or a combination thereof, wherein the engager holder **754**, **854** engages the corrugated filter plate **704a**, **804a**, wherein the engager **752** extended toward a grid support **730** disposed below the filter plate **704** defines a closed position **CP**, and wherein the engager **752** retracted from the grid support **730** below the filter plate **704** defines an open position **OP**.

[0083] An exemplary assembly for a rotary washer comprises: a filter plate having a leading end distally disposed from a trailing end, and an axial filter plate bisection line extending through the filter plate; and a latch assembly comprising: a latch, and a latch holder supporting the latch, wherein the latch is configured to extend in a lateral direction beyond the leading end or the trailing end of the filter plate, wherein an extended latch defines a closed position, and wherein the latch is configured to retract in the lateral direction toward the axial bisection line, and wherein a retracted latch defines an open position.

[0084] In further exemplary embodiments, the filter plate is a corrugated filter plate comprising ridges and channels, the corrugated filter plate having multiple drainage slots defined by areas of the corrugated filter plate and disposed along a width of the corrugated filter plate.

[0085] In still further exemplary embodiments, the removable filter plate assembly further comprises a engager slot defined by areas of a ridge in the corrugated filter plate, wherein the latch of the latch assembly further comprises an elongate leg and a handle, wherein the handle extends through the engager slot. In certain exemplary embodiments, the handle of the latch has a handle base profile, and wherein the handle base profile conforms to a ridge profile of the corrugated filter plate.

[0086] In still further exemplary embodiments, the handle of the latch further comprises ears extending from the handle base profile. In certain embodiments, the latch assembly further comprises a plug configured to be disposed in the engager slot to define a locked position. The

plug may further comprise a key assembly. The plug may have a plug base profile that matches a ridge profile of the corrugated filter plate.

[0087] In certain exemplary embodiments, the latch of the latch assembly engages a first top hat mounting clip adjacently disposed to the leading end in the closed position. In further embodiments, the latch of the latch assembly engages a second top hat adjacently disposed to the trailing edge in the closed position. In still further exemplary embodiments, the first top hat and the second top hat lack cap strips. Further embodiments may comprise an L seal at the leading end.

[0088] In yet a further exemplary embodiments, a removable filter plate for a rotary washer comprises: a filter plate having a leading end distally disposed from a trailing end, an engagement assembly engaged to the filter plate, the engagement assembly comprising: an engager, and an engager holder supporting the engager, wherein the engager is configured to move in an axial direction, wherein the engager disposed at a first axial location define a closed position, and wherein the engager disposed at a second axial location defines an open position.

[0089] An exemplary rotary drum filter removable filter plate assembly comprises: a filter plate having a leading end distally disposed from a trailing end, and an axial filter plate bisection line extending through the filter plate; an engagement assembly engaged to the filter plate, the engagement assembly comprising: an engager, and an engager holder supporting the engager, wherein the engager is configured to extend in a lateral direction toward the leading end or the trailing end of the filter plate, wherein an extended engager defines a closed position, wherein the engager is configured to retract in the lateral direction toward the axial filter plate bisection line, and wherein a retracted engager defines an open position.

[0090] In certain exemplary embodiments, the engager is selected from the group consisting of: a latch, a lever, a cam lever, a knob latch, a clamp, a bolt, a wedge, a clip, a clasp, a screw, and an insert, or a combination thereof.

[0091] In certain exemplary embodiments, the adjacent mounting clip engages a radially distal end of a grid support.

[0092] In certain exemplary embodiments, the extended engager in the closed position extends under a first shelf of a mounting clip adjacent to the leading end of the filter plate, and wherein a plug seal is disposed between the first shelf of the mounting clip and the filter plate.

[0093] An exemplary rotary drum filter removable filter plate assembly comprises: a filter plate having a leading end distally disposed from a trailing end; an engagement assembly engaged to the filter plate, the engagement assembly comprising: an engager, and an engager holder supporting the engager, wherein the engager is configured to move in an axial direction, a radial direction, a lateral direction, a combination of an axial direction and a radial direction, a combination of an axial direction and a lateral direction, a combination of a radial direction and a lateral direction, or a combination thereof, wherein the engager extended toward an adjacent end of the filter plate defines a closed position, and wherein the engager retracted from the adjacent end of the filter plate defines an open position.

[0094] Another exemplary rotary drum filter removable filter plate assembly comprises: a filter plate having a leading end distally disposed from a trailing end; and an engagement assembly engaged to the filter plate, the engagement assembly comprising: an engager, wherein the engager is configured to move in an axial direction, a radial direction, a lateral direction, a combination of an axial direction and a radial direction, a combination of an axial direction and a lateral direction, a combination of a radial direction and a lateral direction, or a combination thereof, wherein the engager extended toward an adjacent end of the filter plate defines a closed position, and wherein the engager retracted from the adjacent end of the filter plate defines an open position.

[0095] In certain exemplary embodiments, the assembly further comprises an engager holder supporting the engager.

[0096] In certain exemplary embodiments, an adjacent mounting clip engages a radially distal end of a grid support, and wherein the extended engager extends toward the adjacent mounting clip.

[0097] In certain exemplary embodiments, the extended engager in the closed position extends under a first shelf of a mounting clip adjacent to the leading end of the filter plate, and wherein a plug seal is disposed between the first shelf of the mounting clip and the filter plate.

[0098] In certain exemplary embodiments, the filter plate is a corrugated filter plate comprising ridges and channels, the corrugated filter plate having multiple drainage slots defined by areas of the corrugated filter plate and disposed along a width of the corrugated filter plate.

[0099] Certain exemplary embodiments further comprise an engager slot defined by areas of a ridge in the corrugated filter plate, wherein the engager of the engagement assembly further comprises an elongate leg and a handle, wherein the handle extends through the engager slot.

[00100] In certain exemplary embodiments, the handle of the engager has a handle base profile, and wherein the handle base profile conforms to a ridge profile of the corrugated filter plate.

[00101] In certain exemplary embodiments, the handle of the engager further comprises ears extending from the handle base profile.

[00102] In certain exemplary embodiments, the handle of the engager further comprises a key and lock mechanism.

[00103] In certain exemplary embodiments, the engagement assembly further comprises a plug configured to be disposed in the engager slot to define a locked position.

[00104] In certain exemplary embodiments, the plug further comprises a key assembly.

[00105] In certain exemplary embodiments, the plug has a plug base profile that matches a ridge profile of the corrugated filter plate.

[00106] In certain exemplary embodiments, the engager of the engagement assembly engages a mounting clip adjacently disposed to the leading end in the closed position.

[00107] In certain exemplary embodiments, the engager of the engagement assembly engages a second mounting clip adjacently disposed to the trailing edge in the closed position.

[00108] In certain exemplary embodiments, the first mounting clip and the second mounting clip lack cap strips.

[00109] In certain exemplary embodiments, the engager is selected from the group consisting of: a latch, a lever, a cam lever, a knob latch, a clamp, a bolt, a wedge, a clip, a clasp, a screw, and an insert, or a combination thereof.

[00110] An exemplary rotary drum filter assembly comprises: a corrugated filter plate comprising ridges and channels, the corrugated filter plate having a leading end distally disposed from a trailing end, and multiple drainage slots defined by areas of the corrugated filter plate and disposed along a width of the corrugated filter plate; an engager slot defined by areas of the corrugated filter plate; an engagement assembly comprising: an engager comprising an elongate leg and a handle, wherein the handle extends through the engager slot, and an engager holder, wherein the engager is disposed in the engager holder and is configured to move in an axial

direction, a radial direction, a lateral direction, a combination of an axial direction and a radial direction, a combination of an axial direction and a lateral direction, a combination of a radial direction and a lateral direction, or a combination thereof, wherein the engager holder engages the corrugated filter plate; a first mounting clip adjacently disposed to the leading end of the corrugated filter plate in an installed position; a second mounting clip adjacently disposed to the trailing end of the corrugated filter plate in the installed position, wherein the engager extended toward an adjacent end of the filter plate defines a closed position, and wherein the engager retracted from the adjacent end of the filter plate defines an open position.

[00111] In certain exemplary embodiments, the engager in the closed position extends under a first shelf of a mounting clip adjacent to the leading end of the filter plate, and wherein a plug seal is disposed between the first shelf of the mounting clip and the filter plate.

[00112] In certain exemplary embodiments, the engager is selected from the group consisting of: a latch, a lever, a cam lever, a knob latch, a clamp, a bolt, a wedge, a clip, a clasp, a screw, and an insert, or a combination thereof.

[00113] While this invention has been particularly shown and described with references to exemplary embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

What is claimed is:

1. A rotary drum filter removable filter plate assembly comprising:
 - a filter plate having a leading end distally disposed from a trailing end, wherein an axial filter plate bisection line is defined as a line extending through the filter plate between the leading end and the trailing end; and
 - an engagement assembly engaged to the filter plate, the engagement assembly comprising:
 - an engager, wherein the engager is configured to extend in a lateral direction toward the leading end or the trailing end of the filter plate and to retract in the lateral direction toward the axial filter plate bisection line, wherein in a closed position the engager is extended under a first shelf of a mounting clip and the filter plate is located above the first shelf of the mounting clip, wherein in an open position the engager is retracted toward the axial filter plate bisection line and away from the first shelf of the mounting clip, and wherein the mounting clip is adjacent to the leading end or the trailing end of the filter plate.
2. The assembly of claim 1, wherein the mounting clip engages a radially distal end of a grid support, and wherein an engagement end of the engager extends toward the mounting clip.
3. The assembly of claim 1 or claim 2, wherein a plug seal is disposed between the first shelf of the mounting clip and the filter plate.
4. The assembly of any one of claims 1 to 3, further comprising an engager holder supporting the engager.
5. A rotary drum filter removable filter plate assembly comprising:
 - a filter plate having a leading end distally disposed from a trailing end;
 - an engagement assembly engaged to the filter plate, the engagement assembly comprising:
 - an engager, and
 - an engager holder supporting the engager, wherein the engager is configured to move in an axial direction, a radial direction, a lateral direction, a combination of an axial direction and a radial direction, a combination of an axial

direction and a lateral direction, a combination of a radial direction and a lateral direction, or a combination thereof, wherein in a closed position the engager is extended under a first shelf of a mounting clip and the leading end or the trailing end of the filter plate overlies the first shelf of the mounting clip.

6. The assembly of claim 5, wherein a plug seal is disposed between the first shelf of the mounting clip and the filter plate.
7. The assembly of claim 5 or claim 6, wherein the filter plate is a corrugated filter plate comprising ridges and channels, the corrugated filter plate having multiple drainage slots defined by apertures in the corrugated filter plate and disposed along a width of the corrugated filter plate.
8. The assembly of claim 7, further comprising an engager slot defined by areas of a ridge in the corrugated filter plate, wherein the engager of the engagement assembly further comprises an elongate leg and a handle, wherein the handle extends through the engager slot.
9. The assembly of claim 8, wherein the handle of the engager has a handle base profile, and wherein the handle base profile conforms to a ridge profile of the corrugated filter plate.
10. The assembly of claim 8 or claim 9, wherein the handle of the engager further comprises ears extending from the handle base profile.
11. The assembly of any one of claims 8 to 10, wherein the handle of the engager further comprises a key and lock mechanism.
12. The assembly of any one of claims 8 to 11, wherein the engagement assembly further comprises a plug configured to be disposed in the engager slot to define a locked position.
13. The assembly of claim 12, wherein the plug further comprises a key assembly.
14. The assembly of claim 12 or claim 13, wherein the plug has a plug base profile that matches a ridge profile of the corrugated filter plate.

15. The assembly of any one of claims 1 to 14, wherein the engager of the engager assembly engages the mounting clip in the closed position.
16. The assembly of any one of claims 1 to 15, wherein the mounting clip lacks a cap strip.
17. The assembly of any one of claims 1 to 16, wherein the engager is selected from the group consisting of: a latch, a lever, a cam lever, a knob latch, a clamp, a bolt, a wedge, a clip, a clasp, a screw, and an insert, or a combination thereof.
18. A rotary drum filter assembly comprising:
 - a corrugated filter plate comprising ridges and channels, the corrugated filter plate having a leading end distally disposed from a trailing end, and multiple drainage slots defined by apertures in the corrugated filter plate and disposed along a width of the corrugated filter plate;
 - an engager slot defined by areas of the corrugated filter plate;
 - an engagement assembly comprising:
 - an engager comprising an elongate leg and a handle, wherein the handle extends through the engager slot, and
 - an engager holder, wherein the engager is disposed in the engager holder and is configured to move in an axial direction, a radial direction, a lateral direction, a combination of an axial direction and a radial direction, a combination of an axial direction and a lateral direction, a combination of a radial direction and a lateral direction, or a combination thereof, wherein the engager holder engages the corrugated filter plate;
 - a first mounting clip adjacently disposed to the leading end of the corrugated filter plate in an installed position; and
 - a second mounting clip adjacently disposed to the trailing end of the corrugated filter plate in the installed position,
 - wherein in a closed position the engager is extended under a first shelf of the first mounting clip and the leading end of the corrugated filter plate is located above the first shelf of the first mounting clip, and wherein in an open position the engager is retracted away from the first shelf of the first mounting clip.

19. The assembly of claim 18, wherein a plug seal is disposed between the first shelf of the first mounting clip and the corrugated filter plate.
20. The assembly of claim 18 or claim 19, wherein the engager is selected from the group consisting of: a latch, a lever, a cam lever, a knob latch, a clamp, a bolt, a wedge, a clip, a clasp, a screw, and an insert, or a combination thereof.
21. A rotary drum filter removable filter plate assembly comprising:
 - a filter plate having a leading end distally disposed from a trailing end, wherein an axial filter plate bisection line is defined as a line extending through the filter plate between the leading end and the trailing end; and
 - an engagement assembly engaged to a mounting clip or a grid support, the engagement assembly comprising:
 - an engager, wherein the engager is configured to extend in a lateral direction toward the leading end or the trailing end of the filter plate and to retract in the lateral direction away from the axial filter plate bisection line, wherein in a closed position the filter plate is located above a first shelf of the mounting clip and the engager is engaged with the filter plate, and wherein in an open position the engager is retracted toward the mounting clip or the grid support.
22. The assembly of claim 21, wherein the engager is selected from the group consisting of: a latch, a lever, a cam lever, a knob latch, a clamp, a bolt, a wedge, a clip, a clasp, a screw, and an insert, or a combination thereof.
23. The assembly of claim 21 or claim 22, wherein the filter plate has apertures defining at least one hole configured to receive an engagement end of the engager in the closed position.









FIG. 1
(Prior Art)


















8/16



Date Reçue/Date Received 2020-06-25





FIG. 6A






FIG. 7A




FIG. 7B




FIG. 8