




(86) Date de dépôt PCT/PCT Filing Date: 2005/11/01
(87) Date publication PCT/PCT Publication Date: 2006/05/18
(85) Entrée phase nationale/National Entry: 2007/04/30
(86) N° demande PCT/PCT Application No.: US 2005/039546
(87) N° publication PCT/PCT Publication No.: 2006/052563
(30) Priorité/Priority: 2004/11/05 (US60/625,611)

(51) Cl.Int./Int.Cl. *H04Q 7/00* (2006.01)
(71) Demandeur/Applicant:
INTERDIGITAL TECHNOLOGY CORPORATION, US
(72) Inventeurs/Inventors:
SHAHEEN, KAMEL M., US;
CARLTON, ALAN GERALD, US;
LU, GUANG, CA;
OLVERA-HERNANDEZ, ULISES, CA;
RUDOLF, MARIAN, CA;
ZAKI, MAGED, CA;
ZUNIGA, JUAN CARLOS, CA
(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : PROCEDE ET SYSTEME DE COMMUNICATION SANS FIL PERMETTANT LA MISE EN OEUVRE D'UN TRANSFERT INDEPENDANT DU SUPPORT ENTRE DES RESEAUX D'ACCES DE TECHNOLOGIES DIVERSES
(54) Title: WIRELESS COMMUNICATION METHOD AND SYSTEM FOR IMPLEMENTING MEDIA INDEPENDENT HANDOVER BETWEEN TECHNOLOGICALLY DIVERSIFIED ACCESS NETWORKS



(57) **Abrégé/Abstract:**

A wireless communication system including at least one IDDD 802 multi-stack wireless transmt/receive unit (WTRU) (110) and a plurality of technologically diversified access networks, such as IEEE 802.X networks and Third Generation Partnership Project (3GPP) networks, that are concurrently deployed. Both the multi-stack WTRU (110) and the technologically diversified networks include a media independent handover (MIH) function. The WTRU is configured to read MIH information transmitted from one of the IEEE 802.X networks, trigger 3GPP authentication and atuhorization procedures based on the MIH information, obtain a local Internet Protocol (IP) address, establish a tunnel to a packet data gateway (PDG) un a 3GPP core network, constructed a care of address (CoA) and register the CoA with a home agent (142) of the WTRU, whereby data destined for the WTRU (110) is routed via the home agent (142) through a new tunnel established between the home agent (142) and a foreign agent (136) based on the CoA. .

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
18 May 2006 (18.05.2006)

PCT

(10) International Publication Number
WO 2006/052563 A3

(51) International Patent Classification:

H04Q 7/00 (2006.01)

(21) International Application Number:

PCT/US2005/039546

(22) International Filing Date:

1 November 2005 (01.11.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/625,611 5 November 2004 (05.11.2004) US

(71) Applicant (for all designated States except US): **INTER-****DIGITAL TECHNOLOGY CORPORATION** [US/US];

300 Delaware Avenue, Suite 527, Wilmington, Delaware 19801 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OLIVERA-HER-****NANDEZ, Ulises** [MX/CA]; 2 Rolland Laniel, Kirkland,Québec H9J 4A5 (CA). **SHAHEEN, Kamel, M.** [US/US];

429 Ashton Drive, King Of Prussia, Pennsylvania 19406

(US). **CARLTON, Alan, Gerald** [GB/US]; 12 WisteriaAvenue, Mineola, New York 11501 (US). **RUDOLF,**

Marian [DE/CA]; 1958 Rue Workman, Montreal, Québec H3J 2P3 (CA). **LU, Guang** [CA/CA]; 2525 Cavendish Blvd., Apt. 934, Montreal, Québec H4B 2Y6 (CA). **ZUNIGA, Juan, Carlos** [MX/CA]; 955 Rue Gohier Ville St. Laurent, Montreal, Québec H4L 3J4 (CA). **ZAKI, Maged** [CA/CA]; 9260 Ceres, Apt. 202, Pierrefonds, Quebec H8Y 3N5 (CA).


(74) Agent: **BALLARINI, Robert, J.**; VOLPE AND KOENIG, P.C., United Plaza, Suite 1600, 30 S. 17th Street, Philadelphia, Pennsylvania 19103 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: WIRELESS COMMUNICATION METHOD AND SYSTEM FOR IMPLEMENTING MEDIA INDEPENDENT HANDOVER BETWEEN TECHNOLOGICALLY DIVERSIFIED ACCESS NETWORKS



(57) Abstract: A wireless communication system including at least one IDDD 802 multi-stack wireless transmt/receive unit (WTRU) (110) and a plurality of technologically diversified access networks, such as IEEE 802.X networks and Third Generation Partnership Project (3GPP) networks, that are concurrently deployed. Both the multi-stack WTRU (110) and the technologically diversified networks include a media independent handover (MIH) function. The WTRU is configured to read MIH information transmitted from one of the IEEE 802.X networks, trigger 3GPP authentication and atuhorization procedures based on the MIH information, obtain a local Internet Protocol (IP) address, establish a tunnel to a packet data gateway (PDG) un a 3GPP core network, constructed a care of address (CoA) and register the CoA with a home agent (142) of the WTRU, whereby data destined for the WTRU (110) is routed via the home agent (142) through a new tunnel established between the home agent (142) and a foreign agent (136) based on the CoA. .

WO 2006/052563 A3

WO 2006/052563 A3

GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

(88) Date of publication of the international search report:

26 April 2007

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

[0001] WIRELESS COMMUNICATION METHOD AND SYSTEM
 FOR IMPLEMENTING MEDIA INDEPENDENT
 HANDOVER BETWEEN TECHNOLOGICALLY
 DIVERSIFIED ACCESS NETWORKS

[0002] FIELD OF INVENTION

[0003] The present invention is related to wireless communication systems. More particularly, the present invention is related a method and system for implementing media independent handovers (MIHs) among technologically diversified access networks (ANs).

[0004] BACKGROUND

[0005] Different types of wireless communication systems have been developed to provide different types of services. Some examples of the wireless communication systems include wireless local area network (WLAN), wireless wide area network (WWAN) and cellular networks such as universal mobile telecommunication systems (UMTS). Each of these systems have been developed and tailored to provide specific applications.

[0006] With the pervasive adoption of wireless communication networks in enterprise, residential and public domains, continuous connectivity can be supported as the users of such networks move from one network to the other. With the emerging "always-on" life style, wireless transmit/receive units (WTRUs), (i.e., mobile stations (MS)), are required to support multiple heterogeneous networks. Thus, a seamless handover between these networks is desired.

[0007] SUMMARY

[008] The present invention is related to a wireless communication system including at least one IEEE 802 multi-stack WTRU and a plurality of technologically diversified access networks, such as IEEE 802.X networks and Third Generation Partnership Project (3GPP) networks, that are concurrently deployed. Both the multi-stack WTRU and the technologically diversified networks include a media independent handover (MIH) function. The WTRU is configured to read MIH information transmitted from one of the IEEE 802.X

networks, trigger 3GPP authentication and authorization procedures based on the MIH information, obtain a local Internet protocol (IP) address, establish a tunnel to a packet data gateway (PDG) in a 3GPP core network, construct a care of address (CoA) and register the CoA with a home agent of the WTRU, whereby data destined for the WTRU is routed via the home agent through a new tunnel established between the home agent and a foreign agent based on the CoA.

[009] BRIEF DESCRIPTION OF THE DRAWINGS

[0010] A more detailed understanding of the invention may be had from the following description, given by way of example and to be understood in conjunction with the accompanying drawings wherein:

[0011] Figure 1 is a block diagram of a wireless communication system configured in accordance with the present invention;

[0012] Figure 2 illustrates inter-AN and intra-AN handovers in accordance with the present invention;

[0013] Figure 3 shows a protocol stack configured in accordance with the present invention;

[0014] Figure 4 shows a media independent handover (MIH) management plane in accordance with the present invention;

[0015] Figures 5A and 5B show protocol stacks of a multi-stack WTRU and the media access in accordance with the present invention;

[0016] Figure 6 shows an MIH state machine in accordance with the present invention;

[0017] Figures 7A, 7B, 7C, 8A and 8B show external service access points (SAPs) in accordance with the present invention;

[0018] Figure 9 illustrates the use of three groups of exemplary triggers;

[0019] Figures 10A and 10B, taken together, show a process for system access, IEEE 802.X and WLAN/3GPP inter-working in accordance with the present invention;

[0020] Figures 11A - 11C, taken together, show a process for system access, an 802.X and 3GPP inter-working failure case in accordance with the present invention;

[0021] Figures 12A and 12B, taken together, show a process for a WTRU initiated and WTRU controlled handover from 802.X to 3GPP in accordance with the present invention;

[0022] Figure 13 shows establishment of a tunnel between a WTRU and a packet data gateway (PDG) in accordance with the present invention;

[0023] Figures 14A-14C, taken together, show a process for WTRU initiated handover from 3GPP to IEEE 802.11 in accordance with the present invention;

[0024] Figure 15 shows the establishment of GPRS tunneling protocol (GTP) tunnels in accordance with the present invention;

[0025] Figures 16A and 16B, taken together, show a process for WTRU initiated 802.X to 802.3 handover in accordance with the present invention;

[0026] Figures 17A and 17B, taken together, show a process for WTRU initiated 802.3 to 802.X handover in accordance with the present invention;

[0027] Figures 18A and 18B, taken together, show a process for initiated and WTRU controlled inter-802 handover in accordance with the present invention;

[0028] Figures 19A and 19B, taken together, show a process for WTRU initiated and WTRU controlled inter-802 handover failure case in accordance with the present invention;

[0029] Figures 20A and 20B, taken together, show a process for network initiated and network controlled inter-802 handover in accordance with the present invention;

[0030] Figure 21 shows a process for WTRU initiated inter-802 fast handover in accordance with the present invention; and

[0031] Figure 22 shows a process for implementing hierarchical MIPv6 (HMIPv6) using a WTRU initiated inter-802 fast handover message flow in accordance with the present invention.

[0032] DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0033] Hereafter, the terminology "wireless transmit/receive unit" (WTRU) includes but is not limited to, a mobile station (MS), a user equipment (UE), a fixed or mobile subscriber unit, a pager, or any other type of device capable of operating in a wired or wireless environment.

[0034] ACRONYMS AND DEFINITIONS

3G	Third Generation
3GPP	3G Partnership Project
AAA	Authentication, Authorization, and Accounting
AG	Access Gateway
AN	Access Network
AP	Access Point
AR	Access Router
BS	Base Station
BSC	Base Station Controller
BSSID	Basic Service Set Identifier
BTS	Base Transceiver Station
BU	Binding Update
ESS	Extended Service Set
CoA	Care of Address
CoN	Correspondent Node
CN	Core Network
CVSE	Critical Vendor/Organization Specific Extensions
ESSID	Extended Service Set ID
FA	Foreign Agent
FBU	Fast-Binding Update
F-HMIP	Fast Handover for Hierarchical Mobile IP
FMIP	Fast Handover Mobile IP
FNA	Fast Neighbor Advertisement
GGSN	Gateway GPRS Support Node
GPRS	General Packet Radio Service
GSM	Global System for Mobile Communication
GTP	GPRS Tunneling Protocol
HLCF	Higher Layer Convergence Function
HA	Home Agent
HAck	Handover Acknowledge

HI	Handover Initiate
HMIP	Hierarchical Mobile IP
HO	Handover
HOF	Handover Function
IEEE	Institute of Electrical and Electronics Engineers
IETF	Internet Engineering Task Force
ICMP	Internet Control Message Protocol
IP	Internet Protocol
ISP	Internet Service Provider
L1	Physical Layer (PHY)
L2	Medium Access Control (MAC) layer and Logical Link Control
(LLC)	
L3	Layer 3
L2TP	L2 Tunneling Protocol
L3SH	L3 Soft Handover
LAN	Local Area Network
LCoA	On-Link Care of Address
LLC	Logical Link Control
LLCF	Lower Layer Convergence Function
MA	Media Access
MAC	Medium Access Control
MAP	Mobility Anchor Point
MIH	Media Independent Handover
MIHO	Media Independent Handover
MIHS	Media Independent Handover Services
MIP	Mobile IP
MLME	MAC Layer Management Entity
MN	Mobile Node
MS	Mobile Station
MT	Mobile Terminal
NVSE	Normal Vendor/Organization Specific Extensions
PDG	Packet Data Gateway

PHY	Physical Layer
PLMN	Public Land Mobile Network
QoS	Quality of Service
RCoA	Regional Care of Address
RFC	Request for Comment
RNC	Radio Network Controller
SAP	Service Access Point
SGSN	Serving GPRS Support Node
SNR	Signal Noise Ratio
TCP	Transmission Control Protocol
UDP	User Datagram Protocol
UE	User Equipment
UMTS	Universal Mobile Telecommunications System
WAG	Wireless Access Gateway
WLAN	Wireless Local Area Network
WPAN	Wireless Personal Area Network
WMAN	Wireless Metropolitan Area Network
WTRU	Wireless Transmit/Receive Unit

[0035] Figure 1 is a block diagram of a wireless communication system 100 configured in accordance with the present invention. The wireless communication system 100 includes a plurality of ANs 102₁-102_x, 104₁-104_x deployed concurrently under different standards and a plurality of Third Generation Partnership Project (3GPP) core networks (CN) 106₁-106_x. An IEEE 802 multi-stack WTRU 110 may access any of the ANs 102₁-102_x, 104₁-104_x while performing handover between the ANs 102₁-102_x, 104₁-104_x. The ANs 102₁-102_x, 104₁-104_x include, but are not limited to, IEEE 802 ANs 102₁-102_x and 3GPP radio access networks (RANs) 104₁-104_x. The IEEE 802 ANs 102₁-102_x may operate under IEEE 802.3, IEEE 802.11, IEEE 802.15 and IEEE 802.16 standards. Hereinafter, the present invention will be explained with reference to IEEE 802 ANs and a 3GPP RAN, but the present invention is applicable to any other types or ANs.

[0036] Each of the 3GPP RANs 104₁-104_x includes a base transceiver station

(BTS)/Node-B 107 and a base station controller (BSC)/radio network controller (RNC) 108. The BSC/RNC 107 is connected to one of a plurality of 3GPP core networks (CN) 106₁-106_x. The IEEE 802 ANs 102₁-102_x comprise a multi-layer media interface unit 112 and an access gateway 114. The multi-layer media interface unit 112 performs physical layer functions and medium access control (MAC) layer functions. The access gateway 114 is a unified interface to external networks, such as the Internet 120 or the 3GPP CNs 106₁-106_x. The access gateway 114 includes an access router 116 for routing data packets to and from the external networks. Therefore, the IEEE 802 multi-stack WTRU 110 may communicate with a CoN 140 over the Internet 120. The IEEE 802 multi-stack WTRU 110 may also communicate with a home agent (HA) 142 and a home authentication, authorization and accounting (AAA) server 144 via a home network 146.

[0037] Each of the 3GPP CNs 106₁-106_x include an AAA server 132, a WLAN access gateway (WAG) 134, a PDG/gateway general packet radio service (GPRS) serving node (GGSN)/foreign agent (FA) 136 and a serving GPRS support node (SGSN) 138. The GGSN and PDG may function as FAs when IPV4 needs to be supported. The PDG may be implemented off an existing GGSN using a subset of a GGSN function and a tunnel termination point. The WAG 134 is a gateway via which the data to and from the access router 116 in the ANs 102₁-102_x is routed to provide the IEEE 802 multi-stack WTRU 110 with 3GPP services. The 3GPP AAA server 132 provides AAA services for the IEEE 802 multi-stack WTRU 110. The PDG 136 is a gateway for 3GPP packet switching (PS)-based services.

[0038] Figure 2 illustrates two different handover scenarios which are implemented in accordance with the present invention. In Figure 2, two different IEEE 802 ANs 202₁, 202₂ are deployed. In a first scenario, a mobile Internet protocol (MIP) handover is implemented between the IEEE 802 multi-stack WTRU 110 and two different ANs 202₁, 202₂. In a second scenario, a handover is implemented between the IEEE 802 multi-stack WTRU 110 and two different IEEE 802 media access (MA) entities 212₁, 212₂ within the same IEEE 802 AN 202₂. In the second case, since mobility can be handled below layer 3, MIP is not

required.

[0039] Figure 3 shows a protocol stack 300 configured in accordance with the present invention. The protocol stack includes a user plane 310 and a separate MIH management plane 320 for performing an MIH operation. The MIH management plane 320 is parallel to the user plane 310.

[0040] The MIH management plane 320 includes an MIH higher layer convergence function (HLCF) 322, a handover function (HOF) 324 and an MIH lower layer convergence function (LLCF) 326. The MIH HLCF 322 provides an interface between the MIH handover plane 320 and the mobility management entity in a particular technology. The HOF 324 collects handover events from the MIH LLCF 326 and determines whether a handover is required based on certain criteria, (e.g., link quality, service and subscription). The MIH LLCF 326 provides an event service that compiles physical layer (PHY) and MAC layer events specific to a particular technology. The event service can be configured in order to determine a set of MAC and PHY measurements that need to be collected. When certain events or a collection of them meet certain configured criteria, (e.g., a signal-to-noise ratio (SNR) threshold), an event indication is generated. The MIH HLCF 322 and the MIH LLCF 326 are implementation specific and it should be noted that any description of the MIH HLCF and the MIH LLCF in the present invention is provided as an example, not as a limitation, and any other variations are possible.

[0041] As illustrated in Figure 3, the MIH management plane 320 may co-exist with other technology-specific handover (HO) function 330, (e.g., IEEE 802.11r intra-ESS fast handover or IEEE 802.16 Netman mobility functions). When no other handover entity exists, handover triggers from PHY and MAC are sent to the MIH LLCF 326 directly. When the MIH handover plane 320 co-exists with the technology-specific HO management plane 330, a two-tier handover method is used, which is implementation specific. For example, one handover management entity may take control of the handover procedures or a combination of functions from both entities may be implemented.

[0042] Figure 4 shows a detailed MIH management plane 320 in accordance with the present invention. The MIH handover plane 320 interfaces with the

system at both higher and lower layers through convergence functions. These convergence functions are system-specific and multiple functions may be present in order to support all system-specific features.

[0043] Preferably, multiple MIH HLCFs 322 and MIH LLCFs 326 are provided. For example, an MIH cellular HLCF 322a for interfacing with a cellular system, an MIH mobile IP HLCF 322b for mobile IP interactions and an MIH intra-IP subnet HLCF 322c for handover within the same IP subnet for HLCF, and an MIH cellular LLCF 326a for a cellular system and an MIH 802.X LLCF 326b, 326c for IEEE 802 systems for LLCF.

[0044] Figures 5A and 5B show protocol stacks of the IEEE 802 multi-stack WTRU 110 and an IEEE 802 AN in accordance with the present invention. As stated above, an MIH management plane is provided in parallel to the user plane both in the IEEE 802 multi-stack WTRU 110 and the AN and the MIH LLCF interfaces to MAC and PHY layers and the MIH HLCF interfaces to higher layer applications.

[0045] Figure 6 shows an MIH state machine 600 in accordance with the present invention. The MIH state machine 600 is applicable to both a network and a WTRU and whether the handover is network initiated or WTRU initiated. Five states are defined as follows: an initialization state 602, a network discovery/update state 604, an MIH steady state 606, an MIH handover prepare state 608 and an MIH handover commit state 610.

[0046] In the initialization state 602, handover configuration parameters are initialized and then a transition is made to the network discovery/update state 604. In the network discovery/update state 604, the MIH management plane 320 gathers information about system conditions and network topology including neighbor lists from different technology. A transition to the MIH steady state 606 is made when an MIH steady state start condition is met (step 612) and a transition is made back to the network discovery/update 604 when an MIH steady state end condition is met (step 614). During operation, the MIH management plane 320 performs network updates to get the latest system conditions. The MIH steady state 606 represents the state when the link condition is good and there is no need to perform handover. However, network

discovery can be performed in background to get the latest neighbor list conditions.

[0047] Upon receiving an MIH handover request, if there is no intra-technology handover in progress, a transition to an MIH handover prepare state 608 is made to prepare a new link (step 616). Preferably, the new link is established without releasing the established link, (i.e., make before break). If the MIH handover setup is aborted (step 618), the MIH goes back to the MIH steady state 606. If MIH handover preparation is accomplished properly, the MIH makes a transition to an MIH handover commit state 610 as long as there is no intra-technology handover in progress (step 620). If the MIH handover is successfully performed (step 624), the MIH makes a transition back to the MIH steady state 606. However, if the MIH handover is aborted (step 622), the MIH makes a transition back to the MIH handover prepare state 608.

[0048] The information flow across the boundaries between the layers is described in terms of service access points (SAPs), which are defined by primitives that represent different items of information and cause actions to take place. Since there are several sublayers, SAPs are divided into those providing MIH handover services to the MIH HLCFs, the ones providing MIH handover services to the MIH LLCFs, and a set of services provided to the external layers, (non-IEEE standards layers), by each one of the specific convergence functions. Figures 7A-7C, 8A and 8B show external SAPs in accordance with the present invention.

[0049] Triggers are used to provide internal, external and peer communication. These triggers do not appear as such on the medium, (e.g., the access interface), but serve to define more clearly the relationships between the different layers and planes. Figure 9 illustrates the use of three groups of exemplary triggers. They are identified as A, B, and C. The number illustrates the sequence of the triggers within the same group.

[0050] Group A illustrates a peer-to-peer communication between a first peer 910 and a second peer 950. Both the first peer 910 and the second peer 950 comprise a MIH management plane 920, 970 and a user plane 930, 960, respectively. An initial request for service from an MIH handover function 924 to

an MIH LLCF 926 is provided by the “request” trigger (1A). This request is sent to the second peer MIH LLCF 976 as shown in a dotted line. The MIH LLCF 976 in the second peer generates an “indication” trigger (2A) to inform the MIH handover function 974 of the request. The MIH handover function 974 responds with a “response” trigger (3A) to the MIH LLCF 976. The response is sent across the link to the LLCF 926 on the first peer, and the LLCF 926 sends a “confirmation” trigger (4A) to the MIH handover function 924.

[0051] When the information is transported from the higher level entity to the lower level entity within the same management plane and within the same node, a pair of “request” and “confirmation” is used as shown by 1A and 4A.

[0052] Group B illustrates the scenario when the information is transported from the lower level entity to the higher level entity within the same management plane and within the same node. A pair of “indication” and “response” is used as shown by 1B and 2B.

[0053] Group C illustrates the scenario when the information is exchanged between the MIH HLCF 922, 972 and higher layer application, such as Mobile IP function 932, 962. A pair of “indication” and “response” is used as shown by 1C and 2C.

[0054] In accordance with the present invention, several remote transport options are supported. MIH may send generic messages that are passed as primitives to a MAC layer, so that dedicated management messages can be used to exchange the information and be delivered as SAP primitives at the other side MIH function. MIH may generate and exchange messages through MIP vendor-specific extensions. Ethernet type frames may be used, similar to 802.1X, to exchange information between management planes. A hybrid approach may be used, on which different convergence layers implement different transport mechanisms.

[0055] Internal triggers are those triggers within MIH functions. External triggers are those between an MIH management plane and a user plane. Tables 1 and 2 are summary of external triggers and internal triggers. The MIH_PHY.set, MIH_PHY.get and MIH_PHY.reset triggers correspond to an MIH_PHYCONFIG trigger. The MIH_MAC.set, MIH_MAC.get and

MIH_MAC.reset triggers correspond to an MIH_PHYCONFIG trigger. These triggers configure the information that should be broadcast over the air to aid the WTRU in the discovery and selection of a suitable network. Furthermore, these triggers set a threshold within both the PHY and MAC layers that are used to determine when an event should be triggered.

Triggers	Source	Destination	Local / Remote	Description
MIH_PHY.set (MIH_PHYCONFIG)	MIH	PHY	both	MIH configures PHY for information services
MIH_PHY.get (MIH_PHYCONFIG)	MIH	PHY	both	MIH enquires configuration info
MIH_PHY.reset (MIH_PHYCONFIG)	MIH	PHY	both	MIH resets PHY configuration
MIH_MAC.set (MIH_MACCONFIG)	MIH	MAC	both	MIH configures MAC for information services
MIH_MAC.get (MIH_MACCONFIG)	MIH	MAC	both	MIH enquires configuration info
MIH_MAC.reset (MIH_MACCONFIG)	MIH	MAC	both	MIH resets MAC configuration
MIH_MACINFO.indication	MAC	MIH	local	MAC sends system information
MIH_MACINFO.response	MIH	MAC	local	Response for the above indication.
MIH_INFO.indication	MIH MIH	L2, L3 handover	local	MIH entities indicate the existence of MIH functions
MIH_INFO.response	L2, L3 handover	MIH	local	Response for the above indication.
MIH_PHYEVENT.indication	PHY	MIH	both	PHY measurement reports
MIH_PHYEVENT.response	MIH	PHY	both	Response for the above indication.
MIH_MACEVENT.indication	MAC	MIH	both	MAC measurement reports
MIH_MACEVENT.response	MIH	MAC	both	Response for the above indication.

Triggers	Source	Destination	Local / Remote	Description
MIH_MACORDER.request	MIH	MAC	local	MIH request HO related MAC actions
MIH_MACORDER.confirmation	MAC	MIH	local	MAC informs MIH if the action is accomplished
MIH_HANDOVER_COMPLETE	MAC	MIH	local	MAC informs MIH that the data path is successfully switched over a new access link (e.g., radio connection).
MIH_HANDOVER_PREPARE.indication	MIH MIH	MIP MAC	local	MIH and inform external entities to prepare for handover
MIH_HANDOVER_PREPARE.response	MIP MAC	MIH MIH	local	Response for the above indication.
MIH_HANDOVER_COMMIT.indication	MIH MIH	MIP MAC	local	MIH informs external entities to execute for handover
MIH_HANDOVER_COMMIT.response	MIP MAC	MIH MIH	local	Response for the above indication.

Table 1

Triggers	Source	Destination	Local / Remote	Description
MIH_SYSINFO.indication	MIH LLCF	HOF	local	MIH LLCF informs HOF of any system information update
MIH_SYSINFO.response	HOF	MIH LLCF	local	Response for the above indication.
MIH_MOBILITY.request	HOF	MIH LLCF	both	HOF sends handover decision to MIH LLCF
MIH_MOBILITY.indication	HOF	MIH HLCF	both	HOF informs MIH HLCF and peer HOF of handover decision
MIH_MOBILITY.response	MIH HLCF	HOF	both	Response of the above indication
MIH_MOBILITY.confirmation	MIH LLCF	HOF	both	Confirmation of the HOF mobility request
MIH_REPORT.indication	MIH LLCF	HOF	local	MIH LLCF sends MIH triggers to HOF
MIH_REPORT.response	HOF	MIH LLCF	local	Response of the above indication
MIH_MACRELEA	HOF	MIH	local	When handover

Triggers	Source	Destination	Local / Remote	Description
SE.request		LLCF		procedures finished, HOF informs MIH LLCF
MIH_MACRELEA SE.confirmation	MIH LLCF	HOF	local	Confirmation of the above request

Table 2

[0056] Figures 10A and 10B, taken together, show a process 1000 for system access, IEEE 802.X and WLAN/3GPP inter-working in accordance with the present invention. The WTRU 110 is powered on and the HOF 324 is initialized. The WTRU 110 performs scanning (active or passive) to find a suitable WLAN/3GPP network (step 1002). The WLAN periodically transmits beacon frames for this purpose. The MIH function of the WLAN may order changes of the content of the beacon frame at any time (step 1004), which is passed by an MIH_MACCONFIG message (step 1006). This may happen either as a manual request from the management system or dynamically based on radio environment measurements or the like.

[0057] If a WLAN network is found, the WTRU 110 reads beacon information transmitted by the network (step 1008). Alternatively, the WTRU 110 may attempt to fetch system information either through probe request and probe response messages or by accessing a known data base within the candidate system at a later stage.

[0058] When the beacon frames are detected, the WTRU 110 first identifies whether MIH information is supported, (e.g., through a specific 802.21 flag broadcast on the beacon frame). If so, the WTRU 110 reads its content. Any MIH information found within a beacon frame, (e.g., system operator identity, PGSS (W-APN), neighboring maps and SMS, IMS, VoIP and other system capabilities), is passed to the HOF 324 through an MIH_MACINFO message (step 1010). MIH specific information is set or updated either manually or dynamically by the AN HOF 324.

[0059] The HOF 324 retrieves system information, selects a candidate 3GPP network based on this information and triggers 3GPP authentication and

association procedures toward the selected network (step 1012). The MIH orders the authentication and association through a MIH_MACORDER message (step 1014). Between the WTRU 110 and the AG 114, an extensible authentication protocol over local area network (LAN), (EAPOL), procedure is initiated (step 1016). As a part of this procedure, the WTRU 110 provides the relevant network access identification (NAI). The AG 114 uses the NAI to route an authentication procedure to the relevant AAA server. The AG 114 triggers EAP-authentication key agreement (AKA) authentication and relay messages to a 3GPP AAA server 132 (step 1018). The AG 114 may route AAA messages to other servers to provide basic services.

[0060] Successful routing of EAP-AKA messages results in an establishment of an Internet protocol security (IPsec) tunnel that carries EAP-AKA messages (step 1020). In addition, the AG 114 may use the NAI to determine whether the user requires basic or premium service. Furthermore, the NAI may be used to route messages to specific ports that may only provide services such as network capabilities available for this particular user.

[0061] Upon successful authentication and authorization the WTRU 110 obtains a local IP address from the local dynamic host configuration protocol (DHCP) server or using address resolution protocol (ARP) (step 1022). Using the selected PDG (-APN) the WTRU 110 derives a fully qualified domain name (FQDN) (step 1024). The WTRU 110 uses the FQDN to determine the IP address of the relevant PDG using the local domain name server (DNS) (steps 1026 and 1028). Once the PDG IP address is obtained, an WTRU-PDG tunnel can be established (step 1030 or 1032).

[0062] The WTRU-PDG tunnel may be established in four different ways: 1) the WTRU 110 establishes a tunnel directly to the PDG; 2) the WTRU 110 establishes a tunnel to the WAG 134 and a tunnel from the WAG 134 to the PDG 136 is further established; 3) the AG 114 establishes a tunnel to the WAG 134 and then a tunnel from the WAG 134 to the PDG 136 is further established; 4) the AG 114 establishes a tunnel directly to the PDG 136.

[0063] Once the tunnel is established, the WTRU 110 either receives agent advertisement messages from the PDG (acting as a foreign agent) or requests it

using an agent solicitation message in accordance to RFC2002 (step 1034). The WTRU 110 uses the PGA router address to construct its care of address (CoA) (step 1036). The WTRU 110 registers its CoA with its home agent (HA) 142 (step 1038). Data destined for the WTRU 110 is now routed via the HA 142 through a new tunnel established between the HA 142 and the FA 136 based on the supplied CoA (step 1040).

[0064] Figures 11A-11C, taken together, show a process 1100 for system access, and 802.X and 3GPP inter-working failure case in accordance with the present invention. The WTRU is powered on and the MIH handover function is initialized. The WTRU performs scanning (active or passive) to find a suitable WLAN/3GPP network (step 1102). The WLAN periodically transmits beacon frames for this purpose. The HOF 324 of the WLAN may order changes of the content of the beacon frame at any time (step 1104), which is passed by an MIH_MACCONFIG message (step 1106). If a WLAN network is found, the WTRU reads beacon information (step 1108). The WTRU reads beacon information and it is passed to the HOF 324 through an MIH_MACINFO message (step 1110).

[0065] The MIH function determines whether one or more values provided within the system information parameters satisfies the necessary condition for system access (step 1112). For example, the MIH function determines whether the system operator is bared, the quality of service (QoS) is adequate or there is a better candidate identified within a potential neighboring set provided in the message.

[0066] If the MIH function determines that the parameters provided by the information service do not satisfy internal configured requirements, then the MIH function orders the MAC layer to return to the scanning phase using a MAC_ORDER message (step 1114).

[0067] If the requirements are satisfied, the MIH function triggers EAPOL authentication using a MIH_MACORDER message (step 1116) and EAPOL procedure is initiated (step 1118). The AG 114 may determine the level of service that the user requires, (e.g., 3GPP IMS), based on the NAI that triggered the authentication procedure or the authentication procedure itself.

[0068] The WTRU authentication is performed according to the EAPOL procedures (step 1120). If authentication fails, the system access is denied and the WTRU returns to the initialization state (step 1122). If the NAI provided does not resolve to any 3GPP server, the AG 114 may reject access or direct to local server for further processing (step 1124). For example, the AG 114 may determine that the user is still allowed to receive basic services, even though the authentication procedure failed for premium services. If the AG 114 is not able to route the authentication request, it may respond by indicating the available AAA servers where the request can be routed. If the WTRU determines that there are no suitable AAA servers, the WTRU may decide to return to the initialization state (step 1126).

[0069] If a successful routing of AAA messages is achieved, an IPSec tunnel is established between the AG 114 and to the 3GPP AAA server 132 and the AG 114 relays an EAP message to the AAA server 132 (step 1128). The AG 114 acts as an authenticator between the WTRU and the AAA server. The AG 114 relays authentication messages between the WTRU and the relevant AAA server.

[0070] If the WTRU fails the cellular authentication procedure (step 1130), access to special services, such as 3GPP services, may be denied and the WTRU returns to the initialization state (step 1132). Alternatively, the AG 114 may still grant access to basic services, (e.g., Internet service), or access to a portal that may provide the user with further information.

[0071] If the cellular AAA server successfully authenticates the WTRU, the WTRU proceeds to obtain a local IP address from the local DHCP (step 1134). Using the W-APN, the WTRU constructs an FQDN (step 1136) and attempts to obtain PDG IP address based on the FQDN (step 1138). If the DNS server cannot resolve the FQDN to any IP address, the WTRU cannot access a PDG within the existing WLAN network (step 1140). The WTRU may choose to return the initialization state or to settle for WLAN only services (step 1142). The AG 114 may choose to provide a "default" PDG address. In this case the WTRU shall provide this information to the end user who may decide to connect to the default PDG. This procedure can be automatic based on configuration parameters within the AG 114 and the WTRU 110.

[0072] If the DNS returns a valid PDG address, the WTRU 110 establishes a tunnel towards the PDG 136, (e.g., a L2TP tunnel), and listens for agent advertisement messages from the PDG 136 (step 1144). If no agent advertisement messages are received the WTRU 110 sends an agent solicitation.

[0073] If no response is received (step 1146), (e.g., MIP is not supported), delivery of a packet from other PDN is still possible through the PDG 136. The WTRU 110 may use the local IP address or may request PDP context activation (step 1148). In this case, WTRU-PDG tunnel IP traffic is routed directly from the WTRU 110 to the Internet 120 via the PDG 136 and no seamless mobility is supported beyond the PDG 136.

[0074] Figures 12A and 12B, taken together, show a process 1200 for a WTRU initiated and a WTRU controlled handover from 802.X to 3GPP in accordance with the present invention.

[0075] Referring to Figure 12A, user data flow is established between the WTRU and the CoN 140 over an 802.X via 3GPP PDG 136 (step 1202). The PDP context is active at the GGSN. The MIH handover function receives measurements while the MIH management entity is in a steady state. If the physical layer detects that predetermined performance thresholds have been crossed, the physical layer sends an event indication, MIH_PHY_EVENT, to the MIH handover function (step 1204). If the MAC layer detects that performance thresholds have been crossed, the MAC layer sends an event indication, MIH_MAC_EVENT, to the MIH handover function (step 1206).

[0076] The MIH processes and filters MAC and PHY layers measurements (step 1208) and performs handover evaluation (step 1210). A combination of events, such as signal quality and specific network characteristics, (e.g., preferred PLMN), can be used to determine whether the handover process shall be triggered. If the MIH handover function determines that a condition (or a combination of them) has been met and therefore a handover attempt shall be triggered, the MIH informs the 3GPP layer, (through HOF_PREPARE), that a handover is imminent on the IEEE 802.X side (step 1212).

[0077] Based on this trigger, the WTRU initiates cell selection and performs a routing area update (step 1214). The routing area update is a process executed by

the WTRU to inform the network whenever it moves from one area to the other. The WTRU is responsible for tracking routing area codes. When a routing area code is different from its last update, the WTRU performs another update by sending it to the network. At this point both radio connection and connections towards new SGSN are established (step 1216).

[0078] The new SGSN requests packet data protocol (PDP) context transfer from the PDG (step 1218). The PDP context is a data present on both the SGSN 138 and the GGSN 136 which contains the subscriber's session information when the subscriber has an active session, including subscriber's IP address, subscriber's IMSI, tunnel ID at the GGSN 136 and the SGSN 138, or the like.

[0079] Figure 13 shows a tunnel established between the WTRU and a PDG in accordance with the present invention. A "snap shot" of the current PDP context is taken at the PDG for both uplink and downlink flows. The PDG transfers this information to the new SGSN. Right after PDP context is transferred, the PDG stops sending downlink packets towards the WTRU. Packets received from a GGSN after this time are buffered. When the PDG is ready to start processing packets, the RNC establishes a new GTP tunnel and sends a duplicate of the packets that is buffered towards the PDG, via the old SGSN. This is done until a timer expires. The PDP context is updated at the GGSN and a new GTP tunnel can be established (via Gn' interface). Packets are now received directly from the GGSN via the PDG.

[0080] Referring to Figure 12B, upon successful PDP context transfer, the 3GPP layer informs MIH handover function that handover has successfully completed (step 1220). At such time 3GPP lower layer and higher layer connections are now established (step 1222) and user data flow is in progress between the WTRU 110 and the CoN 140 over a 3GPP network (step 1224). The HOF 324 orders release of the IEEE 802.X radio connection, (e.g., disassociation), (step 1226) and the old media is torn down (step 1228).

[0081] Figures 14A-14C, taken together, show a process 1400 for a WTRU initiated handover from 3GPP to IEEE 802.11 in accordance with the present invention. User data flow is established between the WTRU 110 and the CoN 140 over the 3GPP network (step 1402). System information is transmitted from

the 3GPP network to the WTRU 110 (step 1404). The 3GPP layer extracts relevant system information that can be used to determine whether a handover to a WLAN system may be warranted and the 3GPP layer forwards this information to the MIH handover function (step 1406). Alternatively, the IEEE 802.X layer in the WTRU 110 may execute periodic scanning, either continuously or when prompted by system information received from the 3GPP component (step 1408).

[0082] Relevant 3GPP system information is forwarded to the MIH function (steps 1410, 1412). The MIH handover function determines whether there is a WLAN suitable for selection based on available information, (e.g., explicit indication, RF signature, geographical location, manual or automatic scanning, specific TMSI assignment, or the like) (step 1414). The MIH function then generates a list of potential candidates for handover (step 1416). The MIH function evaluates candidates for handover based on several aspects, such as system operator and known system capabilities (step 1418).

[0083] The MIH handover function finds a target for handover and triggers handover to 802.X system through MIH_MACORDER message (steps 1420, 1422). The WTRU 110 executes 802.X system association and authentication towards the target WLAN system (step 1424).

[0084] When the WTRU 110 is successfully associated and authenticated (step 1426), EAP is used towards relevant 3GPP AAA server 132 in accordance to RFC 2284 (step 1428). The WTRU 110 uses the WLAN identity and the associated PLMN to construct a FQDN and uses it to obtain the associated PDG address through DNS query. The WTRU 110 uses this address to establish an end-to-end tunnel toward the PDG 136, (e.g., using L2TP), (step 1430). Once the tunnel is established, the WTRU 110 executes a routing area update towards the PDG 136. The routing data update received at the PDG 136 triggers a context transfer request towards the old SGSN 138.

[0085] The PDG 136 establishes a new GPRS tunneling protocol (GTP) tunnel as shown in Figure 13 and sends a duplicate of every packet that is buffered to the new SGSN. This is done until a timer expires or the new SGSN is ready to start processing packets. When the new network has successfully activated the

PDP context, it is now ready to start processing packets. The PDP context is updated at the GGSN and a new GTP tunnel can be established. Packets are now received directly from the GGSN toward the new SGSN.

[0086] Figure 15 shows a GTP tunnel between an old RNC and an old SGSN and a GGSN. A “snap shot” of the current context is taken from the old RNC and it is transferred to the PDG via the old SGSN. Both uplink and downlink context information is captured. Right after PDP context is transferred, the RNC stops sending downlink packets towards the WTRU 110. Packets received from the GGSN 136 after this time are buffered.

[0087] Referring back to Figure 14, after 802.X lower and higher layers are established (step 1434), user data flow from the WTRU 110 to the CoN 140 through the IEEE 802.X network is established (step 1436). The MIH informs that the handover has completed, though a HOF_COMMIT message (step 1438) and the 3GPP radio access bearer (RAB) may be released (step 1440).

[0088] Figures 16A and 16B, taken together, show a process 1600 for WTRU initiated 802.X to 802.3 handover in accordance with the present invention. While a data path is established between the WTRU 110 and the IEEE 802.X network (step 1602), an 802.3 physical connection is established (step 1604) and the MIH detects the IEEE 802.3 physical connections (e.g., RJ45 cable has been plugged) (step 1606).

[0089] Upon detection of an 802.3 physical connection by lower layers, a MIH_PHY_EVENT message is sent towards the MIH handover function (step 1608). This message provides characteristics of the physical link that is used to determine whether a handover should be executed. A multi-stream connection, similar to a “layer 3 or IP-based soft-handover” (L3SH) may be attempted. This depends on a few factors, such as availability of A.C. power that renders battery considerations not applicable.

[0090] The MIH handover function continuously process and filters information provided by lower layers (step 1610) and performs handover evaluation to determine whether one or more condition satisfies criteria for triggering a handover procedure (step 1612).

[0091] If the determination is positive, the MIH handover function triggers

handover procedures (step 1614). This includes transfer of context information, (e.g., header compression context, PPP context, or the like), and switching of user data. If L3SH is used, the context may be activated only after a new connection from the new router to the CoN 140 has been established. This information (L3SH support) needs to be communicated between the old and the new access router.

[0092] The MIH handover function uses an HOF_PREPARE message to trigger both context transfer and MIP procedures at the MIP component (step 1616). The WTRU 110 obtains a new IP address from the IEEE 802.3 AG using the newly established physical connection (step 1618). Either using information coming from the HOF_PREPARE message or using existing MIP message, the WTRU 110 obtains the IP address of the new AG, (i.e., 802.3 AG). This allows the WTRU 110 to contact the IEEE 802.3 AG to initiate context transfer procedures (step 1620).

[0093] While context is being transferred to the new AG, (802.3 AG), (step 1622), data is forwarded from the old AG (802.X AG) (step 1624). This allows the WTRU 110 to receive user data before a new CoA is negotiated with the new 802.3 access router (within the IEEE 802.3 AG). The new AG needs to determine whether the context engine needs to be activated or the data stream should simply be relay from/to the WTRU 110. This can be done based on the L3SH information provided by the old router.

[0094] The WTRU 110 negotiates a new CoA using existing MIP messages (step 1626). As the new CoA is ready and the lower layer connection is established (step 1628), the user data path can now be switched from the CoN 140 to the new AG (step 1630). User data is fully is now flowing entirely through the IEEE 802.3 network.

[0095] An HOF_COMMIT message is sent to inform the MIP layer that the old CoA can now be de-registered (step 1632). The MIH tears down the IEEE 802.X connection through an MIH MACORDER message (steps 1634, 1636). Optionally, the MIH may maintain the old 802.X connection to avoid re-associating procedures, when a handover back to 802.X should be performed.

[0096] Figures 17A and 17B, taken together, show a process 1700 for WTRU

initiated 802.3 to 802.X handover in accordance with the present invention. As an 802.3 connection is established, both lower layers (MAC/PHY) and higher layers, (e.g., IP/MIP) connections are established (step 1702, 1704). User data is flowing between the IEEE 802.3 WTRU and 802.3 network (step 1706). MIH system information may be provided to the MIH handover function (step 1708).

[0097] The MIH processes the MIH_PHY_EVENT message (step 1710). Some events, such as availability of A.C. power supply, may cause the MIH trigger simultaneous connection of both 802.3 and 802.X (step 1712). If the MIH handover function determines to trigger handover to 802.X system (step 1714), the MIH handover function issues an MIH_MACORDER message triggering association and authentication procedures (step 1716). An 802.X physical connection may be optionally established (step 1718). In order to facilitate transfer of context information, the WTRU 110 may optionally provide information about the current 802.3 anchor point (step 1720). An 802.3 anchor point is defined as the IEEE 802.3 AG holding context information for the current IEEE 802.3 connection. This information is used by the IEEE 802.X AG to request context transfer should a handover be imminent.

[0098] When the IEEE 802.3 connection is no longer available, (e.g., RJ45 cable is un-plugged), an event is triggered by the lower layers through a MIH_PHY_EVENT message (step 1722). The MIH function evaluates the conditions that might have generated the trigger, (e.g., link is down), and it determines that an 802.X system access, (if the WTRU 110 is not already associated), and a request for transfer of context information should be issued (step 1724).

[0099] The MIH handover function uses an HOF_PREPARE message to alert the MIP entity that a new AN should be initiated (step 1726). This triggers transfer of context information and forwarding of user data from the old AG (803.2) to the new AG (802.X).

[0100] The WTRU 110 obtains a new IP address from the IEEE 802.X AG using ARP or DHCP (step 1728). This step may be executed earlier. This may happen when the WTRU 110 is first associated and authenticated with the IEEE 802.X AG. Once the IEEE 802.X IP address is available, the WTRU 110 triggers

the context transfer procedure and the data forwarding procedure from the old 802.3 AG to the new 802.X AG (steps 1730, 1732). If L3SH is used, the context may be activated only after a new connection from the new router to the CoN 140 has been established. This information (L3SH support) needs to be communicated between the old and the new access router.

[0101] While context is being transferred to the new AG (802.X AG), data is forwarded from the old AG (802.3 AG) (step 1734). This allows the WTRU 110 to receive user data before a new CoA is negotiated with the new 802.X access router (within the IEEE 802.X AG). The new AG needs to determine whether the context engine needs to be activated or the data stream should simply be relayed from/to the WTRU 110. This can be done based on the L3SH information provided by the old router.

[0102] The WTRU 110 then negotiates new CoA using existing MIP messages (step 1736). As the new CoA is ready and the lower layers connection is established, the user data path can now be switched from the CoN 140 to the new AG (step 1738). An HOF_COMMIT message is sent to inform the MIP side that the old CoA can now be de-registered (step 1740).

[0103] Figures 18A and 18B, taken together, show a process 1800 for WTRU initiated and WTRU controlled inter-802 handover in accordance with the present invention. As 802.X lower layer and higher layer procedures are completed (steps 1802, 1804), a data path with the IEEE 802.X network is established (step 1806). During the IEEE 802.X session in progress, the data path is between the WTRU 110 and the IEEE 802.X AN. The MIH at the IEEE 802.X network may optionally provide system information to its peer (step 1808). Information regarding potential neighbors can be optionally provided peer to peer via the MIH_SYSINFO message.

[0104] Measurements of MAC/PHY are sent to the MIH function via MIH_PHY_EVENT (step 1810). Remote measurements can also be forwarded to the WTRU 110 (steps 1812, 1814, 1816). An MIH LLCF processes the measurements (step 1818). For example, the MIH LLCF can average some measurements and compare them with thresholds and create triggers to indicate HOF.

[0105] The HOF 324 decides if handover is necessary based on the information it gets from network information services and measurement reports (step 1820). In order to make intelligent decision, the MIH handover function maintains information from system information update, (e.g., the neighbor list and neighbor networks' information). The MIH handover function makes preventive handover decisions in two steps, preparation and commit. Different thresholds and decision making algorithms may be used for these two steps.

[0106] If the MIH decides a handover is imminent, the MIH triggers a handover preparation procedure across the network by sending HOF_PREPARE messages to both MIP and MAC/PHY (steps 1822, 1824). Both MIP and layer 2 start to prepare for handover. The WTRU 110 establishes a new layer 2 link with the IEEE 802.Y network (step 1826).

[0107] The WTRU 110 obtains a new IP address from the IEEE 802.X network (step 1828). This step may happen earlier. The WTRU MIP triggers context transfer from the IEEE 802.X network to the IEEE 802.Y network (step 1830). While the context is transferred to the IEEE 802.Y network, the data can be forwarded from the IEEE 802.X AG to the IEEE 802.Y AG (step 1832). This allows the WTRU 110 to receive user data before a new CoA is negotiated with the IEEE 802.Y router.

[0108] The WTRU 110 negotiates a new CoA using existing MIP messages (step 1834). As the new CoA is ready and the lower and higher layers connections are established (step 1836), the user data path now is switched to the IEEE 802.Y network (step 1838).

[0109] A HOF_COMMIT message is sent to inform the MIP side that the old CoA can be deregistered (step 1840). Optionally, the old layer 2 connection can be torn down by MIH_MACORDER message (steps 1842, 1844).

[0110] Figures 19A and 19B, taken together, show a process 1900 for WTRU initiated and WTRU controlled inter-802 handover failure cases. The failure can happen at many phases. As 802.X lower layer and higher layer procedures are completed (steps 1902, 1904), a data path with the IEEE 802.X network is established (step 1906). The MIH at the IEEE 802.X network may optionally provide system information to its peer (step 1908). Measurements of MAC/PHY

are sent to the MIH function via MIH_PHY_EVENT (step 1910). Remote measurements can also be forwarded to the WTRU 110 (steps 1912-1916). An MIH LLCF processes the measurements (step 1918). The MIH handover function decides if handover is necessary based on the information it gets from network information services and measurement reports (step 1920). If the MIH decides a handover is imminent, the MIH triggers a handover preparation procedure across the network by sending HOF_PREPARE messages to both MIP and MAC/PHY (steps 1922, 1924). Both MIP and layer 2 start to prepare handover.

[0111] If the layer 2 link to the IEEE 802.Y network cannot be established (step 1926), the lower layer optionally informs the MIH of the failure, or a timer will expire. The MIH then goes back to the steady state. When MIH sends HOF_PREPARE to higher layer (step 1924), the WTRU 110 tries to obtain a new IP address from the IEEE 802.X network. If the WTRU 110 fails to obtain a new IP address (step 1928), the lower layer may inform the MIH of the failure, or a timer will expire. The MIH then goes back to the steady state (step 1930).

[0112] If all the above succeeds, the WTRU MIP triggers context transfer from the IEEE 802.X network to the IEEE 802.Y network (step 1932). If the context transfer fails, the MIH goes back to the steady state (step 1934). Optionally, the MIH may tear down the layer 2 link to the IEEE 802.Y network. If the context is successfully transferred to the IEEE 802.Y network, the data can be forwarded from the IEEE 802.X AG to the IEEE 802.Y AG (step 1936). This allows the WTRU 110 to receive user data before a new CoA is negotiated with the IEEE 802.Y router.

[0113] If the WTRU 110 fails to negotiate a new CoA using existing MIP messages (step 1938), the transferred context in 802.Y should be deleted (step 1940). Assuming that the context in the IEEE 802.X still exists, the data forwarding should be stopped. The MIH then goes back to the steady state (step 1942). If the new CoA is ready and the lower and higher layers connection is established (step 1944), the user data path now is switched to the IEEE 802.Y network (step 1946).

[0114] An HOF_COMMIT message is sent to inform the MIP side that the old CoA can be de_registered (step 1948). Optionally, the old layer 2 connection can

be torn down by MIH_MACORDER message (steps 1950, 1952).

[0115] Figures 20A and 20B, taken together, show a process 2000 for network initiated and network controlled inter-802 handover in accordance with the present invention. While an 802.X session is in progress, the data path is between the WTRU 110 and the IEEE 802.X AN (step 2002). Measurements of MAC/PHY are sent to the MIH function in the IEEE 802.X AN via an MIH_PHY_EVENT message (step 2004). Remote measurements from the WTRU 110 can also be forwarded to the IEEE 802.X network (steps 2006-2010).

[0116] The MIH LLCF processes the measurements (step 2012). For example, the MIH LLCF can average some measurements and compare them with thresholds and create triggers to indicate MIH handover function. The MIH handover function decides if handover is necessary based on the information it gets from network information services and measurement reports (step 2014). In order to make intelligent decisions, the MIH handover function maintains information from system information update, (e.g., the neighbor list and neighbor networks' information). The MIH handover function makes preventive handover decisions in two steps, preparation and commit. Different thresholds and decision-making algorithms can be used for these two steps.

[0117] If the MIH handover function decides a handover is imminent, it triggers handover preparation procedures across the network by sending HOF_PREPARE messages to both MIP and MAC/PHY (steps 2016, 2020). Both MIP and layer 2 start to prepare handover. At higher layer, the IEEE 802.X AG transfers the MIP context to the IEEE 802.Y AG, and at layer 2, the WTRU 110 establishes a new layer 2 link with the IEEE 802.Y network (step 2018). A peer-to-peer message is sent from the MIH handover function in the IEEE 802.X AN to the MIH handover function at the WTRU 110 (step 2022) and the WTRU prepares lower layer connection with the IEEE 802.Y network (step 2024).

[0118] While context is transferred to the IEEE 802.Y network, the data can be forwarded from the IEEE 802.X AG to the IEEE 802.Y AG (step 2026). This allows the WTRU 110 to receive user data before a new CoA is negotiated with the IEEE 802.Y router. The WTRU 110 negotiates a new CoA using existing MIP messages (step 2028). As the new CoA is ready and the lower layers

connection is established, the user data path now is switched to the IEEE 802.Y network (steps 2030, 2032).

[0119] The MIH handover function continues to process information and checks if a handover should be committed. When a HO decision is made by the MIH handover function, it sends a HOF_COMMIT message to the MIP (step 2034). The trigger is also sent to the MIH peer in the WTRU 110 (step 2036). Upon receiving the MIH handover commit command, the old CoA can be deregistered. Optionally, the MIH handover function may send MIH_MACORDER to tear down the old layer 2 connection (steps 2038, 2040).

[0120] The present invention implements the Fast Handover Protocol in MIH. One of the objectives of the Fast Handover Protocol is to overcome the latency due to MIP registration, and the basic idea is to anticipate movement with the help of link layer (triggers). This implies preparing the network in advance and requires anticipated handover initiated by the WTRU 110 and the network. This is achieved by commencing the registration process slightly before the actual handover.

[0121] Figure 21 shows a process 2100 for WTRU initiated inter-802 fast handover in accordance with the present invention. The WTRU 110 requests information about its neighbors by router solicitation proxy (step 2102). This is used to build an internal list of neighboring APs at the WTRU 110. The WTRU 110 receives information pertaining to its surrounding APs, (such as IP and MAC addresses, operating frequency and ESSID information), via a router advertisement message (step 2104). The WTRU 110 forwards that information to the MIH via a pre-established link between MIH and MIP (not shown).

[0122] The MIH LLCF processes measurements (step 2106) and the MIH handover function performs handover evaluation (step 2108). If the MIH handover function decides to handover, the MIH handover function sends an MIH_HANDOVER_PREPARE trigger to MIP entity (step 2110), which is acknowledged by MIH_HANDOVER_PREPARE response message (step 2116). The WTRU 110 obtains a new CoA (step 2112).

[0123] A fast binding update (FBU) is a message from the WTRU 110 instructing its (previous) AR to start directing its traffic to the new AR. The FBU

is constructed using information extracted from the router advertisement message and is sent after receiving the MIH_HANDOVER_PREPARE.Indication (step 2114). The object of the FBU message is to authorize the previous AR to bind the (previous) CoA to the new CoA

[0124] Having received a FBU, the previous AR starts the procedures for handover and tunnel creation. A handover initiate message, which is Internet Control Message Protocol (ICMPv6) message, is sent by the previous AR to the new AR to trigger the process of the handover (step 2118). A handover acknowledge (HACK) is an ICMPv6 message that is sent by the new AR to the previous AR as a reply to the handover initiate message (step 2120). A Fast Binding Acknowledge (FBACK) message is sent by the previous AR to the new AR to acknowledge receipt of the FBU message after the previous AR receives the HACK from the New AR and to the WTRU 110 for information purposes, (steps 2122, 2126). The temporary tunnel is established between the previous AR and the new AR (step 2124).

[0125] IP routing information is sent from the MIP entity to the MIH handover function (step 2128) and the MIH handover function sends a MIH_HANDOVER_COMMIT message to the MIP entity and the WTRU 110 disconnects with the previous AR (step 2130). The previous AR then starts forwarding packets to new AR (step 2132). In order to announce itself to the new AR, and as soon as the WTRU 110 re-gains connectivity, the WTRU 110 sends a Fast Neighbor Advertisement (FNA) message to the new AR (step 2134). The handover is complete and packets are now delivered to the WTRU 110 from the new AR (step 2136)

[0126] Figure 22 shows a process 2200 for implementing Hierarchical MIPv6 (HMIPv6) using an inter-802 fast handover message flow in accordance with the present invention. This provides localized mobility management for reducing signaling load and handover latency. The concept of global mobility refers to a situation where the WTRU 110 moves from one mobile anchor point (MAP) to another, thus changing its regional care of address (RCoA). A typical scenario of a local mobility case is an WTRU 110 moving within the same MAP region, but changing from one AR to another. These types of local handovers are managed

locally and transparently to WTRU's correspondent hosts.

[0127] A WTRU 110 receives a router advertisement from the new MAP to which it has moved (step 2202). The global address of the MAP is included in the advertisement. Based on the prefix received in the MAP option, the WTRU 110 forms the new RCoA specific to its MAP. The router advertisement, along with the WTRU's measurement results, is forwarded to the MIH via a pre-established link between MIH and MIP. The MIH LLCF analyses these measurements (step 2204). The MIH handover function performs handover evaluation (step 2206). The MIH handover function sends an HANDOVER_PREPARE.Indication trigger to the MIP if the MIH handover function determines that a handover is advantageous or necessary (step 2208) and it is acknowledged by a HANDOVER_PREPARE.Response message (step 2212). The WTRU 110 obtains CoAs, RCoA and On-Link Care of Address (LCoA) (step 2210).

[0128] Upon receiving the MIH_HANDOVER_PREPARE.Indication trigger, the MIP initiates a pre-binding procedure sending an LBU with the LCoA to the previous MAP (step 2211) to reduce packet loss and to perform a rapid handover. This is performed in consistent with the make-before-break principle. At this point, an MIH_HANDOVER_COMMIT.Indication trigger is sent by the MIH to the MIP (step 2214), which is acknowledged by an MIH_HANDOVER_COMMIT.Response message (step 2216).

[0129] The WTRU 110, having received the trigger indicating a handover, then sends a Binding Update (BU) to the new MAP (step 2218). This message includes a "Home Address" option that contains the RCoA. This BU binds the WTRU's RCoA to its LCoA.

[0130] The MAP sends a BACK to the WTRU 110 (step 2220) and the MIP entity sends an IP routing information to the MIH handover function (step 2222). A bi-directional tunnel is then established between the WTRU 110 and the new MAP (step 2224).

[0131] As soon as registration is confirmed with the new MAP, the WTRU registers its new RCoA with the HA by sending a BU specifying the binding to the HA 142 (step 2226).

[0132] This step is part of the MIPv6 route optimization method. A BU

similar to that in the previous step is also sent to the WTRU's CoN 140 (step 2228). This allows the CoN 140 to establish a link with the new MAP for the purpose of transmitting packets directly to that new MAP (step 2230).

[0133] Although the features and elements of the present invention are described in the preferred embodiments in particular combinations, each feature or element can be used alone without the other features and elements of the preferred embodiments or in various combinations with or without other features and elements of the present invention.

*

*

*

CLAIMS

What is claimed is:

1. In a wireless communication system including a plurality of technologically diversified access networks and at least one multi-stack wireless transmit/receive unit (WTRU), the multi-stack WTRU including a protocol stack including a media independent handover (MIH) function, a method for establishing a communication link with the access networks, the method comprising:
 - (a) activating the WTRU and initializing the MIH function;
 - (b) the WTRU scanning for an access network;
 - (c) the WTRU detecting beacon frames transmitted by an access network;
 - (d) the WTRU reading the content of the detected beacon frames if it determines that the beacon frames support MIH information;
 - (e) the WTRU passing MIH information found in the beacon frames to the MIH function; and
 - (f) the MIH function processing the MIH information and establishing a communication link with the access network.
2. The method of claim 1 wherein the WTRU and the access networks implement a fast handover procedure in accordance with mobile Internet protocol version 6 (MIPv6).
3. The method of claim 2 further comprising:
 - the WTRU sending a router solicitation message to a current access router (AR);
 - the current AR sending a router advertisement message to the WTRU;
 - the WTRU performing measurements for a new AR and making a handover decision;
 - the WTRU sending a fast binding update to the current AR;
 - establishing a tunnel between the current AR and the new AR; and
 - delivering a packet through the new AR.

4. The method of claim 1 wherein the WTRU and the access networks implement hierarchy mobile Internet protocol version 6 (HMIPv6).

5. The method of claim 1 further comprising:
a current mobile anchor point (MAP) sending a router advertisement message to the WTRU;
the WTRU receiving the router advertisement from the current MAP;
the MIH function of the WTRU performing measurements for a new MAP and making a handover decision;
the WTRU obtaining at least one care of address (CoA);
the WTRU sending a local binding update to the current MAP;
the WTRU sending a binding update to the new MAP;
the WTRU establishing a tunnel between the WTRU and the new MAP;
the WTRU registering the CoA at a home agent;
the WTRU sending a local binding update to a core network; and
delivering a packet through the new MAP.

6. A wireless communication system for performing a media independent handover (MIH), the system comprising:

a plurality of access networks that are concurrently deployed under different standards, each access network including an MIH function; and
at least one multi-stack wireless transmit/receive unit (WTRU) configured to support multiple wireless standards and including an MIH function, wherein the MIH functions of the WTRU and the access networks obtain information about system conditions and network topology, and perform a handover from a current access network to another access network upon receipt of an MIH trigger.

7. In a wireless communication system including a plurality of IEEE 802.X networks and Third Generation Partnership Project (3GPP) networks that are concurrently deployed, wherein each of at least one multi-stack wireless transmit/receive unit (WTRU) and the networks include a media independent

handover (MIH) function, a method for interworking between at least one of the IEEE 802.X networks and the 3GPP networks, the method comprising:

the MIH function of the WTRU reading MIH information transmitted from the IEEE 802.X network;

the MIH function of the WTRU triggering 3GPP authentication and authorization procedures;

the WTRU obtaining a local internet protocol (IP) address;

the WTRU establishing a tunnel to a packet data gateway (PDG) in a 3GPP core network;

the WTRU constructing a care of address (CoA); and

the WTRU registering the CoA with a home agent of the WTRU, whereby data destined for the WTRU is routed via the home agent through a new tunnel established between the home agent and a foreign agent based on the CoA.

8. The method of claim 7 wherein the MIH information is transmitted via a beacon frame.

9. The method of claim 8 wherein a special flag is used to indicate that MIH information is supported by the beacon frame.

10. The method of claim 7 wherein the MIH information includes at least one of system operator identity, access point name, neighboring maps and system capabilities.

11. The method of claim 7 wherein the WTRU and an access gateway of the IEEE 802.X network use an extensible authentication protocol over local area network (LAN) (EAPOL) procedure for 3GPP authentication.

12. The method of claim 11 wherein the WTRU derives a fully qualified domain name (FQDN) using a selected PDG, and the WTRU uses the FQDN to determine the IP address of the PDG using the local domain name server (DNS) to establish a WTRU-PDG tunnel.

13. The method of claim 12 wherein the WTRU establishes a tunnel directly to the PDG.

14. The method of claim 12 further comprising:
the WTRU establishing a tunnel to a wireless access gateway (WAG); and
the WAG establishing a tunnel to the PDG.

15. The method of claim 12 further comprising:
an access gateway (AG) of the IEEE 802.X network establishes a tunnel to
a wireless access gateway (WAG); and
the WAG establishing a tunnel to the PDG.

16. The method of claim 12 further comprising:
the AG establishing a tunnel directly to the PDG.

17. A system for performing a media independent handover (MIH), the system comprising:
a plurality of IEEE 802.X networks;
a plurality of Third Generation Partnership Project (3GPP) networks which are concurrently deployed with the IEEE 802.X networks; and
at least one wireless transmit/receive unit (WTRU) configured to access both the IEEE 802.X networks and the 3GPP networks, the WTRU comprising an MIH function for performing handover between the IEEE 802.X networks and 3GPP networks.

18. The system of claim 17 wherein the WTRU is configured to read MIH information transmitted from one of the IEEE 802.X networks, trigger 3GPP authentication and authorization procedures based on the MIH information, obtain a local Internet protocol (IP) address, establish a tunnel to a packet data gateway (PDG) in a 3GPP core network, construct a care of address (CoA) and register the CoA with a home agent of the WTRU, whereby data

destined for the WTRU is routed via the home agent through a new tunnel established between the home agent and a foreign agent based on the CoA.

19. A wireless communication system comprising:
a plurality of technologically diversified access networks; and
at least one multi-stack wireless transmit/receive unit (WTRU) including a protocol stack with a media independent handover (MIH) function, wherein the WTRU scans for an access network, detects frames transmitted by an access network, reads the content of the detected beacon frames if it determines that the beacon frames support MIH information, passes MIH information found in the beacon frames to the MIH function, and the MIH function processes the MIH information and establishes a communication link with the access network.

20. The system of claim 19 wherein the WTRU and the access networks implement a fast handover procedure in accordance with mobile Internet protocol version 6 (MIPv6).

21. The system of claim 20 further comprising a current access router (AR), wherein the WTRU sends a router solicitation message to the current AR, the current AR sends a router advertisement message to the WTRU, the WTRU performs measurements for a new AR and makes a handover decision, the WTRU obtains a new care of address (CoA), the WTRU sends a fast binding update to the current AR, a tunnel is established between the current AR and the new AR, and a packet is delivered through the new AR.

22. The system of claim 19 wherein the WTRU and the access networks implement hierarchy mobile Internet protocol version 6 (HMIPv6).

23. The system of claim 19 further comprising a current mobile anchor point (MAP) which sends a router advertisement message to the WTRU, wherein the WTRU receives the router advertisement from the current MAP, the MIH function of the WTRU performs measurements for a new MAP and makes a

handover decision, the WTRU obtains a care of address (CoA), the WTRU sends a local binding update to the current MAP, the WTRU sends a binding update to the new MAP, the WTRU establishes a tunnel between the WTRU and the new MAP, the WTRU registers the CoA at a home agent, the WTRU sends a local binding update to a core network, and a packet is delivered through the new MAP.

24. In a wireless communication system including a plurality of technologically diversified access networks, a multi-stack wireless transmit/receive unit (WTRU) comprising:

a protocol stack including:

a user plane; and

a media independent handover (MIH) management plane in communication with the user plane for managing handovers between the WTRU and different ones of the access networks in response to triggers received from the user plane.

25. The WTRU of claim 24 wherein the protocol stack further comprises at least one technology-specific handover plane.

26. The WTRU of claim 24 wherein the MIH management plane includes:

an MIH higher layer convergence function (HLCF);

a handover function; and

an MIH lower layer convergence function (LLCF).

27. The WTRU of claim 26 wherein the user plane includes:

a mobility management entity;

a physical (PHY) layer; and

a medium access control (MAC) layer.

28. The WTRU of claim 27 wherein the HLCF provides an interface between the handover function and the mobility management entity specific to a particular technology.

29. The WTRU of claim 28 wherein the handover function collects handover events from the HLCF and determines whether a handover is required based on certain criteria.

30. The WTRU of claim 27 wherein the LLCF provides an event service that compiles PHY and MAC layer events specific to a particular technology.

31. The WTRU of claim 27 wherein the LLCF receives handover triggers from the PHY and MAC layers when no handover entity exists.

32. In a wireless communication system including a plurality of technologically diversified access networks, a multi-stack wireless transmit/receive unit (WTRU) having an integrated circuit (IC) comprising:

a protocol stack including:

a user plane; and

a media independent handover (MIH) management plane in communication with the user plane for managing handovers between the WTRU and different ones of the access networks in response to triggers received from the user plane.

33. The IC of claim 32 wherein the protocol stack further comprises at least one technology-specific handover plane.

34. The IC of claim 32 wherein the MIH management plane includes:
an MIH higher layer convergence function (HLCF);
a handover function; and
an MIH lower layer convergence function (LLCF).


35. The IC of claim 34 wherein the user plane includes:
a mobility management entity;
a physical (PHY) layer; and
a medium access control (MAC) layer.

36. The IC of claim 35 wherein the HLCF provides an interface between the handover function and the mobility management entity specific to a particular technology.

37. The IC of claim 35 wherein the handover function collects handover events from the HLCF and determines whether a handover is required based on certain criteria.

38. The IC of claim 35 wherein the LLCF provides an event service that compiles PHY and MAC layer events specific to a particular technology.

39. The IC of claim 35 wherein the LLCF receives handover triggers from the PHY and MAC layers when no handover entity exists.

**FIG. 1**

2/31






FIG. 2






FIG. 5B





FIG. 5A






FIG. 7C

FIG. 7B

FIG. 7A




FIG. 8B

FIG. 8A




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B

12/31




FIG. 11C






FIG. 12A

**FIG. 12B**

15/31

**FIG. 13**




FIG. 14A




FIG. 14B







FIG. 14C





**FIG. 16B**





FIG. 17A

**FIG. 17B**







FIG. 18A

26/31

**FIG. 19A**

**FIG. 19B**

28/31

**FIG. 20A**




FIG. 20B

