

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 April 2009 (23.04.2009)

PCT

(10) International Publication Number
WO 2009/052052 A1

- (51) International Patent Classification:
G02B 5/02 (2006.01) G02B 5/30 (2006.01)
- (21) International Application Number:
PCT/US2008/079725
- (22) International Filing Date: 13 October 2008 (13.10.2008)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/980,205 16 October 2007 (16.10.2007) US
- (71) Applicant (for all designated States except US): 3M INNOVATIVE PROPERTIES COMPANY [US/US]; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): GAIDES, Gary, E. [US/US]; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US). EPSTEIN, Kenneth, A. [US/US]; 3M Center, Post Office Box 33427, Saint Paul, MN 55133-3427 (US).
- (74) Agents: HEITI, Robert, V. et al.; 3M Center, Office of Intellectual Property Counsel Post Office Box 33427, Saint Paul, MN 55133-3427 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL,

[Continued on next page]

(54) Title: HIGHER TRANSMISSION LIGHT CONTROL FILM




Fig. 5

(57) Abstract: A light control film, and light collimating assemblies and liquid crystal displays incorporating such light control films are described. The light control film includes alternating transmissive and absorptive regions, where the refractive index of each transmissive region is greater than the refractive index of each absorptive region. The absorptive regions form interfaces at angles that are close to the perpendicular to the light control film. A portion of the incident light intercepting the absorptive region undergoes Total Internal Reflection, and is transmitted through the film. The axial brightness of light passing through the film is increased, the brightness is more uniform within the viewing angle, and the viewing cutoff angle is sharpened.

WO 2009/052052 A1



NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG,
CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii))*

Declarations under Rule 4.17:

— *as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))*

Published:

— *with international search report*

HIGHER TRANSMISSION LIGHT CONTROL FILM

Field of the Invention

5 This invention generally relates to light control films and displays incorporating same. In particular, the invention relates to light control films having improved transmission of light.

Background

10 Light control film (LCF), also known as light collimating film, is an optical film that is configured to regulate the transmission of light. Various LCFs are known, and typically include a light transmissive film having a plurality of parallel grooves wherein the grooves are formed of a light-absorbing material.

LCFs can be placed proximate a display surface, image surface, or other surface to be viewed. At normal incidence, (i.e. 0 degree viewing angle) where a viewer is looking at an image through the LCF in a direction that is perpendicular to the film surface, the image is viewable. As the viewing angle increases, the amount of light transmitted through the LCF decreases until a viewing cutoff angle is reached where substantially all the light is blocked by the light-absorbing material and the image is no longer viewable. This can provide privacy to a viewer by blocking observation by others that are outside a typical range of viewing angles.

LCFs can be prepared by molding and ultraviolet radiation curing a polymerizable resin on a polycarbonate substrate. Such LCFs are commercially available from 3M Company, St. Paul, MN, under the trade designation "3M™ Filters for Notebook Computers and LCD Monitors".

Advances in display technology have resulted in brighter, higher resolution and more energy efficient displays that consumers want. The brightness and resolution of a display can be reduced when an LCF is positioned in front of the display for security or other purposes. It

would be desirable to have an LCF which does not reduce the brightness and resolution of a display.

Summary

5 Generally, the present invention relates to light control films. The present invention also relates to collimated lighting assemblies and displays incorporating collimated lighting assemblies.

10 In one aspect of the invention, a light control film includes alternating transmissive and absorptive regions located between a light input surface and a light output surface. Each absorptive region includes optically absorptive material selected from a pigment, a dye, or a combination; in one aspect, the material is carbon black pigment. The index of refraction of each transmissive region is greater than the index of refraction of each absorptive region, such that the difference in the refractive indices is not less than 0.005. In one aspect, the difference in the refractive indices is less than 0.1; in another aspect, the difference is between 0.007 and 0.06. A first interface formed between a transmissive region and an adjacent absorptive
15 region defines an interface angle between the first interface and a direction perpendicular to the light output surface, such that the interface angle is not greater than 3 degrees. In one aspect, a second interface formed between the absorptive region and a second adjacent transmissive region forms a second interface angle defined between the second interface and a direction perpendicular to the light output surface such that the second interface angle is not
20 greater than 3 degrees.

In one aspect, light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at greater than 80% of the maximum brightness measured at any angle less than 10 degrees from the direction perpendicular to the light output surface; in another
25 aspect, measured at any angle less than 20 degrees. In one aspect, the light exits the light output surface at greater than 90% of the maximum brightness measured at any angle less than 10 degrees from the perpendicular; in another aspect, measured at any angle less than 20 degrees.

In one aspect, the light control film includes a polar viewing cutoff angle, and light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at less than 10% of the maximum brightness measured at any angle greater than the polar viewing cutoff angle; in another aspect, less than 5% of the maximum brightness.

In one aspect of the invention, a collimated lighting assembly includes a light control film and a light source emitting light toward a light input surface of the light control film. The light control film includes a light input surface and transmissive and absorptive regions. The transmissive region having an index of refraction $N1$, and the absorptive region having an index of refraction $N2$, where $N1-N2$ is not less than 0.005. A first interface between the transmissive region and the adjacent absorptive region makes an angle of less than 3 degrees with a direction perpendicular to the input surface. In one aspect, a second interface formed between the transmissive region and a second absorptive region forms a second interface, and the second interface makes an angle of not greater than 3 degrees with a direction perpendicular to the input surface. In one aspect, the collimated lighting assembly can also include a prismatic film, a reflective polarizer, or a combination of a prismatic film and a reflective polarizer. The prismatic film and the reflective polarizer can be placed between the light source and the light control film. The reflective polarizer can be laminated to the light control film. The prismatic film can be positioned between the light source and the reflective polarizer.

In one aspect of the invention, a liquid crystal display includes a light control film, a light source emitting light toward a light input surface of the light control film, and a liquid crystal display module receiving light from a light output surface of the light control film. The light control film includes alternating transmissive and absorptive regions disposed laterally within a plane defined by a light input surface and a light output surface. The light input surface is positioned opposite the light output surface. The index of refraction of each absorptive region is less than an index of refraction of each transmissive region by at least 0.005. A first interface between a transmissive region and a first adjacent absorptive region defines an interface angle θ_1 measured from a direction perpendicular to the plane, wherein θ_1

is not greater than 3 degrees. In one aspect, a second interface formed between the transmissive region and a second absorptive region forms a second interface angle defined between the second interface and a direction perpendicular to the light output surface such that the second interface angle is not greater than 3 degrees.

5 In one aspect, the liquid crystal display can also include a prismatic film, a reflective polarizer, or a combination of a prismatic film and a reflective polarizer. The prismatic film and the reflective polarizer can be placed between the light source and the light control film. The reflective polarizer can be laminated to the light control film. The prismatic film can be positioned between the light source and the reflective polarizer.

10

These and other aspects of the present application will be apparent from the detailed description below. In no event, however, should the above summaries be construed as limitations on the claimed subject matter, which subject matter is defined solely by the attached claims, as may be amended during prosecution.

15

Brief Description of the Drawings

Throughout the specification reference is made to the appended drawings, where like reference numerals designate like elements, and wherein:

20

FIG. 1 is a cross-section view of an LCF.

FIG. 2 is a perspective view of a microstructured film article.

FIG. 3 is a perspective view of an LCF.

FIG. 4 is a perspective view of an LCF.

FIG. 5 is a schematic cross-section of an LCF.

25

FIG. 6 is a perspective schematic of a backlit display.

FIG. 7 is a plot of the brightness of an LCF.

FIG. 8 is a plot of the brightness of another LCF.

FIG. 9 is a plot of the brightness of another LCF.

The figures are not necessarily to scale. Like numbers used in the figures refer to like components. However, it will be understood that the use of a number to refer to a component in a given figure is not intended to limit the component in another figure labeled with the same number.

5

Detailed Description

The present application is directed to an LCF having an increased brightness and uniformity of transmitted light while maintaining a well-defined viewing cutoff angle. A portion of the light entering the LCF undergoes Total Internal Reflection (TIR) within the LCF, increasing the amount of light transmitted through the film. In one aspect, the LCF is placed between the light source and an image plane of a backlit display, to improve the display brightness and uniformity, without reducing resolution. The included wall angles and difference of indices of refraction between alternating absorbing and transmitting regions are kept small to accomplish these properties.

LCFs are often made to ensure that the absorptive regions absorb as much of the incident light as possible. Highly absorptive regions minimize the amount of light that may “leak” through these regions, and therefore control the directionality and the privacy function of the LCF. Incident light that is reflected from these absorptive regions is also generally minimized to reduce spurious or “ghost” images that can arise from such reflections. LCFs can be placed between a viewer and an image plane of a display to limit the viewing angle of an image. Image planes can be included, for example, in a Liquid Crystal Display (LCD), a graphics display, and an indicia display. In some cases, LCFs can be used in a projection display, where information in the image plane is projected to a receiving surface.

In one aspect, the relative refractive indices of the absorptive and transmissive regions are adjusted. This adjustment may result in a reduction of ghost images produced by reflections within the LCF. When the refractive index of the transmissive region is less than the refractive index of the absorptive region, light incident to the interface between them is refracted into the absorptive region and absorbed. The refractive indexes of the two regions can be essentially “matched” so that the absorptive region refractive index is slightly higher

30

than (if not equal) to the transmissive region, and reflections are essentially eliminated. Unfortunately, the portion of light which is absorbed reduces the total light transmitted through the LCF, and it is desirable to utilize a portion of this absorbed light, without altering the intended viewing angle

5 One aspect of the present invention is an LCF that is placed on the side of the display image plane which is opposite the viewer (i.e. between a light source used to illuminate the display and the image plane of the display). An LCF so positioned, minimizes the formation of ghost images since the LCF collimates the light into a viewing angle prior to reaching an image plane in the display. In one aspect of the invention, a portion of the light which
10 impinges on the interface between the absorptive and transmissive regions in the LCF reflects from the interface and travels to the display, increasing the brightness (or “gain”) of the display within the intended viewing angle. Transmission of light outside of the intended viewing angle is generally not desired. A reflective interface, such as a reflective metal, can cause light to be transmitted outside of the intended viewing angle, and typically is not
15 acceptable.

 The brightness of the display can be increased when incident light undergoes TIR from the interface between the absorptive and transmissive regions. Whether a light ray will undergo TIR or not, can be determined from the incidence angle with the interface, and the difference in refractive index of the materials used in the transmissive and absorptive regions.
20 In one aspect of the invention, the refractive index of the absorptive region is no greater than the refractive index of the transmissive region. In some cases, the index of refraction of the transmissive region is greater than the index of refraction of the light absorptive region by at least about 0.005. In some cases, the difference between the indexes is less than 0.1. In some cases, the difference between the indexes is between 0.007 and 0.06. As used herein,
25 “between” two numbers in a range is meant to include the endpoints of the range. For example, “between 0.007 and 0.06” is meant to include the endpoints 0.007 and 0.06, and all numbers between these two endpoints.

 In one aspect, the LCF can be placed between the light source and the image display plane (e.g. LCD panel) to improve the performance of displays such as automotive displays or

avionics displays. High brightness during daylight conditions is desired for readability; however, the light from the display may produce unwanted reflections at surfaces, such as the front wind screen. Unwanted reflections become more apparent in low ambient light conditions. In one aspect, the brightness of the display is increased and unwanted reflections
5 decreased, since light remains within a controlled viewing angle,

FIG. 1 shows a cross-sectional view of an LCF **100** that includes a light output surface **120** and a light input surface **110** opposite light output surface **120**. LCF **100** includes alternating transmissive regions **130**, absorptive regions **140**, and an interface **150** between
10 transmissive regions **130** and absorptive regions **140**. Transmissive regions **130** have a base width “**W**” disposed apart from each other by a pitch “**P**”, and include a land region “**L**” between absorptive regions **140** and light output surface **120**. Absorptive regions **140** have a base **145**, a height “**H**” and are displaced apart from each other by pitch “**P**”. Interface **150** forms an interface angle θ_I with a normal **160** to light output surface **120**. As described herein, by “normal” to a surface is meant perpendicular to the surface. LCF **100** includes an
15 internal viewing cutoff angle Φ_I defined by the geometry of alternating transmissive regions **130** and absorptive regions **140**.

FIG. 2 shows a microstructured film article **200** comprising at least one microstructured surface **210**, which can be used to make an LCF. In one case, microstructured surface **210** can include a plurality of grooves **201a-201d**. As shown in **FIG. 2**, a continuous land layer **230** can be present between the base of the grooves **220** and the
20 opposing surface **211** of microstructured film article **200**. In one case, grooves **220** can extend all the way through the microstructured film article **200**. In one case, microstructured film article **200** can include a base substrate layer **260** which can be integrally formed with, or separately added to microstructured film article **200**.

FIG. 3 shows an LCF **300** wherein grooves **201a-201d** of **FIG. 2** have been rendered light-absorbing by being filled with a light absorbing material **350**. Light absorbing material **350** in the shape of the recess of the (e.g. groove) microstructure is herein referred to as
25 absorptive region **140**.

FIG. 4 shows an LCF **400** that further includes an optional cover film **470** that can be the same, or different than, base substrate layer **260**. Optional cover film **470** can be bonded to the microstructured surface with an adhesive **410**. Adhesive **410** can be any optically clear adhesive, such as a UV-curable acrylate adhesive, a transfer adhesive, and the like. LCF **400** also includes light input surface **110** and light output surface **120** opposite light input surface **110**, defining a plane. It is to be understood that for the purposes of describing the invention herein, LCF **400** is positioned such that light input surface **110** is disposed proximate to a base **145** of absorptive region **140**, however, light input surface **110** can also be disposed opposite base **145**. In other words, LCF **400** can be positioned such that base **145** is closer to a light source (not shown) that injects light into light input surface **110**, or it can also be positioned such that base **145** is closer to a display plane (not shown) that receives light from light output surface **120**.

As shown in **FIGS. 3** and **4**, transmissive regions **130** between absorptive regions **140** have an included wall angle θ_T , a transmissive region base width “**W**”, an effective height “**H**”, a pitch “**P**”, and a polar viewing cutoff angle Φ_P . Included wall angle θ_T is two times the interface angle θ_I shown in **FIG. 1** for symmetric absorptive regions. In one case, interface angle θ_I can be different for each interface **150**, and included wall angle θ_T is equal to the sum of the interface angles θ_I on each side of absorptive region **140**, for an unsymmetrical absorptive region. Polar viewing cutoff angle Φ_P can be determined by applying Snell’s law to the rays defining the internal viewing cutoff angle Φ_I , using the indices of refraction of optional cover film **470**, adhesive **410**, transmissive regions **130**, base substrate layer **260**, and the material that LCF **400** is immersed in (typically air). Polar viewing cutoff angle Φ_P is equal to the sum of a polar viewing cutoff half angle Φ_1 and a polar viewing cutoff half angle Φ_2 each of which are measured from the normal to light input surface **110**. In some cases, polar viewing cutoff angle Φ_P can be symmetric, and polar viewing cutoff half angle Φ_1 is equal to polar viewing cutoff half angle Φ_2 . In some cases, polar viewing cutoff angle Φ_P can be asymmetric, and polar viewing cutoff half angle Φ_1 is not equal to polar viewing cutoff half angle Φ_2 . For the purposes of this disclosure, an angle

“ Φ ” shown in FIG. 4 and measured from the normal to light input surface **110** along the direction shown, is herein referred to as a “polar viewing angle”. The polar viewing angle Φ can range from 0° (i.e. normal to light input surface **110**) to 90° (i.e. parallel to light input surface **110**).

5 The material properties of transmissive regions **130**, included wall angle θ_T , pitch “**P**”, and transmissive region base width “**W**” can impact light transmission through LCF **400**. LCFs can have relatively large included wall angles, such as greater than 10 degrees or more. Larger wall angles increase the width of the light absorbing regions, thereby decreasing transmission at normal incidence. Smaller wall angles are preferred, such as less than 10
10 degrees, so that the transmission of light at normal incidence can be made as large as possible.

 In one aspect, the present invention can be directed to LCFs where the included wall angle can be not greater than 6° . In one aspect, the included wall angle can be not greater than 5° , such as less than 5° , 4° , 3° , 2° , 1° or 0.1° . As described herein, the included wall angle can be related to the interface angle for symmetric and asymmetric absorptive regions.
15 As such, in one aspect, the interface angle can be 3° , or not greater than 3° , for example not greater than 2.5° , 2° , 1° , or 0.1° . Smaller wall angles can form grooves having a relatively high aspect ratio (**H/W**) at a smaller pitch “**P**”, and can provide a sharper image cutoff at lower viewing angles. In some cases, the transmissive regions have an average height, “**H**”, and an average width at its widest portion, “**W**”, and **H/W** is at least 1.75. In some cases,
20 **H/W** is at least 2.0, 2.5, 3.0 or greater.

 LCFs can be made to have any desired polar viewing cutoff angle. In one aspect, the polar viewing cutoff angle ranges from 40° to 90° or even higher. The polar viewing cutoff angle Φ_P , can be determined as discussed elsewhere by the parameters “ θ_I ”, “**H**”, “**W**”, “**P**”, and the indices of the LCF materials. In some cases, it can also be useful to define a
25 “functional polar viewing angle” which includes light transmitted through the LCF at angles larger than the polar viewing cutoff angle. For example, light that intercepts the absorptive regions at angles slightly larger than the internal viewing cutoff angle Φ_I can “bleed through” the thinnest portions of the absorptive region (i.e. partially transmit through the top and bottom of the light absorbing regions represented as trapezoids shown in **FIG. 1**). The

functional polar viewing angle can be defined as the angle at which the brightness decreases to a small percentage, for example 10%, 5% or even less, of the axial brightness.

FIG. 5 shows an LCF **500** according to one aspect of the present invention. The light transmission of LCF **500** is greater than the light transmission through prior art LCFs, since some of the light impinging on absorptive regions **140** is reflected by TIR. LCF **500** includes transmissive regions **130** comprising a material having index of refraction N_1 , and absorptive regions **140** comprising a material having an index of refraction N_2 which is not greater than N_1 . The critical angle, θ_c (not shown) for the interface is $\theta_c = \arcsin(N_2/N_1)$. Light rays impinging on interface **150** at angles greater than θ_c , undergo TIR at interface **150**. Light rays impinging on interface **150** at angles less than θ_c are absorbed by absorptive regions **140**.

FIG. 5 shows three light rays, **ABC**, **DEF** and **GH** which enter transmissive region **130** through light input surface **110**. Light ray **ABC** enters transmissive region **130** within internal viewing cutoff angle Φ_I , intercepts absorptive region **140** at angle of incidence θ_i greater than θ_c , and undergoes TIR to exit through light output surface **120**. In a similar manner, light ray **DEF** enters transmissive region **130** outside of internal viewing cutoff angle Φ_I , intercepts absorptive region **140** at angle of incidence θ_i greater than θ_c , and undergoes TIR to exit through light output surface **120**. Light ray **GH** enters transmissive region **130** outside internal viewing cutoff angle Φ_I , intercepts absorptive region **140** at angle of incidence θ_i less than θ_c , and is absorbed by absorptive region **140**. The included wall angle θ_T , transmissive index N_1 , and absorptive index N_2 , are adjustable parameters for control of the transmission of light through light output surface **120**. Selection of these parameters can cause some of the light which would otherwise be absorbed by absorptive region **140**, to instead be reflected from interface **150** and directed through the output surface within the intended internal viewing cutoff angle Φ_I .

As the index difference between the absorptive regions and the transmissive regions increases, critical angle θ_c decreases, and more of the light impinging on the interface is reflected from the interface. The LCF has higher brightness (or gain), but can result in the undesired transmission of light through the output surface of the LCF at angles that are larger than the intended viewing cutoff angle. In some cases, it can be desirable to limit the

difference in the relative refractive indexes, in order to control these unwanted reflections. In one aspect, the present invention is directed to LCFs comprising materials that have small differences in refractive index, such as between 0.005 and 0.1, and small interface wall angles, such as not greater than 3° , or between 0.1° and 3° .

5 In some cases, light absorbing materials for the light absorbing regions in LCFs can be any suitable material that functions to absorb or block light at least in a portion of the visible spectrum. In some cases, the light absorbing material can be coated or otherwise provided in grooves or indentations in a light transmissive film to form light absorbing regions. In some cases, light absorbing materials can include a black colorant, such as carbon black. In one
10 embodiment, the carbon black can be a particulate carbon black having a particle size less than 10 microns, for example 1 micron or less. In one embodiment the carbon black can have a mean particle size of less than 1 micron. In some cases, carbon black, another pigment or dye, or combinations thereof can be dispersed in a suitable binder. In some cases, light
15 absorbing materials can include particles or other scattering elements that can function to block light from being transmitted through the light absorbing regions.

 In one aspect, the light absorbing region can comprise substantially the same polymerizable resin composition as the light transmissive material. In this embodiment, the refractive index of the light absorbing region material can be no greater than the refractive
20 index of the light transmissive region material. In some cases, the amount of colorant, such as carbon black, is at least about 1 wt-% and no greater than about 10 wt-% of the total light absorbing region material composition. In some cases, from about 2% to about 5% carbon
25 black by weight can be mixed with an absorptive region resin material to sufficiently absorb incident light. The refractive index of carbon black is higher than 1.5, so in some cases, a low refractive index resin can be mixed with the carbon black to maintain a desired refractive index difference between absorptive and transmissive regions.

 Reflections at the light transmissive region/light absorbing region interface can be controlled by mismatching the relative index of refraction of the light transmissive material and the index of refraction of the light absorbing material over at least a portion of the spectrum, for example the human visible spectrum. In some cases, the index of refraction of

the cured transmissive regions (N1) is greater than the index of refraction of the cured light absorptive regions (N2) by at least about 0.005. In some cases, the index of refraction difference, (N1-N2) is not less than 0.005, or, (N1-N2) is greater than or equal to 0.005. In some cases, the difference between the indexes (N1-N2) can be less than 0.1, and can be
5 between 0.007 and 0.06.

In one aspect, the LCF includes a plurality of light absorbing regions. In some embodiments, the light absorbing regions can be a plurality of channels, as shown elsewhere in the description. In some cases, the LCF can include a plurality of columns such as shown in Fig. 2b of U.S. Patent No. 6,398,370 (Chiu et al.). In some cases, the LCF described herein
10 can be combined with a second LCF, as also described in U.S. Patent No. 6,398,370. In other embodiments, the light absorbing regions are columns, posts, pyramids, cones and other structures that can add angular-dependent light transmitting or light blocking capabilities to a film.

The polymerizable resin can comprise a combination of a first and second
15 polymerizable component selected from (meth)acrylate monomers, (meth)acrylate oligomers, and mixtures thereof. As used herein, "monomer" or "oligomer" is any substance that can be converted into a polymer. The term "(meth)acrylate" refers to both acrylate and methacrylate compounds. In some cases, the polymerizable composition can comprise a (meth)acrylated urethane oligomer, (meth)acrylated epoxy oligomer, (meth)acrylated polyester oligomer, a
20 (meth)acrylated phenolic oligomer, a (meth)acrylated acrylic oligomer, and mixtures thereof. The polymerizable resin can be a radiation curable polymeric resin, such as a UV curable resin. In some cases, polymerizable resin compositions useful for the LCF of the present invention can include polymerizable resin compositions such as are described in U.S. Publication No. 2007/0160811 (Gaides et al.), to the extent that those compositions satisfy the
25 index and absorption characteristics herein described.

A microstructure-bearing article (e.g. microstructured film article **200** shown in **FIG. 2**) can be prepared by a method including the steps of (a) preparing a polymerizable composition; (b) depositing the polymerizable composition onto a master negative microstructured molding surface in an amount barely sufficient to fill the cavities of the

master; (c) filling the cavities by moving a bead of the polymerizable composition between a preformed base and the master, at least one of which is flexible; and (d) curing the composition. The deposition temperature can range from ambient temperature to about 180°F (82°C). The master can be metallic, such as nickel, chrome- or nickel-plated copper or brass, or can be a thermoplastic material that is stable under the polymerization conditions, and has a surface energy that allows clean removal of the polymerized material from the master. One or more of the surfaces of the base film can optionally be primed or otherwise be treated to promote adhesion of the optical layer to the base.

The polymerizable resin compositions described herein are suitable for use in the manufacture of other light transmissive and/or microstructured articles including for example brightness enhancing films and the like. The term "microstructure" is used herein as defined and explained in U.S. Pat. No. 4,576,850 (Martens). Microstructures are generally discontinuities such as projections and indentations in the surface of an article that deviate in profile from an average center line drawn through the microstructure such that the sum of the areas embraced by the surface profile above the center line is equal to the sum of the areas below the line, the line being essentially parallel to the nominal surface (bearing the microstructure) of the article. The heights of the deviations will typically be about +/- 0.005 to +/- 750 microns, as measured by an optical or electron microscope, through a representative characteristic length of the surface, e.g., 1-30 cm. The average center line can be plano, concave, convex, aspheric or combinations thereof. Articles where the deviations are of low order, e.g., from +/- 0.005, +/- 0.1 or, +/- 0.05 microns, and the deviations are of infrequent or minimal occurrence, i.e., the surface is free of any significant discontinuities, can be considered to have an essentially "flat" or "smooth" surface. Other articles have deviations are of high-order, e.g., from +/- 0.1 to +/- 750 microns, and attributable to microstructure comprising a plurality of utilitarian discontinuities which are the same or different and spaced apart or contiguous in a random or ordered manner.

The chemical composition and thickness of the base material can depend on the requirements of the product that is being constructed. That is, balancing the needs for strength, clarity, optical retardance, temperature resistance, surface energy, adherence to the

optical layer, among others. In some cases, the thickness of the base layer can be at least about 0.025 millimeters (mm) and can be from about 0.1 mm to about 0.5 mm.

Useful base materials include, for example, styrene-acrylonitrile, cellulose acetate butyrate, cellulose acetate propionate, cellulose triacetate, polyether sulfone, polymethyl methacrylate, polyurethane, polyester, polycarbonate, polyvinyl chloride, polystyrene, polyethylene naphthalate, copolymers or blends based on naphthalene dicarboxylic acids, polyolefin-based material such as cast or orientated films of polyethylene, polypropylene, and polycyclo-olefins, polyimides, and glass. Optionally, the base material can contain mixtures or combinations of these materials. In one case, the base may be multi-layered or may contain a dispersed component suspended or dispersed in a continuous phase.

In one aspect, examples of base materials include polyethylene terephthalate (PET) and polycarbonate (PC). Examples of useful PET films include photograde polyethylene terephthalate, available from DuPont Films of Wilmington, Delaware under the trade designation "Melinex 618". Examples of optical grade polycarbonate films include LEXAN® polycarbonate film 8010, available from GE Polymershapes, Seattle WA., and Panlite 1151, available from Teijin Kasei, Alpharetta GA.

Some base materials can be optically active, and can act as polarizing materials. A number of bases, also referred to herein as films or substrates, are known in the optical product art to be useful as polarizing materials. Polarization of light through a film can be accomplished, for example, by the inclusion of dichroic polarizers in a film material that selectively absorbs passing light. Light polarization can also be achieved by including inorganic materials such as aligned mica chips or by a discontinuous phase dispersed within a continuous film, such as droplets of light modulating liquid crystals dispersed within a continuous film. As an alternative, a film can be prepared from microfine layers of different materials. The polarizing materials within the film can be aligned into a polarizing orientation, for example, by employing methods such as stretching the film, applying electric or magnetic fields, and coating techniques.

Examples of polarizing films include those described in U.S. Pat. Nos. 5,825,543 (Ouderkirk et al.); 5,783,120 (Ouderkirk et al.); 5,882,774 (Jonza et al.); 5,612,820 (Shrenk et

al.) and 5,486,949 (Shrenk et al.). The use of these polarizer films in combination with prismatic brightness enhancement film has been described, for example, in U.S. Pat. Nos. 6,111,696 (Allen et al.) and 5,828,488 (Ouderkirk et al.). Films available commercially are multilayer reflective polarizer films such as Vikuiti™ Dual Brightness Enhancement Film “DBEF”, available from 3M Company.

The base materials listed herein are not exclusive, and as will be appreciated by those of skill in the art, other polarizing and non-polarizing films can also be useful as the base for the optical products of the invention. These base materials can be combined with any number of other films including, for example, polarizing films to form multilayer structures. The thickness of a particular base can also depend on the desired properties of the optical product.

FIG. 6 shows a perspective schematic of a backlit display **600** according to one exemplary aspect the present invention. Backlit display **600** includes an LCF **630** to define a polar viewing cutoff angle Φ_P of light leaving an output surface **690** of LCF **630**. Polar viewing cutoff angle Φ_P includes a polar viewing cutoff half angle Φ_1 and a polar viewing cutoff half angle Φ_2 measured from a normal **680** to light output surface **690**, as described elsewhere. LCF **630** includes transmissive regions **640** and absorptive regions **650** as described elsewhere. Backlit display **600** includes a light source **610** configured to transmit light through LCF **630**, through an image plane **620**, such as an LCD panel, and on to a viewer **695**. The viewing angle at which the brightness is a maximum, can depend on whether the polar viewing cutoff angle is symmetric about normal **680** or is asymmetric, as described elsewhere. In one aspect, the brightness of backlit display **600** can be greatest along normal **680** (referred to as the “axial brightness”), and decrease as the viewing angle is increased. For asymmetric polar viewing cutoff angles, the maximum brightness may not be coincident with normal **680**. Backlit display **600** can also include an optional brightness enhancement film **660** and a reflective polarizer film **670** to further improve the brightness and uniformity of the display. Brightness enhancement film can be a prism film, such as Vikuiti™ Brightness Enhancement Film “BEF” or Thin Brightness Enhancement Film “TBEF”, available from 3M Company. Reflective polarizer film **670** can be a multilayer optical film, such as Vikuiti™ Dual Brightness Enhancement Film “DBEF”, available from

3M Company). Brightness enhancement film **660** and reflective polarizer film **670**, if included, can be positioned as shown in **FIG. 6**.

5 The present invention should not be considered limited to the particular modeling and examples described herein, but rather should be understood to cover all aspects of the invention as fairly set out in the attached claims. Various modifications, equivalent processes, as well as numerous structures to which the present invention can be applicable will be readily apparent to those of skill in the art to which the present invention is directed upon review of the instant specification. The foregoing description can be better understood
10 by consideration of the embodiments shown by the modeling results and examples that follow.

Ray-trace modeling of LCF

15 The performance of the LCF was modeled using an optical raytrace program. The optical raytrace program provides results comparable to public commercial raytrace software, such as TracePro® (available from Lambda Research Corp., Littleton MA), and LightTools® (available from Optical Research Associates, Pasadena CA).

20 The optical properties of BEF and LCF were inputs into the program, and the physical dimensions and structures were input as shown below. The absorption coefficient of the black resin was calibrated with the actual attenuation of light incident at 37° of a carbon-filled black photo-polymerizable mixed acrylate resin (substantially the same as the “high index black resin” presented in as Mixture 3 in **Table 3**). The model corresponded to an arrangement similar to **FIG. 6**, where light source **610** was a lambertian light source, brightness enhancement film **660** was the Vikuiti™ Brightness Enhancement Film BEF-II
25 design, reflective polarizer film **670** was not used, and LCF **630** was configured as shown in **FIG. 4** as LCF **400** (i.e. with 0.1 mm thick polycarbonate cover film **470**, 0.1 mm thick polycarbonate base substrate layer **260**, and 0.025 mm thick adhesive **410**).

Parallel rays at a viewing angle Φ were traced from image plane **620** toward the lambertian light source **610**, and the luminance (brightness) was recorded. The process was

repeated for viewing angles from 0° to 90° to generate each of the plots. The program accounted for the attenuation by reflection and absorption of the initial ray traversing through the materials and interfaces, until it intercepted the source surface. The attenuation provided a factor for multiplying the surface brightness, and resulted in the brightness at the viewing direction of the initial ray. Plots were generated that show the intensity vs. viewing angle in a plane perpendicular to the film surface and along the groove direction (horizontal plane) and in a plane perpendicular to the film surface and perpendicular to the groove direction (vertical plane). The plots shown in **FIGS. 7-9** include data from both viewing directions. The brightness profile in the horizontal plane is labeled “along groove”.

10

Table 1: Model input parameters common to Examples 1-3

Material, property	Value (units)
PC, index	1.583
PC, absorption coefficient	0.005 (1/mm)
Adhesive, index	1.52
Adhesive, absorption coefficient	0
Transmissive region, index	1.54
Transmissive region, absorption coefficient	0.005 (1/mm)
Absorptive region, absorption coefficient	129 (1/mm)
“H”, height of absorptive region	0.146 mm
“L”, land thickness	0.015 mm
“P”, pitch	0.070 mm
Φ_P , polar viewing cutoff angle	60 degrees

Example 1: Model with interface wall angle = 0.1°

15

The interface wall angle input to the model was set to a value of 0.1°. The resulting width “W” was 0.0523 mm to result in the 60° polar viewing cutoff angle. The index of the absorptive region was set equal to the index of the transmissive region, and the brightness was

calculated at several polar viewing angles by the method described elsewhere. The index was decreased by 0.01 and the calculation was repeated until the difference in the indices was 0.1. The brightness values generated the series of plots shown in **FIG. 7** for a 0.1° interface wall angle. As shown in **FIGS. 7 – 9**, the plot corresponding to matched index values was labeled “A”, and the index difference increased by 0.01 increments moving to the right, ending at the index difference 0.1 represented by the plot labeled “K”.

Example 2: Model with interface wall angle = 1.0°

The same procedure as in **Example 1** was used, with the exception that the interface wall angle input to the model was set to a value of 1.0°, and the resulting width “W” was 0.0571 mm to result in the 60° polar viewing cutoff angle. The brightness values generated the series of plots shown in **FIG. 8** for a 1.0° interface wall angle.

Example 3: Model with interface wall angle = 3.0°

The same procedure as in **Example 1** was used, with the exception that the interface wall angle input to the model was set to a value of 3.0°, and the resulting width “W” was 0.0673 mm to result in the 60° polar viewing cutoff angle. The brightness values generated the series of plots shown in **FIG. 9** for a 3.0° interface wall angle.

20 Representative values for Axial Brightness and Brightness at viewing angle Φ

The polar viewing half angle (PVHA) at which the brightness was 70%, 80% and 90% of the axial brightness (AB) was calculated from the modeled data for selected interface angles θ_I and refractive index differences (N1-N2). These values are represented at **Table 2**.

25 Table 2: Polar viewing half angle for selected percentage values of axial brightness

θ_I , degrees	(N1-N2)	AB, (cd/m2)	PVHA at 90% AB, degrees	PVHA at 80% AB, degrees	PVHA at 70% AB, degrees
0.1	0	124.48	3.6	6.7	10.3
0.1	0.05	126.49	22.2	22.6	23

0.1	0.1	126.25	26	30.6	32.3
1.0	0	119.85	4.7	7.8	11.1
1.0	0.05	133.01	21	21.3	21.6
1.0	0.1	132.7	22	27.9	30
3.0	0	109.28	7.2	10.1	13
3.0	0.05	143.99	17.4	18.2	18.5
3.0	0.1	143.72	19.1	22.5	24

Preparation and Evaluation of LCFs using UV curable materials

LCFs were made and evaluated according to the procedures described below. The following list of materials was used, except as otherwise noted. Four mixtures of radiation curable resins used in these embodiments are shown in **Table 3**.

5

- PET (Melinex 618, DuPont Films, Wilmington, DE) – photograde polyethylene terephthalate; chemically primed on one side.
- PC (LEXAN® 8010, GE Polymershapes, Seattle WA) – photograde polycarbonate film
- 10 SR 285 (Sartomer, Exton PA) – tetrahydrofurfuryl acrylate
- SR 351 (Sartomer, Exton PA) – trimethylolpropane triacrylate (TMPTA)
- SR 602 (Sartomer, Exton PA) - bisphenol A diacrylate with about four moles of ethoxylation
- SR 339 (Sartomer, Exton PA) – 2-phenoxyethyl acrylate
- SR 238 (Sartomer, Exton PA) – 1,6-hexanediol diacrylate
- 15 Photomer 6010 (Cognis, Cincinnati OH) – aliphatic urethane diacrylate
- Photomer 6210 (Cognis, Cincinnati OH) - aliphatic urethane diacrylate
- Ebecryl 350 (UCB Chemicals, Smyrna GA) – acrylated silicone
- 9B385 (Penn Color, Doylestown PA) – carbon black UV curable paste
- SR 9003 (Sartomer, Exton PA) – propoxylated(2) neopentyl glycol diacrylate
- 20 TPO (BASF, Florham Park, NJ) - Lucirin® TPO photoinitiator
- Darocur 1173 (Ciba Specialty Chemicals, Tarrytown NY) – photoinitiator
- Irgacure 369 (Ciba Specialty Chemicals, Tarrytown NY) – photoinitiator
- Irgacure 819 (Ciba Specialty Chemicals, Tarrytown NY) – photoinitiator

25

Table 3: UV polymerizable resin mixture compositions

Sample Description	Mixture Compositions (all percentages are by weight)					Refractive Index ^d
	Mixture 1 Low Index	94% Photomer	5% SR-285	1% Darocur	---	

“Clear” Resin	6010		1173			
Mixture 2 ^a High Index “Clear” Resin	45% Photomer 6010	36.7% SR-602	7.1% SR-238	7.1% SR-351	4.1% SR-339	1.512 (1.496)
Mixture 3 ^b High Index “Black” Resin	67% Photomer 6210	20% 9B385	10% SR- 285	---	---	(1.514)
Mixture 4 ^c Low Index “Black” Resin	73% Ebecryl 350	15% 9B385	5% SR- 9003	4.5% SR-285	---	(1.447)

^a Mixture 2 had 0.1% TPO and 0.35% Darocur 1173 photoinitiators added.

^b Mixture 3 had 1% each of Irgacure 369, Irgacure 819, and Darocur 1173 added.

^c Mixture 4 had 1.5% Darocur 1173 and 1% Irgacure 819 added.

5 ^d Calculated refractive index appears in parenthesis, otherwise it was measured

Refractive index determination of cured resins

10 The resins of Mixture 1 and Mixture 2 were separately mixed, and coated between a
0.008 inch (0.20 mm) PC film and an unprimed 0.005 inch PET film using a precision
laboratory drawdown coater (manufactured by ChemInstruments) to a thickness of
approximately 50 μ m. The resulting laminate was cured using UV radiation (1 pass, 25 feet
per minute, one-side exposure with two Fusion D bulbs), and the PET coversheet was
15 removed. The refractive index of the photopolymerized resins were measured using a
Metricon Model 2010 Prism Coupler System (Metricon Corp, Pennington NJ) at a
wavelength of 633 nm. Due to the presence of the carbon black in Mixtures 3 and 4, this
method could not be used for those mixtures.

20 The calculated refractive index of the resins of Mixtures 1 through 4 were each
determined from published refractive index values for each of the individual components at a
wavelength of 512 nm. A linear mixing rule was used. The increase in refractive index due
to the addition of carbon black added, was 0.009 for every 1% carbon black added by weight
to each mixture.

25 Preparation of Microstructured Films

Microstructured films were made by molding and ultraviolet (UV) light curing the compositions of Mixture 1 and Mixture 2 of **Table 3** on either a 0.007 inch (0.178 mm) on primed PET film or a 0.007 inch (0.178 mm) PC film. For these structured films, a cylindrically-shaped metal roll with finely detailed channels cut into its outer surface served as the mold. The resinous mixture was first coated onto either the PET or the PC substrate film, and then pressed firmly against the metal roll in order to completely fill the mold. Upon polymerization the structured film was removed from the mold. The resulting structure in the cured resin was a series of evenly spaced channels, each having a nominally trapezoidal cross-section. The cured resin channels were about 48 microns wide (at their narrowest), about 146 microns deep, and spaced at about a 70 micron pitch. The included wall angle, θ_T , was about 3.6°. **FIG. 2** is representative of such a microstructured film.

Preparation of Light Collimating Films

Light collimating films were made by filling the gaps between the transparent channels of the microstructured film using each of the resin compositions of Mixture 3 and Mixture 4 listed in **Table 3**. Excess black-containing resin was wiped from the surfaces of the transparent channels. The carbon black filled channels were then cured using UV radiation, resulting in a light collimating film similar to that shown in **FIG. 3**. Each light collimating film was laminated to a 0.008 inch (0.20 mm) PC coversheet film using a UV-curable adhesive (UVX4856 available from Toagosei Co. Ltd, Tokyo, Japan). **FIG. 4** is representative of such a light collimating film. The polar viewing cutoff angle Φ_P for this light collimating film was 60°.

Example 4

A microstructured film was made using the “Mixture 1” low index clear resin composition of **Table 3**, on PC film as described above. The microstructured film was then filled with the “Mixture 4” low index black resin composition of **Table 3**, UV cured, and laminated to PC film using the UV curable adhesive and methods described above, to result in a light collimating film.

Example 5

A microstructured film was made using the “Mixture 2” high index clear resin composition of **Table 3**, on PET film as described above. The microstructured film was then filled with the “Mixture 4” low index black resin composition of **Table 3**, UV cured, and laminated to PC film using the UV curable adhesive and method described above, to result in a light collimating film.

Comparative Example #1

A microstructured film was made using the “Mixture 1” low index clear resin composition of **Table 3**, on PC film as described above. The microstructured film was then filled with the “Mixture 3” high index black resin composition of **Table 3**, UV cured, and laminated to PC film using the UV curable adhesive and method described above, to result in a light collimating film.

Luminance Measurements

An Eldim 80 Conoscope (Eldim Corp, France) was used to measure the luminance (brightness) profiles of a backlight incorporating the LCFs of **Example 4**, **Example 5**, and **Comparative Example 1**. A Sharp 7” TFT LCD module (Model # LQ070T5CRQ1, available from Sharp Electronics, Mahwah NJ) was modified to include a sheet of Vikuiti™ Brightness Enhancement Film (BEF III-5T, available from 3M Company). Brightness data were taken with the placement of a light collimating film between the BEF and the rear polarizer of the LCD panel (similar to the construction given at **FIG. 6**). The results from these measurements are shown at Table 4. The axial brightness was the brightness measured perpendicular to the surface of the LCD panel. The polar viewing half angle (PVHA) at which the brightness was 70%, 80% and 90% of the axial brightness (AB) was measured, and the PVHA at which the brightness was 5% of the AB was also measured. The PVHA at 5% of the AB designated a functional polar viewing angle as described elsewhere. A summary of these results are shown at **Table 4**.

Table 4 Axial brightness and polar ½-view angle data of Light Collimating Films

Sample Description	AB (cd / m ²)	PVHA at 90% AB, degrees	PVHA at 80% AB, degrees	PVHA at 70% AB, degrees	PVHA at 5% AB, degrees
Example 4	243	8.0	11.0	13.0	30.0
Example 5	256	8.5	13.5	16.5	32.4
Comparative Example #1	192	4.0	6.5	8.5	29.6

5 The light collimating films of **Example 4** and **Comparative Example 1** differ only in the black resin composition and refractive index. The light collimating film of **Example 5** used a clear resin that was slightly higher in refractive index than the clear resin used in **Example 4**.

10 Unless otherwise indicated, all numbers expressing feature sizes, amounts, and physical properties used in the specification and claims are to be understood as being modified by the term “about.” Accordingly, unless indicated to the contrary, the numerical parameters set forth in the foregoing specification and attached claims are approximations that can vary depending upon the desired properties sought to be obtained by those skilled in the art utilizing the teachings disclosed herein.

15 Although specific embodiments have been illustrated and described herein, it will be appreciated by those of ordinary skill in the art that a variety of alternate and/or equivalent implementations can be substituted for the specific embodiments shown and described without departing from the scope of the present disclosure. This application is intended to cover any adaptations or variations of the specific embodiments discussed herein. Therefore, 20 it is intended that this disclosure be limited only by the claims and the equivalents thereof.

What is claimed is:

1. A light control film, comprising:

5 a light input surface and a light output surface opposite the light input surface;

alternating transmissive and absorptive regions disposed between the light input surface and the light output surface, each transmissive region having an index of refraction N_1 , and each absorptive region having an index of refraction N_2 , where $N_1 - N_2$ is not less than 0.005;

10 a first interface between a transmissive region and an adjacent absorptive region; and

an interface angle θ_1 defined by the first interface and a direction perpendicular to the light output surface, where θ_1 is not greater than 3 degrees.

15 2. The light control film of claim 1, wherein light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at greater than 80% of the maximum brightness measured at any angle less than 10 degrees from the direction perpendicular to the light output surface.

25 3. The light control film of claim 1, wherein light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at greater than 80% of the maximum brightness measured at any angle less than 20 degrees from the direction perpendicular to the light output surface.

4. The light control film of claim 1, wherein light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light

output surface, and exits the light output surface at greater than 90% of the maximum brightness measured at any angle less than 10 degrees from the direction perpendicular to the light output surface.

5 5. The light control film of claim 1, wherein light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at greater than 90% of the maximum brightness measured at any angle less than 20 degrees from the direction perpendicular to the light output surface.

10

6. The light control film of claim 1, further comprising a polar viewing cutoff angle, and wherein light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at less than 10% of the maximum brightness measured at any angle greater than the polar viewing cutoff angle.

15

7. The light control film of claim 6, wherein light incident to the light input surface exits the light output surface with a maximum brightness in a direction perpendicular to the light output surface, and exits the light output surface at less than 5% of the maximum brightness measured at any angle greater than the polar viewing cutoff angle.

20

8. The light control film of claim 1, wherein N_1-N_2 is less than 0.1.

9. The light control film of claim 1, wherein N_1-N_2 is between 0.007 and 0.06.

25

10. The light control film of claim 1, wherein each absorptive region comprises an optically absorptive material selected from a pigment, a dye, or a combination thereof.

11. The light control film of claim 10, wherein the optically absorptive material is a carbon black pigment.

12. The light control film of claim 1, wherein each of the transmissive and absorptive regions comprise a radiation cured (meth)acrylate polymer.

13. The light control film of claim 1, wherein the transmissive region has a second interface with a second adjacent absorptive region, and an interface angle θ_2 defined by the second interface and a direction perpendicular to the light output surface, where θ_2 is not greater than 3 degrees.

14. A collimated lighting assembly, comprising:

a light control film, comprising:

a light input surface;

transmissive and absorptive regions, the transmissive region having

an index of refraction N_1 , and the absorptive region having an

index of refraction N_2 , where $N_1 - N_2$ is not less than 0.005,

wherein a first interface between the transmissive region and the

absorptive region makes an angle not greater than 3 degrees

with a direction perpendicular to the input surface; and

a light source emitting light toward the light input surface.

15. The collimated lighting assembly of claim 14, further comprising a prismatic film disposed between the light source and the light control film.

16. The collimated lighting assembly of claim 14, further comprising a reflective polarizer disposed between the light source and the light control film.

17. The collimated lighting assembly of claim 16, wherein the reflective polarizer is laminated to the light control film.

5 18. The collimated lighting assembly of claim 16, further comprising a prismatic film disposed between the light source and the reflective polarizer.

19. The light control film of claim 14, wherein the transmissive region has a second interface with a second absorptive region, and the second interface makes an angle of not greater than 3 degrees with the direction perpendicular to the input surface.

10

20. A liquid crystal display, comprising:

a light control film, comprising:

alternating transmissive and absorptive regions disposed laterally

15

within a plane defined by a light input surface and a light output surface opposite the light input surface, an index of refraction of each absorptive region being less than an index of refraction of each transmissive region by at least 0.005;

a first interface between a transmissive region and a first adjacent absorptive region defining an interface angle θ_1 measured from a direction perpendicular to the plane of the film, wherein θ_1 is not greater than 3 degrees;

20

a light source emitting light toward the light input surface; and

a liquid crystal display module receiving light from the light output surface

25

21. The liquid crystal display of claim 20, further comprising a prismatic film disposed between the light source and the light control film.

22. The liquid crystal display of claim 20, further comprising a reflective polarizer disposed between the light source and the light control film.
23. The liquid crystal display of claim 22, wherein the reflective polarizer is laminated to
5 the light control film.
24. The liquid crystal display of claim 22, further comprising a prismatic film disposed between the light source and the reflective polarizer.
- 10 25. The light control film of claim 20, wherein the transmissive region has a second interface with a second adjacent absorptive region, and an interface angle θ_2 defined by the second interface and a direction perpendicular to the light output surface, where θ_2 is not greater than 3 degrees.




Fig. 1




Fig. 2




Fig. 3




Fig. 4

3/6




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

A. CLASSIFICATION OF SUBJECT MATTER**G02B 5/02(2006.01)i, G02B 5/30(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 8 G02B 5/02

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models since 1975

Japanese Utility models and applications for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKIPASS (KIPO internal) "light control film"

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6,398,370 B1 (RAYMOND C. CHIU et al.) 04 June 2002 See the abstract, figures 1-4	1-25
A	US 2007/0160811 A1 (GARY E. GAIDES et al.) 12 July 2007 See the abstract, figures 1-3	1-25
A	US 5,828,488 A (ANDREW J. OUDERKIRK et al.) 27 October 1998 See the abstract	1-25

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

31 DECEMBER 2008 (31.12.2008)

Date of mailing of the international search report

31 DECEMBER 2008 (31.12.2008)

Name and mailing address of the ISA/KR

Korean Intellectual Property Office
Government Complex-Daejeon, 139 Seonsa-ro, Seo-
gu, Daejeon 302-701, Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

JEONG, So Yeon

Telephone No. 82-42-481-5656



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2008/079725

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6398370 B1	04.06.2002	AU 2001-45422 A1	27.05.2002
		CN 1208668 C	29.06.2005
		EP 1334382 A1	13.08.2003
		JP 2004-514167 A	13.05.2004
		KR 10-2003-0048148 A	18.06.2003
		WO 02-41048 A1	23.05.2002
US 2007/0160811 A1	None		
US 5828488 A	27.10.1998	AU 1443595 A	10.07.1995
		AU 712765 B2	18.11.1999
		BR 9510517 A	30.03.1999
		CA 2177714 C	09.08.2005
		CN 1052795 C	24.05.2000
		DE 69423651 D1	27.04.2000
		EP 0735952 B1	22.03.2000
		IL 11 2101 D0	15.03.1995
		JP 3709402 B2	26.10.2005
		KR 10-1998-0700173	30.03.1998
		US 2006-262400 A1	23.11.2006
		US 2006-286396 A1	21.12.2006
		US 2007-0091230 A1	26.04.2007
		US 2007-0121034 A1	31.05.2007
		US 2007-091230 A1	26.04.2007
		US 2007-121034 A1	31.05.2007
		US 5828488 A	27.10.1998
		US 5882774 A	16.03.1999
		US 5962114 A	05.10.1999
		US 5965247 A	12.10.1999
		US 6025897 A	15.02.2000
		US 6096375 A	01.08.2000
		US 6117530 A	12.09.2000
		US 6296927 B1	02.10.2001
		US 6543153 B1	08.04.2003
		US 6613421 B2	02.09.2003
		US 6635337 B2	21.10.2003
		US 6804058 B1	12.10.2004
		US 6888675 B2	03.05.2005
		US 7038745 B2	02.05.2006
		US 7083847 B2	01.08.2006
		WO 95-17303 A1	29.06.1995
WO 95-17692 A1	29.06.1995		
WO 96-19347 A2	27.06.1996		
WO 96-19347 A3	29.08.1996		