

(51) International Patent Classification:
A61N 1/04 (2006.01)(21) International Application Number:
PCT/US2013/073247(22) International Filing Date:
5 December 2013 (05.12.2013)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/733,736 5 December 2012 (05.12.2012) US
61/734,150 6 December 2012 (06.12.2012) US(71) Applicant: **BATTELLE MEMORIAL INSTITUTE**
[US/US]; 505 King Avenue, Columbus, Ohio 43201 (US).(72) Inventors: **BOUTON, Chad, E.**; 7540 Polo Lane, Powell,
Ohio 43065 (US). **FRIEND, Jeffrey**; 505 King Avenue,
Columbus, Ohio 43201 (US).(74) Agent: **KLEIN, Richard, M.**; Fay Sharpe LLP, 1228 Euclid
Avenue, 5th Floor, Cleveland, Ohio 44115 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,
ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CL, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).**Published:**— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: NEUROMUSCULAR STIMULATION CUFF




FIG. 4

(57) Abstract: The present disclosure describes systems, methods, devices for performing thought-controlled neuromuscular stimulation. Also described are methods for producing a neuromuscular stimulation cuff. The systems and methods generally relate to receiving and processing thought signals indicative of an intended action, and then delivering stimulation to effectuate the intended action through a neuromuscular stimulation cuff. The neuromuscular stimulation cuff includes a flexible printed circuit board having at least one finger and a plurality of electrogel discs disposed on the at least one finger. The neuromuscular stimulation cuff may be produced by providing a layer of polyimide, etching a conductive copper circuit including a plurality of electrodes into the layer of polyimide to form an etched circuit layer, adhering a cover layer onto the etched circuit layer to form a flexible printed circuit board (PCB), and cutting at least one finger from the flexible PCB. The neuromuscular stimulation cuff employs a flexible multi-electrode design which allows for reanimation of complex muscle movements

in a patient, including individual finger movement.

NEUROMUSCULAR STIMULATION CUFF

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to U.S. Provisional Patent Application Serial No. 61/733,736, filed on December 5, 2012, and to U.S. Provisional Patent Application Serial No. 61/734,150, filed on December 6, 2012, which are incorporated herein by reference in its entirety.

BACKGROUND

[0002] The present disclosure relates to systems, methods, and devices for thought-controlled neuromuscular stimulation. Generally, the system may be used to receive thought signals indicative of an intended action and provide electrical stimulation to a damaged or degenerated neuromuscular region to effectuate the intended action. Methods to produce a flexible neuromuscular stimulation cuff are also disclosed. The device may be a neuromuscular stimulation cuff which delivers stimulation to restore movement to parts of the body not under volitional control due to damaged or degenerated neural pathways from spinal cord injury, stroke, nerve damage, motor neural disease, and other conditions or injuries. The system can also be used in a patient that has some local neural or muscle degeneration for therapeutic or rehabilitation purposes.

[0003] Subcutaneous implantable neurostimulation cuffs have been commonly used to block pain and to restore function to damaged or degenerative neural pathways. These implantable cuffs are wrapped around a target nerve and generally include one or more electrodes arranged to stimulate the nerve. By including more than one electrode and/or a different geometry of electrodes, implantable cuffs such as the flat interface nerve electrode (FINE) have been able to achieve stimulation selectivity at the level of individual nerve vesicles.

[0004] Transcutaneous neurostimulation cuffs behave similarly to implantable cuffs, however there are important differences. Because the electrodes are placed against the skin, rather than through it, stimulation is preferably performed on skeletal muscle tissue or muscle groups, rather than peripheral nerves located deeper under the skin. Muscular stimulation may be preferable to stimulating major peripheral nerves, e.g.

ulnar, median, radial nerves, as stimulating these nerves may cause a patient to feel a tingling sensation. By increasing the number and layout of electrodes in a neuromuscular cuff, similar to the direction taken with implanted nerve cuff designs, current generation neuromuscular stimulation cuffs have been able to selectively stimulate individual muscles or muscle groups.

[0005] Flexible transcutaneous cuffs have been developed which fit around a human appendage such as a forearm to control the wrist or fingers. These flexible cuffs may include sensors which record muscle activity, or EMG signals, and stimulate in response to the EMG signals. Thin film technologies have also become important in the development of functional electrostimulation (FES) devices. Devices incorporating thin film technology are often based on a polyimide substrate covered by a chromium, gold, or platinum film.

[0006] Current neuromuscular cuffs present many limitations, for example, their inability to receive a stimulation signal which is directly processed from thought signals. These neuromuscular cuffs are also not flexibly positioned over multiple stimulation points. Flexible electrode positioning is desirable when attempting to restore complex muscular movements through neuromuscular stimulation. Current neuromuscular cuffs are also incapable of accommodating a wide range of patient appendage geometries, e.g. varying circumferences, while also staying well adhered to the skin.

[0007] An effective wireless system for transmitting human brain signals directly to muscles, and thereby enabling movement through thought-control, has not yet been developed. Neuromuscular stimulation cuffs for such a system, e.g. which receive an input consisting of encoded "thought" signals and provide stimulation to muscular regions according to the signals, have also not been developed.

BRIEF DESCRIPTION

[0008] The present disclosure relates to systems, methods, and devices for thought-controlled neuromuscular stimulation. Included is a neuromuscular stimulation cuff which receives a thought signal indicative of an intended action, and in response, stimulates a damaged neuromuscular region to effectuate the intended action. The neuromuscular cuff may include a flexible design, e.g., including a plurality of electrodes

arranged on flexible fingers across a single conductive layer. The flexible fingers allow for variable sized neuromuscular regions, e.g. paralyzed limbs, to fit within the neuromuscular cuff. The fingers may also allow for increased electrode positioning choices for reanimation of complex muscle movements. The neuromuscular cuff may further include an array of electrogel discs which provide enhanced electrical contact as well as keep cuff adhered to the skin during stimulation-induced movement.

[0009] In some embodiments, a system for thought-controlled neuromuscular stimulation includes a sensor for monitoring or recording neural signals from a patient, a neural signal processor for receiving the neural signals and processing the neural signals into a re-encoded signal, and a neuromuscular stimulation cuff for delivering stimulation to the patient according to the re-encoded signal.

[0010] In other embodiments, a method for thought-controlled neuromuscular stimulation includes receiving neurological signals from a patient indicative of an intended action, processing neurological signals, generating a re-encoded signal, and delivering neuromuscular stimulation to the patient according to the re-encoded signal to effectuate the intended action.

[0011] In yet other embodiments, a device for neuromuscular stimulation includes a flexible printed circuit board having at least one finger and a plurality of electrogel discs disposed on the at least one finger.

[0012] In additional different embodiments, a method for producing a neuromuscular cuff includes providing a layer of polyimide, etching a conductive copper circuit including a plurality of electrodes into the layer of polyimide to form an etched circuit layer, adhering a cover layer onto the etched circuit layer to form a flexible printed circuit board (PCB), and cutting at least one finger from the flexible PCB.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] The following is a brief description of the drawings, which are presented for the purposes of illustrating the exemplary embodiments disclosed herein and not for the purposes of limiting the same.

[0014] **FIG. 1** is an overview diagram of one embodiment of a system for thought-controlled neuromuscular stimulation.

[0015] FIG. 2 is a block diagram for the decoding and re-encoding architecture operating within the system of FIG. 1.

[0016] FIG. 3 is a flow diagram for one embodiment of a method for providing thought-controlled neuromuscular stimulation.

[0017] FIG. 4 is a perspective drawing of a neuromuscular stimulation cuff device according to an exemplary embodiment, shown in place on a human arm.

[0018] FIG. 5 is a diagram for a concept design for fabricating one embodiment of the neuromuscular stimulation cuff device.

[0019] FIG. 6 is a diagram for an etched circuit layer for fabricating one embodiment of the neuromuscular stimulation cuff device.

[0020] FIG. 7 is a close-up view diagram of the etched circuit layer of FIG. 6.

[0021] FIG. 8 is an alternative close-up view diagram of the etched circuit layer of FIG. 6.

[0022] FIG. 9 is a diagram for a coverlay layer used in fabricating one embodiment of the neuromuscular stimulation cuff device.

[0023] FIG. 10 is a diagram for a silkscreen layer used in fabricating one embodiment of the neuromuscular stimulation cuff device.

[0024] FIG. 11 is a stack-up diagram used in fabricating one embodiment of the neuromuscular stimulation cuff device.

[0025] FIG. 12 is a flow diagram for one embodiment of a method for producing a neuromuscular cuff.

[0026] FIG. 13 is an exemplary photograph showing individual finger movement within a system for thought-controlled neuromuscular stimulation.

[0027] FIG. 14 is an exemplary photograph showing two neuromuscular cuff devices according to one embodiment disposed on a preparation bench.

[0028] FIG. 15 is an exemplary photograph showing two neuromuscular cuff devices according to the embodiment of FIG. 14.

[0029] FIG. 16 is an exemplary photograph showing two neuromuscular cuff devices according to a different embodiment.

[0030] FIG. 17 is an exemplary photograph showing a rigidizer and the primary side of a neuromuscular cuff device according to yet another embodiment.

[0031] FIG. 18 is an exemplary photograph showing the positioning of a patient's arm region over two neuromuscular cuff devices according to the embodiment of FIG. 14.

[0032] FIG. 19 is an exemplary photograph showing two neuromuscular cuff devices according to the embodiment of FIG. 14 which are wrapped around a patient's arm region in preparation for neuromuscular stimulation.

[0033] FIG. 20 is an exemplary photograph showing two neuromuscular cuff devices according to the embodiment of FIG. 14 which are alternatively wrapped around a patient's arm region in preparation for neuromuscular stimulation.

DETAILED DESCRIPTION

[0034] A more complete understanding of the processes and apparatuses disclosed herein can be obtained by reference to the accompanying drawings. These figures are merely schematic representations based on convenience and the ease of demonstrating the existing art and/or the present development, and are, therefore, not intended to indicate relative size and dimensions of the assemblies or components thereof.

[0035] Although specific terms are used in the following description for the sake of clarity, these terms are intended to refer only to the particular structure of the embodiments selected for illustration in the drawings, and are not intended to define or limit the scope of the disclosure. In the drawings and the following description below, it is to be understood that like numeric designations refer to components of like function.

[0036] With reference to FIG. 1 and FIG. 2, a system for thought-controlled neuromuscular stimulation may include a cortical implant 102 implanted into the cerebral cortex region of the brain. The cortical implant 102 in one embodiment includes a microelectrode sensing array, as depicted in FIG. 1. The microelectrode sensing array includes multiple channels (e.g. 96 channels) and may be wired to an amplifier which further amplifies signals received by the microelectrode array. The cortical implant 102 records "brain waves," more particularly neural signals which are representative of a varied set of mental activities. Neural signals include electrical signals produced by neural activity in the nervous system including action potentials,

multi-unit activity, local field potential, ECoG, and EEG. These neural signals are sent wirelessly or, alternatively, through a wired connection, from the cortical implant **102** to a receiver on a neural signal processor device **104** for processing of the neural signals. In another embodiment, a scalp based interface, headset, or other sensor **102** picks up electroencephalogram (EEG) signals and sends them to the receiver on the neural signal processor device **104**.

[0037] The neural signal processor **104** may include a processor including neural decoding algorithms **106** and/or control algorithms **108**. These algorithms **106**, **108** allow for a received neural signal input to be decoded and subsequently re-encoded for use in neuromuscular stimulation. For example, a received neural signal may be isolated to predict arm and/or hand movements a patient is thinking about. The neural signal processor **104** may also include an oscilloscope or other signal waveform viewing and/or manipulation device. The neural signal processor also preferably includes an isolated pulse stimulator **111** which receives a processed signal and generates a pulse signal for use in neuromuscular stimulation by an attached neuromuscular stimulation cuff **110**.

[0038] With reference to **FIG. 2**, the system for thought control at a more complex architectural level includes the cortical implant or sensor **102** and the neural signal processor **104** which allow for the recording of neural signals and the initial processing of the signals, respectively. Initial signal processing may include analog to digital conversion, normalization, and/or other filtering and processing methods known by one having ordinary skill in the art. Initially processed signals are then decoded by the neural decoding algorithms **106**. In exemplary embodiments, the neural decoding algorithms **106** include force-based algorithms with firing-rate estimators.

[0039] The decoded signal output of the neural decoding algorithms **106** is further processed by the stimulation control algorithms **108**. In exemplary embodiments, the stimulation control algorithms **108** produce an output of peak current amplitude modulated, pulse width modulated, or frequency modulated pulse trains going to the cuff electrodes. The pulse train can also be a non-stationary Poisson type train where average pulse rate (frequency) is modulated. This may help reduce muscle fatigue as it more closely matches to the body's natural nervous system. An example of using

poisson-distributed impulse trains to characterize neurons in a region of the brain is disclosed in Pienkowski et al., Wiener-Volterra Characterization of Neurons in Primary Auditory Cortex Using Poisson-Distributed Impulse Train Inputs, J. Neurophysiology (March 2009). Stimulation control algorithms **108** may be altered through input received from a training profile **107**. The training profile **107** may include training profile data representative of past user training sessions, e.g. motion demonstrations or coaching periods. Training data may be used to alter and/or define stimulation control algorithms **108** during signal processing. Incorporating training data into stimulation control algorithms **108** through a model-based approach yields more accurate decoding, e.g. patient thoughts accurately translated into a complex motion, than prior position-based decoding efforts have shown. Additionally or alternatively, wrist-hand position feedback **109** may be used to alter and/or define stimulation control algorithms **108** during signal processing.

[0040] Signal control algorithm **108** output may be sent to the isolated pulse generator **111**, where the signal is converted into a waveform that is suitable for neurostimulation. Suitable waveforms may include monophasic and biphasic pulses with a voltage between 80 to 300 Volts. However, even higher voltages may be used as long as safe current levels are maintained and proper insulation is used. In exemplary embodiments, the waveform is a monophasic pulse with a peak current of 0-20 mA which is modulated to vary strength of muscle contraction, frequency of 50 Hz, and a pulse width duration of 500 ms. The output of the isolated pulse generator **111** is sent to the neuromuscular stimulation cuff **110** to deliver functional electrostimulation to the patient.

[0041] With reference to the flow diagram set forth in **FIG. 3**, a method for providing thought-controlled neuromuscular stimulation **S100** starts at **S101**. At **S102** neurological signals are received from a patient indicative of an intended action. For example, neurological signals may be received through cortical implant **102**. At **S104** the neurological signals are processed, which may include analog to digital conversion or filtering. At **S106**, the digitized signals are decoded by at least one neural decoding algorithm **106**. At **S108**, the decoded signals are processed by at least one stimulation control algorithm **108**. At **S110**, the method alternatively includes altering the

stimulation control algorithms **108** by training data which is stored in the training profile **107**. At **S112**, the method alternatively includes altering the stimulation control algorithms **108** based on movement data, e.g. wrist-hand position feedback **109**. At **S114**, the output of the at least one signal control algorithm **108** is converted into a re-encoded signal consisting of multiple pulse trains, each pulse train going to a corresponding electrode **114**. At **S114**, neuromuscular stimulation is delivered to the patient by sending the re-encoded signal to the neuromuscular stimulation cuff **110**.

[0042] In another embodiment, the method for providing thought-controlled neuromuscular stimulation **S100** further includes at **S117** delivering neuromuscular stimulation to the patient by selectively delivering stimulation to at least one pair of electrodes **114** within a neuromuscular cuff **110** to effectuate the intended action.

[0043] In yet another embodiment, the method **S100** further includes **S103** recording neurological signals from a patient. These neurological signals may be sensed from, e.g., a forearm or wrist region with neural pathway damage. Recording may also occur at a neurologically intact region such as a functional leg, for which stimulation pulses can be provided for stimulating commonly tied motions in damaged limbs, e.g. arms and legs. Commonly tied motions include hip and arm movements or pivoting movements. In the same embodiment, method **S100** at **S118** may further include delivering neuromuscular stimulation to the patient by selectively stimulating to at least one pair of electrodes within the neuromuscular cuff **110** based on the re-encoded signal.

[0044] With reference to **FIG. 4**, an exemplary embodiment of the neuromuscular stimulation cuff **110** includes a flexible printed circuit board (PCB) **112** upon which electrodes **114** and hydrogel discs **116** are arranged in an electrogel disc array **118**. The neuromuscular stimulation cuff **110** fits over a damaged or degenerative neuromuscular region **120**, e.g. a patient's arm as illustrated. The flexible PCB **112** may be comprised of a single layer of flexible polyimide material. Up to approximately twenty electrodes **114** may be individually etched onto each finger **124** of the flexible PCB **112** as a copper layer. In exemplary embodiments, the flexible PCB **112** has a total of eighty electrodes **114** disposed over four fingers **124**. The electrodes **114** may be subsequently plated with a conductive metal such as gold, palladium, or silver for greater conductivity.

[0045] In some embodiments, electrodes **114** both stimulate a neuromuscular region **120** by stimulating individual muscles and/or groups of muscles, as well as monitor or record skeletal muscle activity, specifically electromyography (EMG) signals. Sensed EMG data pertaining to a sensed muscle target may be used in methods for closed or open loop stimulation of the muscle target. Sensed EMG data may also be analyzed in deciding whether to reposition the neuromuscular stimulation cuff **110** within the neuromuscular region **120** or to turn off individual electrodes **114** within the electrogel disc array **118**.

[0046] Hydrogel discs **116** may be rolled over the electrodes **114** to provide enhanced electrical and mechanical coupling. When appropriately aligned, the hydrogel discs **116** completely cover the electrodes **114** and effectively form conductive electrogel discs **117**. Put another way, the electrodes are located between the base layer and the hydrogel discs. Electrical coupling is enhanced in that hydrogel provides greater conductive contact with the skin than is achievable with a bare metal-plated electrode surface. Additionally, a carrier signal provided to any of the electrogel discs **117** in the electrogel array **118** may conduct through the tissues of a patient and be released at any other electrogel disc **117** provided in the array **118**. Enhanced mechanical coupling is provided through the exemplary adherence characteristics of hydrogel to the skin. Hydrogel discs **116** may stay coupled to the skin even during complex patient movement. The hydrogel discs are commercially available as a tape which may be rolled on an electrode surface. One such example includes AmGel 2550 from AmGel Technologies. In the exemplary embodiment of the neuromuscular cuff shown in **FIG. 4**, the hydrogel discs are provided through custom spaced hydrogel discs located on AmGel 2550 rolled hydrogel tape.

[0047] The electrogel disc array **118** is spread over a plurality of fingers **124**, wherein the fingers **124** are cut from the flexible PCB **112** to provide additional flexibility in the placement of electrogel discs **117**. Reanimation of complex motion may require stimulating muscles which are not located directly along the dimensions of a conventionally shaped neuromuscular cuff **110**. By wrapping fingers **124** around different muscular regions, e.g. the lower wrist and thumb, complex motions such as

thumb movement may be reanimated more effectively than with limited placement options.

[0048] **FIGs. 5-11** are views of various layers of the neuromuscular stimulation cuff, and are separated for convenience and understanding. With reference to **FIG. 5**, one embodiment of the neuromuscular stimulation cuff device **110** may be fabricated in accordance with a concept design **500**. Dimensions of and between the various components of the concept design **500** are indicated in millimeters (mm). The concept design **500** includes, as shown here, a single layer of polyimide base material **522**. In some embodiments, the polyimide base material is a DuPont AP8523E polyimide which is 50 μm (micrometers) thick and rolled-annealed copper clad at 18 μm thick. This base material serves as a substrate for the other layers of the neuromuscular stimulation cuff. The base material **522** is cut into four fingers **524**, where the electrodes will be located. The fingers can be attached to each other, for example by five webbings **525** which run between adjacent fingers. An optional fork **526** of polyimide material is located at one end of the fingers. The fork connects all of the fingers, and is provided for structural support for design and mounting. Drilled holes **527** are provided in the fork **526** for support and/or mounting purposes. In some embodiments, the four drilled holes **527** are approximately 2.387 mm in diameter with a tolerance of ± 0.076 mm. Headers **528** extend from the end of each finger opposite that of the fork. These headers are thinner than the fingers, and connect the fingers **524** to a rigidizer **530**. Though not illustrated, webbings can also be provided between adjacent headers as well if desired. The rigidizer **530** is an inflexible circuit board used for interfacing with the neural signal processor **104**. Drilled holes **531** are additionally located on the rigidizer **530** which represent connector pin insertion points. In exemplary embodiments, eighty drilled holes **531** are approximately 1.016 mm in diameter with a tolerance of ± 0.05 mm.

[0049] With reference to **FIG. 6**, an etched circuit layer **600** for fabricating the neuromuscular stimulation cuff device **110** is shown. The etched circuit layer **600** is located on the surface of the polyimide substrate **622**, upon which copper electrodes **640** and connective copper traces **642** are etched. The electrodes **640** and traces **642** run along the four fingers **624** of the substrate **622**. The traces **642** run longitudinally down the four headers **628** to electrically connect the electrodes **642** to the rigidizer

630. The rigidizer **630** is an inflexible circuit board used for interfacing with the neural signal processor **104**. The traces **642** continue onto rigidizer **630** and end, in this exemplary embodiment, at eighty connective points **632**, which represents twenty connective points **632** per finger **624**. Each of the eighty connective points **632** corresponds to an individual electrode **640**, electrically connected through an individual trace **642**.

[0050] FIG. 7 is a closer view of the etched circuit layer **600** of FIG. 6. The substrate **622**, electrodes **640**, and traces **642** are more particularly seen here. Each electrode **640** is individually connected to a single trace **642**, and the trace **642** runs down header **628** to the rigidizer **630** (not shown). In some embodiments, the traces **642** are approximately 0.127 mm in width. As illustrated here, each electrode **640** includes at least one ear **641** which is used to support the electrode **640** upon the substrate **622**. As seen here, each electrode includes a central area **643** and three ears **641**. The central area has a circular shape, and is used as an electrical contact. Each ear extends beyond the perimeter of the central area. As illustrated here, two ears are separated by 60 degrees, and are separated from the third ear by 150 degrees.

[0051] Referring to FIG. 8, the etched circuit layer illustrated in FIG. 6 may include electrodes **640** that are approximately 12 mm in diameter (not counting the ear) and spaced 15 mm apart. This 15 mm spacing between electrodes would dictate the custom spacing required for subsequent application of hydrogel discs **114**.

[0052] FIG. 9 illustrates a coverlay layer **700** which would be placed over the electrodes and traces. The coverlay layer can be made from a single layer of polyimide **722**, which is preferably thinner than the substrate upon which the electrodes and traces are copper-etched. In one embodiment, the coverlay layer is a DuPont LF0110 polyimide material which is a 25 μ m thick coverfilm. A further thickness of 25 μ m of acrylic adhesive can be used for adhering the coverlay layer **700** to the etched circuit layer **600**. The coverlay layer includes a fork **726**, fingers **724**, headers **728**, and rigidizer section **730** which corresponds to these areas on the base substrate **522** and the etched circuit layer **600**. Cutouts **740** are left in the fingers to expose the central area of the electrodes, and on the rigidizer section **730** for the electrical connectors.

[0053] The coverlay layer **700**, when applied over the etched circuit layer **600**, covers the copper traces **642** etched on the fingers **724** and the headers **728**. The coverlay layer **700** does not cover the central area **643** of the electrodes, but does cover the ears **641**, thus fixing the electrodes in place between the substrate and the coverlay layer. In addition, the electrical connectors in the rigidizer section **730** will remain uncovered. The exposed central area of the electrodes **640** are preferably plated with a conductive metal such as tin, platinum, or gold. In one embodiment, exposed copper electrodes are plated with electroless-nickel-immersion-gold (ENIG) at the level of 3-8 ul gold over 100-150 ul nickel.

[0054] **FIG. 10** is a diagram for a silkscreen layer **800** that can be used in fabricating the neuromuscular stimulation cuff device **110**. The silkscreen layer **800** is applied to the combination of the etched circuit layer **600** and coverlay layer **700** to identify individual electronic elements. A first silkscreen identification number **850** is provided to each electrode **840** so that it may be more easily found after visual inspection. In one embodiment, first silkscreen identification numbers **850** span from A1-A20 and D1-D20 to represent eighty individual electrodes **840**. A second silkscreen identification number **852** identifies the connection ports for a rigidizer **830**. In one embodiment, second silkscreen identification numbers **852** span from J1-J4. Both first and second silkscreen identification numbers **850**, **852** are provided on a secondary side of the neuromuscular stimulation cuff **110**, or side facing away from exposed electrodes **740**. In an exemplary embodiment, silkscreen identification numbers **850**, **852** are provided by white epoxy nonconductive ink.

[0055] Referring now to **FIG. 11**, various embodiments of the neuromuscular stimulation cuff device may be fabricated according to stack-up diagram **900**. A polyimide base material provides a substrate **950** upon which various components are fixed. A secondary side rigidizer **830** is laminated to a secondary surface of the substrate **950**. The etched circuit layer **600** is fabricated onto a primary surface of the substrate (opposite the secondary surface), and includes electrodes and traces. The coverlay layer **700** is subsequently adhered to the etched circuit layer **600** which covers the traces and leaves exposed portions of the electrodes. The combination of the substrate **950**, etched circuit layer **600**, and coverlay layer **700** is defined as the flexible

PCB **912**. Primary rigidizer **730** is stacked upon the coverlay layer to complete the electrical connection required to interface the flexible PCB with the neural signal processor **104**.

[0056] With reference to the flow diagram set forth in **FIG. 12**, one embodiment of a method for producing a neuromuscular cuff **S200** starts at **S201**. At **S202** a single layer of polyimide base material **950** is provided. At **S204**, an etched circuit layer is fabricated onto the polyimide base material **950** by etching a conductive copper circuit into the polyimide. At **S206** a polyimide coverlay layer **700** is adhered to the etched circuit layer **600**. Adhering the coverlay layer **700** to the etched circuit layer **600** completes the formation of the flexible PCB **912**. At **S208**, a plurality of fingers **724** may optionally be cut from the flexible PCB **912** to provide additional contact points for stimulation of muscles or sensing EMG signals. At **S210**, finger webbings **725** may optionally be cut from the flexible PCB **912** to separate the fingers **724** and provide additional flexibility, such as to accommodate limb twisting (such as the forearm) while maintaining contact. At **S212**, hydrogel may optionally be rolled over fingers **724** to with electrodes create electrogel discs **117**. At **S214**, a rigidizer **630**, **730**, **830** is attached to the flexible PCB **912** for interfacing with the neural signal processor **104**. At **S216**, the flexible PCB **912** is interfaced with the neural signal processor **104**.

[0057] With reference to **FIG. 13**, individual finger movement within a system for thought-controlled neuromuscular stimulation **1000** is demonstrated. A neuromuscular cuff **1010** according to one embodiment is wrapped over a damaged or degenerative neuromuscular region **1020**. The neuromuscular cuff **1010** is interfaced with a neurological signal processor **1004** through attached rigidizer **1030**. The rigidizer is attached to a connection port **1005** on the neural signal processor **1004**. Received neurological signals indicative of patient thinking about moving their first two digits has been decoded and re-encoded into pulse train signals transmitted to various electrodes on the neuromuscular stimulation cuff **1010**. Using a specific number and spacing of electrodes/electrogel discs **1014**, **1017** in neuromuscular stimulation cuff **1010** has allowed for high resolution and non-invasive neuromuscular stimulation which effectuates the intention of the patient.

[0058] Electrogel discs **1017** operate in pairs when reanimating motion. Individual digit movement may be effectuated through the operation of two to three pairs (4 to 6 units) of electrogel discs **1017** which are stimulating in tandem. Selecting particular pairs of electrogel discs **1017** to reanimate motion as indicated by a decoded brain signal is advantageously performed by the neuromuscular stimulation cuff **1010**, as each electrogel disc **1017** is connected to the neurological signal processor **1004** individually along a single traces etched into a conductive layer of flexible polyimide material.

[0059] With reference to **FIG. 14**, two neuromuscular cuff devices **1010** according to one embodiment are disposed on a preparation bench **1070**. The preparation bench **1070** may be used to keep cuff devices **1010** flat and roll hydrogel tape across electrodes **1016**. Properly adhered hydrogel discs **116** (not shown) should fully cover the surface of electrodes **1014**.

[0060] With reference to **FIG. 15**, two neuromuscular cuff devices **1010** according to the embodiment of **FIG. 14** are shown. The cuff devices **1010** each include a fork **1026** for additional support when designing and/or placing the cuff devices **1010** over a damaged or degenerative neuromuscular region (not shown).

[0061] With reference to **FIG. 16**, two neuromuscular cuff devices **1100** according to a different embodiment are shown. A fork **1126** is provided at one end of each cuff for additional design and/or structural support, similar to the fork **626** in **FIG. 6**. Here, a second fork **1127** is also provided located along the headers **1128**. Put another way, the fingers **1126** are bracketed by a fork on each end. The additional fork **1127** provides additional support in combination with fork **1126** for situations when the neuromuscular cuff **1110** must be stretched flat across a surface. Additional fork **1127** can also maintains fingers **1124** within the same damaged or degenerative neuromuscular region **1120** (not shown), which effectively concentrates stimulation and prevents flexibility.

[0062] With reference to **FIG. 17**, the primary side of another embodiment of the neuromuscular cuff **1200** is shown. Hydrogel discs **1216** have been applied to electrodes **1214** (not shown, covered), forming an electrogel disc array **1218**. Two of the four fingers **1224** still include the hydrogel tape before being separated from

hydrogel discs **1216**. Electrogel discs **1217** are not connected to each other within the array **1218** so that the electrogel discs **1217** may be independently stimulated.

[0063] While not exposed to the air, copper traces **1242** are viewable through the polyimide cover layer **700**. A secondary side rigidizer **1230** is shown by folding the primary side over at the headers **1228**. Connectors **1234** on the secondary side rigidizer **1230** allow for the neuromuscular stimulation cuff **1200** to be interfaced with the neural signal processor **104** (not shown). Each pin **1236** within connector **1234** is electrically connected with a single electrogel disc **1217**.

[0064] With reference to **FIG. 18**, a patient's arm including damaged or degenerative neuromuscular region **1020** is placed over two neuromuscular cuff devices **1010** according to the embodiment of **FIG. 14**. Flexible headers **1028** may be used as support while positioning the device **1010** under an arm.

[0065] With reference to **FIG. 19**, two neuromuscular cuff devices **1010** in an exemplary embodiment are wrapped around a patient's arm region **1020** in preparation for neuromuscular stimulation. The two cuff devices **1010** together provide 160 separate electrodes for stimulating finger or wrist movements. Fingers **1024** the neuromuscular cuff to fit around the arm region **1020** at points of varying circumference. Hydrogel discs **1016** (not shown) keep both cuffs **1010** adhered to the arm.

[0066] With reference to **FIG. 20**, two neuromuscular cuff devices **1010** according to the embodiment of **FIG. 14** are alternatively wrapped around a patient's arm region in preparation for neuromuscular stimulation. Only two fingers **1024** of one of the neuromuscular cuff devices **1010** are being utilized in combination with all fingers **1024** on the other cuff device **1010**. More or less electrodes can be used, as shown in **FIG. 20**, depending on the nature of the damage to a patient's neuromuscular region **1020** and the type of movement one wishes to reanimate through neuromuscular stimulation.

[0067] The present disclosure has been described with reference to exemplary embodiments. Obviously, modifications and alterations will occur to others upon reading and understanding the preceding detailed description. It is intended that the present disclosure be construed as including all such modifications and alterations insofar as they come within the scope of the appended claims or the equivalents thereof.

CLAIMS:

1. A device for neuromuscular stimulation (**110**), comprising a flexible printed circuit board (**112**) including at least one finger (**124**) and a plurality of electrogel discs (**117**) disposed on the at least one finger (**124**).
2. The device according to claim 1, wherein the flexible printed circuit board (**912**) includes an etched circuit layer (**600**).
3. The device according to either of claims 1 or 2, wherein the flexible printed circuit board (**912**) includes a polyimide base material (**950**).
4. The device according to any of claims 1-3, wherein the flexible printed circuit board (**912**) includes a coverlay layer (**700**).
5. The device according to any of claims 1-4, wherein the flexible printed circuit board (**112**) includes a plurality of electrogel discs (**117**) disposed on the at least one finger (**124**), wherein each electrogel disc is independently connected to a rigidizer (**830**).
6. The device according to claim 5, wherein the rigidizer (**830**) interfaces with a neural processing device (**104**).
7. The device according to either of claims 1-6, further including a plurality of fingers (**124**), each finger (**124**) of the plurality having a plurality of electrogel discs (**117**).

8. A system (100) for thought-controlled neuromuscular stimulation, comprising:

a sensor (102) for monitoring or recording neural signals from a patient (101);

a neural signal processor (104) for receiving neural signals and processing the neural signals into a re-encoded signal; and

a neuromuscular stimulation cuff (110) for delivering stimulation to the patient (101) according to the re-encoded signal.

9. The system according to claim 8, wherein the neural signal processor (104) decodes the neural signals according to a neural decoding algorithm (106).

10. The system according to either of claims 8 or 9, wherein the neural signal processor (104) re-encodes the neural signals according to a stimulation control algorithm (108).

11. The system according to any of claims 8-10, wherein the stimulation control algorithm (108) is altered by at least one of a training profile (107) and position feedback data (109).

12. The system according to any of claims 8-11, wherein the neural signals are transmitted wirelessly between the sensor (102) and the neural signal processor (104).

13. The system according to any of claims 8-12, wherein the neuromuscular stimulation cuff (110) includes a flexible printed circuit board (112) having a plurality of electrogel discs (117).

14. The system according to any of claims 8-13, wherein the neuromuscular stimulation cuff (110) delivers stimulation capable of reanimating only one finger within a damaged hand region (103).

15. The system according to any of claims 13-14, wherein the neuromuscular stimulation cuff (**110**) includes at least one finger (**124**) for variably positioning the plurality of electrogel discs (**117**).

16. The system according to any of claims 13-15, wherein the neuromuscular stimulation cuff (**110**) includes a plurality of fingers (**124**) for variably positioning the plurality of electrogel discs (**117**).

17. The system according to any of claims 13-16, wherein the plurality of electrogel discs (**117**) records neural signals from a region of neuromuscular damage (**120**).

18. A method (**S100**) for thought-controlled neuromuscular stimulation, includes:

receiving neurological signals from a patient (**101**) indicative of an intended action;

processing the neurological signals;

generating a re-encoded signal; and

delivering neuromuscular stimulation to the patient (**101**) according to the re-encoded signal to effectuate the intended action.

19. The method according to claim 18, wherein the processing neurological signals includes decoding neurological signals with at least one neural decoding algorithm (**106**).

20. The method according to either of claims 18 or 19, wherein the processing neurological signals includes processing the neurological signals with at least one stimulation control algorithm (**108**).

21. The method according to any one of claims 18-20, wherein delivering neuromuscular stimulation to the patient (**101**) further includes altering the position of electrodes (**114**) within a neuromuscular stimulation cuff (**110**) to effectuate the intended action.

22. The method according to any one of claims 18-21, wherein delivering neuromuscular stimulation to the patient (**101**) further includes selectively delivering stimulation to at least one pair of electrodes (**114**) within a neuromuscular stimulation cuff (**110**) to effectuate the intended action.

23. The method according to any one of claims 18-22, further including recording EMG signals from the damaged neuromuscular region (**120**).

24. The method according to any one of claims 18-23, wherein delivering neuromuscular stimulation to the patient (**101**) further includes selectively delivering stimulation to at least one pair of electrodes (**114**) within a neuromuscular stimulation cuff (**110**) based on the re-encoded signal.

25. A method (**S200**) for producing a neuromuscular stimulation cuff (**110**), comprising:

- providing a layer of polyimide (**950**);
- etching a conductive copper circuit including a plurality of electrodes (**114**) into the layer of polyimide (**950**) to form an etched circuit layer (**600**);
- adhering a coverlay layer (**700**) onto the etched circuit layer (**600**) to form a flexible printed circuit board (PCB) (**912**); and
- cutting at least one finger (**124**) from the flexible PCB (**912**).

26. The method according to claim 25, further including plating the plurality of electrodes (**114**) with at least one of gold and nickel.

27. The method according to either of claims 25 or 26, further including coating the plurality of electrodes **(114)** with hydrogel.

28. The method according to any one of claims 25-27, further including rolling hydrogel over the at least one finger **(124)** to produce an electrogel disc array **(118)**.

29. The method according to any one of claims 25-28, further including cutting a plurality of fingers **(124)** from the flexible PCB **(112)**.

30. The method according to any one of claims 25-29, further including cutting a webbing **(525)** between the plurality of fingers **(124)** to increase flexibility.

31. The method according to any one of claims 25-30, further including laminating a rigidizer **(830)** to the flexible PCB **(112)** for interfacing with a neural signal processor **(104)**.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

600

641 643 640 622

642

625

628




FIG. 7

600

640

622




FIG. 8





FIG. 9



900

STACK-UP DIAGRAM




FIG. 11




FIG. 12

1000




FIG. 13

1000




FIG. 14

1000




FIG. 15




FIG. 16




FIG. 17

1000




FIG. 18

1000

1004

1010

1024

1010

1020




FIG. 19

1000




FIG. 20