




US 20050218366A1


(19) **United States**(12) **Patent Application Publication**
Chick(10) **Pub. No.: US 2005/0218366 A1**(43) **Pub. Date: Oct. 6, 2005**(54) **APPARATUS AND METHOD FOR
OPERATING A WATER VALVE**(52) **U.S. Cl. 251/293**(75) **Inventor: Jon Chick, Shelbyville, TN (US)**

Correspondence Address:

JAMES RICHARDS**58 BONING RD****FAYETTEVILLE, TN 37334 (US)**(73) **Assignee: Chick Tool Company, Inc., Shelbyville,
TN**(21) **Appl. No.: 10/816,743**(22) **Filed: Apr. 2, 2004****Publication Classification**(51) **Int. Cl.⁷ F16K 43/00**(57) **ABSTRACT**

A valve wrench comprising a telescoping shaft assembly further comprising an inner shaft and an outer shaft, a handle pivotally attached to a first end of the shaft assembly, and a work coupling element fixed or mounted on a second end. The inner shaft may include a spring loaded button that engages the outer shaft to hold the inner and outer shaft in an operation position or alternatively in a storage position. The handle pivots to form a compact linear assembly in a storage configuration and is shaped conformal to the telescoping shaft to minimize occupied space in the storage configuration. The inner and outer shafts may be constructed from a number of complementary cross section shapes including rectangular, hexagonal, and spline to assist in the transfer of torque from the handle to the valve. A number of alternative valve coupling elements are provided for different valves.








Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8A Fig. 8B




Fig. 8C




Fig. 8D




Fig. 8E




Fig. 9

APPARATUS AND METHOD FOR OPERATING A WATER VALVE

BACKGROUND

[0001] 1. Field of the Invention

[0002] The present invention pertains generally to the field of hand tools, more particularly, to hand tools having an extensible or collapsible handle for use in operating water valves typically associated with water meters.

[0003] 2. Background of the Invention

[0004] The present invention is a wrench particularly adapted for the operation of an underground water valve of the type typically used in conjunction with a water meter for residential water service. Wrenches for water meter valves are known in the art and are typically called: water valve wrenches, water meter wrenches, street keys, water tee wrenches, or water valve keys or other similar terms. A typical water meter wrench comprises a steel shaft and handle with an end, opposite the handle, adapted to turn a lug or tab on the water meter valve to operate the valve. Water meter valves are usually located in access boxes or man holes that present awkward or inconvenient configurations for operation using more common wrenches or pliers. Thus, a water valve wrench is the preferred tool for the professional or homeowner for operating such valves. A water valve wrench, however, is infrequently used by the homeowner or professional, except for a select few in the water department whose sole task is to turn on or off service to customers. Existing water valve wrenches, however are large and take considerable space in a toolbox, tool room or service truck. Since valve wrenches are infrequently used, they are likely to be left back at the shop, leaving the service professional to make do with less appropriate tools. Thus, there is a need for a compact, convenient, and economical water valve wrench that may be carried on a vehicle or kept in a toolbox without occupying excessive space, yet the wrench should be economical enough for the homeowner who has infrequent, but often acute need for such a wrench when a pipe breaks or other service is needed.

BRIEF DESCRIPTION OF THE INVENTION

[0005] The present invention is a valve wrench with a telescoping shaft and foldable handle that enable the wrench to be stored in a compact manner, packing efficiently with related tools and materials used in the industry.

[0006] The valve wrench comprises a telescoping shaft assembly further comprising an inner shaft and an outer shaft, a handle pivotally attached to a first end of the shaft assembly, and a valve coupling element fixed or mounted on a second end. The inner shaft may include a spring loaded button that engages the outer shaft to hold the inner and outer shaft in an operation position or alternatively in a storage position. The handle pivots to form a compact linear assembly in a storage configuration and is shaped conformal to the telescoping shaft to minimize occupied space in the storage configuration. The inner and outer shafts may be constructed from a number of complementary cross section shapes including rectangular, hexagonal, and spline to assist in the transfer of torque from the handle to the valve. A number of alternative valve coupling elements are provided for different valves. A method for using the valve wrench is also disclosed.

[0007] These and further benefits and features of the present invention will be described in detail with reference to exemplary embodiments in accordance with the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] The invention is described with reference to the following drawings. In the drawings, like numbers represent identical or similar components. The first digits of a reference number identify the drawing number wherein the reference first appears.

[0009] FIG. 1 illustrates an exemplary embodiment of a valve wrench shown in the operational configuration;

[0010] FIG. 2 is an exploded view of the embodiment of FIG. 1 showing the various component parts;

[0011] FIG. 3 illustrates the storage configuration of the valve wrench shown in FIG. 1;

[0012] FIG. 4 is a section view of the storage configuration including the locking button as shown in FIG. 3;

[0013] FIG. 5 is a section view of the storage configuration including an alternate locking button arrangement;

[0014] FIG. 6 is an alternative embodiment of the invention wherein the shaft and handle form an L shape;

[0015] FIG. 7 shows a two part handle embodiment of the invention;

[0016] FIG. 8A shows an alternative valve coupling element;

[0017] FIG. 8B shows an alternative valve coupling element;

[0018] FIG. 8C (not part of the invention) shows a typical water meter valve operated by the present invention;

[0019] FIG. 8D is a side view of an alternative work coupling element;

[0020] FIG. 8E is a bottom view of the alternative work coupling element of FIG. 8D; and

[0021] FIG. 9 shows a method for using the valve wrench.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0022] The present invention will now be described more fully in detail with reference to the accompanying drawings, in which the preferred embodiments of the invention are shown. This invention should not, however, be construed as limited to the embodiments set forth herein; rather, they are provided so that this disclosure will be thorough and complete and will fully convey the scope of the invention to those skilled in art. Like numbers refer to like elements throughout.

[0023] FIG. 1 illustrates an exemplary embodiment of a valve wrench 100 shown in the operational configuration. Referring to FIG. 1, the valve wrench 100 comprises a handle 102, a telescoping shaft further comprising an outer shaft 104 and an inner shaft 106, and a work coupling element 108, or more specifically, a valve coupling element 108.

[0024] The valve wrench **100** shown in **FIG. 1** permits operation of a valve located below grade in a utility box or manhole, yet allows the operator to remain above grade in a comfortable standing or kneeling position. The valve wrench **100** collapses to a compact linear bar form factor of nearly half the operating length for efficient storage in a tool box or workshop or among miscellaneous articles carried on a service truck. Further, the construction of the wrench is simple, potentially utilizing component materials in readily available shapes and sizes, thus reducing costs and enabling the valve wrench **100** to find wide application and deployment.

[0025] A full length prior art valve wrench presents storage difficulties and limits storage possibilities. The prior art handle is prone to catching or snagging on other tools or materials and the length prohibits storage in many toolboxes. The telescoping shaft of the present invention, however, enables the valve wrench **100** to fit inside a toolbox for convenient carrying and efficient organization of tools. The folding handle **102** gives the wrench a linear bar form factor that will not get caught under other storage items or tangled with wires, making the storage efficient and trouble free. The same features that facilitate storage for the end user also facilitate inventory storage and minimize shelf space required in the manufacturing and retail operations for the valve wrench **100**, further lowering costs to the consumer and improving availability to the consumer by making the tool more attractive to retail managers.

[0026] In one embodiment, the wrench may be constructed utilizing square bar and square tubular steel in readily available standard sizes, reducing costs and facilitating manufacture. Further, the valve wrench **100** may be easily constructed of heavy material to sustain the rough treatment and deliver the high torque expected of professional tools.

[0027] Due to the unique properties of the invention, the valve wrench **100** of the present invention presents a more rugged form factor than the prior art full length tool. Not only does the folding handle **102** reduce snags that may result in damage to the valve wrench **100**, but the collapsing shaft reduces the exposure and bending moment of a potentially damaging encounter. The smaller wrench profile presents a smaller target, less likely to be in the path of a heavy falling object or other accident. The smaller bending moment results from the shorter length. The bending moment advantage may be further illustrated by an example. The valve wrench **100** may be on the floor with the two ends resting on objects supporting the valve wrench **100** at the ends with nothing supporting the middle. If a 220 lb (100 kg) workman steps on the middle of the tool, the tendency to bend the valve wrench **100** depends on the strength of the valve wrench **100** and the moment arm, i.e., the distance from the workman's foot to the support at the end of the valve wrench **100**. Since the valve wrench **100** of the present invention is roughly half the length (when in storage configuration), the maximum moment arm is also reduced by roughly half, reducing the tendency to bend.

[0028] In a further advantage, since the telescoping shaft is compounded in the storage configuration, the wrench has the compound strength of both shafts available to resist damage; i.e. since the inner shaft **106** is fully retracted inside the outer shaft **104**, both shafts work together to resist

bending. (To fully realize this benefit, the two shafts should fit close enough so that the outer shaft **104** will not be damaged before engaging the inner shaft **106**.) Not only is the bending moment nearly half, the strength is nearly doubled, resulting in a greatly improved resistance to damage.

[0029] In one embodiment, the tool includes a push button locking snap to secure the tool in either the operation or storage configuration and allow changing the configuration without the use of additional tools such as wrenches or screwdrivers.

[0030] Referring again to **FIG. 1**, the handle **102** comprises a length of U shaped channel steel that is pivotally attached to the outer shaft **104** using a bolt **110**. The bolt **110** is tightened snugly to the handle **102**, but clearance is allowed between the handle **102** and outer shaft **104** to allow the handle **102** to pivot freely, permitting the handle **102** to rotate to a position parallel to the outer shaft **104**. A hanger hole **118** is provided in the handle **102** to allow the valve wrench **100** to be hung by a nail or hook in a workshop or storage area. The compact linear shape of the valve wrench **100** allows efficient storage in this manner.

[0031] The inner shaft **106** comprises a square bar dimensioned to slide freely inside the outer shaft **104** in a telescoping manner, yet sufficiently close fitting to receive torque input from the outer shaft **104** without slipping or binding. The inner shaft **106** includes a locking mechanism to hold the position of the inner shaft **106** relative to the outer shaft **104** in both the operation configuration and in the storage configuration. The locking mechanism comprises a spring loaded button **120** located in the inner shaft **106** that locates and locks in one of two holes **112**, **114** provided in the outer shaft **104**. A storage latch hole **112** is provided in the outer shaft **104** for the storage configuration and an operation latch hole **114** is provided for the operation configuration. The button **120** may be depressed with a finger, allowing the inner shaft **106** to slide within the outer shaft **104** to change configurations. When the alternate configuration is reached, the button **120** will snap into place and hold that alternate configuration. In a further embodiment, multiple holes are provided in the outer shaft **104** to allow different operating lengths of the valve wrench **100**.

[0032] As shown in **FIG. 1**, the inner shaft **106** and outer shaft **104** have a square cross section, however, any suitable cross section may be used. It is advantageous to use matching cross sections for the inner surface of the outer shaft **104** and the outer surface of the inner shaft **106** to allow both axial sliding from the operating configuration to the storage configuration, and to transfer torque in the operating configuration. Thus hexagonal, spline, triangular and other cross sections may be used. A round section could be used with a keyway or other torque transfer means, but other sections are preferred. Note also the cross section need not be uniform for the whole length. For example, in the embodiment shown in **FIG. 1**, only a small length of the inner shaft **106** need be square to transfer torque and maintain alignment for the button **120**. The remaining inner shaft **106** length may be round or any other cross section that fits within the outer shaft **104**. Also, the inner shaft **106** need not be solid, but may be tubular to save material and lighten the weight of the valve wrench **100**.

[0033] The valve coupling element **108**, is affixed to the end of the telescoping shaft opposite the handle **102**. In one

embodiment, a V or U shaped section as shown in **FIG. 1** is used to couple to a control tab on a typical water meter valve. The vertex of the V is attached to the telescoping shaft and the open end of the V is used for coupling to the valve.

[0034] In one embodiment, the work coupling element **108** is formed or welded to the inner shaft **106**. Alternatively, the work coupling element **108** is attached with a bolt or setscrew **116**. In a further alternative, the work coupling element **108** is snapped in place with, for example, a spring loaded ball with friction detent to allow changing the work coupling element **108**.

[0035] **FIG. 2** is an exploded view of the embodiment of **FIG. 1** showing the various component parts. The handle **102** is attached to the outer shaft **104** using a bolt **110** and nut **202**. A handle pivot hole **212** for receiving the bolt **110** is placed near the center of the handle **102**. The outer shaft **104** comprises a length of square tubing having a shaft pivot hole **204** through two opposite sides of the tubing for receiving the pivot bolt **110**. Other forms of attachment such as a rivet or hinge may be used. Note that one side of the outer shaft **104** is rounded **214** to allow the handle **102** to fold down on that side. The other side is flat to provide support for the handle **102**. Alternatively both sides may be dimensioned (e.g., rounded **214**) to allow folding of the handle **102**. The inner shaft **106** includes a spring loaded button **120** mechanism comprising a button **120**, a spring **208** and a button recess **210** to receive the button **120** and spring **208**. The button **120** is held in the button recess **210** by crimping or swaging the opening. Alternate methods may be used for holding the button **120**. Alternate locking mechanisms may be used as well, such as a friction detent, collet or other device. The work coupling element **108** is attached to the inner shaft **106** using a setscrew **116** as shown in **FIG. 2**. Alternate attachment methods may be used as have been discussed.

[0036] In an alternative embodiment (not shown), the inner shaft **106** and outer shaft **104** may be reversed, i.e., the inner shaft **106** may be adapted to be attached to the handle **102** and the outer shaft **104** may be adapted to be attached to the work coupling element **108**.

[0037] In a further embodiment (not shown), multiple telescoping sections may be used for the shaft.

[0038] In one embodiment, the handle **102** has a length of 10 inches (25.4 cm), the outer shaft **104** and inner shaft **106** have a length of 16 inches (40.6 cm), the work coupling element **108** adds 2 inches (5 cm). The resulting operating length when extended is 31.5 in (80 cm). The resulting operating length when retracted is 19 inches (48.3 cm). The resulting storage length with handle **102** rotated parallel to body is 22.5 in (57.2 cm). The inner shaft **106** is 0.5 inch (1.27 cm) square. The outer shaft **104** and handle **102** are made from 0.1 inch (0.254 cm) thickness material. These dimensions are only roughly representative of an embodiment suited to water valve operation. The dimensions may be varied to cover a range of field requirements. For example, the length could be increased considerably to allow operation of valves in deep manholes. Likewise the length could be shorter and materials thinner and lighter to fit in a smaller toolbox.

[0039] **FIG. 3** illustrates the storage configuration of the valve wrench **100** shown in **FIG. 1**. Referring to **FIG. 3**, the

handle **102** is folded parallel to the shaft axis and the inner shaft **106** is fully retracted inside the outer shaft **104**, resulting in a clean and linear bar shaped form factor having minimal protrusions subject to damage in a storage situation such as the back of a service truck or in a tool box.

[0040] **FIG. 4** is a section view of the storage configuration including the locking button **120** as indicated in **FIG. 3**; Referring to **FIG. 4**, the U shaped cross section of the handle **102** is seen to wrap conformally, i.e., close to, the outer shaft **104** for best compact form in the storage configuration. The close, but free fitting square cross section inner shaft **106** is located inside the outer shaft **104**.

[0041] The locking button **120** is installed in the button recess **210** in the inner shaft **106**. The locking button **120** is spring loaded to force the button **120** into one of the latching holes **112**, **114** in the outer shaft **104**, thereby locking the inner shaft **106** and outer shaft **104** in a fixed relative position. The button **120** is freely sliding for a distance inside the recess. The opening of the button **120** recess may be swaged **404** slightly to keep the button **120** inside the button recess **210** to prevent loss of the button **120** if the inner shaft **106** and outer shaft **104** become separated.

[0042] **FIG. 5** is a section view of the storage configuration including an alternate locking button **120** arrangement; Referring to **FIG. 5**, the locking button **120** is placed on the open side **502** of the telescoping shaft that is not covered by the handle **102** when the handle **102** is folded in the storage configuration.

[0043] **FIG. 6** is an alternative embodiment of the invention wherein the shaft and handle **102** form an L shape. Referring to **FIG. 6**, the embodiment shown in **FIG. 6** is similar to the embodiment shown in **FIG. 1** except that the handle **102** is attached near the end of the handle **102** rather than near the middle of the handle **102** as in **FIG. 1**. The advantage of the L shape embodiment is that the total length of the storage configuration is reduced because the handle **102** does not protrude beyond the end of the telescoping shaft assembly when the handle **102** is folded down in the storage configuration. A second set of holes **212** may be provided in the handle **102** to allow the valve wrench **100** to be configured in either the T handle **102** configuration as in **FIG. 1** or the L handle **102** configuration as in **FIG. 6** by removing the bolt **110** and re-installing the bolt **110** in the appropriate set of holes.

[0044] **FIG. 7** shows a two part handle **102** embodiment of the invention. Referring to **FIG. 7**, the handle **102** comprises two parts, a first arm **702** and a second arm **704**. Each arm is pivoted on the bolt **110** such that each part of the handle **102** may be folded down to the outer shaft **104** for storage as indicated by the arrows in **FIG. 7**.

[0045] **FIG. 8A** shows an alternative valve coupling element **108**. **FIG. 8A** and **FIG. 8B** are described with reference to **FIG. 8C**. **FIG. 8C** shows an exemplary water valve including a valve body **808** and control tab **810**.

[0046] Referring to **FIG. 8A**, the valve coupling element **108** is shown attached to the end of the inner shaft **106**. The valve coupling element **108** comprises an elliptical or oval body **802** with a rectangular coupling recess **806** for receiving the control tab **810** on the valve. When the valve wrench **100** is positioned such that the valve control tab **810** is inserted into the end of the valve coupling element **108**,

rotation of the valve wrench **100** will be coupled to the valve, enabling adjustment of the valve. The valve coupling element **108** of **FIG. 8A** fully surrounds the valve control tab **810** to prevent the valve coupling element **108** from slipping off of the control tab **810**.

[0047] **FIG. 8B** shows an alternative valve coupling element **108**. Referring to **FIG. 8B**, the valve coupling element **108** is shown attached to the end of the inner shaft **106**. The valve coupling element **108** comprises a rectangular body **804** having a rectangular cross section with a rectangular coupling recess **806** for receiving the tab **810** on the water valve. When the valve wrench **100** is positioned such that the valve control tab **810** is inserted into the end of the valve coupling element **108**, rotation of the valve wrench **100** will be coupled to the valve, enabling adjustment of the valve.

[0048] Further alternative work coupling elements **108** may be utilized in accordance with the teachings of the present invention to adapt to different valves including such valves as gas valves.

[0049] **FIG. 8C** (not part of the invention) shows a typical water meter valve operated by the present invention. **FIG. 8C** shows a valve body **808** with a rectangular control tab **810** for adjusting the flow. The valve wrench **100** of the present invention may be coupled to the control tab **810** to rotate the control tab **810** to control the flow through the valve.

[0050] **FIG. 8D** is a side view of an alternative work coupling element **108**. The work coupling element **108** of **FIG. 8D** comprises a round body **812** connected to the inner shaft **106**, a notch **814** for coupling to a valve, and a recess **816** configured to receive and operate a five sided bolt as is typically used on water meter access covers. Also shown is a lip **818** to allow lifting the access cover by capturing the five sided bolt head under the lip **818** and lifting the access cover.

[0051] **FIG. 8E** is a bottom view of the alternative work coupling element **108** of **FIG. 8D**.

[0052] The operation of the valve wrench **100** will now be described. To operate the wrench, the inner shaft **106** is extended by pressing the locking button **120** and pulling the inner shaft **106** out to full extension. When full length is reached, the button **120** will snap outwardly and engage the extension hole in the outer shaft **104**, locking the tool in the operating configuration. The handle **102** is then unfolded to a perpendicular orientation relative to the shaft. The tool is coupled to the valve tab **810** by inserting the valve tab **810** into the work coupling element **108** portion of the tool whereupon the handle **102** may be rotated to operate the valve. Alternatively, the tool may be operated without extending the inner shaft **106** to full extension length.

[0053] **FIG. 9** shows a method for using the valve wrench **100** of **FIG. 1**. The steps comprise: extending the inner shaft **106**, **902**; unfolding the handle **102**, **904**; coupling the water meter wrench to a water valve **906**; and rotating the water meter wrench to adjust the water valve **908**. The steps of extending the inner shaft **106**, **902** and unfolding the handle **102**, **904** may be performed in any sequence; however, it may be easier to extend the inner shaft **106** **902** while gripping the water meter wrench with the handle **102** folded around the outer shaft **104**. Note that the handle **102** may cover the button **120** in the storage configuration as shown

in **FIG. 3**. If it is desired to operate the button **120** with the handle **102** folded, the button **120** should be located on the side not covered by the handle **102** or an alternate locking method may be utilized.

[0054] Conclusion

[0055] While particular embodiments of the invention have been described, it will be understood, however, that the invention is not limited thereto, since modifications may be made by those skilled in the art, particularly in light of the foregoing teachings. It is, therefore, contemplated by the appended claims to cover any such modifications that incorporate those features or those improvements which embody the spirit and scope, of the present invention.

What is claimed is:

1. A device for operating a valve comprising:
 - a at least one handle pivotally attached to a first shaft,
 - a second shaft slidable in a telescoping arrangement with said first shaft and rotationally coupled to said first shaft; and
 - a valve coupling element attached to said second shaft for coupling rotational motion from said handle to said valve.
2. A device as in claim 1 wherein said handle is attached to said first shaft at the center of the length of said handle.
3. A device as in claim 1 wherein said handle is attached to said first shaft at one end of the length of said handle.
4. A device as in claim 1 wherein said first shaft is the outer shaft and said second shaft is the inner shaft in said telescoping arrangement.
5. A device as in claim 4 wherein at least part of the length of said inner shaft has a cross section forming one of the set including a rectangle, triangle, hexagon, and spline.
6. A device as in claim 5 wherein said rectangle is a square.
7. A device as in claim 1 wherein said valve coupling element is attached to said second shaft by welding.
8. A device as in claim 1 wherein said valve coupling element is removable from said second shaft.
9. A device as in claim 1 wherein said valve coupling element includes a substantially rectangular recess for coupling to a valve.
10. A device as in claim 1 wherein said valve coupling element is V shaped wherein the vertex of said V is attached to said second shaft and the open portion of said V is for coupling to said valve.
11. A device as in claim 1 further including a locking mechanism for locking said first shaft and said second shaft in a fixed relative position.
12. A device as in claim 11 wherein said locking mechanism comprises a spring loaded button located in said second shaft.
13. A method for operating a valve comprising the steps of:
 - 1) providing a valve wrench, said valve wrench comprising a foldable handle coupled to a telescoping shaft, said telescoping shaft having a valve coupling element attached thereto;
 - 2) extending said telescoping shaft;
 - 3) unfolding said handle;

4) coupling said valve wrench to said valve; and

5) rotating said valve wrench to adjust said valve.

14. A method as in claim 13 wherein said valve wrench further includes a locking means configured to lock said

telescoping shaft in at least a storage configuration, the method further including the step of unlocking said telescoping shaft.

* * * * *