



US 20140202476A1

(19) **United States**(12) **Patent Application Publication****Egoyants et al.**(10) **Pub. No.: US 2014/0202476 A1**(43) **Pub. Date: Jul. 24, 2014**(54) **HEATING SMOKEABLE MATERIAL**(30) **Foreign Application Priority Data**

(75) Inventors: **Petr Egoyants**, St. Petersburg (RU);
Dmitry Volobuev, St. Petersburg (RU);
Pavel Fimin, St. Petersburg (RU); **Oleg**
Abramov, St. Petersburg (RU); **Leonid**
Chechurin, St. Petersburg (RU); **Luba**
Mitnik-Gankin, St. Petersburg (RU)

Sep. 6, 2011 (RU) 2011 136 869
Apr. 23, 2012 (GB) 1207054.6

Publication Classification

(73) Assignee: **BRITISH AMERICAN TOBACCO**
(INVESTMENTS) LIMITED, London
(GB)


(51) **Int. Cl.**
A24F 47/00 (2006.01)
(52) **U.S. Cl.**
CPC **A24F 47/008** (2013.01)
USPC **131/329**

(21) Appl. No.: **14/127,144**(22) PCT Filed: **Aug. 24, 2012**(86) PCT No.: **PCT/EP2012/066524**

§ 371 (c)(1),

(2), (4) Date: **Mar. 31, 2014**(57) **ABSTRACT**

An apparatus comprising a heater configured to heat smokeable material to volatilize at least one component of the smokeable material, wherein the heater is elongate and comprises a plurality of independently controllable heating regions arranged sequentially along a longitudinal axis of the heater.






FIG. 1





FIG. 2






FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9

**FIG. 10**




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20

HEATING SMOKEABLE MATERIAL

FIELD

[0001] The invention relates to heating smokeable material.

BACKGROUND

[0002] Smoking articles such as cigarettes and cigars burn tobacco during use to create tobacco smoke. Attempts have been made to provide alternatives to these smoking articles by creating products which release compounds without creating tobacco smoke. Examples of such products are so-called heat-not-burn products which release compounds by heating, but not burning, tobacco.

SUMMARY

[0003] According to the invention, there is provided an apparatus comprising a heater configured to heat smokeable material to volatilize at least one component of the smokeable material, wherein the heater is elongate and comprises a plurality of independently controllable heating regions arranged sequentially along a longitudinal axis of the heater.

[0004] A length of each heating region may be less than a length of the heater.

[0005] Each heating region may comprise a longitudinal heating element having a length which is less than a length of the heater.

[0006] The heating regions may be arranged in end-to-end relationship along the longitudinal axis of the heater.

[0007] The heater may comprise a longitudinal surface which extends over the plurality of heating regions.

[0008] The heater may be configured to heat smokeable material located around an outside of the longitudinal surface of the heater.

[0009] Each heating region may comprise a disk-shaped section of heater.

[0010] The heater may be arranged along a longitudinal axis of the apparatus and smokeable material may be located co-axially outwardly of a longitudinal surface of the heater.

[0011] The smokeable material may comprise a substantially tubular body of smokeable material.

[0012] The heater may be configured to heat smokeable material located inside a longitudinal surface of the heater.

[0013] Each heating region may comprise a ring-shaped section of heater.

[0014] The heater may be arranged along a longitudinal axis of the apparatus and smokeable material may be located co-axially inwardly of a longitudinal surface of the heater.

[0015] The heater may comprise an embossed exterior surface configured to heat smokeable material.

[0016] The heater may be substantially cylindrical in shape.

[0017] Each heating region may comprise a substantially cylindrical section of the heater.

[0018] The heater may be configured to heat the smokeable material to a temperature in a range of approximately 100° C. to 250° C., such as temperature in a range of approximately 150° C. to approximately 250° C.

[0019] Each heating region may be arranged to heat a different section of the smokeable material.

[0020] The apparatus may comprise a controller configured to activate the heating regions sequentially over a period of time.

[0021] The controller may be configured to activate each heating region in response to a puff.

[0022] The heater may be a substantially ceramics heater responsive to electrical energy to emit thermal energy.

[0023] The apparatus may be configured to heat the smokeable material without combusting the smokeable material.

[0024] According to the invention, there is provided a heater configured to heat smokeable material to volatilize at least one component of the smokeable material, wherein the heater comprises a plurality of independently controllable heating regions arranged sequentially along a longitudinal axis of the heater.

[0025] According to an aspect of the invention, there is provided an apparatus configured to heat smokeable material to volatilize at least one component of the smokeable material, comprising an infra-red heater.

[0026] The infra-red heater may comprise a halogen infra-red heater.

[0027] For exemplary purposes only, embodiments of the invention are described below with reference to the accompanying figures in which:

BRIEF DESCRIPTION OF THE FIGURES

[0028] FIG. 1 is a perspective, partially cut-away illustration of an apparatus configured to heat smokeable material to release aromatic compounds and/or nicotine from the smokeable material;

[0029] FIG. 2 is a perspective, partially cut-away illustration of an apparatus configured to heat smokeable material, in which the smokeable material is provided around an elongate ceramic heater divided into radial heating sections;

[0030] FIG. 3 is an exploded, partially cut-away view of an apparatus configured to heat smokeable material, in which the smokeable material is provided around an elongate ceramic heater divided into radial heating sections;

[0031] FIG. 4 is a perspective, partially cut-away illustration of an apparatus configured to heat smokeable material, in which the smokeable material is provided around an elongate infra-red heater;

[0032] FIG. 5 is an exploded, partially cut-away illustration of an apparatus configured to heat smokeable material, in which the smokeable material is provided around an elongate infra-red heater;

[0033] FIG. 6 is a schematic illustration of part of an apparatus configured to heat smokeable material, in which the smokeable material is provided around a plurality of longitudinal, elongate heating sections spaced around a central longitudinal axis;

[0034] FIG. 7 is a perspective illustration of part of an apparatus configured to heat smokeable material, in which the regions of smokeable material are provided between pairs of upstanding heating plates;

[0035] FIG. 8 is a perspective illustration of the apparatus shown in FIG. 7, in which an external housing is additionally illustrated;

[0036] FIG. 9 is an exploded view of part of an apparatus configured to heat smokeable material, in which the regions of smokeable material are provided between pairs of upstanding heating plates;

[0037] FIG. 10 is a flow diagram showing a method of activating heating regions and opening and closing heating chamber valves during puffing;

[0038] FIG. 11 is a schematic illustration of a gaseous flow through an apparatus configured to heat smokeable material;

[0039] FIG. 12 is a graphical illustration of a heating pattern which can be used to heat smokeable material using a heater;

[0040] FIG. 13 is a schematic illustration of a smokeable material compressor configured to compress smokeable material during heating;

[0041] FIG. 14 is a schematic illustration of a smokeable material expander configured to expand smokeable material during puffing;

[0042] FIG. 15 is a flow diagram showing a method of compressing smokeable material during heating and expanding the smokeable material for puffing;

[0043] FIG. 16 is a schematic, cross-sectional illustration of a section of vacuum insulation configured to insulate heated smokeable material from heat loss;

[0044] FIG. 17 is another schematic, cross-sectional illustration of a section of vacuum insulation configured to insulate heated smokeable material from heat loss;

[0045] FIG. 18 is a schematic, cross-sectional illustration of a heat resistive thermal bridge which follows an indirect path from a higher temperature insulation wall to a lower temperature insulation wall;

[0046] FIG. 19 is a schematic, cross-sectional illustration of a heat shield and a heat-transparent window which are moveable relative to a body of smokeable material to selectively allow thermal energy to be transmitted to different sections of the smokeable material through the window; and

[0047] FIG. 20 is schematic, cross sectional illustration of part of an apparatus configured to heat smokeable material, in which a heating chamber is hermetically sealable by check valves.

DETAILED DESCRIPTION

[0048] As used herein, the term ‘smokeable material’ includes any material that provides volatilized components upon heating and includes any tobacco-containing material and may, for example, include one or more of tobacco, tobacco derivatives, expanded tobacco, reconstituted tobacco or tobacco substitutes.

[0049] An apparatus 1 for heating smokeable material comprises an energy source 2, a heater 3 and a heating chamber 4. The energy source 2 may comprise a battery such as a Li-ion battery, Ni battery, Alkaline battery and/or the like, and is electrically coupled to the heater 3 to supply electrical energy to the heater 3 when required. The heating chamber 4 is configured to receive smokeable material 5 so that the smokeable material 5 can be heated in the heating chamber 4. For example, the heating chamber 4 may be located adjacent to the heater 3 so that thermal energy from the heater 3 heats the smokeable material 5 therein to volatilize aromatic compounds and nicotine in the smokeable material 5 without burning the smokeable material 5. A mouthpiece 6 is provided through which a user of the apparatus 1 can inhale the volatilized compounds during use of the apparatus 1. The smokeable material 5 may comprise a tobacco blend.

[0050] As shown in FIG. 1, the heater 3 may comprise a substantially cylindrical, elongate heater 3 and the heating chamber 4 is located around a circumferential, longitudinal surface of the heater 3. The heating chamber 4 and smokeable material 5 therefore comprise co-axial layers around the heater 3. However, as will be evident from the discussion below, other shapes and configurations of the heater 3 and heating chamber 4 can alternatively be used.

[0051] A housing 7 may contain components of the apparatus 1 such as the energy source 2 and heater 3. As shown in FIG. 1, the housing 7 may comprise an approximately cylindrical tube with the energy source 2 located towards its first end 8 and the heater 3 and heating chamber 4 located towards its opposite, second end 9. The energy source 2 and heater 3 extend along the longitudinal axis of the housing 7. For example, as shown in FIG. 1, the energy source 2 and heater 3 can be aligned along the central longitudinal axis of the housing 7 in an end-to-end arrangement so that an end face of the energy source 2 faces an end face of the heater 3. The length of the housing 7 may be approximately 130 mm, the length of energy source may be approximately 59 mm, and the length of the heater 3 and heating region 4 may be approximately 50 mm. The diameter of the housing 7 may be between approximately 15 mm and approximately 18 mm. For example, the diameter of the housing’s first end 8 may be 18 mm whilst the diameter of the mouthpiece 6 at the housing’s second end 9 may be 15 mm. The diameter of the heater 3 may be between approximately 2.0 mm and approximately 6.0 mm. The diameter of the heater 3 may, for example, be between approximately 4.0 mm and approximately 4.5 mm or between approximately 2.0 mm and approximately 3.0 mm. Heater diameters outside these ranges may alternatively be used. The depth of the heating chamber 4 may be approximately 5 mm and the heating chamber 4 may have an exterior diameter of approximately 10 mm at its outwardly-facing surface. The diameter of the energy source 2 may be between approximately 14.0 mm and approximately 15.0 mm, such as 14.6 mm.

[0052] Heat insulation may be provided between the energy source 2 and the heater 3 to prevent direct transfer of heat from one to the other. The mouthpiece 6 can be located at the second end 9 of the housing 7, adjacent the heating chamber 4 and smokeable material 5. The housing 7 is suitable for being gripped by a user during use of the apparatus 1 so that the user can inhale volatilized smokeable material compounds from the mouthpiece 6 of the apparatus 1.

[0053] Referring to FIGS. 2 and 3, the heater 3 may comprise a ceramics heater 3. The ceramics heater 3 may, for example, comprise base ceramics of alumina and/or silicon nitride which are laminated and sintered. Alternatively, referring to FIGS. 4 and 5, the heater 3 may comprise an infra-red (IR) heater 3 such as a halogen-IR lamp 3. The IR heater 3 may have a low mass and therefore its use can help to reduce the overall mass of the apparatus 1. For example, the mass of the IR heater may be 20% to 30% less than the mass of a ceramics heater 3 having an equivalent heating power output. The IR heater 3 also has low thermal inertia and therefore is able to heat the smokeable material 5 very rapidly in response to an activation stimulus. The IR heater 3 may be configured to emit IR electromagnetic radiation of between approximately 700 nm and 4.5 μ m in wavelength.

[0054] As indicated above and shown in FIG. 1, the heater 3 may be located in a central region of the housing 7 and the heating chamber 4 and smokeable material 5 may be located around the longitudinal surface of the heater 3. In this arrangement, thermal energy emitted by the heater 3 travels in a radial direction outwards from the longitudinal surface of the heater 3 into the heating chamber 4 and the smokeable material 5.

[0055] The heater 3 may optionally comprise a plurality of individual heating regions 10. The heating regions 10 may be operable independently of one another so that different

regions 10 can be activated at different times to heat the smokeable material 5. The heating regions 10 may be arranged in the heater 3 in any geometric arrangement. However, in the examples shown in the figures, the heating regions 10 are geometrically arranged in the heater 3 so that different ones of the heating regions 10 are arranged to predominately and independently heat different regions of the smokeable material 5.

[0056] For example, referring to FIG. 2, the heater 3 may comprise a plurality of axially aligned heating regions 10. The regions 10 may each comprise an individual element of the heater 3. The heating regions 10 may, for example, all be aligned with each other along a longitudinal axis of the heater 3, thus providing a plurality of independent heating zones along the length of the heater 3. Each heating region 10 may comprise a heating cylinder 10 having a finite length which is significantly less than the length of the heater 3 as a whole. The arrangement and features of the cylinders 10 are discussed below in terms of heating disks, where each disk has a depth which is equivalent to cylinder length. The heating disks 10 are arranged with their radial surfaces facing one another along the length of the heater 3. The radial surfaces of each disk 10 may touch the radial surfaces of its neighbouring disks 10. Alternatively, a heat insulating or heat reflecting layer may be present between the radial surfaces of the disks 10 so that thermal energy emitted from each one of the disks 10 does not substantially heat the neighbouring disks 10 and instead travels predominately outwards from the circumferential surface of the disk 10 into the heating chamber 4 and smokeable material 5. Each disk 10 may have substantially the same dimensions as the other disks 10.

[0057] In this way, when a particular one of the heating regions 10 is activated, it supplies thermal energy to the smokeable material 5 located radially around the heating region 10 without substantially heating the remainder of the smokeable material 5. For example, referring to FIG. 2, the heated region of smokeable material 5 may comprise a ring of smokeable material 5 located around the heating disk 10 which has been activated. The smokeable material 5 can therefore be heated in independent sections, for example rings, where each section corresponds to smokeable material 5 located directly around a particular one of the heating regions 10 and has a mass and volume which is significantly less than the body of smokeable material 5 as a whole.

[0058] Additionally or alternatively, referring to FIG. 6, the heater 3 may comprise a plurality of elongate, longitudinally extending heating regions 10 positioned at different locations around the central longitudinal axis of the heater 3. Although shown as being of different lengths in FIG. 6, the longitudinally extending heating regions 10 may be of substantially the same length so that each extends along substantially the whole length of the heater 3. Each heating region 10 may comprise, for example, an individual IR heating element 10 such as an IR heating filament 10. Optionally, a body of heat insulation or heat reflective material may be provided along the central longitudinal axis of the heater 3 so that thermal energy emitted by each heating region 10 travels predominately outwards from the heater 3 into the heating chamber 4 and thus heats the smokeable material 5. The distance between the central longitudinal axis of the heater 3 and each of the heating regions 10 may be substantially equal. The heating regions 10 may optionally be contained in a substantially infra-red and/or heat transparent tube, or other housing, which forms a longitudinal surface of the heater 3. The heat-

ing regions 10 may be fixed in position relative to the other heating regions 10 inside the tube.

[0059] In this way, when a particular one of the heating regions 10 is activated, it supplies thermal energy to the smokeable material 5 located adjacent to the heating region 10 without substantially heating the remainder of the smokeable material 5. The heated section of smokeable material 5 may comprise a longitudinal section of smokeable material 5 which lies parallel and directly adjacent to the longitudinal heating region 10. Therefore, as with the previous example, the smokeable material 5 can be heated in independent sections.

[0060] As will be described further below, the heating regions 10 can each be individually and selectively activated.

[0061] The smokeable material 5 may be comprised in a cartridge 11 which can be inserted into the heating chamber 4. For example, as shown in FIG. 1, the cartridge 11 can comprise a smokeable material tube 11 which can be inserted around the heater 3 so that the internal surface of the smokeable material tube 11 faces the longitudinal surface of the heater 3. The smokeable material tube 11 may be hollow. The diameter of the hollow centre of the tube 11 may be substantially equal to, or slightly larger than, the diameter of the heater 3 so that the tube 11 is a close fit around the heater 3. The length of the cartridge 11 may be approximately equal to the length of the heater 3 so that the heater 3 can heat the cartridge 11 along its whole length.

[0062] The housing 7 of the apparatus 1 may comprise an opening through which the cartridge 11 can be inserted into the heating chamber 4. The opening may, for example, comprise a ring-shaped opening located at the housing's second end 9 so that the cartridge 11 can be slid into the opening and pushed directly into the heating chamber 4. The opening is preferably closed during use of the apparatus 1 to heat the smokeable material 5. Alternatively, a section of the housing 7 at the second end 9 is removable from the apparatus 1 so that the smokeable material 5 can be inserted into the heating chamber 4. An example of this is shown in FIG. 9. The apparatus 1 may optionally be equipped with a user-operable smokeable material ejection unit, such as an internal mechanism configured to slide used smokeable material 5 off and/or away from the heater 3. The used smokeable material 5 may, for example, be pushed back through the opening in the housing 7. A new cartridge 11 can then be inserted as required.

[0063] In an alternative configuration of heater 3, the heater 3 comprises a spirally shaped heater 3. The spirally shaped heater 3 may be configured to screw into the smokeable material cartridge 11 and may comprise adjacent, axially-aligned heating regions 10 so as to operate in substantially the same manner as described the linear, elongate heater 3 described above.

[0064] In an alternative configuration of heater 3 and heating chamber 4, the heater 3 comprises a substantially elongate tube, which may be cylindrical, and the heating chamber 4 is located inside the tube 3 rather than around the heater's outside. The heater 3 may comprise a plurality of axially-aligned heating sections, which may each comprise a heating ring configured to heat smokeable material 5 located radially inwardly from the ring. In this way, the heater 3 is configured to independently heat separate sections of smokeable material 5 in the heating chamber 4 in a manner similar to the heater 3 described above in relation to FIG. 2. The heat is

applied radially inwardly to the smokeable material 5, rather than radially outwardly as previously described.

[0065] Alternatively, referring to FIGS. 7, 8 and 9, a different geometrical configuration of heater 3 and smokeable material 5 can be used. More particularly, the heater 3 can comprise a plurality of heating regions 10 which extend directly into an elongate heating chamber 4 which is divided into sections by the heating regions 10. During use, the heating regions 10 extend directly into an elongate smokeable material cartridge 11 or other substantially solid body of smokeable material 5. The smokeable material 5 in the heating chamber 4 is thereby divided into discrete sections separated from each other by the spaced-apart heating regions 10. The heater 3, heating chamber 4 and smokeable material 5 may extend together along a central, longitudinal axis of the housing 7. As shown in FIGS. 7 and 9, the heating regions 10 may each comprise a projection 10, such as an upstanding heating plate 10, which extends into the body of smokeable material 5. The projections 10 are discussed below in the context of heating plates 10. The principal plane of the heating plates 10 may be substantially perpendicular to the principal longitudinal axis of the body of smokeable material 5 and heating chamber 4 and/or housing 7. The heating plates 10 may be parallel to one another, as shown in FIGS. 7 and 9. Each section of smokeable material 5 is bounded by a main heating surface of a pair of heating plates 10 located either side of the smokeable material section, so that activation of one or both of the heating plates 10 will cause thermal energy to be transferred directly into the smokeable material 5. The heating surfaces may be embossed to increase the surface area of the heating plate 10 against the smokeable material 5. Optionally, each heating plate 10 may comprise a thermally reflective layer which divides the plate 10 into two halves along its principal plane. Each half of the plate 10 can thus constitute a separate heating region 10 and may be independently activated to heat only the section of smokeable material 5 which lies directly against that half of the plate 10, rather than the smokeable material 5 on both sides of the plate 10. Adjacent plates 10, or facing portions thereof, may be activated to heat a section of smokeable material 5, which is located between the adjacent plates, from substantially opposite sides of the section of smokeable material 5.

[0066] The elongate smokeable material cartridge or body 11 can be installed between, and removed from, the heating chamber 4 and heating plates 10 by removing a section of the housing 7 at the housing's second end 9, as previously described. The heating regions 10 can be individually and selectively activated to heat different sections of the smokeable material 5 as required.

[0067] In this way, when a particular one or pair of the heating regions 10 is activated, it supplies thermal energy to the smokeable material 5 located directly adjacent to the heating region(s) 10 without substantially heating the remainder of the smokeable material 5. The heated section of smokeable material 5 may comprise a radial section of smokeable material 5 located between the heating regions 10, as shown in FIGS. 7 to 9.

[0068] The apparatus 1 may comprise a controller 12, such as a microcontroller 12, which is configured to control operation of the apparatus 1. The controller 12 is electronically connected to the other components of the apparatus 1 such as the energy source 2 and heater 3 so that it can control their operation by sending and receiving signals. The controller 12 is, in particular, configured to control activation of the heater

3 to heat the smokeable material 5. For example, the controller 12 may be configured to activate the heater 3, which may comprise selectively activating one or more heating regions 10, in response to a user drawing on the mouthpiece 6 of the apparatus 1. In this regard, the controller 12 may be in communication with a puff sensor 13 via a suitable communicative coupling. The puff sensor 13 is configured to detect when a puff occurs at the mouthpiece 6 and, in response, is configured to send a signal to the controller 12 indicative of the puff. An electronic signal may be used. The controller 12 may respond to the signal from the puff sensor 13 by activating the heater 3 and thereby heating the smokeable material 5. The use of a puff sensor 13 to activate the heater 3 is not, however, essential and other means for providing a stimulus to activate the heater 3 can alternatively be used. The volatilized compounds released during heating can then be inhaled by the user through the mouthpiece 6. The controller 12 can be located at any suitable position within the housing 7. An example position is between the energy source 2 and the heater 3/heating chamber 4, as illustrated in FIG. 3.

[0069] If the heater 3 comprises two or more heating regions 10 as described above, the controller 12 may be configured to activate the heating regions 10 in a predetermined order or pattern. For example, the controller 12 may be configured to activate the heating regions 10 sequentially along or around the heating chamber 4. Each activation of a heating region 10 may be in response to detection of a puff by the puff sensor 13 or may be triggered in an alternative way, as described further below.

[0070] Referring to FIG. 10, an example heating method may comprise a first step S1 in which a first puff is detected followed by a second step S2 in which a first section of smokeable material 5 is heated in response to the first puff. In a third step S3, hermetically sealable inlet and outlet valves 24 may be opened to allow air to be drawn through the heating chamber 4 and out of the apparatus 1 through the mouthpiece 6. In a fourth step, the valves 24 are closed. These valves 24 are described in more detail below with respect to FIG. 20. In fifth S5, sixth S6, seventh S7 and eighth S8 steps, a second section of smokeable material 5 may be heated in response to a second puff, with a corresponding opening and closing of the heating chamber inlet and outlet valves 24. In ninth S9, tenth S10, eleventh S11 and twelfth S12 steps, a third section of the smokeable material 5 may be heated in response to a third puff with a corresponding opening and closing of the heating chamber inlet and outlet valves 24, and so on. Means other than a puff sensor 13 could alternatively be used. For example, a user of the apparatus 1 may actuate a control switch to indicate that he/she is taking a new puff. In this way, a fresh section of smokeable material 5 may be heated to volatilize nicotine and aromatic compounds for each new puff. The number of heating regions 10 and/or independently heatable sections of smokeable material 5 may correspond to the number of puffs for which the cartridge 11 is intended to be used. Alternatively, each independently heatable smokeable material section 5 may be heated by its corresponding heating region(s) 10 for a plurality of puffs such as two, three or four puffs, so that a fresh section of smokeable material 5 is heated only after a plurality of puffs have been taken whilst heating the previous smokeable material section.

[0071] Instead of activating each heating region 10 in response to an individual puff, the heating regions 10 may alternatively be activated sequentially, one after the other, in response to a single, initial puff at the mouthpiece 6. For

example, the heating regions 10 may be activated at regular, predetermined intervals over the expected inhalation period for a particular smokeable material cartridge 11. The inhalation period may, for example, be between approximately one and approximately four minutes. Therefore, at least the fifth and ninth steps S5, S9 shown in FIG. 10 are optional. Each heating region 10 may be activated for a predetermined period corresponding to the duration of the single or plurality of puffs for which the corresponding independently heatable smokeable material section 5 is intended to be heated. Once all of the heating regions 10 have been activated for a particular cartridge 11, the controller 12 may be configured to indicate to the user that the cartridge 11 should be changed. The controller 12 may, for example, activate an indicator light at the external surface of the housing 7.

[0072] It will be appreciated that activating individual heating regions 10 in order rather than activating the entire heater 3 means that the energy required to heat the smokeable material 5 is reduced over what would be required if the heater 3 were activated fully over the entire inhalation period of a cartridge 11. Therefore, the maximum required power output of the energy source 2 is also reduced. This means that a smaller and lighter energy source 2 can be installed in the apparatus 1.

[0073] The controller 12 may be configured to de-activate the heater 3, or reduce the power being supplied to the heater 3, in between puffs. This saves energy and extends the life of the energy source 2. For example, upon the apparatus 1 being switched on by a user or in response to some other stimulus, such as detection of a user placing their mouth against the mouthpiece 6, the controller 12 may be configured to cause the heater 3, or next heating region 10 to be used to heat the smokeable material 5, to be partially activated so that it heats up in preparation to volatilize components of the smokeable material 5. The partial activation does not heat the smokeable material 5 to a sufficient temperature to volatilize nicotine. A suitable temperature could be below 120° C., such as 100° C. or below. An example is a temperature between 60° C. and 100° C., such as a temperature between 80° C. and 100° C. The temperature may be less than 100° C. In response to detection of a puff by the puff sensor 13, the controller 12 can then cause the heater 3 or heating region 10 in question to heat the smokeable material 5 further in order to rapidly volatilize the nicotine and other aromatic compounds for inhalation by the user. If the smokeable material 5 comprises tobacco, a suitable temperature for volatilizing the nicotine and other aromatic compounds may be 100° C. or above, such as 120° C. or above. An example is a temperature between 100° C. and 250° C., such as between 100° C. and 220° C., between 100° C. and 200° C., between 150° C. and 250° C. or between 130° C. and 180° C. The temperature may be more than 100° C. An example full activation temperature is 150° C., although other values such as 250° C. are also possible. A super-capacitor can optionally be used to provide the peak current used to heat the smokeable material 5 to the volatilization temperature. An example of a suitable heating pattern is shown in FIG. 12, in which the peaks may respectively represent the full activation of different heating regions 10. As can be seen, the smokeable material 5 is maintained at the volatilization temperature for the approximate period of the puff which, in this example, is two seconds.

[0074] Three example operational modes of the heater 3 are described below.

[0075] In a first operational mode, during full activation of a particular heating region 10, all other heating regions 10 of the heater are deactivated. Therefore, when a new heating region 10 is activated, the previous heating region is deactivated. Power is supplied only to the activated region 10.

[0076] Alternatively, in a second operational mode, during full activation of a particular heating region 10, one or more of the other heating regions 10 may be partially activated. Partial activation of the one or more other heating regions 10 may comprise heating the other heating region(s) 10 to a temperature which is sufficient to substantially prevent condensation of components such as nicotine volatilized from the smokeable material 5 in the heating chamber 4. The temperature of the heating regions 10 which are partially activated is less than the temperature of the heating region 10 which is fully activated. The smokeable material 10 located adjacent the partially activated regions 10 is not heated to a temperature sufficient to volatilize components of the smokeable material 5.

[0077] Alternatively, in a third operational mode, once a particular heating region 10 has been activated, it remains fully activated until the heater 3 is switched off. Therefore, the power supplied to the heater 3 incrementally increases as more of the heating regions 10 are activated during inhalation from the cartridge 11. As with the second mode previously described, the continuing activation of the heating regions 10 substantially prevent condensation of components such as nicotine volatilized from the smokeable material 5 in the heating chamber 4.

[0078] The apparatus 1 may comprise a heat shield 3a, which is located between the heater 3 and the heating chamber 4/smokeable material 5. The heat shield 3a is configured to substantially prevent thermal energy from flowing through the heat shield 3a and therefore can be used to selectively prevent the smokeable material 5 from being heated even when the heater 3 is activated and emitting thermal energy. Referring to FIG. 19, the heat shield 3a may, for example, comprise a cylindrical layer of heat reflective material which is located co-axially around the heater 3. Alternatively, if the heater 3 is located around the heating chamber 4 and smokeable material 5 as previously described, the heat shield 3a may comprise a cylindrical layer of heat reflective material which is located co-axially around the heating chamber 4 and co-axially inside of the heater 3. The heat shield 3a may additionally or alternatively comprise a heat-insulating layer configured to insulate the heater 3 from the smokeable material 5. The heat shield 3a comprises a substantially heat-transparent window 3b which allows thermal energy to propagate through the window 3b and into the heating chamber 4 and smokeable material 5. Therefore, the section of smokeable material 5 which is aligned with the window 3b is heated whilst the remainder of the smokeable material 5 is not. The heat shield 3a and window 3b may be rotatable or otherwise moveable with respect to the smokeable material 5 so that different sections of the smokeable material 5 can be selectively and individually heated by rotating or moving the heat shield 3a and window 3b. The effect is similar to the effect provided by selectively and individually activating the heating regions 10 referred to above. For example, the heat shield 3a and window 3b may be rotated or otherwise moved incrementally in response to a signal from the puff detector 13. Additionally or alternatively, the heat shield 3a and window 3b may be rotated or otherwise moved incrementally in response to a predetermined heating period having elapsed. Movement or rotation of the heat shield 3a and window 3b

may be controlled by electronic signals from the controller 12. The relative rotation or other movement of the heat shield 3a/window 3b and smokeable material 5 may be driven by a stepper motor 3c under the control of the controller 12. This is illustrated in FIG. 19. Alternatively, the heat shield 3a and window 3b may be manually rotated using a user control such as an actuator on the housing 7. The heat shield 3a does not need to be cylindrical and may comprise optionally comprise one or more suitably positioned longitudinally extending elements and/or plates.

[0079] It will be appreciated that a similar result can be obtained by rotating or moving the smokeable material 5 relative to the heater 3, heat shield 3a and window 3b. For example, the heating chamber 4 may be rotatable around the heater 3. If this is the case, the above description relating to movement of the heat shield 3a can be applied instead to movement of the heating chamber 4 relative to the heat shield 3a.

[0080] The heat shield 3a may comprise a coating on the longitudinal surface of the heater 3. In this case, an area of the heater's surface is left uncoated to form the heat-transparent window 3b. The heater 3 can be rotated or otherwise moved, for example under the control of the controller 12 or user controls, to cause different sections of the smokeable material 5 to be heated. Alternatively, the heat shield 3a and window 3b may comprise a separate shield 3a which is rotatable or otherwise moveable relative to both the heater 3 and the smokeable material 5 under the control of the controller 12 or other user controls.

[0081] Referring to FIG. 6, the apparatus 1 may comprise air inlets 14 which allow external air to be drawn into the housing 7 and through the heated smokeable material 5 during puffing. The air inlets 14 may comprise apertures 14 in the housing 7 and may be located upstream from the smokeable material 5 and heating chamber 4 towards the first end 8 of the housing 7. This is shown in FIG. 1.

[0082] Another example is shown in FIG. 11. Air drawn in through the inlets 14 travels through the heated smokeable material 5 and therein is enriched with smokeable material vapours, such as aroma vapours, before being inhaled by the user at the mouthpiece 6. Optionally, as shown in FIG. 11, the apparatus 1 may comprise a heat exchanger 15 configured to warm the air before it enters the smokeable material 5 and/or to cool the air before it is drawn through the mouthpiece 6. For example, the heat exchanger 15 may be configured to use heat extracted from the air entering the mouthpiece 6 to warm new air before it enters the smokeable material 5.

[0083] The apparatus 1 may comprise a smokeable material compressor 16 configured to cause the smokeable material 5 to compress upon activation of the compressor 16. The apparatus 1 can also comprise a smokeable material expander 17 configured to cause the smokeable material 5 to expand upon activation of the expander 17. The compressor 16 and expander 17 may, in practice, be implemented as the same unit as will be explained below. The smokeable material compressor 16 and expander 17 may optionally operate under the control of the controller 12. In this case, the controller 12 is configured to send a signal, such as an electrical signal, to the compressor 16 or expander 17 which causes the compressor 16 or expander 17 to respectively compress or expand the smokeable material 5. Alternatively, the compressor 16 and expander 17 may be actuated by a user of the apparatus 1 using a manual control on the housing 7 to compress or expand the smokeable material 5 as required.

[0084] The compressor 16 is principally configured to compress the smokeable material 5 and thereby increase its density during heating. Compression of the smokeable material increases the thermal conductivity of the body of smokeable material 5 and therefore provides a more rapid heating and consequent rapid volatilization of nicotine and other aromatic compounds. This is preferable because it allows the nicotine and aromatics to be inhaled by the user without substantial delay in response to detection of a puff. Therefore, the controller 12 may activate the compressor 16 to compress the smokeable material 5 for predetermined heating period, for example one second, in response to detection of a puff. The compressor 16 may be configured to reduce its compression of the smokeable material 5, for example under the control of the controller 12, after the predetermined heating period. Alternatively, the compression may be reduced or automatically ended in response to the smokeable material 5 reaching a predetermined threshold temperature. A suitable threshold temperature may be in the range of approximately 100° C. to 250° C., such as between 100° C. and 220° C., between 150° C. and 250° C., between 100° C. and 200° C. or between 130° C. and 180° C. The threshold temperature may be above 100° C., such as a value above 120° C., and may be user selectable. A temperature sensor may be used to detect the temperature of the smokeable material 5.

[0085] The expander 17 is principally configured to expand the smokeable material 5 and thereby decrease its density during puffing. The arrangement of smokeable material 5 in the heating chamber 4 becomes more loose when the smokeable material 5 has been expanded and this aids the gaseous flow, for example air from the inlets 14, through the smokeable material 5. The air is therefore more able to carry the volatilized nicotine and aromatics to the mouthpiece 6 for inhalation. The controller 12 may activate the expander 17 to expand the smokeable material 5 immediately following the compression period referred to above so that air can be drawn more freely through the smokeable material 5. Actuation of the expander 17 may be accompanied by a user-audible sound or other indication to indicate to the user that the smokeable material 5 has been heated and that puffing can commence.

[0086] Referring to FIGS. 13 and 14, the compressor 16 and expander 17 may comprise a spring-actuated driving rod which is configured to compress the smokeable material 5 in the heating chamber 4 when the spring is released from compression. This is schematically illustrated in FIGS. 13 and 14, although it will be appreciated that other implementations could be used. For example, the compressor 16 may comprise a ring, having a thickness approximately equal to the tubular-shaped heating chamber 4 described above, which is driven by a spring or other means into the heating chamber 4 to compress the smokeable material 5. Alternatively, the compressor 16 may be comprised as part of the heater 3 so that the heater 3 itself is configured to compress and expand the smokeable material 5 under the control of the controller 12. For example, where the heater 3 comprises upstanding heating plates 10 of the type previously described, the plates 10 may be independently moveable in a longitudinal direction of the heater 3 to expand or compress the sections of smokeable material 5 which are located adjacent to them. A method of compressing and expanding the smokeable material 5 is shown in FIG. 15.

[0087] Thermal insulation 18 may be provided between the smokeable material 5 and an external surface 19 of the housing 7 to reduce heat loss from the apparatus 1 and therefore

improve the efficiency with which the smokeable material **5** is heated. For example, referring to FIG. 1, a wall of the housing **7** may comprise a layer of insulation **18** which extends around the outside of the heating chamber **4**. The insulation layer **18** may comprise a substantially tubular length of insulation **18** located co-axially around the heating chamber **4** and smokeable material **5**. This is shown in FIG. 1. It will be appreciated that the insulation **18** could also be comprised as part of the smokeable material cartridge **11**, in which it would be located co-axially around the outside of the smokeable material **5**.

[0088] Referring to FIG. 16, the insulation **18** may comprise vacuum insulation **18**. For example, the insulation **18** may comprise a layer which is bounded by a wall material **19** such as a metallic material. An internal region or core **20** of the insulation **18** may comprise an open-cell porous material, for example comprising polymers, aerogels or other suitable material, which is evacuated to a low pressure. The pressure in the internal region **20** may be in the range of 0.1 to 0.001 mbar. The wall **19** of the insulation **18** is sufficiently strong to withstand the force exerted against it due to the pressure differential between the core **20** and external surfaces of the wall **19**, thereby preventing the insulation **18** from collapsing. The wall **19** may, for example, comprise a stainless steel wall **19** having a thickness of approximately 100 μm . The thermal conductivity of the insulation **18** may be in the range of 0.004 to 0.005 W/mK. The heat transfer coefficient of the insulation **18** may be between approximately 1.10 W/(m²K) and approximately 1.40 W/(m²K) within a temperature range of between 100° C. and 250° C., such as between approximately 150 degrees Celsius and approximately 250 degrees Celsius. The gaseous conductivity of the insulation **18** is negligible. A reflective coating may be applied to the internal surfaces of the wall material **19** to minimize heat losses due to radiation propagating through the insulation **18**. The coating may, for example, comprise an aluminium IR reflective coating having a thickness of between approximately 0.3 μm and 1.0 μm . The evacuated state of the internal core region **20** means that the insulation **18** functions even when the thickness of the core region **20** is very small. The insulating properties are substantially unaffected by its thickness. This helps to reduce the overall size of the apparatus **1**.

[0089] As shown in FIG. 16, the wall **19** may comprise an inwardly-facing section **21** and an outwardly-facing section **22**. The inwardly-facing section **21** substantially faces the smokeable material **5** and heating chamber **4**. The outwardly-facing section **22** substantially faces the exterior of the housing **7**. During operation of the apparatus **1**, the inwardly-facing section **21** may be warmer due to the thermal energy originating from the heater **3**, whilst the outwardly-facing section **22** is cooler due to the effect of the insulation **18**. The inwardly-facing section **21** and the outwardly-facing section **22** may, for example, comprise substantially parallel longitudinally-extending walls **19** which are at least as long as the heater **3**. The internal surface of the outwardly-facing wall section **22**, i.e. the surface facing the evacuated core region **20**, may comprise a coating for absorbing gas in the core **20**. A suitable coating is a titanium oxide film.

[0090] Referring to the schematic illustration in FIG. 17, a thermal bridge **23** may connect the inwardly-facing wall section **21** to the outwardly-facing wall section **22** at the edges of the insulation **18** in order to completely encompass and contain the low pressure core **20**. The thermal bridge **23** may comprise a wall **19** formed of the same material as the inwardly and outwardly-facing sections **21**, **22**. A suitable

material is stainless steel, as previously discussed. The thermal bridge **23** has a greater thermal conductivity than the insulating core **20** and therefore may undesirably conduct heat out of the apparatus **1** and, in doing so, reduce the efficiency with which the smokeable material **5** is heated.

[0091] To reduce heat losses due to the thermal bridge **23**, the thermal bridge **23** may be extended to increase its resistance to heat flow from the inwardly-facing section **21** to the outwardly-facing section **22**. This is schematically illustrated in FIG. 18. For example, the thermal bridge **23** may follow an indirect path between the inwardly-facing section **21** of wall **19** and the outwardly-facing section **22** of wall **19**. This may be facilitated by providing the insulation **18** over a longitudinal distance which is longer than the lengths of the heater **3**, heating chamber **4** and smokeable material **5** so that the thermal bridge **23** can gradually extend from the inwardly-facing section **21** to the outwardly-facing section **22** along the indirect path, thereby reducing the thickness of the core **20** to zero, at a longitudinal location in the housing **7** where the heater **3**, heating chamber **4** and smokeable material **5** are not present.

[0092] Referring to FIG. 20, as previously discussed, the heating chamber **4** insulated by the insulation **18** may comprise inlet and outlet valves **24** which hermetically seal the heating chamber **4** when closed. The valves **24** can thereby prevent air from undesirably entering and exiting the chamber **4** and can prevent smokeable material flavours from exiting the chamber **4**. The inlet and outlet valves **24** may, for example, be provided in the insulation **18**. For example, between puffs, the valves **24** may be closed by the controller **12** so that all volatilized substances remain contained inside the chamber **4** in-between puffs. The partial pressure of the volatilized substances between puffs reaches the saturated vapour pressure and the amount of evaporated substances therefore depends only on the temperature in the heating chamber **4**. This helps to ensure that the delivery of volatilized nicotine and aromatic compounds remains constant from puff to puff. During puffing, the controller **12** is configured to open the valves **24** so that air can flow through the chamber **4** to carry volatilized smokeable material components to the mouthpiece **6**. A membrane can be located in the valves **24** to ensure that no oxygen enters the chamber **4**. The valves **24** may be breath-actuated so that the valves **24** open in response to detection of a puff at the mouthpiece **6**. The valves **24** may close in response to a detection that a puff has ended. Alternatively, the valves **24** may close following the elapse of a predetermined period after their opening. The predetermined period may be timed by the controller **12**. Optionally, a mechanical or other suitable opening/closing means may be present so that the valves **24** open and close automatically. For example, the gaseous movement caused by a user puffing on the mouthpiece **6** may be used to open and close the valves **24**. Therefore, the use of the controller **12** is not necessarily required to actuate the valves **24**.

[0093] The mass of the smokeable material **5** which is heated by the heater **3**, for example by each heating region **10**, may be in the range of 0.2 to 1.0 g. The temperature to which the smokeable material **5** is heated may be user controllable, for example to any temperature within the temperature range of 100° C. to 250° C., such as any temperature within the range of 150° C. to 250° C. and the other volatilizing temperature ranges previously described. The mass of the apparatus **1** as a whole may be in the range of 70 to 125 g. A battery **2** with a capacity of 1000 to 3000 mAh and voltage of 3.7V can be

used. The heating regions **10** may be configured to individually and selectively heat between approximately 10 and 40 sections of smokeable material **5** for a single cartridge **11**.

[0094] It will be appreciated that any of the alternatives described above can be used singly or in combination. For example, as discussed above, the heater **3** may be located around the outside of the smokeable material **5** rather than the smokeable material **5** being located around the heater **3**. The heater **3** may therefore circumscribe the smokeable material **5** to apply heat to the smokeable material **5** in a substantially radially inward direction.

1. An apparatus comprising a heater configured to heat smokeable material to volatilize at least one component of the smokeable material, wherein the heater is elongate and comprises a plurality of independently controllable heating regions arranged sequentially along a longitudinal axis of the heater.

2. An apparatus according to claim **1**, wherein a length of each heating region is less than a length of the heater.

3. An apparatus according to claim **1**, wherein each heating region comprises a longitudinal heating element having a length which is less than a length of the heater.

4. An apparatus according to any preceding claim, wherein the heating regions are arranged in end-to-end relationship along the longitudinal axis of the heater.

5. An apparatus according to any preceding claim, wherein the heater comprises a longitudinal surface which extends over the plurality of heating regions.

6. An apparatus according to claim **5**, wherein the heater is configured to heat smokeable material located around an outside of the longitudinal surface of the heater.

7. An apparatus according to any preceding claim, wherein each heating region comprises a disk-shaped section of heater.

8. An apparatus according to any preceding claim, wherein the heater is arranged along a longitudinal axis of the apparatus and smokeable material is located co-axially outwardly of a longitudinal surface of the heater.

9. An apparatus according to claim **8**, wherein the smokeable material comprises a substantially tubular body of smokeable material.

10. An apparatus according to any of claims **1** to **5**, wherein the heater is configured to heat smokeable material located inside a longitudinal surface of the heater.

11. An apparatus according to any of claim **1** to **5**, or **10**, wherein each heating region comprises a ring-shaped section of heater.

12. An apparatus according to any of claim **1** to **5**, **10** or **11**, wherein the heater is arranged along a longitudinal axis of the apparatus and smokeable material is located co-axially inwardly of a longitudinal surface of the heater.

13. An apparatus according to any preceding claim, wherein the heater comprises an embossed exterior surface configured to heat smokeable material.

14. An apparatus according to any preceding claim, wherein the heater is substantially cylindrical in shape.

15. An apparatus according to any preceding claim, wherein each heating region comprises a substantially cylindrical section of the heater.

16. An apparatus according to any preceding claim, wherein the heater is configured to heat the smokeable material to a temperature in a range of approximately 100° C. to 250° C.

17. An apparatus according to any preceding claim, wherein each heating region is arranged to heat a different section of the smokeable material.

18. An apparatus according to any preceding claim, comprising a controller configured to activate the heating regions sequentially over a period of time.

19. An apparatus according to claim **18**, wherein the controller is configured to activate each heating region in response to a puff.

20. An apparatus according to any preceding claim, wherein the heater is a substantially ceramics heater responsive to electrical energy to emit thermal energy.

21. An apparatus according to any preceding claim, wherein the apparatus is configured to heat the smokeable material without combusting the smokeable material.

22. A heater configured to heat smokeable material to volatilize at least one component of the smokeable material, wherein the heater is elongate and comprises a plurality of independently controllable heating regions arranged sequentially along a longitudinal axis of the heater.

* * * * *