



(43) International Publication Date
7 February 2013 (07.02.2013)

- (51) International Patent Classification:
B01L 9/06 (2006.01) *B03C 1/28* (2006.01)
- (21) International Application Number:
PCT/US2012/044534
- (22) International Filing Date:
28 June 2012 (28.06.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/513,265 29 July 2011 (29.07.2011) US
- (71) Applicant (for all designated States except US): **CORNING INCORPORATED** [US/US]; 1 Riverfront Plaza, Corning, New York 14831 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **EL-FAHMAWI, Bas-sam** [CA/US]; 4195 Horatio Way, Fremont, California 94555 (US).

(74) Agent: **BUTLER, Gregory B.**; Corning Incorporated, Intellectual Property Department, SP-Ti-03-01, Corning, New York 14831 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MAGNETIC SEPARATION DEVICE AND METHODS




FIG. 7

(57) Abstract: A method and apparatus for separating a non-magnetic material from magnetic material is provided. A magnetic separation device includes at least one magnetic element for producing a magnetic field. The magnetic separation device further includes a first support portion including a threaded opening that threadably receives a threaded portion of a container to fixedly attach the container to the first support portion in an aligned orientation with respect to the magnetic element. The threaded opening retains the container in the aligned orientation when inverting the magnetic separation device.



Published:

— with international search report (Art. 21(3))

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))

MAGNETIC SEPARATION DEVICE AND METHODS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of priority under 35 U.S.C. § 119 of U.S. Provisional Application Serial No. 61/513,265 filed on July 29, 2011 the content of which is relied upon and incorporated herein by reference in its entirety.

TECHNICAL FIELD

[0002] The invention relates to apparatus and methods for separation and, more particularly, to apparatus and methods for magnetic separation.

BACKGROUND

[0003] It is known to use magnetic bead based separation to separate a desired material within a container. More specifically, a magnetic material can be added to a solution in a container. Desired material can then be associated with the magnetic material. A magnetic device can then be used to separate the magnetic material, together with the associated desired material from the solution in the container.

SUMMARY

[0004] The following presents a simplified summary of the disclosure in order to provide a basic understanding of some example aspects described in the detailed description.

[0005] In one example aspect of the disclosure, a magnetic separation device is provided comprising at least one magnetic element configured to produce a magnetic field and a first support portion including a threaded opening configured to threadingly receive a threaded portion of a container to fixedly attach the container to the first support portion in an aligned orientation with respect to the magnetic element. The threaded opening is configured to retain the container in the aligned orientation when inverting the magnetic separation device.

[0006] In another example aspect of the disclosure, a method of separating a non-magnetic material from magnetic material is provided. The method includes the step of inserting a non-magnetic material and a magnetic material into an interior area of a container. The method further includes the steps of fixedly mounting the container in an aligned orientation relative to a magnetic element and attracting the magnetic material to an interior

surface of the container while the container is in the aligned orientation. The method further includes the step of repositioning the container to pour a quantity of the non-magnetic material out of the interior area of the container while retaining a quantity of the magnetic material within the interior area. The container remains in the aligned orientation while repositioning the container.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] These and other aspects are better understood when the following detailed description is read with reference to the accompanying drawings, in which:

[0008] **FIG. 1** is a front elevation view of an example magnetic separation device;

[0009] **FIG. 2** is a top plan view of the magnetic separation device of **FIG. 1**;

[0010] **FIG. 3** is a sectional view of the magnetic separation device along line 3-3 of **FIG. 2**;

[0011] **FIG. 4** is a sectional view of the magnetic separation device along either of lines 4a-4a or 4b-4b of **FIG. 2**;

[0012] **FIG. 5** illustrates an example step of fixedly mounting a container to a carriage of the magnetic separation device of **FIG. 1**;

[0013] **FIG. 6** illustrates the carriage of **FIG. 5** being mounted to a base such that the container achieves an aligned orientation relative to a magnetic element;

[0014] **FIG. 7** illustrates the optional step of releasably attaching a second support portion to a first support portion of **FIG. 6**;

[0015] **FIG. 8** illustrates an example step of repositioning the magnetic separation device of **FIG. 7** to pour a quantity of non-magnetic material out of an interior area of the container;

[0016] **FIG. 9** illustrates an optional step of using an absorbent material to remove an additional quantity of the non-magnetic material;

[0017] **FIG. 10** illustrates a container being fixedly mounted to a base of the magnetic separation device of **FIG. 1**;

[0018] **FIG. 11** illustrates the container being fixedly mounted in an aligned orientation relative to a magnetic element of the magnetic separation device of **FIG. 10**;

[0019] **FIG. 12** illustrates an example step of repositioning the magnetic separation device of **FIG. 11** to pour a quantity of the non-magnetic material out of the interior area of the container; and

[0020] **FIG. 13** illustrates a method of using an absorbent material to remove an additional quantity of the non-magnetic material.

DETAILED DESCRIPTION

[0021] Examples will now be described more fully hereinafter with reference to the accompanying drawings in which example embodiments are shown. Whenever possible, the same reference numerals are used throughout the drawings to refer to the same or like parts. However, aspects may be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

[0022] **FIG. 1** illustrates a front elevation view of a magnetic separation device **101** incorporating aspects of the disclosure. The magnetic separation device **101** can include a wide variety of configurations including various designs, sizes, shapes or functional features designed to separate a desired material from a non-magnetic material using a magnetic material. The magnetic separation device **101** can be formed from a number of different materials, such as plastic, or the like.

[0023] The magnetic separation device **101** can include a carriage **103**. The carriage **103** can include a first surface **105** and a second surface **107** that are substantially planar (see **FIG. 1**). The carriage **103** can have a rectangular shape (see **FIG. 2**). It is to be understood that the carriage **103** is not limited to the size or shape in the shown examples. For instance, in further examples, the carriage **103** could include a substantially square, oval, circular shape, or the like. Similarly, the carriage **103** is not limited to being substantially planar. In further examples, either or both of the first surface **105** and second surface **107** may extend along a plane that is not parallel to the other of the first surface **105** and the second surface **107**. In one example, the second surface **107** could include multiple levels, such as a first level that is non-parallel to a second level. The carriage **103** may comprise a number of different materials, including plastic, or the like. Furthermore, the carriage **103** can comprise a single, integrally formed structure, or multiple structures that, together, comprise the carriage **103**.

[0024] As shown in **FIG. 2**, the carriage **103** can comprise a main support portion **201** and a second support portion **203**. The main support portion **201** and the second support portion **203** can be removably attached to each other, such that the main support portion **201** and the second support portion **203** comprise separate pieces. The main support portion **201**

can include a recess, cavity, or the like that is sized and shaped to receive the second support portion **203**.

[0025] The second support portion **203** can be removably attached to the main support portion **201**. Specifically, the second support portion **203** can be selectively attached (see **FIGS. 2 and 3**) or removed (see **FIG. 6**) from the main support portion **201**. The second support portion **203** can be sized and shaped to fit within the recess of the main support portion **201**. As such, when the second support portion **203** is attached to the main support portion **201**, the main support portion **201** and the second support portion **203** are substantially flush with each other such that a substantially planar surface is formed. The second support portion **203** can be rectangularly shaped, though, other sizes and shapes are configured. For instance, the second support portion **203** could be larger or smaller in size, and/or could take on a number of shapes, such as a square shape, half-circle shape, etc. It is to be understood that the recess in the main support portion **201** can be sized and shaped to match the shape in the second support portion **203**. Accordingly, in one example, the recess in the main support portion **201** can comprise a rectangular shape when the second support portion **203** can comprise a similar rectangular shape.

[0026] The main support portion **201** and the second support portion **203** can be attached, such as removably attached, to each other using any number of attachment structures. In one example, a tongue and groove structure may be provided wherein one of the support portions includes the tongue and the other of the support portions includes the groove. For instance, as shown in **FIG. 3**, the main support portion **201** can include a groove **303** while the second support portion **203** can include a tongue **301**. The tongue **301** can protrude from a side of the second support portion **203**. The tongue **301** can extend partially or completely around the second support portion **203**. It is contemplated that a single tongue **301** can be provided extending partially or completely around the second support portion **203** or a plurality of tongues be provided extending partially or completely around the second support portion **203**. The tongue **301** can be provided on the side of the second support portion **203** that makes contact with and engages with the groove **303** of the main support portion **201**. As such, the tongue **301** can project outwardly along one side, two sides, or three sides of the second support portion **203**. The tongue **301** can comprise a square shape, as shown, or can include a variety of other shapes, such as a triangle, rectangle, or the like.

[0027] The main support portion **201** can include the groove **303** that may extend partially or completely around a side of the recess. The groove **303** can be sized and shaped

to match or be slightly larger than the size and shape of the tongue **301** of the second support portion **203**. The groove **303** can project inwardly from the side of the recess towards an interior portion of the main support portion **201**. The groove **303** can extend along portions of the recess that match the locations of the tongue **301**. For instance, if the tongue **301** extends along three sides of the second support portion **203**, then the groove **303** can extend along all three sides of the recess. As such, the tongue **301** can engage and project into the groove **303** when the second support portion **203** is attached to the main support portion **201**.

[0028] In another example, a snapping connection, latching mechanism or other attachment mechanism may be used to attach the main support portion **201** to the second support portion **203**. Furthermore, removable attachment may be provided wherein the second support portion **203** may be subsequently removed from the main support portion **201** sometime after attachment. Moreover, attachment may limit, such as prevent relative movement between the main support portion **201** and the second support portion **203**. For example, the tongue and groove arrangement may prevent limit movement in one direction while allowing sliding movement during the attachment step. Moreover, once in the appropriate position, a snapping connection may be provided to help inhibit premature removal of the second support portion from the main support portion. In further examples, the attachment may be permanent wherein, once attached, removal of the second support portion from the main support portion may not be possible without damaging the support portions.

[0029] In still further examples, the second support portion may be an optional component or may not be provided at all. As such, the entire support portion may comprise a single support portion. Alternatively, the second support portion may be provided as an optional attachment to increase the quantity of containers that may simultaneously undergo the separation procedure.

[0030] As shown in **FIG. 2**, the carriage **103** can further include one or more openings **205**. In one example, the one or more openings **205** can extend completely through the carriage **103** (see **FIG. 3**) from the first surface **105** to the second surface **107**. In one example, the openings **205** comprise circular shapes although other shapes may be used in further examples. Moreover, the openings may include substantially identical dimensions (e.g., internal diameters if circular) to accommodate containers of similar or identical sizes. Alternatively, the openings may include different dimensions (e.g., different internal diameters) to allow processing of containers having different sizes. As shown, the one or

more openings **205** can include a structure for fixedly mounting with a container. For example, as shown, the openings **205** can each include the illustrated internal thread, along an internal surface of the one or more openings **205**. As such, in the illustrated example, the one or more openings **205** can comprise threaded openings although other fixing structures may be provided in further examples.

[0031] The one or more openings **205** are shown to include a plurality of openings **205** and, more specifically, twelve openings although any number of one or more openings may be provided in accordance with aspects of the disclosure. A portion of the one or more openings **205** can extend along a first axis **207a** while another portion of the one or more openings **205** can extend along a separate second axis **207b**. As shown in **FIG. 2**, a first set of six of the one or more openings **205** can extend along a substantially linear first axis **207a** that is positioned on the main support portion **201**. A second set of six of the one or more openings **205** can extend along a substantially linear second axis **207b** positioned on the second support portion **203**. The one or more openings **205** are not limited to extending along a linear axis, and could extend along a non-linear axis, such as by being staggered, or the like.

[0032] The one or more openings **205** are not limited to twelve openings as shown, and could include more openings or fewer openings. For instance, the first set of the one or more openings **205** could include more than six openings or less than six openings while the second set of the one or more openings **205** could similarly include more than six openings or less than six openings. Each of the one or more openings **205** can be spaced apart from an adjacent opening **205**. In one example, spacing between adjacent openings **205** could be around 18 millimetres, however, a variety of distances is contemplated. Moreover, as shown, the spacing of the openings **205** is identical although different spacings may be provided in further examples.

[0033] As shown in **FIG. 4**, the carriage **103** can further include legs **401**. The legs **401** can be formed integrally with the carriage **103** as a single piece or, in the alternative, can be separately attached. As shown, the legs **401** can be attached to the first surface **105**, for example, by the illustrated threaded connection, and can project outwardly from the first surface **105**. The legs **401** can be positioned at opposing ends of the carriage **103** although the legs may be positioned at other locations, such as central portions of the carriage. The legs **401** can include any number of legs. For instance, **FIG. 4** illustrates an example with a total of four legs with two legs positioned at one end and two legs positioned at an opposing

end. However, the legs **401** could a total of two or more legs in a wide range of locations. Providing two or more legs can help inhibit rotation of the carriage. In further examples, a single leg may be provided. In such examples, the leg may have a noncircular shape to prevent relative rotation of the carriage with respect to other parts of the magnetic separation device **101**. As such, the legs **401**, if provided, can take on a variety of sizes, shapes, and lengths, and are not limited to the shown examples.

[0034] Referring back to **FIG. 1**, the magnetic separation device **101** can further include a base **109** that, in one example, can be removably attached to the carriage **103**. The base **109** can include a supporting structure **111** (see **FIG. 3**). The supporting structure **111** can comprise a substantially planar structure although nonplanar configurations may be use. A planar structure may be desired in examples where the magnetic separation device **101** is to be supported on a planar surface, such as a table. In such examples, the orientation of the containers being supported by the magnetic separation device **101** can be adjusted or maintained at a desired orientation during separation. As such, the supporting structure **111** can include a first side **113** and a second side **115** that is opposite from the first side **113**. In one example, at least the second side **115** can be substantially planar, such that the second side **115** can be placed on a flat surface and support the magnetic separation device **101**.

[0035] The supporting structure **111** can have a rectangular shape, though other sizes and shapes are contemplated. In one example, the supporting structure **111** can include a size, shape, length and/or width that is substantially similar or identical to the size, shape, length, and/or width of the rectangular carriage **103**. In further examples, the supporting structure **111** can comprise a substantially square, oval, circular shape, or the like.

[0036] In addition or alternatively to the openings **205** in the carriage **103**, as shown in **FIG. 3**, the supporting structure **111** of the base **109** can further or alternatively include one or more base openings **305**. The base openings **305** can be positioned on the first side **113** of the supporting structure **111** and can extend partially or completely through the supporting structure **111**. In the shown example, the base openings **305** can extend from the first side **113** at a surface of the supporting structure **111** to an interior portion of the supporting structure **111**. The base openings **305** can be substantially similar or identical in structure to the one or more openings **205** in the carriage **103**. For instance, the base openings **305** can comprise a circular shape. The base openings **305** can further include a threading positioned along an internal surface of the base openings **305**, such that the base

openings **305** comprise threaded openings. The base openings **305** are shown to include a female threading, but as with the openings **205**, are not limited to the structure as shown.

[0037] The base openings **305** can be positioned to follow the pattern of the one or more openings **205** in the carriage **103** in **FIG. 2**. Specifically, the an axis extending through a center of each of the one or more openings **205** can extend through a center of one of the base openings **305** positioned on the supporting structure **111**. Accordingly, the base openings **305** can be positioned directly underneath the one or more openings **205**. As such, either of the openings **205**, **305** may be used to provide appropriate alignment of the container as discussed more fully below. Moreover, while the illustrated example shows the magnetic separation device including both carriage openings **205** and base openings **305**, in further examples, the magnetic separation device may only include base openings **305** or may only include carriage openings **205**. Still further, although a removable carriage **103** is illustrated, in further examples, a support member may be provided that is integral or otherwise attached to the base. In such examples, the openings **205** may be an integral part of the entire magnetic separation device wherein the openings may not be move relative to the magnets that can be provided in examples provided with a carriage.

[0038] As shown in **FIG. 1**, the base **109** may be provided with a pair of lateral support members **117**. If provided, the lateral support members **117** can extend from the first side **113** of the supporting structure **111** in a direction extending away from the first side **113**. The lateral support members **117** can be positioned at opposing ends of the supporting structure **111**. The lateral support members **117** are positioned such that an open area can extend between the lateral support members **117**. Although not required in all examples, the lateral support members **117** may provide increased rigidity and/or help protect containers fixed to the magnetic separation device.

[0039] The lateral support members **117**, if provided, can further include one or more leg openings **403** for receiving the legs **401** of the carriage **103**. The leg openings **403** can comprise a recess, opening, aperture, or the like, and can extend partially through the lateral support members **117**. The leg openings **403** can be sized and shaped to receive the legs **401**, and could be slightly larger in size than the legs **401** such that a snug fit between the legs **401** and the leg openings **403** can be provided. Similarly, the number of leg openings **403** in the supporting structure **111** can be equal to or greater than the number of legs **401** provided in the carriage **103**. Providing more leg openings than legs can provide optional mounting

capability for the carriage **103**. Alternatively, providing the same number of leg openings as legs can guarantee proper alignment of the containers relative to the magnet elements.

[0040] The legs **401** can be selectively inserted and removed from the leg openings **403**. For instance, when the legs **401** are inserted into the leg openings **403**, such as in an attached position, the carriage **103** is mounted to the base **109**. In the attached position, lateral movement of the carriage **103** is limited, and, in some examples, the carriage **103** can be designed for selective movement in the vertical direction. In one example, the carriage **103** is latched into position wherein the carriage resists vertical movement to slide the legs **401** out of the leg openings **403**. If desired, the carriage may be unlatched, such that the carriage **103** can be removed from the base **109** by moving the carriage **103**, such as by lifting, in the direction longitudinal to the direction along which the legs **401** and leg openings **403** extend. As such, the carriage **103** can be moved between an attached and detached position with respect to the base **109**.

[0041] As shown in **FIG. 1**, the base **109** can further include a central support member **119**. The central support member **119** can extend from the first side **113** of the supporting structure **111** in a direction substantially perpendicular to the first side **113**. The central support member **119** can extend between the optional lateral support members **117**. More specifically, the central support member **119** can be attached and/or integrally formed with one of the lateral support members **117** at one end and with the other of the lateral support members **117** at an opposing end. The central support member **119** can extend along a length of the supporting structure **111**. In one example, the central support member **119** can extend from a midpoint of the supporting structure **111** (see **FIG. 3**). However, it is to be understood that the central support member **119** can be offset from the midpoint of the supporting structure **111** in further examples. The central support member **119** can be formed as a single piece with the supporting structure **111** and/or the lateral support members **117** or can be attached as a separate piece. Similar to the lateral support members **117**, the central support member **119** can be attached to the supporting structure **111** and/or to the lateral support members **117** with any number of attachment structures, such as adhesives, screws, snap fit means, or the like.

[0042] Referring to **FIGS. 1** and **3**, the central support member **119** can further include one or more magnet openings **121**. The magnet openings **121** can extend partially or completely across the central support member **119**. The magnet openings **121** can comprise a first row and a second row of magnet openings **121**. As shown, each of the first row and the

second row can include six magnet openings **121**. The magnet openings **121** can be aligned in a column defined by a separating axis **125a**, such that there are six columns. Specifically, one magnet opening **121** can be positioned above a second magnet opening **121** with the separating axis **125a** extending through the two magnet openings **121**. Likewise, another pair of magnet openings **121** may be aligned along another separating axis **125b** adjacent to the first separating axis **125a**. The separating axis **125a**, **125b** can be perpendicular to the first surface **105** and the first side **113**. While only one separating axis **125** is shown, it is to be understood that each of the columns having magnet openings **121** is oriented substantially identically with respect to a corresponding separating axis. In addition, one of the one or more openings **205** and one of the one or more base openings **305** can be aligned with a column of the magnet openings **121**. As such, a corresponding separating axis **125a**, **125b** can extend through each of the one opening **205**, one base opening **305**, and two magnet openings **121**.

[0043] It is to be understood that the number of magnet openings **121** and the number of rows of magnet openings **121** is not limited to the example described herein. For instance, more magnet openings **121** or fewer magnet openings **121** are contemplated. Similarly, more than two rows of magnet openings **121** or as few as one row of magnet openings **121** are also contemplated.

[0044] As shown in **FIGS. 1** and **3**, the base **109** can support one or more magnetic elements **123**. The magnetic elements **123** can be mounted to the central support member **119** of the base **109** by being inserted into the magnet openings **121**. The magnetic elements **123** can be sized to have a diameter that is slightly larger than a diameter of the magnet openings **121**. As such, the magnetic elements **123** can be press fit or otherwise secured to the magnet openings **121** without falling out. In a further example, an attachment structure can assist in attaching the magnetic elements **123** to the magnet openings **121**. The attachment structure could include an adhesive, epoxy, snap fit means, or the like, that can provide additional support in attaching the magnetic elements **123** to the magnet openings **121**. It is to be understood that the magnetic elements **123** are not limited to being positioned within the central support member **119**. In further examples, one or more of the lateral support members **117** and/or the supporting structure **111** could include one or more magnetic elements **123**.

[0045] Once attached to the magnet openings **121**, the magnetic elements **123** are positioned at the same location as the magnet openings **121**. More specifically, the magnetic

elements **123** can be oriented in a plurality of columns, with two magnetic elements **123** in each column. As such, one magnetic element **123** can be positioned above a second magnetic element with the separating axis **125** extending through the two magnetic elements **123**. Accordingly, as described above, the separating axis **125** can extend through each of the one opening **205**, one base opening **305**, and the column having two magnetic elements **123**. Providing a plurality of magnetic elements **123** along the separating axis **125** can help facilitate separation of magnetic material **603** from a relatively long container **501** discussed and illustrated with respect to **FIG. 6** below. Furthermore, a plurality of magnetic elements **123** along the separating axis **125** can allow relatively short containers to be used. For instance, with reference to **FIG. 6**, a much shorter container **501** may be used, wherein the upper magnetic element **123** can still be effective to facilitate separation of the magnetic material from the relatively short containers. Furthermore, at least one of the magnetic elements **123** can be designed to be positioned adjacent the lower end of the container. As such, the magnetic elements **123** may act on the magnetic material that collects near the bottom of the container under the influence of gravity to make use of the magnets more effective.

[0046] Moreover, as shown in **FIG. 3**, the ends of the magnetic elements **123** can be flush with corresponding surfaces of the central support member **119**. In further examples, the ends of the magnetic elements **123** may be recessed within the corresponding surfaces of the central support member **119**. In still further examples, the ends of the magnetic elements **123** may protrude from the corresponding surfaces of the central support member **119**. In some examples, the magnetic elements **123** may be mounted such that the ends of the magnetic elements **123** protrude a predetermined distance from the surfaces of the central support member **119**. As such, the ends of the magnetic elements **123**, in some examples, may be designed to engage or be positioned immediately adjacent to containers **501** discussed below to help facilitate attraction of magnetic material **603** as discussed below.

[0047] The magnetic elements **123** can include a number of different magnetic materials that can produce a magnetic field. For instance, the magnetic elements **123** can comprise a permanent magnet, an electro magnet, a rare earth magnet, or the like. Similarly, while a plurality of magnetic elements **123** are shown in the illustrated examples, it is to be understood that a single magnetic element could be provided instead. The magnetic elements **123** are attached to the base **109** can produce a magnetic field. As shown in **FIG. 3**, a single

magnet may be provided to present a field at opposite sides of the central support member **119** although a plurality of magnets may be provided in further examples.

[0048] Referring to **FIGS. 5-7**, the magnetic separation device **101** accommodates a container **501**. The container **501** can include a variety of structures that can hold a substance. The container **501** can be substantially circular and have a wall surrounding an interior area **605**. The container **501** can include an opening **503** positioned at one end such that the interior area **605** can be accessed through the opening **503**. In the shown examples, the container **501** can further include a threaded portion **505**. The threaded portion **505** can be positioned at either or both ends of the container **501**. For instance, the threaded portion **505** can be disposed at the end of the container **501** that is adjacent the opening **503** (see **FIG. 5**). In another example, a container **1001** can include a threaded portion **1003** that is disposed at an end of the container **1001** that is opposite from an opening **1005** (see **FIG. 10**). In yet another example, both ends of a container could include threaded portions.

[0049] The threaded portion **505**, **1003** can be sized to be threadingly received by either of the one or more openings **205** in the carriage **103** or the base openings **305** in the base **109**. For instance, when the threaded portion **505**, **1003** is received by the one or more openings **205** or the base openings **305**, then the container **501**, **1001** can be fixedly suspended from the carriage **103** (e.g., see **FIGS. 6-7**) or fixedly supported by the base **109** (e.g., see **FIG. 11**). By being fixedly suspended or fixedly supported, the container **501**, **1001** can be prevented from being inadvertently detached from the carriage **103** and/or the base **109**. Moreover, the aligned orientation of the container **501**, **1001** can be maintained while pouring out the liquid after separation has been obtained within the container. In one example, the threaded portions **505**, **1003** can comprise a male threaded portion while the one or more openings **205** and the base openings **305** can comprise female receiving threaded portions. As such, the threaded portion **505**, **1003** of the container **501**, **1001** can be attached to either of the carriage **103** or the base **109** by screwing the threaded portion **505**, **1003** into one of the one or more openings **205** or the base openings **305**. Once the threaded portion **505**, **1003** is threadingly received by the one or more openings **205** or the base openings **305**, the container **501**, **1001** is fixedly attached to the carriage **103** or the base **109**.

[0050] Referring now to **FIGS. 6** and **7**, the container **501**, **1001** can receive a material, such as a liquid, fluid, solid, or the like, through the opening **503**, **1005**. Once the material is inserted through the opening **503**, **1005**, the material can be held within the interior area **605**. The material can comprise a mixture including either or both of a non-

magnetic material **601** and a magnetic material **603**. The non-magnetic material **601** can include a variety of materials, such as a liquid, fluid, or the like. For instance, the non-magnetic material **601** can include, but is not limited to, a biological solution such as blood, urine, tissue, cells, macromolecules such as nucleic acid cell based assays, antibody and protein purifications, or the like. The magnetic material **603**, which can include magnetic beads or the like, can be added to the non-magnetic material **601** in the container **501**, **1001**. After the non-magnetic material **601** and the magnetic material **603** are added, the magnetic material **603** can attract a desired material from the non-magnetic material **601**. The desired material can attach to the magnetic material **603**, such that the desired material is separated from the non-magnetic material.

[0051] Methods of separating the non-magnetic material **601** from the magnetic material **603** can now be discussed with reference to the carriage **103** of **FIG. 5**. As shown, the container **501** can initially be provided having the non-magnetic material **601** and the magnetic material **603** within the interior area **605**. Either the non-magnetic material **601** or the magnetic material **603** can be added first to the container **501** through the opening **503** or, alternatively, the non-magnetic material **601** and the magnetic material **603** can be added together at the same time, such as in a mixture. The non-magnetic material **601** and the magnetic material **603** can interact with each other, such that a quantity of the non-magnetic material **601**, which may include the desired material, can engage and/or bind with the magnetic material **603**.

[0052] The carriage **103** can optionally initially rest on a surface **511** while remaining detached from the base **109**. An end cap **507** can be removed from the threaded portion **505** of the container **501**. The container **501** can be aligned with one of the one or more openings **205** in the carriage **103**. The container **501** can be rotated in a direction **509** such that the threaded portion **505** rotatably and threadingly engages the one of the one or more openings **205**. It is to be understood that the direction **509** could be clockwise or counterclockwise, and the arrow in the shown example is not intended to be limiting. The container **501** can continue to be rotated until the container **501** is fixedly mounted to the carriage **103**. Accordingly, the container **501** can be fixedly mounted to the carriage **103** by screwing the threaded portion **505** into the threaded opening **205** of either or both of the main support portion **201** or the second support portion **203**. Once the container **501** is fixedly mounted to the carriage **103**, the opening **503** in the container **501** can extend at least partially through the opening **205** in the carriage **103**. In further examples, the container **501** can be screwed

into the carriage **103** such that the edge defining the opening **503** is substantially flush with the second surface **107**. In this example, the opening **503** may not extend past the second surface **107**, such that the second surface **107** and edges of the opening **503** form a substantially planar surface.

[0053] Referring now to **FIG. 6**, the method can then optionally proceed to the step of fixedly mounting the container **501** in an aligned orientation relative to the magnetic elements **123**. After the container is fixedly mounted to the carriage **103**, the carriage **103** can be attached to the base **109**, such as by inserting the legs **401** into the leg openings **403**. Once attached, the container **501** can be retained in the aligned orientation relative to the magnetic elements **123**. As shown, the container **501** can project from the main support portion **201** towards the supporting structure **111**. The container can extend along a side of the central support member **119** such that the container is in proximity to the magnetic elements **123**. Accordingly, in the aligned orientation, the container **501** can project parallel to and along the separating axis **125** such that the container **501** is positioned close enough in proximity to the magnetic elements **123** that the contents of the container **501** can be at least partially within the magnetic field. In this example, while in the aligned orientation, the contents of the container, including either or both of the non-magnetic material **601** and the magnetic material **603**, can be influenced by the magnetic field and the magnetic elements **123**.

[0054] Referring now to **FIG. 7**, the method can then optionally proceed to the step of attaching the second support portion **203** to the main support portion **201**. While **FIG. 6** does not include the second support portion **203**, it is to be understood that the second support portion **203** can optionally be provided, or, in the alternative, the carriage **103** may not include the second support portion **203**. In the shown example of **FIG. 7**, the container **501** can be fixedly mounted to the second support portion **203**. It is to be understood, however, in further examples, that the second support portion **203** may not include the container **501** and could be attached to the main support portion **201** with some or all of the openings **205** not having containers **501**. Accordingly, the second support portion **203** can be attached to the main support portion **201** independently of the presence of containers **501** attached to the second support portion **203** and/or the main support portion **201**.

[0055] The second support portion **203** can be attached to the main support portion **201** by inserting the second support portion **203** in a direction transverse to the central axis **307** (see **FIG. 3**). The second support portion **203** can first be aligned with the recess in the main support portion **201**. Next, the second support portion **203** can be moved towards the

main support portion **201** in the transverse direction, such as perpendicular to, the central axis **307**. The second support portion **203** can be moved into engagement with the main support portion **201** until the groove **303** receives the tongue **301**. Once the tongue **301** partially or fully enters the groove **303**, the second support portion **203** is attached to the main support portion **201**.

[0056] If the second support portion **203** includes one or more containers **501**, the one or more containers can be in the aligned orientation once the second support portion **203** is attached to the main support portion **201**. Similar to the example discussed above with respect to **FIG. 6**, the containers **501** that are attached to the second support portion **203** can project parallel to and along the separating axis **125a**, **125b** such that the containers **501** are positioned close enough in proximity to the magnetic elements **123** that the contents of the containers **501** can be at least partially within the magnetic field. Accordingly, in the aligned orientation, the contents of the containers **501** held by the second support portion **203**, including either or both of the non-magnetic material **601** and the magnetic material **603**, can be influenced by the magnetic field and the magnetic elements **123**.

[0057] Referring now to **FIGS. 6** and **7**, the method can then optionally proceed to the step of attracting the magnetic material **603** to an interior surface of the container **501** while the container **501** is in the aligned orientation. Since the non-magnetic material **601** and the magnetic material **603** can each be influenced by the magnetic field and the magnetic elements **123** in the aligned orientation, the magnetic material **603** can be attracted towards the magnetic elements **123**. As shown, the magnetic material **603** can accumulate on or near an interior surface surrounding the interior area **605** that is closest in proximity to the magnetic elements **123**. The magnetic material **603** can accumulate along a portion or substantially the entire length of the container **501** at the interior surface.

[0058] Referring now to **FIG. 8**, the method can then optionally proceed to the step of repositioning the container **501** to pour a quantity of the non-magnetic material **601** out of the interior area **605** while retaining a quantity of the magnetic material **603** within the interior area **605**. The magnetic separation device **101** can be repositioned, such as by rotating or inverting the magnetic separation device **101**. When the magnetic separation device **101** is repositioned, the container **501** can also be repositioned since the container is attached to the carriage **103**. The container **501** can remain in the aligned orientation even while repositioned, rotated, or the like, due to the container **501** being fixedly attached to the carriage **103**. As such, in the aligned orientation, the magnetic material **603** can remain

attracted to the interior surface of the container **501** even when pouring out the non-magnetic material **601**.

[0059] When the container **501** is repositioned, the magnetic material **603** can remain attracted to the interior surface of the container **501** while a quantity of the non-magnetic material **601** can be poured out of the container **501** through the opening **503**. A separate quantity of the non-magnetic material **601**, which can include the desired material, can remain attached to the magnetic material **603** within the container **501**. As such, a quantity of the non-magnetic material **601** is poured out of the container while a second quantity of the non-magnetic material remains attached to the magnetic material **603** on the interior surface of the container **501**.

[0060] The quantity of non-magnetic material **601** can be poured into a receiving device **801**. The receiving device **801** is only generically/schematically shown, and is not limited to the examples shown herein. For instance, the receiving device **801** can include nearly any type of receptacle (e.g., dish, tube, bottle, or the like). Similarly, while one receiving device **801** is shown, a plurality of receiving devices can be provided such that the receiving device **801** can comprise one or more receiving devices.

[0061] Referring now to **FIG. 9**, the method can then optionally proceed to the step of depositing a quantity of the non-magnetic material **601** onto an absorbent material **901**. After a majority of the non-magnetic material **601** has been removed from the container **501**, an excess quantity of non-magnetic material **601** can further be removed from the container **501**. In this example, the absorbent material **901** can be provided and positioned underneath one or more of the openings **503**. A user can shake, tap, and/or move the magnetic separation device **101** such that the excess quantity of the non-magnetic material **601** can pour out of the opening **503** and onto the absorbent material **901**. At the same time, the container **501** can retain the aligned orientation such that the magnetic material **603** can remain attracted to the interior surface of the container **501** due to the fixed attachment.

[0062] Referring now to **FIGS. 10-13**, further example methods of separating the non-magnetic material **601** from the magnetic material **603** can now be discussed. In this example method, the container **1001** can be attached to the base **109** instead of the carriage **103**. The attachment and pouring steps can be substantially the same and/or identical to the steps described above, but will be described in detail below.

[0063] As shown in **FIG. 10**, the container **1001** can include the opening **1005** at a first end and the threaded portion **1003** at an opposed second end. The container **1001** can

initially be provided having the non-magnetic material **601** and the magnetic material **603** within the interior area **605**. Either the non-magnetic material **601** or the magnetic material **603** can be added first to the container **1001** through the opening **1005** or, alternatively, the non-magnetic material **601** and the magnetic material **603** can be added together at the same time, such as in a mixture. The non-magnetic material **601** and the magnetic material **603** can interact with each other, such that a quantity of the non-magnetic material **601**, which may include the desired material, can engage and/or bind with the magnetic material **603**.

[0064] The base **109** can initially rest on a surface while remaining detached from the carriage **103** although the carriage may not be used. The end cap **507** (see **FIG. 5**) can be removed from the threaded portion **1003** of the container **1001**. The container **1001** can be aligned with one of the one or more base openings **305** in the base **109**. The container **1001** can be rotated in a direction **509** such that the threaded portion **1003** rotatably and threadingly engages the one of the one or more base openings **305**. The container **1001** can continue to be rotated until the container **1001** is fixedly mounted to the base **109**. Accordingly, the container **1001** can be fixedly mounted to the base **109** by screwing the threaded portion **1003** into the base opening **305** of the base **109**.

[0065] Referring now to **FIG. 11**, the method can then optionally proceed to the step of fixedly mounting the container **1001** in an aligned orientation relative to the magnetic elements **123**. After the container **1001** is fixedly mounted to the base **109**, the carriage **103** can optionally be attached to the base **109**, such as by inserting the legs **401** into the leg openings **403**. Once attached, the container **1001** can be retained in the aligned orientation relative to the magnetic elements **123**. As shown, the container **1001** can extend along a side of the central support member **119** such that the container **1001** is in proximity to the magnetic elements **123**. Accordingly, in the aligned orientation, the container **1001** can project parallel to and along the separating axis **125a**, **125b** such that the container **1001** is positioned close enough in proximity to the magnetic elements **123** that the contents of the container **1001** can be at least partially within the magnetic field. In this example, while in the aligned orientation, the contents of the container **1001**, including either or both of the non-magnetic material **601** and the magnetic material **603**, can be influenced by the magnetic field and the magnetic elements **123**.

[0066] Referring still to **FIG. 11**, the method can then optionally proceed to the step of attracting the magnetic material **603** to an interior surface of the container **1001** while the container **1001** is in the aligned orientation. Since the non-magnetic material **601** and the

magnetic material **603** can each be influenced by the magnetic field and the magnetic elements **123** in the aligned orientation, the magnetic material **603** can be attracted towards the magnetic elements **123**. As shown, the magnetic material **603** can accumulate on or near an interior surface surrounding the interior area **605** that is closest in proximity to the magnetic elements **123**. The magnetic material **603** can accumulate along a portion or substantially the entire length of the container **1001** at the interior surface.

[0067] Referring now to **FIG. 12**, the method can then optionally proceed to the step of repositioning the container **1001** to pour a quantity of the non-magnetic material **601** out of the interior area **605** while retaining a quantity of the magnetic material **603** within the interior area **605**. The magnetic separation device **101** can be repositioned, such as by rotating or inverting the magnetic separation device **101**. When the magnetic separation device **101** is repositioned, the container **1001** can also be repositioned since the container is attached to the base **109**. The container **1001** can remain in the aligned orientation even while repositioned, rotated, or the like, due to the container **1001** being fixedly attached to the base **109**. As such, in the aligned orientation, the magnetic material **603** can remain attracted to the interior surface of the container **1001**.

[0068] When the container **1001** is repositioned, the magnetic material **603** can remain attracted to the interior surface of the container **1001** while a quantity of the non-magnet material **601** can be poured out of the container **1001** through the opening **1005**. A separate quantity of the non-magnetic material **601**, which can include the desired material, can remain attached to the magnetic material **603** within the container **1001**. As such, a quantity of the non-magnetic material **601** is poured out of the container while a second quantity of the non-magnetic material remains attached to the magnetic material **603** on the interior surface of the container **1001**. The quantity of non-magnetic material **601** can be poured into the receiving device **801** as described above. Referring now to **FIG. 13**, the method can then optionally proceed to the step of depositing a quantity of the non-magnetic material **601** onto the absorbent material **901** as described above. As mentioned previously, a user can shake, tap, and/or move the magnetic separation device **101** such that the excess quantity of the non-magnetic material **601** can pour out of the opening **1005** and onto the absorbent material **901**. At the same time, the container **1001** can retain the aligned orientation such that the magnetic material **603** can remain attracted to the interior surface of the container **1001** due to the fixed attachment of the container **1001** with the base **109**.

[0069] As explained herein, the container **501**, **1001** can be fixedly attached to a first support portion of the magnetic separation device **101**. It is to be understood that the first support portion can include either of the base **109**, the carriage **103** and/or another support portion of the device. For instance, when the container **501**, **1001** is attached to the base **109**, then the base **109** can be considered the first support portion. In the alternative, when the container **501**, **1001** is attached to the carriage **103**, then the carriage **103** can be considered the first support portion. Similarly, the first support portion could further include either of the main support portion **201** and/or the second support portion **203**. For instance, when the container **501**, **1001** is attached to the main support portion **201**, then the main support portion **201** can be considered the first support portion. In the alternative, when the container **501**, **1001** is attached to the second support portion **203**, then the second support portion **203** can be considered the first support portion. As such, the first support portion is not limited to a specific structure, and could include any part of the magnetic separation device **101** to which the container **501**, **1001** can be attached.

[0070] It will be apparent to those skilled in the art that various modifications and variations can be made without departing from the spirit and scope of the claimed invention.

CLAIMS

What is claimed is:

1. A magnetic separation device comprising:
at least one magnetic element configured to produce a magnetic field; and
a first support portion including a threaded opening configured to threadingly receive a threaded portion of a container to fixedly attach the container to the first support portion in an aligned orientation with respect to the magnetic element, wherein the threaded opening is configured to retain the container in the aligned orientation when inverting the magnetic separation device.
2. The magnetic separation device of claim 1, wherein the threaded opening extends entirely through the first support portion, wherein the threaded opening is configured to fixedly suspend the container in the aligned orientation.
3. The magnetic separation device of claim 1, wherein the first support portion comprises a base and the magnetic element is supported by the base.
4. The magnetic separation device of claim 1, further comprising a base and the magnetic element is supported by the base.
5. The magnetic separation device of claim 4, further comprising a carriage including the first support portion, wherein the carriage is configured to be mounted with respect to the base such that the container is in the aligned orientation.
6. The magnetic device of claim 5, further comprising a second support portion including a threaded opening configured to threadingly receive a threaded portion of a container to fixedly attached the container to the second support portion, wherein the second support portion is configured to be releasably attached to the first support portion.
7. A method of separating a non-magnetic material from magnetic material comprising the steps of:

inserting a non-magnetic material and a magnetic material into an interior area of a container;



fixedly mounting the container in an aligned orientation relative to a magnetic element;



attracting the magnetic material to an interior surface of the container while the container is in the aligned orientation; and

repositioning the container to pour a quantity of the non-magnetic material out of the interior area of the container while retaining a quantity of the magnetic material within the interior area, wherein the container remains in the aligned orientation while repositioning the container.

8. The method of claim 7, wherein the step of fixedly mounting the container includes mounting a threaded portion of the container into a threaded opening of a support portion.

1 / 7





3 / 7




FIG. 5




FIG. 6

4 / 7




FIG. 7




FIG. 8

5 / 7




FIG. 9




FIG. 10

6 / 7




FIG. 11




FIG. 12




FIG. 13

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2012/044534

A. CLASSIFICATION OF SUBJECT MATTER
INV. B01L9/06 B03C1/28
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B03C B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 136 126 A2 (CORNING GLASS WORKS [US]) 3 April 1985 (1985-04-03) the whole document -----	1-8
X	EP 0 030 086 A1 (TECHNICON INSTR [US]) 10 June 1981 (1981-06-10) the whole document -----	1-8
X	WO 90/14891 A1 (DYNAL AS [NO]) 13 December 1990 (1990-12-13) the whole document -----	1-8
X	DE 31 02 029 A1 (EUROP LAB MOLEKULARBIOLOG [DE]) 26 August 1982 (1982-08-26) the whole document ----- -/--	1-8



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

16 November 2012

Date of mailing of the international search report

26/11/2012

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Skaropoulos, N

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2012/044534

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2010/225920 A1 (XIA JIULIN [US] ET AL) 9 September 2010 (2010-09-09) paragraph [0081] - paragraph [0084] -----	1-8
A	WO 83/00932 A1 (BECKMAN INSTRUMENTS INC [US]) 17 March 1983 (1983-03-17) the whole document -----	1-8
A	DE 10 2009 027454 A1 (BOSCH GMBH ROBERT [DE]) 5 January 2011 (2011-01-05) the whole document -----	1-8
A	US 6 558 632 B1 (GUELLER ROLF [CH] ET AL) 6 May 2003 (2003-05-06) the whole document -----	1-8

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2012/044534

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0136126	A2	03-04-1985	CA 1220168 A1 DE 3478665 D1 EP 0136126 A2 JP 1822144 C JP 5022181 B JP 60067858 A	07-04-1987 20-07-1989 03-04-1985 10-02-1994 26-03-1993 18-04-1985
EP 0030086	A1	10-06-1981	CA 1152559 A1 DE 3070333 D1 EP 0030086 A1 US 4438068 A	23-08-1983 25-04-1985 10-06-1981 20-03-1984
WO 9014891	A1	13-12-1990	NO 892202 A WO 9014891 A1	03-12-1990 13-12-1990
DE 3102029	A1	26-08-1982	NONE	
US 2010225920	A1	09-09-2010	NONE	
WO 8300932	A1	17-03-1983	EP 0086833 A1 JP S58501367 A WO 8300932 A1	31-08-1983 18-08-1983 17-03-1983
DE 102009027454	A1	05-01-2011	CN 102470072 A DE 102009027454 A1 EP 2448541 A1 US 2012181285 A1 WO 2011000623 A1	23-05-2012 05-01-2011 09-05-2012 19-07-2012 06-01-2011
US 6558632	B1	06-05-2003	AU 9733398 A CA 2308414 A1 DE 59802862 D1 EP 1027148 A1 JP 2001522714 A US 6558632 B1 WO 9924160 A1	31-05-1999 20-05-1999 28-02-2002 16-08-2000 20-11-2001 06-05-2003 20-05-1999