



(12) UK Patent (19) GB (11) 2 190 936 (13) B

(54) Title of Invention

Flooring panels for free cable laying

(51) INT CL⁴; E04C 2/52

(21) Application No
8703214.0

(22) Date of filing
12 Feb 1987

(30) Priority data

(31) 61124973

(32) 30 May 1986

(33) JP

(43) Application published
2 Dec 1987

(45) Patent published
13 Dec 1989

(73) Proprietor(s)
Kyodo Electric Co Ltd

(Incorporated in Japan)

24-12 Higashi 3-chome
Shibuya-ku
Tokyo
Japan

(72) Inventor(s)
Minoru Yoshida
Hiroshi Yoshida
Toshiro Ishikawa
Minoru Kanosaka
Nobuyuki Ishii

(74) Agent and/or
Address for Service
R G C Jenkins & Co
26 Caxton Street
London SW1H 0RJ

(52) Domestic classification
(Edition J)
E1D DCG2 DF142 DLEKM2
D1071 D1072 D1079 D2132
D422 D431 D509 D532 D903
U1S S1588 S1700 S1706

(56) Documents cited
None

(58) Field of search

As for published application
2190936 A viz:
UK CL E1D
INT CL⁴ E04B E04C
updated as appropriate

1/8

219936

FIG. 1






FIG. 12



2/8

FIG. 2



3/8

FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9





FIG. 10



7/8

2190936

FIG. 11




FIG. 13




FIG. 14





FIG. 15



FLOORING PANELS FOR FREE CABLE LAYINGBACKGROUND OF THE INVENTIONField of the Invention

5 The present invention relates to a flooring panel
and to systems incorporating such panels, and more
particularly to a flooring panel for use in a site for
electrical devices such as computers or office
10 automation devices for laying cables such as power
feed cables, signal cables or communication cables for
interconnecting the computers or devices.

Description of the Prior Art

15 An elevated floor structure has so far been known
as the aforementioned flooring structure adapted for laying
the cables above the permanent floor.

20 As an example, the Japanese Patent Laid-open
Publication No. 112954/1985 discloses an elevated floor
structure comprised of a plurality of flooring panels
supported over a permanent floor by plural spacers such
as blocks or pedestals securely placed on the permanent
floor. The cables of various types such as the power feed
lines, signal lines and the communication lines are laid
25 in the space between the permanent floor and the flooring
panels so as to be pulled at desired locations to the space
above the flooring panels for electrical connection with
the devices or computers.

30 In such previously proposed floor constructions,
the cables tend to be laid in disorder in the space below
the flooring panels. In such case, when the signal or
communication lines or cables are in close proximity to
a power feed line or cable, noises or similar hindrances
may be occasionally produced in the signal or communication
35 lines due to voltages induced from the power feed line.

Above all, the signal or communication lines contacting with the feed line may cause a serious danger to the equipment or human attendants. In addition, such disorderly or hybrid cable laying is not desirable since, when the cable laying is to be changed or a cable or cables are to be annexed at the time of reallocation or extension of the electrical devices, it is rendered difficult to determine to which device a given cable is actually connected.

Moreover, in the aforementioned previously proposed flooring structure, a great deal of skill and labor is required in adjusting the height of the spacer members installed on the permanent floor in order to provide a flat surface of the floor panels. In addition, the horizontal surface thus obtained tends to be deviated from the true level with prolonged usage so that it becomes necessary to perform an operation of re-adjusting the level which again requires considerable skill and labor.

SUMMARY OF THE INVENTION

It would therefore be desirable to provide a floor panel according to which the construction on the permanent flooring and the cable laying operation may be performed efficiently and the interaction between different types of cables may be minimized.

The flooring panel according to a first aspect of the present invention is defined by claim 1 hereinbelow.

According to a second aspect of the present invention there is provided a flooring panel system as defined by claim 19 hereinbelow.

According to a third aspect of the present invention there is provided a flooring panel system as defined by claim 20 hereinbelow.

The flooring panel may be in the form of a plurality of rectangular modular flooring panels having at least one shape and size, and a plurality of at least one type of such modular floor panels are
5 installed on a floor of a building for forming a continuous cable laying space.

Preferably there are formed a plurality of types of the modular flooring panels with different types of cable laying spaces, these modular flooring panels
10 being selectively installed under a cable laying condition such as the volume of cables to be laid.

An additional space may be formed by selective removal of the blocks secured to a flat plate. This additional space may be in communication with the
15 cable laying spaces and used for accommodating cable laying devices or electrical devices. The additional space thus accommodating the electrical devices may be covered with a cover member.

A spacer may be provided at the intersection of
20 the cable laying spaces for separating the intersecting cables from each other.

Each block preferably has holding means for holding a partitioning flat plate member at at least one intermediate position along the height of the
25 blocks, whereby the cable laying space is divided into plural subspaces or layers.

5

10

15 BRIEF DESCRIPTION OF THE DRAWINGS

The objects and features of the present invention will become more apparent from the consideration of the following detailed description taken in conjunction with the accompanying drawings in which:

20

FIG. 1 is a perspective view showing an embodiment of the flooring panel according to the present invention;

25

FIG. 2 is an exploded perspective view of the flooring panel shown in FIG. 1;

FIG. 3 is a sectional view taken along a chain line III-III in Fig. 2;

30

FIGS. 4 and 5 are sectional views, similar to FIG. 3, showing an alternative embodiment of the flooring panel of the present invention;

35

FIGS. 6 and 7 are schematic plan views showing an example of the flooring panels of the present invention

as applied to the construction site;

FIG. 8 is a partially cut-away, perspective view schematically showing an example of the flooring panels of the present invention as applied to the construction site, with a portion being cut away;

FIGS. 9 and 10 are exploded perspective views showing an example of the flooring panel of the present invention operatively connected to an electrical device;

FIG. 11 is a partially cut-away, perspective view showing an alternative embodiment of the flooring panel of the present invention, with one portion being cut away;

FIGS. 12 and 14 are perspective views showing a modification of a cover plate used in the flooring panel of the present invention;

FIG. 13 is an exploded perspective view showing a portion of the flooring panel according to a further alternative embodiment of the present invention; and

FIG. 15 is a schematic plan view showing the flooring panel according to another alternative embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIGS. 1, 2 and 3, a flooring panel 10 according to a specific embodiment of the present invention basically includes a substantially square or rectangular flat sheet 12 of a reduced thickness, a plurality of blocks each being of a substantially cubic form and secured to one of the main surfaces of the sheet 12, and a cover plate 18 for covering cable laying ducts

16a and 16b formed intermediate groups of these blocks 14.

According to the present embodiment, each block 14 is generally of a parallelepipedic form, and preferably made of a solid material, such as hard synthetic material or light-weight concrete prepared by admixing sawdust, foam or perlite into mortar or cement. The blocks may also be in the form of a column as shown in FIG. 11 or in the form of a square pillar or prism as shown in FIG. 13.

The sheet 12 may for example be in the form of a rectangle of 40 cm - 60 cm with a reduced thickness and made of any suitable flexible material such as ordinary or hard synthetic resin, rubber, steel or aluminium. The sheet 12 is used as a substrate on which the plural blocks are securely supported so that it is required to be flexible enough to conform to the natural irregularities of a building floor surface. According to the present embodiment, a plurality of such sheets 12 of the same shape are formed as modules or units, and laid on the floor side by side to cover the permanent building floor having any arbitrary surface measure. It is noted that the sheet may be formed as an elongated sheet strip of a prescribed width or as a flooring having the same shape as the building floor. The panel 10 may be permanently secured to the building floor by an adhesive or a double-sided adhesive tape applied to the lower sides of the blocks 14 and/or the sheets 12. The panel 10 may also be removably secured to the building floor by using transient fasteners such as pressure-sensitive adhesives or surface fasteners.

In the present embodiment, the blocks 14 are arranged in four groups or sections 14a, 14b, 14c and 14d at the four corners of the square sheet 12, as shown, with each group 14a to 14d consisting of plural blocks 14. In

the present embodiment, nine blocks 14 are arranged in a square pattern in each of these sections. If a section is of a reduced area or surface measure, it may consist only of a single block having the same shape as the section,
5 without consisting of a plurality of blocks.

These groups are separated from one the other by the cable laying ducts 16a and 16b in a cruciform having prescribed widths a and b, respectively. Those blocks
10 defining the cable laying ducts 16a and 16b, namely six 14A of the nine blocks 14 of one section confronting to the ducts 16A to 16C in the present embodiment, are each formed with a step or shoulder 26 on one side or both sides forming a corner. The steps 26 are designed to support
15 an edge 28 of the cover plate 18. With the exception of a step 26a of the block 14B to be later described, the height of the steps from the upper surface of the sheet 12 is selected so that the upper surface of the cover plate 18, when placed on the steps 26, runs approximately parallel
20 to or flush with the upper surface of the block 14.

As may be seen from FIG. 3, the blocks 14 are arranged relative to one another so that a small gap or spacing S is defined between the adjacent blocks 14. The
25 spacing S in side elevation may be approximately rectangular as shown in FIG. 3 or V-shaped as shown in FIGS. 4 and 5. In the latter case, the block 14 is in the form of a truncated pyramid. By the provision of the spacing S, the adjacent blocks 14 do not abut on each other even when the
30 sheet 12 becomes flexed due to natural irregularities of the building floor so that the sheet may adapt itself freely to these irregularities.

The blocks 14 may for example be affixed to and
35 held by the upper surface of the sheet 12 by an adhesive,

FIG. 3. These blocks 14 may also be covered with a layer 22 of the same material as the sheet 12. The covering layer 22 is molded with plural recesses having the same shape and pitch as the blocks 14 such that the blocks can be
5 snugly received in these recesses and secured to the layer 22 with an adhesive. When the blocks 14 are formed of mortar, the blocks may be completed by casting the mortar into these recesses. Thus, in this case, the overall surfaces of the block 14 are covered with the sheet 12 and
10 the layer 22.

Alternatively, as shown in FIG. 4, when the blocks 14 are combined and held together by the covering layer 22 cast integrally therewith, the sheet 12 may be omitted.
15 In this case, the upper and lateral sides of the blocks 14 are covered with the sheet 12 and the covering layer 22 such that the blocks 14 are flexibly connected together by the covering layer 22.

20 The cable ducts 16a and 16b are covered with the covering plate 18 which has an overall size not in excess of that of the sheet 12 and a cruciform shape slightly larger than the cable ducts 16a and 16b. The covering plate 18 is formed of a suitable sturdy material, such as steel,
25 aluminium or hard synthetic material, since it is disposed on the upper opening of the wiring channels 16a and 16b for securely supporting various large-size units placed on a raised floor, not shown.

30 The cover plate 18 may be of the size of the flooring panel 10, that is, of approximately the same size as the sheet 12. FIG. 11 illustrates such an embodiment. Also, in the embodiment shown in FIG. 8, the cover plate having the same shape and size as the flooring panel 10
35 may be advantageously placed on the panel. Alternatively,

plural flooring panels 10 may be covered with a sole cover plate. Also, as shown in FIG. 13, the sole square flooring panel 10 may be covered with plural cover plates 18 each having a rectangular form and the size lesser than that of the square flooring panel. Or alternatively, only the cable ducts 16a and 16b included in the sole flooring panel 10 may be covered with a sole cover plate 18, as shown in FIGS. 1 and 12. In such case, the cover plate 18 may be in the shape of a cruciform, a parallel cross or a lattice so as to conform to the shape of the cable ducts 16a and 16b. Still alternatively, the upper opening part of the cable ducts of a sole flooring panel 10 may be covered with plural cover plates.

For example, in the case of the parallel cross shaped cable ducts, four cruciform cover plates may be advantageously employed for separately covering the upper opening part of the cable ducts. If the cable ducts are formed by three vertical channels and two horizontal channels arranged orthogonally to each other, six cruciform cover plates are advantageously employed. Similarly, when the channels are formed by three horizontal and vertical channels arranged in a lattice structure, nine cruciform cover plates are employed. The cover plates in the form of parallel crosses or the cover plates in the cruciform shape may also be combined to conform to the overall shape of the cable ducts. If the flooring panel has a rectangular overall shape and the cable ducts in the form of a lattice or the parallel crosses, two different types of the cruciform cover plates with different lengths of the cruciform arms may be employed in dependence upon the laying pitch or laying interval of the cable ducts.

The upper surface of the cover plate 18 may be coated with a layer of a shock-absorbing material 20. The

layer 20 improves the conformability of the cover plate 18 to the flooring thereon, if any, and to the blocks 14 and the walking feel. The layer 20 may be applied to the upper surface of the cover plate 18 by coating a synthetic resin film or depositing short fibers of synthetic resin by electro-static implanting.

When the layer 20 is applied to the cover plate 18 as the electro-statically implanted short fibers, a top layer 48 laid on the whole structure of flooring panel 10 inclusive of the cover plate 18 tends to be affixed well to the implanted fiber layer 20, resulting in frictional engagement with and hence the correct positioning on the layer 20 of the top layer 48. This in turn results in preventing the top layer 48 from shifting horizontally under the walking shock. When the top layer 48 is properly held in this manner, any fasteners used conventionally for securing the top layer 48 may be dispensed with so that the top layer 48 can be laid efficiently.

The flooring panel 10 is laid on the permanent building floor, and the cables 50 are then housed in the cable ducts 16a and 16b as required and covered with the cover plate 18, which is finally covered with the upper plate 48. The cables 50 may be branched at any intermediate point by a cable outlet 34, FIG. 2, while the connection between an outlet 60 and an electrical component may be achieved by a cable laying fixture 56, FIG. 9.

In the embodiment shown in FIG. 1, the cover plate 18 is in a cruciform shape. The cover plate 18 may have for example a circular opening 24 in one of its arms for pulling out the cable 50, FIG. 8, via the cable ducts 16a or 16b. The cover plate 18 having the opening 24 may be placed on top of the cable ducts 16a and 16b, and the cables

50 placed in for example the cable ducts 16a may be led to the outside via the opening 24.

5 When mounting the cable outlet 34 such as the high or low tension outlet to the opening 24, a prop or pedestal 30 in the form of an inverted letter U may be placed below the opening 24. To this end, steps or shoulders 26a of both blocks 14B associated with the opening 24 are lower in height than the step 26, such that, when 10 the pedestal 30 is placed on the step 26a and the cover plate 18 is placed on the pedestal 30, the cover plate 18 may have its upper surface 20 substantially flush with respect to the upper surface of the blocks 14.

15 The pedestal 30 has a central circular tapped opening 32 in which a male threaded neck 36 of the cable outlet 34 is engaged through the opening 24 in the cover plate 18. The cable outlet 34 is engaged via the cover plate 18 with the pedestal 30 and is also adapted to pull 20 the cable outwards through a cable pull-out port 38. The pull-out port 38 may be oriented in the desired direction by turning the outlet 34 about the neck 36. Although the top layer 48 such as a carpet or a plastic tiling is laid on the cover plate 18, the neck 38 of the cable outlet 34 25 may be threadedly engaged with the tapped hole 32 of the pedestal 30 through the opening 24 in the cover plate 18 and an opening in the top layer 48 for securing the cable outlet 34 to the flooring panel 10.

30 The upper surface 52 of the pedestal 30 may be covered with the same shock-absorbing material as the layer 20 of the cover plate 18 for absorbing the shock otherwise applied to the pedestal 30 from the cover plate 18.

The pedestal 30 with the tapped hole may be of desired shape other than the inverted U shape. For example, it may be a flat plate provided with the tapped hole 32 and supported by the step 26a of the block 14B so that the tapped hole is aligned with the opening 24 in the cover plate 18. Alternatively, the pedestal in the form of the flat plate may be adhered or welded to the underside of the cover plate 18 so that its tapped hole is aligned with the opening 24 of the cover plate 18.

Since a pair of the blocks 14B each having the step 26a of a lower height are provided so as to be in register with the cable pull-out openings 24 of the cable ducts 16a and 16b, the cover plate 18 having only one opening 24 may be used and rotated manually by steps of 90° in dependence upon a desired cable pull-out position, so that the cable can be pulled outwards through the desired one of these four positions. In such a manner, the position of the cable outlet 34 and the orientation of the cable pull-out port 38 can be changed finely as desired in order to deal with changes in the pulling out or branching position of the cables 50. It is noted that several cable pull-out openings 24 may be provided to the cover plate 18.

The cover plate 18 is designed to support the weight of the various devices or the body weight of human attendants. On the other hand, the sheet 12 may preferably be deformed easily to conform to the irregularities on the surface of the blocks 14 that are caused by the occasional inundations of the building flooring to which the floor panel 10 is applied. To this end, the cover plate 18 of the present embodiment is formed with slits 40 at the neck of its cruciform arms such that the cover plate 18 may be deformed easily at the slits 40 to conform to surface irregularities of the blocks caused by the flexure of the

sheet 12 due to the inundations of the permanent building floor. By virtue of these slits 40, the cover plate 18 may be flexible enough to conform to the inundations of the building floor without lowering the withstand load properties even when the cover plate is of a reduced thickness. The slits 40 may have the shape, number and disposition such as are shown in FIGS. 12 and 13 and, hence those shown in FIG. 1 are not limiting the present invention. In other words, the width, length, shape and number as well as the position of the slits 40 may be determined as a function of the shape and the plate thickness of the cover plate 18. These slits may also be used for visual inspection of the types and the current status of the cable 50 accommodated within the cable ducts 16a and 16b without removing the cover plate 18.

When the floor panel 10 as a whole is covered with a sole cover plate or by plural split-type cover plates, the cover plate or plates can be secured in position by simply placing the cover plate or plates. FIG. 8 shows such an example.

Alternatively, in the case of a floor panel 10 shown in FIG. 11 wherein a large number of blocks 14 in the form of columns for example are arranged in an orderly array on the sheet 12, the cover plate 18 having the same large number of the circular openings 44 in register with upper portions 42 of the columns 14 is employed. In such a case, the cover plate 18 is supported with the circular openings thereof engaged by the upper portions 42 of the columns 14, the cover plate 18 then resting on the steps 26 formed on the periphery of the columns 14. The height of each step 26 from the upper surface of the sheet 12 is selected such that the cover plate 18, when resting on the steps 26, has its upper surface 20 substantially flush with

the upper surface of the upper portions 42 of the blocks 14.

5 In the case of the floor panel 10 as shown in
FIG. 13 wherein a large number of prismatic blocks 14, for
example, are arranged on the sheet 12, a cover plate 18
is used which has a number of recesses 46 in register with
the upper portions 42 of the prisms 14 or square pillars.
In this case, the cover plate 18 is supported with the
10 recesses 46 engaging with the upper terminal portions 42
of the prisms 14, the cover plate 18 then resting on the
steps 26 formed about the periphery of these prisms 14.
The height of the step 26 from the upper surface of the
sheet 12 is so selected that the cover plate 18, when
resting on the steps 26, has its upper surface 20
15 substantially flush with the upper surface of the terminal
portions 42 of the blocks.

The unitary or split type cover plate 18 covering
only the upper opened part of the cable ducts may be
20 retained and supported by the steps 26 formed on the sides
of the blocks 14A confronting to the cable ducts 16a and
16b, as shown for example in FIG. 2.

The cover plate 18 need not be in the form of
25 a flat plate as described above, but may have its peripheral
portions 28 bent downwards so as to have a channel shape
or the shape of an inverted letter U when seen in a vertical
section. In such a case, the cover plate 18 is supported
with both legs 28 of the inverted letter U resting on the
30 surface of the sheet 12 at the bottom of the cable ducts
16a and 16b such that the upper surface 20 of the cover
plate 18 is flush with the upper surface of the blocks 14.
Hence there is no necessity of providing the steps 26 to
the blocks 14A confronting to the cable ducts 16a and 16b.
35 Referring to FIG. 6, there is shown an embodiment wherein

a number of flooring panels 10 each having the cruciform cable ducts 16a and 16b are laid on the building floor. In the present embodiment, the floor panels 10 are of the same type such that cable conduits of a lattice shape as
5 a whole are defined by the cruciform cable ducts 16a and 16b of the respective flooring panels. The cables 50 may be placed in the cable ducts such that the same type of the cables are housed in the same cable ducts. In such a manner, hybrid cable laying of different types of cables
10 may be avoided, thus resulting in improved operability. Those portions of the sheet 12 corresponding to the bottom surfaces of the cable ducts 16a and 16b that are to be used in accordance with the scheduled routing of the cable interconnections may be afforded with indications in a color
15 tape or paint designating the types and the routing of the cables 50. In such a manner, the cable routing can be checked visually so that the efficiency in the cable laying and the subsequent maintenance operations may be improved.

20 Referring again to FIG. 2, a bridge shaped spacer 80 may be provided at a crossing point of the cruciform cable ducts 16a and 16b. The spacer 80 may have the size to conform with the area of the crossing point of the ducts 16a and 16b, and may be so designed that the cables housed
25 within one duct, such as the duct 16a and those housed within the other duct 16b, are passed above and below the spacer 80, respectively. This results in separation of two cables of different types, usage or application, such as the power cable and the communication cable, from each
30 other for avoiding their crossing contact so that the power line may be inhibited from interfering with the communication cable.

35 The spacer 80 may be formed for example of hard synthetic resin or metal such as steel or aluminium. If

need be, the spacer 80 may be coated with a layer of an electrical insulating or a shock-absorbing material. This results in improving the electrical safety and minimizing noise induction due to the personnel walking on the flooring panel 10.

FIG. 7 shows an embodiment wherein a flooring panel 10a having lattice-shaped cable ducts 16c with relatively narrow duct widths and another flooring panel 10b having similarly lattice-shaped ducts 16a and 16b of larger duct widths defining only one block 14d at the center and four corner blocks 14. These floor panels 10a and 10b are laid on the permanent flooring of the building with the cable ducts 16a, 16b and 16c in communication with one another. The flooring panel 10b with the larger duct width is placed in a zone with a higher cable volume per unit area, as in the vicinity of an electrical arrangement 54, such as a power distribution board, where the trunk line of the cables 50 or the large number of cables 50 are concentrated or branched, while the flooring panel 10a with a lesser duct width is placed in the other zones where the cable volume per unit area is lower. In such a case, although discontinuities may be caused in the number, the pitch and width of the cable ducts 16a to 16c as a function of the disposition of the flooring panels 10a and 10b, proper flooring panels can be selected as the occasion may require in order to provide the continuous cable ducts. In such a manner, plural types of the flooring panels can be made available and selectively positioned as a function of the cable volume in order to deal with the actual cable laying conditions.

FIG. 8 shows the disposition of the flooring panels in the vicinity of the electrical equipment 54 where the cable concentration is higher, as in the vicinity of

the distribution board. Since the volume of the cables
50 per unit area, or cable concentration density, is high
in the vicinity of the electrical equipment 54, rectangular
floor panels 10c having a larger duct width and cruciform
5 cable duct 16d are placed in the vicinity of the equipment
54. Since the area surrounding the equipment 54 is lower
in the cable density, there are placed flooring panels 10d
having the cable duct 16e in the form of parallel cross
and a narrower duct width. The flooring panel 10d has a
10 square shape different from the rectangular shape of the
flooring panel 10c. The square flooring panels 10e having
the narrow duct width and the cable ducts 16f in the form
of parallel crosses are laid in the area surrounding the
floor panels 10d where the cable density is still lower.
15 In the present embodiment, however, square floor panels
10f having broader cable ducts 16g are placed in areas where
the cable density is higher despite an increased distance
thereof from the electrical equipment 54. By laying the
flooring panels 10c, 10d, 10e and 10f having different duct
20 widths as a function of the cable laying conditions such
as the cable volume or density, the cable laying or
interconnections can be made without any inconvenience
despite cable concentration or branching. The flooring
panels 10 can also be applicable to any situations pursuant
25 to the volume of cables.

By the way, the blocks 14 secured to the sheet
12 may be dispensed with if need be. For example, the
square cable laying fixture 56 may be accommodated in a
30 square space 58 obtained by eliminating several blocks 14
in the vicinity of the center of a block, such as a block
14a. The fixture 56 may include for example an outlet 60
for a power line and an outlet 62 for a communication or
signal line. Since a cable inlet opening 64 is formed on
35 at least one side of the fixture 56, the block 14 facing

to the inlet opening 64 of the side of the fixture 56, where the cable 50 is desired to be introduced, is removed, and the cable 50 is then introduced via a resulting conduit 68 and the inlet opening 64 into the fixture 56. Several
5 blocks 14 confronting to the crossing point of the cable ducts 16a and 16b may also be removed and the fixture 56 placed in the resulting square space 58. Preferably, the fixture 56 has a removable door-type cover 66 in which the upper surface of the cover 66 is approximately flush with
10 or projects from the upper surface of the blocks 14 on closing the cover 66.

Referring to FIG. 10, a small-sized electrical device 70 such as an optical link or an A/D converter may
15 be accommodated within an additional space 72 which is formed by removing a block 14 facing to, for example, the cable duct 16a. The leads 74 of the device 70 may be directed towards an opening 68 for connecting to the cable 50. When the element 70 is lower in height than the block
20 14, a cover member 76 may be placed on the element 70. The cover member 70 also has a channel shape or the shape of the inverted letter U, the legs 28 of which are set so as to be equal in height to the blocks 14. The cover member 76 is used not only for protecting the element 70, but for
25 improving the strength of the blocks 14 defining the additional space 72.

The element 70 may be secured to those portions of the sheet 12 exposed at the bottom of the additional
30 space 72 by fasteners such as screws or with the use of an adhesive or a double-sided adhesive tape. In such a manner, the cable laying fixture or electrical elements can be installed in any desired location such as an intermediate point of the cable 50 by removing the blocks
35 14 as the occasion may demand, so that the cable laying

operation is facilitated. The space 58 or 72 obtained by removing the blocks 14 may be used not only as the mounting site for the fixture 56 or devices 70, but as the winding or storage area for superfluous cable length portions.

5

The surfaces of electric device 70 and cover 66 of fixture 56 may also be coated with a layer of electrostatically implanted fibers as in the case of cover plate 18, resulting in preventing top layer 48 from shifting horizontally, as well as softening walking shock.

10

FIG. 11 shows an embodiment wherein the cable laying space for the cables 50 is divided into an upper and lower spaces or layers 86 and 88. More specifically, each block 14 has generally the shape of a column, and a cable laying space of a prescribed width c or d is formed between the two adjacent columnar blocks 14. Each block 14 has a peripheral step 26b at a mid height and another peripheral step 26 in the vicinity of an upper terminal portion 42. In such a manner, the block 14 has three different diameters such that these diameters become lesser from the bottom towards the top of the block 14. The cover plate 18 has a number of circular openings 44 in register with the blocks 14, with each opening 44 being of such a diameter that the cover plate is supported by the steps 26 of the upper terminal portions 42 of the blocks 14, so that the cover plate 18 is supported by the steps 26 at the height of these steps 26 when the openings 44 of the plate 18 are engaged by the upper terminal portions 42.

20
25
30

According to the present embodiment, a number of partitioning plates 84 having corner recesses or notches 82 in the form of quadrants in register with the blocks 14 may be placed so as to be supported at the corners on the central steps 26, the notches 82 being of such a

35

diameter that the plates 84 can be supported in this manner by the central steps 26. The upper and lower spaces 86 and 88 may be defined in this manner for accommodating the cables 50. The partitioning plate 84 may be of the same material as the cover plate 18, as an example. The partitioning plates 84 may also be advantageously formed with cable pull-out openings and/or slits for improving its flexibility as in the case of the cover plate 18. The columnar blocks 14 may also be provided with an additional step or steps for providing three or more separate spaces for accommodating the cables or wiring.

In the present embodiment, the partitioning plate 84 has the size approximately equal to the rectangle defined by the four columnar blocks 14. As an alternative, the partitioning plate may be in the form of a flat plate of approximately the same size as the flooring panel 10 and having circular apertures corresponding to the recesses 82 in register with the columnar blocks 14. The partitioning plates 84 may be provided only in areas with a higher cable density. The partitioning plates 84 may also be used for providing a site for storing electrical devices or winding of superfluous cable length portions.

The cable laying ducts 16a to 16c may be arranged in other than the cruciform or latticed shapes. For example, a number of longitudinal rows of the cable ducts and another number of transverse rows of the cable ducts different from the number of the longitudinal rows may be arranged in one flooring panel 10 orthogonally to each other, for example, two transverse rows may be provided for one longitudinal row as shown in FIG. 15. Or alternatively, the flooring panel 10 may be formed with obliquely extending cable laying ducts as in the form of letters X or Y.

From the foregoing it will be appreciated that the cable ducts having any desired cable housing capacities may be easily formed with the desired layout by laying the modular floor panels on the permanent building floor. The
5 cables may be introduced in place within the cable ducts through the open top thereof so that the laying and branching operation may be performed easily. The cover plate may be removably attached from above so that any changes or addition of the cable laying accompanying the
10 extension or reallocation of devices after the initial cable laying or inspection of the cable laying state can be implemented easily.

While the present invention has been described
15 with reference to the particular illustrative embodiments, it is not to be restricted by those embodiments but only by the appended claims. It is to be appreciated that those skilled in the art can change or modify the embodiments without departing from the scope of the present
20 invention.

C L A I M S

- 1 1. A flooring panel to be laid on a floor of a
building for placing a cable therein, CHARACTERIZED BY
comprising:
- 5 a plurality of blocks (14) of solid material;
 holding means (12, 22) including a flexible
material for holding said blocks (14) so that said blocks
(14) define a plurality of sections (14a-14d), each of said
sections (14a-14d) containing at least one block (14) with
a cable laying space (16a-16g) defined between adjacent
10 ones of the sections (14a-14d); and
 a covering member (18) supported by at least a
portion of said blocks (14) for covering at least an upper
opening of the cable laying space (16a-16g), said covering
member (18) presenting a surface that is continuous with
15 upper surfaces of said blocks (14) to form a substantially
flat, top surface of said flooring panel (10).
- 1 2. A flooring panel in accordance with claim 1,
 CHARACTERIZED IN THAT
 said covering member (18) is formed of a flat
plate of a rigid material;
5 said flat plate having a slit (40) formed to allow
the flat plate to be bent.
- 1 3. A flooring panel in accordance with claim 1
or claim 2, CHARACTERISED IN THAT said covering member
(18) has an opening (24) formed through which a cable
(50) is pulled out form the cable laying space.
- 1 4. A flooring panel in accordance with claim 3,
 CHARACTERIZED IN THAT
 said cable laying space (16a-16g) is defined in
plan in a generally symmetrical cruciform shape;

1
said covering member (18) having a generally symmetrical cruciform shape in plan substantially corresponding to the cable laying space (16a-16g);

5 said opening (24) for pulling out the cable (50) being formed in one arm of the cruciform shape of said covering member (18).

5. A flooring panel in accordance with claim 3 or claim 4, CHARACTERISED BY a holding member (30), engageable with a cable pulling out device (34)
10 attached to said opening (24) for pulling out the cable, for holding the cable pulling out device (34) to said covering member (18).

6. A flooring panel in accordance with any one of claims 1 to 5, CHARACTERISED IN THAT
15 said cable laying space (16a-16g) includes at least one cable laying duct (16a, 16d) extending in a first direction, and at least one cable laying duct (16b, 16e) extending in a second direction intersecting the first direction;

20 said covering member (18) being of a flat configuration covering at least an upper opening of the cable laying ducts (16a, 16b, 16d, 16e).

7. A flooring panel in accordance with any one of claims 1 to 6, CHARACTERISED IN THAT a layer of
25 shock absorbing material (20) is formed on at least one primary surface of said covering member (18).

8. A flooring panel in accordance with claim 7, CHARACTERISED IN THAT said layer of the shock absorbing material (20) includes a layer of electro-
30 statically implanted fibers.

9. A flooring panel in accordance with any one of claims 1 to 8, CHARACTERISED IN THAT

said holding means (12,22) includes a flexible flat plate member (12);

5 said blocks (14) being held on one primary surface of said plate member (12).

10. A flooring panel in accordance with any one of claims 1 to 9, CHARACTERISED IN THAT said holding means (12,22) includes a layer of flexible material
10 (22) covering and holding said blocks (14) from above.

11. A flooring panel in accordance with any one of claims 1 to 8, CHARACTERISED IN THAT said holding means (12, 22) comprises:

15 a flexible flat plate member (12) for holding said blocks (14) on one primary surface of said plate member (12); and

 a layer of flexible material (22) for covering and holding said blocks (14) from above.

12. A flooring panel in accordance with any one of claims 1 to 11, CHARACTERISED IN THAT
20

 each of said sections (14a-14d) includes a plurality of blocks (14);

 a gas (S) being defined between adjacent ones of said blocks (14).

25 13. A flooring panel in accordance with any one of claims 1 to 11, CHARACTERISED IN THAT

 each of said sections (14a-14d) includes a plurality of blocks (14);

30 said blocks (14) being removably held by said holding means (12, 22);

 whereby an additional space (58, 68) communicating with the cable laying space (16a-16g) is formed by

selectively removing said blocks (14).

1 14. A flooring panel in accordance with claim 13,
CHARACTERIZED BY an additional covering member (76)
overlying an upper opening of the additional space (58, 68).

1 15. A flooring panel in accordance with any one of
claims 1 to 14, CHARACTERIZED IN THAT
 said sections (14a-14d) define said cable laying
spaces (16a-16g) intersecting one another;
5 said flooring panel (10) further comprising a
spacer member (80) that can be arranged at an intersection
of the spaces (16a-16g) for spacing cables (50) mutually
intersecting at the intersection from one another.

1 16. A flooring panel in accordance with claim 1,
 CHARACTERIZED BY
 a flat plate (84) having a portion (82) cut out
to receive said blocks (14);
5 said blocks (14) having means (26b) for supporting
said flat plate (84) with the cut-out portion (82) at at
least one position intermediate in height of said blocks
(14);
 whereby the cable laying space (16a-16g) is
10 divided into a plurality of layers (86, 88) by said flat
plate (84).

1 17. A flooring panel in accordance with claim 16,
CHARACTERIZED IN THAT said flat plate (84) is substantially
equal in size to said covering member (18), said cut-out
portion (82) being formed in the form of apertures
5 corresponding to said blocks (14).

1 18. A flooring panel in accordance with claim 16, or
claim 17, CHARACTERISED IN THAT

each of said plurality of blocks (14) includes
a column (14, FIG. 11) defining one of the sections, said
5 columns (14) being held in an array by said holding means
(12, 22);

said flat plate (84) being of substantially the
same size as the rectangle formed by mutually adjacent four
of said blocks (14) arranged in the array, said cut-out
10 portions (82) being in the form of notches each partially
receiving associated one of said four blocks (14).

1 19. A flooring panel system wherein a plurality of
modular flooring panels (10) of at least one type are laid
on a floor of a building,

CHARACTERIZED IN THAT

5 each of said modular flooring panels (10)
comprises:

a plurality of blocks (14) of solid material;
holding means (12, 22) including a flexible
material generally rectangular in plan configuration for
10 holding said blocks (14) so that said blocks (14) define
a plurality of sections (14a-14d), each of said sections
(14a-14d) including at least one block (14) with a space
(16a-16g) for laying a cable (50) defined between adjoining
ones of said sections (14a-14d); and

15 a cover member (18) supported by at least a
portion of said blocks (14) for covering at least an upper
opening of the space (16a-16g), said cover member (18)
presenting a surface continuous with upper surfaces of said
blocks (14) to form a substantially flat, top surface of
20 said modular flooring panel (10);

whereby the cable laying spaces (16a-16g) are
defined in communication with one another when said modular
flooring panels (10) are laid on the building floor.

1 20. A flooring panel system wherein a plurality
of modular flooring panels (10) of plural types are
laid on a floor of a building,

CHARACTERIZED IN THAT

5 each of said modular flooring panels (10)
comprises:

 a plurality of blocks (14) of solid material;
 holding means (12, 22) including a flexible
material generally rectangular in plan configuration for
10 holding said blocks (14) so that said blocks (14) define
a plurality of sections (14a-14d), each of said sections
(14a-14d) including at least one block (14) with a space
(16a-16g) for laying a cable (50) defined between adjacent
ones of said sections (14a-14d), said spaces (14a-14d) being
15 different among the plural types of said modular flooring
panels (10) in at least one of shape, size, number and
position; and

 a cover member (18) supported by at least a
portion of said blocks (14) for covering at least an upper
20 opening of the space (16a-16g), said cover member (18)
presenting a surface continuous with upper surfaces of said
blocks (14) to form a substantially flat, top surface of
said modular flooring panel (10);

 whereby the cable laying spaces (16a-16g) are
25 defined in communication with one another when said modular
flooring panels (10) of the different types are selectively
laid on the building floor under a cable laying condition
including the number of cables (50).

1 21. A flooring panel substantially as herein described
with reference to the accompanying drawings.

REGISTER ENTRY FOR GB2190936

Form 1 Application No GB8703214.0 filing date 12.02.1987

Priority claimed:
30.05.1986 in Japan - doc: 61124973

Title FLOORING PANELS FOR FREE CABLE LAYING

Applicant/Proprietor
KYODO ELECTRIC CO LTD, Incorporated in Japan, 24-12 Higashi 3-chome,
Shibuya-ku, Tokyo, Japan [ADP No. 00560268001]

Inventors
MINORU YOSHIDA, 26-6 Chuohrinkan 3-chome, Yamato-shi, Kanagawa, Japan
[ADP No. 03943479001]

HIROSHI YOSHIDA, 26-7 Chuohrinkan 3-chome, Yamato-shi, Kanagawa, Japan
[ADP No. 03943487001]

TOSHIRO ISHIKAWA, 12-14 Chuoh 7-chome, Yamato-shi, Kanagawa, Japan
[ADP No. 03943495001]

MINORU KANESAKA, 19-2-302 Kitakasai 2-chome, Edogawa-ku, Tokyo, Japan
[ADP No. 03943503001]

NOBUYUKI ISHII, 12-18 Kamirenjaku 6-chome, Mitaka-shi, Tokyo, Japan
[ADP No. 03943511001]

Classified to
E1D U1S
E04C

Address for Service
R G C JENKINS & CO, 12-15 Fetter Lane, LONDON, EC4A 1PL, United Kingdom
[ADP No. 00000950002]

Publication No GB2190936 dated 02.12.1987

Examination requested 03.03.1988

Patent Granted with effect from 13.12.1989 (Section 25(1)) with title FLOORING
PANELS FOR FREE CABLE LAYING.

19.08.1989 Notification of change of Address For Service address of
R G C JENKINS & CO, 12-15 Fetter Lane, LONDON, EC4A 1PL, United
Kingdom [ADP No. 00000950002]
to
R G C JENKINS & CO, 26 Caxton Street, LONDON, SW1H 0RJ, United
Kingdom [ADP No. 00000950001]
dated 09.05.1989. Official evidence filed on GB2190936
Entry Type 7.3 Staff ID. 3BH1 Auth ID. A0

01.11.1993 Application under Section 32 filed on 27.10.1993
Entry Type 10.1 Staff ID. DM Auth ID. F20

01.11.1993 Notification of change of Applicant/Proprietor name of
KYODO ELECTRIC CO LTD, Incorporated in Japan, 24-12 Higashi
3-chome, Shibuya-ku, Tokyo, Japan [ADP No. 00560268001]
to

✓ KYODO KY-TEC CORP., Incorporated in Japan, 24-12 Higashi 3-Chome,
SHIBUYA-KU, Tokyo, Japan [ADP No. 06418214001] *recent*

dated 01.10.1992. Official evidence filed on GB2190936 *none*

Entry Type 7.2 Staff ID. SA Auth ID. F20

**** END OF REGISTER ENTRY ****

DA80-01
FG

OPTICS - PATENTS

04/11/93 15:49:32
PAGE: 1

RENEWAL DETAILS

PUBLICATION NUMBER GB2190936

PROPRIETOR(S)

Kyodo Ky-Tec Corp., Incorporated in Japan, 24-12 Higashi 3-Chome,
SHIBUYA-KU, Tokyo, Japan

DATE FILED 12.02.1987

DATE GRANTED 13.12.1989

DATE NEXT RENEWAL DUE 12.02.1994

DATE NOT IN FORCE

DATE OF LAST RENEWAL 01.02.1993

YEAR OF LAST RENEWAL 07

STATUS PATENT IN FORCE