

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 April 2008 (10.04.2008)

PCT

(10) International Publication Number
WO 2008/043044 A2

(51) International Patent Classification:
A61F 2/02 (2006.01)

(21) International Application Number:
PCT/US2007/080485

(22) International Filing Date: 4 October 2007 (04.10.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/849,414 4 October 2006 (04.10.2006) US

(71) Applicant (for all designated States except US): **NDO SURGICAL, INC.** [US/US]; 125 High Street, Suite 7, Mansfield, MA 02048 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **LAUFER, Michael, D.** [US/US]; 1259 El Camino Real, #211, Menlo Park, CA 94025 (US). **BROMANDER, Thomas** [US/US]; 28 Candlewood Drive, Andover, MA 01810 (US). **CRUZ, Amos** [US/US]; 25 Vine Street, Franklin, MA 02038 (US).

(74) Agents: **KOHLER, Thomas, D.** et al.; Morgan Lewis & Bockius LLP, 2 Palo Alto Square, 3000 El Camino Real, Suite 700, Palo Alto, CA 94306 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

(54) Title: DEVICES AND METHODS FOR ENDOLUMINAL GASTRIC RESTRICTION TISSUE MANIPULATION, AND DRUG DELIVERY

(57) Abstract: An endoluminal treatment device and method includes introducing an endoluminal device into a lumen of a patient and engaging a wall of the lumen with an implant device. The implant device can be a drug delivery device or medical device.



WO 2008/043044 A2

DEVICES AND METHODS FOR ENDOLUMINAL GASTRIC RESTRICTION, TISSUE MANIPULATION, AND DRUG DELIVERY

CROSS-REFERENCE TO RELATED APPLICATION

[001] This application claims the benefit of Provisional Patent Application No. 60/849,414, filed October 4, 2006, which is incorporated by reference herein in its entirety.

TECHNICAL FIELD OF THE INVENTION

[002] Generally, the present invention is related to endoluminal surgical devices, methods, device, and drug delivery. More particularly, the devices and methods provide for endoluminal gastric restriction, endoluminal gastric tissue reconfiguration, endoluminal drug delivery, endoluminal device delivery, and the like.

BACKGROUND OF THE FIELD OF THE INVENTION

[003] Laparoscopic surgery has greatly reduced the size and scope of incisions made in a patient and resulted in reduced morbidity and mortality rates. However, even with the reductions in the size and scope of incisions as a result of laparoscopic surgery, complications in and during surgical procedures remain. A technique that is developing to further reduce surgical complications is to work through an endoluminal access port. One endoluminal access port is the mouth and this access port can give a surgeon access to a patient's esophagus and stomach.

[004] Stomach tissue often needs surgical treatment to treat fistulas and to close transgastric incisions to stop stomach fluids from leaking from the stomach to surrounding tissue and to stop infectious matter from spreading from or to the stomach tissue. Other stomach treatments include stomach reduction procedures for obese patients. Traditionally, physicians have been placing devices such as the Lap Band® on the external surface of the gastric wall to create a restricted stomach capacity. Another traditional procedure for stomach reduction includes a laparoscopic procedure in which surgeons protrude into the stomach from the exterior of the patient and staple the stomach into a smaller volume. This restriction creates a pouch inside the stomach which fills

quickly when food is ingested and assists in generating a sensation of being full.

However, these procedures have drawbacks such as complications from port punctures of the stomach, large incisions, substantial recovery time, expense, lost productive work time, infection, and the like.

[005] However, the incision required by the current surgical procedures include a morbidity and mortality rate that can be reduced by reducing or eliminating the need for an incision by approaching the surgical site through endoluminal procedures.

SUMMARY OF THE INVENTION

[006] According to an embodiment, the present invention includes an implant device including a medical implant configured to be implanted into a lumen of a body without creating an incision in the body, wherein the medical implant is configured to maintain a plication in a wall of the lumen and wherein the medical implant includes a medical treatment. The medical treatment can include a drug delivery, a time released drug delivery, a coating, a biological stimulation device, a monitoring device, a feeding tube, a bioresorbable material, and combinations thereof. The biological stimulation device can be selected from the group consisting of an electrical stimulation device, mechanical stimulation device, vibratory device, sound device, ultra-sound device, chemical stimulatory device, neuro-transmitter stimulation device, thermal stimulation, sensory stimulatory device, and combinations thereof.

[007] In some embodiments, the implant device further includes a controller configured to control the biological stimulation device. The controller can control the biological stimulation device from external to the body and through radio frequency. The monitoring device can be selected from the group of a pH sensor, pressure sensor, video sensor, chemical sensor, hormone sensor, dilation sensor, fluid sensor, ion sensor, tissue extension sensor, and combinations thereof. In some embodiments, the medical treatment includes material selected from radioactive material, chemotherapy material, biological material, and combinations thereof.

[008] In some embodiments, the medical treatment is configured to treat a gastric condition. In some embodiments, the medical implant includes bioresorbable material including a drug.

[009] In alternative embodiments, an endoscopic treatment method includes introducing an endoscopic device into a lumen of a patient without creating an incision in the patient, engaging a wall of the lumen with an end effector of the endoscopic device to form a plication, and activating the end effector to secure the plication with an anchor object and a treatment device, wherein the treatment device is coupled with the anchor object.

[0010] In some embodiments, an endoscopic treatment method includes introducing an endoscopic device into a lumen of a patient without creating an incision in the patient, introducing a treatment device into the lumen, engaging a wall of the lumen with an end effector of the endoscopic device, forming a first plication in the wall of the lumen, forming a second plication in the wall of the lumen adjacent the first plication, and coupling the first plication with the second plication to thereby form a first double plication wherein an open pocket is formed between the first plication and the second plication. In alternative embodiments, the method includes forming a second double plication adjacent the first double plication, wherein a second open pocket formed by the second double plication and the open pocket formed by the first double plication are axially aligned. In other embodiments, the method includes forming an artificial biological tube by aligning multiple double plications such that open pockets formed by the multiple double plications axially align. In some embodiments, the method includes coupling the first double plication with the second double plication.

[0011] According to yet other embodiments, an endoscopic GERD treatment method includes introducing an endoscopic device into a lumen of a patient without creating an incision in the patient, engaging a wall of the lumen with an end effector of the endoscopic device, and forming a plication in the wall of the lumen near the gastro-esophageal-junction such that an artificial biologic tube is formed distal to the gastro-esophageal-junction to block gastric fluid from interfering with tissue of the esophagus. In some embodiments, the method includes forming a plurality of plications extending distally from the gastro-esophageal-junction. In some embodiments, the artificial

biologic tube is between about 0.5 cm and about 5 cm in length. In alternative embodiments, the artificial biologic tube is between about 0.5 cm and about 3 cm in diameter. In further embodiments, the plurality of plications is coupled together with glue, suture, wire, or tissue re-growth after stimulation.

[0012] In other embodiments, an endoscopic obesity treatment method includes introducing an endoscopic device into a stomach of a patient without creating an incision in the patient, engaging a wall of the stomach with an end effector of the endoscopic device, and forming a plication in the wall of the stomach such that an artificial biologic tube is formed within the stomach of the patient and thereby reducing a volume of the stomach to treat obesity.

[0013] In alternative embodiments, a medical implant apparatus includes an anchor object configured to couple with tissue and an adjustable mechanism configured to interact with the anchor object such as to apply alternative forces upon the anchor object in response to a stimulus. In some embodiments, the adjustable mechanism is coupled with the anchor object through suture material. In other embodiments, the adjustable mechanism is coupled with the anchor object through surgical wire. In some embodiments, the adjustable mechanism shortens in response to a stimuli. In some embodiments, the adjustable mechanism includes a mechanism selected from the group consisting of: piezoelectric, magnetic, screw-threads, spring, memory metal, elastic, mechanical mechanism, temperature sensitive material, and combinations thereof. According to some embodiments, the stimuli is selected from the group of a radio frequency, ultra-sound, mechanical force, pressure, direct mechanical manipulation, magnetic force, chemical interaction, enzyme interaction, fluid, temperature, biological fluid, cellular interaction, cellular by-product, inter-cellular constituent, intra-cellular constituent, food, digestion by-product, a lapse of time, and combinations thereof. In some embodiments, the device further includes a plurality of anchor objects wherein each anchor object is coupled with the adjustable mechanism such that an adjustable substantially sphincter shaped tissue structure is formed.

[0014] According to some embodiments, a method for temporary tissue restructuring includes implanting an anchor object onto tissue to be adjustably restructured, associating

an adjustable mechanism with the anchor object such that a force generated by the adjustable mechanism can change a relative position of the anchor object with respect to the adjustable mechanism and thereby restructures tissue, and stimulating the adjustable mechanism to generate the force. In some embodiments, the method further includes a plurality of anchor objects, wherein each anchor object is coupled with the adjustable mechanism. The plurality of anchor objects can be coupled in series with the adjustable mechanism. In some embodiments, the method includes shortening the adjustable mechanism in response to a stimuli and thereby resulting in a distance between the adjustable mechanism and the anchor object reducing such as to tighten tissue between the anchor object and the adjustable mechanism. In other embodiments, the adjustable mechanism includes a mechanism selected from the group of: piezoelectric, magnetic, screw-threads, spring, memory metal, elastic, mechanical mechanism, temperature sensitive material, and combinations thereof. In some embodiments, the stimulating is selected from a radio frequency, ultra-sound, mechanical force, pressure, direct mechanical manipulation, magnetic force, chemical interaction, enzyme interaction, fluid, temperature, biological fluid, cellular interaction, cellular by-product, inter-cellular constituent, intra-cellular constituent, food, digestion by-product, a lapse of time, and combinations thereof.

[0015] According to alternative embodiments, the present invention discloses a surgical tool support system that includes an anchor object configured and dimensioned to be attached to a body tissue and a manipulation line extending from the anchor object and configured and dimensioned to couple with a surgical tool. In some embodiments, the manipulation line is fabricated from one of the group of a suture, resorbable suture, stainless steel, surgical wire, braided wire, and combinations thereof.

[0016] In alternative embodiments, the present invention also includes a method of manipulating a surgical tool including forming an incision in body tissue, attaching a manipulation line to body tissue near the incision, introducing a surgical device through the incision in the body tissue, attaching a free end of the manipulation line to the surgical device, and manipulating the surgical tool to perform a medical treatment procedure. The manipulation line can provide a cantilever for the surgical tool. The manipulation line at least partially supports the surgical device. In some embodiments,

method includes implanting a plurality of manipulation lines between the body tissue and the surgical tool. The plurality of manipulation lines are evenly distributed around the surgical tool.

BRIEF DESCRIPTION OF THE FIGURES

[0017] FIG. 1 shows a schematic view of an endoluminal surgical device according to an embodiment of the present invention;

[0018] FIG. 2 shows a schematic view of a tissue engaging end effector of an endoluminal surgical device according to an embodiment of the present invention;

[0019] FIG. 3 shows an implanted device according to an embodiment of the present invention;

[0020] FIG. 4 shows an device positioned on an end effector prior to implantation according to an embodiment of the present invention;

[0021] FIG. 5 shows a tissue plication including an implanted device according to an embodiment of the present invention;

[0022] FIG. 5A shows an alternative embodiment of an implant device;

[0023] FIG. 6 shows another device positioned on an end effector prior to implantation according to an embodiment of the present invention;

[0024] FIG. 7 shows another tissue plication including an implanted device according to an embodiment of the present invention;

[0025] FIG. 8 shows yet device positioned on an end effector prior to implantation according to an embodiment of the present invention;

[0026] FIG. 9 shows another tissue plication including an implanted device according to an embodiment of the present invention;

[0027] FIG. 10 shows an end effector with a tissue plication formed on a needle of the end effector according to an embodiment of the present invention;

[0028] FIG. 11 shows an end effector with multiple tissue plications formed on a needle of the end effector according to an embodiment of the present invention;

[0029] FIGS. 12A-12C show embodiments of a tissue plication and corresponding open tissue pocket according to embodiments of the present invention;

[0030] FIGS. 13A and 13B show implanted devices according to other embodiments of the present invention;

[0031] FIG. 14 shows an implanted device according to another embodiment of the present invention;

[0032] FIGS. 15A and 15B show an adjustable implantable device according to an embodiment of the present invention;

[0033] FIG. 16 shows a surgical device stabilization device according to an embodiment of the present invention; and

[0034] FIG. 17 shows a guide wire for guiding a tissue retractor according to an embodiment of the present invention.

DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

[0035] An endoluminal device 100, such as that shown in FIG. 1 and disclosed in U.S. Patent No's. 6,835,200; 6,821,285; 6,773,441; 6,663,639; 6,506,196; and 6,494,888, and U.S. Published Application No's. 2005/0033328; 2004/0194790; 2004/0193194; 2004/0193193; 2004/0193184; 2004/0193117; 2002/0193816; and U.S. Provisional patent application no 60/741,510 filed December 1, 2005, the disclosure of each being hereby incorporated by reference in their entirety, is utilized in the present invention to manipulate tissue of a patient. Generally, the endoluminal device 100 is configured such that it can be positioned within a hollow organ by entry through a body cavity opening, such as for example, positioning the device into the stomach via the mouth of a patient. Once situated, the device is capable of manipulating tissue and implanting objects or devices.

[0036] According to some embodiments of the present invention, methods and devices are provided for delivering devices or drugs into the lumen of an organ, manipulate tissue, close incisions, repair fistulas, and the like by an endoluminal approach. The tissue of an organ, such as for example, the stomach, can be manipulated to generate a fold, plication, or tube and a suture based implant can be implanted to maintain the

manipulated character of the tissue. In some embodiments, a drug or device can also be introduced into the lumen of the organ and implanted or attached to the organ wall with a suture based implant. In some embodiments, after the tissue is manipulated into folds or plications the folds can be positioned vertically with respect to each other and the suture based implants can be drawn together such as to form an artificial biological tube.

[0037] Referring to FIG. 1, endoluminal surgical device 100 is shown according to an embodiment of the present invention. Endoluminal surgical device 100 further includes a generally longitudinal and flexible shaft 102 that includes an end effector 200 (FIG. 2) configured near its distal end. End effector 200 includes first arm 202 and second arm 204. First arm 202 and second arm 204 are configured to engage tissue and implant anchor object 220. According to some embodiments, anchor object 220 generally includes pledgets 222 and 224 which, according to some embodiments, are connected by suture 226. Endoluminal surgical device 100, end effector 200, and anchor object 220 are further disclosed in the reference publications and applications that are incorporated herein by reference. As described in further detail in the publications and applications incorporated herein by reference, anchor object can be constructed from any biocompatible material, such as, but not limited to, stainless steel, cobalt chromium, titanium, alloys of such metals, biocompatible polymers, soluble polymers, non-soluble polymers, swellable polymers, absorbable polymers, suture material, bioresorbable suture, bioabsorbable suture, combinations thereof, or the like.

[0038] Referring now to FIG.3, endoluminal surgical device 100 is utilized to manipulate tissue. Tissue from the wall of a hollow organ, such as for example the stomach, is formed into plications, such as plication P1. Plication P1 is formed by gathering or manipulating tissue of the wall of the organ with end effector 200 into a fold and piercing the folded tissue with needle 206 of end effector 200. Needle 206 includes suture 312 and a suture based implant or pledget 314 associated therewith. According to an embodiment, one end of suture 312 is attached to pledget 314 and the other end of suture 312 remains free and outside the patient. According to an alternative embodiment, both ends of suture 312 remain free and outside the patient's body, however, pledget 314 is attached to suture at a predetermined location. Pledget 314 can be loosely attached or securely attached to suture 312 by a knot, a clip, integral with suture 312, combinations

thereof, or the like. Following implantation of pledget 314, a second pledget 316 is positioned with respect to suture 312. Second pledget 316 is preferable positioned with respect to suture 312 outside the body, however, second pledget 316 can be positioned onto suture 12 inside the hollow organ. Second pledget 316 is then moved into the hollow organ to be manipulated, a second fold of tissue or plication P2 is formed with the endoluminal or endoscopic surgical device 100 and plication P2 is pierced with needle 206 of the endoscope 100. When plication P2 is pierced, suture 312 is pushed through plication P2, thereby, bringing pledget 316 into position adjacent a side of plication P2. Following positioning of pledgets 314 and 316, suture 312 is tightened such that plication P1 and plication P2 are drawn together. Preferably, pledget 314 and pledget 316 are positioned on opposing sides of plication P1 and P2, respectively. In an alternative embodiment, pledget 314 and pledget 316 are positioned on the same side of plication P1 and plication P2. After suture 312 is tightened such that plication P1 and plication P2 are approximated together, suture 312 is fixed. According to alternative embodiments, suture 312 can be either removably fixed or irremovably fixed to hold plication P1 and plication P2 in position. Suture 312 can be fixed with a knot, a suture clip, fused together, combinations thereof, or the like. Furthermore, a predetermined pressure can be applied through the tightening of suture 312 such as to generate a predetermined treatment condition between the plications. According to some embodiments, this procedure is performed in the stomach of a patient. According to one embodiment of treating a stomach condition, plication P1 and plication P2 are formed approximately 2 cm from gastro-esophageal (GE) junction 310. According to alternative embodiments, plication P1 and plication P2 are formed between 2 cm and 5 cm from GE junction 310. Where the stomach condition to be treated requires enhancement or replacement of the gastric valve, such plications are preferably located in cooperative relationship with the GE junction to form an artificial gastric valve.

[0039] According to alternative embodiments, pledgets 314 and 316 may or may not be used to form plications P1 and P2, respectively. It should be appreciated that depending on a condition to be treated, tissue type being treated, location of treatment, size or area to be treated, combinations thereof, and the like, pledgets 314 and 316 may not be necessary, thereby, using suture 312 to form plications P1 and P2 and tighten plications

P1 and P2 together. In some embodiments, multiple pledgets can be implanted adjacent one another such as to treat a large tissue disturbance, such as a large incision, re-incision, necrotic site, fistula, combinations thereof, or the like.

[0040] In some embodiments, a patch 318 can be introduced with endoluminal device 100 into the organ to be treated. Patch 318 can be associated with a tissue engaging portion of the device and placed on the wall of the organ when the tissue engaging portions grasp the wall to form the plication. In some embodiments, patch 318 may be coupled with a plication, such as plication P2, through the securing implant such as pledget 316. In one exemplary embodiment, patch 318 may be formed as a resilient, clip-like member having at least two arms that can be secured to a plication previously formed by manipulating the tissue with the endoluminal device 100. As shown, for example, in Fig. 3, piercing of the tissue is not required for securing such an embodiment. According to alternative embodiments, patch 318 can be attached at a plurality of locations to the wall of the organ. Patch 318 can increase the integrity of the organ. In some embodiments, patch 318 includes therapeutic agents such as, for example, antibiotics, drugs, inhibiting agents, anti-inflammatory agents, combinations thereof, and the like. The therapeutic agents can be coated on patch 318 or they can be dispersed throughout the material that forms patch 318. Patch 318 can also be fabricated from non-absorbable or bio-resorbable materials. Other treatment devices as described below also may be employed.

[0041] Referring now to FIG. 4, end effector 200 is shown having first arm 402 and second arm 404. First arm 402 and second arm 404 are configured to engage and manipulate tissue. In some embodiments, second arm 404 includes a tissue piercing needle 406. In some embodiments, implant device 410 includes suture 412 that is attached to implant 414. In some embodiments implant 414 can be, but is not limited to, a drug delivery device, such as for example a delayed delivery material, delayed absorbable drug eluding material, selectively drug permeable material or membrane, time release delivery device, combination thereof, or the like. In alternative embodiments, implant 414 can be, but is not limited to a stimulator device, such as for example, an electrical stimulation device, mechanical stimulation device, vibratory device, sound stimulation device, ultra-sound stimulation device, combinations thereof, or the like. In

some embodiments, the stimulation device can be configured to stimulate a sense of a patient. In a preferred embodiment, the sense stimulated by the stimulation device can be a sense of satiety in the patient such that the patient's desire for eating is subsided. In further alternative embodiments, implant 414 can be, but is not limited to, a sensory device, such as for example, a device to monitor pH, pressure, temperature, salinity, hydration, cellular activity, protein levels, glucose levels, insulin levels, hormone levels, biological function, biological secretion, cellular uptake, cellular secretion, combinations thereof, and the like. In further embodiments, implant 414 can be, but is not limited to, a device to control biological activity, such as for example, inter or intra cellular pH, temperature, salinity, cellular function, cellular excretion, cellular uptake, glucose levels, insulin levels, combinations thereof, and the like. In alternative embodiments, suture 412 can be resorbable suture material or non-resorbable suture material.

[0042] In some embodiments, first arm 402 and second arm 404 are positioned with respect to tissue that is to be manipulated. The arms are manipulated by actuating a control on endoluminal surgical device 100. When first arm 402 and second arm 404 are actuated, they move toward each other and tissue positioned between the arms is engaged and pierced with needle 406. In some embodiments, needle 406 is coupled with suture 412, and suture 412 is attached to implant device 410. Following activation of the arms and piercing tissue with needle 406, suture 412 is pierced through the tissue and extends through the tissue with implant device 410 on one side of the pierced tissue and a free end of suture 412 on the other side of the pierced tissue. Alternatively, suture 412 can be formed as a loop to be secured around a natural or formed anatomical feature, such as a plication, utilizing first and second arms 402 and 404 without piercing the tissue.

[0043] According to FIG. 5, implant device 500 is shown implanted with respect to tissue of a patient. According to an embodiment, tissue, such as stomach wall tissue 504 and stomach mucosa 502 are formed into a plication 520. Plication 520 is affixed with an anchor object that includes pledgets 506 and 510. In some embodiments, pledgets 506 and 510 can be coupled together with a tee bar 508 and suture 512 and in other embodiments pledgets can be coupled together only with suture 512. Implant 514 is attached to the anchor object. According to some embodiments, as shown in FIG 5, implant 514 can be integral with pledget 510, coupled with pledget 510, or removable

coupled with pledget 514. In some embodiments, the coupling between pledget 510 and implant 514 can be degradable over a predetermined time such that implant 514 become detached from pledget 510. According to other embodiments, implant 514 can be any of the implant devices, sensors, drugs, drug delivery devices, monitors, control devices, combinations thereof, and the like that are described herein and/or incorporated into this application by reference. For example, as shown in FIG. 5A, implant 514 is incorporated directly into pledget 510.

[0044] Referring now to FIG. 6, end effector 200 is shown having first arm 602 and second arm 604. Second arm is shown having needle 606 for piercing tissue, however, as will be appreciated first arm 602 and second arm 604 and the components associated therewith can be interchanged such that needle 606 could be associated with first arm 602, and the like. Needle 606 is coupled or threaded with suture 612, which includes a pledget 610 associated therewith. As shown in FIG. 6, first arm 602 is configured to couple with implant 614. Implant 614 further includes an affixing portion 616 for engaging with needle 606 and coupling thereto to bind tissue therebetween. In some embodiments, implant 614 can be any of the implant devices described herein or incorporated herein by reference. In other embodiments, suture 612 and pledget 610 can be fabricated according to other embodiments described herein or incorporated herein by reference.

[0045] According to FIG. 7, a plication 720 can be formed from a tissue wall or lining 704 that may or may not include a mucosa 702. Plication 720 is formed from binding tissue 704 with an anchor object that includes pledgets 706 and 710. In some embodiments, pledgets 706 and 710 can be coupled with suture 712 and tee bar 708. According to some embodiments, implant 714 can be implanted with anchor object by coupling implant 714 between tissue wall 704 or tissue mucosa 702 and pledget 706.

[0046] According to other embodiments, as shown in FIG. 8, implant 814 can be implanted on a tether such that implant 814 is relatively affixed to tissue but not rigidly affixed to any particular tissue. According to FIG. 8, end effector 200 includes first arm 802, second arm 804, and tissue retractor 806. Second arm 804 includes tissue piercing needle 808 for piercing tissue and implanting implant 814. Needle 808 further includes

suture 812 for affixing tissue that is pierced by needed 808 into a plication. Suture 812 can include pledget 810 for biasing against tissue. In some embodiments, suture 812 extends further beyond pledget 810 and couples with implant 814. In other embodiments, second suture 816 extends from pledget 810 and couples with implant 814. According to such embodiments, implant 814 is implanted into a patient and affixed into a general location, however, implant 814 is semi-free to move within patient to the extent of tether provided between pledget 810 and implant 814. FIG. 9 shows tethered implant 814 in an implanted position with respect to a tissue plication 920. According to some embodiments, plication 920 is formed by anchoring a plication of tissue with an anchor object that includes implant 814 tethered thereto by second suture 816.

[0047] Referring now to FIGS. 10-12C, a plication that forms an open pocket or biologic tube is shown. In FIG. 10, an end effector 200 has a first arm 1002, a second arm 1004, and a tissue retractor 1014 and is used to form a tissue plication 1006, as described herein. Plication 1006 is formed by grasping tissue with retractor 1014 and manipulating first arm 1002 and second arm 1004 together such that needle 1008 pierces the tissue. Suture 1012 is associated with needle 1008 such that suture 1012 is pierced through tissue with needle 1008. After piercing the tissue with needle 1008, the tissue is retained on needle 1008. Referring now to FIG. 11, retractor 1014 is used a second time to grasp a second portion of tissue such that the tissue can be positioned with respect to first arm 1002, second arm 1004, and needle 1008 and be pierced with needle 1008 to form second plication 1102. By forming two adjacent plications 1006 and 1102, an open pocket 1104 is formed. In some embodiments, an implant 1106 is housed in open pocket 1104.

[0048] In some embodiments, end effector 200 can have multiple retractors 1014 such that the retractor does not have to be removed from the tissue after forming a first plication in order to form a second plication. In other words, a first retractor 1014 can grasp tissue and form a first plication while a second retractor grasps other tissue and forms a second plication. Next, the two plications can be anchored together such that an open pocket 1104 is formed therebetween. In yet other embodiments, tissue graspers are introduced into the surgical site percutaneously for grasping tissue and manipulating it into adjacent plications that form the tube or open pocket 1104. In some embodiments, the tissue graspers pull tissue around the shaft 102 of the surgical device and position the

tissue for implantation of the anchor object. Next, an anchor object is implanted to fasten the plications around the shaft of the surgical device. After the desired number of plications are fixed around the shaft of the surgical device, the end effector 200 is straightened such as to be axially aligned with shaft 102 and the shaft 102 and end effector 200 are removed through the open pocket 1104 of the tissue plications, leaving behind open pocket 1104, or as shown in FIGS. 12B and 12C artificial tissue tube 1250.

[0049] According to some embodiments, as shown in FIG. 12A, tissue 1220 that forms pocket 1104 between plications 1006 and 1102 may be tissue that requires treatment or can be used for locating a treatment. According to such embodiments, implant 1106 positioned in pocket 1104 is configured to treat tissue 1220 or otherwise provide treatment to surrounding areas. In other embodiments, tissue 1220 can be removed following the double plication procedure described with respect to FIGS. 10-12A. In other embodiments, tissue 1220 may dissolve or resorb following the double plication procedure.

[0050] In other embodiments, multiple double plication procedures, such as the double plication procedure described with respect to FIGS. 10-12 can be performed on the same tissue, in the same organ, or the like. In some embodiments, as shown in FIGS. 12B-12C axially aligned double plications 1240, 1242, 1244, and 1246 can be positioned adjacent to each other such that each open pocket 1104, formed between the plications 1006 and 1102, is generally aligned and forms an artificial biological tube 1250. In some embodiments, artificial biological tube 1250 is formed by drawing each double plication together. In some embodiments, each plication 1240, 1242, 1244, and/or 1246 can be drawn together using surgical glue, suture material, surgical wire, staples, scoring the tissue such that the tissue reforms together, combinations thereof, or the like.

[0051] In some embodiments, vertically aligned double plications 1240, 1242, and 1244 are positioned, beginning at or distally near the gastro-esophageal-junction (GEJ) 1252 and extend into the stomach, thereby forming an artificial GEJ or gastric tube 1250. In some embodiments, when the artificial gastric tube is flaccid, *i.e.*, empty, the artificial gastric tube acts as a gastric flap or valve for protecting the esophagus from gastric fluids. Thus, the formation of such an artificial gastric tube can be a treatment for gastro-

esophageal reflux disorder (GERD). In other embodiments, the formation of an artificial gastric tube can be a technique for gastric reconstruction or reduction surgery. According to such embodiments, the formation of such an artificial gastric tube effectively reduces the volume of the stomach of a patient, and thereby, stimulates the stomach into providing a sense of satiety with consumption of a smaller amount of food. According to some embodiments, between 1 and about 10 plications are positioned adjacent each other to form artificial tube 1250. In other embodiments, between 1 and about 8 plications are positioned adjacent each other to form artificial tube 1250. In yet other embodiments, between 1 and about 5 plications are positioned adjacent each other to form artificial tube 1250. In yet other embodiments, between 1 and about 3 plications are positioned adjacent each other to form artificial tube 1250. In still other embodiments, a single plication is positioned adjacent the GEJ to form artificial tube 1250 or GERD treatment. According to other embodiments, between about 5 and about 8 plications are positioned adjacent each other to form artificial tube 1250. According to some embodiments, when artificial tube 1250 is formed with between one and two tissue plications, artificial tube 1250 is about 1 cm in length. In other embodiments, when artificial tube 1250 includes between about 10 to about 20 tissue plications, artificial tube 1250 is about 10 cm in length. In some embodiments, the diameter of artificial tube 1250 is between about 0.2 cm and about 10 cm. In other embodiments, the diameter of artificial tube 1250 is between about 0.5 cm and about 5 cm. In some embodiments, the diameter of artificial tube 1250 is between about 0.5 cm and about 3 cm. In some embodiments, the diameter of artificial tube 1250 is between about 0.5 cm and about 2 cm.

[0052] According to another embodiment, an implant device 1306 can be implanted onto tissue 1302 with multiple attachments, as shown in FIGS. 13A and 13B. According to some embodiments as shown in FIG. 13A, an implant 1306 can be located or held in position by coupling retractors 1304A – 1304D to tissue 1302 and/or implant device 1306. In some embodiments, as shown in FIG. 13B, implant 1306 may be such a shape or dimension that multiple anchor implants are required for proper or secure attachment of implant 1306 to tissue 1302. As shown in FIG. 13B, multiple anchors 1308A – 1308D are implanted through tissue 1302 and implant 1306 to affix implant 1306 as desired to tissue 1302. According to some embodiments, anchors 1308A – 1308D include pledgets

1310 and suture 1312. According to some embodiments, pledgets 1310 and suture 1312 can be fabricated in accord with and from the materials of other pledgets and sutures described herein and incorporated herein by reference.

[0053] Referring now to FIG. 14, anchor implant 1400 includes a coupling 1402 and pledgets 506 and 510 coupled together by suture 512. Anchor implant 1400 is configured to couple tissue 502, 504 to itself or to an implanted device. According to some embodiments, coupling 1402 is configured to provide a site on anchor implant 1400 for attaching an implantable device, mechanical tool, drug eluding device, sensor, other device described or incorporated herein, combinations thereof, or the like. In some embodiments, coupling 1402 can be, but is not limited to a hook, clip, Velcro, magnet, loop, combinations thereof, or the like. According to some embodiments, coupling 1402 can be formed from a non-resorbable polymer, resorbable polymer, biodegradable polymer, drug eluding polymer, stainless steel, titanium, cobalt chromium, surgical material, combinations thereof, or the like.

[0054] According to another embodiment, as shown in FIG. 17, endoluminal surgical device 100 includes guide wire 1702 that includes tissue engaging retractor tip 1704. According to some embodiments, tissue engaging retractor tip 1704 is configured to releasable attach to tissue at a site near where an implant attachment site is targeted. In some embodiments, tissue engaging retractor tip 1704 can be, but is not limited to a cork-screw type design, screw threads, a hook, a loop, jaws, locking jaws, combinations thereof, and the like. In use, having a guide wire 1702 that can attach to tissue or target a tissue at or near an implant site can help direct where the implant device will pass and increases the efficiency and effectiveness of surgical procedures because the path that the device is require to pass is less rigorous and/or straighter.

[0055] Referring now to FIGS. 15A and 15B, an adjustable implantable device 1500 is shown. In some embodiments, adjustable implantable device 1500 includes anchor implants 1506 and 1508, however, the number of anchor implants used in practice can vary to what is necessary for a particular procedure being performed, corrected, or desired. In some embodiments, anchor implants include pledgets 1510 connected by suture 1512. In some embodiments, anchor implant 1506 is coupled with adjustment

mechanism 1514 by suture 1516 and anchor implant 1508 is coupled with adjustment mechanism 1514 by suture 1518. Adjustment mechanism 1514 is configured to adjust a physical parameter, such as for example, length, width, diameter, rotational axis, combinations thereof, or the like, in response to stimulation. In a preferred embodiment, adjustment mechanism 1514 linearly shortens in response to a predetermined stimulation. In some embodiments, a predetermined stimulation can be, but is not limited to, a radio frequency, ultra-sound, mechanical force, pressure, direct mechanical manipulation, magnetic force, chemical interaction, enzyme interaction, fluid, temperature, biological fluid, cellular interaction, cellular by-product, inter-cellular constituent, intra-cellular constituent, food, digestion by-product, time, combinations thereof, or the like.

[0056] In some embodiments, adjustable implant device 1500 is implanted into the tissue surrounding the gastro-esophageal-junction (GEJ). Having the adjustable implant device 1500 implanted in or near the GEJ allows the adjustable implant device 1500 to assist or augment the natural function of the GEJ. According to an embodiment, in a relaxed state adjustable implant device 1500 leaves the GEJ in an open state such that food, liquids, or the like can be passed from the esophagus into the stomach of a patient. However, following activation, adjustable mechanism 1514 shortens and, thereby, tightens the GEJ such that gastric fluids are blocked from passing from the stomach into the esophagus and causing or worsening a patient's GERD condition. In some embodiments, adjustable mechanism 1514 can be a threaded mechanism, a coil mechanism, a spring mechanism, a magnetic mechanism, a ratchet mechanism, memory material, piezoelectric material, temperature sensitive material, combinations thereof, or the like.

[0057] In an alternative embodiment, adjustable implant device 1500 can be implanted in a stomach of a patient. Implanting adjustable implant device 1500 into a stomach allows a patient or physician to reversibly and/or temporarily restrict the volume of the stomach of a patient in response to a predetermined stimulus. According to some embodiments adjustable implant device 1500, when implanted in the stomach of a patient, can be retracted or adjusted prior to consuming food and thereby act as a temporary gastric restriction device. In some embodiments, adjustable implant device 1500 can be configured to respond to a digestive by-product, a cellular excretion, particular gastric fluids, an external stimulation, combinations thereof, or the like. It will be appreciated

that adjustable implant device 1500 can be implanted in many locations in a patient, such as but not limited to, any sphincter, tubular organ such as the intestine, muscle, skeletal system, combinations thereof, or the like.

[0058] Referring now to FIG. 16, a surgical stabilization system is shown. According to some surgical procedures a surgical device needs to be inserted through tissue, a tissue wall such as an abdominal wall, an organ wall such as the stomach, or the like. Often, when performing such surgical procedures a surgeon loses much control over a working end of a surgical instrument after the instrument has been passed through the tissue wall. According to an embodiment of the present invention, devices and mechanisms for improving surgical dexterity includes attaching stabilizers such as stabilizers 1406, 1414, and 1422 to tissue 1402 and shaft of implant device 102. According to alternative embodiments, more or less stabilizers can be utilized depending the requirements of a particular situation. For simplicity sake only one stabilizer will be described, however, it will be appreciated that each stabilizer includes generally the same construction.

According to some embodiments, a stabilizer, such as stabilizer 1406 for example, includes a tissue anchor end and a device anchor end. The tissue anchor end includes pledgets 1416 and 1417 connected by suture material 1418. Pledgets 1416 and 1417 and suture material 1418 can be implanted according to methods and with devices disclosed herein or incorporated herein by reference. Pledget 1417 is further connected to line 1420 that extends from pledget 1417 to device 102. Line 1420 can be, but is not limited to, suture material, wire, rods, k-wires, t-bars, or other surgical material or devices that can support tension, pressure, and/or torque. According to some embodiments, the device anchoring end of stabilization 1418 can be configured to couple to an attachment on device 102 such that a force applied to stabilizer 1418 can be translated to device 102 and/or manipulation force applied to device 102 can be leveraged over and around stabilization 1418. It will be appreciated that stabilization devices can be implanted as desired to assist in manipulating surgical device 102.

WHAT IS CLAIMED IS:

1. An implant device, comprising:
a medical implant configured to be implanted into a lumen of a body without creating an incision in skin;
the medical implant being configured to maintain a plication in a wall of the lumen;
wherein the medical implant applies a medical treatment to the body after implantation.
2. The implant of claim 1, wherein the medical implant comprises a member selected from the group consisting of a drug delivery device, a time released drug delivery device, a coating, a biological stimulation device, a monitoring device, a feeding tube, a bioresorbable material, and combinations thereof.
3. The implant of claim 1, wherein the medical treatment includes material selected from the group consisting of radioactive material, chemotherapy material, biological material, and combinations thereof.
4. The implant of claim 1, wherein the medical implant comprises bioresorbable material including a drug.
5. An endoscopic treatment method, comprising:
introducing an endoscopic device into a lumen of a patient without creating an incision in the patient's skin;
engaging a wall of the lumen with an end effector of the endoscopic device to form a plication; and
activating the end effector to secure the plication with an anchor object and a treatment device, wherein the treatment device is coupled with the anchor object, wherein the treatment device applies a medical treatment to the patient after the plication is secured.

6. The method of claim 5, wherein the treatment device includes a drug delivery device.
7. The method of claim 5, wherein the treatment device includes material selected from the group consisting of radioactive material, chemotherapy material, biological material, and combinations thereof.
8. The method of claim 5, wherein the treatment device includes a bioresorbable material including a drug.
9. An endoscopic treatment method, comprising:
 - introducing an endoscopic device into a body cavity of a patient without creating an incision in the patient's skin;
 - introducing a treatment device into the cavity;
 - engaging a wall of the cavity with an end effector of the endoscopic device;
 - forming a plication in the wall of the cavity such that an open pocket is formed in the wall of the cavity; and
 - coupling an implant device with the plication, wherein the implant device delivers a drug to the patient.
10. An endoscopic treatment method, comprising:
 - introducing an endoscopic device into a lumen of a patient without creating an incision in the patient's skin;
 - introducing a treatment device into the lumen;
 - engaging a wall of the lumen with an end effector of the endoscopic device; and
 - forming a plication in the wall of the lumen such that an open pocket is formed in the wall of the lumen.
11. The method of claim 10, further comprising forming an artificial biological tube by forming multiple plications such that open pockets formed by the multiple plications are axially aligned.

12. The method of claim 10, further comprising:
 - forming a second plication in the wall of the lumen such that a second open pocket is formed in the wall of the lumen, wherein the plications are adjacent, and wherein the open pockets are axially aligned; and
 - coupling the plication with the second plication.
13. The method of claim 10, further comprising:
 - forming a second plication in the wall of the lumen adjacent the first plication;
 - and
 - coupling the first plication with the second plication to thereby form a first double plication;
 - wherein the open pocket is formed between the first plication and the second plication.
14. An endoscopic GERD treatment method, comprising:
 - introducing an endoscopic device into a lumen of a patient without creating an incision in the patient's skin;
 - engaging a wall of the lumen with an end effector of the endoscopic device;
 - forming a plication in the wall of the lumen near the patient's gastro-esophageal junction such that an artificial biologic tube is formed distal to the gastro-esophageal junction to block gastric fluid from interfering with tissue of the patient's esophagus.
15. An endoscopic obesity treatment method, comprising:
 - introducing an endoscopic device into a stomach of a patient without creating an incision in the patient's skin;
 - engaging a wall of the stomach with an end effector of the endoscopic device;
 - forming a plication in the wall of the stomach such that an artificial biologic tube is formed within the stomach of the patient, thereby reducing a volume of the stomach to treat obesity.

16. An endoscopic treatment method, comprising:
introducing an endoscopic device into a lumen of a patient without creating an incision in the patient's skin;
introducing a treatment device into the lumen;
engaging a wall of the lumen with an end effector of the endoscopic device;
forming at least one first plication in the wall of the lumen;
forming at least one second plication in the wall of the lumen adjacent the first plication;
coupling the first plication with the second plication to thereby form at least one first double plication;
wherein an open pocket is formed between the first plication and the second plication;
wherein the double plication is positioned in cooperative relationship with the patient's gastro-esophageal-junction so as to form an artificial gastric valve.
17. An endoscopic treatment method, comprising:
introducing an endoscopic device into a lumen of a patient without creating an incision in the patient's skin;
introducing a treatment device into the lumen;
engaging a wall of the lumen with an end effector of the endoscopic device;
forming at least one first plication in the wall of the lumen;
forming at least one second plication in the wall of the lumen adjacent the first plication;
coupling the first plication with the second plication to thereby form at least one first double plication, wherein an open pocket is formed between the first plication and the second plication; and
coupling an implant device with the first or second plication.
18. The method of claim 17, wherein the implant device is a drug delivery device.

19. An endoscopic treatment method, comprising:
introducing an endoscopic device into a lumen of a patient without creating an incision in the patient's skin;
introducing a treatment device into the lumen;
engaging a wall of the lumen with an end effector of the endoscopic device;
forming at least first and second plications in the wall of the lumen such that at least first and second open pockets are formed in the wall of the lumen;
wherein the plications are adjacent, and wherein the open pockets are axially aligned.
20. An endoscopic treatment method, comprising:
introducing an endoscopic device into a lumen of a patient without creating an incision in the patient;
introducing a treatment device into the lumen;
engaging a wall of the lumen with a tissue grasper inserted into the lumen;
forming a plication in the wall of the lumen with the tissue grasper; and
anchoring the plication with an anchor object such that an open pocket is formed in the wall of the lumen.
21. A system for endoscopic treatment, comprising:
an endoscopic device configured and dimensioned to be introduced into a lumen of a patient without creating an incision in the patient;
a tissue grasper configured to engage a wall of the lumen from within the lumen and to form a plication in the wall; and
an anchor object configured to anchor the plication such that an open pocket is formed in the wall.
22. A medical implant apparatus, comprising:
an anchor object configured to couple with tissue; and
an adjustable mechanism configured to interact with the anchor object such as to apply alternative forces upon the anchor object in response to a stimulus.

23. The implant of claim 22, wherein the adjustable mechanism includes a member selected from the group consisting of: piezoelectric material, magnetic material, screw-threads, a spring, a memory metal, elastic material, a mechanical mechanism, a temperature sensitive material, and combinations thereof.
24. The implant of claim 22, wherein the stimulus is selected from the group consisting of: a radio frequency, ultra-sound, a mechanical force, pressure, direct mechanical manipulation, a magnetic force, a chemical interaction, enzyme interaction, a fluid, a temperature, a biological fluid, cellular interaction, a cellular by-product, an inter-cellular constituent, an intra-cellular constituent, food, a digestion by-product, a lapse of time, and combinations thereof.
25. A method for temporary tissue restructuring, comprising:
implanting an anchor object onto tissue to be adjustably restructured;
associating an adjustable mechanism with the anchor object such that a force generated by the adjustable mechanism can change a position of the anchor object with respect to the adjustable mechanism, and thereby restructure the tissue; and
stimulating the adjustable mechanism to generate the force.
26. The method of claim 25, further comprising shortening the adjustable mechanism in response to a stimulus and thereby resulting in a distance between the adjustable mechanism and the anchor object reducing such as to tighten tissue between the anchor object and the adjustable mechanism.
27. A method of manipulating a surgical tool, comprising:
forming an incision in body tissue;
attaching a manipulation line to body tissue near the incision;
introducing the surgical tool through the incision in the body tissue;
attaching a free end of the manipulation line to the surgical tool; and
manipulating the surgical tool to perform a medical treatment procedure.

28. The method of claim 27, wherein the manipulation line at least partially supports the surgical tool.
29. The method of claim 27, further comprising applying tension, pressure, or torque to the manipulation line.
30. A surgical tool support system, comprising:
- an elongate member configured for insertion into a body cavity;
 - an anchor object configured and dimensioned to be manipulated by said elongated member to be attached to a body tissue within said cavity; and
 - a manipulation line extending from the anchor object and configured and dimensioned to extend outside said body cavity for manipulation of tissue secured by the anchor object.

1/19




FIG. 1

2/19




FIG. 2

3/19




FIG. 3

4/19




FIG. 4

5/19




FIG. 5

6/19




FIG. 6

7/19




FIG. 7

8/19




FIG. 8

9/19




FIG. 9

10/19




FIG. 10

11/19




FIG. 11

12/19




FIG. 12A

13/19




FIG 12B

14/19




FIG. 12C

15/19




FIG. 13A




FIG. 13B

16/19




FIG. 14

17/19




FIG. 15A




FIG. 15B




FIG. 16

19/19




FIG. 17