



(12) **DEMANDE DE BREVET CANADIEN**
CANADIAN PATENT APPLICATION
(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2017/02/02
(87) Date publication PCT/PCT Publication Date: 2017/08/10
(85) Entrée phase nationale/National Entry: 2018/07/27
(86) N° demande PCT/PCT Application No.: US 2017/016155
(87) N° publication PCT/PCT Publication No.: 2017/136512
(30) Priorité/Priority: 2016/02/05 (EP16154490.3)

(51) Cl.Int./Int.Cl. *C11D 1/83* (2006.01),
C11D 17/04 (2006.01), *C11D 3/20* (2006.01),
C11D 3/43 (2006.01)
(71) Demandeur/Applicant:
THE PROCTER & GAMBLE COMPANY, US
(72) Inventeurs/Inventors:
KEULEERS, ROBBY RENILDE FRANCOIS, BE;
LA BEQUE, REGINE, BE;
SCHITTKO, STEFAN, BE
(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : COMPOSITION DE DETERGENT A LESSIVE LIQUIDE
(54) Title: LIQUID LAUNDRY DETERGENT COMPOSITION

(57) **Abrégé/Abstract:**

A liquid laundry detergent composition suitable for formulation into a water-soluble unit dose article, wherein the liquid laundry detergent composition comprises; a. an anionic surfactant; b. a non-ionic surfactant; c. 1,2-propanediol; d. dipropylene glycol; and a water-soluble unit dose article comprising said liquid laundry detergent composition.

- (51) International Patent Classification:
C11D 1/83 (2006.01) *C11D 3/43* (2006.01)
C11D 3/20 (2006.01) *C11D 17/04* (2006.01)

(21) International Application Number:
PCT/US2017/016155

(22) International Filing Date:
2 February 2017 (02.02.2017)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
16154490.3 5 February 2016 (05.02.2016) EP

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).

(72) Inventors: **KEULEERS, Robby, Renilde, Francois**; NV Procter & Gamble Services Company SA, Temselaan 100, Strombeek-Bever, 1853 Brussels (BE). **LA BEQUE, Reginine**; NV Procter & Gamble Services Company SA, Temselaan 100, Strombeek-Bever, 1853 Brussels (BE). **SCHITTKO, Stefan**; NV Procter & Gamble Services Company SA, Temselaan 100, Strombeek-Bever, 1853 Brussels (BE).

(74) Agents: **KREBS, Jay, A.** et al.; c/o The Procter & Gamble Company, Global Patent Services, One Procter & Gamble Plaza, C8-229, Cincinnati, OH 45202 (US).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report (Art. 21(3))*

(54) Title: LIQUID LAUNDRY DETERGENT COMPOSITION

(57) Abstract: A liquid laundry detergent composition suitable for formulation into a water-soluble unit dose article, wherein the liquid laundry detergent composition comprises; a. an anionic surfactant; b. a non-ionic surfactant; c. 1,2-propanediol; d. dipropylene glycol; and a water-soluble unit dose article comprising said liquid laundry detergent composition.

LIQUID LAUNDRY DETERGENT COMPOSITION

FIELD OF THE INVENTION

The present invention relates to liquid laundry detergent compositions, unit dose articles
5 comprising said detergents and use of said liquid laundry detergent compositions and unit dose articles.

BACKGROUND OF THE INVENTION

Liquid laundry detergent compositions are available in the form of water-soluble unit
10 dose articles. Such water-soluble unit dose articles are preferred by consumers as they are convenient to use and reduce accidental spillage during detergent dosage in the wash operation.

Such water-soluble unit dose articles comprise a water-soluble film, preferably a polyvinylalcohol containing film that is formed into a pouch comprising an internal compartment. The liquid laundry detergent composition is comprised within the internal
15 compartment such that the liquid laundry detergent composition is surrounded by the film and in contact with the film that forms the inner surface of the internal compartment.

During manufacture, a first film is deformed in a mould to form an open cavity into which the liquid laundry detergent composition is added via a filling nozzle. After filling a second film is laid over the open filled cavity and sealed to the first film about a seal area.

20 However, an issue is that the liquid laundry detergent composition tends to 'string' between the cavity and the filling nozzle. This 'stringing' is the phenomenon wherein due to the properties of the liquid it remains attached to the nozzle forming a 'capillary' between the nozzle and the open cavity. As the apparatus moves the filled cavity away from the nozzle and brings a new cavity to be filled into position underneath the nozzle, the distance between the nozzle and
25 filled cavity is sufficient to break the 'string'. However, this results in some of the liquid laundry detergent composition from the string accidentally falling onto other parts of the open unit dose article such as the seal area. This can affect the ability of the two films to be sealed together and can result in premature rupture or failure of the unit dose article.

Therefore, there is a need in the art for a liquid laundry detergent composition suitable
30 for use in a water-soluble unit dose article whereby the instances of stringing of the liquid laundry detergent composition during manufacture of water-soluble unit dose articles comprising said liquid laundry detergent composition are reduced.

It was surprisingly found that the liquid laundry detergent composition of the present invention wherein the presence of 1,2-propanediol and dipropylene glycol in specific ratio to one another and presence of anionic and non-ionic surfactants in specific ratios to one another addressed this technical problem.

5 It was also further surprisingly found that when formed into a water-soluble unit dose article the plasticization properties of the film as manufactured were minimally affected by contact with the liquid detergent of the present invention over time. Upon manufacture of the film, it has certain dissolution and tensile properties. Careful balance of the film plasticization properties are needed to ensure the film is not too 'floppy' hence affecting the unit dose article
10 aesthetics and its dissolution characteristics when contacting water, and not too brittle, leading to unwanted premature rupture of the unit dose article ahead of use. This plasticization of the film can be negatively affected by contact with the liquid detergent over time.

In addition it was also surprisingly found that water-soluble unit dose articles comprising compositions according to the present invention exhibited improved dissolution profiles in water
15 as compared to comparative water-soluble unit dose articles.

SUMMARY OF THE INVENTION

A first aspect of the present invention is a liquid laundry detergent composition suitable for formulation into a water-soluble unit dose article, wherein the liquid laundry detergent
20 composition comprises;

- a. an anionic surfactant;
- b. a non-ionic surfactant;
- c. 1,2-propanediol;
- d. dipropylene glycol;

25 wherein the weight ratio of the anionic surfactant to the non-ionic surfactant is from 5:1 to 1:1, preferably from 3.5:1 to 1.25:1, more preferably from 2.5:1 to 1.5:1;
wherein the total weight percentage of the 1,2-propanediol and dipropylene glycol is between 5% and 25% by weight of the liquid laundry detergent composition, and
wherein the weight ratio of 1,2-propanediol to dipropylene glycol is between 1:1 and 10:1,
30 preferably between 1:1 and 5:1, most preferably between 2:1 and 4:1; and
wherein the liquid laundry detergent composition comprises between 0.5% and 20% by weight of the liquid laundry detergent composition of water.

A second aspect of the present invention is a water-soluble unit dose article comprising a water-soluble film and a liquid laundry detergent composition according to the present invention.

5 A third aspect of the present invention is a process of washing fabrics comprising the steps of contacting the liquid laundry detergent composition or unit dose article according to the present invention with water such that the liquid laundry detergent composition is diluted in water by at least 400 fold to form a wash liquor, and contacting fabrics with said wash liquor.

10 A fourth aspect of the present invention is the use of a liquid laundry detergent composition according to the present invention for reducing stringing of the liquid laundry detergent composition during manufacture of water-soluble unit dose articles, for controlling plasticization properties of a film when formulated into a water-soluble unit dose article, for improving dissolution profiles in water of water-soluble unit dose articles comprising said liquid laundry detergent composition, or a mixture thereof.

15 DETAILED DESCRIPTION OF THE INVENTION

Liquid laundry detergent composition

The present invention is to a liquid laundry detergent composition suitable for formulation into a water-soluble unit dose article. Water-soluble unit dose articles are described
20 in more detail below.

The liquid laundry detergent composition comprises;

- a. an anionic surfactant;
- b. a non-ionic surfactant;
- c. 1,2-propanediol;
- 25 d. dipropylene glycol.

The weight ratio of the anionic surfactant to the non-ionic surfactant is from 5:1 to 1:1, preferably from 3.5:1 to 1.25:1, more preferably from 2.5:1 to 1.5:1. For the avoidance of any doubt, by 'weight of the anionic surfactant' we herein mean the total weight of all anionic surfactant present. In accordance with the present invention the term 'anionic surfactant' does
30 not include fatty acids or their corresponding salt (soap).

By 'weight of non-ionic surfactant' we herein mean the total weight of all non-ionic surfactant present.

Preferably, the liquid laundry detergent composition comprises 22% and 32%, more preferably between 25% and 29% by weight of the liquid laundry detergent composition of the anionic surfactant. The anionic surfactant and non-ionic surfactants are described in more detail below.

5 The total weight percentage of the 1,2-propanediol and dipropylene glycol is between 5% and 25%, preferably between 10% and 20%, most preferably between 13% and 17% by weight of the liquid laundry detergent composition. The weight ratio of 1,2-propanediol to dipropylene glycol is between 1:1 and 10:1, preferably between 1:1 and 5:1, most preferably between 2:1 and 4:1.

10 Dipropylene glycol and 1,2-propanediol are commercially available materials and any commercial available 1,2-propanediol and dipropylene glycol is suitable for the present invention. Those skilled in the art will know how and where to source such materials. Dipropylene glycol is commercially available from Dow Chemical Company headquartered in Michigan, USA or Adeka Corporation with headquarters in Tokyo, Japan.

15 The liquid laundry detergent composition may comprise a fatty acid or salt thereof. Preferably, the liquid laundry detergent composition comprises between 3% and 10%, more preferably between 5% and 7% by weight of the liquid laundry detergent composition of a fatty acid or salt thereof. The fatty acid or salt thereof is described in more detail below.

20 The liquid laundry detergent composition comprises between 0.5% and 20%, more preferably between 1% and 15%, most preferably between 5% and 12% by weight of the unit dose article of water.

 The liquid laundry detergent composition may comprise glycerol, preferably wherein the glycerol is present between 2 and 10%, more preferably between 3% and 5% by weight of the liquid laundry detergent composition.

25 The liquid laundry detergent composition may comprise an alkanolamine, preferably the alkanolamine comprises monoethanolamine, triethanolamine or a mixture thereof, most preferably the alkanolamine comprises monoethanolamine. Preferably, the liquid laundry detergent composition comprises between 5% and 15%, more preferably between 8% and 12% by weight of the liquid laundry detergent composition of the alkanolamine, preferably of
30 monoethanolamine, triethanolamine or a mixture thereof, most preferably of monoethanolamine.

 Preferably, the liquid laundry detergent composition has a pH between 6 and 10, more preferably between 6.5 and 8.9, most preferably between 7 and 8. The pH of the liquid laundry detergent composition may be measured as a 10% dilution in demineralized water at 20°C.

Without wishing to be bound by theory, it is believed that it is the presence specifically of 1,2-propanediol and dipropylene glycol at a specific ratio as well as of the anionic and nonionic surfactant at a specific ratio to one another that ensures a lower extensional rheology profile and as such a reduced stringing behavior of the liquid laundry detergent composition.

5 The liquid laundry detergent composition may comprise a hydrogenated castor oil. The hydrogenated castor oil is described in more detail below.

The liquid laundry detergent composition may comprise an adjunct ingredient preferably selected from hueing dyes, polymers, surfactants, builders, dye transfer inhibiting agents, dispersants, enzymes, enzyme stabilizers, catalytic materials, bleach activators, polymeric
10 dispersing agents, anti-redeposition agents, suds suppressors, aesthetic dyes, opacifiers, perfumes, perfume delivery systems, structurants, hydrotropes, processing aids, pigments and mixtures thereof.

Anionic surfactant

15 Preferably, the anionic surfactant is selected from linear alkylbenzene sulphonate, alkyl sulphate, alkoxylated alkyl sulphate or a mixture thereof.

Preferably, the anionic surfactant comprises alkylbenzene sulphonate and alkoxylated alkyl sulphate, wherein the weight ratio of alkylbenzene sulphonate to alkoxylated alkyl sulphate is between 3:1 and 1:1, more preferably between 2:1 and 1:1. More preferably, the anionic
20 surfactant comprises alkylbenzene sulphonate and ethoxylated alkyl sulphate, wherein the weight ratio of alkylbenzene sulphonate to ethoxylated alkyl sulphate is between 3:1 and 1:1, more preferably between 2:1 and 1:1.

Preferably, the liquid laundry detergent composition comprises 22% and 32%, more preferably between 25% and 29% by weight of the liquid laundry detergent composition of the
25 anionic surfactant. For the avoidance of any doubt, by 'weight percentage of the anionic surfactant' we herein mean the weight percentage of all anionic surfactant present. For example, wherein the composition comprises linear alkylbenzene sulphonate and alkoxylated alkyl sulphate the weight percentage of the anionic surfactant is the sum of the weight percentage of linear alkyl benzene sulphonate and the weight percentage of alkoxylated alkyl sulphate.

30 In accordance with the present invention the term 'anionic surfactant' does not include fatty acids or their corresponding salt (soap).

Suitable anionic surfactants useful herein can comprise any of the conventional anionic surfactant types typically used in liquid detergent products. These include the alkyl benzene sulfonic acids and their salts as well as alkoxyated or non-alkoxyated alkyl sulfate materials.

Exemplary anionic surfactants are the alkali metal salts of C₁₀-C₁₆ alkyl benzene sulfonic acids, or C₁₁-C₁₄ alkyl benzene sulfonic acids. In one aspect, the alkyl group is linear and such linear alkyl benzene sulfonates are known as "LAS". Alkyl benzene sulfonates, and particularly LAS, are well known in the art. Especially useful are the sodium, potassium and amine linear straight chain alkylbenzene sulfonates in which the average number of carbon atoms in the alkyl group is from about 11 to 14.

Specific, non-limiting examples of anionic surfactants useful herein include the acid or salt forms of: a) C₁₁-C₁₈ alkyl benzene sulfonates (LAS); b) C₁₀-C₂₀ primary, branched-chain and random alkyl sulfates (AS), including predominantly C₁₂ alkyl sulfates; c) C₁₀-C₁₈ secondary (2,3) alkyl sulfates with non-limiting examples of suitable cations including sodium, potassium, ammonium, amine and mixtures thereof; d) C₁₀-C₁₈ alkyl alkoxy sulfates (AE_xS) wherein x is from 1-30; e) C₁₀-C₁₈ alkyl alkoxy carboxylates in one aspect, comprising 1-5 ethoxy units; f) mid-chain branched alkyl sulfates; g) mid-chain branched alkyl alkoxy sulfates; h) modified alkylbenzene sulfonate; i) methyl ester sulfonate (MES); and j) alpha-olefin sulfonate (AOS).

In accordance with the present invention the term 'anionic surfactant' does not include fatty acids or their corresponding salt (soap).

Non-ionic surfactant

The non-ionic surfactant is selected from a fatty alcohol alkoxyate, an oxo-synthesised fatty alcohol alkoxyate, Guerbet alcohol alkoxyates, alkyl phenol alcohol alkoxyates or a mixture thereof.

The nonionic surfactant may comprise an ethoxylated nonionic surfactant. The ethoxylated nonionic surfactant may be, e.g., primary and secondary alcohol ethoxylates, especially the C₈-C₂₀ aliphatic alcohols ethoxylated with an average of from 1 to 50 or even 20 moles of ethylene oxide per mole of alcohol, and more especially the C₁₀-C₁₅ primary and secondary aliphatic alcohols ethoxylated with an average of from 1 to 10 moles of ethylene oxide per mole of alcohol.

The ethoxylated alcohol non-ionic surfactant can be, for example, a condensation product of from 3 to 8 mol of ethylene oxide with 1 mol of a primary alcohol having from 9 to 15 carbon atoms.

5 The non-ionic surfactant may comprise a fatty alcohol ethoxylate of formula $RO(EO)_nH$, wherein R represents an alkyl chain between 4 and 30 carbon atoms, (EO) represents one unit of ethylene oxide monomer and n has an average value between 0.5 and 20.

Hydrogenated castor oil

10 Hydrogenated castor oil (HCO) as used herein most generally can be any hydrogenated castor oil or derivative thereof, provided that it is capable of crystallizing in the liquid laundry detergent composition. Castor oils may include glycerides, especially triglycerides, comprising C_{10} to C_{22} alkyl or alkenyl moieties which incorporate a hydroxyl group. Hydrogenation of castor oil, to make HCO, converts the double bonds which may be present in the starting oil as ricinoleyl moieties. As such, the ricinoleyl moieties are converted into saturated hydroxyalkyl
15 moieties, e.g., hydroxystearyl. The HCO herein may be selected from: trihydroxystearin; dihydroxystearin; and mixtures thereof. The HCO may be processed in any suitable starting form, including, but not limited to those selected from solid, molten and mixtures thereof. The corresponding percentage of hydrogenated castor oil delivered into a finished laundry detergent product may be below 1.0%, typically from 0.1% to 0.8%. HCO may be present at a level of
20 between 0.01% and 1%, or even between 0.05% and 0.8% by weight of the liquid laundry detergent composition.

HCO of use in the present invention includes those that are commercially available. Non-limiting examples Elementis, Plc.

25 While the use of hydrogenated castor oil is preferred, any crystallisable glyceride can be used within the scope of the invention. Preferred crystallisable glyceride(s) have a melting point of from 40 °C to 100 °C.

Fatty acid or salt thereof

30 The term 'fatty acid' includes fatty acid or fatty acid salts. The fatty acids are preferably carboxylic acids which are often with a long unbranched aliphatic tail, which is either saturated or unsaturated. Suitable fatty acids include ethoxylated fatty acids. Suitable fatty acids or salts of the fatty acids for the present invention are preferably sodium salts, preferably C_{12} - C_{18} saturated and/or unsaturated fatty acids more preferably C_{12} - C_{14}

saturated and/or unsaturated fatty acids and alkali or alkali earth metal carbonates preferably sodium carbonate.

Preferably the fatty acids are selected from the group consisting of lauric acid, myristic acid, palmitic acid, stearic acid, topped palm kernel fatty acid, coconut fatty acid and mixtures thereof.

Water-soluble unit dose article

A second aspect of the present invention is a water-soluble unit dose article comprising a water-soluble film and a liquid laundry detergent composition according to the present invention. The water-soluble film is described in more detail below.

The water-soluble unit dose article comprises at least one water-soluble film shaped such that the unit-dose article comprises at least one internal compartment surrounded by the water-soluble film. The at least one compartment comprises the liquid laundry detergent composition. The water-soluble film is sealed such that the liquid laundry detergent composition does not leak out of the compartment during storage. However, upon addition of the water-soluble unit dose article to water, the water-soluble film dissolves and releases the contents of the internal compartment into the wash liquor.

The compartment should be understood as meaning a closed internal space within the unit dose article, which holds the liquid laundry detergent. Preferably, the unit dose article comprises a water-soluble film. The unit dose article is manufactured such that the water-soluble film completely surrounds the liquid laundry detergent composition and in doing so defines the compartment in which the liquid laundry detergent resides. The unit dose article may comprise two films. A first film may be shaped to comprise an open compartment into which the liquid laundry detergent is added. A second film is then laid over the first film in such an orientation as to close the opening of the compartment. The first and second films are then sealed together along a seal region. The film is described in more detail below.

The unit dose article may comprise more than one compartment, even at least two compartments, or even at least three compartments. The compartments may be arranged in superposed orientation, i.e. one positioned on top of the other. Alternatively, the compartments may be positioned in a side-by-side orientation, i.e. one orientated next to the other. The compartments may even be orientated in a 'tyre and rim' arrangement, i.e. a first compartment is positioned next to a second compartment, but the first compartment at least partially surrounds

the second compartment, but does not completely enclose the second compartment. Alternatively one compartment may be completely enclosed within another compartment.

Wherein the unit dose article comprises at least two compartments, one of the compartments may be smaller than the other compartment. Wherein the unit dose article
5 comprises at least three compartments, two of the compartments may be smaller than the third compartment, and preferably the smaller compartments are superposed on the larger compartment. The superposed compartments preferably are orientated side-by-side.

In a multi-compartment orientation, the liquid laundry detergent according to the present invention may be comprised in at least one of the compartments. It may for example be
10 comprised in just one compartment, or may be comprised in two compartments, or even in three compartments.

Each compartment may comprise the same or different compositions. The different compositions could all be in the same form, or they may be in different forms.

The water-soluble unit dose article may comprise at least two internal compartments,
15 wherein the liquid laundry detergent composition is comprised in at least one of the compartments, preferably wherein the unit dose article comprises at least three compartments, wherein the liquid laundry detergent composition is comprised in at least one of the compartments.

20 Water-soluble film

The film of the present invention is soluble or dispersible in water and comprises at least one polyvinylalcohol or a copolymer thereof. Preferably, the water-soluble film comprises a blend of at least two different polyvinylalcohol homopolymers, at least two different
25 polyvinylalcohol copolymers, at least one polyvinylalcohol homopolymer and at least one polyvinylalcohol copolymer or a combination thereof.

The water-soluble film preferably has a thickness of from 20 to 150 micron, preferably 35 to 125 micron, even more preferably 50 to 110 micron, most preferably from about 70 to 90 microns especially about 76 micron. By film thickness, we herein mean the thickness of the film
30 prior to any deformation during manufacture.

Preferably, the film has a water-solubility of at least 50%, preferably at least 75% or even at least 95%, as measured by the method set out here after using a glass-filter with a maximum pore size of 20 microns:

5 grams $\pm$ 0.1 gram of film material is added in a pre-weighed 3L beaker and 2L $\pm$ 5ml of distilled water is added. This is stirred vigorously on a magnetic stirrer, Labline model No. 1250 or equivalent and 5 cm magnetic stirrer, set at 600 rpm, for 30 minutes at 30°C. Then, the mixture is filtered through a folded qualitative sintered-glass filter with a pore size as defined
5 above (max. 20 micron). The water is dried off from the collected filtrate by any conventional method, and the weight of the remaining material is determined (which is the dissolved or dispersed fraction). Then, the percentage solubility or dispersability can be calculated.

Preferred film materials are preferably polymeric materials. The film material can, for example, be obtained by casting, blow-moulding, extrusion or blown extrusion of the polymeric
10 material, as known in the art.

Preferred polymers, copolymers or derivatives thereof suitable for use as pouch material are selected from polyvinyl alcohols, polyvinyl pyrrolidone, polyalkylene oxides, acrylamide, acrylic acid, cellulose, cellulose ethers, cellulose esters, cellulose amides, polyvinyl acetates, polycarboxylic acids and salts, polyaminoacids or peptides, polyamides, polyacrylamide,
15 copolymers of maleic/acrylic acids, polysaccharides including starch and gelatine, natural gums such as xanthum and carragum. More preferred polymers are selected from polyacrylates and water-soluble acrylate copolymers, methylcellulose, carboxymethylcellulose sodium, dextrin, ethylcellulose, hydroxyethyl cellulose, hydroxypropyl methylcellulose, maltodextrin, polymethacrylates, and most preferably selected from polyvinyl alcohols, polyvinyl alcohol
20 copolymers and hydroxypropyl methyl cellulose (HPMC), and combinations thereof. Preferably, the level of polymer in the pouch material, for example a PVA polymer, is at least 60%. The polymer can have any weight average molecular weight, preferably from about 1000 to 1,000,000, more preferably from about 10,000 to 300,000 yet more preferably from about 20,000 to 150,000.

Preferably, the water-soluble unit dose article comprises polyvinylalcohol.

25 Mixtures of polymers can also be used as the pouch material. This can be beneficial to control the mechanical and/or dissolution properties of the compartments or pouch, depending on the application thereof and the required needs. Suitable mixtures include for example mixtures wherein one polymer has a higher water-solubility than another polymer, and/or one polymer has a higher mechanical strength than another polymer. Also suitable are mixtures of
30 polymers having different weight average molecular weights, for example a mixture of PVA or a copolymer thereof of a weight average molecular weight of about 10,000- 40,000, preferably around 20,000, and of PVA or copolymer thereof, with a weight average molecular weight of

about 100,000 to 300,000, preferably around 150,000. Also suitable herein are polymer blend compositions, for example comprising hydrolytically degradable and water-soluble polymer blends such as polylactide and polyvinyl alcohol, obtained by mixing polylactide and polyvinyl alcohol, typically comprising about 1-35% by weight polylactide and about 65% to 99% by weight polyvinyl alcohol.

Preferred for use herein are PVA polymers which are from about 60% to about 98% hydrolysed, preferably about 80% to about 90% hydrolysed, to improve the dissolution characteristics of the material.

Preferred films exhibit good dissolution in cold water, meaning unheated distilled water. Preferably such films exhibit good dissolution at temperatures of 24°C, even more preferably at 10°C. By good dissolution it is meant that the film exhibits water-solubility of at least 50%, preferably at least 75% or even at least 95%, as measured by the method set out here after using a glass-filter with a maximum pore size of 20 microns, described above.

Preferred films are those supplied by Monosol.

Of the total PVA resin content in the film described herein, the PVA resin can comprise about 30 to about 85 wt% of the first PVA polymer, or about 45 to about 55 wt% of the first PVA polymer. For example, the PVA resin can contain about 50 w.% of each PVA polymer, wherein the viscosity of the first PVA polymer is about 13 cP and the viscosity of the second PVA polymer is about 23 cP, measured as a 4% polymer solution in demineralized water at 20°C.

Preferably the film comprises a blend of at least two different polyvinylalcohol homopolymers and/or copolymers.

Most preferably the water soluble film comprises a blend of at least two different polyvinylalcohol homopolymers, especially a water soluble film comprising a blend of at least two different polyvinylalcohol homopolymers of different average molecular weight, especially a blend of 2 different polyvinylalcohol homopolymers having an absolute average viscosity difference $|\mu_2 - \mu_1|$ for the first PVOH homopolymer and the second PVOH homopolymer, measured as a 4% polymer solution in demineralized water, in a range of 5 cP to about 15 cP, and both homopolymers having an average degree of hydrolysis between 85% and 95% preferably between 85% and 90%. The first homopolymer preferably has an average viscosity of 10 to 20 cP preferably 10 to 15 cP The second homopolymer preferably has an average viscosity

of 20 to 30 cP preferably 20 to 25 cP. Most preferably the two homopolymers are blended in a 40/60 to a 60/40 weight % ratio.

Alternatively the water soluble film comprises a polymer blend comprising at least one copolymer comprising polyvinylalcohol and anionically modified monomer units. In particular
5 the polymer blend might comprise a 90/10 to 50/50 weight % ratio of a polyvinylalcohol homopolymer and a copolymer comprising polyvinylalcohol and anionically modified monomer units. Alternatively the polymer blend might comprise a 90/10 to 10/90 weight % ratio of two different copolymers comprising polyvinylalcohol and anionically modified monomer units.

General classes of anionic monomer units which can be used for the PVOH copolymer
10 include the vinyl polymerization units corresponding to monocarboxylic acid vinyl monomers, their esters and anhydrides, dicarboxylic monomers having a polymerizable double bond, their esters and anhydrides, vinyl sulfonic acid monomers, and alkali metal salts of any of the foregoing. Examples of suitable anionic monomer units include the vinyl polymerization units corresponding to vinyl anionic monomers including vinyl acetic acid, maleic acid, monoalkyl
15 maleate, dialkyl maleate, monomethyl maleate, dimethyl maleate, maleic anhydride, fumaric acid, monoalkyl fumarate, dialkyl fumarate, monomethyl fumarate, dimethyl fumarate, fumaric anhydride, itaconic acid, monomethyl itaconate, dimethyl itaconate, itaconic anhydride, vinyl sulfonic acid, allyl sulfonic acid, ethylene sulfonic acid, 2-acrylamido-1-methylpropanesulfonic acid, 2-acrylamido-2-methylpropanesulfonic acid, 2-methylacrylamido-2-methylpropanesulfonic
20 acid, 2-sulfoethyl acrylate, alkali metal salts of the foregoing (e.g., sodium, potassium, or other alkali metal salts), esters of the foregoing (e.g., methyl, ethyl, or other C₁-C₄ or C₆ alkyl esters), and combinations thereof (e.g., multiple types of anionic monomers or equivalent forms of the same anionic monomer). In an aspect, the anionic monomer can be one or more acrylamido methylpropanesulfonic acids (e.g., 2-acrylamido-1-methylpropanesulfonic acid, 2-acrylamido-2-
25 methylpropanesulfonic acid, 2-methylacrylamido-2-methylpropanesulfonic acid), alkali metal salts thereof (e.g., sodium salts), and combinations thereof. In an aspect, the anionic monomer can be one or more of monomethyl maleate, alkali metal salts thereof (e.g., sodium salts), and combinations thereof.

The level of incorporation of the one or more anionic monomer units in the PVOH
30 copolymers is not particularly limited. In some aspects, the one or more anionic monomer units are present in a PVOH copolymer in an amount in a range of about 2 mol.% to about 10 mol.% (e.g., at least 2.0, 2.5, 3.0, 3.5, or 4.0 mol.% and/or up to about 3.0, 4.0, 4.5, 5.0, 6.0, 8.0, or 10 mol.% in various embodiments), individually or collectively.

Naturally, different film material and/or films of different thickness may be employed in making the compartments of the present invention. A benefit in selecting different films is that the resulting compartments may exhibit different solubility or release characteristics.

5 The film material herein can also comprise one or more additive ingredients. For example, it can be beneficial to add plasticisers, for example glycerol, ethylene glycol, diethyleneglycol, propylene glycol, dipropylene glycol, sorbitol and mixtures thereof. Other additives may include water and functional detergent additives, including surfactant, to be delivered to the wash water, for example organic polymeric dispersants, etc.

10 The film may be opaque, transparent or translucent. The film may comprise a printed area. The printed area may cover between 10 and 80% of the surface of the film; or between 10 and 80% of the surface of the film that is in contact with the internal space of the compartment; or between 10 and 80% of the surface of the film and between 10 and 80% of the surface of the compartment.

15 The area of print may cover an uninterrupted portion of the film or it may cover parts thereof, i.e. comprise smaller areas of print, the sum of which represents between 10 and 80% of the surface of the film or the surface of the film in contact with the internal space of the compartment or both.

The area of print may comprise inks, pigments, dyes, blueing agents or mixtures thereof. The area of print may be opaque, translucent or transparent.

20 The area of print may comprise a single colour or maybe comprise multiple colours, even three colours. The area of print may comprise white, black, blue, red colours, or a mixture thereof. The print may be present as a layer on the surface of the film or may at least partially penetrate into the film. The film will comprise a first side and a second side. The area of print may be present on either side of the film, or be present on both sides of the film. Alternatively, 25 the area of print may be at least partially comprised within the film itself.

The area of print may comprise an ink, wherein the ink comprises a pigment. The ink for printing onto the film has preferably a desired dispersion grade in water. The ink may be of any color including white, red, and black. The ink may be a water-based ink comprising from 10% to 80% or from 20% to 60% or from 25% to 45% per weight of water. The ink may comprise from 30 20% to 90% or from 40% to 80% or from 50% to 75% per weight of solid.

The ink may have a viscosity measured at 20°C with a shear rate of 1000s⁻¹ between 1 and 600 cPs or between 50 and 350 cPs or between 100 and 300 cPs or between 150 and 250 cPs.

The measurement may be obtained with a cone- plate geometry on a TA instruments AR-550 Rheometer.

The area of print may be achieved using standard techniques, such as flexographic printing or inkjet printing. Preferably, the area of print is achieved via flexographic printing, in which a film is printed, then moulded into the shape of an open compartment. This compartment is then filled with a detergent composition and a second film placed over the compartment and sealed to the first film. The area of print may be on either or both sides of the film.

Alternatively, an ink or pigment may be added during the manufacture of the film such that all or at least part of the film is coloured.

The film may comprise an aversive agent, for example a bittering agent. Suitable bittering agents include, but are not limited to, naringin, sucrose octaacetate, quinine hydrochloride, denatonium benzoate, or mixtures thereof. Any suitable level of aversive agent may be used in the film. Suitable levels include, but are not limited to, 1 to 5000ppm, or even 100 to 2500ppm, or even 250 to 2000ppm.

Process of making

Those skilled in the art will be aware of processes to make the liquid laundry detergent composition of the present invention. Those skilled in the art will be aware of standard processes and equipment to make the liquid laundry detergent compositions.

Those skilled in the art will be aware of standard techniques to make the unit dose article. Standard forming processes including but not limited to thermoforming and vacuum forming techniques may be used.

A preferred method of making the water-soluble unit dose article according to the present invention comprises the steps of moulding a first water-soluble film in a mould to form an open cavity, filling the cavity with the liquid laundry detergent composition, laying a second film over the first film to close the cavity, and sealing the first and second films together to produce the water-soluble unit dose article.

Process of washing fabrics

One aspect of the present invention is a process of washing fabrics comprising the steps of contacting the liquid laundry detergent composition or unit dose article of the present invention with water such that the liquid laundry detergent composition is diluted in water by at least 400 fold to form a wash liquor, and contacting fabrics with said wash liquor.

The liquid laundry detergent composition or unit dose article of the present invention can be added to a wash liquor to which laundry is already present, or to which laundry is added. The liquid laundry detergent composition or unit dose article may be used in an automatic washing machine operation and added directly to the drum or to the dispenser drawer. The liquid laundry detergent composition or unit dose article may be used in combination with other laundry detergent compositions such as fabric softeners or stain removers. The liquid laundry detergent composition may be used as pre-treat composition in which it is added directly to a fabric, preferably a fabric stain, ahead of the wash operation.

- 10 The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as “40 mm” is intended to mean “about 40 mm.”

15

EXAMPLES

The following base formulations were prepared using standard mixing techniques and equipment known to those skilled in the art.

Ingredient (wt %)	Base I	Base II
Solvent system (described below)	20.0	20.0
Water	10.0	10.0
Monethanolamine	10.4	8.4
Linear alkylbenzene sulphonic acid	22.1	16.9
C12-14EO3S anionic surfactant	15.0	11.3
C12-14EO7 nonionic surfactant	3.9	13.7
Top palm kernel Fatty Acid	6.1	5.1
Citric acid	0.7	0.7
Ethoxylated polyethyleneimine (PEI600EO20)	3.3	3.5
Amphiphilic graft copolymer comprising terephthalate	2.6	2.6
Hydroxyethyldiphosphonic acid	2.3	2.5

Brightener 49	0.4	0.4
Hydrogenated Castor Oil	0.1	0.1
Mg Cl ₂	0.3	0.3
Minors (perfume, dye, suds suppressor, enzyme, antioxidant)	Balance	Balance

The examples for testing were prepared as follows, wherein the solvent system for each example is described together with the base formulation to which it was added.

Wt%	Comparative Example A	Comparative Example B	Comparative Example C	Comparative Example D	Example 1
Base formulation	I	I	I	I	II
Solvent systems					
P-diol	12 wt%	16 wt%	4 wt%	-	12 wt%
DPG	4 wt%	-	12 wt%	16 wt%	4 wt%
Glycerol	4 wt%	4 wt%	4 wt%	4 wt%	4 wt%

Example 1 is according to the present invention, whereas comparative examples A-D differ in surfactant ratio or solvent system ratio.

Liquid stringing

- 5 The liquid stringing profile of Comparative Example A and Example 1 formulations was assessed by measuring the breakup time of a capillary formed upon extension of a test sample to a certain strain using a Haake Caber I extensional rheometer (Caber : capillary break-up extensional rheometer). The sample diameter was set to 6 mm, initial sample height to 3 mm, final sample height to 17.27mm, stretch profile was set to linear and strike time set on 100ms.
- 10 The data tabulated below illustrate that a liquid formulation according to the invention (Example 1) was less sensitive to liquid stringing, i.e. shows a shorter capillary breakup time, than

Comparative Example A, having an anionic to non-ionic surfactant weight ratio outside the scope of the invention.

	Caber capillary breakup time (s)	
	Comparative Example A	Example 1
average	1.04	0.64s
standard deviation	0.09	0.08

5

Unit dose article dissolution performance

The relative dissolution performance of a unit dose article comprising Comparative Example A formulation versus a unit dose article comprising example 1 formulation was investigated. The data tabulated below illustrate that a water soluble pouch comprising a liquid formulation according to the invention (Example 1) dissolving faster than a water soluble pouch comprising a liquid formulation according to Comparative Example A.

For this unit dose article dissolution testing Ariel 3-in-1 PODS unit dose laundry products, as commercialized by the Procter and Gamble company in the UK in January 2016, were made, single variable replacing the liquid in the three compartment by respectively Comparative Example A and Example 1 formulations. Unit dose article dissolution testing was done by measuring conductivity over time when dissolving a water soluble unit dose article comprising the respective formula compositions in a beaker test. Unit dose articles were held in a pouch holder case in order to prevent them getting damaged by the mixer blades. The unit dose articles were immersed in a 5 liter glass beaker (diameter 17 cm) containing 3 litre of demineralised water (< 5 μ S.cm) at 20 $\pm$ 1 °C. The water was agitated with a mechanical stirrer (type IKA Eurostar power control) set at 70 RPM connected to an impeller having a diameter of 10cm and the impeller blades fixed at the 1000ml height level of the beaker. A conductivity sensor (type : Mettler Toledo Seven Excellence) was inserted in the wash solution with the bottom of the sensor being adjusted to the 2000ml height level of the beaker. Unit dose articles were added to the agitated water and conductivity measurement started when unit dose articles were immersed in the water. The % dissolution at 15 minutes is defined as the relative % of

conductivity reached after 15 minutes compared to the conductivity of a fully dissolved unit dose article. The experiment was replicated 6 times and the average value is reported. Unit dose articles were matured for two weeks after production and pre-conditioned for 24 hours at 23°C, 50%rH before testing.

5

average dissolution after 15 min [%]	
Comparative Example A	Example 1
42	79

Film plasticization properties

The impact of varying solvent system on water soluble film plasticization properties was assessed within laundry detergent formulations suitable for water-soluble unit dose articles (low water). More particularly the relative ratio of 1,2-propanediol (P-Diol) and dipropyleneglycol (DPG) and anionic to non-ionic surfactant were varied to be within and outside the scope of the current invention. Film stress data tabulated below clearly show that film plasticization properties are better maintained within the laundry detergent formulation comprising a solvent and surfactant system according to the invention (Example 1), compared to solvent and surfactant systems outside the scope of the invention (Comparative Examples B to D), preventing pouch floppiness or film brittleness accordingly.

An 85 µm thick polyvinylalcohol based water soluble film, as present in Ariel 3-in-1 PODS unit dose laundry products, as commercialized by the Procter and Gamble Company in the UK in January 2016, was used to assess film plasticization dependency upon varying solvent system.

Film plasticization impact of varying solvent systems in a base laundry detergent formulation was defined through measuring film stress upon 100% strain. A test film was subjected to an ageing experiment through immersing the film in respective example and comparative example formulations as described above, and the film stress upon 100% strain post-immersion data were compared versus data of the virgin film (not immersed in the example formulations).

A film sample of 12cm by 17 cm was immersed within 150 ml of test liquid by 1) selecting a flat clean inert glass recipient, 2) covering the bottom of the recipient with a thin layer of the example formulation to be tested, 3) carefully spreading the film to be tested on the liquid, 4) gently pushing air bubbles trapped under the film towards the sides, 5) gently pouring the remaining example formulation on top of the film, in such a way that the film is fully immersed into the liquid, ensuring that the film is free of wrinkles and that no air bubbles are in contact with the film, and 6) closing the glass container and 7) storing the closed container for 5 days at 35°C followed by 1 night at 21 °C and 40% relative humidity. After ageing, the film was removed from the formulation example and gently wiped dry with a soft dry liquid absorbing paper, followed immediately by measuring the post film immersion stress-strain profile. The film stress upon strain profile was measured using an Instron instrument (system ID #5567J4072 available from the Instron company). Film plasticization properties were defined at constant temperature and relative humidity conditions ($21 \pm 1^\circ\text{C}$ and $45 \pm 5\%$ RH). The gauge length was set to 25 mm. 5 strips of 1 inch width and 12 cm long were cut out of the piece of film in machine direction, i.e. the direction the film moves during the production process (the direction of film movement during manufacture is defined by the direction in which the film is unwound from the roll in which it has been shipped from the manufacturer). The stress-strain curve was defined for these 5 replicates and the average stress at 100% strain value for a strain speed of 500mm/min is reported below.

	stress @ 100 % strain [MPa] (post film immersion)				
	virgin	Comparative Example B	Comparative Example C	Comparative Example D	Example 1
average	11.4	9.7s	16.7s	16.7s	11.1
standard deviation	0.2	0.4	0.9	0.8	1.1

As can be seen from the data, film immersed in the formulations of the present invention maintained substantially the same plasticization properties as the virgin film. However, the comparative examples were either over, or under plasticised.

CLAIMS

What is claimed is:

1. A liquid laundry detergent composition suitable for formulation into a water-soluble unit dose article, wherein the liquid laundry detergent composition comprises;
 - a. an anionic surfactant;
 - b. a non-ionic surfactant;
 - c. 1,2-propanediol;
 - d. dipropylene glycol;wherein the weight ratio of the anionic surfactant to the non-ionic surfactant is from 5:1 to 1:1, preferably from 3.5:1 to 1.25:1, more preferably from 2.5:1 to 1.5:1; and wherein the total weight percentage of the 1,2-propanediol and dipropylene glycol is between 5% and 25% by weight of the liquid laundry detergent composition, and wherein the weight ratio of 1,2-propanediol to dipropylene glycol is between 1:1 and 10:1, preferably between 1:1 and 5:1, most preferably between 2:1 and 4:1; wherein the liquid laundry detergent composition comprises between 0.5% and 20% by weight of the liquid laundry detergent composition of water.
2. The liquid laundry detergent composition according to claim 1 comprising between 22% and 32% preferably between 25% and 29% by weight of the liquid laundry detergent composition of the anionic surfactant.
3. The liquid laundry detergent composition according to any preceding claims wherein the anionic surfactant is selected from linear alkylbenzene sulphonate, alkyl sulphate, alkoxyated alkyl sulphate or a mixture thereof, preferably wherein the anionic surfactant comprises linear alkylbenzene sulphonate and ethoxylated alkyl sulphate, most preferably wherein the anionic surfactant comprises linear alkylbenzene sulphonate and ethoxylated alkyl sulphate in a weight ratio of linear alkylbenzene sulphonate to ethoxylated alkyl sulphate of between 3:1 and 1:1, more preferably between 2:1 and 1:1.
4. The liquid laundry detergent composition according to any preceding claims, wherein the liquid laundry detergent comprises a fatty acid or salt thereof, preferably wherein the liquid laundry detergent composition comprises between 3% and 10%, more preferably

between 5% and 7% by weight of the liquid laundry detergent composition of a fatty acid or salt thereof.

5. The liquid laundry detergent composition according to any preceding claims wherein the non-ionic surfactant is selected from a fatty alcohol alkoxylate, an oxo-synthesised fatty alcohol alkoxylate, Guerbet alcohol alkoxylates, alkyl phenol alcohol alkoxylates or a mixture thereof.
6. The liquid laundry detergent composition according to any preceding claims comprising between 1% and 15%, most preferably between 5% and 12% by weight of the liquid laundry detergent composition of water.
7. The liquid laundry detergent composition according to any preceding claims wherein the total weight percentage by weight of the liquid laundry detergent composition of 1,2-propanediol and dipropylene glycol is between 10% and 20%, preferably between 13% and 17%.
8. The liquid laundry detergent composition according to any preceding claims comprising glycerol, preferably wherein the glycerol is present between 2% and 10%, preferably between 3% and 5% by weight of the liquid laundry detergent composition.
9. The liquid laundry detergent composition according to any preceding claims wherein the liquid laundry detergent composition comprises monoethanolamine, preferably wherein the liquid laundry detergent composition comprises between 5% and 15%, more preferably between 8% and 12% by weight of the liquid laundry detergent composition of monoethanolamine.
10. The liquid laundry detergent composition according to any preceding claims wherein the liquid laundry detergent composition has a pH between 6 and 10, more preferably between 6.5 and 8.9, most preferably between 7 and 8.
11. The liquid laundry detergent composition according to any preceding claims wherein the liquid laundry detergent composition comprises hydrogenated castor oil.

12. The liquid laundry detergent composition according to any preceding claims comprising an adjunct ingredient selected from hueing dyes, polymers, surfactants, builders, dye transfer inhibiting agents, dispersants, enzymes, enzyme stabilizers, catalytic materials, bleach activators, polymeric dispersing agents, anti-redeposition agents, suds suppressors, aesthetic dyes, opacifiers, perfumes, perfume delivery systems, structurants, hydrotropes, processing aids, pigments and mixtures thereof.
13. A water-soluble unit dose article comprising a water-soluble film and a liquid laundry detergent composition according to any preceding claims, preferably wherein the water-soluble film comprises a blend of at least two different polyvinylalcohol homopolymers, at least two different polyvinylalcohol copolymers, at least one polyvinylalcohol homopolymer and at least one polyvinylalcohol copolymer or a combination thereof.
14. A method of making a water-soluble unit dose article according to claim 13 comprising the steps of moulding a first water-soluble film in a mould to form an open cavity, filling the cavity with the liquid laundry detergent composition, laying a second film over the first film to close the cavity, and sealing the first and second films together to produce the water-soluble unit dose article.
15. A process of washing fabrics comprising the steps of contacting the liquid laundry detergent composition or unit dose article according to any preceding claims with water such that the liquid laundry detergent composition is diluted in water by at least 400 fold to form a wash liquor, and contacting fabrics with said wash liquor.
16. Use of a liquid laundry detergent composition according to any of claims 1-12 for reducing stringing of the liquid laundry detergent composition during manufacture of water-soluble unit dose articles, for controlling plasticization properties of a film when formulated into a water-soluble unit dose article, for improving dissolution profiles in water of water-soluble unit dose articles comprising said liquid laundry detergent composition, or a mixture thereof.