





(86) Date de dépôt PCT/PCT Filing Date: 2013/04/16
(87) Date publication PCT/PCT Publication Date: 2013/10/24
(45) Date de délivrance/Issue Date: 2022/11/22
(85) Entrée phase nationale/National Entry: 2014/10/10
(86) N° demande PCT/PCT Application No.: US 2013/036816
(87) N° publication PCT/PCT Publication No.: 2013/158666
(30) Priorité/Priority: 2012/04/16 (US61/624,643)

(51) Cl.Int./Int.Cl. *C12M 1/22* (2006.01),
C12M 1/00 (2006.01), *C12M 1/12* (2006.01),
C12M 1/14 (2006.01), *C12M 1/16* (2006.01),
C12Q 1/04 (2006.01)
(72) Inventeurs/Inventors:
BROWNE, DOUGLAS J., US;
KARAKOZIAN, SARKIS, US;
CHEN, XIAOWEI, US
(73) Propriétaire/Owner:
RAPID MICRO BIOSYSTEMS, INC., US
(74) Agent: GOWLING WLG (CANADA) LLP

(54) Titre : DISPOSITIF DE CULTURES CELLULAIRES
(54) Title: CELL CULTURING DEVICE



(57) Abrégé/Abstract:

The invention features devices and kits for capturing and culturing microorganisms (e.g., bacteria, fungi, or protists) and methods of using the devices and kits to detect microorganisms in environmental and other samples. The device includes a nutrient media having a flat growth area on which microorganisms can grow. Samples are collected by contacting the device with any environmental sample, e.g., rolling device on a work surface or exposing device to air, or by filtering a sample through a membrane. Microorganisms deposited on the membrane derive nutrients from the underlying media and grow into colonies that can then be detected using methods known in the art. The detected colonies can be imaged digitally or with film.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2013/158666 A1


(43) International Publication Date
24 October 2013 (24.10.2013)

- (51) International Patent Classification:
C12Q 1/04 (2006.01) *C12M 1/00* (2006.01)
C12M 1/14 (2006.01)
- (21) International Application Number:
PCT/US2013/036816
- (22) International Filing Date:
16 April 2013 (16.04.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
61/624,643 16 April 2012 (16.04.2012) US
- (71) Applicant: **RAPID MICRO BIOSYSTEMS, INC.**
[US/US]; One Oak Park Drive, Bedford, MA 01730 (US).
- (72) Inventors: **BROWNE, Douglas, J.**; 28 Pacer Way, Groton, MA 01450 (US). **KARAKOZIAN, Sarkis**; 25 Grove Street, Apt. 1, Belmont, MA 02478 (US). **CHEN, Xiaowei**; 22 Freemont Street, Lexington, MA 02421 (US).
- (74) Agent: **MCDONALD, J., Cooper**; Clark & Elbing LLP, 101 Federal Street, 15th Floor, Boston, MA 02110 (US).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,

[Continued on next page]

(54) Title: CELL CULTURING DEVICE

Figure 1



(57) Abstract: The invention features devices and kits for capturing and culturing microorganisms (e.g., bacteria, fungi, or protists) and methods of using the devices and kits to detect microorganisms in environmental and other samples. The device includes a nutrient media having a flat growth area on which microorganisms can grow. Samples are collected by contacting the device with any environmental sample, e.g., rolling device on a work surface or exposing device to air, or by filtering a sample through a membrane. Microorganisms deposited on the membrane derive nutrients from the underlying media and grow into colonies that can then be detected using methods known in the art. The detected colonies can be imaged digitally or with film.

WO 2013/158666 A1



MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

CELL CULTURING DEVICE

5

BACKGROUND OF THE INVENTION

The invention relates to the fields of cell culture and detection.

10 In many industries, particularly the food, beverage, healthcare, electronic, and pharmaceutical industries, it is essential to analyze samples rapidly for the degree of contamination by microorganisms, such as bacteria, yeasts, or molds.

One microbial culture technique, called microbial enumeration or colony counting, quantifies the number of microbial cells in a sample. The microbial enumeration method, which is based on *in situ* microbial replication, generally yields one visually detectable "colony" for
15 each microbial cell in the sample. Thus, counting the visible colonies allows microbiologists to accurately determine the number of microbial cells in a sample. To perform microbial enumeration, bacterial cells can be dispersed on the surface of nutrient agar in Petri dishes ("agar plates") and incubated under conditions that permit *in situ* bacterial replication. Microbial enumeration is simple, ultra-sensitive, inexpensive, and quantitative but may also be slow.

20 There is a need for additional culturing devices and methods for rapid microbial enumeration.

SUMMARY OF THE INVENTION

The invention provides devices and kits for capturing and culturing microorganisms, e.g.,
25 present in environmental samples. In one aspect, the invention provides a cell culturing device including a base that contains nutrient media for microorganisms; a porous membrane overlaying the nutrient media; and a lid that mates with the base to cover the membrane and the nutrient media. The nutrient media has a flat growth area raised above the base and a circumferential area that slopes from the edge of the flat growth area to the base, and the nutrient
30 media is capable of sustaining growth of microorganisms in the growth area. In certain embodiments, the base includes polystyrene. The base may also include a circumferential groove across which the membrane is sealed. The membrane includes, for example, a mixed

cellulose ester membrane. The membrane may be substantially non-radiative and substantially non-reflective and/or black.

5 In other embodiments, the growth area has a flatness of 100 to 450 μm before collection of a sample or 300 to 500 μm after collection of a sample. The nutrient media may or may not sustain growth of microorganisms in the circumferential area. The membrane may be attached to the base by a film that is sealed to the base. Alternatively, the device may further include a film applied to the base and circumferential area, in which the film adheres the membrane to the base.

10 In another aspect the invention provides a cell culturing device including, a base that contains nutrient media for microorganisms, in which the nutrient media has a flat growth area (e.g., a flatness of about 100 to 450 microns) raised above the base, in which the nutrient media is capable of sustaining growth of microorganisms in the growth area, a film overlaying the nutrient media, in which the film and the nutrient media have a circumferential area that slopes from the edge of the flat growth area to the base, and the film has an opening to expose a portion
15 of the flat growth area, and a lid that mates to the base to cover the nutrient media. In another embodiment, the device also includes a porous membrane in contact with the exposed growth area.

In another aspect, the invention provides a kit for cell culturing including a cell culturing device that includes, a base that contains nutrient media for microorganisms, in which the
20 nutrient media has a flat growth area (e.g., flatness of about 100 to 450 microns) raised above the base, in which the nutrient media is capable of sustaining growth of microorganisms in the growth area, and a film (e.g., a non-porous film) overlaying the nutrient media, in which the film and the nutrient media have a circumferential area that slopes from the edge of the flat growth area to the base, and the film has an opening to expose a portion of the flat growth area, a porous
25 membrane configured for placement on the exposed portion of the flat growth area; and a lid that mates with the base to cover the membrane and the nutrient media. In another embodiment, the film has fiducial marks for placement of a membrane on the growth area. In one embodiment, the kit also includes a filtration device, such as the device in WO 2007/038478 .

30 In one embodiment of any of the devices or kits of the invention, the lid may include an optically clear material disposed to allow imaging of the growth area. The lid when attached to the base may also prevent contamination by ingress of microorganisms, in which the lid is separated from the membrane by an air gap. The device may include a unique ID label on the base. The ID label may be a bar code or 2D barcode. The ID label may be used to track the
35 device identity, device compatibility with automated detection instruments and protocols, device

expiration date, sterilization history, and other information of interest. The device may also include indentations or protrusions to allow for alignment and gripping by human users or instrumentation, e.g., in the lid and/or the device. In certain embodiments, a device is not compressible in the lateral direction, e.g., to maintain flatness of the growth area. In such

5 embodiment, one or more mechanically supporting elements may be incorporated into the device to provide rigidity in the lateral direction. In other embodiments, the device includes a fiducial mark, e.g., of radiative plastic, printed fluorescent material, embossed fluorescent material, or a through hole exposing fluorescent media, material, or plastics, located, e.g., outside the growth area. For devices with a separable membrane, the fiducial mark may be a through hole in the

10 membrane that is located outside of the area through which a sample is filtered. Such a through hole may expose fluorescent nutrient media, plastic, or printed material. Fiducial marks may be employed to align a membrane with a growth area and/or in the automated alignment of multiple images taken from a device.

In another embodiment, the base mates to the lid to prevent a rotation of greater than

15 about 50 μm of the base relative to the lid.

In another embodiment, the invention provides a device or a kit in which the base has a bottom surface and a side wall extending around the perimeter of and upward from the bottom surface, in which the nutrient media is within the side wall of the base, and the lid has a top surface and a side wall extending around the perimeter of and downward from the top surface; in

20 which the lid reversibly secures to the base (e.g., the lid secures to the base by axial compression or the lid secures to the base by rotation of the lid relative to the base).

In another embodiment, the lid or the base also includes a circumferential rim (e.g., continuous or discontinuous) extending laterally from the side wall of the base or from the side wall of the lid and a first detent extending laterally from the side wall of the base or from the

25 side wall of the lid, in which the circumferential rim has a proximal side facing away from the top of the lid or the bottom of the base, a distal side facing toward the top of the lid or the bottom of the base, and a lateral edge connecting the proximal and distal sides, in which the lid has the circumferential rim and the base has at least one first detent, or the lid has at least one first detent and the base has the circumferential rim, and in which the lid is secured to the base by

30 interengagement between the circumferential rim and the at least one first detent. In another embodiment, at least one first detent extending laterally defines a gap between the first detent and the bottom surface of the base or the top surface of the lid, in which the gap is sized to accept the circumferential rim, and the first detent engages the distal side of the circumferential rim. The first detent may alternatively engage the lateral side of the circumferential rim. The

35 device may include at least one second detent extending laterally from the side wall, in which the

circumferential rim includes a kerf, and the second detent engages the kerf. Another embodiment of the invention may include a device in which the distal side of the rim is sloped, and the at least one first detent engages the distal side of the rim by relative rotation of the lid to the base. The device may include a plurality of circumferential rims and first detents, in which
5 the lid secures to the base by relative rotation of 90 degrees or less, e.g., 45 degrees or less. The device may include a stop on the lid or base that arrests rotation of the circumferential rim after a specified amount of rotation.

In another aspect, the invention provides a kit including a cell culturing device containing a base that contains nutrient media for microorganisms; and a porous membrane overlaying the
10 nutrient media, in which the nutrient media has a flat growth area raised above the base and a circumferential area that slopes from the edge of the flat growth area to the base, and in which the nutrient media is capable of sustaining microorganisms in the growth area; a protective lid attached to the base and preventing contamination by ingress of microorganisms, in which the protective lid is separated from the membrane by an air gap; and an optical lid attachable to the
15 base when the protective lid is removed and including an optically clear material disposed to allow imaging of the growth area when attached to the base.

In a further aspect, the invention provides a kit including a cell culturing device containing a base that contains nutrient media for microorganisms, in which the nutrient media has a flat growth area raised above the base, in which the nutrient media is capable of sustaining
20 growth of microorganisms in the growth area, a film overlaying the nutrient media, in which the film and the nutrient media have a circumferential area that slopes from the edge of the flat growth area to the base, and the film has an opening to expose a portion of the flat growth area, a porous membrane configured for placement on the exposed portion of the flat growth area; a protective lid attached to the base and preventing contamination by ingress of microorganisms,
25 in which the protective lid is separated from the growth area by an air gap; and an optical lid attachable to the base when the protective lid is removed and including an optically clear material disposed to allow imaging of the growth area when attached to the base. The kit may also include a filtration device as described herein.

The invention also features a method for monitoring the presence of microorganisms by
30 providing a device or kit of the invention; contacting the growth area of the device with a volume of air or a surface; incubating the device to allow growth of microorganisms; and determining the extent of growth of microorganisms. Exemplary surfaces include industrial and laboratory surfaces and garments. In certain embodiments, the sample is collected by rolling the device so that the circumferential area and growth area contact the surface or passing the volume
35 of air over the growth area. The extent of growth may be determined by optically imaging the

growth area. An image may be analyzed to quantify the number of microorganisms. The incubation and determining steps may be repeated to determine colonies of microorganisms that grow over time.

5 In another aspect, the invention provides a method for monitoring the presence of microorganisms in a sample by providing a device or kit of the invention, filtering a sample through the membrane, placing the membrane on the growth area, incubating the device to allow growth of microorganisms; and determining the extent of growth of microorganisms. The extent of growth may be determined by optically imaging the growth area. An image may be analyzed to quantify the number of microorganisms. The incubation and determining steps may be repeated to determine colonies of microorganisms that grow over time.

By a “substantially non-radiative” object is meant an object that does not emit light, e.g., by fluorescence, phosphorescence, or luminescence.

By a “substantially non-reflective” object is meant an object that reflects less than 25%, 10%, 5%, 1%, or 0.1% of the light used to image the object.

15 By a “securing member” is meant a component or feature of aspect of a mechanical mechanism that joins or affixes two entities. Exemplary securing members are threads, catches, detents, rims, latches, hooks, clasps, snaps, bayonet mounts, J-shaped hooks, L-shaped hooks, dents, protrusions, ribs, spring tongues, tabs, grooves, stops, notches, holes, kerfs, compression fits, interference fits, jam fits, cams, and cam stops. By “secures” is meant to mate, join or form a union between two entities in which the rotation of the two entities relative to each other is limited.

By “circumferential” is meant around the perimeter. Circumferential is not limited to circular shapes, for the purpose of this invention.

25 Other features and advantages will be apparent from the following description, the drawings, and the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1A is an exploded view of a device of the invention. Figure 1B is a photograph of a device with the cover removed.

30 Figures 2A-2B are cross-sectional views of a device of the invention. Figure 2A is a cross-sectional view of a device with a protective lid installed before use of the device. Figure 2B is a cross-sectional view of a device with an optical lid installed.

Figures 3A-3B are cross-sectional views showing details of attachment of a membrane to a base. Figure 3A is a cross-sectional view of a part of a device showing an expansion trough.

Figure 3B is a schematic depiction of a part of a device showing the location of a film or edge coating and expansion trough.

Figure 4 is a depiction of a base of a device of the invention including a region for application of a bar code, mechanically supporting elements (ribs), a double circumferential side wall, indentations (V features) for alignment and gripping, and a feature for optical alignment.

Figure 5A is an exploded view of a device of the invention including a protective lid, a circumferential film with fiducial marks (dashes), a base with nutrient media and a growth area, and a bar code label. Figure 5B is a photograph of a device of the invention including a circumferential film with fiducial marks (dashes), a base with nutrient media and a growth area, and a membrane with circumferential fiducial through holes overlaying the growth area and partially overlaying the circumferential film.

Figure 6 is a schematic depiction of a device of the invention including an optical lid with a circumferential rim and a base with three first detents (Snap detent, Detail A of Figure 6) and three second detents (Centering detents, Detail B of Figure 6).

Figure 7 is a schematic depiction of a device of the invention including a lid with a kerfed circumferential rim (Detail D in Figure 7) and a base with three first detents (Ball detents, Detail B in Figure 7), and three third detents (Centering detents, Detail C in Figure 7), and nine second detents (Detail A in Figure 7) that are configured to fill within the kerfs.

Figure 8 is a schematic depiction of a device of the invention including a lid having a discontinuous circumferential rim (see Detail A in Figure 8) and a base with two types of detents that are complementary to the discontinuous rim of the lid. The detents of the base are separated by about 40 degrees relative to the circumference. The first detents (see Detail C of Figure 8) and second detents (see Detail B of Figure 8) engage the discontinuous rim. The lid also has a visual indicator (rim feature).

Figure 9 is a schematic depiction of a device of the invention including a lid that has two discontinuous, sloping circumferential rims and a base with three first detents and two stops (Cam Stop, Detail A in Figure 9).

Figure 10 is a photograph of a device of the invention including a base, a membrane overlaying a nutrient media, and a circumferential area which slopes to the base. In addition, fiducial marks (dots) can be seen in the circumferential area.

Figure 11 is a photograph of microbial colonies grown on a device and visible to the human eye.

Figures 12A-12C are a set of images showing the use of a device in monitoring different types of environmental samples: air (Figure 12A), surfaces such as work areas (Figure 12B), and garments such as gloves or sleeves (Figure 12C).

Figure 13A is an exploded view of a filtration device including a funnel, a membrane with fiducial marks, a mesh support pad, and a filtration base. Figure 13B is a photograph of an assembled filtration device.

Figures 14A-14D are a set of images showing the monitoring of a liquid sample using a filtration device and a device of the invention. Figure 14A is a photograph of the assembled filtration device, a protective lid, and a device of the invention. Figure 14B is a photograph of filtering a sample through the membrane within the filtration device. Figure 14C is a photograph of the disassembled filtration device, showing the funnel, membrane on the filtration base, protective lid, and a device of the invention. Figure 14D is a photograph showing the transfer of the membrane to a device of the invention, in which the membrane is placed with the fiducial marks on the circumferential rim and fiducial marks (circumferential through holes) in the membrane allow for alignment of multiple images take of the membrane.

DETAILED DESCRIPTION OF THE INVENTION

The invention features devices and kits for capturing and culturing microorganisms (e.g., bacteria, fungi, or protists) and methods of using the devices and kits to detect microorganisms in environmental samples. The device is useful for rapid environmental monitoring and can be used to collect microorganisms, for example, by rolling the device on a surface. The device is then incubated to allow any microorganisms collected to grow into colonies, which are indicative of microbial contamination.

Device

The cell culturing devices of the invention facilitate the sample collection, sample growth, and detection of microorganisms within a sample. Devices of this invention allow for efficient, cost effective, and robust microorganism monitoring for a wide variety of applications.

The device, e.g., as shown in (Figures 1A-1B), includes a base that contains nutrient media overlaid by a porous membrane. The membrane is in conformal contact with the nutrient media. The membrane and nutrient media form a flat growth area surrounded by a sloping circumferential area. In preferred embodiments, the membrane allows nutrients to pass through and sustain microbial growth in the growth area but not in the circumferential area. In one aspect of the invention, the device is useful for automated detection of microorganisms, e.g., using the Growth Direct™ system for rapid colony counting, e.g., as described in U.S.

Publication No. 2003/0082516 .

The device may be of any appropriate size, e.g., that of a RODAC™ plate.

The base may be substantially non-radiative and non-reflective and may be made of any suitable material, e.g., polystyrene or other plastic. The base may also have a circumferential groove (also referred to as an expansion trough) that can be used for attachment of a membrane (e.g., as shown in Figures 2 and 3). The base may be produced by methods known in the art, e.g., injection molding.

The device, e.g., the base and/or the lid, may include indentations (e.g., as shown in Figure 4) or protrusions for gripping or alignment on the device. In certain embodiments, the device is not compressible in the lateral direction. For example, the device may include one or more mechanically supporting elements (Figure 4) to maintain the flatness of the growth area during handling.

The device includes a porous membrane, e.g., one having fluorescence properties commensurate with detection of autofluorescent microbial microcolonies. For example, the membrane is substantially non-radiative and non-reflective for detection of autofluorescent microbial microcolonies. Membranes may be manufactured from materials including cellulose, cellulose acetate, polystyrene, polyethylene, polycarbonate, polyethylene terephthalate (PET), polyolefin, ethylene vinyl acetate, polypropylene, polysulfone, polytetrafluoroethylene, nylon, and silicone copolymer. The choice of membrane depends, in part, on the type of cell to be cultured (e.g., microorganisms that grow attached to a surface (anchorage-dependent), microorganisms that grow in suspension (anchorage-independent), or microorganisms that grow as attached to a surface or in suspension), degree of permeability, and rate of transfer of fluids and gases. An exemplary membrane is a black mixed cellulose ester membrane (Sartorius AG).

The membrane is placed over the nutrient media so that the membrane and media are in conformal contact. The membrane and nutrient media form a flat growth area raised above the base with a circumferential sloping area around the edges. Such a design makes the device suitable for contact testing, e.g., by rolling the device on a surface. The membrane and nutrient media form a growth area that is flat across an area, e.g., of 10, 15, 20, 25, 30, 35, or 50 cm², preferably at least at least 25 cm². The membrane on the nutrient media has a flatness of about 100 to 600 μm, e.g., 200 to 350 μm, e.g., about 300 μm, as fabricated or 300 to 500 μm, e.g., about 450 μm, after collection of sample. The membrane is preferably factory installed and stays wet for the life of the product. The membrane has pores so that microorganisms deposited on the membrane may obtain nutrients from the underlying nutrient media. Examples of membrane pore sizes are 0.45 μm and 0.22 μm.

Solid or semi-solid nutrient growth media can be employed in the present device. Examples include Sabouraud dextrose agar (SDA), R2A agar, tryptic soy agar (TSA) letheen, and plate count agar (PCA). The media may be poured onto the base in a molten liquid state and

then allowed to solidify into a flat growth area that is raised above the base and a circumferential area that slopes from the edge of the flat growth area to the base. The flatness of the growth area may be controlled by surface tension and by filling normal to gravity. The flatness of the growth area may also be achieved using several alternate methods. For example, one method to achieve

5 a flat growth area includes pouring molten nutrient media onto the underside of a pre-attached, wet membrane. In this alternate method, the membrane is pre-attached to a base that has an opening on the bottom. The opening is used to fill molten nutrient media, e.g., agar. This opening is then sealed post filling by a cover or film. The membrane is circumferentially sealed to prevent leakage. The membrane expands or inflates during the filling process and may be

10 shaped by trapping within a nest or cavity of appropriate shape. Another method to achieve flatness is to pre-bow the base mid section downward by approximately 150 to 200 μm , e.g., using vacuum. The nutrient media is poured, and, once the media solidifies with a concave surface, the bowing force is released and the growth area springs back to the flat state. Alternatively, the nutrient media may be a liquid media held in a porous matrix, which is shaped

15 to have a flat growth area and sloping circumferential area.

The membrane is preferably secured to prevent peeling during use. The membrane may be installed by heat sealing to the base, e.g., by bridging over a circumferential groove. The groove (Figure 3A) allows expansion of the membrane without wrinkling. The groove also traps any moisture formed during the attachment. Alternatively, the membrane may be attached to the

20 device using a circumferential film, e.g., of PET, co-PET, acetate, or polyimide, that may be used to define the edges of the growth area. The film may be made black. The film may be substantially non-radiative and/or non-reflective. The film may contain several layers (Figure 3B). Such layers allow for heat fusion to the membrane without damaging the membrane, low fluorescence, and/or low reflectance. A film may also cover the circumferential area to prevent

25 growth of microorganisms outside the flat growth area. This arrangement is beneficial in confining growth to an area of the device, e.g., for imaging or visual inspection.

In alternative design, a device does not include an integral membrane. This device also includes a nutrient media raised above the base, a flat growth area, a film overlaying the circumferential area of the nutrient media (Figure 5A and 5B), and the circumferential area that

30 slopes from the edge of the flat growth area to the base. The device includes a film that overlays the circumferential area (in whole or in part), and the film has an opening to expose a portion of the flat growth area. The opening in the film and the nutrient media form a growth area that is flat across an area, e.g., of 10, 15, 20, 25, 30, 35, or 50 cm^2 , preferably at least at least 25 cm^2 . Suitable films include any non-porous or hydrophobic plastic or material, e.g., PET, co-PET,

35 acetate, or polyimide. The film may be made black. The film may be substantially non-radiative

and/or non-reflective. The growth area provides a surface where a porous membrane, e.g., exposed, to a sample may be overlaid. The nutrient media provides sustained growth of organisms on the top surface of the overlaid membrane, thereby providing a device for cell culturing and detection of contamination.

5 The device also includes a lid. The lid is for example a protective lid (Figure 2A) that does not contact the membrane and prevents contamination of the device prior to use. The lid may also be an optical lid (Figure 2B) with an optically clear window for imaging the growth area, e.g., with visible or UV light. An exemplary material for the lid is Zeonor® 1060R (polycycloolefin resin; Zeon Chemicals LP). Glass may also be employed. The optical lid may
10 also be used as a protective lid prior to use. The lid mates to the base to seal the membrane and nutrient media from outside contamination. The lid may be produced by methods known in the art, e.g., injection molding. All or part of the lid may be non-radiative and/or non-reflective.

 A lid secures to the base using securing members present on both the lid and the base. The lid and base may secure or engage reversibly, in which the lid and base may be separated
15 and reattached multiple times. Securing the lid to the base affixes the lid relative to the base in the axial direction (z-axis), thereby sealing the device. Securing members may provide alignment of the lid relative to the base securing in the lateral directions (x-axis and y-axis). Preferably, the lid protects the base and also prevents rotation of the lid relative to the base, e.g., to less than 50 μm .

20 A lid may be secured to the base with axial compression. For example, a circumferential rim (Figure 6) on the lid and detents (snap detents, Figure 6, Detail A) on the base may be used to secure the lid to the base once an axial force is applied to the lid. The detent is deflected as the circumferential rim passes the detent. The circumferential rim rests in a gap between the snap detent and the bottom surface of the base. The snap detent (Detail A of Figure 6) may have
25 a pointed protrusion to reduce the contacting surface area of the snap detent, thus increasing the force per area applied to the circumferential rim. In addition to the snap detents, centering detents can be used that apply pressure to the lateral edge of a circumferential rim (Detail B of Figure 6), thus fixing the position of the lid. The reproducibility of the optical lid position relative to the base is important for improving the consistency of automated sample imaging.
30 Securing and preventing movement of the optical lid improves the reproducibility of the automated image analysis.

 In an alternative embodiment, the base may include multiple ball detents (Detail B of Figure 7), multiple second detents (Detail A of Figure 7), and multiple centering detents, (Detail C of Figure 7), around perimeter of the base. The lid is secured to the base first detent by a
35 circumferential rim (Figure 7). The second detents help align the lid relative to the base. The

kerfed circumferential rim (Detail D of Figure 7) prevents rotation of the lid relative to the base because the second detents (Detail A of Figure 7) fill the kerfs of the rim.

A lid may be secured to the base with a rotational motion of less than or equal to 90 degrees. For example, the lid may have a series of discontinuous circumferential rims (Figure 8, Detail A). The discontinuous circumferential rims may or may not be evenly distributed around the perimeter, each about 40 degrees apart (Figure 8). A series of detents may be located on the base (Figure 8). Two variations of detents are shown (Detail C and Detail B of Figure 8), but a single type may be employed. The first detent engages to the top edge (distal edge adjacent to top surface of the lid) of the circumferential rim in the portion opposite the vertical portion of the discontinuous circumferential rim. The second detent engages to the top edge (distal edge adjacent to top surface of the lid) of the circumferential rim.

A lid may also be secured to the base with a rotational motion of less than or equal to 90 degrees. For example, the base includes multiple detents (Detail A of Figure 9) sized and shaped to reversibly secure to a discontinuous, sloped circumferential rim (Figure 9). The first detent has a horizontal length with a top surface that prevents lid from being installed in wrong location. The first detent facilitates a jam fit by providing an upper boundary that increasingly interacts with the variable height (sloped) discontinuous circumferential as the lid is twisted relative to the base. A stop (cam stop, Detail A of Figure 9) provides a rotational boundary for the discontinuous circumferential rim. The increasing height of the circumferential rim engages the first detent as the rim is turned about 90 degrees, thereby inducing a jam fit. The cam stop prevents over-rotation, providing a stop for the leading edge of the circumferential rim.

Additional non-limiting exemplary securing members and mechanisms for securing a lid to the base include: threads, clamps, gaskets, magnets, crown caps, and friction fits. For example, a lid of the device of the invention may be configured with a series of threads. A base of the invention may be configured with a complimentary series of threads, for securing the lid to the base.

The protective lid and the optical lid may attach to the same base using the same or different mechanisms. The securing members may be on the lid or the base. For example, the circumferential rim may be on the lid, and the detents on the base. Alternatively, the detents may be on the lid, and the circumferential rim on the base. Circumferential rim may also be on the outer or inner perimeter of the side wall of the lid or the base.

The device may include features that indicate successful securing of the lid to the base. For example, a rim feature on a lid (Figure 8) may be above a base and be visible before the lid is secured to the base. Once the lid is secured to the base, the rim feature is not visible above the base, thereby indicating a successful union of the lid and the base. The device may include

securing members compatible with automation. For example, a securing member may be sized and shaped such that robotic transfer arms may engage a securing member, thereby facilitating the automated use of the device.

The device may also include a fiducial mark, e.g., printed fluorescent material, embossed fluorescent material, radiative plastic, or a through hole exposing fluorescent media, material, or plastics. Other fiducial marks are known in the art. The fiducial mark may be outside the growth area (Figure 5B and Figure 10). The fiducial mark may help align a membrane with the device (Figure 5B). A fiducial mark may be used to align multiple images acquired from the same device, e.g., taken at different times, or the fiducial mark may be used to align the device within an imager. The fiducial marks may be at any position on the device that is suitable for imaging, e.g., the base, the circumferential area, the growth area, or the lid.

The device may also have a unique ID label imprinted or affixed on the device to aid in automated handling or sample tracking, e.g., by the Growth Direct™ system. The ID label may be a bar code or 2D barcode. The ID label may be used to track the device identity, device compatibility with instruments and protocols, device expiration date, sterilization history, and other information of interest.

Methods of use

The devices can be used to monitor the presence of microorganisms, e.g., in the environment. Environmental samples may include, without limitation, air, surfaces, and garments. The devices and kits of the invention may be used in any situation where microbial contamination needs to be rapidly detected, e.g., laboratories, hospitals, manufacturing areas, and “clean rooms” for nanotechnology manufacturing and applications. Exemplary surface samples include surfaces of stainless steel, glass or granite work surfaces, walls, floors and equipment surfaces. Surface may also include anatomical structures such as fingers and foreheads. Exemplary garment samples include jacket sleeves, gloves, chest plate and any other portion of wearable garment. The method may include: contacting the growth area of the device with a volume of air or a surface; incubating the device to allow growth of microorganisms (incubation may occur at, above, or below room temperature); and determining the extent of growth of microorganisms, e.g., by manual counting or by automated counting of colonies (as shown in Figure 11). Any culturable microorganism, including bacteria, cyanobacteria, protozoa, and fungi may be employed in conjunction with the device described herein. The device can be used for aerobic and anaerobic testing.

The sample may be collected by rolling the device so that the circumferential area and the growth area contact the surface. The surface can be, e.g., work surfaces such as a laboratory

surface or industrial surface (Figure 12B), garments (Figure 12C), or gloves (Figure 12C). In another aspect of the invention, air samples can be tested by passing a volume of air over the growth area, e.g., in an air monitor (Figure 12A) or by leaving the device uncovered for a period of time.

5 After sample collection, the device is typically covered using the optical cover and is incubated for microorganisms to grow, e.g., in an incubator at temperatures above or below room temperature. In one embodiment, after sample collection, the device is placed within the Growth Direct™ system for incubation and imaging. The device may be imaged at predefined intervals of time, and microorganisms may be detected by suitable methods known in the art, 10 e.g., fluorescence (via autofluorescence or stains), reflectance, or absorbance. Alternatively, vital stains may be introduced into the nutrient media and absorbed into the microorganisms during growth. Detection may be repeated to discern growing colonies from non-growing microorganisms or debris. Images of microorganisms may be recorded, either digitally or with film. The optical lid of the device may be removed manually or using automation and replaced 15 with a protective lid during storage. The protective lid may reversibly secure the base using one or more securing members. An optical lid may reversibly secure the base using one or more securing members.

 Alternatively the sample may be collected by filtering a sample through a membrane and then applying the membrane to the device of the invention. For example, a membrane and 20 filtration device (Figure 13A and 13B, and Figure 14A) may be used to filter a liquid sample, thus collecting any contaminating microorganisms on the membrane. As shown in Figures 13A-13B, an exemplary filtration device includes a funnel that traps a membrane to a filtration base. The membrane is supported by a mesh support pad to maintain flatness during filtration. Other filtration devices are known in the art, e.g., as described in WO 2007/038478. A sample of 25 interest is passed through the membrane to collect microorganisms (Figure 14B). The membrane is removed from the filtration device and overlaid onto the nutrient media of a device configured to accept a membrane (Figures 14C-14D). The membrane may be aligned relative to the fiducial marks on the film (dashes). The membrane may include fiducial marks, e.g., through holes in the region outside of the filtered area. Such through holes can be used to 30 expose fluorescent media, plastic, or printed material that is otherwise covered by the membrane. The membrane may be larger diameter than the exposed growth area and overlap the circumferential film. The membrane may adhere to the growth area by wetting from the nutrient. The membrane and device are then covered, incubated, and imaged as described above.

 Other methods and instruments for manual or automated colony counting that can be 35 used with the device are known in the art.

Kit for environmental monitoring and filtering

The invention also features a kit which includes the device, a protective lid, and an optical lid. The kit may be shipped with a protective cover installed on the device. The device
5 with the protective cover and the optical cover may be packaged separately or together in sterile packaging. In use, the protective cover is removed, the sampling is done, and the optical cover is then installed.

Alternatively, the invention also features a kit which includes the device, a protective lid, a membrane, and an optical lid. The kit may be shipped with a protective cover installed on the
10 device. The device with the protective cover, membrane and the optical cover may be packaged separately or together in sterile packaging. In use, the protective cover is removed, the sampling is done, and the optical cover is then installed. Such kits may also include a filtration device as discussed herein.

15 Other Embodiments

Various modifications and variations of the described method and system of the invention will be apparent to those skilled in the art .

CLAIMS

1. A cell culturing device comprising:
 - (a) a base that contains nutrient media for microorganisms;
 - (b) a porous membrane overlaying the nutrient media, wherein the nutrient media has a flat growth area raised above the base and a circumferential area that slopes downwardly from the edge of the flat growth area to the base, and wherein the nutrient media is capable of sustaining growth of microorganisms in the flat growth area; and
 - (c) a lid that mates with the base to cover the porous membrane and the nutrient media.
2. The device of claim 1, wherein the flat growth area has a flatness of 100 to 450 microns before collection of a sample or 300 to 600 microns or less after collection of the sample.
3. The device of claim 1, wherein the porous membrane is not porous in the circumferential area.
4. The device of claim 1, wherein the porous membrane is attached to the base by a film that is sealed to the base.
5. The device of claim 1, further comprising a film applied to the base and circumferential area, wherein the film adheres the porous membrane to the base.
6. The device of claim 1, wherein the base comprises a circumferential groove across which the porous membrane is sealed.
7. A cell culturing device comprising:
 - (a) a base that contains nutrient media for microorganisms, wherein the nutrient media has a flat growth area raised above the base, wherein the nutrient media is capable of sustaining growth of microorganisms in the flat growth area,
 - (b) a film overlaying the nutrient media, wherein the film and the nutrient media have a circumferential area that slopes downwardly from the edge of the flat growth

- area to the base, and the film has an opening to expose a portion of the flat growth area, and
- (c) a lid that mates to the base to cover the nutrient media.
8. The device of claim 7, further comprising a porous membrane in contact with the exposed portion of the flat growth area.
9. A kit for cell culturing comprising:
- (a) a cell culturing device comprising:
 - (i) a base that contains nutrient media for microorganisms, wherein the nutrient media has a flat growth area raised above the base, wherein the nutrient media is capable of sustaining growth of microorganisms in the flat growth area, and
 - (ii) a film overlaying the nutrient media, wherein the film and the nutrient media have a circumferential area that slopes downwardly from the edge of the flat growth area to the base, and the film has an opening to expose a portion of the flat growth area,
 - (b) a porous membrane configured for placement on the exposed portion of the flat growth area; and
 - (c) a lid that mates with the base to cover the porous membrane and the nutrient media.
10. The device of claim 7 or kit of claim 9, wherein the flat growth area has a flatness of 100 to 450 microns.
11. The device of claim 7 or kit of claim 9, wherein the film is not porous.
12. The device of claim 7 or kit of claim 9, wherein the film has fiducial marks for placement of the porous membrane on the exposed portion of the flat growth area.
13. The device of claim 8 or kit of claim 9, wherein the porous membrane has through holes.
14. The device of claim 1 or 8 or the kit of claim 9, wherein the porous membrane comprises a mixed cellulose ester membrane.

15. The device of claim 1 or 8 or the kit of claim 9, wherein the porous membrane is substantially non-radiative and substantially non-reflective.
16. The device of claim 1 or 8 or the kit of claim 9, wherein the porous membrane is black.
17. The device of claim 1 or 7 or kit of claim 9, wherein the base comprises polystyrene.
18. The device of claim 1 or 7 or kit of claim 9, further comprising a fiducial mark.
19. The device or kit of claim 18, wherein the fiducial mark is outside the flat growth area.
20. The device or kit of claim 19, wherein the fiducial mark comprises radiative plastic, printed fluorescent material, or embossed fluorescent material.
21. The device of claim 1 or 7 or kit of claim 9, wherein the lid comprises an optically clear material disposed to allow imaging of the flat growth area.
22. The device of claim 1 or 7 or kit of claim 9, wherein the lid when attached to the base prevents contamination by ingress of microorganisms, and wherein the lid is separated from the porous membrane by an air gap.
23. The device of claim 1 or 7 or kit of claim 9, further comprising a unique ID label on the base.
24. The device of claim 1 or 7 or kit of claim 9, wherein the base mates to the lid to prevent a rotation of greater than about 50 μm of the base relative to the lid.

25. The device of claim 1 or 7 or kit of claim 9, wherein the base has a bottom surface and a side wall extending around the perimeter of and upward from the bottom surface, wherein the nutrient media is within the side wall of the base, and the lid has a top surface and a side wall extending around the perimeter of and downward from the top surface; wherein the lid reversibly secures to the base.
26. The device or kit of claim 25, wherein the lid secures to the base by axial compression.
27. The device or kit of claim 25, wherein the lid secures to the base by rotation of the lid relative to the base.
28. The device or kit of claim 25, further comprising a circumferential rim extending laterally from the side wall of the base or from the side wall of the lid and a first detent extending laterally from the side wall of the base or from the side wall of the lid, wherein the circumferential rim has a proximal side facing away from the top of the lid or the bottom of the base, a distal side facing toward the top of the lid or the bottom of the base, and a lateral edge connecting the proximal and distal sides, wherein the lid has the circumferential rim and the base has at least one first detent, or the lid has at least one first detent and the base has the circumferential rim, and wherein the lid is secured to the base by interengagement between the circumferential rim and the at least one first detent.
29. The device or kit of claim 28, wherein the circumferential rim is continuous around the side wall of the base or the side wall of the lid.
30. The device or kit of claim 28, wherein the at least one first detent extending laterally defines a gap between the first detent and the bottom surface of the base or the top surface of the lid, wherein the gap is sized to accept the circumferential rim, and the first detent engages the distal side of the circumferential rim.
31. The device or kit of claim 28, wherein the at least one first detent engages the lateral side of the circumferential rim.

32. The device or kit of claim 28, further comprising at least one second detent extending laterally from the side wall, wherein the circumferential rim comprises a kerf, and the second detent engages the kerf.
33. The device or kit of claim 28, wherein the circumferential rim is not continuous along the circumference of the side wall of the base or the lid.
34. The device or kit of claim 33, wherein the distal side of the rim is sloped, and the at least one first detent engages the distal side of the circumferential rim by relative rotation of the lid to the base.
35. The device or kit of claim 34, further comprising a plurality of circumferential rims and first detents, wherein the lid secures to the base by relative rotation of 90 degrees or less.
36. The device or kit of claim 34, further comprising a stop on the lid or base that arrests rotation of the circumferential rim after a specified amount of rotation.
37. A method for monitoring the presence of microorganisms in the environment, the method comprising the steps of:
- (a) providing the device according to any one of claims 1-6 and 14-36;
 - (b) contacting the flat growth area of the device with a volume of air or a surface;
 - (c) incubating the device to allow growth of microorganisms; and
 - (d) determining the extent of growth of microorganisms, thereby monitoring the presence of the microorganisms in the environment.
38. The method of claim 37, wherein the surface is an industrial or laboratory surface or a garment.
39. The method of claim 37, wherein step (b) comprises rolling the device so that the circumferential area and the flat growth area contact the surface or passing the volume of air over the flat growth area.

40. The method of claim 37, wherein step (d) comprises optically imaging the flat growth area.
41. The method of claim 40, further comprising analyzing the image to quantify the number of microorganisms.
42. The method of claim 40, further comprising repeating steps (c) and (d) to determine growing colonies of microorganisms.
43. A method for monitoring the presence of microorganisms in a sample, the method comprising the steps of:
- (a) providing the device or the kit according to any one of claims 8-36;
 - (b) filtering the sample through the porous membrane;
 - (c) placing the porous membrane on the flat growth area;
 - (d) incubating the device to allow growth of microorganisms; and
 - (e) determining the extent of growth of microorganisms, thereby monitoring the presence of the microorganisms in the sample.
44. The method of claim 43, wherein step (e) comprises optically imaging the flat growth area.
45. The method of claim 44, further comprising analyzing the image to quantify the number of microorganisms.
46. The method of claim 44, further comprising repeating steps (d) and (e) to determine growing colonies of microorganisms.
47. A kit comprising:
- (a) a cell culturing device comprising:
 - i) a base that contains nutrient media for microorganisms, and
 - ii) a porous membrane overlaying the nutrient media, wherein the nutrient media has a flat growth area raised above the base and a circumferential

area that slopes downwardly from the edge of the flat growth area to the base, and wherein the nutrient media is capable of sustaining microorganisms in the flat growth area,


- (b) a protective lid attached to the base and preventing contamination by ingress of microorganisms, wherein the protective lid is separated from the porous membrane by an air gap; and
- (c) an optical lid attachable to the base when the protective lid is removed and comprising an optically clear material disposed to allow imaging of the flat growth area when attached to the base.

48. A kit for cell culturing comprising:

- (a) a cell culturing device comprising:
 - i) a base that contains nutrient media for microorganisms, wherein the nutrient media has a flat growth area raised above the base, wherein the nutrient media is capable of sustaining growth of microorganisms in the flat growth area, and
 - ii) a film overlaying the nutrient media, wherein the film and the nutrient media have a circumferential area that slopes from the edge of the flat growth area to the base, and the film has an opening to expose a portion of the flat growth area,
- (b) a porous membrane configured for placement on the exposed portion of the flat growth area;
- (c) a protective lid attached to the base and preventing contamination by ingress of microorganisms, wherein the protective lid is separated from the flat growth area by an air gap; and
- (d) an optical lid attachable to the base when the protective lid is removed and comprising an optically clear material disposed to allow imaging of the flat growth area when attached to the base.

Figure 1

A




B



Figure 2

A

With protective lid



B

With optical lid





Figure 3

A

Details of membrane attachment and corralling the organisms



B




Figure 4





Figure 5

A



Protective Lid


Film (Mask) w/
Fiducial Marks

Cassette Base

ID Label

Figure 5

B






Figure 6





Figure 7

Figure 8



Discontinuous circumferential rims 8x, 45° intervals
Detents secure in two specific locations
All 8 partial circumferential rims secure with either
First or Second Detent (Detail A)

Figure 9




Figure 10



Figure 11





Figure 12

A



B



C



Figure 13

A




Figure 13

B



Figure 14

A



B





Figure 14


C



D



A



Funnel

Membrane with
Fiducials

Mesh Support Pad

Filtration Base

B

