

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2012/135764 A1

(43) International Publication Date
4 October 2012 (04.10.2012)

WIPO | PCT

(51) International Patent Classification:
A61F 2/44 (2006.01)

(21) International Application Number:
PCT/US2012/031693

(22) International Filing Date:
30 March 2012 (30.03.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/469,778 30 March 2011 (30.03.2011) US

(71) Applicant (for all designated States except US): TRINITY ORTOPEDICS, LLC [US/US]; 8817 Production Avenue, San Diego, CA 92121 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MARINO, James, F. [US/US]; 2620 St. Tropez Place, La Jolla, CA 92037 (US). ELBANNA, Jamil [US/US]; 17285 Grandee Place, San Diego, CA (US).

(74) Agents: HERNANDEZ, Fred, C. et al.; Mitz Levin Cohn Ferris Glovsky and Popeo, P.C., One Financial Center, Boston, MA 02111 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ARTICULATING INTERBODY CAGE AND METHODS THEREOF

Figure 1A



(57) Abstract: Disclosed herein are devices (100), systems and methods of use relating to articulating intervertebral cages. In one aspect, disclosed is an intervertebral device (100) for use in a human spine including an anterior end (104); a posterior end (102); and at least four peripheral walls (22,24,26). The peripheral walls (26) define an interior volume surrounding a midline of the device and include a superior wall (22), an inferior wall (24) and a pair of opposing, generally trapezoidal - shaped sidewalls (26) that are rotatable from a first configuration to at least a second configuration such that the device is expandable in first dimension. Each of the internal hinge elements includes an axis that is co-planar with the midline of the device.

ARTICULATING INTERBODY CAGE AND METHODS THEREOF

REFERENCE TO PRIORITY DOCUMENT

[0001] This application claims the benefit of priority under 35 U.S.C. 119(e) of U.S. Provisional Patent Application Serial No. 61/469,778, filed March 30, 2011. Priority of the aforementioned filing date is hereby claimed and the disclosure of the provisional patent application is hereby incorporated by reference in its entirety.

BACKGROUND

[0002] A significant number of adults have had an episode of back pain or suffer chronic back pain emanating from a region of the spinal column. A number of spinal disorders are caused by traumatic spinal injuries, disease processes, aging processes, and congenital abnormalities that cause pain, reduce the flexibility of the spine, decrease the load bearing capability of the spine, shorten the length of the spine, and/or distort the normal curvature of the spine. Many people suffering from back pain resort to surgical intervention to alleviate their pain.

[0003] Disc degeneration can contribute to back pain. With age, the nucleus pulposus of the intervertebral discs tends to become less fluid and more viscous. Dehydration of the intervertebral disc and other degenerative effects can cause severe pain. Annular fissures also may be associated with a herniation or rupture of the annulus causing the nucleus to bulge outward or extrude out through the fissure and impinge upon the spinal column or nerves (i.e. a “ruptured” or “slipped” disc).

[0004] In addition to spinal deformities that can occur over several motion segments, spondylolisthesis (i.e. forward displacement of one vertebra over another, usually in the lumbar or cervical spine) is associated with significant axial and/or radicular pain. Patients who suffer from such conditions can experience diminished ability to bear loads, loss of mobility, extreme and debilitating pain, and oftentimes suffer neurological deficit in nerve function.

[0005] Failure of conservative therapies to treat spinal pain such as for example bed rest, pain and muscle relaxant medication, physical therapy or steroid injection often urges patients to seek spinal surgical intervention. Many surgical techniques, instruments and spinal disc implants have been described that are intended to provide less invasive, percutaneous, or minimally-invasive access to a degenerated intervertebral spinal disc. Instruments are introduced through the annulus for performing a discectomy and implanting bone growth materials or biomaterials or spinal disc implants within the annulus. One or more annular incisions are made into the disc to receive spinal disc implants or bone growth material to promote fusion, or to receive a pre-formed, artificial, functional disc replacement implant.

[0006] Extensive perineural dissection and bone preparation can be necessary for some of these techniques. In addition, the disruption of annular or periannular structures can result in loss of stability or nerve injury. As a result, the spinal column can be further weakened and/or result in surgery-induced pain syndromes.

[0007] Various posterior interbody approaches such as posterior lumbar interbody fusion (PLIF) and transforaminal lumbar interbody fusion (TLIF) necessitate placing an interbody device through a relatively small annular aperture from a posterior access dissection path. The desire to restore disc space height and create lordosis through anterior distraction is in conflict with the application of a fixed height interbody spacer through a limited posterior approach. In addition, the larger the "foot-print" of the interbody spacer, the less likely it will subside. This is not only due to reduced endplate pressure but also better load bearing bone near the perimeter of the endplate (versus the central region).

SUMMARY

[0008] In one aspect, disclosed is an intervertebral device for use in a human spine. The device includes an anterior end; a posterior end; and at least four peripheral walls defining an interior volume surrounding a midline of the device. The peripheral walls include a superior wall, an inferior wall and a pair of opposing, generally trapezoidal-shaped sidewalls. Each of the trapezoidal-shaped sidewalls

includes an internal hinge element that is rotatable from a first configuration to at least a second configuration such that the device is expandable in first dimension. Each of the internal hinge elements includes an axis that is coplanar with the midline of the device.

[0009] The device can be additionally expandable in a second dimension. The first dimension can include a caudal-cephalad dimension and the second dimension can include a medial-lateral dimension. Each of the internal hinge elements can be positioned along the midline of its respective sidewall. The superior wall and the inferior wall each can mate with the pair of opposing sidewalls at a rotatable joint. The internal hinge element can couple a superior plate element to an inferior plate element. Each of the internal hinge elements further can include a plurality of overhangs configured to restrict articulation from the first configuration to the second configuration. The cephalad surface of the superior wall can be configured to engage a first vertebra of the human spine. At least a portion of the caudal surface of the inferior wall can be configured to engage a second vertebra of the human spine. The cephalad surface of the superior wall and the caudal surface of the inferior wall can be configured to penetrate the respective superior and inferior endplates.

[0010] The cephalad surface of the superior wall and the caudal surface of the inferior wall can include projection elements that engage the respective superior and inferior vertebral endplates. The projection elements can include a wedge shape and provide additional separation between the superior and inferior vertebral endplates. The projection elements can include a tapered distal tip. The outer surfaces of the pair of opposing sidewalls can include projection elements. The projection elements can impart further stiffness to the opposing sidewalls. The generally trapezoidal-shaped sidewalls can be oriented relative to the spine such that the longer segment is anterior and the shorter segment is posterior. The device can create a desired lordosis in the spine. Each of the at least four peripheral walls can be generally trapezoidal-shaped. The internal hinge element can include a plurality of ridge elements that form a linear track upon expansion of the intervertebral device to the

second configuration. The internal hinge element can further include a plurality of overhangs configured to restrict articulation from the first configuration to the second configuration.

[0011] The device can further include a brace configured to be positioned within the interior volume of the intervertebral device to support the intervertebral device under load. The brace can include a cylindrical element having a tapered outer diameter such that when positioned in the interior volume the brace is larger near the anterior region than the posterior region. The brace element can have a fixed dimension. The brace element can prevent one or more of the peripheral walls from articulating from the second configuration towards the first configuration. The brace element can be configured to be translated from an initial introductory orientation to a final stabilization orientation. The brace element can include fenestrations configured to permit growth of tissue from one vertebral endplate to a second vertebral endplate.

[0012] In an interrelated aspect, disclosed is a method of treating a spine. The method includes positioning an intervertebral device in a first configuration into a space between adjacent vertebrae. The intervertebral device includes an anterior end, a posterior end, and at least four peripheral walls defining an interior volume. The peripheral walls include a superior wall, an inferior wall and a pair of opposing sidewalls. At least two of the peripheral walls are generally trapezoidal. The opposing sidewalls include an articulation mechanism having a plurality of hinges. The first configuration includes the plurality of hinges articulated to minimize the interior volume of the intervertebral device. The method also includes inserting a brace through the interior volume of the intervertebral device in a posterior to anterior direction to deploy the intervertebral device into a second configuration to separate the adjacent vertebrae and create a desired lordosis in the spine. The second configuration includes an interior volume that is larger than when the device is in the first configuration. The method includes locking the brace such that the plurality of hinges is prevented by the brace from articulating into the first configuration.

[0013] The method can further include inserting an elongate tool into the interior volume to expand the device towards the second configuration prior to inserting the brace. Inserting the elongate tool can include using a tapered projecting tip on the elongate tool to pry open and at least partially articulate the plurality of hinges. The method can further include expanding an elastomeric element on the elongate tool using hydraulic pressure. The method can further include collapsing the elastomeric element on the elongate tool and withdrawing the tool through a central bore extending through a longitudinal axis of the brace.

[0014] In an interrelated aspect, disclosed is a device including caudal and cephalad plates that are positioned adjacent to vertebral endplates within an intervertebral disc space. The device includes lateral walls attached to the caudal and cephalad plates via an articulating mechanism. At least one of the lateral walls includes a hinge element restricted from achieving an on-center or over-center articulation position. The device is configured to be inserted into an intervertebral disc space in a reduced dimension configuration and subsequently expanded to an enlarged dimension configuration.

[0015] One or more of the caudal plate, cephalad plate, and lateral walls can be relatively radiolucent. The device can further include one or more osteoinductive, osteoproliferative, osteoconductive materials positioned internal to the device and extending from a caudal vertebral endplate to a cephalad vertebral endplate. One or both of the caudal and cephalad plates can include an external textured surface. The enlarged dimension configuration can be dimensionally expanded along an axis or arc other than that associated with caudal - cephalad expansion.

[0016] In an interrelated aspect, disclosed is a device including caudal and cephalad plates that are positioned adjacent to vertebral endplates within an intervertebral disc space, and at least two lateral walls attached to the caudal and cephalad plates via an articulating mechanism. The device includes an internal brace positioned between the plates and the at least two lateral walls. Caudal-cephalad compressive loading of the device results in compression of the internal

brace along axes extending between the caudal and cephalad plates as well as between at least two lateral walls. The device is configured to be inserted into an intervertebral disc space in a reduced dimension configuration and subsequently expanded to an enlarged dimension configuration.

[0017] One or more of the caudal plate, cephalad plate, and lateral walls can be relatively radiolucent. The device can further include one or more osteoinductive, osteoproliferative, osteoconductive materials positioned internal to the device and extending from a caudal vertebral endplate to a cephalad vertebral endplate. One or both of the caudal and cephalad plates can include an external textured surface. The enlarged dimension configuration can be dimensionally expanded along an axis or arc other than that associated with caudal - cephalad expansion.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Reference is made to the following description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout.

[0019] Figures 1A to 1D provide a side perspective view of an intervertebral device from a fully collapsed configuration (Figure 1A) to a fully expanded configuration (Figure 1D).

[0020] Figure 2A provides a detailed view of the posterior end an intervertebral device of the present embodiments in the fully expanded configuration.

[0021] Figure 2B provides a detailed view of the anterior end an intervertebral device of the present embodiments in the fully expanded configuration.

[0022] Figure 2C provides a detailed view from the lateral side of an intervertebral device of the present embodiments in the fully expanded configuration.

[0023] Figure 3A provides a detailed view of the anterior end an intervertebral device of the present embodiments in the fully collapsed configuration.

[0024] Figure 3B provides a detailed view of the anterior end an intervertebral device of the present embodiments in a slightly expanded configuration.

[0025] Figure 3C provides a detailed view from the lateral side of an intervertebral device of the present embodiments in the fully collapsed configuration.

[0026] Figures 4A to 4E provides a perspective view of an intervertebral device and support brace of the present embodiments as the brace is inserted into the interior of an intervertebral device and rotated into a locked position.

[0027] Figures 5A to 5E provides a side view of an intervertebral device and support brace of the present embodiments as the brace is inserted into the interior of an intervertebral device and rotated into a locked position.

[0028] Figures 6A to 6E provides a posterior view of an intervertebral device and support brace of the present embodiments as the brace is inserted into the interior of an intervertebral device and rotated into a locked position.

[0029] Figures 7A to 7E provides an anterior view of an intervertebral device and support brace of the present embodiments as the brace is inserted into the interior of an intervertebral device and rotated into a locked position.

[0030] Figures 8A to 8C provide a detailed view of the hinge mechanism of an intervertebral device of the present embodiments and related elements (e.g., ridge and overhang).

[0031] Figure 9 provides a top view of a support brace of the present embodiments showing detail on the design of the anterior end of the wedge element comprising the features of a flange, groove and lock as the diameter of the wedge element extends past the diameter of the brace cap.

[0032] Figure 10A provides a perspective view of the expansion of an intervertebral device and support brace of the present embodiments.

[0033] Figure 10B provides an anterior view of the expansion of an intervertebral

device and support brace of the present embodiments.

[0034] Figure 11A provides a perspective view of another embodiment of an intervertebral device.

[0035] Figure 11B provides a perspective view of the intervertebral device of Figure 11A in an expanded configuration.

[0036] Figure 12A provides a side, cross-sectional view of an embodiment of an intervertebral device in an expanded configuration.

[0037] Figure 12B provides a perspective, cut-away view of the intervertebral device of Figure 12A.

[0038] It is to be understood that implants described herein may include features not necessarily depicted in each figure. In some embodiments, an endplate engaging surface of any implant may have regularly or irregularly spaced protrusions of uniform or various shapes and sizes to facilitate retention of the implant in a desired position between vertebrae.

DETAILED DESCRIPTION

[0039] The devices and methods described herein can address the surgical desire to implant an interbody cage through a relatively small posterior access annulotomy, while providing for lordotic inducing disc space distraction and an expanded "foot-print" for endplate support. The devices described herein can be initially delivered into the disc space, in a collapsed or folded form and then expanded *in situ*.

[0040] The shape and/or size of an implant or other device disclosed herein may be chosen according to factors including, but not limited to, the surgical approach employed for insertion, the intended position in the spine, and a size of the patient. For example, intervertebral devices may range from about 6 mm to about 18 mm in height (e.g., 7 mm, 8 mm, 9 mm, 10 mm, 10.5 mm, 11 mm, 12 mm, 13 mm, 14 mm,

15 mm, 16 mm, 17 mm). Heights outside these ranges may be used as required by a patient's anatomy. The width may range from about 8 mm to about 16 mm. Implants that are substantially rectangular or trapezoidal may range from about 9 mm to about 14 mm medial-lateral with PLIF and TLIF approaches. The height (or caudal-cephalad) dimension can be between about 9 mm to about 14 mm. It should be appreciated that the dimensions can be slightly less or slightly greater than these dimensions.

[0041] The devices described herein can be used in the vertebral column in one or more spinal motion segments, including cervical, thoracic, lumbar, and sacral regions of the spine. It should also be understood that more than one device can be implanted, for example at the same spinal motion segment or in different spinal motion segments. It should also be understood that a variety of approaches can be used to implant the devices described herein, for example anterior approach, posterior, transforaminal approaches and other approaches known in the art.

[0042] The devices described herein can be expanded such that a height of the device and/or a separation distance between two parts of the device is increased. In some embodiments, an implant may be expanded after insertion of the implant in a human spine.

[0043] The devices described herein can also articulate such that at least two members of the implant are capable of undergoing rotational motion with respect to each other in at least one direction after insertion in a human spine (e.g., a hinge design). For example, an articulating intervertebral device or cage can include segments united by joints or hinges. The devices described herein can increase in dimension both medial-lateral as well as cephalad-caudal generally along its entire anterior-posterior length by virtue of the joints or hinges associated with the four peripheral walls (medial, lateral, cephalad, and caudal).

[0044] In certain embodiments, expansion of an implant after insertion in a human spine may allow articulation of the device. That is, the intervertebral device may not

display articulating motion before expansion of the implant in a human spine. In other embodiments, expansion of an implant after insertion in a human spine may allow an increased range of motion (increased articulation) between at least two members of the implant.

[0045] An implant may be constructed of one or more biocompatible metals having a non-porous quality and a smooth finish. In some embodiments, an implant may be constructed of ceramic and/or one or more other suitable biocompatible materials, such as biocompatible polymers. In certain embodiments, an implant may be constructed of a combination of one or more biocompatible metals and one or more ceramic and/or polymeric materials. In some embodiments, the device is made of implantable metal alloy materials including, but not limited to, titanium, vanadium, aluminum alloy, or titanium alloy or from implant grade biocompatible polymers including, but not limited to polyether ether ketone (PEEK). The devices described herein can be made of carbon fiber composites and polycarbonate materials.

[0046] According to some embodiments, the intervertebral device can include at least four walls, which may be described as a superior wall, an inferior wall, and two lateral or side walls. In some embodiments, the intervertebral device can include at least four walls, wherein at least two walls are hinged walls. In some embodiments, the hinged walls are opposing walls (*i.e.*, opposing lateral or side walls; opposing superior and inferior walls; or opposing cephalic and caudal surfaces). The walls may be hinged along their respective midlines. The walls may also be hinged where they couple to one another such that a hinge is formed at each corner of the intervertebral device. In some embodiments, the intervertebral device has hinge elements at each corner where the peripheral walls meet and hinge elements along the midline of each peripheral wall.

[0047] In some embodiments, the intervertebral device can include at least four walls, wherein at least four walls are hinged walls. The walls may be hinged along their respective midlines. For example, the superior (*i.e.* cephalad), inferior (*i.e.* caudal) and lateral walls may be hinged along their respective midlines.

[0048] The intervertebral device may be symmetrical along a longitudinal axis such that the opposing walls are identical or mirror images of each other. In some embodiments, the superior (*i.e.* cephalad) and inferior (*i.e.* caudal) walls are narrower posterior than anterior. In some embodiments, each wall is narrower posterior than anterior. According to some embodiments, the anterior portion of the intervertebral device may be tapered in the sagittal and transverse planes.

[0049] In some embodiments, at least two of the walls of the intervertebral device are generally trapezoidal. The parallel segments of the trapezoidal walls may be oriented such that the longer segment is anterior and the shorter segment is posterior, for example, to form a lordotic taper. In some embodiments, the trapezoidal walls are hinged, for example, along their respective midlines. In other embodiment, all peripheral walls are trapezoidal shaped and narrower at a posterior end compared to an anterior end when positioned within the spine.

[0050] In some embodiments, the intervertebral device can include a plurality of block elements that are integrated/ interconnected in the hinge design. As the intervertebral device is moved from the collapsed to the expanded configuration, the block elements of the intervertebral device can give way to open areas or apertures. Further, the interior volume of the intervertebral device can be filled with materials such as bone cement, bone graft and other materials including diffusible, migratory, and osteoconductive materials. The open areas can allow egress of the material filling the interior volume. It should be appreciated, however, that the devices described herein can be used without filling of the internal volume with material.

[0051] In some embodiments, an endplate engaging surface of an implant may include teeth, spikes, ridges or other projections that can penetrate or grip the endplate. In some embodiments, members of an implant may include one or more openings to accommodate packing of bone graft material and/or to allow for bone ingrowth. In certain embodiments, one or more surfaces of an implant may include material, such as osteoconductive scaffolding, to enhance integration of the implant in a patient's spine. In certain embodiments, implants depicted herein may include

features allowing the implant to provide a desired lordotic angle between vertebrae. A desirable lordotic angle can be between about 8 degrees to about 18 degrees. For example, the superior and/or inferior walls may optionally include teeth, spikes, ridges or other projections (e.g., tapered projecting elements) that protrude perpendicular from the superior and/or inferior surfaces, such that deployment results in this or these element(s) extending into the adjacent endplate(s). That is, the projecting elements (e.g. spikes, teeth, etc.) from the superior and/or inferior walls may be designed to penetrate the respective superior and inferior endplates upon expansion of the device to further stabilize the device and mitigate implant migration.

[0052] Figures 1A - 1D provide an illustration of an intervertebral device **100** according to some embodiments as the device is expanded from a fully collapsed (Figure 1A) to a fully expanded/ articulated (Figure 1D) configuration. The intervertebral device **100** can include a posterior portion **102**, an anterior portion **104** opposite from the posterior portion **102**. The walls of the intervertebral device **100** can be generally trapezoidal, wherein the parallel segments of the trapezoidal walls are oriented such that the longer segment is anterior and the shorter segment is posterior. Each wall can be narrower posterior than anterior.

[0053] Figure 1A illustrates an intervertebral device **100** with four walls or surfaces: a superior wall **22**, inferior wall **24**, and two lateral sidewalls **26**. The superior wall **22** is opposite from the inferior wall **24**, with a pair of sidewalls **26** between the superior wall **22** and inferior wall **24**. The superior wall **22** and inferior wall **24** are the portions of intervertebral device **100** closest to the exposed ends of vertebral bodies when implant **100** is in implantation space. The superior wall **22** and inferior wall **24** may also be referred to as the cephalad surface and caudal surface, respectively. Superior (i.e. cephalad) **22**, inferior (i.e. caudal) **24** and lateral sidewalls **26** can be hinged along their respective midlines. Each wall can be narrower posterior than anterior. The superior wall **22**, inferior wall **24**, and sidewalls **26** thus define an implant body having a cephalad surface, a caudal surface, and an

internal fusion promotion cavity extending between.

[0054] The superior and inferior walls **22, 24** may optionally include projecting elements **30**. In some embodiments, the projecting elements **30** can be tapered and have a cone or spiked shape such that a sharpened distal end can penetrate one or more of the respective superior and inferior endplates and function to further stabilize the intervertebral device **100** and mitigate implant migration when in the fully expanded configuration. In another embodiment, the projecting elements **30** can have a blunt shape such that they do not penetrate the endplates. In another embodiment, the projecting elements **30** can have a wedge shape such that they provide additional “lift” against one or more of the vertebral endplates (see Figures 11A and 11B). It should be appreciated that the projecting elements **30** having this configuration can also penetrate the endplates at one or more regions of the wedge. The projecting elements **30** can also have an elongate shape and further include a texture or additional barb elements on their surface that can penetrate the endplates.

[0055] When the intervertebral device **100** is in the unexpanded configuration, the projecting elements **30** can be directed inward or toward the midline of each wall surface on which they are positioned such that the projecting elements **30** have a sub-flush configuration in the collapsed state and do not snag tissues during implantation. The projecting elements **30** upon expansion can extend beyond the outer perimeter of the peripheral walls such that they provide additional height or lift on the vertebrae or penetrate the vertebral endplates. In the embodiment shown in Figures 11A-11B, the projecting elements **30** provide a ribbed surface that prevents migration making the intervertebral device is less prone to slippage once implanted between the vertebrae.

[0056] It should be appreciated that the superior and inferior walls **22, 24** can have apertures, through-holes or other features providing for an open architecture between the projecting elements **30** such that bone growth material or other material inserted within the interior volume of the device can penetrate the walls and contact the vertebral endplates for promotion of bone fusion.

[0057] The projecting elements **30** can also be positioned on one or more of the opposing sidewalls **26**. The projecting elements **30** positioned on the sidewalls **26** can provide additional stiffness and enhance wall bearing stability. The opposing sidewalls **26** can increase the thickness of the walls in the regions where the projecting elements **30** are positioned and prevent buckling of the walls upon application of a load.

[0058] The superior wall **22** and inferior wall **24** can each mate with the two lateral walls **26** at a joint having a rotatable hinge arrangement. The hinge arrangement can include a plurality of interlocking hinge elements **60**. The hinge arrangement may include block elements **40** that give way to openings or apertures **42** when the device is rotated around the joint and expanded from a collapsed to an expanded configuration (see Figure 1D). The block elements **40** can allow for material implanted within the interior volume to exit the device **100** and make contact with the vertebral endplates. The hinge arrangement can further include a plurality of ridge elements **62** and overhangs **64** (see Figure 8A to 8C). Depending on the position of the ridge elements **62** and overhangs **64**, expansion of the device **100** can vary. The overhangs **64** can be configured to allow for hypo-extension, hyper-extension or on center extension of the wall elements. For example, the overhangs **64** can be configured relative to the hinge element **60** to prevent (or allow) over-expansion or over-extension around the hinge. In an embodiment, the overhangs **64** can be configured to allow over-expansion such that one or more of the walls has an A-frame type architecture. In another embodiment, the overhangs **64** can be configured to allow under-expansion such that one or more of the walls has a V-frame type architecture. In another embodiment, the overhangs **64** can be configured to allow on center expansion such that one or more of the walls has a parallel arrangement (see Figure 8C).

[0059] One or more of the superior wall **22**, inferior wall **24**, and two lateral sidewalls **26** can be monolithic. The one or more of the superior wall **22**, inferior wall **24**, and two lateral sidewalls **26** can also include two or more wall portions that

articulate relative to one another. As best shown in Figure 1C, the lateral sidewalls **26** can each include a superior plate element **26a** coupled by an internal hinge mechanism **60a** to an inferior plate element **26b**. The axis of the internal hinge mechanism **60a** can be coplanar with the midline of the device. Further, the axis of the internal hinge mechanism **60a** of one lateral sidewall **26** can be coplanar with the axis of the internal hinge mechanism **60a** of the opposing lateral sidewall **26** just as the axis of the internal hinge mechanism **60a** of the superior wall **22** can be coplanar with the axis of the internal hinge mechanism **60a** of the inferior wall **24**. The axis of the internal hinge mechanism **60a** can be non-parallel to the axis of the hinge mechanism **60b** that couples the superior plate element **26a** of the lateral sidewall **26** to the superior wall **22**. Further, the axis of the internal hinge mechanism **60a** can be also non-parallel to the axis of the hinge mechanism **60c** that couples the inferior plate element **26b** of the lateral sidewall **26** to the inferior wall **24**. The device, in turn, can include bifurcated, hinged monolithic sidewalls having a trapezoidal shape such that the hinge axes are coplanar with the midline of the device, but non-parallel to each other.

[0060] When the device **100** is fully expanded, the ridge elements **62** can line up to form a linear track. In some embodiments, the linear track formed by the ridge elements **62** extends from the anterior end **102** and partially towards the posterior end **104** of the intervertebral device **100** (e.g., 20% to 80% of the length of the device). The portion of the fully expanded intervertebral device **100** absent the linear track can be configured to contact the wedge portion **220** of the brace **200**, discussed in detail herein. The portion of the fully expanded intervertebral device **100** having the linear track can be configured to contact the flange **232** of the second segment of the wedge portion **230** of the brace **200**, discussed in detail herein.

[0061] The intervertebral device **100** may further include small openings or suture holes **52** for receiving respective ends of a tether **50** (e.g., suture, thread, cable, braid, metallic filaments, and the like). The holes **52** can extend completely through one or more of the walls of the intervertebral device **100** and can be configured for

receiving respective ends of tether **50**. The tether **50** may be incorporated into the intervertebral device **100** prior to, during or after implantation. The tether **50** can be loose in the pre-deployed or collapsed state and become taut in the deployed or expanded configuration of the intervertebral device **100**. The tether **50** may also be configured to stabilize the intervertebral device **100** or block the fill material delivered to the cavity of the expanded intervertebral device **100** from oozing out.

[0062] The device may be expanded *in situ*. Various methods for *in situ* expansion are considered herein. In one embodiment, mechanical distraction using a wedging tool to pry the walls apart or an articulating tool that pushes or pulls opposing walls apart is considered. In some embodiments, an obturator can be used. The obturator can have a tapered end that fits into an entry port of the collapsed intervertebral device **100** and an outer diameter that can force the walls of the intervertebral device **100** outward into at least a partially expanded configuration. The outer diameter of the obturator can be between about 6 mm to about 7 mm, although smaller and larger outer diameters are considered herein. In other embodiments, *in situ* expansion can be performed using hydraulic expansion such as with an expandable element such as an elastomeric balloon (see Figures 12A-12B), as will be discussed in more detail below.

[0063] Once fully expanded, the intervertebral device **100** may be further stabilized with a cylindrical brace **200** (see e.g., Figures 4A to 4E). The brace **200** can support the intervertebral device **100** under load. In some embodiments, the brace **200** slides from posterior **102** to anterior **104**, while locking on the opposing four walls **20** adjacent to the hinge mechanism **60**, via relatively linear tracks that employ some form of undercut geometry. In some embodiments, the linear tracks are formed by the ridge elements **62** positioned on the hinge mechanism **60**.

[0064] In some embodiments, the brace can include a detent mechanism, a shank **202** and posterior cap **210**. The brace **200** may be of identical length to that of the intervertebral device **100**, or slightly smaller (e.g., 0.2 mm to 5 mm shorter). The brace **200** is designed to match the geometry of the cavity created by the full

expansion of the intervertebral device **100**. In some embodiments, the brace **200** is cylindrical having a diameter that expands conically when progressing from the posterior end to the anterior end in a manner that corresponds to the geometry of the interior of the intervertebral device **100**. The brace **200** may further include a plurality of wedge locking elements **220** and/or a plurality of bore holes **240**.

[0065] The plurality of bore holes **240** may be pre-filled with a material, such as a bone growth material, or filled after implantation. In some embodiments, the bore holes **240** and/or openings accommodate packing of bone graft material and/or to allow for bone in-growth. In certain embodiments, one or more surfaces of an implant may include material, such as osteoconductive scaffolding, to enhance integration of the implant in a patient's spine. The bore holes **240** can extend through one or more walls of the brace **200**, such as in a caudal-cephalad orientation as well as a medial-lateral orientation. The brace **200** can also be cannulated and include a central bore **245** extending along its longitudinal axis for insertion of materials and/or devices through the brace **200** (see Figures 12A-12B) as will be discussed in more detail below.

[0066] The top of the posterior cap **210** may include a cap screw **250** such as a hex, slot, or square nut for use in the mechanical rotation of the brace **200** (see e.g., 6A to 6E). The posterior cap or wall **210** may be associated with the brace **200** or may be independently associated with the expanded device **100**, to further stabilize the walls and to obstruct material from displacing from the interior of the device via the posterior portal. This posterior cap or wall may be locked to the perimeter walls with mating interior and/or exterior geometries, with or without a screw lock and detent mechanism.

[0067] In some embodiments, the posterior cap **210** has a geometry that is designed to stop the advancement of the brace **200** into the intervertebral device **100**. In some embodiments, the cap **210** is round and of a diameter larger than the opening at the posterior **102** of the intervertebral device **100**. For example, Figures 4A to 4E and Figures 5A to 5E provide different views illustrating the advance of the

brace **200** into the cavity created by the full expansion of the intervertebral device **100**. These figures show that the brace **200** can be advanced into the interior of the intervertebral device **100** until progress is halted by the engagement of the cap **210** and posterior end **102** of the intervertebral device **100**.

[0068] This bottoming out of the brace **200** indicates that the brace **200** is ready to be locked into position, which may be accomplished via rotation of the brace **200** and deployment of a detent mechanism. In some embodiments, the brace **200** is locked into position by the engagement of the wedge locking body **220** with the walls of the intervertebral device **100**. Figures 4A and 5A illustrate a wedge locking body **220** according to some embodiments. In some embodiments, the brace **200** has a first internal diameter that forms the shank **202**. The shank **202** may expand conically from the posterior to the anterior of the brace **200** or may have a single diameter from the posterior to the anterior of the brace **200**. In some embodiments, the brace **200** additionally has a second diameter, which is defined by the area taken by the plurality of wedge locking body elements **220** that protrude from the shank **202**. The diameter the plurality of wedge locking body elements **220** may expand conically from the posterior to the anterior of the brace **200** or may have a single diameter from the posterior to the anterior of the brace **200**. In this regard, the diameter of the shank **202** and diameter associated with the wedge elements **220** expand conically from the posterior to the anterior of the brace **200** in a manner that corresponds to the tapering of the intervertebral device **100**. The outer surfaces of the wedge elements **220** are generally configured to match the contour of the interior walls of the intervertebral device **100**. In some embodiments, the wedge elements **220** are integrally joined to the shank **202** and may have a right-angled shape.

[0069] In some embodiments, the brace includes four wedge elements **220** that together form a cruciform, which functions to further stabilize the walls and to obstruct material from displacing/egressing from the interior of the device via the posterior portal. In some embodiments the cruciform provides support along the midlines of the walls **22**, **24**, **26** of the intervertebral device **100**.

[0070] The brace **200** may be inserted into the intervertebral device **100** such that the wedge elements **220** are angled to the corners of the intervertebral device **100** such that the brace freely slides into the interior of the intervertebral device **100** (see e.g., Figures 4 and 5). The brace **200** can advance until movement is halted by the posterior cap **210**. The brace can then be rotated (clockwise or counterclockwise as appropriate) into a locked position guided by the wedge elements **220**. The wedge elements **220** can be integrally joined to the shank **202** and may have a right-angled shape. The brace **200** can be rotated such that the wedge elements **220** engage the walls of the intervertebral device **100**. When the outer surfaces of the wedge elements fully engage the walls of the intervertebral device **100**, the free sliding motion of the brace **200** can give way to the wedging action created by the force created between the walls of the intervertebral device **100** and the wedging elements **220** of the brace. The brace **200** can be formed of a variety of materials including, but not limited to PEEK or carbon fiber composite. The material can be selected to minimize the effect of radiodense material obstructing X-ray visualization of the interbody bone or graft consolidation.

[0071] In some embodiments, the wedge locking body **220** may include two distinct sections: a first posterior section **220** and a second anterior section **230**. Figure 9 provides an enlarged view of the second anterior section **230** of the wedge element. The second anterior section **230** may include a flange **232**, a groove **234**, and a lock **236**. The flange **232** is designed to engage the linear track created by the ridges **62** of the hinge mechanism **60** on the intervertebral device **100** upon rotation of the brace **200** into the lock position (as shown in Figure 7A to 7E). In this manner, the flange **232** resists further rotation of the brace **200**. The ridges **62** fit inside the groove **234** and the lock **236** prevents/resists the backward movement of the brace **200**.

[0072] A posterior cap or wall may be associated with the cruciform bracing or may be independently associated with the expanded intervertebral device, to further stabilize the walls and to obstruct material from displacing from the interior of the

device via the posterior portal. In some embodiments, the posterior cap or wall is locked to the perimeter walls with mating interior and/or exterior geometries, with or without a screw lock and detent mechanism.

[0073] Additionally, a cable element may be used that extends from one opposing wall to another anteriorly, to mitigate deployment significantly beyond the most stable position of relatively coplanar configuration of the lateral walls in the fully extended position as well as to partially contain material delivered into the intervertebral device from the posterior portal.

[0074] Figures 10A and 10B show a brace **300** according to some embodiments as the brace **300** moves from the collapsed to the fully engaged support position. The brace **300** can include a cap **310** and central screw **310**. The cap **310** can be configured to correspond to the posterior end of the implant **100**. The brace **300** can be inserted into the interior cavity of the intervertebral device **400**. The brace **300** can be in position once the posterior cap **310** engages and aligns to posterior end of the intervertebral device **400**. Pressure can be applied to the central screw **312**, and the central screw **312** toward the cap **310**. The central screw **312** may be locked/snapped into place upon engagement of the cap **310**. The pressure applied to the central screw **312** also can cause deployment of the support pads **320**, which is connected to the central screw **312** via a lever mechanism **330**. The pads **320** can engage walls of the implant and provide support in all four quadrants. The support pads **320** may optionally be configured to engage a lock mechanism **340** on the implant **100** to further prevent the brace from migrating after deployment.

[0075] As mentioned above, the peripheral walls can be at least partially expanded prior to insertion of the brace by prying open or expanding the walls from the initial introductory configuration of reduced height and volume to an expanded position of increased height and volume. An elongate tool, such as an obturator, can be used. For example, the obturator can include a tapered projecting tip that can have external surface thread form to couple to a complementary threaded entry port at a posterior end of the device. Alternatively or in addition to the obturator, the

peripheral walls of the intervertebral device **100** can be at least partially expanded *in situ* prior to insertion of the brace **200** using an expanding element **1205** positioned on an obturator **1210** (see Figures 12A-12B). The walls can be expanded symmetrically in a simultaneous manner, alternatively, the walls can be expanded asymmetrically or in a sequential manner. The obturator **1210** having a tapered distal end **1215** can be inserted such that it inserts through the posterior end of the intervertebral device **100**. The distal end **1215** of the obturator **1210** can have a coupling mechanism such as threads such that couple with a complementary threaded entry port near the posterior end of the device **100**, such that the obturator **1210** can be used to pull itself into the interior volume of the intervertebral device **100** while urging the expandable element **1205** surrounding an outer surface of the distal end **1215** of the obturator **1210** into the interior volume. The obturator **1210** need not include threads and can be tapped into the entry using another tool. The expandable element **1205** on the distal end **1215** of the obturator **1210** can be inserted through the interior volume towards an anterior region of the interior volume where it can be expanded radially outward. The expandable element **1205** can be formed of an elastomeric material, such as a balloon, that can be pressurized such as with a gas or fluid to hydraulically expand the expandable element **1205**. Hydraulic expansion of the expandable element **1205** positioned in the interior volume can urge the peripheral walls of the device towards the second, expanded configuration. An anterior region of the expandable element **1205** can have a larger radially expansion than a more proximal region of the expandable element **1205** to accommodate the wedge-shaped intervertebral device **100**. The expandable element **1205** can be positioned on the obturator **1210** near a tapered, projecting tip of the distal end **1215**.

[0076] Once the intervertebral device **100** is at least partially expanded using the expandable element **1205** on the obturator **1210**, the brace **200** can be inserted over the obturator **1210** by virtue of the bore **245** extending through the brace **200** along its longitudinal axis. The brace **200** can be inserted such that an anterior opening **247** to the bore **245** is at least in contact with a proximal region of the expandable

element 1205. The expandable element 1205 can be collapsed back down around an outer surface of the obturator 1210 and withdrawn through the bore 245 of the brace 200. The brace 200 can be urged in a more anterior direction to maintain the expanded configuration of the intervertebral device 100 and then locked into position.

[0077] The devices described herein can include caudal and cephalad plates that are positioned adjacent to vertebral endplates within an intervertebral disc space. The devices can include at least two lateral walls attached to the caudal and cephalad plates via an articulating mechanism. Any of the plates and walls can be relatively radiolucent. Further, any of the plates and walls can include an external surface that is textured. At least one of the lateral walls can include a hinge element that is restricted from achieving an on-center or over-center articulation position. The devices can be configured to be inserted into an intervertebral disc space in a reduced dimension configuration and subsequently expanded to an enlarged dimension configuration. In the enlarged dimension configuration, materials can be positioned and contained within the internal volume of the device. Such materials can include one or more osteoinductive, osteoproliferative, osteoconductive materials. The materials can extend from an inferior (caudal) vertebral endplate to a superior (cephalad) vertebral endplate. The enlarged dimension configuration can be dimensionally expanded along an axis or arc other than the expansion associated with caudal - cephalad expansion. The devices can further include an internal brace positioned between the plates and the at least two lateral walls. The brace can be compressed by the caudal-cephalad compressive loading of the device along axes extending between the caudal and cephalad plates as well as between at least two lateral walls.

[0078] The intervertebral device can be implanted through a relatively small posterior access annulotomy, while providing for lordotic support inducing disc space distraction and an expanded "foot-print" for endplate support.

[0079] In some embodiments, the intervertebral device is delivered by an insertion

tool that provides relatively smooth boundary surfaces, such that insertion adjacent to nerve roots or dura would be less hazardous. The intervertebral device may further include extensive fenestration of its surfaces, to provide for fibrous, vascular, and osseous in-growth. This will further stabilize the device and facilitate bone growth from endplate to adjacent endplate.

[0080] As mentioned above, the intervertebral device can be initially delivered into the disc space, in a collapsed or folded form and then expanded *in situ*. The intervertebral device may be expanded *in situ* using a variety of methods, including, but not limited to, hydraulic expansion (e.g., using an expanding balloon), mechanical distraction (e.g., using a wedging tool to pry the walls apart), or an articulating tool (e.g., one that pushes or pulls opposing walls apart).

[0081] In some embodiments, the intervertebral device is delivered by an insertion tool or outer sheath that provides relatively smooth boundary surfaces, such that insertion adjacent to nerve roots or dura would be less hazardous. The brace and/or obturator may also be delivered via a sheath.

[0082] In some embodiments, the intervertebral device includes extensive fenestration of its surfaces, to provide for fibrous, vascular, and osseous in-growth from neighboring and adjacent vertebrae and/or vertebral endplates. This will further stabilize the device and facilitate bone growth from endplate to adjacent endplate.

[0083] According to some embodiments, methods are provided in which an intervertebral device as described herein is introduced into the intervertebral disc space with the hinged walls articulated as to reduce or minimize the cross-sectional delivery area requirement or insertion volume of introduction, with subsequent deployment of the device in an expanded geometry, such that the hinged elements are relatively parallel in their stabilized and/or deployed configuration. The deployment into the expanded geometry can be performed by a separate tool inserted within the interior volume of the device such that the walls of the device are pried open and expanded outward. The walls can be articulated using a wedge-like

tool or hydraulic expansion.

[0084] Some embodiments provide an interbody intervertebral device indicated for vertebral body replacement or interbody fusion. The intervertebral device may be inserted through an open, or minimally invasive, posterior, anterior, or transforaminal approach into the implantation space to maintain or restore the height of a disc space after a discectomy or other procedure. Fusion of the vertebral bodies may take place over the course of 6-12 months during which it may be desired to maintain an appropriate space between the vertebral bodies.

[0085] Some embodiments provide an artificial interbody spinal fusion intervertebral device for insertion within an implantation space formed across the height of a disc space between vertebral bodies of a human spine.

[0086] Other embodiments can include a surgical kit for surgery on human spines having vertebral bodies and disc spaces having heights between some of the vertebral bodies, the vertebral bodies having an anterior aspect and a posterior aspect and a depth therebetween. According to one embodiment, a surgical kit can comprise a set of different sized articulating interbody cages for insertion within implantation spaces formed across the heights of the disc spaces.

[0087] Another embodiment can include a method of manufacturing an articulating interbody cage for insertion within an implantation space formed across the height of a disc space between vertebral bodies of a human spine, the vertebral bodies having an anterior aspect and a posterior aspect and a depth therebetween.

[0088] While this specification contains many specifics, these should not be construed as limitations on the scope of what is claimed or of what may be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single

embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or a variation of a sub-combination. Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. Only a few examples and implementations are disclosed. Variations, modifications and enhancements to the described examples and implementations and other implementations may be made based on what is disclosed.

CLAIMS

WHAT IS CLAIMED IS:

1. An intervertebral device for use in a human spine, the device comprising:
 - an anterior end;
 - a posterior end; and
 - at least four peripheral walls defining an interior volume surrounding a midline of the device, wherein the peripheral walls comprise a superior wall, an inferior wall and a pair of opposing, generally trapezoidal-shaped sidewalls,
wherein each of the trapezoidal-shaped sidewalls comprises an internal hinge element that is rotatable from a first configuration to at least a second configuration such that the device is expandable in first dimension, and
wherein each of the internal hinge elements comprises an axis that is coplanar with the midline of the device.
2. The device of claim 1, wherein the device is additionally expandable in a second dimension.
3. The device of claim 2, wherein the first dimension comprises a caudal-cephalad dimension and the second dimension comprises a medial-lateral dimension.
4. The device of claim 1, wherein each of the internal hinge elements is positioned along the midline of its respective sidewall.
5. The device of claim 1, wherein the superior wall and the inferior wall each mate with the pair of opposing sidewalls at a rotatable joint.

6. The device of claim 1, wherein the internal hinge element couples a superior plate element to an inferior plate element.

7. The device of claim 1, wherein each of the internal hinge elements further comprises a plurality of overhangs configured to restrict articulation from the first configuration to the second configuration.

8. The device of claim 1, wherein the cephalad surface of the superior wall is configured to engage a first vertebra of the human spine, and wherein at least a portion of the caudal surface of the inferior wall is configured to engage a second vertebra of the human spine.

9. The device of claim 1, wherein the cephalad surface of the superior wall and the caudal surface of the inferior wall are configured to penetrate the respective superior and inferior endplates.

10. The device of claim 1, wherein the cephalad surface of the superior wall and the caudal surface of the inferior wall comprise projection elements that engage the respective superior and inferior vertebral endplates.

11. The device of claim 10, wherein the projection elements comprise a wedge shape and provide additional separation between the superior and inferior vertebral endplates.

12. The device of claim 10, wherein the projection elements comprise a tapered distal tip.

13. The device of claim 10, wherein the outer surfaces of the pair of opposing sidewalls comprise projection elements, wherein the projection elements impart further stiffness to the opposing sidewalls.

14. The device of claim 1, wherein the generally trapezoidal-shaped sidewalls are oriented relative to the spine such that the longer segment is anterior and the shorter segment is posterior.

15. The device of claim 14, wherein the device creates a desired lordosis in the spine.

16. The device of claim 1, wherein each of the at least four peripheral walls is generally trapezoidal-shaped.

17. The device of claim 1, wherein the internal hinge element comprises a plurality of ridge elements that form a linear track upon expansion of the intervertebral device to the second configuration.

18. The device of claim 17, wherein the internal hinge element further comprises a plurality of overhangs configured to restrict articulation from the first configuration to the second configuration.

19. The device of claim 1, further comprising a brace configured to be positioned within the interior volume of the intervertebral device to support the intervertebral device under load.

20. The device of claim 19, wherein the brace comprises a cylindrical element having a tapered outer diameter such that when positioned in the interior volume the brace is larger near the anterior region than the posterior region.

21. The device of claim 19, wherein the brace element has a fixed dimension.

22. The device of claim 19, wherein the brace element prevents one or more of the peripheral walls from articulating from the second configuration towards the first configuration.

23. The device of claim 19, wherein the brace element is configured to be translated from an initial introductory orientation to a final stabilization orientation.

24. The device of claim 19, wherein the brace element comprises fenestrations configured to permit growth of tissue from one vertebral endplate to a second vertebral endplate.

25. A method of treating a spine, comprising:

positioning an intervertebral device in a first configuration into a space between adjacent vertebrae, the intervertebral device comprising:

an anterior end, a posterior end, and at least four peripheral walls defining an interior volume, wherein the peripheral walls comprise a superior wall, an inferior wall and a pair of opposing sidewalls, wherein at least two of the peripheral walls are generally trapezoidal, and wherein the opposing sidewalls comprise an articulation mechanism having a plurality of hinges, wherein the first configuration comprises the plurality of hinges articulated to minimize the interior volume of the intervertebral device;

inserting a brace through the interior volume of the intervertebral device in a posterior to anterior direction to deploy the intervertebral device into a second configuration to separate the adjacent vertebrae and create a desired lordosis in the spine, wherein the second configuration comprises an interior volume that is larger than when the device is in the first configuration; and

locking the brace such that the plurality of hinges are prevented by the brace from articulating into the first configuration.

26. The method of claim 25, further comprising inserting an elongate tool into the interior volume to expand the device towards the second configuration prior to inserting the brace.

27. The method of claim 26, wherein inserting the elongate tool comprises using a tapered projecting tip on the elongate tool to pry open and at least partially articulate the plurality of hinges.

28. The method of claim 26, further comprising expanding an elastomeric element on the elongate tool using hydraulic pressure.

29. The method of claim 28, further comprising collapsing the elastomeric element on the elongate tool and withdrawing the tool through a central bore extending through a longitudinal axis of the brace.

30. A device comprising:

caudal and cephalad plates that are positioned adjacent to vertebral endplates within an intervertebral disc space;

at least two lateral walls attached to the caudal and cephalad plates via an articulating mechanism, wherein at least one of the lateral walls includes a hinge element restricted from achieving an on-center or over-center articulation position,

wherein the device is configured to be inserted into an intervertebral disc space in a reduced dimension configuration and subsequently expanded to an enlarged dimension configuration.

31. The device of claim 30, wherein one or more of the caudal plate, cephalad plate, and lateral walls is relatively radiolucent.

32. The device of claim 30, further comprising one or more osteoinductive, osteoproliferative, osteoconductive materials positioned internal to the device and extending from a caudal vertebral endplate to a cephalad vertebral endplate.

33. The device of claim 30, wherein one or both of the caudal and cephalad plates comprises an external textured surface.

34. The device of claim 30, wherein the enlarged dimension configuration is dimensionally expanded along an axis or arc other than that associated with caudal - cephalad expansion.

35. A device comprising:

caudal and cephalad plates that are positioned adjacent to vertebral endplates within an intervertebral disc space;

at least two lateral walls attached to the caudal and cephalad plates via an articulating mechanism;

an internal brace positioned between the plates and the at least two lateral

walls, such that caudal- cephalad compressive loading of the device results in compression of the internal brace along axes extending between the caudal and cephalad plates as well as between at least two lateral walls,

wherein the device is configured to be inserted into an intervertebral disc space in a reduced dimension configuration and subsequently expanded to an enlarged dimension configuration.

36. The device of claim 35, wherein one or more of the caudal plate, cephalad plate, and lateral walls is relatively radiolucent.

37. The device of claim 35, further comprising one or more osteoinductive, osteoproliferative, osteoconductive materials positioned internal to the device and extending from a caudal vertebral endplate to a cephalad vertebral endplate.

38. The device of claim 35, wherein one or both of the caudal and cephalad plates comprises an external textured surface.

39. The device of claim 35, wherein the enlarged dimension configuration is dimensionally expanded along an axis or arc other than that associated with caudal - cephalad expansion.

Figure 1A




Figure 1B






Figure 1C




4/40

Figure 1D




5/40

Figure 2A




6/40

Figure 2B




7/40

Figure 2C




8/40

Figure 3A



9/40

Figure 3B



10/40

Figure 3C






Figure 4A




12/40

Figure 4B




13/40

Figure 4C




14/40

Figure 4D




15/40

Figure 4E




16/40

Figure 5A




17/40

Figure 5B


18/40

Figure 5C




19/40

Figure 5D




20/40

Figure 5E




21/40

Figure 6A




22/40

Figure 6B




23/40

Figure 6C




24/40

Figure 6D




25/40

Figure 6E




26/40

Figure 7A




27/40

Figure 7B


28/40

Figure 7C




29/40

Figure 7D




30/40

Figure 7E




31/40

Figure 8A




32/40


Figure 8B



33/40

Figure 8C





35/40






Figure 10B



37/40

Figure 11A



38/40

Figure 11B






Figure 12A



40/40

Figure 12B



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2012/031693

A. CLASSIFICATION OF SUBJECT MATTER
INV. A61F2/44
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
A61F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 126 689 A (BRETT DARRELL C) 3 October 2000 (2000-10-03)	1-18, 30-34
Y	column 2, line 28 - column 6, line 35; claims; figures -----	19-24, 35-39
Y	US 2005/131536 A1 (EISERMANN L ET AL) 16 June 2005 (2005-06-16) paragraphs [0035] - [0049]; claims; figures -----	19-24, 35-39
A	WO 2010/078468 A2 (JIMENEZ O F ET AL) 8 July 2010 (2010-07-08) claims; figures 1a-30d -----	1-24, 30-39
A	US 2008/243255 A1 (BUTLER M S ET AL) 2 October 2008 (2008-10-02) claims; figures -----	1-24, 30-39
		-/-

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier application or patent but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
14 June 2012	22/06/2012
Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Kühne, H

INTERNATIONAL SEARCH REPORTInternational application No
PCT/US2012/031693**C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2009/125242 A1 (VEXIM) 15 October 2009 (2009-10-15) claims; figures -----	1-24, 30-39
A	WO 2005/120400 A2 (CERAVIC) 22 December 2005 (2005-12-22) claims; figures -----	1-24, 30-39

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2012/031693

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.: **25-29**
because they relate to subject matter not required to be searched by this Authority, namely:
No International Preliminary Examining Authority shall be required to search an international application on an international application if, and to the extent to which, its subject matter are methods for treatment of the human or animal body by surgery (Rule 39.1(iv) PCT).
2. Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying an additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2012/031693

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
US 6126689	A	03-10-2000	AU	6953400 A	30-01-2001
			CA	2375689 A1	18-01-2001
			EP	1210037 A1	05-06-2002
			US	6126689 A	03-10-2000
			US	6409766 B1	25-06-2002
			WO	0103616 A1	18-01-2001
<hr style="border-top: 1px dashed black;"/>					
US 2005131536	A1	16-06-2005	AT	493950 T	15-01-2011
			AU	2004299064 A1	30-06-2005
			CA	2549106 A1	30-06-2005
			CN	1909853 A	07-02-2007
			EP	1706075 A2	04-10-2006
			JP	2007513718 A	31-05-2007
			US	2005131536 A1	16-06-2005
			US	2009312837 A1	17-12-2009
			WO	2005058209 A2	30-06-2005
<hr style="border-top: 1px dashed black;"/>					
WO 2010078468	A2	08-07-2010	CN	102341066 A	01-02-2012
			EP	2376030 A2	19-10-2011
			WO	2010078468 A2	08-07-2010
<hr style="border-top: 1px dashed black;"/>					
US 2008243255	A1	02-10-2008	US	2008243255 A1	02-10-2008
			WO	2008121317 A1	09-10-2008
<hr style="border-top: 1px dashed black;"/>					
WO 2009125242	A1	15-10-2009	US	2009281628 A1	12-11-2009
			WO	2009125242 A1	15-10-2009
<hr style="border-top: 1px dashed black;"/>					
WO 2005120400	A2	22-12-2005	AU	2005251536 A1	22-12-2005
			CA	2567274 A1	22-12-2005
			CN	101031259 A	05-09-2007
			FR	2871366 A1	16-12-2005
			FR	2871367 A1	16-12-2005
			JP	2011005264 A	13-01-2011
			US	2005278036 A1	15-12-2005
			US	2006004455 A1	05-01-2006
			US	2011046739 A1	24-02-2011
			WO	2005120400 A2	22-12-2005
<hr style="border-top: 1px dashed black;"/>					