



US011362687B2

(12) **United States Patent**
Tsai et al.

(10) **Patent No.:** **US 11,362,687 B2**
(45) **Date of Patent:** ***Jun. 14, 2022**

(54) **WIRELESS COMMUNICATION DEVICE**

(71) Applicant: **HTC CORPORATION**, Taoyuan (TW)

(72) Inventors: **Tiao-Hsing Tsai**, Taoyuan (TW);
Chien-Pin Chiu, Taoyuan (TW);
Hsiao-Wei Wu, Taoyuan (TW);
Yi-Hsiang Kung, Taoyuan (TW);
Shen-Fu Tzeng, Taoyuan (TW);
Li-Yuan Fang, Taoyuan (TW)

(73) Assignee: **HTC CORPORATION**, Taoyuan (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/880,036**

(22) Filed: **May 21, 2020**

(65) **Prior Publication Data**

US 2020/0287572 A1 Sep. 10, 2020

Related U.S. Application Data

(60) Continuation of application No. 16/239,710, filed on Jan. 4, 2019, now Pat. No. 10,700,716, which is a (Continued)

(51) **Int. Cl.**

H04B 1/38 (2015.01)
H04B 1/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **H04B 1/006** (2013.01); **H01Q 1/243** (2013.01); **H01Q 5/328** (2015.01); **H01Q 5/35** (2015.01);

(Continued)

(58) **Field of Classification Search**

CPC **H04B 1/0053**; **H04B 1/0064**; **H01Q 1/00**;
H01Q 5/00; **H01Q 1/243**; **H01Q 9/42**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

10,158,381 B2 * 12/2018 Tsai **H04B 1/40**
10,211,858 B2 * 2/2019 Tsai **H04B 1/006**
(Continued)

FOREIGN PATENT DOCUMENTS

CN 200986965 A 12/2007
CN 200986965 Y 12/2007
(Continued)

OTHER PUBLICATIONS

Chinese language office action dated Aug. 2, 2019, issued in application No. CN 201711214164.4.

(Continued)



Primary Examiner — Tuan Pham

(74) *Attorney, Agent, or Firm* — McClure, Qualey & Rodack, LLP

(57) **ABSTRACT**

A wireless communication device is provided. The wireless communication device includes a housing, a circuit board, a radio frequency module and an antenna. The housing has a frame and a back cover to define a receiving space. The circuit board is disposed in the receiving space, and defines a clearance area from the housing in the receiving space. The circuit board includes a ground terminal, a first feeding point, and a second feeding point. The antenna includes at least one metal conductor coupled to the first feeding point and the second feeding point, respectively, to provide a low frequency resonant path, a first middle frequency resonant path, a second middle frequency resonant path and a high frequency resonant path.

24 Claims, 22 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 16/139,107, filed on Sep. 24, 2018, now Pat. No. 10,211,858, which is a division of application No. 15/821,777, filed on Nov. 23, 2017, now Pat. No. 10,158,381.
- (60) Provisional application No. 62/428,183, filed on Nov. 30, 2016.
- (51) **Int. Cl.**
H01Q 5/328 (2015.01)
H01Q 5/371 (2015.01)
H01Q 1/24 (2006.01)
H01Q 5/35 (2015.01)
H04B 1/40 (2015.01)
H04W 88/06 (2009.01)
- (52) **U.S. Cl.**
 CPC *H01Q 5/371* (2015.01); *H04B 1/40* (2013.01); *H04W 88/06* (2013.01)
- (58) **Field of Classification Search**
 CPC H01Q 21/28; H01Q 5/328; H01Q 5/35; H01Q 5/371; H01B 1/006; H01B 1/40
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 10,700,716 B2* 6/2020 Tsai H01Q 1/243
 2010/0277376 A1* 11/2010 Chakam H01Q 1/243
 343/702

- 2012/0001815 A1* 1/2012 Wong H01Q 9/0414
 343/749
- 2013/0027254 A1 1/2013 Korva et al.
 2013/0057437 A1 3/2013 Chiu et al.
 2013/0063313 A1 3/2013 Ban et al.
 2013/0335280 A1* 12/2013 Chen, III H01Q 21/30
 343/745
- 2014/0015729 A1 1/2014 Uejima et al.
 2014/0184465 A9 7/2014 Uejima et al.
 2016/0254832 A1* 9/2016 Yoo H01Q 5/378
 455/575.5
- 2017/0012341 A1* 1/2017 Mai H01Q 13/16
 2017/0142241 A1* 5/2017 Kim H04M 1/0218
 2017/0338546 A1* 11/2017 Wong H01Q 1/48

FOREIGN PATENT DOCUMENTS

- | | | | |
|----|-----------|---|---------|
| CN | 101335375 | A | 12/2008 |
| CN | 101388494 | A | 3/2009 |
| CN | 101662067 | A | 3/2010 |
| CN | 102983405 | A | 3/2013 |
| CN | 103000986 | A | 3/2013 |
| CN | 103296385 | A | 9/2013 |
| CN | 203721879 | A | 7/2014 |
| CN | 204391272 | U | 6/2015 |
| CN | 105990638 | A | 10/2016 |

OTHER PUBLICATIONS

- Chinese language office action dated May 14, 2021, issued in application No. CN 202010412479.5.
 English language translation of Chinese office action.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5




FIG. 6




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 16A




FIG. 16B




FIG. 16C




FIG. 16D

WIRELESS COMMUNICATION DEVICE

CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a Continuation Application of U.S. application Ser. No. 16/239,710 filed Jan. 4, 2019 (now U.S. Pat. No. 10,700,716), which is a Continuation Application of U.S. application Ser. No. 16/139,107 filed Sep. 24, 2018 (now U.S. Pat. No. 10,211,858, issued on Feb. 19, 2019), which is a Divisional Application of U.S. application Ser. No. 15/821,777 filed Nov. 23, 2017, now U.S. Pat. No. 10,158,381 issued on Dec. 18, 2018, which claims priority to U.S. Provisional Application Ser. No. 62/428,183 filed on Nov. 30, 2016, all of which are hereby incorporated by reference in their entireties.

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a wireless communication device. More particularly, the wireless communication device of the present invention has an antenna operating in multiple frequency bands at the same time so as to support the carrier aggregation (CA) technology.

Descriptions of the Related Art

With the vigorous development of wireless communication industries, the demands for wireless transmission data amount are increasing day by day. To meet the demands of users, a rapid wireless transmission speed is necessary. Therefore, the mainstream fourth generation of mobile communication systems (e.g., the LTE mobile communication system) adopts the CA technology to simultaneously receive data on multiple frequency bands via the antenna to increase the transmission speed.

However, in consideration of the pleasant appearance and the size of wireless communication devices (particularly, mobile phones), an urgent need exists in the art to provide a multi-band antenna within a complicated and small receiving space of the housing and combine the antenna with a metal frame.

SUMMARY OF THE INVENTION

The present invention provides an antenna design with multiple feeding sources, which is capable of feeding multiple radio frequency (RF) signal sources to a same antenna physical structure to share an antenna clearance area and save the space occupied by the antenna within a wireless communication device, and is capable of utilizing a suitable physical structural design to achieve a high isolation and a high radiant efficiency among multiple RF signal resources. Moreover, the antenna design with multiple feeding sources of the present invention may also add active components to optimize impedance matching and increase the real-time adjustability of the operation frequency band.

In one embodiment, a wireless communication device, comprises: a housing, having a frame; a circuit board, having a plurality of ground terminal, a first feeding point, and a second feeding point; a radio frequency (RF) module, being disposed on the circuit board and coupled to the first feeding point and the second feeding point; and an antenna, for transmitting and receiving an RF signal. The antenna comprises: a first metal conductor, coupling to the first

feeding point and extending toward a lateral direction; and a second metal conductor, coupling to the second feeding point and extending toward a longitudinal direction. The first metal conductor and the second metal conductor are formed by two parts of the frame respectively, and the frame has at least one cut point, and each of the at least one cut point is formed in one of an upper portion, a lower portion, a left portion, and a right portion of the frame.

In another embodiment, a wireless communication device comprises: a circuit board, having a plurality of ground terminal, a first feeding point, and a second feeding point; a radio frequency (RF) module, being disposed on the circuit board and coupled to the first feeding point and the second feeding point; and an antenna, for transmitting and receiving an RF signal. The antenna comprises: a first metal conductor, coupling to the first feeding point and extending toward a lateral direction; a second metal conductor, coupling to the second feeding point and extending toward a longitudinal direction; and an extension metal piece, coupling the first metal conductor to the second metal conductor; and a housing, having a frame and a back cover to define a receiving space. The circuit board is disposed in the receiving space, and the first metal conductor and the second metal conductor are formed by two parts of the frame respectively.

The detailed technology and preferred embodiments implemented for the subject invention are described in the following paragraphs accompanying the appended drawings for people skilled in this field to well appreciate the features of the claimed invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic exploded view of a mobile communication device 1 according to a first embodiment of the present invention;

FIG. 2A to FIG. 2C are schematic views illustrating multiple resonant paths according to the first embodiment of the present invention;

FIG. 3A is a schematic structural view of an antenna comprising a single-pole-four-throw (SP4T) switch SW1 according to a second embodiment of the present invention;

FIG. 3B is a schematic structural view of an antenna comprising a switch SW2 according to the second embodiment of the present invention;

FIG. 3C is a schematic structural view of an antenna comprising both the SP4T switch SW1 and the switch SW2 according to the second embodiment of the present invention;

FIG. 4 is a schematic structural view of an antenna according to a third embodiment of the present invention;

FIG. 5 is a schematic structural view of an antenna according to a fourth embodiment of the present invention;

FIG. 6 is a schematic structural view of an antenna according to a fifth embodiment of the present invention;

FIG. 7A to FIG. 7C are schematic views illustrating multiple resonant paths according to the fifth embodiment of the present invention;

FIG. 8A is a schematic structural view of an antenna comprising the SP4T switch SW1 according to a sixth embodiment of the present invention;

FIG. 8B is a schematic structural view of an antenna comprising the switch SW2 according to the sixth embodiment of the present invention;

FIG. 8C is a schematic structural view of an antenna comprising both the SP4T switch SW1 and the switch SW2 according to the sixth embodiment of the present invention;

FIG. 9 is a schematic structural view of an antenna according to a seventh embodiment of the present invention;

FIG. 10A is a schematic front view of a finished product of the mobile communication device 1 according to an eighth embodiment of the present invention;

FIG. 10B is a schematic back view of the finished product of the mobile communication device 1 according to the eighth embodiment of the present invention;

FIG. 11A is a schematic front view of a finished product of the mobile communication device 1 according to a ninth embodiment of the present invention;

FIG. 11B is a schematic back view of the finished product of the mobile communication device 1 according to the ninth embodiment of the present invention;

FIG. 12A is a schematic front view of a finished product of the mobile communication device 1 according to a tenth embodiment of the present invention;

FIG. 12B is a schematic back view of the finished product of the mobile communication device 1 according to the tenth embodiment of the present invention;

FIG. 13A is a schematic front view of a finished product of the mobile communication device 1 according to an eleventh embodiment of the present invention;

FIG. 13B is a schematic back view of the finished product of the mobile communication device 1 according to the eleventh embodiment of the present invention;

FIG. 14A is a schematic front view of a finished product of the mobile communication device 1 according to a twelfth embodiment of the present invention;

FIG. 14B is a schematic back view of the finished product of the mobile communication device 1 according to the twelfth embodiment of the present invention;

FIG. 15A to FIG. 15D are schematic views illustrating four implementations of the mobile communication device 1 according to a thirteenth embodiment of the present invention; and

FIG. 16A to FIG. 16D are schematic views illustrating four implementations of the mobile communication device 1 according to a fourteenth embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following description, the present invention will be explained with reference to embodiments thereof. However, these embodiments are not intended to limit the present invention to any specific environment, applications or particular implementations described in these embodiments. Therefore, description of these embodiments is only for purpose of illustration rather than to limit the present invention. It should be appreciated that, in the following embodiments and the attached drawings, elements unrelated to the present invention are omitted from depiction; and dimensional scales among individual elements in the attached drawings are provided only for illustration, but not to limit the actual scale.

Please refer to FIG. 1 for a first embodiment of the present invention, and FIG. 1 is a schematic exploded view of a mobile communication device 1 of the present invention. The mobile communication device 1 comprises a housing 11, a circuit board 13, a radio frequency (RF) module 15 and an antenna 17. The housing 11 at least comprises a frame FM and a back cover BC to define a receiving space RS. It shall be noted that, based on the principle of simplifying the description, other components of the mobile communication device 1 such as a display module, an image capturing

module, a power module, an input module and components irrelevant to the present invention are omitted from depiction in the drawings.

When the circuit board 13 is disposed in the receiving space RS, the circuit board 13 defines a clearance area together with the housing 11 so that the antenna 17 can be disposed within the clearance area, thereby protecting the antenna 17 from interference caused by remaining electronic components on the circuit board 13 or other components of the mobile communication device 1. Moreover, to prevent the housing 11 from influencing characteristics of the antenna 17, the frame FM and a slash part DA of the back cover BC are made of non-metal materials, while the remaining part except for the slash part DA may be made of metal materials or non-metal materials. The clearance area may be an area in the receiving space RS that is not overlapped with the circuit board 13 or further comprises an area that is overlapped with a pure flexible board of the circuit board 13, so the clearance area is generally defined by the frame FM and the slash part DA of the back cover BC. The configuration of the clearance area is known by those of ordinary skill in the art, and thus will not be further described herein. In another embodiment, the antenna 17 may be combined with the frame FM, i.e., at least a part of the frame FM is capable of receiving and transmitting RF signals, and detailed technical contents thereof are as described later.

The circuit board 13 has a ground terminal G, a first feeding point FP1 and a second feeding point FP2. In this embodiment, the first feeding point FP1 is a low/middle frequency feeding point, and the second feeding point FP2 is a high frequency feeding point. The RF module 15 is disposed on the circuit board 13 and coupled to the first feeding point FP1 and the second feeding point FP2. The antenna 17 is disposed in the clearance area and is configured to transmit and receive an RF signal. The antenna 17 comprises a first metal conductor MC1, a second metal conductor MC2 and an extension metal piece EMC. The first metal conductor MC1 and the second metal conductor MC2 may be formed on a surface of a carrier plate in the form of a plane metal layer, while the extension metal piece EMC is formed on the other opposite surface, but it is not limited thereto.

The first metal conductor MC1 extends toward a lateral direction of the frame FM, i.e., the first metal conductor MC1 is located in the lateral direction H of the frame FM when the circuit board 13 and the antenna 17 are disposed in the receiving space RS. The first metal conductor MC1 has a first free end FE1 and a second free end FE2, and the first metal conductor MC1 is extendedly coupled from a first extension point EP_A between the first free end FE1 and the second free end FE2 to the first feeding point FP1, and is coupled from a second extension point EP_B between the first extension point EP_A and the second free end FE2 to the ground terminal G via a passive component PC. Parts of the second metal conductor MC2 extend toward a longitudinal direction of the frame FM and parts of the second metal conductor MC2 extend toward a lateral direction of the frame FM (i.e., the second metal conductor MC2 is located both in the lateral direction H and the longitudinal direction L of the frame FM), and the second metal conductor MC2 has a first endpoint E1 adjacent to the second free end FE2 of the first metal conductor MC1 and a second endpoint E2 away from the second free end FE2 of the first metal conductor MC1.

The second metal conductor MC2 is extendedly coupled from the first endpoint E1 to the ground terminal G and from

the second endpoint E2 to the ground terminal G respectively. The second metal conductor MC2 is also coupled from between the first endpoint E1 and the second endpoint E2 to the second feeding point FP2. Moreover, the extension metal piece EMC is disposed on a surface different from a surface on which the first metal conductor MC1 and the second metal conductor MC2 are disposed, and the extension metal piece EMC is coupled between the second free end FE2 of the first metal conductor MC1 and the first endpoint E1 of the second metal conductor MC2 to serve as a connecting bridge between the first metal conductor MC1 and the second metal conductor MC2, thereby extending the resonant path of the antenna 17.

In this way, as shown in FIG. 2A to FIG. 2C, the antenna 17 has a low frequency resonant path LRP from the first feeding point FP1 to the first free end FE1 of the first metal conductor MC1, which is equivalent to a quarter of a wavelength of a low frequency operation frequency (e.g., 700 MHz). Meanwhile, the antenna 17 further has a first middle frequency resonant path MRP1 from the first feeding point FP1 via the extension metal piece EMC to the ground terminal G to which the first endpoint E1 of the second metal conductor MC2 is extendedly coupled, and the first middle frequency resonant path MRP1 is equivalent to a half of a wavelength of a first middle frequency operation frequency (e.g., 1710 MHz). The antenna 17 further has a second middle frequency resonant path MRP2 from the first feeding point FP1 to the first free end FE1 of the first metal conductor MC1, which is equivalent to three quarters of a wavelength of a second middle frequency operation frequency (e.g., 2170 MHz). Moreover, the antenna 17 further has a high frequency resonant path HRP from the second feeding point FP2 to the second endpoint E2 of the second metal conductor MC2, to the ground terminal G to which the first endpoint E1 is extendedly coupled, and via the extension metal piece EMC to the ground terminal G to which the second extension point EP_B of the first metal conductor MC1 is extendedly coupled, and the high frequency resonant path HRP is equivalent to a half of a wavelength of a high frequency operation frequency (e.g., 2300 MHz).

It shall be appreciated that, a passive component PC (e.g., an inductor, a capacitor and any combination thereof) connects the second extension point EP_B of the first metal conductor MC1 and the ground terminal G so as to adjust the high frequency resonant path HRP of the antenna 17. In other embodiments, the present invention may also achieve the purpose of changing the length of the high frequency path via physical winding. Moreover, in other embodiments, the second extension point EP_B may also be disposed at the same position as the first extension point EP_A so that the second extension point EP_B and the first extension point EP_A are overlapped on the first metal conductor.

It shall be appreciated that, through the length design of the resonant paths, the present invention enables the high-frequency signal to regard the first feeding point FP1 as an open end, so the two feeding sources (the first feeding point FP1 and the second feeding point FP2) have a high isolation therebetween and the antenna 17 maintains a good radiation efficiency. The first metal conductor MC1 may be coupled to the first feeding point FP1 via a connector (e.g., a metal elastic piece or a metal screw), and the second metal conductor MC2 may also be coupled to the second feeding point FP2 via a connector (e.g., a metal elastic piece or a metal screw). Similarly, the second metal conductor MC2 may also be coupled to the ground terminal G respectively from the first endpoint E1 and the second endpoint E2 via the connector.

A second embodiment of the present invention is as shown in FIG. 3A to FIG. 3C. To simplify the description, the housing 11 is omitted in FIG. 3A to FIG. 3C. In the implementation of FIG. 3A, the mobile communication device 1 further comprises a single-pole-four-throw (SP4T) switch SW1 which is configured to selectively couple an adjustment point AP between the first extension point EP_A of the first metal conductor MC1 and the first free end FE1 to the ground terminal G via a passive component (e.g., an inductor) to adjust the low frequency operation frequency and the second middle frequency operation frequency of the antenna 17. Specifically, the SP4T switch SW1 provides four paths for coupling to the ground terminal G, so through connecting a passive component (e.g., an inductor) in series on the four paths, the present invention can make the operation frequency of the antenna (e.g., adjust the low frequency operation frequency from 699 MHz to 960 MHz) adjustable and further improve the impedance matching effect. In an actual application, the inductor connected in series with the SP4T switch SW1 may adopt an inductance of 15 nH.

On the other hand, in the implementation of FIG. 3B, the mobile communication device 1 further comprises a switch SW2 which is configured to selectively couple the extension metal piece EMC to the ground terminal to adjust the first middle frequency operation frequency and the high frequency operation frequency of the antenna 17. Similarly, through connecting a passive component (e.g., an inductor) in series with the switch SW2, the present invention can make the operation frequency of the antenna (e.g., switch the high frequency operation frequency between 2300 MHz and 2700 MHz) adjustable and further improve the impedance matching effect. In an actual application, the inductor connected in series with the switch SW2 may adopt an inductance of 22 nH. Moreover, in the implementation of FIG. 3C, the mobile communication device 1 may comprise both the SP4T switch SW1 and the switch SW2.

Please refer to FIG. 4 for a third embodiment of the present invention. Similarly, to simplify the description, the housing 11 is omitted in FIG. 4, and FIG. 4 only focuses on structural features of the antenna 17. This embodiment differs from the first embodiment in that: the first metal conductor MC1 further extends toward a longitudinal direction of the frame FM in addition to the lateral direction of the frame FM so that the first free end FE1 and the second free end FE2 of the first metal conductor MC1 are located at two longitudinal sides of the frame FM respectively. Moreover, the second metal conductor MC2 only extends toward the longitudinal direction of the frame so that the first endpoint E1 and the second endpoint E2 thereof are all located at a longitudinal side of the frame FM.

Similarly, the extension metal piece EMC is disposed on a surface different from the surface on which the first metal conductor MC1 and the second metal conductor MC2 are disposed, and the extension metal piece EMC is coupled between the second free end FE2 of the first metal conductor MC1 and the first endpoint E1 of the second metal conductor MC2 to serve as a connecting bridge between the first metal conductor MC1 and the second metal conductor MC2, thereby extending the resonant path of the antenna 17.

In this case, the antenna 17 also has a low frequency resonant path from the first feeding point FP1 to the first free end FE1 of the first metal conductor MC1, which is equivalent to a quarter of a wavelength of a low frequency operation frequency (e.g., 700 MHz). Meanwhile, the antenna 17 also has a first middle frequency resonant path from the first feeding point FP1 via the extension metal piece

EMC to the ground terminal G to which the first endpoint E1 of the second metal conductor MC2 is extendedly coupled, and the first middle frequency resonant path is equivalent to a half of a wavelength of a first middle frequency operation frequency (e.g., 1710 MHz). The antenna 17 also has a second middle frequency resonant path from the first feeding point FP1 to the first free end FE1 of the first metal conductor MC1, which is equivalent to three quarters of a wavelength of a second middle frequency operation frequency (e.g., 2170 MHz). Moreover, the antenna 17 also has a high frequency resonant path from the second feeding point FP2 to the second endpoint E2 of the second metal conductor MC2, and via the extension metal piece EMC to the ground terminal G to which the second extension point EP_B of the first metal conductor MC1 is extendedly coupled, and the high frequency resonant path is equivalent to a half of a wavelength of a high frequency operation frequency (e.g., 2300 MHz).

It shall be appreciated that, the low frequency resonant path, the first middle frequency resonant path, the second middle frequency resonant path and the high frequency resonant path of the antenna 17 of this embodiment shall be appreciated by those of ordinary skill in the art based on the above descriptions, and thus are omitted from depiction in the drawings. Moreover, as shall also be appreciated by those of ordinary skill in the art, the aforesaid relationships between the resonant paths and the operation frequencies refer to equivalent relationships instead of complete equality in length of physical structures, and the equivalence in length of the structures may be adjusted in combination of other suitable passive components through impedance matching.

Moreover, in other embodiments, the mobile communication device 1 may also add the SP4T switch SW1 and/or the switch SW2 to the antenna 17 so that the operation frequency of the antenna is adjustable and the impedance matching effect is further improved, as described in the second embodiment. The implementation where the SP4T switch SW1 and/or the switch SW2 is added shall be readily appreciated by those of ordinary skill in the art, and thus will not be further described herein.

Please refer to FIG. 5 for a fourth embodiment of the present invention. Similarly, to simplify the description, the housing 11 is omitted in FIG. 5, and FIG. 5 only focuses on structural features of the antenna 17. This embodiment differs from the first embodiment in that: the first metal conductor MC1 further extends toward a longitudinal direction of the frame FM in addition to the lateral direction of the frame FM so that the first free end FE1 of the first metal conductor MC1 is located at a lateral side of the frame FM while the second free end FE2 is located at a longitudinal side of the frame FM. Moreover, the second metal conductor MC2 only extends toward the longitudinal direction of the frame so that the first endpoint E1 and the second endpoint E2 thereof are all located at a longitudinal side of the frame FM.

Similarly, the antenna 17 of this embodiment also has the low frequency resonant path, the first middle frequency resonant path, the second middle frequency resonant path and the high frequency resonant path. These resonant paths shall be appreciated by those of ordinary skill in the art based on the description of the aforesaid embodiments, and thus are omitted from depiction in the drawings. Moreover, the mobile communication device 1 of this embodiment may also add the SP4T switch SW1 and/or the switch SW2 to the antenna 17 so that the operation frequency of the antenna is

adjustable and the impedance matching effect is further improved, as described in the second embodiment.

Please refer to FIG. 6 for a fifth embodiment of the present invention. Similarly, to simplify the description, the housing 11 is omitted in FIG. 6, and FIG. 6 only focuses on structural features of the antenna 17. This embodiment differs from the aforesaid embodiments in that: the antenna 17 of this embodiment is adapted for use in the wireless communication device 1 of a larger size, so the wireless communication device 1 of this embodiment has a larger receiving space RS in which the circuit board 13 and the antenna 17 are provided, and the extension metal piece EMC is not required to extend the resonant path of the antenna 17.

Specifically, the antenna 17 of this embodiment comprises a metal conductor MC which extends toward both a lateral direction and a longitudinal direction of the frame. The metal conductor MC has a free end FE and an endpoint E. The metal conductor MC is extendedly coupled from a first extension point EP1 between the free end FE and the endpoint E to the first feeding point FP1, coupled from a second extension point EP2 between the first extension point EP1 and the free end FE via a passive component PC to the ground terminal G, and is extendedly coupled from a third extension point EP3 between the first extension point EP1 and the endpoint E to the ground terminal G. Moreover, the metal conductor MC is coupled from between the third extension point EP3 and the endpoint E to the second feeding point FP2, and is coupled from the endpoint E to the ground terminal G.

In this way, as shown in FIG. 7A to FIG. 7C, the antenna 17 has the low frequency resonant path LRP from the first feeding point FP1 to the free end FE of the metal conductor MC, which is equivalent to a quarter of a wavelength of a low frequency operation frequency (e.g., 700 MHz). Meanwhile, the antenna 17 also has the first middle frequency resonant path MRP1 from the first feeding point FP1 to the ground terminal G to which the third extension point EP3 is extendedly coupled, and the first middle frequency resonant path MRP1 is equivalent to a half of a wavelength of a first middle frequency operation frequency (e.g., 1710 MHz). The antenna 17 also has the second middle frequency resonant path MRP2 from the first feeding point FP1 to the free end FE of the metal conductor MC, which is equivalent to three quarters of a wavelength of a second middle frequency operation frequency (e.g., 2170 MHz). Moreover, the antenna 17 also has the high frequency resonant path HRP from the second feeding point FP2 to the endpoint E of the metal conductor MC, to the ground terminal G to which the third extension point EP3 is extendedly coupled, and to the ground terminal G to which the second extension point EP2 is extendedly coupled, and the high frequency resonant path HRP is equivalent to a half of a wavelength of a high frequency operation frequency (e.g., 2300 MHz).

Similarly, a passive component PC (e.g., an inductor, a capacitor and any combination thereof) connects the second extension point EP2 of the metal conductor MC1 and the ground terminal G so as to adjust the high frequency resonant path HRP of the antenna 17. In other embodiments, the present invention may also achieve the purpose of changing the length of the high frequency path via physical winding. Moreover, in other embodiments, the first extension point EP1 may also be disposed at the same position as the second extension point EP2 so that the extension point EP1 and the extension point EP2 are overlapped on the metal conductor MC.

A sixth embodiment of the present invention is as shown in FIG. 8A to FIG. 8C. To simplify the description, the

housing **11** is omitted in FIG. **8A** to FIG. **8C**. Similar to the second embodiment, the mobile communication device **1** of this embodiment may also add the SP4T switch **SW1** and the switch **SW2** to the antenna **17** of the fifth embodiment. In the implementation of FIG. **8A**, the SP4T switch **SW1** is configured to selectively couple an adjustment point **AP1** between the first extension point **EP1** of the metal conductor **MC** and the free end **FE** to the ground terminal **G** via a passive component (e.g., an inductor) to adjust the low frequency operation frequency and the second middle frequency operation frequency.

On the other hand, in the implementation of FIG. **8B**, the switch **SW2** is configured to selectively couple an adjustment point **AP2** between the first extension point **EP1** of the metal conductor **MC** and the third extension point **EP3** to the ground terminal **G** via a passive component (e.g., an inductor) to adjust the first middle frequency operation frequency and the high frequency operation frequency. Similarly, in the implementation of FIG. **8C**, the mobile communication device **1** comprises both the SP4T switch **SW1** and the switch **SW2**.

Please refer to FIG. **9** for a seventh embodiment of the present invention. Similarly, to simplify the description, the housing **11** is omitted in FIG. **9**, and FIG. **9** only focuses on structural features of the antenna **17**. This embodiment differs from the fifth embodiment in that: the metal conductor **MC** further extends toward the longitudinal direction of the frame **FM** so that the free end **FE** thereof is located at a longitudinal side of the frame **FM**.

In this case, the antenna **17** also has a low frequency resonant path from the first feeding point **FP1** to the free end **FE** of the metal conductor **MC**, which is equivalent to a quarter of a wavelength of a low frequency operation frequency (e.g., 700 MHz). Meanwhile, the antenna **17** also has a first middle frequency resonant path from the first feeding point **FP1** to the ground terminal **G** to which the third extension point **EP3** is extendedly coupled, and the first middle frequency resonant path is equivalent to a half of a wavelength of a first middle frequency operation frequency (e.g., 1710 MHz). The antenna **17** also has a second middle frequency resonant path from the first feeding point **FP1** to the free end **FE** of the metal conductor **MC**, which is equivalent to three quarters of a wavelength of a second middle frequency operation frequency (e.g., 2170 MHz). Moreover, the antenna **17** also has a high frequency resonant path from the second feeding point **FP2** to the endpoint **E** of the metal conductor **MC**, to the ground terminal **G** to which the third extension point **EP3** is extendedly coupled and to the ground terminal **G** to which the second extension point **EP2** is extendedly coupled, and the high frequency resonant path is equivalent to a half of a wavelength of a high frequency operation frequency (e.g., 2300 MHz).

It shall be appreciated that, the low frequency resonant path, the first middle frequency resonant path, the second middle frequency resonant path and the high frequency resonant path of the antenna **17** of this embodiment shall be appreciated by those of ordinary skill in the art based on the above descriptions, and thus are omitted from depiction in the drawings. Moreover, as shall also be appreciated by those of ordinary skill in the art, the aforesaid relationships between the resonant paths and the operation frequencies refer to equivalent relationships instead of complete equality in length of physical structures, and the equivalence in length of the structures may be adjusted in combination of other suitable passive components through impedance matching.

Moreover, in other embodiments, the mobile communication device **1** may also add the SP4T switch **SW1** and/or the switch **SW2** to the antenna **17** so that the operation frequency of the antenna is adjustable and the impedance matching effect is further improved, as described in the sixth embodiment. The implementation where the SP4T switch **SW1** and/or the switch **SW2** is added shall be readily appreciated by those of ordinary skill in the art, and thus will not be further described herein.

Please refer to FIG. **10A** and FIG. **10B** for an eighth embodiment of the present invention, and FIG. **10A** and FIG. **10B** are schematic front and back views of a finished product of the mobile communication device **1** of the present invention. A front side of the finished product of the mobile communication device **1** is as shown in FIG. **10A**, in which a screen **DP**, an earpiece **EP** and the frame **FM** are presented. Moreover, a back side of the finished product of the mobile communication device **1** is as shown in FIG. **10B**, in which the back cover **BC** and the frame **FM** are presented. It shall be noted that, based on the principle of simplifying the description, other components of the mobile communication device **1** that can be presented on the front side, the back side or the frame **FM** and that are irrelevant to the present invention are omitted from depiction in the drawings. For example, as shall be appreciated by those of ordinary skill in the art, a front image capturing module (a front camera), a fingerprint identification module or the like may be presented on the front side, a rear image capturing module (a rear camera) may be configured on the back side, and a charge interface, a power switch or the like may be configured on the frame **FM**, but it is not limited thereto.

In this embodiment, the antenna **17** is disposed at the bottom of the mobile communication device **1**, i.e., disposed at a place near to a microphone (not shown), so the first metal conductor **MC1** and the second metal conductor **MC2** are formed by two parts of the frame **FM** respectively. The first free end **FE1** and the second free end **FE2** of the first metal conductor **MC1** form two breaks of the frame **FM** respectively at the lower portion of the frame **FM**. However, in other embodiments, the antenna **17** may also be disposed at the top of the mobile communication device **1**, i.e., disposed at a place near to the earpiece, so that the first free end **FE1** and the second free end **FE2** of the first metal conductor **MC1** form two breaks of the frame **FM** respectively at the upper portion of the frame **FM**. The implementation of the present invention where the antenna **17** is disposed at the top of the mobile communication device **1** shall be appreciated by those of ordinary skill in the art based on the above description, and thus will not be further described herein.

In this embodiment, the slash part **DA** of the back cover **BC** is made of a non-metal material, and other parts except for the slash part **DA** may be made of a metal or non-metal material, as described in the first embodiment. In other words, the slash part **DA** of the clearance area is made of a non-metal material to avoid influence on the performance of the antenna **17**, while other parts except for the slash part **DA** may be made of a metal or non-metal material. Moreover, the breaks may be filled with any insulating substance to increase the look and the feel of the device.

Please refer to FIG. **11A** and FIG. **11B** for a ninth embodiment of the present invention, and FIG. **11A** and FIG. **11B** are schematic front and back views of a finished product of the mobile communication device **1** of the present invention. Similarly, a front side of the finished product of the mobile communication device **1** is as shown in FIG. **11A**, in which a screen **DP**, an earpiece **EP** and the frame **FM** are

11

presented. Moreover, a back side of the finished product of the mobile communication device **1** is as shown in FIG. **11B**, in which the back cover **BC** and the frame **FM** are presented.

Similarly, in this embodiment, the antenna **17** is disposed at the bottom of the mobile communication device **1**, i.e., disposed at a place near to a microphone (not shown), so the first metal conductor **MC1** and the second metal conductor **MC2** are formed by two parts of the frame **FM** respectively. However, this embodiment differs from the eighth embodiment in that: two breaks of the frame **FM** formed by the first free end **FE1** and the second free end **FE2** of the first metal conductor **MC1** are respectively formed at a left portion and a right portion of the frame **FM**.

Please refer to FIG. **12A** and FIG. **12B** for a tenth embodiment of the present invention, and FIG. **12A** and FIG. **12B** are schematic front and back views of a finished product of the mobile communication device **1** of the present invention. Similarly, a front side of the finished product of the mobile communication device **1** is as shown in FIG. **12A**, in which a screen **DP**, an earpiece **EP** and the frame **FM** are presented. Moreover, a back side of the finished product of the mobile communication device **1** is as shown in FIG. **12B**, in which the back cover **BC** and the frame **FM** are presented.

Similarly, in this embodiment, the antenna **17** is disposed at the bottom of the mobile communication device **1**, i.e., disposed at a place near to a microphone (not shown), so the first metal conductor **MC1** and the second metal conductor **MC2** are formed by two parts of the frame **FM** respectively. However, this embodiment differs from the eighth embodiment and the ninth embodiment in that: two breaks of the frame **FM** formed by the first free end **FE1** and the second free end **FE2** of the first metal conductor **MC1** are respectively formed at a right portion and a lower portion of the frame **FM** (with reference to the front side of the mobile communication device **1**).

As described previously, in other embodiments, the antenna **17** may also be disposed at the top of the mobile communication device **1**, i.e., disposed at a place near to the earpiece, so that the first free end **FE1** and the second free end **FE2** of the first metal conductor **MC1** respectively form two breaks of the frame **FM** at a left portion and an upper portion of the frame **FM** respectively. The implementation of the present invention where the antenna **17** is disposed at the top of the mobile communication device **1** shall be appreciated by those of ordinary skill in the art based on the above description, and thus will not be further described herein.

Please refer to FIG. **13A** and FIG. **13B** for an eleventh embodiment of the present invention, and FIG. **13A** and FIG. **13B** are schematic front and back views of a finished product of the mobile communication device **1** of the present invention. Similarly, a front side of the finished product of the mobile communication device **1** is as shown in FIG. **13A**, in which a screen **DP**, an earpiece **EP** and the frame **FM** are presented. Moreover, a back side of the finished product of the mobile communication device **1** is as shown in FIG. **13B**, in which the back cover **BC** and the frame **FM** are presented.

Similarly, in this embodiment, the antenna **17** is disposed at the bottom of the mobile communication device **1**, i.e., disposed at a place near to a microphone (not shown), so the metal conductor **MC** is formed by a part of the frame **FM**. A break of the frame **FM** formed by the free end **FE** of the metal conductor **MC** is formed at a lower portion of the frame **FM**. However, in other embodiments, the antenna **17** may also be disposed at the top of the mobile communication device **1**, i.e., disposed at a place near to the earpiece,

12

so that the free end **FE** of the metal conductor **MC** forms a break of the frame **FM** at an upper portion of the frame **FM**. The implementation of the present invention where the antenna **17** is disposed at the top of the mobile communication device **1** shall be appreciated by those of ordinary skill in the art based on the above description, and thus will not be further described herein.

Please refer to FIG. **14A** and FIG. **14B** for a twelfth embodiment of the present invention, and FIG. **14A** and FIG. **14B** are schematic front and back views of a finished product of the mobile communication device **1** of the present invention. Similarly, a front side of the finished product of the mobile communication device **1** is as shown in FIG. **14A**, in which a screen **DP**, an earpiece **EP** and the frame **FM** are presented. Moreover, a back side of the finished product of the mobile communication device **1** is as shown in FIG. **14B**, in which the back cover **BC** and the frame **FM** are presented.

Similarly, in this embodiment, the antenna **17** is disposed at the bottom of the mobile communication device **1**, i.e., disposed at a place near to a microphone (not shown), so the metal conductor **MC** is formed by a part of the frame **FM**. A break of the frame **FM** formed by the free end **FE** of the metal conductor **MC** is formed at a right portion of the frame **FM** (with reference to the front side of the mobile communication device **1**). However, in other embodiments, the antenna **17** may also be disposed at the top of the mobile communication device **1**, i.e., disposed at a place near to the earpiece, so that the free end **FE** of the metal conductor **MC** forms a break of the frame **FM** at a left portion of the frame **FM**. The implementation of the present invention where the antenna **17** is disposed at the top of the mobile communication device **1** shall be appreciated by those of ordinary skill in the art based on the above description, and thus will not be further described herein.

Please refer to FIG. **15A** to FIG. **15D** for a thirteenth embodiment of the present invention, and FIG. **15A** to FIG. **15D** respectively illustrate four implementations where the frame **FM** has two breaks and the back cover **BC** is a metal conductor as a whole. In FIG. **15A** and FIG. **15B**, the two breaks extend from the frame **FM** and across an edge of the back cover **BC** to connect with each other so that the first metal conductor **MC1** is insulated from the back cover **BC**. In FIG. **15A**, a slot **ST** formed by the connection of the two breaks is formed on the back cover **BC**, and in FIG. **15B**, the slot **ST** formed by the connection of the two breaks is formed on the frame **FM**. Like the breaks, the slot **ST** may be filled with any insulating substance, thereby increasing the look and the feel of the device.

Moreover, in FIG. **15C** and FIG. **15D**, the two breaks extend from the frame **FM** and across a body of the back cover **BC** to connect with each other so as to divide the back cover **BC** into a first part **BC1** and a second part **BC2**, and the first part **BC1** makes contact with the first metal conductor **MC1** and the second part **BC2** is insulated from the first metal conductor **MC2**. In this case, the first part **BC1** of the back cover **BC** may be regarded as an extension of the first metal conductor **MC1** of the antenna **17** to serve as a radiating body. In FIG. **15C**, the slot **ST** formed by the connection of the two breaks has the same width as that of the breaks of the frame **FM**, while in FIG. **15D**, the slot **ST** formed by the connection of the two breaks has a width greater than that of the breaks of the frame **FM**.

As shall be readily appreciated by those of ordinary skill in the art, the shape of the slot **ST** formed by the connection of the two breaks is not limited to a straight strip in other embodiments. Therefore, a slot **ST** of any shape shall fall

13

within the scope of the present invention as long as the slot ST can insulate the first metal conductor MC1 from the back cover BC or divide the back cover BC into the first part BC1 and the second part BC2.

Please refer to FIG. 16A to FIG. 16D for a fourteenth embodiment of the present invention, and FIG. 16A to FIG. 16D respectively illustrate four implementations where the frame FM has a break and the back cover BC is a metal conductor as a whole. In FIG. 16A and FIG. 16B, the break extends from the frame FM and across an edge of the back cover BC to the endpoint E of the metal conductor MC so that the metal conductor MC is insulated from the back cover BC. In FIG. 16A, the slot ST formed by the extension of the break is formed on the back cover BC, and in FIG. 16B, the slot ST formed by the extension of the break is formed on the frame FM.

Moreover, in FIG. 16C and FIG. 16D, the break extends from the frame FM and across a body of the back cover BC to the endpoint E of the metal conductor MC so as to divide the back cover BC into a first part BC1 and a second part BC2, and the first part BC1 makes contact with the metal conductor MC and the second part BC2 is insulated from the metal conductor MC. In this case, the first part BC1 of the back cover BC may be regarded as an extension of the metal conductor MC of the antenna 17 to serve as a radiating body. In FIG. 16C, the slot ST formed by the extension of the break is formed on the back cover BC, and in FIG. 16D, the slot ST formed by the extension of the break is formed on the frame FM. Moreover, as shall also be appreciated by those of ordinary skill in the art, the width of the slot ST on the back cover BC may be greater than that of the break of the frame FM in FIG. 16C and FIG. 16D, i.e., similar to that of FIG. 15D.

As shall be readily appreciated by those of ordinary skill in the art, the shape of the slot ST formed by the extension of the break is not limited to a straight strip in other embodiments. Therefore, a slot ST of any shape shall fall within the scope of the present invention as long as the slot ST can insulate the metal conductor MC from the back cover BC or divide the back cover BC into the first part BC1 and the second part BC2.

According to the above descriptions, the present invention provides an antenna design with multiple feeding sources, which is capable of feeding multiple radio frequency (RF) signal sources to a same antenna physical structure to share an antenna clearance area and save the space occupied by the antenna within the wireless communication device, and is capable of utilizing a suitable physical structural design to achieve a high isolation among multiple RF signal resources and a high radiant efficiency. Moreover, the antenna architecture of the present invention may achieve the same radiant effect in combination with the metal frame, and may also add active components to optimize impedance matching and increase the real-time adjustability of the operation frequency band.

The above disclosure is related to the detailed technical contents and inventive features thereof. People skilled in this field may proceed with a variety of modifications and replacements based on the disclosures and suggestions of the invention as described without departing from the characteristics thereof. Nevertheless, although such modifications and replacements are not fully disclosed in the above descriptions, they have substantially been covered in the following claims as appended.

What is claimed is:

1. A wireless communication device, comprising:
 - a housing, having a frame;

14

- a circuit board, having a plurality of ground terminal, a first feeding point, and a second feeding point;
- a radio frequency (RF) module, being disposed on the circuit board and coupled to the first feeding point and the second feeding point; and

- an antenna, for transmitting and receiving an RF signal, the antenna comprising:

- a first metal conductor, coupling to the first feeding point and extending toward a lateral direction; and

- a second metal conductor, coupling to the second feeding point and extending toward a longitudinal direction;

wherein the first metal conductor and the second metal conductor are formed by two parts of the frame respectively, and the frame has at least one cut point, and each of the at least one cut point is formed in one of an upper portion, a lower portion, a left portion, and a right portion of the frame;

wherein the first metal conductor extends at least toward the lateral direction of the frame, the first metal conductor has a first free end and a second free end, the first metal conductor is extendedly coupled from a first extension point between the first free end and the second free end to the first feeding point, and the first metal conductor is coupled from a second extension point between the first extension point and the second free end to a first ground terminal via a passive component.

2. The wireless communication device of claim 1, further comprising:

- an extension metal piece, coupling the first metal conductor to the second metal conductor to extend at least one of a plurality of resonant paths of the antenna.

3. The wireless communication device of claim 2, wherein the first metal conductor and the second metal conductor are formed on a surface of a carrier plate in the form of a plane metal layer, and the extension metal piece is formed on an opposite surface of the carrier plate.

4. The wireless communication device of claim 1, wherein the housing further has a back cover to define a receiving space, and the circuit board is disposed in the receiving space and defines a clearance area from the housing, and the antenna is disposed in the clearance area.

5. The wireless communication device of claim 1, wherein the second metal conductor extends at least toward the longitudinal direction of the frame, the second metal conductor has a first endpoint adjacent to the second free end of the first metal conductor and a second endpoint away from the second free end of the first metal conductor, the second metal conductor is extendedly coupled from the first endpoint to a second ground terminal and from the second endpoint to a third ground terminal respectively, and the second metal conductor is coupled from between the first endpoint and the second endpoint to the second feeding point.

6. The wireless communication device of claim 2, wherein the extension metal piece coupled between the second free end of the first metal conductor and the first endpoint of the second metal conductor, and the plurality of resonant paths includes a low frequency resonant path, a first middle frequency resonant path, a second middle frequency resonant path, and a high frequency resonant path;

wherein the low frequency resonant path starts from the first feeding point to the first free end of the first metal conductor, the first middle frequency resonant path starts from the first feeding point via the extension metal piece to the second ground terminal to which the first endpoint of the second metal conductor is extend-

15

edly coupled, the second middle frequency resonant path starts from the first feeding point to the first free end of the first metal conductor, and the high frequency resonant path starts from the second feeding point to the second endpoint of the second metal conductor, to the second ground terminal to which the first endpoint is extendedly coupled, and via the extension metal piece to the first ground terminal to which the second extension point of the first metal conductor is extendedly coupled.

7. The wireless communication device of claim 6, wherein the low frequency resonant path is equivalent to a quarter of a wavelength of a low frequency operation frequency, the first middle frequency resonant path is equivalent to a half of a wavelength of a first middle frequency operation frequency, the second middle frequency resonant path is equivalent to three quarters of a wavelength of a second middle frequency operation frequency, and the high frequency resonant path is equivalent to a half of a wavelength of a high frequency operation frequency.

8. The wireless communication device of claim 6, further comprising:

a switch, being configured to selectively couple the extension metal piece to a fourth ground terminal via another passive component to adjust a first middle frequency operation frequency and a high frequency operation frequency.

9. The wireless communication device of claim 5, wherein the first extension point and the second extension point are overlapped on the first metal conductor.

10. The wireless communication device of claim 5, further comprising:

a single-pole-four-throw (SP4T) switch, being configured to selectively couple an adjustment point between the first extension point of the first metal conductor and the first free end to a fifth ground terminal via another passive component to adjust the low frequency operation frequency and the second middle frequency operation frequency.

11. The wireless communication device of claim 5, wherein the first free end and the second free end of the first metal conductor form two cut points of the frame respectively.

12. The wireless communication device of claim 11, wherein the second metal conductor further extends toward the lateral direction and the longitudinal direction of the frame, and the two cut points are formed in one of the upper portion and the lower portion of the frame.

13. The wireless communication device of claim 11, wherein the first metal conductor further extends toward the lateral direction and the longitudinal direction of the frame, and the two cut points are formed in the left portion and the right portion of the frame respectively.

14. The wireless communication device of claim 11, wherein the back cover is of a metal material, and one cut point extends from one side of the frame and across the whole back cover to connect with another cut point so that the first metal conductor is insulated from the back cover.

15. The wireless communication device of claim 11, wherein the back cover is of a metal material, and the two cut points extend from the frame and across a body of the back cover to connect with each other so as to divide the back cover into a first part and a second part, wherein the first part makes contact with the first metal conductor and the second part is insulated from the first metal conductor.

16. The wireless communication device of claim 11, wherein the first metal conductor further extends toward the

16

lateral direction and the longitudinal direction of the frame, and one of the two cut points is formed in one of the left portion and the right portion of the frame, and the other of the two cut points is formed in one of the upper portion and the lower portion of the frame.

17. A wireless communication device, comprising:

a circuit board, having a plurality of ground terminal, a first feeding point, and a second feeding point;

a radio frequency (RF) module, being disposed on the circuit board and coupled to the first feeding point and the second feeding point; and

an antenna, for transmitting and receiving an RF signal, the antenna comprising:

a first metal conductor, coupling to the first feeding point and extending toward a lateral direction;

a second metal conductor, coupling to the second feeding point and extending toward a longitudinal direction; and

an extension metal piece, coupling the first metal conductor to the second metal conductor; and

a housing, having a frame and a back cover to define a receiving space;

wherein the circuit board is disposed in the receiving space;

wherein the first metal conductor and the second metal conductor are formed by two parts of the frame respectively; and

the first metal conductor does not overlap the second metal conductor;

wherein the first metal conductor extends at least toward the lateral direction of the frame, the first metal conductor has a first free end and a second free end, the first metal conductor is extendedly coupled from a first extension point between the first free end and the second free end to the first feeding point, and the first metal conductor is coupled from a second extension point between the first extension point and the second free end to a first ground terminal via a passive component.

18. The wireless communication device of claim 17, wherein a first free end and a second free end of the first metal conductor form two cut points of the frame respectively, and the two cut points are filled with insulating substance.

19. The wireless communication device of claim 17, wherein the second metal conductor further extends toward the lateral direction and the longitudinal direction of the frame, and the two cut points are formed in one of an upper portion and a lower portion of the frame.

20. The wireless communication device of claim 17, wherein the first metal conductor further extends toward the lateral direction and the longitudinal direction of the frame, and the two cut points are formed in a left portion and a right portion of the frame respectively.

21. The wireless communication device of claim 17, wherein the first metal conductor further extends toward the lateral direction and the longitudinal direction of the frame, and one of the two cut points is formed in one of a left portion and a right portion of the frame, and the other of the two cut points is formed in one of an upper portion and a lower portion of the frame.

22. The wireless communication device of claim 17, wherein:

the second metal conductor extends at least toward the longitudinal direction of the frame, the second metal conductor has a first endpoint adjacent to the second free end of the first metal conductor and a second

17

endpoint away from the second free end of the first metal conductor, the second metal conductor is extendedly coupled from the first endpoint to a second ground terminal and from the second endpoint to a third ground terminal respectively, and the second metal conductor is coupled from between the first endpoint and the second endpoint to the second feeding point;

the extension metal piece coupled between the second free end of the first metal conductor and the first endpoint of the second metal conductor to extend at least one of a plurality of resonant paths of the antenna, and the plurality of resonant paths includes a low frequency resonant path, a first middle frequency resonant path, a second middle frequency resonant path, and a high frequency resonant path; and

the low frequency resonant path starts from the first feeding point to the first free end of the first metal conductor, the first middle frequency resonant path starts from the first feeding point via the extension metal piece to the second ground terminal to which the first endpoint of the second metal conductor is extend-

18

edly coupled, the second middle frequency resonant path starts from the first feeding point to the first free end of the first metal conductor, and the high frequency resonant path starts from the second feeding point to the second endpoint of the second metal conductor, to the second ground terminal to which the first endpoint is extendedly coupled, and via the extension metal piece to the first ground terminal to which the second extension point of the first metal conductor is extendedly coupled.

23. The wireless communication device of claim 17, wherein the first metal conductor and the second metal conductor are disposed on a surface different from a surface which the extension metal piece is disposed on.

24. The wireless communication device of claim 17, wherein the first metal conductor is coupled to the first feeding point via a first connector, and the second metal conductor is coupled to the second feeding point via a second connector.

* * * * *