



US005995797A

# United States Patent [19]

[11] Patent Number: **5,995,797**

Shigeta et al.

[45] Date of Patent: **Nov. 30, 1999**

[54] **IMAGE FORMING APPARATUS WHICH CONVEYS UNFIXED TONER IMAGES TO A FIXING DEVICE IN AN UNDISTURBED AND STABLE MANNER SO THAT IMAGES MAY BE FORMED ON BOTH SIDES OF A SHEET**

5,422,710 6/1995 Shirasaka et al. .... 399/322  
5,752,130 5/1998 Tanaka et al. .... 399/308 X  
5,826,143 10/1998 Haneda et al. .... 399/309 X

[75] Inventors: **Kunio Shigeta; Yotaro Sato; Hisayoshi Nagase; Satoshi Haneda**, all of Hachioji; **Toshihide Miura**, Koganei, all of Japan

*Primary Examiner*—Arthur T. Grimley  
*Assistant Examiner*—Hoan Tran  
*Attorney, Agent, or Firm*—Frishauf, Holtz, Goodman, Langer & Chick, P.C.

[73] Assignee: **Konica Corporation**, Tokyo, Japan

### [57] ABSTRACT

[21] Appl. No.: **09/081,513**

In an image forming apparatus provided with a first image carrying member; a belt-shaped second image carrying member onto which a toner image is transferred from the first image carrying member; a pair of rotatable fixing members forming a nip region for fixing the toner images transferred on the both sides of the sheet; a conveying device for guiding the sheet separated from an end of the belt-shaped second image carrying member to the pair of rotatable fixing members, when the sheet is nipped and conveyed through the nip region of the pair of rotatable fixing members, the belt-shaped second image carrying member and the pair of rotatable fixing members are arranged such that the sheet is conveyed so as to form a loop protruding from a line connecting the entrance of the nip region and the end of the belt-shaped second image carrying member.

[22] Filed: **May 20, 1998**

### [30] Foreign Application Priority Data

May 26, 1997 [JP] Japan ..... 9-135220  
Jun. 23, 1997 [JP] Japan ..... 9-165754  
Aug. 28, 1997 [JP] Japan ..... 9-232695

[51] Int. Cl.<sup>6</sup> ..... **G03G 15/20**

[52] U.S. Cl. .... **399/322; 399/397; 399/400**

[58] Field of Search ..... 399/322, 320, 399/297, 299, 302, 303, 308, 309, 400, 401, 122, 306, 307, 397; 430/126

### [56] References Cited

#### U.S. PATENT DOCUMENTS

4,941,021 7/1990 Uchida et al. .... 399/322

**32 Claims, 15 Drawing Sheets**




FIG. 1




FIG. 2




FIG. 3 (A)




FIG. 3 (B)




FIG. 3 (C)




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13






FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21





FIG. 22



**IMAGE FORMING APPARATUS WHICH  
CONVEYS UNFIXED TONER IMAGES TO A  
FIXING DEVICE IN AN UNDISTURBED AND  
STABLE MANNER SO THAT IMAGES MAY  
BE FORMED ON BOTH SIDES OF A SHEET**

**BACKGROUND OF THE INVENTION**

The present invention relates to an electrophotographic type image forming apparatus such as a copier, printer, facsimile device, or similar device, in which a charging means, an image writing means, and developing means are arranged around an image carrier, and a toner image formed on the image carrier is transferred onto both surfaces of transfer material and fixed.

Conventionally, in two-sided image formation, an image forming method is used in which a one-side image formed on the image carrier is transferred onto a transfer material and fixed; the transfer sheet is temporarily accommodated in a two-sided reversal sheet feeding device; the transfer material is fed from the two-sided reversal sheet feeding device in timed relationship with the image formed again on the image carrier; and the other side image is transferred on the transfer material and fixed.

As described above, in this two-sided image forming apparatus, conveyance of the transfer material such as feeding to the two-sided reversal sheet feeding device, and two times passage through the fixing device, is carried out. Accordingly, reliability of the transfer material conveyance is low, and jamming of the transfer material or shrinkle is sometimes caused. In addition, as is commonly known, conveyance length of the transfer material becomes larger. Therefore, there was a problem that it takes much time for copying.

With respect to this, a method in which fixing is carried out only once after toner images have been formed on two sides of the transfer material, is proposed in Japanese Patent Publication Nos. 37538/1974, 28740/1979, and Japanese Patent Publication Open to Public Inspection Nos. 44457/1989, and 214576/1992.

The inventors of the present invention are investigating an image forming apparatus and an image forming method, in which a plurality of sets of toner image forming means composed of a charging means, image writing means, developing means, etc., are arranged around a photoreceptor drum (the first image carrier means); after superimposed color toner images formed on the photoreceptor drum are temporarily and collectively transferred onto a belt-like toner image receiving body (the second image carrier means) by a first transfer means, superimposed color toner images are formed again on the photoreceptor drum; a transfer material fed in timed relationship with the toner image on the photoreceptor drum and the toner image on the toner image receiving body, is electrically charged by a transfer material charging means, and is attracted to the toner image receiving body; the toner image on the photoreceptor drum is transferred by the first transfer means as an obverse side image, and the toner image on the toner image receiving body is transferred by the second transfer means as a reverse side image, respectively onto two sides of the transfer material conveyed on the toner image receiving body; after that, the transfer material is separated from the toner image receiving body by discharging of a transfer material separation means; the toner images on the transfer material are fixed by a fixing device (fixing means); and a two-sided color image is formed.

As described above, in the above-mentioned image forming apparatus, the number of passage of the transfer sheet on

which a toner image is transferred on both sides through the fixing device is allowed to be once. Accordingly, reliability of the transfer material conveyance is high, and conveyance path of the transfer material is shortened, increasing processing speed of image forming.

However, in the above-described image forming apparatus, because the transfer material having unfixed toner images on two sides is conveyed to the fixing device, the toner image receiving body and the fixing device are closely arranged to each other, and the transfer material separated from the toner image receiving body is directly sent to the fixing device. However, when the toner image receiving body is arranged closely to the fixing device, problems occur in which the toner image receiving body is deformed, the toner image transferred onto the toner image receiving body is slightly fused and is hardly transferred, or toner fixedly adheres onto the toner image receiving body. For this reason, the toner image receiving body and the fixing device are arranged with some distance, a conveying section having a spur member (spur) is provided between them, and the transfer material is conveyed from the toner image receiving body to the fixing device by the spur. However, problems occur in which, during transfer material conveyance by the spur, the transfer material is pressed to the direction of the spur, and spur trace occurs on the toner image on the transfer material or the spur is stained by toner, thereby, a toner stain occurs on the transfer material conveyed due to the spur.

The first object of the present invention is to solve the above-described problems, and to provide an image forming apparatus in which generation of a spur trace on a toner image on the transfer material is prevented and toner stain on the transfer material due to stain by spur is prevented.

Further, there is also a problem in which, after the toner images have been transferred onto both sides of the transfer material conveyed by a toner image receiving body, in the case where the transfer material is separated from a toner image receiving body, and the toner images on the transfer material are fixed while the transfer material is being nipped and conveyed by the fixing device, the conveyance speed of the transfer material by the fixing device and that of the transfer material by the toner image receiving body are set to the same speed. However, even if aforesaid conveyance speeds are set to be the same, the transfer material is pulled by a slight speed difference caused between the two conveyance speeds, and unfixed toner images transferred onto two sides of the transfer material are partially disturbed.

The present invention has solved the above problems, and as the result, the second object of the present invention is to provide an image forming apparatus in which, even if a change of speed is generated in the conveyance speed of the transfer material by the second image carrier means or in the conveyance speed of the transfer material by the fixing means, it can be prevented that the transfer material is strongly pulled, and thereby the toner image on the obverse and the reverse side thereof can be transferred and fixed without deteriorating the image quality.

**SUMMARY OF THE INVENTION**

The above-described first object is attained by the following image forming apparatus.

- An apparatus for forming an image, comprising:
- a first image carrying member;
  - toner image forming means for forming toner images on the first image carrying member;
  - a belt-shaped second image carrying member onto which the toner image is transferred from the first image carrying member;

a first transfer member for transferring the toner image from the first image carrying member to a first side of a sheet;

a second transfer member for transferring the toner image from the second image carrying member to a second side of the sheet;

fixing means for fixing the toner images transferred on the both sides of the sheet, the fixing means forming a nip region between a pair of rotatable fixing members and fixing the toner images onto the sheet by nipping and conveying the sheet through the nip region;

conveying means, provided between the belt-shaped second image carrying member and the fixing means, for guiding the sheet separated from an end of the belt-shaped second image carrying member to the fixing means, wherein when the sheet is nipped and conveyed through the nip region of the fixing means, the belt-shaped second image carrying member and the fixing means are arranged such that the sheet is conveyed so as to form a loop protruding from an extended plane of a sheet conveying plane of the belt-shaped second image carrying member toward the opposite side of the conveying means.

Further, the above-described first object can be attained by the following image forming apparatuses corresponding to the preferable embodiment.

An image forming apparatus having a first image carrier means on which a toner image formed by a toner image forming means is carried; a second image carrier means onto which the toner image carried by the first image carrier means is transferred, and on the surface e of which the transferred toner image is carried; a first transfer means by which the toner image carried by the first image carrier means is transferred onto an obverse side of the transfer material; a second transfer means by which the toner image carried on the second image carrier means is transferred onto a reverse side of the transfer material; and a fixing means in which the transfer material is held and conveyed by a rotating set of fixing members, and by which the toner images transferred onto both sides of the transfer material are fixed, wherein the transfer material is conveyed by the second image carrier means, and after the transfer material is separated from the second image carrier means, the toner images are fixed by the fixing means, the image forming apparatus is characterized in that a conveyance section having a spur to convey the transfer material is provided on the reverse surface side of the transfer material lower than the extended surface of the transfer material conveyance surface of the second image carrier means, between the second image carrier means and the fixing means, and the transfer material is sent to the fixing means through the conveyance section; the transfer material is separated from the belt-like second image carrier means at the end portion on the fixing means side of the second image carrier means, and is moved to the fixing means along the spur of the conveyance section; the transfer material is separated from the spur when the leading edge of the transfer material is nipped by a nip portion formed of a pair of the fixing members of the fixing means; and the transfer material is conveyed through the fixing means under the condition that it is separated from the spur.

An image forming apparatus having a first image carrier means on which a toner image formed by a toner image forming means is carried; a second image carrier means onto which the toner image carried by the first image carrier means is transferred, and on the surface e of which the transferred toner image is carried; a first transfer means by

which the toner image carried by the first image carrier means is transferred onto the second image carrier means or an obverse side of the transfer material conveyed by the second image carrier means; a second transfer means by which the toner image carried on the second image carrier means is transferred onto a reverse side of the transfer material; and a fixing means for fixing toner images transferred onto both sides of the transfer material, the image forming apparatus is characterized in that a conveyance section having a plurality of sets of spur members to convey the transfer material is provided between the second image carrier means and the fixing means, and the transfer material is sent to the fixing means through the conveyance section; the transfer material conveyance speed by the fixing means is set to be lower than the transfer material conveyance speed by the second image carrier means; a curvature section which is formed of roller members to stretch the second image carrier means, and by which the transfer material is separated from the second image carrier means, is provided at an end portion on the fixing means side of the second image carrier means; all of the plurality of sets of the spur members are arranged on the reverse surface side of the transfer material, lower than the surface including an entrance of the nip portion of the fixing means and the separation position of the second image carrier means at which the curvature portion of the second image carrier means begins to have the curvature; and the separation position is arranged to be located on the reverse surface side of the transfer material, lower than the tangent at the entrance of the nip portion of the fixing means.

The above-described second object is attained by an image forming apparatus having an image forming body; a means for forming the toner image on the image forming body; an intermediate transfer body which can transfer the toner image on the image forming body and serves as a transfer material conveyance means; a first transfer means for transferring the toner image on the image forming body onto the intermediate transfer body or the obverse side of the transfer material; a second transfer means for transferring the toner image on the intermediate transfer body onto the reverse side of the transfer material; and a fixing means in which the transfer material is nipped and conveyed by rotating paired fixing members and by which the toner image on the transfer material is fixed, the image forming apparatus is characterized in that the conveyance speed of the transfer material by the fixing means is set to be lower than that of the transfer material by the intermediate transfer body.

The above object is attained by an image forming apparatus having a first image carrier means on which a toner image formed by a toner image forming means is carried; a second image carrier means onto which the toner image carried by the first image carrier means is transferred, and on the surface of which the transferred toner image is carried; a first transfer means by which the toner image carried by the first image carrier means is transferred onto an obverse side of the transfer material; a second transfer means by which the toner image carried on the second image carrier means is transferred onto a reverse side of the transfer material, and an image forming apparatus in which the transfer material is conveyed by the second image carrier means and after the transfer material is separated from the second image carrier means, the toner images transferred onto both sides of the transfer material are fixed by the fixing means, the image forming apparatus is characterized in that a conveyance section is provided between the second image carrier means and the fixing means, and the transfer material is sent to the

fixing means through the conveyance section; and a spur rotatable by the transfer material and a cleaning member which comes into contact with the leading edge portion of the spur and cleans the spur, are provided in the conveyance section.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a structural sectional view of a color image forming apparatus showing an example of an image forming apparatus according to the present invention.

FIG. 2 is a side sectional view of the first image carrier means in FIG. 1.

FIGS. 3(A) to 3(C) are views showing a toner image forming condition on both sides of a transfer material by the image forming apparatus according to the present invention.

FIG. 4 is a structural sectional view of the image forming apparatus.

FIG. 5 is a view showing a conveyance section.

FIG. 6 is a perspective view of a spur provided in the conveyance section.

FIG. 7 is a view showing the first example of the roller structure used in a fixing means.

FIG. 8 is a view showing the first example of a method for conveying the transfer material by the roller structure in FIG. 7.

FIG. 9 is a view showing the second example of a method for conveying the transfer material by the roller structure in FIG. 7.

FIG. 10 is a view showing the second example of the roller structure used in the fixing means and a transfer material conveyance method using it.

FIG. 11 is a view showing the third example of the roller structure used in the fixing means and a transfer material conveyance method using it.

FIG. 12 is a view showing the conveyance section.

FIG. 13 is a perspective view of a spur member provided in the conveyance section in FIG. 12.

FIG. 14 is a view showing a positional relationship of a nip portion, a curvature portion of the second image carrier means, and the spur member.

FIG. 15 is a view showing a looping shape of the transfer material formed by the second image carrier means and the fixing means.

FIG. 16 is a view showing the roller structure used in the fixing means and the second example of the shape of its nip portion.

FIGS. 17 and 18 are illustrations showing the posture of conveyance of the transfer material with respect to the fixing means.

FIG. 19 is a view showing the first example of a fitting method of a cleaning member to the spur.

FIG. 20 is a perspective view showing a cleaning member.

FIG. 21 is a view showing the second example of a fitting method of the cleaning member to the spur.

FIG. 22 is a view showing the third example of a fitting method of the cleaning member to the spur.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The example of the present invention will be described below. The description of the present column does not limit the technological scope of claims or the meaning of terms,

but the following conclusive description shows the best mode of the present invention and does not limit the meaning of terms and technological scope of the present invention. In this connection, in the following description of the example, the surface of one side of the transfer material opposing to the first image carrier means in a transfer area is referred to as the obverse side, the surface of the other side of the transfer material, that is, the surface of the other side of the transfer material opposing to the second image carrier means is referred to as the reverse side, an image transferred onto the obverse side of the transfer material is referred to as an obverse side image, and an image transferred onto the surface of the other side of the transfer material is referred to as a reverse side image.

Referring to FIG. 1 to FIG. 3, an image formation process and each mechanism of an example of an image forming apparatus according to the present invention will be described below. FIG. 1 is a structural sectional view of a color image forming apparatus showing an example of an image forming apparatus according to the present invention. FIG. 2 is a side sectional view of the first image carrier means in FIG. 1. FIGS. 3(A) through (C) are views showing a toner image forming condition when images are formed on both sides of transfer material and feeding of the transfer material. FIG. 3(A) is a view showing the toner image forming condition when the toner image formed on the first image carrier means is transferred onto the second image carrier means for forming the reverse side image. FIG. 3(B) is a view showing toner image forming condition when the obverse side image is formed on the first image carrier means in timed relationship with the reverse side image on the second image carrier means and feeding of the transfer material. FIG. 3(C) is a view showing the two-sided image formation onto the transfer material which is conveyed by the second image carrier means.

In FIG. 1, numeral 10 is a photoreceptor drum which is the first image carrier means, numeral 11 is a scorotron charger which is a charging means for each color, numeral 12 is an exposure optical system which is an image writing means for each color, numeral 13 is a developing device which is a developing means for each color, numeral 14a is a toner image receiving body which is the second image carrier means, numeral 14c is a transfer device which is the first transfer means, numeral 14g is a reverse side transfer device, numeral 150 is a paper charger which is a transfer material charging means, numeral 14h is a paper separation AC discharger, numeral 160 is a conveyance section, and numeral 17 is a fixing device which is a fixing means.

The photoreceptor drum 10 serving as the first image carrier means is structured, for example, such that a transparent conductive layer, a photoreceptor layer such as an a-Si layer or an organic photoreceptor layer, or the like, are formed on the outer periphery of a cylindrical base body, formed of a transparent member such as optical glass or transparent acrylic resin, and is rotated clockwise as shown by an arrow in FIG. 1 under the condition that the conductive layer is electrically grounded.

As shown in FIG. 2, the photoreceptor drum 10 uses a drum shaft 30, fixed to the apparatus main body by bearings B1 and B2, inserted into flange members 10a and 10b of both end portions by which the photoreceptor drum 10 is fixed, as a bearing and is rotatably supported thereby, and is rotated at a constant speed in a predetermined direction when a gear G integrally provided onto the flange member 10b is engaged with a driving gear, not shown, provided on the apparatus main body side and driven.

In the present example, a scorotron charger 11 as a charging means for each color, an exposure optical system

**12** as an image writing means for each color, and a developing device **13** as a developing means for each color are integrated into one set, and **4** sets are provided for color image formation processes of yellow (Y), magenta (M), cyan (C) and black (K), and are arranged in the order of Y, M, C and K with respect to the rotation direction of the photoreceptor drum **10** as shown by an arrow in FIG. 1.

The scorotron charger **11** as the charging means for each color has a control grid which has a predetermined potential voltage, and a discharging electrode **11a** composed of, for example, a saw-toothed electrode, and is mounted facing the photoreceptor layer of the photoreceptor drum **10**. The scorotron charger **11** conducts a charging action (in the present example, negative charging) by corona discharging with the same polarity of as toner, so that uniform potential voltage is applied on the photoreceptor drum **10**. As a discharging electrode **11a**, a wire electrode or a needle-shaped electrode may also be used other than the above-described electrode.

An exposure optical system **12** as an image writing means for each color is arranged inside the photoreceptor drum **10** such that an exposure position on the photoreceptor drum **10** is on the downstream side in the rotating direction of the photoreceptor drum **10** with respect to the scorotron charger **11** for each color. As shown in FIG. 2, each exposure optical system **12** is an exposure unit composed of a linear exposure element **12a** in which a plurality of LEDs (light emitting diode) as an light emitting element for image exposure light, arranged in the primary scanning direction in parallel with the drum shaft **30**, are aligned array-like, a light converging light transmission body (trade name: Selfoc lens array) **12b** as an image formation element, and a lens holder **12c**, and is attached to a holding member **20**. A transfer simultaneous exposure device **12d** and a uniform exposure device **12e** are attached to the holding member **20** other than the exposure optical system **12** for each color, and these are integrally accommodated inside the light transmissive base body of the photoreceptor drum **10**. The exposure optical system **12** for each color image-exposes the photoreceptor layer of the photoreceptor drum **10** from the rear side according to image data for each color, which has been read by an image reading apparatus separately provided from the apparatus, and stored in a memory, and an electrostatic latent image is formed on the photoreceptor drum **10**. As the exposure element **12a**, an exposure element other than the above element may be used in which a plurality of light emitting elements such as an FL (fluorescent substance light emission), EL (electroluminescence), PL (plasma discharge), etc., are aligned array-like. In this connection, the wavelength of light emission of the image exposure light emitting element is usually used within the of 780–900 nm, within which permeability for Y, M, C toners is high, however, in the present example, because the image exposure is conducted from the rear side, the shorter wavelength of 400–780 nm, which has rather insufficient permeability for color toner, may also be allowable. Incidentally, in FIG. 2, symbol WA is a lead wire from light emitting elements (LEDs) of an image exposure means.

A developing device **13** as a developing means for each color is respectively provided with a developing sleeve **131** which has a predetermined gap with respect to the peripheral surface of the photoreceptor drum **10** and is rotated in the same direction as the rotating direction of the photoreceptor drum **10**, and which is formed of, for example, cylindrical non-magnetic stainless steel or aluminum material with 0.5–1 mm thickness and 15–25 mm outer diameter, and a developing casing **138**, in which one-component or two-component developer of yellow (Y), magenta (M), cyan (C)

and black (K) is respectively accommodated. Each developing device **13** is kept to be in non-contact with the photoreceptor drum **10** with a predetermined interval of, for example, 100–500  $\mu\text{m}$  by a roller, not shown in the drawing, and by applying developing bias voltage in which DC voltage and AC voltage are superimposed on each other, onto the developing sleeve **131**, non-contact reversal development is conducted and a toner image is formed on the photoreceptor drum **10**.

A toner image receiving body **14a** as the second image carrier means is an endless belt with  $10^8$ – $10^{15}$   $\Omega\cdot\text{cm}$  volume resistivity, and is a seamless belt of 2 layer construction in which, for example, 5–50  $\mu\text{m}$  thick fluorine coating, preferably as a toner filming prevention layer, is conducted outside the 0.1–1.0 mm semi-conductive film base body, in which conductive material is dispersed in engineering plastic such as modified polyimide, thermohardening polyimide, ethylene-tetrafluoro ethylene copolymer, polyvinylidene fluoride, nylon alloy, etc. As a belt base body, other than the above base body, 0.1–1.0 mm thick semi-conductive rubber belt, in which conductive material is dispersed in silicon rubber or urethane rubber, may also be used. The toner image receiving body **14a** is inscribed with a driving roller **14d**, a driven roller **14e** and a tension roller **14i** and stretched around them, and is rotated counterclockwise as shown by an arrow in FIG. 1. The driving roller **14d** is rotated by a driving motor, not shown in the drawing, thereby the toner image receiving body **14a** is driven for rotation. When the toner image receiving body **14a** is rotated, the driven roller **14e** and the tension roller **14i** are rotated thereby. The slack of the belt of the toner image receiving body **14a** during rotation is strained by the tension roller **14i** which is supported movable due to elastic force by a spring not illustrated.

A transfer device **14c** as the first transfer means is a corona discharger, provided facing the photoreceptor drum **10** with the toner image receiving body **14a** between them, and a transfer area **14b** is formed between the toner image receiving body **14a** and the photoreceptor drum **10**. DC voltage with the reverse polarity to that of toner (positive polarity in the present example) is applied onto the transfer device **14c**, and a transfer electric field is formed in the transfer area **14b**, thereby, the toner image on the photoreceptor drum **10** is transferred onto the toner image receiving body **14a** or the obverse side of recording paper P, which is the transfer material.

A reverse side transfer device **14g** as the second transfer means, constituted preferably of a corona discharger, is provided facing the electrically grounded conductive driving roller **14d** with the toner image receiving body **14a** between them, and DC voltage with the reverse polarity to that of toner (positive polarity in the present example) is applied onto the reverse side transfer device **14g**, thereby, the toner image on the toner image receiving body **14a** is transferred onto the reverse side of the transfer material.

A paper charger **150** as a transfer material charging means is provided facing the electrically grounded driven roller **14e** with the toner image receiving body **14a** between them, is a conductive brush capable of coming into contact with and not capable of being released from the contact with the toner image receiving body **14a** by using a support shaft **152** as a rotation fulcrum, thereby it charges recording paper P fed to toner image receiving body **14a** so as to be attracted to the toner image receiving body **14a**. As a transfer material charging means, in addition to the above, conductive rollers capable of coming into contact with and not capable of being released from the contact with the toner image receiving

body **14a**, in which DC voltage having the same polarity is impressed, a semi-conductor film member, a blade member or a corona discharger which does not contact with toner image receiving body **14a** can be used.

A paper separation AC discharger **14h**, preferably constituted of a corona discharger, as a transfer material separation means is provided at need, being placed by the side of the reverse side transfer device **14g**, facing the electrically grounded conductive driving roller **14d** with the toner image receiving body **14a** between them, at the end portion on the fixing device **17** side of the toner image receiving body **14a**, and AC voltage on which DC voltage with the same polarity as that of toner or the reverse polarity to that of toner is superimposed, is applied onto the paper separation AC discharger **14h**, so that the recording paper P conveyed by the toner image receiving body **14a** is discharged and is separated from toner image receiving body **14a**.

A conveyance section **160** is provided between the toner image receiving body **14a** and the fixing device **17**, and spurs **162** are provided on the upper surface of the conveyance section **160**. The spur **162** takes up the end of recording paper Prepared from toner image receiving body **14a** due to the curvature of a curvature section provided at the end of fixing device **17** of toner image receiving body **14a** and discharging effect by paper separation AC discharger **14h** provided as necessary, and conveys the recording paper P guiding on the reverse side thereof with the toner image on its reverse side to the fixing device **17** while preventing the disturbance of the reverse side toner image.

The fixing device **17** as the fixing means is a heat roller fixing device composed of 2 rollers **17a** and **17b** having a heater inside respectively. Aforesaid fixing device **17** provides heat and pressure due to conveying the recording material having toner images on both sides after being separated from toner image receiving body **14a** by sandwiching it between rollers **17a** and **17b** and fixes the toner image on the transfer material by applying heat and pressure onto the toner image between the fixing roller **17a** and the pressure contact roller **17b**.

Next, an image forming process will be described.

When image recording starts, the photoreceptor drum **10** is rotated clockwise as shown by an arrow in FIG. 1 by the start of a photoreceptor driving motor, not shown in the drawings, and simultaneously, application of potential voltage is started onto the photoreceptor drum **10** by the charging operation of the scorotron charger **11** of yellow (Y).

After the potential voltage has been applied onto the photoreceptor drum **10**, image writing by an electric signal corresponding to the first color signal, that is, Y image data is started by the exposure optical system **12** of Y, and thereby, an electrostatic latent image corresponding to a Y image of the document image is formed on the surface of the photoreceptor drum **10**.

The above-described Y latent image formed on photoreceptor drum **10** is non-contact reversal—developed and a yellow (Y) toner image is formed on photoreceptor drum **10**.

Next, the potential voltage is applied onto the photoreceptor drum **10** from above the Y toner image by the charging operation of a magenta (M) scorotron charger **11**, image writing by the electric signal corresponding to the second color signal, that is, M image data is conducted by an exposure optical system **12** of M, and a magenta (M) toner image is superimposed on the above-described yellow (Y) toner image by the non-contact reversal development by the developing device **13** of M and is formed.

By the same process, a cyan (C) toner image corresponding to the third color signal is further superimposed on the

previous toner images and formed by the scorotron charger **11** of cyan (C), exposure optical system **12** of C and developing device **13** of C, and a black (K) toner image corresponding to the fourth color signal is successively superimposed on the cyan toner image and formed by the scorotron charger **11** of black (K), exposure optical system **12** of K, and developing device **13** of K. The super imposed color toner image of 4 colors of yellow (Y), magenta (M), cyan (C), and black (K) is formed on the peripheral surface of the photoreceptor drum **10** during a single rotation of the photoreceptor drum **10** (toner image forming means).

Image writing onto the photoreceptor layer on the photoreceptor drum **10** by these Y, M, C, K exposure optical system **12** is conducted from the inside of the drum through the light transmissive base body. Accordingly, the image writing corresponding to the second, third and fourth color signals is conducted entirely without being influenced by the previously formed toner images, and thereby, the electrostatic latent image with the same quality as that of an image corresponding to the first color signal, can be formed.

The superimposed color toner images as the reverse side image formed on the photoreceptor drum **10**, serving as the first image carrier means, by the above-described image forming process, are collectively transferred onto the toner image receiving body **14a** as the second image carrier means, in the transfer area **14b**, by the transfer device **14c**, serving as the first transfer means (FIG. 3 (A)). At that time, uniform exposure may be conducted by the transfer simultaneous exposure device **12d** provided inside the photoreceptor drum **10** so that good transfer can be conducted.

Toner remaining on the peripheral surface of the photoreceptor drum **10** after transfer, is discharged by a photoreceptor drum AC discharger **16**, and after that, moved to a cleaning device **19** as a first image carrier means cleaning means, cleaned by a cleaning blade **19a** formed of rubber material in contact with the photoreceptor drum **10**, and is collected into a waste toner container, not shown, by a screw **19b**. The peripheral surface of the photoreceptor drum **10** is discharged by exposure by a pre-charging uniform exposure device **12e** using, for example, light emitting diodes, and hysteresis of photoreceptor drum **10** due to previous image formation is eliminated.

After a superimposed color toner image, which is a reverse side image, has been formed on the toner image receiving body **14a** due to the forgoing, succeedingly, in the same manner as the above color image forming processes, a superimposed color toner image, which is an obverse side image, is formed on the photoreceptor drum **10** (FIG. 3(B)). In this case, image data is changed so that the obverse side image formed on the photoreceptor drum **10** forms a mirror image with respect to the reverse side image previously formed on the photoreceptor drum **10**.

The recording sheet P, serving as the transfer material, is sent from a sheet feed cassette **15**, which is a transfer sheet accommodation means, to a timing roller **15b**, serving as a transfer material feeding means, by a feeding roller **15a**, and the recording sheet P is in timed relationship with the color toner image of the obverse side image carried on the photoreceptor drum **10**, and the color toner image of the reverse side image carried on the toner image receiving body **14a**, by the drive of the timing roller **15b**, and recording paper P is sent to the transfer area **14b**. By a paper charger **150**, recording paper P is paper-charged to the same polarity as that of toner, and through a color toner image of the reverse image carried on toner image receiving body **14a**, aforesaid recording paper P is attracted to the toner image

receiving body **14a** and sent together with the movement of toner image receiving body **14a**.

In the transfer area **14b**, the color toner image of obverse side image on the photoreceptor drum **10** is collectively transferred onto the obverse side of the recording sheet P by the transfer device **14c** as the first transfer means. At that time, the reverse side image carried on the toner image receiving body **14a** is not transferred onto the recording sheet P, but remains on the toner image receiving body **14a**. Incidentally, in the case of transfer by the transfer device **14c**, uniform exposure may be conducted by the transfer simultaneous exposure device **12d**, which is provided inside the photoreceptor drum **10** and opposite to the transfer area **14b**, using, for example, light emitting diodes, so that transfer can be finely conducted.

The recording sheet P, onto the obverse side of which the color toner image is transferred, is successively conveyed to a reverse side transfer device **14g**, serving as the second transfer means, and color toner image on the reverse side carried on the toner image receiving body **14a** is collectively transferred onto the reverse side of the recording sheet P by the reverse side transfer device **14g** (FIG. 3(C)).

The recording sheet P, in which color toner image was transferred onto the both surfaces thereof as explained above, is separated from the toner image receiving body **14a** by the curvature of the driving roller **14d** to drive the toner image receiving body **14a**, and by the discharging operation of a paper separation AC discharger **14h** as a transfer material separation means, which is provided at need on downstream side of reverse surface transfer device **14g**, and is conveyed to the fixing device **17** as the fixing means, through a conveyance section **160** provide with a spur **162**, which will be described later.

In fixing device **17** as the fixing means structured by **2** roller-like fixing members in both of which a heater is housed. The toner image adhered onto the obverse and reverse sides of the recording sheet P is fixed when the heat and pressure are applied onto it at a nip portion formed of a fixing roller **17a** as a fixing member which is arranged to fix the color toner image of the obverse side image, and a pressure contact roller **17b** as the fixing member arranged to fix the toner image of the reverse side image (image on the lower surface side). The recording sheet P on which two-sided image recording has been conducted, is reversed through a fixing delivery sheet roller **17e**, conveyance rollers **18a**, **18b**, and delivery sheet roller **18**, and is conveyed, and is delivered to the upper portion of the apparatus, with the toner image of the obverse side image facing downward. Further, as shown by a one-dotted chain line in FIG. 1, a switching member, not shown, may be provided at a rear portion of the fixing delivery sheet roller **17e** of an exit of the fixing device **17** so that the recording sheet P advances straight with the toner image of the obverse side image facing upward, to a tray provided outside the apparatus, and is delivered.

Toner, remaining on the toner image receiving body **14a** after transferring, is cleaned by a toner image receiving body cleaning device **140** which is provided opposite to the driven roller **14e** with the toner image receiving body **14a** between them, and which has a toner image receiving body cleaning blade **141** which can be rotated around a support shaft **142** and can be in contact with and contact-released from the toner image receiving body **14a**.

The toner remaining on the photoreceptor drum **10** after transferring, is discharged by a photoreceptor drum AC discharger **16**, and after that, remaining toner is removed by

the cleaning device **19**. By the pre-charging uniform exposure device **12e**, hysteresis of the photoreceptor drum **10** due to previous image formation is eliminated, and the photoreceptor drum **10** enters the next image formation cycle.

By using the above-described method, the superimposed color toner image are collectively transferred, thereby, doubling of the color image, scattering of toner, or frictional damage on the toner image receiving body **14a** hardly occurs, and therefore, a fine two-sided color image having smaller image deterioration can be formed.

Image data for each color of the document inputted into the above-described color image forming apparatus is read by an image reading device **50** provided separately from the apparatus main body or provided in the upper portion of the apparatus main body shown, for example, in FIG. 4.

When the image reading device **50** is used, the document D is stacked in the order of pages from the lower side, with the obverse side facing downward, and the lowermost document D is carried toward a conveyance path **53** by the operation of a carrying belt **51** and a handling roller **52**.

The carried-out document D removes a guide plate **53a**, which is activated at a position shown by a solid line, and withdraws it to a position shown by a dashed line. The document D is fed onto a transparent platen glass **55** through a conveyance belt **54**, and is temporarily stopped at a document reading position with the reverse side facing downward.

The reverse side image of the document D on the platen glass **55** is read by the reading operation due to the speed V of the first mirror unit **56** and the moving exposure due to the speed V/2 of the second mirror unit in the same direction, and is formed on **3** image pick-up elements CCDs through a projection lens L and a dichroic prism M, wherein the first mirror unit **56** is composed of an illumination lamp and the first mirror, and the second mirror unit **57** is composed of the second mirror and the third mirror which are arranged V-shape. The reverse side image which has been color-separated and formed on the image pick-up elements CCDs, is stored in an image memory (I) as each color image data after being image-processed, outputted to each exposure optical system **12** as an electric signal, and a latent image is formed on the photoreceptor drum **10**. The toner image formed after developing, is transferred by the transfer device **14c**, and the reverse side image is formed on the toner image receiving body **14a**.

In the image reading device **50**, when reading of the reverse side image has been completed, the obverse side and the reverse side of the document D are reversed through a reversed sheet feeding path **58** by a temporary reverse rotation of a conveyance belt **54**, fed again onto the platen glass **55** by the conveyance belt **54** through the conveyance path **53**, and is temporarily stopped at the document reading position under the condition that the obverse side faces downward.

The obverse side image of the document D on the platen glass **55** is read by the scanning optical system, temporarily stored in an image memory (II) as each color image data after image processing and outputted to each exposure optical system **12** as an electric signal, and the obverse side image is formed on the photoreceptor drum **10**.

The reverse side image formed on the toner image receiving body **14a** and the obverse side image formed on the photoreceptor drum **10** are respectively transferred onto the obverse side and the reverse side of the first recording sheet P fed from the sheet feed cassette **15**, and the copy cycle of the first sheet is completed. The recording sheet P having the

obverse side toner image and the reverse side toner image is fixed by the fixing device 17, the obverse side and reverse side of the recording sheet P are reversed, and the recording sheet P is delivered with the obverse side facing downward onto a tray provided outside the apparatus.

In the case of copying the second and subsequent sheet, the document D is not read, the reverse side image is formed by outputting image data from the image memory (I), the obverse side image is formed by outputting image data from the image memory (II), and the obverse side image and the reverse side image are respectively transferred onto the obverse and reverse sides of the second and subsequent recording sheet P fed from the sheet feed cassette 15. The recording sheet P having the obverse side toner image and the reverse side toner image is fixed by the fixing device 17, and is stacked on the previously delivered recording sheets in the order of pages with the obverse side facing downward.

On the other hand, in the image reading device 50, the document D which has been read, is delivered onto the tray 60 by the operation of the conveyance belt 54 through the delivery sheet roller 59 such that the document D is stacked on the tray 60 in the order of pages from the lower side with the obverse side facing downward.

#### The First Example of the Transfer Sheet Loop Formation

Referring to FIGS. 5, 6 and 1, a conveyance section having a spur according to the present invention will be described below. FIG. 5 is a view showing the conveyance section, and FIG. 6 is a perspective view of a spur provided in the conveyance section.

A conveyance section 160 provided with a spur 162 on the side lower than the extended surface of the transfer material conveyance surface of the toner image receiving body 14a, is provided between the toner image receiving body 14a and the fixing device 17, and the recording sheet P separated from the toner image receiving body 14a is conveyed through the conveyance section 160 to the fixing device 17 which is vertically provided with the fixing roller 17a and the pressure contact roller 17b.

A central shaft 162a integrally provided in the spur 162 is inserted into a hole of a semi-circular stop portion 163b which is provided on the opposite side of the guide surface 163a of a conveyance guide member 163, a leading edge portion of the central shaft 162a is held by an E-shaped ring E, and the spur 162 is rotatably fitted to the conveyance guide member 163. A plurality of conveyance guide members 163 provide with spurs 162 are fitted to a conveyance section casing 161, and thus, the conveyance section 160 is structured.

The guide surface 163a of the conveyance guide member 163 is provided on the transfer material conveyance surface side rather than at the rotation center of the spur 162. Due to this, even when the leading edge portion of the recording sheet p separated from the toner image receiving body 14a comes into contact with the guide surface 163a, it is taken up and sent to the spur 162, the spur 162 is rotated under the condition that a protruded portion 162b of the spur 162 comes into contact with the recording sheet P or sticks into it, and the recording sheet P is conveyed to the fixing device 17 without being rubbed.

The spur 162, formed of a 0.05–0.5 mm thick and 5–25 mm outer diameter metallic plate in which a metallic plate such as a stainless steel plate or a copper plate is etching-processed, or a 0.5–2.0 mm thick and 5–25 mm outer diameter resin member, is used, and is formed of a polygonal

member, for example, hexagonal plate-like member, in which a sharp protruded portion 162b is provided on the leading edge of the member.

In FIG. 7 and FIG. 8, in the case of two-side image formation in which a large amount of thermal capacity is needed at fixing, the recording sheet P intermittently passes the fixing device, and in the case of only one-side obverse side image formation, the recording sheet P continuously passes the fixing device 17. In any case, the fixing roller 17a to fix obverse side image preferably has fine thermal conductivity and large thermal capacity. As shown in FIG. 7, in respective roller members of the fixing device 17, a hard roller using a metallic roller member 171a such as steel member or aluminium member, for example, on the surface of which Teflon coating is conducted, is used for the fixing roller 17a as the upper roller member; and a soft roller in which, a rubber roller 172b using, for example, silicon member is formed around a metallic pipe 172a using, for example, aluminium member, and for example, Teflon coating is conducted on the surface, is used for the pressure contact roller 17b as the lower roller member. When both rollers are in pressure-contact with each other, a convex circular arc nip portion T is formed on the side of pressure contact roller 17b using the soft roller. Halogen heaters 171c and 172c for a fixing heat are provided inside respective rollers.

As shown in FIG. 8, the recording sheet P on both sides of which the color toner image is formed, is separated from the toner image receiving body 14a by the curvature of the driving roller 14d to drive the toner image receiving body 14a, and by the discharging operation of the paper separation AC discharger 14h as the transfer material separation means provided opposite to the driving roller 14d at need at the end portion of the toner image receiving body 14a.

The recording sheet P separated from the toner image receiving body 14a as the second image carrier means, is conveyed by the spur 162 provided lower side of the extended surface of the transfer material conveyance surface PL1 of the toner image receiving body 14a, and is sent to the nip portion T of the fixing device 17 as the fixing means composed of the upper and lower rollers in which the hard roller is used as the fixing roller 17a, and the soft roller is used as the pressure contact roller 17b.

When the leading edge of the recording sheet P as the transfer material is nipped by a circular arc nip portion T of the fixing roller 17a, a force acts on the recording sheet P to take up it in the tangential direction of the fixing roller 17a at the point P1 on the entry side of the recording sheet P in the nip portion T, a loop is formed so that the reverse side of the recording sheet P is separated from the spur 162 as shown by a bold line arrow in FIG. 8, the recording sheet P is conveyed in the upper portion of the conveyance section 160 under the condition that the recording sheet P is separated from the spur 162, and the recording sheet P is fixed by the fixing device 17. In this case, the extended surface of the transfer material conveyance surface PL1 of the toner image receiving body 14a preferably comes into contact with the vicinity of the nip portion T of the fixing roller 17a as the upper roller member of the fixing device 17, for example, a 1–3 mm upper portion of the point P1 on the entry side of the recording sheet p in the nip portion T. Thereby, the recording sheet P smoothly advances into the nip portion T.

As described above, because the obverse side image fixing roller is the hard roller, even when the recording sheet or OHT used as the transfer material contacts with the

obverse side image fixing roller, the obverse side image fixing roller is not damaged. Further, because the reverse side image fixing roller is the soft roller, the width of nip portion is larger, so that fine fixing can be conducted.

Further, a plate-like entry guide member 165 as shown by a one-dotted chain line in FIG. 8 may be provided between the conveyance section 160 and the fixing device 17, and thereby, the leading edge of the recording sheet P comes into contact with the fixing roller 17a as the upper roller member through the entry guide member 165. In this case, when the leading edge portion of the entry guide member 165 is provided lower the point P1 in the nip portion T, it is preferable because the toner image of the reverse side image of the recording sheet P is not rubbed by the leading edge portion of the entry guide member 165.

Due to the foregoing, generation of a spur track on the toner image on the transfer material and toner contamination of a transfer material due to contamination of spur are prevented.

#### The Second Example of Loop Formation of the Transfer Sheet

According to FIG. 9, in the present example, the conveyance section 160 described in FIG. 8 is arranged upper than that in FIG. 8, and the construction of rollers of the fixing means is the same as that described in FIG. 6.

The recording sheet P on both sides of which the color toner image is formed, is separated from the toner image receiving body 14a by the curvature of the driving roller 14d to drive the toner image receiving body 14a, and by the discharging operation of the paper separation AC discharger 14h as the transfer material separation means provided opposite to the driving roller 14d at need at the end portion of the toner image receiving body 14a.

The recording sheet P separated from the toner image receiving body 14a as the second image carrier means, is conveyed by the spur 162 provided lower side of the extended surface of transfer material conveyance surface PL1 of the toner image receiving body 14a, and is sent to the circular arc nip portion T of the fixing device 17 as the fixing means composed of the upper and lower rollers, in which the hard roller is used as the fixing roller 17a, and the soft roller is used as the pressure contact roller 17b.

When the leading edge of the recording sheet P as the transfer material is nipped by the circular arc nip portion T of the fixing roller 17a, a force acts on the recording sheet P to take up it in the tangential direction of the fixing roller 17a at the point P1 on the entry side of the recording sheet P in the nip portion T, the reverse side of the recording sheet P is separated from the spur 162 as shown by a bold line arrow in FIG. 9, the recording sheet P is conveyed in the upper portion of the conveyance section 160 under the condition that the recording sheet P is separated from the spur 162, and the recording sheet P is fixed by the fixing device 17.

The extended surface PL2 of the recording sheet P conveyance surface along the spur 162 comes into contact with the vicinity of the nip portion T of the fixing roller 17a as the upper roller member of the fixing device 17, for example, a 0.5–2.5 mm upper portion of the point P1 on the entry side of the recording sheet p in the nip portion T. Thereby, the recording sheet P smoothly enters into the nip portion T.

As described above, because the obverse side image fixing roller is the hard roller, even when the recording sheet or OHP used as the transfer material contacts with the obverse side image fixing roller, the obverse side image

fixing roller is not damaged. Further, because the reverse side image fixing roller is the soft roller, the width of nip portion is larger, so that fine fixing can be conducted.

Due to the above description, generation of the spur track on the toner image on the transfer material and toner contamination of a transfer material due to contamination of spur are prevented.

#### The Third Example of Loop Formation of the Transfer Material

According to FIG. 10, as the roller members of the fixing device 17 of the present example, a fixing roller 17c using the soft roller is used as the upper roller, instead of the upper fixing roller 17a using the hard roller described in FIGS. 7 and 8.

As respective roller members of the fixing device 17, a soft roller in which a rubber roller 173b using, for example, silicon member is formed around a metallic pipe 173a using, for example, aluminum member, is used for the fixing roller 17c as the upper roller member and provided with Teflon coat on the surface thereof, and, in the same manner as the upper roller member, a soft roller in which a rubber roller 172b using, for example, silicon member is formed around a metallic pipe 172a using, for example, aluminum member, and for example, Teflon coating is conducted on the surface, is also used for the pressure contact roller 17b as the lower roller member. When both rollers are in pressure-contact with each other, a nip portion T is formed on the upper and lower rollers respectively using the soft roller. Because the upper and lower rollers are composed of soft rollers, the nip portion T is linearly provided almost perpendicular to the surface PL3 passing the central axis of the fixing roller 17c and that of the pressure contact roller 17b. Halogen heaters 173c and 172c for a fixing heat are provided inside respective roller members.

Because the nip portion T is formed linearly, the surface PL3 is provided such that the upper roller is inclined toward the delivery side of the recording sheet P with respect to the extended surface of transfer material conveyance surface PL1 of the toner image receiving body 14a as the second image carrier means, the fixing roller 17c and the pressure contact roller 17b are arranged with inclination, and the entrance of the nip portion T is provided above the exit with inclination.

The recording sheet P on both sides of which the color toner image is formed, is separated from the toner image receiving body 14a by the curvature of the driving roller 14d to drive the toner image receiving body 14a as necessary, and by the discharging operation of the paper separation AC discharger 14h as the transfer material separation means provided opposite to the driving roller 14d at need at the end portion of the toner image receiving body 14a.

The recording sheet P separated from the toner image receiving body 14a as the second image carrier means, is conveyed by the spur 162 provided lower side of the transfer material conveyance surface PL1 of the toner image receiving body 14a, and is sent to the nip portion T of the fixing device 17 as the fixing means composed of the upper and lower rollers, in which the soft rollers are used as the fixing roller 17a and the pressure contact roller 17b.

When the leading edge of the recording sheet P as the transfer material is nipped by the nip portion T of the fixing device 17, a force acts on the recording sheet P to take up it in the extension direction of the linear nip portion T provided with inclination, the reverse side of the recording sheet P is separated from the spur 162 as shown by a bold line

arrow in FIG. 10, the recording sheet P is conveyed above the conveyance section 160 under the condition that the recording sheet P is separated from the spur 162, and the recording sheet P is fixed by the fixing device 17. In this case, the extended surface of the transfer material conveyance surface PL1 of the toner image receiving body 14a preferably comes into contact with the vicinity of the nip portion T of the fixing roller 17c as the upper roller member of the fixing device 17, for example, a 1–3 mm upper portion of the point P1 on the entry side of the recording sheet P in the nip portion T. Thereby, the recording sheet P smoothly enters into the nip portion T.

Due to the above description, generation of the spur track on the toner image on the transfer material and toner contamination of a transfer material due to contamination of spur are prevented.

#### The Fourth Example of Loop Formation of the Transfer Sheet

According to FIG. 11, as the roller member of the fixing device of the present example, a thermal fixing film 17d serving as a hard roller, which will be described below, is used as the upper roller member, instead of the upper fixing roller 17a described in FIGS. 7 and 8.

The thermal fixing film 17d as the upper roller member is structured by, for example, a fixing film 174a of 40–100  $\mu\text{m}$  thin film, a plate-like heat emitting body (ceramic heater) 174b, and a heater holder 174c to hold the ceramic heater 174b. The seamless type fixing film 174a is structured by an inside base member, an intermediate conductive layer and a surface releasing layer. In the same manner as described in FIG. 6, for the pressure contact roller 17b as the lower roller member, a soft roller in which a rubber roller 172b, for example, using silicon material is formed around a metallic pipe 172a using, for example, aluminum material, is used, and a halogen heater 172c for fixing heat is provided inside the roller member. When both rollers pressure-contacts with each other, a convex circular arc nip portion T is formed on the side of the pressure contact roller 17b using the soft roller.

The base member of the fixing film 174a is resistant to high temperature, and under the high temperature, it is rotated while sliding on the ceramic heater 174b. As the material in which a change in dimension is small and a high elastic modulus is maintained under such the circumstance, polyimide resin is preferably used, and it is preferable that carbon is dispersed so that a 5–20  $\mu\text{m}$  thickness layer is formed on the surface of 20–80  $\mu\text{m}$  thick polyimide resin and the total thickness becomes about 40–100  $\mu\text{m}$ . When the thickness becomes about 40  $\mu\text{m}$ , strength and rigidity is increased, so that deviation during rotation of the fixing film 174a can be regulated at the end portion without being buckled. Further, when the thickness is more than 100  $\mu\text{m}$ , the thermal conductivity is lowered, and the thermal capacity is increased, thereby, it is difficult to instantaneously heat the material, and power consumption is also increased. Further, in order to prevent the offset, 2 layer construction in which, for example, a fluorine resin (PEA or PTFE) layer is provided as a releasing layer, is preferable, and further, a conductive layer is provided and electrically grounded so that influence of triboelectric charge generated by sliding between the inner surface of the base material of the fixing film 174a and the surface of the ceramic heater 174b, is eliminated.

Further, in order to release peeling electrostatic charge of the trailing edge portion of the recording sheet P under the

low environment, a conductive filament is inserted into the releasing layer so that the resistance value is decreased, and thereby offset is prevented. However, when the resistance value is too low, because transfer electric charge leaks and offset occurs, the resistance value of  $2 \times 10^{10}$ – $5 \times 10^{11}$   $\Omega/\text{cm}^2$  is preferable.

The recording sheet P on both sides of which the color toner image is formed, is separated from the toner image receiving body 14a by the curvature of the driving roller 14d to drive the toner image receiving body 14a, and by the discharging operation of the paper separation AC discharger 14h as the transfer material separation means provided opposite to the driving roller 14d at the end portion of the toner image receiving body 14a.

The recording sheet P separated from the toner image receiving body 14a as the second image carrier means, is conveyed by the spur 162 provided lower side of the extended surface of transfer material conveyance surface PL1 of the toner image receiving body 14a, and is sent to the nip portion T of the fixing device 17 as the fixing means, composed of the upper and lower rollers, in which the thermal fixing film 17d is used as the hard roller serving as the upper roller, and the soft roller is used as the pressure contact roller 17b.

When the leading edge of the recording sheet P as the transfer material is nipped by a circular arc nip portion T of the fixing device 17, a force acts on the recording sheet P to take up it in the tangential direction of the thermal fixing film 17d at the point P1 on the entry side of the recording sheet P in the nip portion T, the reverse side of the recording sheet P is separated from the spur 162 as shown by a bold line arrow in FIG. 11, the recording sheet P is conveyed above the conveyance section 160 under the condition that the recording sheet P is separated from the spur 162, and the recording sheet P is fixed by the fixing device 17. In this case, the extended surface of the transfer material conveyance surface PL1 of the toner image receiving body 14a preferably comes into contact with the vicinity of the nip portion T of the thermal fixing film 17d as the upper roller member of the fixing device 17, for example, a 1–3 mm upper portion of the point P1 on the entry side of the recording sheet p in the nip portion T. Thereby, the recording sheet P smoothly enters into the nip portion T.

As described above, as a roller for surface image fixing, thermal fixing film which effects as a hard roller is used. Further, because the reverse side image fixing roller is the soft roller, the width of nip portion is larger, so that fine fixing can be conducted.

Due to the above description, generation of the spur track onto the toner image on the transfer material and toner contamination of a transfer material due to contamination of spur are prevented, and image frictional damage by the second image carrier means and transfer slippage by the second transfer means, which are caused when the transfer material is pulled, in the case where the transfer material is nipped by the fixing means, can be prevented.

#### The Fifth Example of Loop Formation of the Transfer Sheet

Referring to FIGS. 12, 13 and 1, the spur member and the conveyance section having the spur member will be described below. FIG. 12 is a view showing the conveyance section, and FIG. 13 is a perspective view of the spur member provided in the conveyance section in FIG. 12.

The recording sheet P is conveyed while being attracted by the toner image receiving body 14a in which driving

roller **14d**, as a roller member, is driven to be rotated moved by a driving roller **14d** which is a roller member driven by the driving motor **M1**, and on the reverse surface side of the recording sheet **P** lower than the transfer material conveyance surface of the toner image receiving body **14a** or its extended surface **PL1** (hereinafter, it is called the transfer material conveyance surface **PL1**), the conveyance section **160** provided with the spur **162** which serves as the spur member, is arranged between the toner image receiving body **14a** and the fixing device **17**, and the recording sheet **P** separated from the toner image receiving body **14a** is conveyed to the fixing device **17** provided vertically with fixing roller **17a** and the pressure contact roller **17b**, through the conveyance section **160**.

A plurality of spurs **162** are provided parallelly as spur groups **H1**, **H2**, in the direction perpendicular to the conveyance direction of the recording sheet **P**, that is, in the longitudinal direction of the fixing device **17**. Spur groups at least more than 1 group are provided.

The spur **162**, formed of a 0.05–0.5 mm thick and 3–25 mm outer diameter metallic plate in which a metallic plate such as a stainless steel plate or a copper plate is etching-processed, or a 0.5–2.0 mm thick and 3–25 mm outer diameter insulating resin member, is used, and is formed of a polygonal member, for example, hexagonal plate-like member, in which a sharp protruded portion **162b** is provided on the leading edge of the member. In the case where the spur **162** is formed of a metallic plate, it is preferable that the spur **162** is electrically grounded through an electrical resistance of  $10^8$ – $10^{14}$   $\Omega$ . The reason why the spur **162** is electrically grounded through the metallic plate and a high resistance, or using a high resistance member, is that toner or the transfer material has electrical charges, and therefore, electrical charge accumulation on the spur **162** or toner adhesion to the spur by the mirror image force is prevented by discharging so that disturbance of the toner image is prevented. In the same condition, it may also be possible that the metallic plate is made to be on floating and insulated condition, thereby, toner adhesion is prevented and disturbance of toner image is prevented. Further, it may also be possible that voltage with the same polarity as that of toner (in the present example, negative polarity) is applied on the metallic plate so that toner adhesion is prevented, and thereby, disturbance of the toner image is prevented. When an insulating member such as an insulating resin member, or the like, is used for the spur **162**, toner adhesion by the electric charge accumulation or mirror image force is prevented by charging, in the same manner as in the case of floating, and thereby, disturbance of the toner image can also be prevented.

The guide surface **163a** of the conveyance guide member **163** is provided on the transfer material conveyance surface side (upper surface) rather than at the rotation center of the spur **162**. Due to this, even when the leading edge portion of the recording sheet **p** separated from the toner image receiving body **14a** comes into contact with the guide surface **163a**, it is taken up by the guide surface **163a** and sent to the spur **162**, the spur **162** is rotated under the condition that a protruded portion **162b** of the spur **162** comes into contact with the recording sheet **P** or sticks into it, and the recording sheet **P** on which the toner image is not rubbed, is conveyed to the fixing device **17**.

As shown in FIG. **14**, the recording sheet **P** on both sides of which the color toner image is formed, is separated from the toner image receiving body **14a** by the curvature of a curvature portion **KT** of the toner image receiving body **14a** trained around the driving roller **14d**, and by the discharging

operation of the paper separation AC discharger **14h** as the transfer material separation means provided opposite to the driving roller **14d** at need at the end portion of the toner image receiving body **14a**.

The recording sheet **P** is conveyed by the spur **162** provided on the reverse surface side (lower side) lower than the transfer material conveyance surface **PL1** of the toner image receiving body **14a**, and is sent to the nip portion **T** of the fixing device **17** as the fixing means composed of the upper and lower rollers in which the hard roller is used as the fixing roller **17a**, and the soft roller is used as the pressure contact roller **17b**. A point **P1** at the entry of the nip portion **T** is provided on the reverse surface side of the recording sheet **P** lower than the transfer material conveyance surface **PL1** of the toner image receiving body **14a**.

For the driving roller **14d** as the roller member, around which the toner image receiving body **14a** is trained, and which drives the toner image receiving body **14a**, generally, as the outer diameter of the driving roller **14d**, a roller having approximately 10–30 mm outer diameter is used and the curvature portion **KT** is formed. Further, the outer diameter of the upper and lower rollers of the fixing device **17** is approximately 30–60 mm. The distance **L** in the parallel direction with respect to the transfer material conveyance surface **PL1** between the point **P1** at the entry of the nip portion **T** and a separation position **P2** at which the curvature portion **KT** of the toner image receiving body **14a** begins to have curvature, is generally about 50–200 mm.

In the above description, a conveyance speed **V2** of the recording sheet **P** by the fixing device **17** is set to be lower than a conveyance speed **V1** of the recording sheet **P** by the toner image receiving body **14a**, and the conveyance speed **V2** is, with respect to the conveyance speed **V1**,  $0.002 \times V2 \leq V1 - V2 \leq 0.05 \times V2$ . Due to this, a loop of the recording sheet **P** is formed between the point **P1** at the entry of the nip portion **T** and a separation position **P2** at which the curvature portion **KT** of the toner image receiving body **14a** begins to have curvature. The loop of the recording sheet **P** is convex on the obverse surface side of the recording sheet **P** in the vicinity of the nip portion **T** by the nip portion **T** formed to be circular arc (convex-shape) on the reverse surface side of the recording sheet **P**, and is formed in the direction separated from the spur **162**. When the velocity ratio is larger than 0.998, the loop of the recording sheet **P** is hardly formed, and the recording sheet is conveyed under the condition that the recording sheet **P** is pushed toward the spur **162**, and sometimes disturbance (frictional damage) of the reverse side toner image occurs. Further, when the velocity ratio is not larger than 0.950, too large loop is formed, conveyance of the recording sheet **P** becomes unstable, the loop reaches the toner image receiving body **14a**, and the recording sheet **P** is lifted from the toner image receiving body **14a**, and thereby, sometimes a transfer trouble occurs at the reverse surface transfer device **14g**.

Further, all of plural sets **H1** and **H2** of spurs **162** are arranged on the reverse surface side (lower side) of the recording sheet **P**, which is lower than the surface **PL4** including the point **P1** at the entry of the nip portion **T** of the fixing device **17** and a separation position **P2** of the toner image receiving body **14a**, at which the curvature portion **KT** of the toner image receiving body **14a** begins to have curvature, and the separation position **p2** is arranged on the reverse surface side (lower side) of the recording sheet **P**, which is lower than the tangent **PL5** at the point **P1** of the entry of the nip portion **T**. Thereby, the recording sheet **P** separated from the separation position **P2** seldom receives the pressure from the spur **162** while it naturally drops by its

self weight, and smoothly enters into the nip portion T; the number of contact of the recording sheet P with the spur 162 or contact time is decreased; the contact force of the recording sheet P with the spur 162 is greatly reduced, and the recording sheet P is conveyed from the toner image receiving body 14a to the fixing device 17, thereby, the stain of the toner image on the reverse side of the recording sheet by the spur 162 is prevented.

Further, as described above, when the entry of the nip portion T is provided on the reverse surface side of the recording sheet P lower than the transfer material conveyance surface PL1 of the toner image receiving body 14a, and the distance in the parallel direction between the point P1 at the entry of the nip portion T and the separation position P2 of the toner image receiving body 14a with respect to the transfer material conveyance surface PL1 is L and the distance between the point P1 and the point P2, perpendicular to the transfer material conveyance surface PL1, is H, then, the relationship  $0.02 \leq H/L \leq 0.1$  is preferable. When  $H/L \leq 0.02$ , the position of the spur 162 is higher with respect to the recording sheet P which is naturally dropped and conveyed, the pressing force to the reverse side toner image by the protruded portion 162a of the spur 162 is larger, and thereby, a stain (frictional damage) of the reverse side toner image frequently occurs. Further, when  $H/L > 0.1$ , a fall of the recording sheet P after it is separated from the separation position P2, with respect to the spur 162 becomes larger, the conveyance of the recording sheet P by the spur is unstable, and thereby, entering of the recording sheet P into the nip portion T or gripping by the nip portion T is not conducted satisfactorily.

As described above, the spur 162 is used as an auxiliary means of the conveyance of the recording sheet P, a change of the conveyance track of the recording sheet P by the spur 162 is prevented, the recording sheet P is stably conveyed in the constant direction from the toner image receiving body 14a to the fixing device 17, and thereby, a stain of the reverse side toner image by the spur 162 of the recording sheet P conveyed from the toner image receiving body 14a to the fixing device 17 is prevented. In addition, disturbance of toner and transfer deviation on the reverse surface due to that recording paper P is pulled when recording paper P is sandwiched by fixing device 17 can be prevented.

#### The Sixth Example of Loop Formation of the Transfer Material

According to FIG. 16, as the roller members of the fixing device 17 of the present example, a fixing roller 17c using the soft roller is used as the upper roller, instead of the upper fixing roller 17a using the hard roller described in FIG. 14.

As respective roller members of the fixing device 17, a soft roller in which a rubber roller 173b using, for example, silicon member is formed around a metallic pipe 173a using, for example, aluminum member, and for example, Teflon coating is conducted on the surface, is used for the fixing roller 17c as the upper roller member, and, in the same manner as the upper fixing roller member, a soft roller in which a rubber roller 172b using, for example, silicon member is formed around a metallic pipe 172a using, for example, aluminum member, and for example, Teflon coating is conducted on the surface, is also used for the pressure contact roller 17b as the lower fixing roller member. When both rollers are in pressure-contact with each other, a nip portion T is formed between the upper and lower rollers respectively using the soft roller. Because the upper and lower rollers are composed of soft rollers, the nip portion T

is linearly provided almost perpendicular to the surface PL3 passing the central axis of the fixing roller 17c and that of the pressure contact roller 17b. Halogen heaters 173c and 172c for a fixing heat are provided inside respective roller members.

The nip portion T is formed linearly, the surface PL3 is provided such that the upper roller is inclined toward the delivery side of the recording sheet P with respect to the transfer material conveyance surface PL1 of the toner image receiving body 14a as the second image carrier means, and the line formed between the point P1 at the entry and the point P3 at the exit of the nip portion T formed by the fixing roller 17c and the pressure contact roller 17b is provided with inclination toward the reverse surface side with respect to the conveyance direction of the recording sheet P.

The recording sheet P on both sides of which the color toner image is formed, is separated from the toner image receiving body 14a by the curvature of a curvature portion KT of the toner image receiving body 14a trained around the driving roller 14d, and by the discharging operation of the paper separation AC discharger 14h as the transfer material separation means provided opposite to the driving roller 14d at need at the end portion of the toner image receiving body 14a. The recording sheet P is conveyed by the spur 162 provided on the reverse surface side (lower side) lower than the transfer material conveyance surface PL1 of the toner image receiving body 14a, and is sent to the nip portion T of the fixing device 17 as the fixing means composed of the upper and lower rollers in which the soft roller is used as the fixing roller 17c, and the soft roller is used as the pressure contact roller 17b.

The loop of the recording sheet P is formed by the nip portion T provided with inclination, in the same manner as described in FIG. 15. The loop is convex on the obverse surface side of the recording sheet P in the vicinity of the nip portion T, and is formed in the direction separated from the spur 162. The positional relationship of the nip portion T of the fixing device 17, the curvature section KT of the toner image receiving body 14a, and the spur 162 is structured in the same manner as described in FIG. 14. Thereby, while the recording sheet P separated from the separation position P2 naturally drops by self weight, the recording sheet P seldom receives the pressure from the spur 162 t, and smoothly enters into the nip portion T; the number of contact of the recording sheet P with the spur 162 or contact time is decreased; the contact force of the recording sheet P with the spur 162 is greatly reduced, and the recording sheet P is conveyed from the toner image receiving body 14a to the fixing device 17, thereby, the stain of the toner image on the reverse side of the recording sheet by the spur 162 is prevented.

Further, the spur 162 is used as an auxiliary means of the conveyance of the recording sheet P, a change of the conveyance track of the recording sheet P by the spur 162 is prevented, the recording sheet P is stably conveyed in the predetermined direction from the toner image receiving body 14a to the fixing device 17, and thereby, a stain of the reverse side toner image by the spur 162 of the recording sheet P conveyed from the toner image receiving body 14a to the fixing device 17 is prevented.

#### The Seventh Example of the Loop Formation of the Transfer Sheet

Referring to FIGS. 17 and 18, the present example will be described below.

The conveyance speed of the transfer material by the fixing means in the image forming apparatus of the present

example, that is, the peripheral speed  $V_2$  of the nip portion T formed by the roller 17a (fixing roller 17a) and the roller 17b (fixing roller 17b) is set to the slightly lower speed than the conveyance speed of the transfer material by the second image carrier means, that is, the peripheral speed  $V_1$  of the toner image receiving body 14a. Accordingly, the recording sheet P as the transfer material produces some slacks between a position where recording paper P is separated from toner image receiving body 14a and the nip portion T formed by the roller 17a, after the leading edge portion of the recording sheet P has been nipped in the nip portion T, and is conveyed while forming a loop.

The nip portion T of the fixing means is formed to be convex with respect to the reverse surface side of the transfer material, that is, the roller 17b side as shown in FIG. 17, or the inclination of the entry and the exit of the nip portion T is formed into a plane inclined on the reverse surface side with respect to the conveyance direction of the transfer material as shown in FIG. 18. After the leading edge of the recording sheet P separated from the peripheral surface of the toner image receiving body 14a comes into contact with the peripheral surface of the roller 17a, the recording sheet P is conveyed to the nip portion T along the peripheral surface, nipped and heated, and the toner images transferred onto both of obverse side and reverse side are simultaneously fixed by the fixing device 17.

As the result, after the transfer of the toner image, the recording sheet P is almost linearly conveyed as shown by a one-dotted chain line in the initial stage of separation from the toner image receiving body 14a and comes into contact with the peripheral surface of the fixing roller 17a, and in the late stage of separation after the leading edge of the recording sheet P is nipped by the nip portion T, the recording sheet P is conveyed while forming the convex loop on the side surface side, by the force according to the shape of the nip portion T, as shown by a two-dotted chain line. When a variation range of the posture of conveyance satisfies the conveyance condition, which will be described later, it is limited, and thereby, the conveyed recording sheet P is stably conveyed, delivered without disturbing the transferred toner image, and is fixed.

In the delivery of the recording sheet P to the fixing device 17, when an amount of the slack of the recording sheet P by the loop formation is not larger than 5% of the minimum conveyance distance by which the conveyance between a position where recording paper P is separated from toner image receiving body 14a and the nip portion can be conducted, the recording sheet can be conveyed without any trouble. When the amount of slack is not smaller than 5% and the recording sheet is loosened, the toner image on the obverse side of the recording sheet is rubbed by the paper separation AC discharger 14h and the obverse image is disturbed, or the recording sheet P is bent at the entry of the nip portion of the fixing device and jamming easily occurs. The above description is confirmed by experiments by inventors of the present invention. Accordingly, the difference between the conveyance speed  $V_1$  by the toner image receiving body 14a and the conveyance speed  $V_2$  by the rollers 17a and 17b is set as follows.

When the maximum length of the recording sheet P used in the present image forming apparatus is  $L_1$ , the minimum conveyance distance by which the conveyance between a position where recording paper P is separated from toner image receiving body 14a and the nip portion T can be carried out is  $L_2$ , the slack amount of the recording sheet P after time  $t$  has passed after the leading edge of the recording sheet P has been nipped in the nip portion T is  $X_1$ , and the moving distance of the recording sheet P after time  $t$  has passed is  $X_2$ ,

$$t = X_2 / V_2 \quad (1)$$

$$X_1 = (V_1 - V_2)t \quad (2)$$

By equations (1) and (2), the difference between the conveyance speed is

$$V_1 - V_2 = (X_1 / X_2) \times V_2 \quad (3)$$

As the conditional relationship obtained by the previous experiments,

$$X_1 \leq L_2 \times 0.05$$

The maximum moving distance of the recording sheet P on the nip surface at the time is

$$X_{2max} = L_1 - L_2$$

Accordingly, by the equation (3),  $V_1$  and  $V_2$  may be set so as to satisfy the following equation,

$$V_1 - V_2 \leq \{(L_2 \times 0.05) / (L_1 - L_2)\} \times V_2 \quad (4)$$

Further, the relationship (4) is given a margin,

$$V_1 - V_2 \leq \{(L_2 \times 0.05) / L_1\} \times V_2 \quad (5)$$

Further, in order to stably form an adequate amount of loop on the conveyance path, the difference between  $V_1$  and  $V_2$  is preferably more than 1% of  $V_2$ , for the safety's sake, and it is the preferable condition that the difference satisfies the following conditional relationship (6) together with the relationship (5).

$$0.01 \times V_2 \leq V_1 - V_2 \leq \{(L_2 \times 0.05) / L_1\} \times V_2 \quad (6)$$

Incidentally, in FIGS. 17 and 18, driven roller 140d is provided so as to support the toner image receiving body 14a.

#### Example of a Conveyance Section Having No Spur Wheel

In the above-mentioned embodiment, a conveyance section having a spur was explained. However, the present invention is not limited thereto. In conveyance section 160 explained in FIGS. 5 and 6, spur 162 is not provided. In addition, in place of conveyance guide member 163, a conveyance guide wire whose diameter was 50–150  $\mu\text{m}$  was extended at the same position as guide surface 163a of the above-mentioned conveyance guide member. This can be used as a conveyance guide member.

The conveyance section having a conveyance guide wire is provided on the reverse surface of the transfer material from the extended surface of the transfer material conveyance surface of toner image receiving body 14a between toner image receiving body 14a and fixing device 17. The conveyance guide wire is extended parallel to the direction of the conveyance of transfer material or extending with an opening angle of 5–20°. Distance between a position where toner image receiving body 14a start having curvature at the end of fixing device 17 and the inlet portion of the nip portion of fixing device 17 is ordinarily set to be 50–200 mm at a conveyance section having a spur.

The end of recording paper P separated from toner image receiving body 14a is temporarily brought into contact with a conveyance guide wire. Following it, it is separated from the conveyance guide wire due to stiffness of recording paper P. While it is separated from the conveyance guide wire, it advances to the nip portion of fixing device 17.

When the end of recording paper P is sandwiched at the nip portion, a loop is formed in such a manner that recording paper P is additionally separated from the conveyance guide wire due to the form of the nip portion or the inclination of the nip surface. Recording paper P is conveyed to fixing device 17 while not being contacted to the conveyance guide wire.

Due to the above, the occurrence of toner contamination of the transfer material due to scrubbing of the toner image on the transfer material due to the conveyance guide wire or contamination of the conveyance guide wire.

#### Examples of Cleaning for the Spur

Referring to FIGS. 19 to 22, a cleaning member for the spur and its arrangement will be described below. FIG. 19 is a view showing the first example of a fitting method of the cleaning member for the spur. FIG. 20 is a perspective view showing the cleaning member. FIG. 21 is a view showing the second example of the fitting method of the cleaning member for the spur. FIG. 22 is a view showing the third example of the fitting method of the cleaning member for the spur.

As described in FIGS. 5 and 6, the conveyance section 160 having the spur is provided between the toner image receiving body 14a as the second image carrier means and the fixing device 17 as the fixing means.

The recording sheet P on both sides of which the color toner image is formed, is separated from the toner image receiving body 14a by the curvature of the driving roller 14d to drive the toner image receiving body 14a, and by the discharging operation of the paper separation AC discharger 14h as the transfer material separation means provided opposite to the driving roller 14d at need at the end portion of the toner image receiving body 14a.

The recording sheet P separated from the toner image receiving body 14a as the second image carrier means, is conveyed by the spur 162 provided in the conveyance section 160, and is sent to the nip portion T of the fixing device 17 as the fixing means composed of the fixing roller 17c and the pressure contact roller 17b, and toner images on both sides of the recording sheet P are fixed.

As shown in FIGS. 19 and 20, the central shaft 162a integrated with the spur 162 is fitted to the conveyance guide member 163, and the spur 162 is rotatable with respect to the conveyance guide member 163. The recording sheet P on which the toner image is formed, is conveyed on the spur 162. The protruded portion 162b of the spur 162 driven by the recording sheet P is stained by the reverse side toner image, and a stain by the image is generated on the conveyed recording sheet P by the toner adhered onto the protruded portion 162b. Therefore, a cleaning member 210 is provided so that toner adhered onto the protruded portion 162b is cleaned. Further, the guide surface 163a of the conveyance guide member 163 is provided on the side of passage of the recording sheet P rather than the center of the spur 162, so that taking up of the leading edge of the recording sheet P after separation of the recording sheet P from the toner image receiving body 14a, described in FIG. 5, is conducted. Thereby, the frictional damage of the toner image due to falling of the leading edge portion of the recording sheet P at the time of entrance of the transfer material into the conveyance section, or due to falling of the trailing edge at the time of passing through the conveyance section, can be prevented.

As shown in FIG. 20, the cleaning member 210 is composed of a cleaning brush 211 and a brush holder 212 to hold the cleaning brush 211. In FIG. 20, the cleaning brush

211 is provided in a position opposite to the spur 162, however, the brush section may be continuously provided.

By using the brush member as the cleaning member, the rotation of the spur is finely maintained, and the spur is satisfactorily cleaned.

As shown in FIG. 19, the cleaning member 210 is arranged such that a leading edge of the cleaning brush 211 is on the downstream side of the rotational direction of the spur 162 on the opposite side of the passage side of the recording sheet P, and the leading edge portion of the cleaning brush 211 is in contact with the protruded portion 162b. When whiskers of the cleaning brush 211 are parallelly arranged, the rotation of the spur 162 is not disturbed and the toner adhered to the protruded portion 162b is cleaned. In order to finely clean the adhered toner, a coarse-whiskered brush is preferable. Further, when the protruded portion 162b comes into deep-contact with the brush of the cleaning brush 211, the spur 162 is faultily rotated, therefore, it is preferable that the protruded portion 162b is in shallow-contact with the brush, for example, with about 0.5–1.5 mm depth of the leading edge portion.

Due to the above description, the cleaning member is arranged so that the conveyance of the transfer material is not disturbed.

Further, as shown in FIG. 21, the following may also be possible: the cleaning member 210 is arranged in such a manner that the cleaning member 210 is almost vertically provided on the lower side of the rotating section of the spur 162 on the opposite side of the passage side of the recording sheet P, and the leading edge portion of the cleaning brush 211 comes into contact with the protruded portion 162b, so that the toner adhered to the protruded portion 162b is cleaned. In this case, the protruded portion 162b can more deeply be in contact with the brush, rather than in the case where the cleaning brush 211 is horizontally provided. However, when the protruded portion 162b is in deep-contact with the brush of the cleaning brush 211, the spur is faultily rotated, therefore, it is preferable that about 1.0–2.0 mm depth of the leading edge portion is in contact with the brush.

Owing to the above description, the cleaning member is arranged such that the conveyance of the transfer material is not disturbed.

Further, as shown in FIG. 22, the following is also possible: the cleaning member 210 is arranged on the guide surface 163a of the conveyance guide member 162 on the passage side of the recording sheet P, and the leading edge of the cleaning brush 211 of the cleaning member 210 is in contact with the protruded portion 162b of the spur 162, thereby, the toner adhered to the protruded portion 162b is cleaned. The brush surface of the cleaning brush 211 may also be arranged on the same surface as the guide surface 163a. In FIG. 24, the cleaning member 210 is arranged on the downstream side of the rotational direction of the spur 162 with respect to the contact position with the recording sheet P, however, it may also be allowable that the cleaning member 210 is arranged on the guide surface 163a of the conveyance guide member 163, or on the same surface as the guide surface 163a on the upstream side, so that the leading edge of the brush of the cleaning brush 211 is in contact with the protruded portion 162b.

Owing to the description in FIGS. 19 to 22 a position where recording paper P is separated from toner image receiving body 14a, the spur is finely cleaned and the spur is prevented from staining.

Further, as the example of the two-sided image forming apparatus, the color image forming apparatus is described,

however, the present invention is not necessarily limited to that, but it can also be applied for a monochromatic two-sided image forming apparatus in the same process as that described in FIG. 1.

Further, in the image forming apparatus of the present invention, other than the two-sided image formation by which the images are formed on both sides of the transfer material as described in examples, of course, the single-side image formation by which the image is formed on the single side, that is, only on the obverse side or reverse side of the transfer material, can be conducted.

As described above, according to the present invention, generation of the spur track onto the toner image on the transfer material and toner contamination of a transfer material due to contamination of spur are prevented, and a frictional damage of the image when the transfer material is nipped in the fixing means is prevented.

The spur is finely cleaned, and the spur is prevented from staining.

The rotation of the spur is finely maintained, and the spur is finely cleaned.

The frictional damage of the toner image caused by falling of the leading edge portion at the time of entry of the transfer material into the conveyance section, and by falling of the trailing edge at the time of passage of the trailing edge through the conveyance section, is prevented.

The cleaning member is arranged so that conveyance of the transfer material is not prevented.

According to the present invention, the transfer material has no pulling force which lowers the image quality, and has an adequate slack stably, in the conveyance process of the transfer material to the fixing means from second image carrier means, thereby, there is no possibility to disturb the toner image, and the transfer sheet is successively conveyed to the transfer area and, next, to the fixing area.

When the transfer material is delivered to each area, the toner image is prevented from being disturbed, and the safety and reliability are assured. The excessive slack of the transfer material is prevented, and generation of conveyance failure such as jamming is prevented.

As the result, an image forming apparatus is provided in which the conveyance characteristics of the transfer material, on both sides of which toner images are held, are stable and satisfactory, and the formed image is not deteriorated and can be recorded with the high quality.

What is claimed is:

1. An apparatus for forming an image, comprising:

a first image carrying member;

toner image forming means for forming reverse side and obverse side toner images on the first image carrying member;

a belt-shaped second image carrying member onto which the reverse side toner image is transferred;

a first transfer member for transferring the obverse side toner image from the first image carrying member to a first side of a sheet;

a second transfer member for transferring the reverse side toner image from the belt-shaped second image carrying member to a second side of the sheet;

a fixing device for simultaneously fixing the toner images transferred onto the first and second sides of the sheet, the fixing device forming a nip region between a pair of rotatable fixing members and fixing the toner images onto the sheet by nipping and conveying the sheet through the nip region; and

a conveyance section comprising a spur wheel, provided between the belt-shaped second image carrying member and the fixing device, for conveying a leading edge portion of the sheet separated from an end of the belt-shaped second image carrying member to the fixing device,

wherein the belt-shaped second image carrying member is arranged to form a sheet conveying plane on which the sheet is conveyed toward the fixing device;

wherein the belt-shaped second image carrying member and the fixing device are arranged such that when the sheet is nipped and conveyed through the nip region, the sheet is conveyed so as to form a loop protruding above a connecting line that connects an entrance to the nip region and an end of the sheet conveying plane of the belt-shaped second image carrying member, and

wherein a top of the spur wheel of the conveyance section is located beneath the connecting line.

2. The apparatus of claim 1, wherein the loop is protruded from a plane extended from the sheet conveying plane of the belt-shaped second image carrying member.

3. The apparatus of claim 1, wherein the loop is protruded from an extended plane of the sheet conveying plane of the belt-shaped second image carrying member toward an opposite side of the conveyance section.

4. The apparatus of claim 1, wherein the conveyance section comprises a linear guide member extended in a direction of sheet conveyance.

5. The apparatus of claim 1, wherein the conveyance section and the belt-shaped second image carrying member are located at a same side of a plane extended from the sheet conveying plane of the belt-shaped second image carrying member.

6. The apparatus of claim 1, wherein the sheet forms the loop in accordance with a shape of the nip region of the fixing device and the belt-shaped second image carrying member.

7. The apparatus of claim 6, wherein the nip region is shaped to protrude from a line connecting the entrance to and an exit from the nip region toward a same side of the conveyance section.

8. The apparatus of claim 7, wherein a first one of the pair of rotatable fixing members comprises a soft roller and a second one of the pair of rotatable fixing members comprises a hard roller.

9. The apparatus of claim 7, wherein the nip region of the fixing device is shaped to protrude toward the second side of the sheet.

10. The apparatus of claim 7 wherein the pair of rotatable fixing members and the belt-shaped second image carrying member are arranged such that a first one of the pair of rotatable fixing members contacts the first side of the sheet and a plane extended from the sheet conveying plane of the belt-shaped second image carrying member collides with the first one of the pair of rotatable fixing members.

11. The apparatus of claim 8, wherein the soft roller is arranged to be brought into pressure contact with the hard roller so that the soft roller is deformed to form the nip region.

12. The apparatus of claim 1, wherein a first one of the pair of rotatable fixing members is arranged to contact the first side of the sheet and a plane extended from the sheet conveying plane of the belt-shaped second image carrying member intersects with the first one of the pair of rotatable fixing members.

13. The apparatus of claim 1, wherein a first one of the pair of rotatable fixing members is arranged to contact the

first side of the sheet and a second guide member is provided between the conveyance section and the fixing device and causes the sheet to collide with the first one of a pair of rotatable fixing members.

- 14.** An apparatus for forming an image, comprising: 5  
 a first image carrying member;  
 toner image forming means for forming reverse side and obverse side toner images on the first image carrying member;  
 a belt-shaped second image carrying member onto which the reverse side toner image is transferred; 10  
 a first transfer member for transferring the obverse side toner image from the first image carrying member to a first side of a sheet;  
 a second transfer member for transferring the reverse side toner image from the belt-shaped second image carrying member to a second side of the sheet; 15  
 a fixing device for simultaneously fixing the toner images transferred onto the first and second sides of the sheet, the fixing device forming a nip region between a pair of rotatable fixing members and fixing the toner images onto the sheet by nipping and conveying the sheet through the nip region; and 20  
 a conveyance section, provided between the belt-shaped second image carrying member and the fixing device, for guiding the sheet separated from an end of the belt-shaped second image carrying member to the fixing device, 25  
 wherein the belt-shaped second image carrying member is arranged to form a sheet conveying plane on which the sheet is conveyed toward the fixing device;  
 wherein the belt-shaped second image carrying member and the fixing device are arranged such that when the sheet is nipped and conveyed through the nip region, the sheet is conveyed so as to form a loop protruding from a connecting line that connects an entrance to the nip region and an end of the sheet conveying plane of the belt-shaped second image carrying member, 30  
 wherein the sheet forms the loop in accordance with a shape of the nip region and the belt-shaped second image carrying member, and 40  
 wherein the pair of rotatable fixing members are arranged such that a line connecting the entrance to and an exit from the nip region is inclined relative to a plane extended from the sheet conveying plane of the belt-shaped second image carrying member. 45
- 15.** The apparatus of claim **14**, wherein the pair of rotatable fixing members are soft rollers. 50
- 16.** The apparatus of claim **14**, wherein the belt-shaped second image carrying member and the conveyance section are located at a same side of the line connecting the entrance to and the exit from the nip region.

- 17.** An apparatus for forming an image, comprising: 55  
 a first image carrying member;  
 toner image forming means for forming reverse side and obverse side toner images on the first image carrying member;  
 a belt-shaped second image carrying member onto which the reverse side toner image is transferred; 60  
 a first transfer member for transferring the obverse side toner image from the first image carrying member to a first side of a sheet;  
 a second transfer member for transferring the reverse side toner image from the belt-shaped second image carrying member to a second side of the sheet; 65

a fixing device for simultaneously fixing the toner images transferred onto the first and second sides of the sheet, the fixing device forming a nip region between a pair of rotatable fixing members and fixing the toner images onto the sheet by nipping and conveying the sheet through the nip region; and

a conveyance section, provided between the belt-shaped second image carrying member and the fixing device, for guiding the sheet separated from an end of the belt-shaped second image carrying member to the fixing device,

wherein the belt-shaped second image carrying member is arranged to form a sheet conveying plane on which the sheet is conveyed toward the fixing device;

wherein the belt-shaped second image carrying member and the fixing device are arranged such that when the sheet is nipped and conveyed through the nip region, the sheet is conveyed so as to form a loop protruding from a connecting line that connects an entrance to the nip region and an end of the sheet conveying plane of the belt-shaped second image carrying member, and

wherein a sheet conveying speed of the fixing device is set to be slower than a sheet conveying speed of the belt-shaped second image carrying member.

**18.** The apparatus of claim **17**, wherein the loop is maintained by a difference in the conveying speed between the fixing device and the belt-shaped second image carrying member.

**19.** The apparatus of claim **17**, wherein the nip region is shaped to protrude from a line connecting the entrance to and an exit from the nip region toward a same side of the conveyance section.

**20.** The apparatus of claim **17**, wherein the pair of rotatable fixing members are arranged such that a line connecting the entrance to and an exit from the nip region is inclined relative to a plane extended from the sheet conveying plane of the belt-shaped second image carrying member.

**21.** The apparatus of claim **20**, wherein the belt-shaped second image carrying member and the conveyance section are located at a same side of the line connecting the entrance to and the exit from the nip region.

**22.** The apparatus of claim **17**, wherein the sheet conveying speed of the fixing device and the sheet conveying speed of the belt-shaped second image carrying member are controlled such that a maximum height of the loop is kept lower than a predetermined height.

**23.** The apparatus of claim **22**, wherein the sheet conveying speed  $V_2$  (mm/sec.) of the fixing device and the sheet conveying speed  $V_1$  (mm/sec.) of the belt-shaped second image carrying member satisfy the following formula,

$$0.01 \times V_2 \leq V_1 - V_2 \leq (L_2 \times 0.05 / L_1) \times V_2$$

wherein a maximum length of the sheet in a direction of sheet conveyance is  $L_1$  (mm) and a shortest distance between a separating position at which the sheet is separated from the belt-shaped second image carrying member and an entrance to the nip region of the fixing device is  $L_2$  (mm).

**24.** An apparatus for forming an image, comprising:

- a first image carrying member;  
 toner image forming means for forming reverse side and obverse side toner images on the first image carrying member;  
 a belt-shaped second image carrying member onto which the reverse side toner image is transferred;

31

a first transfer member for transferring the obverse side toner image from the first image carrying member to a first side of a sheet;

a second transfer member for transferring the reverse side toner image from the belt-shaped second image carrying member to a second side of the sheet;

a fixing device for simultaneously fixing the toner images transferred onto the first and second sides of the sheet, the fixing device forming a nip region between a pair of rotatable fixing members and fixing the toner images onto the sheet by nipping and conveying the sheet through the nip region;

a separating section, provided at a fixing device-side end of the belt-shaped second image carrying member, for separating the sheet from the belt-shaped second image carrying member; and

a conveyance section, provided between the belt-shaped second image carrying member and the fixing device, for guiding the sheet separated from the belt-shaped second image carrying member to the fixing device, wherein the belt-shaped second image carrying member is arranged to form a sheet conveying plane on which the sheet is conveyed toward the fixing device;

wherein the belt-shaped second image carrying member and the fixing device are arranged such that when the sheet is nipped and conveyed through the nip region, the sheet is conveyed so as to form a loop protruding from a connecting line that connects an entrance to the nip region and an end of the sheet conveying plane of the belt-shaped second image carrying member, and

wherein the fixing device, the conveyance section and the belt-shaped second image carrying member are arranged such that the conveyance section and the separating section are located at a same side of a plane extended from an entrance to the nip region, and

wherein the nip region is shaped to protrude from a line connecting the entrance to and an exit from the nip region toward a same side of the conveyance section.

25. The apparatus of claim 24, wherein a roller member to support the belt-shaped second image carrying member is provided at the separating section to form a curved portion so that the sheet is separated by a curvature of the curved portion.

26. The apparatus of claim 24, wherein a sheet conveying speed of the fixing device is set to be slower than a sheet conveying speed of the belt-shaped second image carrying member.

27. The apparatus of claim 24, wherein the entrance to the nip region is located at a second side of the sheet from the sheet conveying plane of the belt-shaped second image carrying member, and wherein a distance L parallel to the sheet conveying plane between the entrance to the nip region and the separating section and a distance H perpendicular to

32

the sheet conveying plane between the entrance to the nip region and the separating section satisfy the following formula:

$$0.02 \leq H/L \leq 0.1$$

28. An apparatus for forming an image, comprising:  
 a first image carrying member;  
 toner image forming means for forming reverse side and obverse side toner images on the first image carrying member;  
 a belt-shaped second image carrying member onto which the reverse side toner image is transferred;  
 a first transfer member for transferring the obverse side toner image from the first image carrying member to a first side of a sheet;  
 a second transfer member for transferring the reverse side toner image from the belt-shaped second image carrying member to a second side of the sheet;  
 a fixing device for simultaneously fixing the toner images transferred onto the first and second sides of the sheet, the fixing device forming a nip region between a pair of rotatable fixing members and fixing the toner images onto the sheet by nipping and conveying the sheet through the nip region; and  
 a conveyance section, provided between the belt-shaped second image carrying member and the fixing device, for guiding the sheet separated from an end of the belt-shaped second image carrying member to the fixing device,  
 wherein the belt-shaped second image carrying member is arranged to form a sheet conveying plane on which the sheet is conveyed toward the fixing device;

wherein the belt-shaped second image carrying member and the fixing device are arranged such that when the sheet is nipped and conveyed through the nip region, the sheet is conveyed so as to form a loop protruding from a connecting line that connects an entrance to the nip region and an end of the sheet conveying plane of the belt-shaped second image carrying member, and

wherein the conveyance section comprises a rotatable spur wheel and a cleaning member arranged to contact a tip end of the spur wheel so as to clean the spur wheel.

29. The apparatus of claim 28, wherein the cleaning member comprises a brush member.

30. The apparatus of claim 28, wherein the conveyance section comprises a guide member extended in a direction of sheet conveyance, and the guide member is arranged between the conveyed sheet and a center of the spur wheel.

31. The apparatus of claim 30, wherein the cleaning member is located at a same side as the center of the spur wheel with respect to the guide member.

32. The apparatus of claim 30, wherein the cleaning member is located at an opposite side to the center of the spur wheel with respect to the guide member.

\* \* \* \* \*