



(22) **Date de dépôt/Filing Date:** 2002/08/01

(41) **Mise à la disp. pub./Open to Public Insp.:** 2003/02/01

(45) **Date de délivrance/Issue Date:** 2015/09/22

(62) **Demande originale/Original Application:** 2 396 483

(30) **Priorité/Priority:** 2001/08/01 (CA2,354,611)

(51) **Cl.Int./Int.Cl.** **B61F 5/12** (2006.01),
B61D 3/10 (2006.01), **B61D 3/18** (2006.01),
B61F 5/04 (2006.01)


(72) **Inventeur/Inventor:**
FORBES, JAMES W., CA

(73) **Propriétaire/Owner:**
NATIONAL STEEL CAR LIMITED, CA

(74) **Agent:** BERESKIN & PARR LLP/S.E.N.C.R.L.,S.R.L.

(54) **Titre : WAGON A MARCHANDISES AVEC SUSPENSION A AMORTISSEMENT**

(54) **Title: RAIL ROAD FREIGHT CAR WITH DAMPED SUSPENSION**



(57) **Abrégé/Abstract:**

An auto rack rail road freight car is provided for carrying low density, relatively high value, relatively fragile lading. The car has trucks that have multiple dampers in a four corner arrangement in the sideframes. The spring groups in the side frames are relatively soft, giving a low vertical bounce natural frequency. In an articulated embodiment, differentially placed ballast is mounted in a biased arrangement to load the coupler end trucks to encourage a dynamic response similar to the dynamic response of the internal trucks.

RAIL ROAD FREIGHT CAR WITH DAMPED SUSPENSION**Abstract of the Disclosure**

An auto rack rail road freight car is provided for carrying low density, relatively high value, relatively fragile lading. The car has trucks that have multiple dampers in a four corner arrangement in the sideframes. The spring groups in the side frames are relatively soft, giving a low vertical bounce natural frequency. In an articulated embodiment, differentially placed ballast is mounted in a biased arrangement to load the coupler end trucks to encourage a dynamic response similar to the dynamic response of the internal trucks.

RAIL ROAD FREIGHT CAR WITH DAMPED SUSPENSION

Field of the Invention

5 This invention relates to the field of rail road freight cars.

Background of the Invention

10 This invention can be used with the invention described in my US Patent No. 6,659,016 entitled Rail Road Freight Car with Resilient Suspension, filed August 1, 2001.

15 Auto rack rail road cars are used to transport automobiles. Typically, auto-rack rail road cars are loaded in the "circus loading" manner, by driving vehicles into the cars from one end, and securing them in places with chocks, chains or straps. When the trip is completed, the chocks are removed, and the cars are driven out.

20 Automobiles are a high value, relatively fragile type of lading. Damage due to dynamic loading in the railcar may tend to arise principally in two ways. First, there are the longitudinal input loads transmitted through the draft gear due to train line action or shunting. Second, there are vertical, rocking and transverse dynamic responses of the rail road car to track perturbations as transmitted through the rail car suspension. It would be desirable to improve ride quality to lessen the chance of damage occurring.

25 In the context of longitudinal train line action, damage most often occurs from two sources (a) slack run-in and run out; (b) humping or flat switching. Rail road car draft gear have been designed against slack run-out and slack run-in during train operation, and also against the impact as cars are coupled together. Historically, common types of draft gear, such as that complying with, for example, AAR specification M-901-G, have been rated to withstand an impact at 5 m.p.h. (8 km/h) at a coupler force of 30 500,000 Lbs. (roughly 2.2×10^6 N). Typically, these draft gear have a travel of $2 \frac{3}{4}$ to $3 \frac{1}{4}$ inches in buff before reaching the 500,000 Lbs. load, and before "going solid". The term "going solid" refers to the point at which the draft gear exhibits a steep increase in resistance to further displacement. If the impact is large enough to make the draft gear 35 "go solid" then the force transmitted, and the corresponding acceleration imposed on the lading, increases sharply. While this may be acceptable for ores, coal or grain, it is

undesirably severe for more sensitive lading, such as automobiles or auto parts, rolls of paper, fresh fruit and vegetables and other high value consumer goods such as household appliances or electronic equipment. Consequently, from the relatively early days of the automobile industry there has been a history of development of longer travel draft gear to provide lading protection for relatively high value, low density lading, in particular automobiles and auto parts, but also farm machinery, or tractors, or highway trailers.

Historically, the need for slack was related, at least in part, to the difficulty of using a steam locomotive to “lift” (that is, move from a standing start) a long string of rail road cars with journal bearings, particularly in cold weather. For practical purposes, presently available diesel-electric locomotives are capable of lifting a unit train of one type of cars having little or no slack. Given the availability of locomotives that develop continuous high torque from a standing start, it is possible to re-examine the issue of slack action from basic principles. By eliminating, or reducing, the accumulation of slack, the use of short travel buff gear may tend to reduce the relative longitudinal motion between adjacent rail road cars, and may tend to reduce the associated velocity differentials and accelerations between cars. The use of short travel, or ultra-short travel, buff gear also has the advantage of eliminating the need for relatively expensive, and relatively complicated EOCC units, and the fittings required to accommodate them.

In terms of dynamic response through the trucks, there are a number of loading conditions to consider. First, there is a direct vertical response in the “vertical bounce” condition. This may typically arise when there is a track perturbation in both rails at the same point, such as at a level crossing or at a bridge or tunnel entrance where there may be a relatively sharp discontinuity in track stiffness. A second “rocking” loading condition occurs when there are alternating track perturbations, typically such as used formerly to occur with staggered spacing of 39 ft rails. This phenomenon is less frequent given the widespread use of continuously welded rails, and the generally lower speeds, and hence lower dynamic forces, used for the remaining non-welded track. A third loading condition arises from elevational changes between the tracks, such as when entering curves in which case a truck may have a tendency to warp. A fourth loading condition arises from truck “hunting”, typically at higher speeds, where the truck oscillates transversely between the rails. During hunting, the trucks tend most often to deform in a parallelogram manner. Fifth, lateral perturbations in the rails sometimes arise where the rails widen or narrow slightly, or one rail is more worn than another, and so on.

There are both geometric and historic factors to consider related to these loading conditions. One historic factor is the near universal usage of the three-piece style of freight car truck in North America. While other types of truck are known, the three piece truck is overwhelmingly dominant in freight service in North America. The three piece truck relies on a primary suspension in the form of a set of springs trapped in a “basket” between the truck bolster and the side frames. For wheel load equalisation, a three piece truck uses one set of springs, and the side frames pivot about the truck bolster ends in a manner like a walking beam. The *1980 Car & Locomotive Cyclopedia*, states at page 669 that the three piece truck offers “interchangeability, structural reliability and low first cost but does so at the price of mediocre ride quality and high cost in terms of car and track maintenance”. It would be desirable to retain many or all of these advantages while providing improved ride quality.

In terms of rail road car truck suspension loading regimes, the first consideration is the natural frequency of the vertical bounce response. The static deflection from light car (empty) to maximum laded gross weight (full) of a rail car at the coupler tends to be typically about 2 inches. In addition, rail road car suspensions have a dynamic range in operation, including a reserve travel allowance.

In typical historical use, springs were chosen to suit the deflection under load of a full coal car, or a full grain car, or fully loaded general purpose flat car. In each case, the design lading tended to be very heavy relative to the rail car weight. For example, the live load for a 286,000 lbs. car may be of the order of five times the weight of the dead sprung load (i.e., the weight of the car, including truck bolsters but less side frames, axles and wheels). Further, in these instances, the lading may not be particularly sensitive to abusive handling. That is, neither coal nor grain tends to be badly damaged by poor ride quality. As a result, these cars tend to have very stiff suspensions, with a dominant natural frequency in vertical bounce mode of about 2 Hz. when loaded, and about 4 to 6 Hz. when empty. Historically, much effort has been devoted to making freight cars light for at least two reasons. First, the weight to be back hauled empty is kept low, reducing the fuel cost of the backhaul. Second, as the ratio of lading to car weight increases, a higher proportion of hauling effort goes into hauling lading, rather than hauling the railcar.

By contrast, an autorack car, or other type of car for carrying relatively high value, low density lading such as auto parts, electronic consumer goods, or white goods

more generally, has the opposite loading profile. A two unit articulated autorack car may have a light car (i.e., empty) weight of 165,000 lbs., and a lading weight when fully loaded of only 35 – 40,000 lbs., per car body unit. That is, not only may the weight of the lading be less than the sprung weight of the rail road car unit, it may be less than 40 % of the car weight. The lading typically has a high, or very high, ratio of value to weight. Unlike coal or grain, automobiles are relatively fragile, and hence more sensitive to a gentle (or a not so gentle) ride. As a relatively fragile, high value, high revenue form of lading, it may be desirable to obtain superior ride quality to that suitable for coal or grain.

One way to improve ride quality is to increase the dead sprung weight of the rail road car body. Another way to improve ride quality is to decrease the spring rate. Decreasing the spring rate involves further considerations. Historically the deck height of a flat car tended to be very closely related to the height of the upper flange of the center sill. This height was itself established by the height of the cap of the draft pocket. The size of the draft pocket was standardised on the basis of the coupler chosen, and the allowable heights for the coupler knuckle. The deck height usually worked out to about 41 inches above top of rail. For some time auto rack cars were designed to a 19 ft height limit. To maximise the internal loading space, it has been considered desirable to lower the main deck as far as possible, particularly in tri-level cars. Since the lading is relatively light, the rail car trucks have tended to be light as well, such as 70 Ton trucks, as opposed to 100, 110 or 125 Ton trucks for coal, ore, or grain cars at 263,000, 286,000 or 315,000 lbs. gross weight on rail. Since the American Association of Railroads (AAR) specifies a minimum clearance of 5” above the wheels, the combination of low deck height, deck clearance, and minimum wheel height set an effective upper limit on the spring travel, and reserve spring travel range available. If softer springs are used, the remaining room for spring travel below the decks may well not be sufficient to provide the desired reserve height. In consequence, the present inventor proposes, contrary to lowering the main deck, that the main deck be higher than 42 inches to allow for more spring travel.

As noted above, many previous auto rack cars have been built to a 19 ft height. Another major trend in recent years has been the advent of “double stack” intermodal container cars capable of carrying two shipping containers stacked one above the other in a well or to other freight cars falling within the 20 ft 2 in. height limit of AAR plate H. Many main lines have track clearance profiles that can accommodate double stack cars.

Consequently, it is now possible to use auto rack cars built to the higher profile of the double stack intermodal container cars.

While decreasing the primary vertical bounce natural frequency appears to be advantageous for auto rack rail road cars generally, including single car unit auto rack rail road cars, articulated auto rack cars may also benefit not only from adding ballast, but from adding ballast preferentially to the end units near the coupler end trucks. As explained more fully in the description below, the interior trucks of articulated cars tend to be more heavily burdened than the end trucks, primarily because the interior trucks share loads from two adjacent car units, while the coupler end trucks only carry loads from one end of one car unit. It would be advantageous to even out this loading so that the trucks have roughly similar vertical bounce frequencies.

Three piece trucks currently in use tend to use friction dampers, sometimes assisted by hydraulic dampers such as can be mounted, for example, in the spring set. Friction damping has most typically been provided by using spring loaded blocks, or snubbers, mounted with the spring set, with the friction surface bearing against a mating friction surface of the columns of the side frames, or, if the snubber is mounted to the side frame, then the friction surface is mounted on the face of the truck bolster. There are a number of ways to do this. In some instances, as shown at p. 847 of the *1984 Car & Locomotive Cyclopedia* lateral springs are housed in the end of the truck bolster, the lateral springs pushing horizontally outward on steel shoes that bear on the vertical faces of the side columns of the side frames. This provides roughly constant friction (subject to the wear of the friction faces), without regard to the degree of compression of the main springs of the suspension.

In another approach, as shown at p. 715 of the *1997 Car & Locomotive Cyclopedia*, one of the forward springs in the main spring group, and one of the rearward springs in the main spring group bear upon the underside, or short side, of a wedge. One of the long sides, typically an hypotenuse of a wedge, engages a notch, or seat, formed near the outboard end of the truck bolster, and the third side has the friction face that abuts, and bears against, the friction face of the side column (either front or rear, as the case may be), of the side frame. The action of this pair of wedges then provides damping of the various truck motions. In this type of truck the friction force varies directly with the compression of the springs, and increases and decreases as the truck flexes. In the vertical bounce condition, both friction surfaces work in the same direction. In the

warping direction (when one wheel rises or falls relative to the other wheel on the same side, thus causing the side frame to pivot about the truck bolster) the friction wedges work in opposite directions against the restoring force of the springs.

5 The “hunting” phenomenon has been noted above. Hunting generally occurs on tangent (i.e., straight) track as railcar speed increases. It is desirable for the hunting threshold to occur at a speed that is above the operating speed range of the rail car. During hunting the side frames tend to want to rotate about a vertical axis, to a non-perpendicular angular orientation relative to the truck bolster sometimes called
10 “parallelogramming” or lozenging. This will tend to cause angular deflection of the spring group, and will tend to generate a squeezing force on opposite diagonal sides of the wedges, causing them to tend to bear against the side frame columns. This diagonal action will tend to generate a restoring moment working against the angular deflection. The moment arm of this restoring force is proportional to half the width of the wedge,
15 since half of the friction plate lies to either side of the centreline of the side frame. This tends to be a relatively weak moment connection, and the wedge, even if wider than normal, tends to be positioned over a single spring in the spring group.

20 Typically, for a truck of fixed wheelbase length, there is a trade-off between wheel load equalisation and resistance to hunting. Where a car is used for carrying high density commodities at low speeds, there may tend to be a higher emphasis on maintaining wheel load equalisation. Where a car is light, and operates at high speed there will be a greater emphasis on avoiding hunting. In general, the parallelogram deformation of the truck in hunting is deterred by making the truck laterally more stiff.
25 One approach to discouraging hunting is to use a transom, typically in the form of a channel running from between the side frames below the spring baskets. Another approach is to use a frame brace.

30 One way to address the hunting issue is to employ a truck having a longer wheelbase, or one whose length is proportionately great relative to its width. For example, at present two axle truck wheelbases may range from about 5' – 3" to 6' – 0". However, the standard North America track gauge is 4' – 8 ½", giving a wheelbase to track width ratio possibly as small as 1.12. At 6' – 0" the ratio is roughly 1.27. It would be preferable to employ a wheelbase having a longer aspect ratio relative to the track
35 gauge. As described herein, one aspect of the present invention employs a truck with a longer wheelbase, preferably about 80 or 86 inches, giving a ratio of 1.42 or 1.52. This

increase in wheelbase length may tend also to be benign in terms of wheel loading equalisation.

5 In a typical spring seat and spring group arrangement, the side frame window may typically be of the order of 21 inches in height from the spring seat base to the underside of the overarching compression member, and the width of the side frame window between the wear plates on the side frame columns is typically about 18", giving a side frame window that is taller than wide in the ratio of about 7:6. Similarly, the bottom spring seat has a base that is typically about 18 inches long to correspond to the width of 10 the side frame window, and about 16 inches wide in the transverse direction, that is being longer than wide. It may be advantageous to make the side frame windows wider, and the spring seat correspondingly longer to accommodate larger diameter long travel springs with a softer spring rate. At the same time, lengthening the wheel base of the truck may also be advantageous since it is thought that a longer wheelbase may 15 ameliorate truck hunting performance, as noted above. Such a design change is counter-intuitive since it may generally be desired to keep truck size small, and widening the unsupported window span may not have been considered desirable heretofore.

20 Another way to raise the hunting threshold is to increase the parallelogram stiffness between the bolster and the side frames. It is possible, as described herein, to employ pairs of wedges, of comparable size to those previously used, the two wedges being placed side by side and each individually supported by a different spring, or being the outer two wedges in a three deep spring group, to give a larger moment arm to the restoring force and to the damping associated with that force.

25 The use of multiple variable friction force dampers in which the wedges are mounted over members of the spring group, is shown in US Patent 3,714,905 of Barber, issued February 6, 1973. The damper arrangement shown by Barber is not apparently presently available in the market, and does not seem ever to have been made available 30 commercially.

35 Notably, the damper wedges shown in Barber appear to have relatively sharply angled wedges, with an included angle between the friction face (i.e., the face bearing against the side frame column) and the sliding face (i.e., the angled face seated in the damper pocket formed in the bolster, typically the hypotenuse) of roughly 35 degrees. The angle of the third, or opposite, horizontal side face, namely the face that seats on top

of the vertically oriented spring, is the complementary angle, in this example, being about 55 degrees. It should be noted that as the angle of the wedge becomes more acute, (i.e., decreasing from about 35 degrees) the wedge may have an undesirable tendency to jam in the pocket, rather than slide.

5

Barber, above, shows a spring group of variously sized coils with four relatively small corner coils loading the four relatively sharp angled dampers. From the relative sizes of the springs illustrated, it appears that Barber was contemplating a spring group of relatively traditional capacity – a load of about 80,000 lbs., at a “solid” condition of 3 1/16 inches of travel, for example, and an overall spring rate for the group of about 25,000 lbs/inch, to give 2 inches of overall rail car static deflection for about 200,000 lbs live load.

10

Apparently keeping roughly the same relative amount of damping overall as for a single damper, Barber appears to employ individual B331 coils ($k = 538$ lb/in, (+/-)) under each friction damper, rather than a B432 coil ($k = 1030$ lb/in, (+/-)) as might typically have been used under a single damper for a spring group of the same capacity. As such, it appears that Barber contemplated that springs accounting for somewhat less than 15 % of the overall spring group stiffness would underlie the dampers.

15

20

These spring stiffnesses might typically be suitable for a rail road car carrying iron ore, grain or coal, where the lading is not overly fragile, and the design ratio of live load to dead sprung load is typically greater than 3: 1. It might not be advantageous for a rail road car for transporting automobiles, auto parts, consumer electronics or other white goods of relatively low density and high value where the design ratio of live load to dead sprung load may be well less than 2: 1, and quite possibly lying in the range of 0.4: 1 to 1: 1.

25

It has been noted that the frictional force produced by friction damper wedges differs depending on whether the damper is being loaded, or unloaded. In the terminology employed, the damper is being “loaded” when the bolster is moving downward in the sideframe window, since the spring force is increasing, and hence the load, or force on the damper is increasing. Similarly, the damper is being “unloaded” when the bolster is moving upward toward the top of the sideframe window, since the force in the springs, and hence the load in the wedges, is decreasing.

30

35

The equations can be written as

$$\text{While loading: } F_d = \mu_c F_s \frac{(\cot(\phi) - \mu_s)}{1 + (\mu_s - \mu_c) \cot(\phi) + \mu_s \mu_c}$$

5

$$\text{While unloading: } F_d = \mu_c F_s \frac{(\cot(\phi) + \mu_s)}{1 + (\mu_s - \mu_c) \cot(\phi) + \mu_s \mu_c}$$

Where: F_d = friction force on the sideframe column

10

F_s = force in the spring

μ_s = friction coefficient of the angled face on the bolster

μ_c is the coefficient of friction against the sideframe column

ϕ is the included angle between the angled face on the bolster and the friction face bearing against the column

15

For a given angle, a friction load factor, C_f can be determined as $C_f = F_d / F_s$. This load factor C_f will tend to be different depending on whether the bolster is moving up or down. A graph of upward and downward load factors as a function of wedge angle is shown in Figure 7 based on a μ_s of 0.2 and a μ_c of 0.4, values which are thought to be roughly representative of service conditions.

20

When the wheels encounter a perturbation in the rail, their reaction to the perturbation will tend to transmit a force through the suspension into the rail road car body. The force transmitted will tend to be the sum of the spring force plus the friction force in the dampers. For a relatively gentle ride, it is desirable that the damping force as the wheels move up relative to the carbody not be excessive, and that the damping be stronger when the car body is moving upward relative to the wheels.

25

With a relatively sharply angled wedge, as typified by wedges in the 30 - 35 degree range such as appear to be shown by Barber, and as employed in wedges known to be commonly in use, the load factor may tend to be significantly higher when the bolster is moving downward relative to the side frame than when the bolster is moving upward. It may be desirable to lessen, or reverse this relationship, as may tend to occur for angles above about 40 to 45 degrees. (See Figure 7).

30

35

In the past, spring groups have been arranged such that the spring loading under the dampers has been proportionately small. That is, the dampers have typically been seated on side spring coils, as shown in the AAR standard spring groupings shown in the 1997 *Car & Locomotive Cyclopedia* at pages 743 – 746, in which the side spring coils, inner and outer as may be, are often B321, B331, B421, B422, B432, or B433 springs as compared to the main spring coils, such that the springs under the dampers have lower spring rates than the other coil combinations in the other positions in the spring group. As such, the dampers may be driven by less than 15 % of the total spring stiffness of the group generally.

In US Patent 5,046,431 of Wagner, issued September 10, 1991, the standard inboard-and-outboard gib arrangement on the truck bolster was replaced by a single central gib mounted on the side frame column for engaging the shoulders of a vertical channel defined in the end of the truck bolster. In doing this, the damper was split into inboard and outboard portions, and, further, the inboard and outboard portions, rather than lying in a common transverse vertical plane, were angled in an outwardly splayed orientation.

Wagner's gib and damper arrangement may not necessarily be desirable in obtaining a desired level of ride quality. In obtaining a soft ride it may be desirable that the truck be relatively soft not only in the vertical bounce direction, but also in the transverse direction, such that lateral track perturbations can be taken up in the suspension, rather than be transmitted to the car body, (and hence to the lading), as may tend undesirably to happen when the gibs bottom out (i.e., come into hard abutting contact with the side frame) at the limit of horizontal travel.

The present inventor has found it desirable that there be an allowance for lateral travel of the truck bolster relative to the wheels of the order of 1 to 1 - ½ inches to either side of a neutral central position. Wagner does not appear to have been concerned with this issue. On the contrary, Wagner appears to show quite a tight gib clearance, with relatively little travel before solid contact. Furthermore, transverse displacement of the truck bolster relative to the side frame is typically resiliently resisted by the horizontal shear in the spring groups, and by the pendulum motion of the side frames rocking on the crowns of the bearing adapters, these two components being combined like springs in series. Wagner's canted dampers appear to make lateral translation of the bolster stiffer, rather than softer. This may not be advantageous for relatively fragile lading. In the view

of the present inventor, while it is advantageous to increase resistance to the hunting phenomenon, it may not be advantageous to do so at the expense of increasing lateral stiffness.

5 It is desirable that a relatively larger portion of the spring effort be used to load the dampers, with the employment of a larger damper wedge angle. As such, the same magnitude of damping force may tend to be achieved with a combination of relatively softer springs than previously used, with a larger included angle in the wedges. Alternatively, a greater damping force than before may be achieved with wedges having a
10 relatively modest angle with springs of the same stiffness as before, the included angle being chosen in the 45 to 65 degree range. The opportunity to vary wedge angle and spring stiffness thus gives an opportunity to tune the amount of damping in some measure. In addition, it would be advantageous to use a larger included angle in the wedge, both for these reasons, and because wedges with a larger included angle may tend
15 to be less prone to jamming and may result in more favourable dynamic behaviour as indicated by Figure 7.

 In the damper groups themselves, it is thought that parallelogram deflection of the truck such that the truck bolster is not perpendicular to the side frame, as during hunting,
20 may tend to cause the dampers to try to twist angularly in the damper seats. In that situation one corner of the damper may tend to be squeezed more tightly than the other. As a result, the tighter corner may try to retract relative to the less tight corner, causing the damper wedge to squirm and rotate somewhat in the pocket. This tendency to twist may also tend to reduce the squaring, or restoring force that tends to move the truck back
25 into a condition in which the truck bolster is square relative to the side frames.

 Consequently, it may be desirable to discourage this twisting motion by limiting the freedom to twist, as, for example, by introducing a groove or ridge, or keyway, or channel feature to govern the operation of the spring in the damper pocket. It may also
30 be advantageous to use a split wedge to discourage twisting, such that one portion of the wedge can move relative to the other, thus finding a different position in a linear sense without necessarily forcing the other portion to twist. Further still, it may be advantageous to employ a means for encouraging a laterally inboard portion of the damper, or damper group, to be biased to its most laterally inboard position, and a
35 laterally outboard portion of the damper, or the damper group, to be biased to its most laterally outboard position. In that way, the moment arm of the restoring force may tend

to remain closer to its largest value. One way to do this, as described in the description of the invention, below, is to add a secondary angle to the wedge.

In the terminology herein, wedges have a primary angle ϕ , namely the included angle between (a) the sloped damper pocket face mounted to the truck bolster, and (b) the side frame column face, as seen looking from the end of the bolster toward the truck center. This is the included angle described above. A secondary angle is defined in the plane of angle ϕ , namely a plane perpendicular to the vertical longitudinal plane of the (undeflected) side frame, tilted from the vertical at the primary angle. That is, this plane is parallel to the (undeflected) long axis of the truck bolster, and taken as if sighting along the back side (hypotenuse) of the damper.

The secondary angle β is defined as the lateral rake angle seen when looking at the damper parallel to the plane of angle ϕ . As the suspension works in response to track perturbations, the wedge forces acting on the secondary angle will tend to urge the damper either inboard or outboard according to the angle chosen. Inasmuch as the tapered region of the wedge may be quite thin in terms of vertical through-thickness, it may be desirable to step the sliding face of the wedge (and the co-operating face of the bolster seat) into two or more portions. This may be particularly so if the angle of the wedge is large.

Split wedges and two part wedges having a chevron, or chevron like, profile when seen in the view of the secondary angle can be used. Historically, split wedges have been deployed as a pair over a single spring, the split tending to permit the wedges to seat better, and to remain better seated, under twisting condition than might otherwise be the case. The chevron profile of a solid wedge may tend to have the same intent of preventing rotation of the sliding face of the wedge relative to the bolster in the plane of the primary angle of the wedge. Split wedges and compound profile wedges can be employed in pairs as described herein.

In a further variation, where a single broad wedge is used, with a compound or other profile, it may be desirable to seat the wedge on two or more springs in an inboard-and-outboard orientation to create a restoring moment such as might not tend to be achieved by a single spring alone. That is, even if a single large wedge is used, the use of two, spaced apart springs may tend to generate a restoring moment if the wedge tries to twist, since the deflection of one spring may then be greater than the other.

When the dampers are placed in pairs, either immediately side-by-side or with spacing between the pairs, the restoring moment for squaring the truck will tend not only to be due to the increase in compression to one set of springs due to the extra tendency to squeeze the dampers downward in the pocket, but due to the difference in compression between the springs that react to the extra squeezing of one diagonal set of dampers and the springs that act against the opposite diagonal pair that will tend to be less tightly squeezed.

The bolster is typically permitted to travel laterally to either side relative to the side frames, and for the side frames to have limited angular rotation about an axis parallel to the longitudinal axis of the rail car more generally. It is desirable that after an initial perturbation, the bolster return to a central, angularly squared position. An increase in the normal force at the friction face, as discussed, may tend to return the side frames to a "square" condition relative to the truck bolster. In sideways displacement, return of the truck to a centered position may tend to cease when the friction in the dampers matches the lateral restoring force in the spring groups. This tendency may be reduced by the tendency of the springs to return to a laterally centered position as the truck works in the vertical bounce and warp conditions. However, it may be desirable to enhance this restoring tendency. In the view of the present inventor it may be advantageous to install some, or all of the springs in the inner and outer rows of the spring group at a slight anhedral angle relative to each other, so that they form a symmetrical V.

Summary of the Invention

In an aspect of the invention there is a rail road freight car having at least one rail car unit. The rail road freight car is supported by three piece rail car trucks for rolling motion along rail road tracks. At least a first rail car truck of the three piece rail car trucks has a rigid truck bolster and a pair of first and second side frame assemblies. The truck bolster has first and second ends. The first rail car truck has a suspension including first and second spring groups mounted between the first and second ends of the truck bolster and the first and second side frames respectively. The rail car truck suspension has a natural vertical bounce frequency of less than 4.0 Hz. when the rail road freight car is unloaded. A first set of friction dampers is mounted between the truck bolster and the first side frame assembly. A second set of friction dampers is mounted between the truck

bolster and the second side frame assembly. The first set of friction dampers includes at least a first friction damper and a second friction damper. The first and second friction dampers are independently biased, and the second friction damper is mounted more laterally outboard than the first friction damper.

5

In an additional feature of that aspect of the invention, the set of dampers includes at least third and fourth friction dampers. The third and fourth friction dampers are independently biased, and the third friction damper is mounted more laterally outboard than the fourth friction damper. The third friction damper is longitudinally spaced
10 relative to the first friction damper, and the fourth friction damper is longitudinally spaced relative to the second friction damper. In another additional feature, the suspension is at rest on a straight track, a transverse vertical plane bisects the truck bolster to define a plane of symmetry, and the first, second, third and fourth friction dampers are arranged in a symmetrical formation relative to the transverse vertical plane.

15

In yet another additional feature, a longitudinal vertical plane intersects the side frame and the first, third, second and fourth dampers are symmetrically arranged in a symmetrical formation relative to the longitudinal vertical plane. In still another additional feature, the four dampers are arranged in a formation that is both longitudinally and transversely symmetrical.

20

In a further additional feature, the first damper has a first friction face. The second damper has a second friction face. The first friction face lies in a first plane. The second friction face lies in a second plane, and the first and second planes have mutually parallel normal vectors. In yet a further additional feature, the first damper has a first
25 friction face. The second damper has a second friction face, and the first and second friction faces are coplanar. In still a further additional feature, the first and second dampers sit side-by-side. In another additional feature, the first and second dampers are transversely spaced from each other. In still another additional feature, the first and second dampers are separated by a land, and a spring of one of the spring groups acts
30 against the land.

30

In yet another additional feature, the natural vertical bounce frequency is less than 3 Hz. when the rail road car is unladen. In still yet another additional feature, the first and second spring groups each have a vertical bounce spring rate, and the vertical bounce
35 spring rate is less than 20,000 lbs per inch, per spring group. In an additional feature, the

35

first and second spring groups each have a vertical bounce spring rate, and the vertical bounce spring rate is less than 12,000 lbs per inch, per spring group.

5 In another additional feature, the side frames have wear plates facing the bolster ends. The sets of friction dampers are mounted in pockets defined in the ends of the bolsters, and the friction dampers have friction faces bearing against the wear plates of the side frames. In yet another additional feature, the first and second friction dampers bear on a common wear plate. In still another additional feature, the wear plate presents an uninterrupted surface to the first and second dampers.

10 In a further additional feature, the first and second dampers each include an angled wedge seated in one of the pockets of the bolster. In yet a further additional feature, the angled wedge has a first surface slidingly engaged in a first pocket of the pockets of the bolster. The first surface is inclined at a primary angle defined between
15 the first surface and the friction face thereof. The primary angle is greater than 35 degrees. The pocket has a mating inclined surface. In still a further feature, the wedge first surface has a secondary angle cross-wise to the first angle.

20 In still yet a further additional feature, the first damper is biased laterally inboard and the second damper is biased laterally outboard. In another additional feature, a friction discouraging material is applied to enhance sliding of the first damper relative to the bolster pocket. In yet another additional feature, at least one of the dampers is a split damper. In still another additional feature, the split damper is laterally asymmetrically biased in a direction chosen from (a) laterally inboard; and (b) laterally outboard. In still
25 yet another additional feature, the angled surface is stepped. In a further additional feature, the wedge has an inclined chevron cross-section. The chevron has asymmetric wings. In another additional feature, the wedge has an inclined chevron cross-section, one wing of the chevron lying at a steeper angle than the other. In yet another additional feature, the wedge has a pair of first and second inclined flanks. One of the flanks is
30 steeper than the other.

In still another additional feature, the first spring group has an overall vertical bounce spring rate, k_1 . A portion of the spring group provides biasing for the dampers. The portion has a summed vertical spring rate, k_2 , that is at least 20 % of the overall
35 vertical bounce spring rate. In still yet another additional feature, the ratio of $k_2 : k_1$ is at least as great as 1/4. In another additional feature, the ratio of $k_2 : k_1$ is at least as great as

1/3. In yet another additional feature, the ratio of $k_2 : k_1$ is at least as great as 4/9. In another additional feature, the spring groups include coil springs and first and second dampers seat on coils having an outer diameter of greater than 7 ½ inches. In still another additional feature, the spring groups include coil springs and the first and second dampers seat on coils having an outer diameter of greater than 5 inches. In yet another additional feature, the side frames are mounted to a wheelset, and the truck bolster has at least one inch of lateral travel to either side relative to the wheelset. In a further additional feature, the first side frame is swingingly mounted on wheel bearings, and the first side frame, by itself, has a transverse swinging natural frequency of less than 1.4 Hz. In still a further additional feature, the side frames are mounted on a wheelset. The first truck has a natural frequency for lateral displacement of the truck bolster relative to the wheelset; and the natural frequency for lateral displacement is less than 1.0 Hz.

In yet a further additional feature, the first truck has an AAR rating of at least “70 Ton”. In still a further additional feature, the first truck has a capacity chosen from the set of rail road freight car truck capacities consisting of (a) 70 Ton; (b) 70 Ton Special; (c) 100 Ton; (d) 110 Ton; and (e) 125 Ton. In another additional feature, the first truck has a wheelset having wheels of greater than 33 inches in diameter.

In a further additional feature, each of the side frames has a pair of side frame columns. The side frame columns have bearing surfaces for engaging the friction dampers. A bolster window is defined therebetween. The bolster window has a height and a width. The width is measured between the friction faces and the width is greater than the depth. In another additional feature, the width is at least 8/7 as large as the depth. In still another additional feature, the width is at least 24 inches. In yet another additional feature, the first and second side frames each respectively have a spring seat for receiving, respectively. The first and second spring groups, and the spring seat has a transverse width of greater than 15 inches. In still yet another additional feature, the spring seat has a length of at least 24 inches.

In a further additional feature, at least one rail car unit has ballasting supported by the first truck. In yet a further additional feature, the rail road car is an articulated rail road car. In still a further additional feature, the rail car unit is an end car unit of the articulated rail road car. The end car unit has a coupler end and an articulated connector end, and the first rail car truck supports the coupler end of the end car unit. In another additional feature, the end car unit, when empty, has a weight distribution asymmetrically

biased toward the first truck. In yet another additional feature, the end car unit has ballasting distributed asymmetrically heavily toward the coupler end thereof. In still another additional feature, the rail car unit has a deck carried above the first truck upon which lading can be carried. In a further additional feature, the deck is surmounted by a housing for protection the lading. In yet a further additional feature, the housing has doors giving access to the deck. In still a further additional feature, the deck is a circus-loading deck upon which wheeled vehicles can be conducted. In another additional feature, the rail road freight car is an auto-rack rail road car.

In yet another additional feature, the rail car unit has at least a first coupler end, and a coupler mounted thereat. The coupler has less than 25/32" of slack. In still another additional feature, the rail car unit has at least a first end, and a coupler mounted thereat. The couplers are chosen from the set of coupler families consisting of (a) AAR Type F couplers; (b) AAR Type H couplers; and (c) AAR Type CS couplers. In still yet another additional feature, the rail car unit has at least a first coupler end, draft gear mounted thereat and a coupler mounted to the draft gear. The draft gear has a deflection of less than 2 1/2 inches at 500,000 lbs buff load. In a further additional feature, the rail car unit has at least a first coupler end, draft gear mounted thereat and a coupler mounted to the draft gear. The draft gear has a deflection of less than 1 inch at 700,000 lbs buff load.

In another aspect of the invention there is a railroad three piece freight car truck. The truck has a rigid truck bolster and a pair of first and second side frame assemblies. The truck bolster has first and second ends. A resilient suspension includes first and second spring groups mounted between the first and second ends of the truck bolster and the first and second side frames respectively. The resilient suspension of the first of the trucks has a vertical bounce spring rate of less than 20,000 lbs per spring group. A first set of friction dampers is mounted between the truck bolster and the first side frame assembly. A second set of friction dampers is mounted between the truck bolster and the second side frame assembly. The set of friction dampers includes at least a first friction damper and a second friction damper. The first and second friction dampers are independently biased, and the first friction damper is mounted more laterally outboard than the second friction damper.

In another aspect of the invention there is a rail road freight car three piece truck. The truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a wheelset. The sideframes are mounted to the wheelset, and the

bolster is mounted transversely relative to the side frames. The spring groups are mounted in the sideframes. The bolster has first and second ends resiliently supported by the first and second spring groups. Each of the spring groups has a vertical spring rate of less than 20,000 lbs/in. A first set of friction dampers is mounted to act between the first end of the truck bolster and the first side frame, and a second set of friction dampers is mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers include four dampers arranged in a four cornered layout.

In another aspect of the invention there is a railroad freight car three piece truck for rolling along rail road tracks. The tracks have a gauge width. The three piece truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a pair of first and second axles each having wheels mounted at opposite ends thereof. The wheelset has a longitudinal wheelbase and a transverse track width corresponding to the gauge width. The wheelbase is at least 1.3 times as great as the gauge width. The side frames are mounted to the wheelset, and the bolster is mounted transversely relative to the side frames. The spring groups are mounted in the sideframes. The bolster has first and second ends resiliently supported by the first and second spring groups. A first set of friction dampers is mounted to act between the first end of the truck bolster and the first side frame, and a second set of friction dampers is mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers include four individually sprung dampers arranged in a four cornered layout.

In another aspect of the invention there is a railroad freight car three piece truck. The truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a wheelset. The side frames are mounted to the wheelset, and the bolster is mounted transversely relative to the side frames. The spring groups are mounted in the side frames. The bolster has first and second ends resiliently supported by the first and second spring groups. A first set of friction dampers is mounted to act between the first end of the truck bolster and the first side frame, and a second set of friction dampers is mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers include four individually sprung dampers arranged in a four cornered layout. The four dampers include a first transversely inboard damper and a first transversely outboard damper, seated in respective first and second damper pockets. The first transversely inboard damper is biased to a transversely inboard

position in the first damper pocket, and the first transversely outboard damper is biased to a transversely outboard position in the second damper pocket.

5 In another aspect of the invention there is a railroad freight car three piece truck. The truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a wheelset. The side frames are mounted to the wheelset, and the bolster is mounted transversely relative to the side frames. The spring groups are mounted in the side frames. The bolster has first and second ends resiliently supported by the first and second spring groups. A first set of friction dampers is mounted to act
10 between the first end of the truck bolster and the first side frame, and a second set of friction dampers is mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers include four individually sprung dampers arranged in a four cornered layout. The dampers are wedge shaped. The wedge shapes have a primary angle of greater than 35 degrees.

15 In another aspect of the invention there is a railroad freight car three piece truck. The truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a wheelset. The side frames are mounted to the wheelset, and the bolster is mounted transversely relative to the side frames. The spring groups are mounted in the side frames. The bolster has first and second ends resiliently supported by the first and second spring groups. A first set of friction dampers is mounted to act
20 between the first end of the truck bolster and the first side frame. A second set of friction dampers is mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers include four dampers arranged in a four cornered layout. Each of the bolster ends has a set of damper pockets for receiving the first and second sets of the dampers. The dampers are damper wedges having a spring loaded base portion, a friction face for engaging a friction wear plate, and a sliding face for engaging the damper pockets. The wedges have a primary wedge angle between the friction face and the sliding face of greater than 35 degrees.

30 In another aspect of the invention there is a railroad freight car three piece truck. The truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a wheelset. The side frames are mounted to the wheelset, and the bolster is mounted transversely relative to the side frames. The spring groups are mounted in the side frames. The bolster has first and second ends resiliently supported by the first and second spring groups. A first set of friction dampers are mounted to act
35

between the first end of the truck bolster and the first side frame, and a second set of friction dampers are mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers include four dampers arranged in a four cornered layout. The dampers are wedge shaped. The wedge shapes have a primary angle of greater than 35 degrees.

In another aspect of the invention there is a rail road freight car three piece truck. The truck has a bolster, a pair of first and second side frames, a pair of first and second spring groups, and a wheelset. The side frames are mounted to the wheelset, and the bolster is mounted transversely relative to the side frames. The spring groups are mounted in the side frames. The bolster has first and second ends resiliently supported by the first and second spring groups. Each of the spring groups have an overall vertical spring rate. Each of the spring groups include a plurality of springs. A first set of friction dampers are mounted to act between the first end of the truck bolster and the first side frame, and a second set of friction dampers are mounted to act between the second end of the bolster and the second side frame. Each of the sets of friction dampers are sprung on damper loading members of plurality of springs of the spring groups. The damper loading member of each of the spring groups account for at least 25 % of the vertical spring rate of each of the spring groups.

In another aspect of the invention there is a railroad freight car. The freight car has a rail road car body carried on rail road car trucks for rolling motion along rail road car tracks. The rail road car body has a deck for carrying lading, and side sills running alongside the deck. The body has a first end and a second end. The body has a coupler mounted to at least the first end of the body. A main bolster is mounted to the body adjacent to the first end of the body longitudinally inboard of the coupler. The main bolster extends transversely between the side sills. The main bolster has first and second arms extending laterally outboard from a centreplate. The centreplate is mounted to a first of the rail road car trucks on a vertical axis defining a truck center. The first rail road car truck has wheels spaced laterally outboard a half track gauge width distance from the truck center. The arms of the main bolster has a wheel clearance portion extending laterally away from the truck center over a range of distance bracketing the half track gauge width distance. The wheel clearance portion of the main bolster lying at least 7 inches higher than the first height.

In another aspect of the invention there is a railroad freight car. The freight car has a rail road car body carried on rail road car trucks for rolling motion along rail road car tracks. The rail road car body has a deck for carrying lading, and side sills running alongside the deck. The body has a first end and a second end. The body has a coupler mounted to at least the first end of the body. A main bolster is mounted to the body adjacent to the first end of the body longitudinally inboard of the coupler. The main bolster has first and second arms extending laterally outboard from a center plate. The first rail road car truck has wheels for running along the rail road track. The arms of the main bolster has a wheel clearance relief defined therein. The arms of the bolster has a first depth of section at the clearance relief and a second depth of section laterally outboard of the clearance relief. The second depth of section are greater than the first depth of section.

In another aspect of the invention there is a three piece rail road car truck. The truck has a first rail car truck having a truck bolster and a pair of first and second side frame assemblies. The truck bolster has first and second ends. First and second spring groups are mounted between the first and second ends of the truck bolster and the first and second side frames respectively. A first set of friction dampers are mounted between the truck bolster and the first side frame assembly. A second set of friction dampers are mounted between the truck bolster and the second side frame assembly. The first set of friction dampers include at least a first friction damper. The first spring group has at least a first spring and a second spring. The first friction damper is sprung on the first and second springs. The first spring is mounted laterally outboard relative to the first spring.

Brief Description of the Drawings

Figure **1a** shows a side view of a single unit auto rack rail road car;

Figure **1b** shows a cross-sectional view of the auto-rack rail road car of Figure **1a** in a bi-level configuration, one half section of Figure **1b** being taken through the main bolster and the other half taken looking at the cross-tie outboard of the main bolster;

Figure **1c** shows a half sectioned partial end view of the rail road car of Figure **1a** illustrating the wheel clearance below the main deck, half of the section being taken through the main bolster, the other half section being taken outboard of the truck with the main bolster removed for clarity;

Figure **1d** shows a partially sectioned side view of the rail road car of Figure **1c** illustrating the relationship of the truck, the bolster and the wheel clearance, below the main deck;

Figure **2a** shows a side view of a two unit articulated auto rack rail road car;

Figure **2b** shows a side view of an alternate auto rack rail road car to that of Figure **2a**, having a cantilevered articulation;

Figure **3a** shows a side view of a three unit auto rack rail road car;

Figure **3b** shows a side view of an alternate three unit auto rack rail road car to the articulated rail road unit car of Figure **3a**, having cantilevered articulations;

Figure **3c** shows an isometric view of an end unit of the three unit auto rack rail road car of Figure **3b**;

Figure **4a** is a partial side sectional view of the draft pocket of the coupler end of any of the rail road cars of Figures **1a**, **2a**, **2b**, **3a**, or **3b** taken on '4a – 4a' as indicated in Figure **1a**; and

Figure **4b** shows a top view of the draft gear at the coupler end of Figure **4a** taken on '4b – 4b' of Figure **4a**;

Figure **5a** shows an isometric view of a three piece truck for the auto rack rail road cars of Figures **1a**, **2a**, **2b**, **3a** or **3b**;

Figure **5b** shows a side view of the three piece truck of Figure **5a**;

Figure **5c** shows a top view of half of the three piece truck of Figure **5b**;

Figure **5d** shows a partial section of the three piece truck of Figure **5b** taken on '5d – 5d';

Figure **5e** shows a partial isometric view of the truck bolster of the three piece truck of Figure **5a** showing friction damper seats;

Figure **5f** shows a force schematic for dampers in the side frame of the truck of Figure **5a**.

Figure **6a** shows a side view of an alternate three piece truck to that of Figure **5a**;

Figure **6b** shows a top view of half of the three piece truck of Figure **6a**; and

Figure **6c** shows a partial section of the three piece truck of Figure **6a** taken on '6c – 6c'.

Figure **7** shows a graph of Friction Factor for sliding dampers as a function of Wedge Angle, in upward and downward motion as an aid to explanation of the dampers of the truck of Figure **5a**;

Figure **8a** shows an alternate version of the bolster of Figure **5e**, with a double sized damper pocket for seating a large single wedge having a welded insert;

Figure **8b** shows an alternate optional dual wedge for a truck bolster like that of Figure **8a**;

5 Figure **8c** shows an alternate bolster, similar to that of Figure **5a**, having a pair of spaced apart wedge pockets, and pocket inserts with both primary and secondary wedge angles;

Figure **8d** shows an alternate bolster, similar to that of Figure **8c**, and split wedges;

10 Figure **9** shows an optional non-metallic wear surface arrangement for dampers such as used in the bolster of Figure **8b**;

Figure **10a** shows a bolster similar to that of Figure **8c**, having a wedge pocket having primary and secondary angles and a split wedge arrangement for use therewith;

Figure **10b** shows an alternate stepped single wedge for the bolster of Figure **10a**;

15 Figure **10c** is a view looking along a plane on the primary angle of the split wedge of Figure **10a** relative to the bolster pocket;

Figure **10d** is a view looking along a plane on the primary angle of the stepped wedge of Figure **10b** relative to the bolster pocket;

20 Figure **11a** shows an alternate bolster and wedge arrangement to that of Figure **8b**, having secondary wedge angles;

Figure **11b** shows an alternate, split wedge arrangement for the bolster of Figure **11a**;

Figure **11c** shows a cross-section of a stepped damper wedge for use with a bolster as shown in Figure **11a**;

25 Figure **11d** shows an alternate stepped damper to that of Figure **11c**;

Figure **12a** is a section of Figure **5b** showing a replaceable side frame wear plate;

Figure **12b** is a sectional view on of the side frame of Figure **12a** with the near end of the side frame sectioned and the nearer wear plate removed to show the location of the wear plate of Figure **12a**;

30 Figure **12c** shows a compound bolster pocket for the bolster of Figure **12a**;

Figure **12d** shows a side view detail of the bolster pocket of Figure **12c**, as installed, relative to the main springs and the wear plate;

Figure 12e shows an isometric view detail of a split wedge version and a single wedge version of wedges for use in the compound bolster pocket of Figure 12c;

Figure 12f shows an alternate, stepped steeper angle profile for the primary angle of the wedge of the bolster pocket of Figure 12d;

Figure 12g shows a welded insert having a profile for mating engagement with the corresponding face of the bolster pocket of Figure 12d;

Figure 13a shows an alternate spring arrangement to that of Figure 12a;

Figure 13b shows mutually inclined springs on section '13b – 13b' of Figure 13a;

Figure 14a shows an exploded isometric view of an alternate bolster and side frame assembly to that of Figure 5a, in which horizontally acting springs drive constant force dampers;

Figure 14b shows a side-by-side double damper arrangement similar to that of Figure 14a;

Figure 15 shows an isometric view of an alternate spring seat basket for the truck of Figure 5a, having a spring insertion access feature.

Figure 16a shows an isometric view of an alternate railroad car truck to that of Figure 5a.

Figure 16b shows a side view of the three piece truck of Figure 16a.

Figure 16c shows a top view of the three piece truck of Figure 16a.

Figure 16d shows an end view of the three piece truck of Figure 16a.

Figure 16e shows a schematic of a spring layout for the truck of Figure 16a.

DETAILED DESCRIPTION OF THE INVENTION

The description that follows, and the embodiments described therein, are provided by way of illustration of an example, or examples, of particular embodiments of the principles of the present invention. These examples are provided for the purposes of explanation, and not of limitation, of those principles and of the invention. In the description, like parts are marked throughout the specification and the drawings with the same respective reference numerals. The drawings are not necessarily to scale and in some instances proportions may have been exaggerated in order more clearly to depict certain features of the invention.

In terms of general orientation and directional nomenclature, for each of the rail road cars described herein, the longitudinal direction is defined as being coincident with the rolling direction of the car, or car unit, when located on tangent (that is, straight) track. In the case of a car having a center sill, whether a through center sill or stub sill, the longitudinal direction is parallel to the center sill, and parallel to the side sills, if any. Unless otherwise noted, vertical, or upward and downward, are terms that use top of rail, **TOR**, as a datum. The term lateral, or laterally outboard, refers to a distance or orientation relative to the longitudinal centerline of the railroad car, or car unit, indicated as **CL - Rail Car**. The term “longitudinally inboard”, or “longitudinally outboard” is a distance taken relative to a mid-span lateral section of the car, or car unit. Pitching motion is angular motion of a rail car unit about a horizontal axis perpendicular to the longitudinal direction. Yawing is angular motion about a vertical axis. Roll is angular motion about the longitudinal axis.

Reference is made in this description to rail car trucks and in particular to three piece rail road freight car trucks. Several AAR standard truck sizes are listed at page 711 in the *1997 Car & Locomotive Cyclopedia*. As indicated, for a single unit rail car having two trucks, a “40 Ton” truck rating corresponds to a maximum gross car weight on rail (GWR) of 142,000 lbs. Similarly, “50 Ton” corresponds to 177,000 lbs, “70 Ton” corresponds to 220,000 lbs, “100 Ton” corresponds to 263,000 lbs, and “125 Ton” corresponds to 315,000 lbs. In each case the load limit per truck is then half the maximum gross car weight on rail. Two other types of truck are the “110 Ton” truck for 286,000 LbsGWR and the “70 Ton Special” low profile truck sometimes used for auto rack cars. Given that the rail road car trucks described herein tend to have both longitudinal and transverse axes of symmetry, a description of one half of an assembly may generally also be intended to describe the other half as well, allowing for differences between right hand and left hand parts.

Figures **1a**, **2a**, **2b**, **3a**, and **3b**, show different types of rail road freight cars in the nature of auto rack rail road cars, all sharing a number of similar features. Figure **1a** (side view) shows a single unit autorack rail road car, indicated generally as **20**. It has a rail car body **22** supported for rolling motion in the longitudinal direction (i.e., along the rails) upon a pair of three-piece rail road freight car trucks **23** and **24** mounted at main bolsters at either of the first and second ends **26**, **28** of rail car body **22**. Body **22** has a housing structure **30**, including a pair of left and right hand sidewall structures **32**, **34** and

an over-spanning canopy, or roof **36** that co-operate to define an enclosed lading space. Body **22** has staging in the nature of a main deck **38** running the length of the car between first and second ends **26, 28** upon which wheeled vehicles, such as automobiles can be conducted by circus-loading. Body **22** can have staging in either a bi-level configuration, as shown in Figure **1b**, in which a second, or upper deck **40** is mounted above main deck **38** to permit two layers of vehicles to be carried; or a tri-level configuration with a mid-level deck, similar to deck **40**, and a top deck, also similar to deck **40**, are mounted above each other, and above main deck **38** to permit three layers of vehicles to be carried. The staging, whether bi-level or tri-level, is mounted to the sidewall structures **32, 34**. Each of the decks defines a roadway, trackway, or pathway, by which wheeled vehicles such as automobiles can be conducted between the ends of rail road car **20**.

A through center sill **50** extends between ends **26, 28**. A set of cross-bearers **52** extend to either side of center sill **50**, terminating at side sills **56, 58** that run the length of car **20** parallel to outer sill **50**. Main deck **38** is supported above cross-bearers **52** and between side sills **56, 58**. Sidewall structures **32, 34** each include an array of vertical support members, in the nature of posts **60**, that extend between side sills **56, 58**, and top chords **62, 64**. A corrugated sheet roof **66** extends between top chords **62** and **64** above deck **38** and such other decks as employed. Radial arm doors **68, 70** enclose the end openings of the car, and are movable to a closed position to inhibit access to the interior of car **20**, and to an open position to give access to the interior. Each of the decks has bridge plate fittings (not shown) to permit bridge plates to be positioned between car **20** and an adjacent car when doors **68** or **70** are opened to permit circus loading of the decks. Both ends of car **20** have couplers and draft gear for connecting to adjacent rail road cars.

Two – Unit Articulated Auto Rack Car

Similarly, Figure **2a** shows a two unit articulated auto rack rail road car, indicated generally as **80**. It has a first rail car unit body **82**, and a second rail car unit body **85**, both supported for rolling motion in the longitudinal direction (i.e., along the rails) upon rail car trucks **84, 86** and **88**. Rail car trucks **84** and **88** are mounted at main bolsters at respective coupler ends of the first and second rail car unit bodies **83** and **84**. Truck **86** is mounted beneath articulated connector **90** by which bodies **83** and **84** are joined together. Each of bodies **83** and **84** has a housing structure **92, 93**, including a pair of left and right

hand sidewall structures **94, 96** (or **95, 97**) and a canopy, or roof **98** (or **99**) that define an enclosed lading space. A bellows structure **100** links bodies **82** and **83** to discourage entry by vandals or thieves.

5 Each of bodies **82, 83** has staging in the nature of a main deck similar to deck **38** running the length of the car unit between first and second ends **104, 106** (**105, 107**) upon which wheeled vehicles, such as automobiles can be conducted. Each of bodies **82, 83** can have staging in either a bi-level configuration, as shown in Figure **1b**, or a tri-level configuration. Other than brake fittings, and other minor fittings, car unit bodies **82** and
10 **83** are substantially the same, differing in that car body **82** has a pair of female side-bearing arms adjacent to articulated connector **90**, and car body **83** has a co-operating pair of male side bearing arms adjacent to articulated connector **90**.

Each of car unit bodies **82** and **83** has a through center sill **110** that extends
15 between the first and second ends **104, 106** (**105, 107**). A set of cross-bearers **112, 114** extend to either side of center sill **110**, terminating at side sills **116, 118**. Main deck **102** (or **103**) is supported above cross-bearers **112, 114** and between side sills **116, 118**. Sidewall structures **94, 96** and **95, 97** each include an array of vertical support members, in the nature of posts **120**, that extend between side sills **116, 118**, and top chords **126, 128**.
20 A corrugated sheet roof **130** extends between top chords **126** and **128** above deck **102** and such other decks as may be employed.

Radial arm doors **132, 134** enclose the coupler end openings of car bodies **82** and **83** of rail road car **80**, and are movable to respective closed positions to inhibit access to
25 the interior of rail road car **80**, and to respective open positions to give access to the interior thereof. Each of the decks has bridge plate fittings (upper deck fittings not shown) to permit bridge plates to be positioned between car **80** and an adjacent auto rack rail road car when doors **132** or **134** are opened to permit circus loading of the decks.

30 For the purposes of this description, the cross-section of Figure **1b** can be considered typical also of the general structure of the other railcar unit bodies described below, whether **82, 85, 202, 204, 142, 144, 146, 222, 224** or **226**. It should be noted that Figure **1b** shows a stepped section in which the right hand portion shows the main bolster **75** and the left hand section shows a section looking at the cross-tie **77** outboard of the

main bolster. The sections of Figures **1b** and **1c** are typical of the sections of the end units described herein at their coupler end trucks, such as trucks **232**, **148**, **84**, **88**, **210**, **206**. The upward recess in the main bolster **75** provides vertical clearance for the side frames (typically 7" or more). That is, the clearance 'X' in Figure **1c** is about 7 inches in one embodiment between the side frames and the bolster for an unladen car at rest.

As may be noted, the web of main bolster **75** has a web rebate **79** and a bottom flange that has an inner horizontal portion **69**, an upwardly stepped horizontal portion **71** and an outboard portion **73** that deepens to a depth corresponding to the depth of the bottom flange of side sill **58**. Horizontal portion **69** is carried at a height corresponding generally to the height of the bottom flange of side sill **58**, and portion **71** is stepped upwardly relative to the height of the bottom flange of side sill **58** to provide greater vertical clearance for the side frame of truck **23** or **24** as the case may be.

Three or More Unit Articulated Auto Rack Car

Figure **3a** shows a three unit articulated autorack rail road car, generally as **140**. It has a first end rail car unit body **142**, a second end rail car unit body **144**, and an intermediate rail car unit body **146** between rail car unit bodies **142** and **144**. Rail car unit bodies **142**, **144** and **146** are supported for rolling motion in the longitudinal direction (i.e., along the rails) upon rail car trucks **148**, **150**, **152**, and **154**. Rail car trucks **148** and **150** are "coupler end" trucks mounted at main bolsters at respective coupler ends of the first and second rail car bodies **142** and **144**. Trucks **152** and **154** are "interior" or "intermediate" trucks mounted beneath respective articulated connectors **156** and **158** by which bodies **142** and **144** are joined to body **146**. For the purposes of this description, body **142** is the same as body **82**, and body **144** is the same as body **83**. Rail car body **146** has a male end **159** for mating with the female end **160** of body **142**, and a female end **162** for mating with the male end **164** of rail car body **144**.

Body **146** has a housing structure **166** like that of Figure **1b**, that includes a pair of left and right hand sidewall structures **168** and a canopy, or roof **170** that co-operate to define an enclosed lading space. Bellows structures **172** and **174** link bodies **142**, **146** and **144**, **146** respectively to discourage entry by vandals or thieves.

Body **146** has staging in the nature of a main deck **176**, similar to deck **38**, running the length of the car unit between first and second ends **178**, **180** defining a roadway upon which wheeled vehicles, such as automobiles can be conducted. Body **146** can have staging in either a bi-level configuration or a tri-level configuration, to co-operate with the staging of bodies **142** and **144**.

Other than brake fittings, and other ancillary features, car bodies **142** and **144** are substantially the same, differing to the extent that car body **142** has a pair of female side-bearing arms adjacent to articulated connector **156**, and car body **144** has a co-operating pair of male side bearing arms adjacent to articulated connector **158**.

Other articulated auto-rack cars of greater length can be assembled by using a pair of end units, such as male and female end units **82** and **83**, and any number of intermediate units, such as intermediate unit **146**, as may be suitable. In that sense, rail road car **140** is representative of multi-unit articulated rail road cars generally.

Alternate Configurations

Alternate configurations of multi-unit rail road cars are shown in Figures **2b** and **3b**. In Figure **2b**, a two unit articulated auto-rack rail road car is indicated generally as **200**. It has first and second rail car unit bodies **202**, **204** supported for rolling motion in the longitudinal direction by three rail road car trucks, **206**, **208** and **210** respectively. Rail car unit bodies **202** and **204** are joined together at an articulated connector **212**. In this instance, while rail car bodies **202** and **204** share the same basic structural features of rail car body **22**, in terms of a through center sill, cross-bearers, side sills, walls and canopy, and vehicles decks, rail car body **202** is a "two-truck" body, and rail car body **204** is a single truck body. That is, rail car body **202** has main bolsters at both its first, coupler end, and at its second, articulated connector end, the main bolsters being mounted over trucks **206** and **208** respectively. By contrast, rail car body **204** has only a single main bolster, at its coupler end, mounted over truck **210**. Articulated connector **212** is mounted to the end of the respective center sills of rail car bodies **202** and **204**, longitudinally outboard of rail car truck **208**. The use of a cantilevered articulation in this manner, in which the pivot center of the articulated connector is offset from the nearest truck center, is described more fully in my co-pending U.S. patent application 09 /

614,815 for a Rail Road Car with Cantilevered Articulation filed July 12, 2000, incorporated herein by reference, and may tend to permit a longer car body for a given articulated rail road car truck center distance as therein described.

5 Figure **3b** shows a three-unit articulated rail road car **220** having first end unit **222**, second end unit **224**, and intermediate unit **226**, with cantilevered articulated connectors **228** and **230**. End units **222** and **224** are single truck units of the same construction as car body **204**. Intermediate unit **226** is a two truck unit having similar construction to car body **202**, but having articulated connectors at both ends, rather than
10 having a coupler end. Figure **3c** shows an isometric view of end unit **224** (or **222**). Analogous five pack articulated rail road cars having cantilevered articulations can also be produced. Many alternate configurations of multi-unit articulated rail road cars employing cantilevered articulations can be assembled by re-arranging, or adding to, the units illustrated.

15 In each of the foregoing descriptions, each of rail road cars **20**, **80**, **140**, **200** and **220** has a pair of first and second coupler ends by which the rail road car can be releasably coupled to other rail road cars, whether those coupler ends are part of the same rail car body, or parts of different rail car bodies of a multi-unit rail road car joined by
20 articulated connections, draw-bars, or a combination of articulated connections and draw-bars.

 Figures **4a** and **4b** show the draft gear at a first coupler end **300** of rail road car **20**, coupler end **300** being representative of either of the coupler ends and draft gear arrangement of rail road car **20**, and of rail road cars **80**, **140**, **200** and **220** more
25 generally. Coupler pocket **302** houses a coupler indicated as **304**. It is mounted to a coupler yoke **308**, joined together by a pin **310**. Yoke **308** houses a coupler follower **312**, a draft gear **314** held in place by a shim (or shims, as required) **316**, a wedge **318** and a filler block **320**. Fore and aft draft gear stops **322**, **324** are welded inside coupler pocket
30 **302** to retain draft gear **314**, and to transfer the longitudinal buff and draft loads through draft gear **314** and on to coupler **304**. In the preferred embodiment, coupler **304** is an AAR Type F70DE coupler, used in conjunction with an AAR Y45AE coupler yoke and an AAR Y47 pin. In the preferred embodiment, draft gear **314** is a Mini-BuffGear such as manufactured Miner Enterprises Inc., or by the Keystone Railway Equipment Company,

of 3420 Simpson Ferry Road, Camp Hill, Pa. As taken together, this draft gear and coupler assembly yields a reduced slack, or low slack, short travel, coupling as compared to an AAR Type E coupler with standard draft gear or hydraulic EOCC device. As such it may tend to reduce overall train slack. In addition to mounting the Mini-BuffGear directly to the draft pocket, that is, coupler pocket **302**, and hence to the structure of the rail car body of rail road car **20**, (or of the other rail road cars noted above) the construction described and illustrated is free of other long travel draft gear, sliding sills and EOCC devices, and the fittings associated with them.

Mini-BuffGear has between $5/8$ and $3/4$ of an inch displacement travel in buff at a compressive force greater than 700,000 Lbs. Other types of draft gear can be used to give an official rating travel of less than $2\ 1/2$ inches under M-901-G, or if not rated, then a travel of less than 2.5 inches under 500,000 Lbs. buff load. For example, while Mini-BuffGear is preferred, other draft gear is available having a travel of less than $1\ 3/4$ inches at 400,000 Lbs., one known type has about 1.6 inches of travel at 400,000 Lbs., buff load. It is even more advantageous for the travel to be less than 1.5 inches at 700,000 Lbs. buff load and, as in the embodiment of Figures **4a** and **4b**, preferred that the travel be at least as small as 1" inches or less at 700,000 Lbs. buff load.

Similarly, while the AAR Type F70DE coupler is preferred, other types of coupler having less than the $25/32$ " (that is, less than about $3/4$ ") nominal slack of an AAR Type E coupler generally or the $20/32$ " slack of an AAR E50ARE coupler can be used. In particular, in alternative embodiments with appropriate housing changes where required, AAR Type F79DE and Type F73BE (members of the Type F Family), with or without top or bottom shelves; AAR Type CS; or AAR Type H couplers can be used to obtain reduced slack relative to AAR Type E couplers.

In each of the autorack rail car embodiments described above, each of the car units has a weight, that weight being carried by the rail car trucks with which the car is equipped. In each of the embodiments of articulated rail cars described above there is a number of rail car units joined at a number of articulated connectors, and carried for rolling motion along railcar tracks by a number of railcar trucks. In each case the number of articulated car units is one more than the number of articulations, and one less than the number of trucks. In the event that in alternate embodiments some of the cars units are

joined by draw bars the number of articulated connections will be reduced by one for each draw bar added, and the number of trucks will increase by one for each draw bar added. Typically articulated rail road cars have only articulated connections between the car units. All cars described have releasable couplers mounted at their opposite ends.

5

In each embodiment described above, where at least two car units are joined by an articulated connector, there are end trucks (e.g. **150, 232**) inset from the coupler ends of the end car units, and intermediate trucks (e.g. **154, 234**) that are mounted closer to, or directly under, one or other of the articulated connectors (e.g. **156, 230**). In a car having cantilevered articulations, such as shown in Figure **2b** or **3b**, the articulated connector is mounted at a longitudinal offset distance (the cantilever arm **CA**) from the truck center. In each case, each of the car units has an empty weight, and also a design full weight. The full weight is usually limited by the truck capacity, whether 70 ton, 100 ton, 110 ton (286,000 lbs.) or 125 ton. In some instances, with low density lading, the volume of the lading is such that the truck loading capacity cannot be reached without exceeding the volumetric capacity of the car body.

10

15

20

25

The dead sprung weight of a rail car unit is generally taken as the body weight of the car unit, including any ballast, as described below, plus that portion of the weight of the truck borne by the springs, (most typically taken as being the weight of the truck bolsters). The unsprung weight of the trucks is, primarily, the weight of the side frames, the axles and the wheels, plus ancillary items such as the brakes, springs, and axle bearings and bearing adapters. The unsprung weight of a three piece truck may generally be about 8800 lbs. The live load is the weight of the lading. The sum of (a) the live load; (b) the dead sprung load; and (c) the unsprung weight of the trucks is the gross railcar weight on rail.

30

35

In each of the embodiments described above, each of the rail car units has a weight and a weight distribution of the dead sprung weight of the carbody which determines the dead sprung load carried by each truck. In each of the embodiments described above, the sum of the sprung weights of all of the car bodies of an articulated car is designated as W_0 . (The sprung mass, M_0 , is the sprung weight W_0 divided by the gravitational constant, g . In each case where a weight is given herein, it is understood that conversion to mass can be readily made in this way, particularly as when calculating natural frequencies). For a single unit, symmetrical rail road car, such as car **20**, the weight on both trucks is equal. In all of the articulated auto rack rail road car

embodiments described above, the distributed sprung weight on any end truck, is at least $\frac{2}{3}$, and no more than $\frac{4}{3}$ of the nearest adjacent interior truck, such as an interior truck next closest to the nearest articulated connector. It is advantageous that the dead sprung weight be in the range of $\frac{4}{5}$ to $\frac{6}{5}$ of the dead sprung weight carried by the interior truck, and it is preferred that the dead sprung weight be in the range of 90 % to 110 % of the interior truck. It is also desirable that the dead sprung weight on any truck, W_{DS} , fall in the range of 90 % to 110 % of the value obtained by dividing W_O by the total number of trucks of the rail road car. Similarly, it is desirable that the dead sprung weight plus the live load carried by each of the trucks be roughly similar such that the overall truck loading is about the same. In any case, for the embodiments described above, the design live load for one truck, such as an end truck, can be taken as being at least 60 % of the design live load of the next adjacent truck, such as an internal truck. In terms of overall dead and live loads, in each of the embodiments described the overall sprung load of the end truck is at least 70 % of the nearest adjacent internal truck, advantageously 80 % or more, and preferably 90 % of the nearest adjacent internal truck.

Inasmuch as the car weight would generally be more or less evenly distributed on a lineal foot basis, and as such the interior trucks would otherwise reach their load capacities before the coupler end trucks, weight equalisation may be achieved in the embodiments described above by adding ballast to the end car units. That is, the dead sprung weight distribution of the end car units is biased toward the coupler end, and hence toward the coupler end truck (e.g. **84**, **88**, **206**, **210**, **150**, **232**). For example, in the embodiments described above, a first ballast member is provided in the nature of a main deck plate **350** of unusual thickness **T** that forms part of main deck **38** of the rail car unit. Plate **350** extends across the width of the end car unit, and from the longitudinally outboard end of the deck a distance **LB**. In the embodiment of Figures **3b** and **3c** for example, the intermediate or interior truck **234** may be a 70 ton truck near its sprung load limit of about 101,200 lbs., on the basis of its share of loads from rail car units **222** and **226** (or, symmetrically **224** and **226** as the case may be), while, without ballast, end trucks **232** would be at a significantly smaller sprung load, even when rail car **220** is fully loaded. In this case, thickness **T** can be $1\frac{1}{2}$ inches, the width can be 112 inches, and the length **LB** can be 312 inches, giving a weight of roughly 15,220 lbs., centered on the truck center of end truck **232**. This gives a dead load of end car unit **222** of roughly 77,000 lbs., a dead sprung load on end truck **232** of about 54,000 lbs., and a total sprung load on truck **232** can be about 84,000 lbs. By comparison, center car unit **226** has a dead sprung load of about 60,000 lbs., with a dead sprung load on interior truck **234** of about

55,000 lbs., and yielding a total sprung load on interior truck **234** of 101,000 lbs when car **220** is fully loaded. In this instance as much as a further 17,000 lbs. (+/-) of additional ballast can be added before exceeding the “70 Ton” gross weight on rail limit for the coupler end truck, **232**. Ballast can also be added by increasing the weight of the lower flange or webs of the center sill, also advantageously reducing the center of gravity of the car.

Similar weight distributions can be made for other capacities of truck whether 100 Ton, 110 Ton or 125 Ton. Although any of these sizes of trucks can be used, it is preferable to use a truck with a larger wheel diameter. That is, while 33 inch wheels (or even 28” wheels in a 70 Ton Special”) can be used, wheels larger than 33 inches in diameter are preferred such as 36 inch or 38 inch wheels.

Figures **5a**, **5b**, **5c**, **5d** and **5e** all relate to a three piece truck **400** for use with the rail road cars of Figure **1a**, **2a**, **2b**, **3a** or **3b**. Figures **1c** and **1d** show the relationship of this truck to the deck level of these rail road cars. Truck **400** has three major elements, those elements being a truck bolster **402**, symmetrical about the truck longitudinal centreline, and a pair of first and second side frames, indicated as **404**. Only one side frame is shown in Figure **5c** given the symmetry of truck **400**. Three piece truck **400** has a resilient suspension (a primary suspension) provided by a spring groups **405** trapped between each of the distal (i.e., transversely outboard) ends of truck bolster **402** and side frames **404**.

Truck bolster **402** is a rigid, fabricated beam having a first end for engaging one side frame assembly and a second end for engaging the other side frame assembly (both ends being indicated as **406**). A center plate or center bowl **408** is located at the truck center. An upper flange **410** extends between the two ends **406**, being narrow at a central waist and flaring to a wider transversely outboard termination at ends **406**. Truck bolster **402** also has a lower flange **412** and two fabricated webs **414** extending between upper flange **410** and lower flange **412** to form an irregular, closed section box beam. Additional webs **415** are mounted between the distal portions of upper flange **410** and **414** where bolster **402** engages one of the spring groups **405**. The transversely distal region of truck bolster **402** also has friction damper seats **416**, **418** for accommodating friction damper wedges as described further below.

Side frame **404** is a casting having bearing seats **419** into which bearing adapters **420**, bearings **421**, and a pair of axles **422** mount. Each of axles **422** has a pair of first and second wheels **423**, **425** mounted to it in a spaced apart position corresponding to the width of the track gauge of the track upon which the rail car is to operate. Side frame **404** also has a compression member, or upper beam member **424**, a tension member, or lower beam member **426**, and vertical side columns **428** and **430**, each lying to one side of a vertical transverse plane **425** bisecting truck **400** at the longitudinal station of the truck center. A generally rectangular opening is defined by the co-operation of the upper and lower beam members **424**, **426** and vertical columns **428**, **430**, into which the distal end of truck bolster **402** can be introduced. The distal end of truck bolster **402** can then move up and down relative to the side frame within this opening. Lower beam member **426** has a bottom or lower spring seat **432** upon which spring group **405** can seat. Similarly, an upper spring seat **434** is provided by the underside of the distal portion of bolster **402** to engages the upper end of spring group **405**. As such, vertical movement of truck bolster **402** will tend to compress or release the springs in spring group **405**.

In the embodiment of Figure **5a**, spring group **405** has two rows of springs **436**, a transversely inboard row and a transversely outboard row, each row having four large (8 inch +/-) diameter coil springs giving vertical bounce spring rate constant, k , for group **405** of less than 10,000 lbs / inch. This spring rate constant can be in the range of 6000 to 10,000 lbs / in., and is advantageously in the range of 7000 to 9500 lbs / in, giving an overall vertical bounce spring rate for the truck of double these values, preferably in the range of 14000 to 18,500 lbs / in for the truck. The spring array can include nested coils of outer springs, inner springs, and inner-inner springs depending on the overall spring rate desired for the group, and the apportionment of that stiffness. The number of springs, the number of inner and outer coils, and the spring rate of the various springs can be varied. The spring rates of the coils of the spring group add to give the spring rate constant of the group, typically being suited for the loading for which the truck is designed.

Each side frame assembly also has four friction damper wedges arranged in first and second pairs of transversely inboard and transversely outboard wedges **440**, **441**, **442** and **443** that engage the sockets, or seats **416**, **418** in a four-cornered arrangement. The corner springs in spring group **405** bear upon a friction damper wedge **440**, **441**, **442** or **443**. Each of vertical columns **428**, **430** has a friction wear plate **450** having transversely inboard and transversely outboard regions against which the friction faces of wedges **440**,

441, 442 and 443 can bear, respectively. Bolster gibs 451 and 453 lie inboard and outboard of wear plate 450 respectively. Gibs 451 and 453 act to limit the lateral travel of bolster 402 relative to side frame 404. The deadweight compression of the springs under the dampers will tend to yield a reaction force working on the bottom face of the wedge, trying to drive the wedge upward along the inclined face of the seat in the bolster, thus urging, or biasing, the friction face against the opposing portion of the friction face of the side frame column. In one embodiment, the springs chosen can have an undeflected length of 15 inches, and a dead weight deflection of about 3 inches.

As seen in the top view of Figure 5c, and in the schematic sketch of Figure 5f the side-by-side friction dampers have a relatively wide averaged moment arm L to resist angular deflection of the side frame relative to the truck bolster in the parallelogram mode. This moment arm is significantly greater than the effective moment arm of a single wedge located on the spring group (and side frame) centre line. Further, the use of independent springs under each of the wedges means that whichever wedge is jammed in tightly, there is always a dedicated spring under that specific wedge to resist the deflection. In contrast to older designs, the overall damping face width is greater because it is sized to be driven by relatively larger diameter (e.g., 8 in +/-) springs, as compared to the smaller diameter of, for example, AAR B 432 out or B 331 side springs, or smaller. Further, in having two elements side-by-side the effective width of the damper is doubled, and the effective moment arm over which the diagonally opposite dampers work to resist parallelogram deformation of the truck in hunting and curving greater than it would have been for a single damper.

In the illustration of Figure 5e, the damper seats are shown as being segregated by a partition 452. If a longitudinal vertical plane 454 is drawn through truck 400 through the center of partition 452, it can be seen that the inboard dampers lie to one side of plane 454, and the outboard dampers lie to the outboard side of plane 454. In hunting then, the normal force from the damper working against the hunting will tend to act in a couple in which the force on the friction bearing surface of the inboard pad will always be fully inboard of plane 454 on one end, and fully outboard on the other diagonal friction face. For the purposes of conceptual visualisation, the normal force on the friction face of any of the dampers can be idealised as an evenly distributed pressure field whose effect can be approximated by a point load whose magnitude is equal to the integrated value of the pressure field over its area, and that acts at the centroid of the pressure field. The center of this distributed force, acting on the inboard friction face of wedge 440 against column

428 can be thought of as a point load offset transversely relative to the diagonally outboard friction face of wedge 443 against column 430 by a distance that is notionally twice dimension 'L' shown in the conceptual sketch of Figure 5f. In the example, this distance is about one full diameter of the large spring coils in the spring set. It is a significantly greater effective moment arm distance than found in typical friction damper wedge arrangements. The restoring moment in such a case would be, conceptually, $M_R = [(F_1 + F_3) - (F_2 + F_4)]L$. As indicated by the formulae on the conceptual sketch of Figure 5f, the difference between the inboard and outboard forces on each side of the bolster is proportional to the angle of deflection ϵ of the truck bolster relative to the side frame, and since the normal forces due to static deflection x_0 may tend to cancel out, $M_R = 4k_c \tan(\epsilon) \tan(\theta) L$, where θ is the primary angle of the damper, and k_c is the vertical spring constant of the coil upon which the damper sits and is biased.

Further, in typical friction damper wedges, the enclosed angle of the wedge tends to be somewhat less than 35 degrees measured from the vertical face to the sloped face against the bolster. As the wedge angle decreases toward 30 degrees, the tendency of the wedge to jam in place increases. Conventionally the wedge is driven by a single spring in a large group. The portion of the vertical spring force acting on the damper wedges can be less than 15 % of the group total. In the embodiment of Figure 5b, it is 50 % of the group total (i.e., 4 of 8 equal springs). The wedge angle of wedges 440, 442 is significantly greater than 35 degrees. With reference again to Figure 7, the use of more springs, or more precisely a greater portion of the overall spring stiffness, under the dampers, permits the enclosed angle of the wedge to be over 35 degrees, and advantageously larger, in the range of between roughly 37 to 40 or 45 degrees to roughly 60 or 65 degrees.

Where a softer suspension is used employing a relatively small number of large diameter springs, such as in a 2 x 4, 3 x 3, or 3 x 5 group as described in the detailed description of the invention herein, dampers may be mounted over each of four corner positions. In that case, the portion of spring force acting under the damper wedges may be in the 25 – 50 % range for springs of equal stiffness. If the coils or coil groups are not of equal stiffness, the portion of spring force acting under the dampers may be in the range of perhaps 20 % to 70 %. The coil groups can be of unequal stiffness if inner coils are used in some springs and not in others, or if springs of differing spring constant are used.

The size of the spring group embodiment of Figure 5b yields a side frame window opening having a width between the vertical columns of side frame **404** of roughly 33 inches. This is relatively large compared to existing spring groups, being more than 25 % greater in width. Truck **400** has a correspondingly greater wheelbase length, indicated as **WB**. **WB** is advantageously greater than 73 inches, or, taken as a ratio to the track gauge width, is advantageously greater than 1.30 time the track gauge width. It is preferably greater than 80 inches, or more than 1.4 times the gauge width, and in one embodiment is greater than 1.5 times the track gauge width, being as great, or greater than, about 86 inches. Similarly, the side frame window is advantageously wider than tall, the measurement across the wear plate faces of the side frame columns being advantageously greater than 24", possibly in the ratio of greater than 8:7 of width to height, and possibly in the range of 28" or 32" or more, giving ratios of greater than 4:3 and greater than 3:2. The spring seat may have lengthened dimensions to correspond to the width of the side frame window, and a transverse width of 15 ½ - 17" or more.

In Figures **6a**, **6b** and **6c**, there is an alternate embodiment of soft spring rate, long wheelbase three piece truck, identified as **460**. Truck **460** employs constant force inboard and outboard, fore and aft pairs of friction dampers **466** mounted in the distal ends of truck bolster **468**. In this arrangement, springs **470** are mounted horizontally in pockets in the distal ends of truck bolster **468** and urge, or bias, each of the friction dampers **466** against the corresponding friction surfaces of the vertical columns of the side frames.

The spring force on friction damper wedges **440**, **441**, **442** and **443** varies as a function of the vertical displacement of truck bolster **402**, since they are driven by the vertical springs of spring group **405**. By contrast, the deflection of springs **470** does not depend on vertical compression of the main spring group **472**, but rather is a function of an initial pre-load. Although the arrangement of Figure **6a**, **6b** and **6c** still provides inboard and outboard dampers and independent springing of the dampers, the embodiment of Figures **5b** is preferred.

In the embodiments of Figures **1a**, **1b**, **2a**, **2b**, **3a** and **3b**, the ratio of the dead sprung weight, **WD**, of the rail car unit (being the weight of the car body plus the weight of the truck bolster) without lading to the live load, **WL**, namely the maximum weight of lading, be at least 1:1. It is advantageous that this ratio **WD : WL** lie in the range of 1:1 to 10:3. In one embodiment of rail car of Figures **1a**, **1b**, **2a**, **2b**, **3a** and **3b** the ratio can

be about 1.2 : 1. It is more advantageous for the ratio to be at least 1.5 : 1, and preferable that the ratio be greater than 2 : 1.

Figures 8a and 8b

5

Figures 8a and 8b show a partial isometric view of a truck bolster 480 that is generally similar to truck bolster 400 of Figure 5d, except insofar as bolster pocket 482 does not have a central partition like web 452, but rather has a continuous bay extending across the width of the underlying spring group, such as spring group 436. A single wide damper wedge is indicated as 484. Damper 484 is of a width to be supported by, and to be acted upon, by two springs 486, 488 of the underlying spring group. In the event that bolster 400 may tend to deflect to a non-perpendicular orientation relative to the associated side frame, as in the parallelogramming phenomenon, one side of wedge 484 will tend to be squeezed more tightly than the other, giving wedge 484 a tendency to twist in the pocket about an axis of rotation perpendicular to the angled face (i.e., the hypotenuse face) of the wedge. This twisting tendency may also tend to cause differential compression in springs 486, 488, yielding a restoring moment both to the twisting of wedge 484 and to the non-square displacement of truck bolster 480 relative to the truck side frame. As there may tend to be a similar moment generated at the opposite spring pair at the opposite side column of the side frame, this may tend to enhance the self-squaring tendency of the truck more generally.

20

25

Also included in Figure 8b is an alternate pair of damper wedges 490, 492. This dual wedge configuration can similarly seat in bolster pocket 482, and, in this case, each wedge 490, 492 sits over a separate spring. Wedges 490, 492 are vertically slidable relative to each other along the primary angle of the face of bolster pocket 482. When the truck move to an out of square condition, differential displacement of wedges 490, 492 may tend to result in differential compression of their associated springs, e.g., 486, 488 resulting in a restoring moment as above.

30

35

The sliding motion described above may tend to cause wear on the moving surfaces, namely (a) the side frame columns, and (b) the angled surfaces of the bolster pockets. To alleviate, or ameliorate, this situation, consumable wear plates 494 can be mounted in bolster pocket 482 (with appropriate dimensional adjustments) as in Figure 8b. Wear plates 494 can be smooth steel plates, possibly of a hardened, wear resistant alloy, or can be made from a non-metallic, or partially non-metallic, relatively low

friction wear resistant surface. Other plates for engaging the friction surfaces of the dampers can be mounted to the side frame columns, and indicated by item **496** in Figure **14a**.

5 For the purposes of this example, it has been assumed that the spring group is two coils wide, and that the pocket is, correspondingly, also two coils wide. The spring group could be more than two coils wide. The bolster pocket is assumed to have the same width as the spring group, but could be less wide. For two coils where in some
10 embodiments the group may be more than two coils wide. A symmetrical arrangement of the dampers relative to the side frame and the spring group is desirable, but an asymmetric arrangement could be made. In the embodiments of Figures **5a**, **8a** and **16a**, the dampers are in four cornered arrangements that are symmetrical both about the center axis of the truck bolster and about a longitudinal vertical plane of the side frame.

15 Similarly, the wedges themselves can be made from a relatively common material, such as a mild steel, and the given consumable wear face members in the nature of shoes, or wear members. Such an arrangement is shown in Figure **9** in which a damper wedge is shown generically as **500**. The replaceable, consumable wear members are indicated as **502**, **504**. The wedges and wear members have mating male and female
20 mechanical interlink features, such as the cross-shaped relief **503** formed in the primary angled and vertical faces of wedge **500** for mating with the corresponding raised cross shaped features **505** of wear members **502**, **504**. Sliding wear member **502** is preferably made of a non-metallic, low friction material.

25 Although Figure **9** shows a consumable insert in the nature of a wear plate, the entire bolster pocket can be made as a replaceable part, as in Figure **8a**. This bolster pocket can be made of a high precision casting, or can be a sintered powder metal assembly having desired physical properties. The part so formed is then welded into place in the end of the bolster, as at **506** indicated in Figure **8a**.

30 The underside of the wedges described herein, wedge **500** being typical in this regard, has a seat, or socket **507**, for engaging the top end of the spring coil, whichever spring it may be, spring **562** being shown as typically representative. Socket **507** serves to discourage the top end of the spring from wandering away from the intended generally
35 central position under the wedge. A bottom seat, or boss for discouraging lateral wandering of the bottom end of the spring is shown in Figure **14a** as item **508**.

Thus far only primary angles have been discussed. Figure 8c shows an isometric view of an end portion of a truck bolster 510, generally similar to bolster 400. As with all of the truck bolsters shown and discussed herein, bolster 510 is symmetrical about the longitudinal vertical plane of the bolster (i.e., cross-wise relative to the truck generally) and symmetrical about the vertical mid-span section of the bolster (i.e., the longitudinal plane of symmetry of the truck generally, coinciding with the rail car longitudinal center line). Bolster 510 has a pair of spaced apart bolster pockets 512, 514 for receiving damper wedges 516, 518. Pocket 512 is laterally inboard of pocket 514 relative to the side frame of the truck more generally. Consumable wear plate inserts 520, 522 are mounted in pockets 512, 514 along the angled wedge face.

As can be seen, wedges 516, 518 have a primary angle, α as measured between vertical sliding face 524, (or 526, as may be) and the angled vertex 528 of outboard face 530. For the embodiments discussed herein, primary angle α will tend to be greater than 40 degrees, and may typically lie in the range of 45 – 65 degrees, possibly about 55 - 60 degrees. This angle will be common to the slope of all points on the sliding hypotenuse face of wedge 516 (or 518) when taken in any plane parallel to the plane of outboard end face 530. This same angle α is matched by the facing surface of the bolster pocket, be it 512 or 514, and it defines the angle upon which displacement of wedge 516, (or 518) is intended to move relative to that surface.

A secondary angle β gives the inboard, (or outboard), rake of the hypotenuse surface of wedge 516 (or 518). The true rake angle can be seen by sighting along plane of the hypotenuse face and measuring the angle between the hypotenuse face and the planar outboard face 530. The rake angle is the complement of the angle so measured. The rake angle may tend to be greater than 5 degrees, may lie in the range of 10 to 20 degrees, and is preferably about 15 degrees. A modest angle is desirable.

When the truck suspension works in response to track perturbations, the damper wedges may tend to work in their pockets. The rake angles yield a component of force tending to bias the outboard face 530 of outboard wedge 518 outboard against the opposing outboard face of bolster pocket 514. Similarly, the inboard face of wedge 516 will tend to be biased toward the inboard planar face of inboard bolster pocket 512. These inboard and outboard faces of the bolster pockets are preferably lined with a low friction surface pad, indicated generally as 532. The left hand and right hand biases of

the wedges may tend to keep them apart to yield the full moment arm distance intended, and, by keeping them against the planar facing walls, may tend to discourage twisting of the dampers in the respective pockets.

5 Bolster **510** includes a middle land **534** between pockets **512**, **514**, against which another spring **536** may work, such as might be found in a spring group that is three (or more) coils wide. However, whether two, three, or more coils wide, and whether employing a central land or no central land, bolster pockets can have both primary and secondary angles as illustrated in the example embodiment of Figure **8c**, with or without
10 (though preferably with) wear inserts.

In the case where a central land, such as land **534** separates two damper pockets, the opposing wear plates of the side frame columns need not be monolithic. That is, two wear plate regions could be provided, one opposite each of the inboard and outboard
15 dampers, presenting planar surfaces against which those dampers can bear. Advantageously, the normal vectors of those regions are parallel, and most conveniently those surfaces are co-planar and perpendicular to the long axis of the side frame, and present a clear, un-interrupted surface to the friction faces of the dampers.

20 The examples of Figures **8a**, **8b** and **8c** are arranged in order of incremental increases in complexity. The Example of Figure **8d** again provides a further incremental increase in complexity. Figure **8d** shows a bolster **540** that is similar to bolster **510** except insofar as bolster pockets **542**, **544** each accommodate a pair of split wedges **546**, **548**. Pockets **542**, **544** each have a pair of bearing surfaces **550**, **552** that are inclined at
25 both a primary angle and a secondary angle, the secondary angles of surfaces **550** and **552** being of opposite hand to yield the damper separating forces discussed above. Surfaces **550** and **552** are also provided with linings in the nature of relatively low friction wear plates **554**, **556**. Each of pockets **542** and **544** accommodates a pair of split wedges **558**, **560**. Each pair of split wedges seats over a single spring **562**. Another
30 spring **564** bears against central land **566**.

The example of Figure **10a** shows a combination of a bolster **570** and biased split wedges **572**, **574**. Bolster **570** is the same as bolster **540** except insofar as bolster pockets **576**, **578** are stepped pockets in which the steps, e.g., items **580**, **582**, have the same
35 primary angle, and the same secondary angle, and are both biased in the same direction, unlike the symmetrical sliding faces of the split wedges in Figure **8d**, which are left and

right handed. Thus the outboard pair of split wedges **584** has a first member **586** and a second member **588** each having primary angle α and secondary angle β , and are of the same hand such that in use both the first and second members will tend to be biased in the outboard direction (i.e. toward the distal end of bolster **570**). Similarly, the inboard pair of split wedges **590** has a first member **592** and a second member **594** each having primary angle α , and secondary angle β , except that the sense of secondary angle β is in the opposite direction such that members **592** and **592** will tend in use to be driven in the inboard direction (i.e., toward the truck center).

As shown in the partial sectional view of Figure **10c**, a replaceable monolithic stepped wear insert **596** is welded in the bolster pocket **580** (or **582** if opposite hand, as the case may be). Insert **596** has the same primary and secondary angles α and β as the split wedges it is to accommodate, namely **586**, **588** (or, opposite hand, **592**, **594**). When installed, and working, the more outboard of the wedges, **588** (or, opposite hand, the more inboard of the wedges **592**) has a vertical and longitudinally planar outboard face **600** that bears against a similarly planar outboard face **602** (or, opposite hand, inboard face **604**) These faces are preferably prepared in a manner that yields a relatively low friction sliding interface between them. In that regard, a low friction pad may be mounted to either surface, preferably the outboard surface of pocket **580**. The hypotenuse face **606** of member **588** bears against the opposing outboard land **610** of insert **596**. The overall width of outboard member **588** is greater than that of outboard land **610**, such that the inboard planar face of member **588** acts as an abutment face to fend inboard member **586** off of the surface of the step **612** in insert **596**.

In similar manner inboard wedge member **586** has a hypotenuse face **614** that bears against the inboard land portion **616** of insert **596**. The total width of bolster pocket **580** is greater than the combined width of wedge members, such that a gap is provided between the inboard (non-contacting) face of member **586** and the inboard planar face of pocket **580**. The same relationship, but of opposite hand, exists between pocket **582** and members **592**, **594**.

In an optional embodiment, a low friction pad, or surfacing, can be used at the interface of members **586**, **588** (or **592**, **594**) to facilitate sliding motion of the one relative to the other.

In this arrangement, working of the wedges, i.e., members **586**, **588** against the face of insert **596** will tend to cause both members to move in one direction, namely to their most outboard position. Similarly, members **592** and **594** will work to their most inboard positions. This may tend to maintain the wedge members in an untwisted orientation, and may also tend to maintain the moment arm of the restoring moment at its largest value, both being desirable results.

When a twisting moment of the bolster relative to the side frames is experienced, as in parallelogram deformation, all four sets of wedges will tend to work against it. That is, the diagonally opposite pairs of wedges in the outboard pocket of one side of the bolster and on the inboard pocket on the other side will be compressed, and the opposite side will be, relatively, relieved, such that a differential force will exist. The differential force will work on a moment arm roughly equal to the distance between the centers of the inboard and outboard pockets, or slightly more given the gap arrangement.

In the further alternative arrangement of Figures **10b** and **10d**, a single, stepped wedge **620** is used in place of the pair of split wedges e.g., members **586**, **588**. A corresponding wedge of opposite hand is used in the other bolster pocket.

In the further alternative embodiment of Figures **11a**, a truck bolster **630** has welded bolster pocket inserts **632** and **634** of opposite hands welded into accommodations in its distal end. In this instance, each bolster pocket has an inboard portion **636** and an outboard portion **638**. Inboard and outboard portions **636** and **638** share the same primary angle α , but have secondary angles β that are of opposite hand. Respective inboard and outboard wedges are indicated as **640** and **642**, and each seats over a vertically oriented spring **644**, **646**. In this case bolster **630** is similar to bolster **480** of Figure **8a**, to the extent that the bolster pocket is continuous – there is no land separating the inner and outer portions of the bolster pocket. Bolster **630** is also similar to bolster **510** of Figure **8c**, except that rather than the bolster pockets of opposite hand being separated, they are merged without an intervening land.

In the further alternative of Figure **11b**, split wedge pairs **648**, **650** (inboard) and **652**, **654** (outboard) are employed in place of the single inboard and outboard wedges **640** and **642**.

In some instances the primary angle of the wedge may be steep enough that the thickness of section over the spring might not be overly great. In such a circumstance the wedge may be stepped in cross section to yield the desired thickness of section as show in the details of Figures 11c and 11d.

5

Figure 12a shows the placement of a low friction bearing pad for bolster 480 of Figure 8a. it will be appreciated that such a pad can be used at the interface between the friction damper wedges of any of the embodiments discussed herein. In Figure 12a, the truck bolster is identified as item 660 and the side frame is identified as item 662. Side frame 662 is symmetrical about the truck centerline, indicated as 664. Side frame 662 has side frame columns 668 that locate between the inner and outer gibs 670, 672 of truck bolster 660. The spring group is indicated generally as 674, and has eight relatively large diameter springs arranged in two rows, being an inboard row and an outboard row. Each row has four springs in it. The four central springs 676, 677, 678, 679 seat directly under the bolster end 680. The end springs of each row, 681, 682, 683, 684 seat under respective friction damper wedges 685, 686, 687, 688. Consumable wear plates 689, 690 are mounted to the wide, facing flanges 691, 692 of the side frame columns, 688. As shown in Figure 12b, plates 689, 690 are mounted centrally relative to the side frames, beneath the juncture of the side frame arch 692 with the side frame columns. The lower longitudinal member of the side frame, bearing the spring seat, is indicated as 694.

20

Referring now to Figure 12c and 12e, bolster 660 has a pair of left and right hand, welded-in bolster pocket assemblies 700, 702, each having a cast steel, replaceable, welded-in wedge pocket insert 704. Insert 704 has an inboard-biased portion 706, and an outboard-biased portion 708. Inboard end spring 682 (or 681) bears against an inboard-biased split wedge pair 710 having members 712, 714, and outboard end spring 684 (or 683) bears against an outboard-biased split wedge pair 716 having members 718, 720. As suggested by the names, the outboard-biased wedges will tend to seat in an outboard position as the suspension works, and the inboard-biased wedges will tend to seat in an inboard position.

25

30

Each insert portion 706, 708 is split into a first part and a second part for engaging, respectively, the first and second members of a commonly biased split wedge pair. Considering pair 710, inboard leading member 712 has an inboard planar face 724, that, in use, is intended slidingly to contact the opposed vertically planar face of the bolster pocket. Leading member 712 has a bearing face 726 having primary angle α and

35

secondary angle β . Trailing member **714** has a bearing face **728** also having primary angle α and secondary angle β , and, in addition, has a transition, or step, face **730** that has a primary angle α and a tertiary angle ϕ .

5 Insert **704** has a corresponding an array of bearing surfaces having a primary angle α , and a secondary angle β , with transition surfaces having tertiary angle ϕ for mating engagement with the corresponding surfaces of the inboard and outboard split wedge members. As can be seen, a section taken through the bearing surface resembles a
10 chevron with two unequal wings in which the face of the secondary angle β is relatively broad and shallow and the face associated with tertiary angle ϕ is relatively narrow and steep.

 In Figure **12e**, it can be seen that the sloped portions of split wedge members **718**, **720** extend only partially far enough to overlies a coil spring **726**. In consequence, wedge
15 members **718** and **720** each have a base portion **728**, **730** having a fore-and-aft dimension greater than the diameter of spring **726**, and a width greater than half the diameter of spring **726**. Each of base portions **728**, **730** has a downwardly proud, roughly semi-circular boss **732** for seating in the top of the coil of spring **726**. The upwardly angled portion **734**, **736** of each wedge member **718**, **720** is extends upwardly of base portion
20 **728**, **730** to engage the matingly angled portions of insert **704**.

 In a further alternate embodiment, the split wedges can be replaced with stepped wedges **740** of similar compound profile, as shown In Figure **12f**. In the event that the
25 primary wedge angle is relatively steep (i.e., greater than about 45 degrees when measured from the horizontal, or less than about 45 degrees when measured from the vertical). Figure **12g** shows a welded in insert **742** having a profile for mating engagement with the corresponding wedge faces.

 Figures **13a** and **13b** illustrate a further alternate embodiment, being generally
30 similar to the 2 x 4 spring layout of the embodiment of Figure **8a**. However, in this example, while the damper arrangement is as in Figure **8a**, the central four springs **744**, **745**, **746**, and **747** are installed in inboard and outboard pairs in spring seats in which the springs do not act on a vertical line (assuming no lateral translation of bolster **748** relative to side frame **750**), but rather are splayed to act on a dihedral angle λ from the vertical,
35 this splayed inclination tending to urge bolster **748** to a centered neutral position of lateral

translation relative to side frame **750**. The angle of splay is relatively modest, being in the range of 0 to 10 degrees from the vertical, and may be about 5 degrees.

Figures **14a** and **14b** illustrate a bolster, side frame and damper arrangement in which dampers **760**, **761** are independently sprung on horizontally acting springs **762**, **763** housed in side-by-side pockets **764**, **765** in the distal end of bolster **770**. Although only two dampers are shown, it will be understood that a pair of dampers faces toward each of the opposed side frame columns. Dampers **760**, **761** each include a block **768** and a consumable wear member **772**, the block and wear member having male and female indexing features **774** to maintaining their relative position. An arrangement of this nature permits the damper force to be independent of the compression of the springs in the main spring group. A removable grub screw fitting **778** is provided in the spring housing to permit the spring to be pre-loaded and held in place during installation.

Figure **15** shows a bottom spring seat **780** for a side frame **782**. Bottom Spring seat **780** has a base portion **784** upon which to rest the springs of a spring group, such as those described above, and includes an upstanding peripheral retaining wall, **786**. Retaining wall **786** has an opening, or gate **788** to permit springs to slide into place from the outside. The last spring slid in during installation, or the first spring out during removal, seats in a depression, or relief, or seat, **790**, and is thereby discouraged from moving out through gate **788** while in operation.

Figures **16a**, **16b** and **16c** show a preferred truck **800**, having a bolster **802**, a side frame **804**, a spring group **806**, and a damper arrangement **808**. The spring group has a 5 x 3 arrangement, with the dampers being in a spaced arrangement generally as shown in Figure **8c**, and having a primary damper angle that may tend to be somewhat sharper given the smaller proportion of the total spring group that works under the dampers (*i.e.*, 4 / 15 as opposed to 4 / 9 in Figure **8c**).

The embodiments described have natural vertical bounce frequencies that are less than the 4 – 6 Hz. range of freight cars more generally. In addition, a softening of the suspension to 3.0 hz would be an improvement, yet the embodiments described herein, whether for individual trucks or for overall car response can employ suspensions giving less than 3.0 Hz in the unladen vertical bounce mode. That is, the fully laden natural vertical bounce frequency for one embodiment of rail cars of Figures **1a**, **1b**, **2a**, **2b**, **3a** and **3b** is 1.5 Hz or less, with the unladen vertical bounce natural frequency being less

than 2.0 Hz, and advantageously less than 1.8 Hz. It is preferred that the natural vertical bounce frequency be in the range of 1.0 Hz to 1.5 Hz. The ratio of the unladen natural frequency to the fully laden natural frequency is less than 1.4 : 1.0, advantageously less than 1.3 : 1.0, and even more advantageously, less than 1.25 : 1.0.

5

In the embodiments described above, it is preferred that the spring group be installed without the requirement for pre-compression of the springs. However, where a higher ratio of dead sprung weight to live load is desired, additional ballast can be added up to the limit of the truck capacity with appropriate pre-compression of the springs. It is advantageous for the spring rate of the spring groups be in the range of 6,400 to 10,000 lbs/in per side frame group, or 12,000 to 20,000 lbs/in per truck in vertical bounce.

10

15

20

In the embodiments of Figures **5a**, **8a**, and **16a**, the gibs are shown mounted to the bolster inboard and outboard of the wear plates on the side frame columns. In the embodiments shown herein, the clearance between the gibs and the side plates is desirably sufficient to permit a motion allowance of at least $\frac{3}{4}$ " of lateral travel of the truck bolster relative to the wheels to either side of neutral, advantageously permits greater than 1 inch of travel to either side of neutral, and more preferably permits travel in the range of about 1 or $1 - \frac{1}{8}$ " to about $1 - \frac{5}{8}$ or $1 - \frac{9}{16}$ " inches to either side of neutral, and in one embodiment against either the inboard or outboard stop.

25

30

In a related feature, in the embodiments of Figures **5a**, **8a** and **16a**, the side frame is mounted on bearing adapters such that the side frame can swing transversely relative to the wheels. While the rocker geometry may vary, the side frames shown, by themselves, have a natural frequency when swinging of less than about 1.4 Hz, and preferably less than 1 Hz, and advantageously about 0.6 to 0.9 Hz. Advantageously, when combined with the lateral spring stiffness of a spring group in shear, the overall lateral natural frequency of the truck suspension, for an unladen car, may tend to be less than 1 Hz for small deflections, and preferably less than 0.9 Hz.

35

The most preferred embodiments of this invention combine a four cornered damper arrangement with spring groups having a relatively low vertical spring rate, and a relatively soft response to lateral perturbations. This may tend to give enhanced resistance to hunting, and relatively low vertical and transverse force transmissibility through the suspension such as may give better overall ride quality for high value low

density lading, such as automobiles, consumer electronic goods, or other household appliances, and for fresh fruit and vegetables.

5 While the most preferred embodiments combine these features, they need not all
be present at one time, and various optional combinations can be made. As such, the
features of the embodiments of the various figures may be mixed and matched, without
departing from the spirit or scope of the invention. For the purpose of avoiding redundant
description, it will be understood that the various damper configurations can be used with
spring groups of a 2 X 4, 3 X 3, 3:2:3, 3 X 5 or other arrangement. Similarly, although
10 the discussion involves trucks for rail road cars for carrying low density lading, it applies
to trucks for carrying relatively fragile high density lading such as rolls of paper, for
example, where ride quality is an important consideration. Further, while the improved
ride quality features of the damper and spring sets are most preferably combined with a
low slack, short travel, set of draft gear, for use in a "No Hump" car, these features can be
15 used in cars having conventional slack and longer travel draft gear.

The principles of the present invention are not limited to auto rack rail road cars,
but apply to freight cars, more generally, including cars for paper, auto parts, household
appliances and electronics, shipping containers, and refrigerator cars for fruit and
20 vegetables. More generally, they apply to three piece freight car trucks in situations
where improved ride quality is desired, typically those involving the transport of
relatively high value, low density manufactured goods.

Various embodiments of the invention have now been described in detail. Since
25 changes in and or additions to the above-described best mode may be made without
departing from the nature, spirit or scope of the invention, the invention is not to be limited
to those details, but only according to a purposive construction of the claims as required by
law.

30

Claims

I claim:

1. A truck for a rail road freight car, said truck comprising:
 - a pair of first and second sideframes, said sideframes being seated upon wheelsets for rolling motion in a longitudinal direction along railroad tracks;
 - a truck bolster extending in a transverse direction between the sideframes, said truck bolster having a first end carried by said first sideframe, and a second end carried by said second sideframe;
 - a first group of dampers mounted to work between said first end of said bolster and said first sideframe;
 - a second group of dampers mounted to work between said second end of said bolster and said second sideframe;
 - said first group of dampers including at least a first damper, and a second damper, said first damper being mounted transversely outboard relative to said second damper;
 - said first damper being biased to work between said first end of said truck bolster and said first sideframe;
 - said second damper being biased to work between said first end of said truck bolster and said first sideframe;
 - said first and second dampers each seat in a damper accommodation, the accommodation having a transversely inboard wall and an opposed transversely outboard wall;
 - said first damper being independently biased;
 - said second damper being independently biased; and
 - one of said first and second dampers being independently biased in said transverse direction by its mounting in its accommodation to bear against one of (a) said transversely inboard wall; and (b) said transversely outboard wall.
2. The truck of claim 1 wherein both said first damper and said second damper are biased transversely.
3. The truck of claim 2 wherein said first and second dampers are biased transversely in opposite directions.

4. The truck of claim 3 wherein said first damper is biased transversely outboard, and said second damper is biased transversely inboard.
5. The truck any one of claims 1 to 4 wherein said first damper group includes a third damper, said third damper being independently biased.
6. The truck of claim 5 wherein said first damper group also includes a fourth damper, said fourth damper being independently biased.
7. The truck of claim 6 wherein said third and fourth dampers are both transversely biased.
8. The truck of claim 7 wherein said third and fourth dampers are transversely biased in opposite directions.
9. The truck of claim 8 wherein said third damper is mounted transversely outboard relative to said fourth damper, said third damper is biased transversely outboard, and said fourth damper is biased transversely inboard.
10. The truck of any one of claims 1 to 4, wherein said first damper group includes a third damper and a fourth damper, said third damper being transversely outboard of said fourth damper, all of said first, second, third and fourth dampers being independently biased; and said first, second, third and fourth dampers being located in a four-cornered arrangement.
11. The truck of any one of claims 1 to 10 wherein said first damper is biased by a first spring, said second damper is biased by a second spring, and a third spring is mounted between said first and second springs.
12. The truck of any one of claims 1 to 11 wherein said first sideframe has a long axis, and said dampers of said first group of dampers bear against said sideframe at planar surface interfaces thereof to which said long axis of said first sideframe is normal.
13. The truck of any one of claims 1 to 12 wherein said first sideframe has a long axis, and said first and second dampers bear against said sideframe at surface interfaces thereof that are co-planar.

14. The truck of any one of claims 1 to 13 wherein said dampers include damper wedges having a primary damper angle, α , that is greater than 35 degrees.
15. The truck of any one of claims 1 to 14 wherein said dampers include damper wedges having a transverse damper angle, β , that is in the range of 5 to 20 degrees.
16. A truck for a rail road freight car, said truck comprising:
- a pair of first and second sideframes, said sideframes being seated upon wheelsets for rolling motion in a longitudinal direction along railroad tracks;
 - a truck bolster extending in a transverse direction between the sideframes, said truck bolster having a first end carried by said first sideframe, and a second end carried by said second sideframe;
 - a first group of dampers mounted to work between said first end of said bolster and said first sideframe;
 - a second group of dampers mounted to work between said second end of said bolster and said second sideframe;
 - said first group of dampers including at least a first damper, and a second damper, said first damper being mounted transversely outboard relative to said second damper;
 - said first damper being biased to work between said first end of said truck bolster and said first sideframe;
 - said second damper being biased to work between said first end of said truck bolster and said first sideframe;
 - said first damper being independently biased;
 - said second damper being independently biased;
 - one of said first and second dampers being biased in said transverse direction;
 - said first end of said truck bolster has a first damper accommodation, said first damper being seated therein;
 - said first end of said truck bolster has a second damper accommodation, said second damper being seated therein;
 - said first damper includes a first damper wedge having a primary angle oriented to force said first damper against said first sideframe;
 - said first damper wedge has a secondary angle oriented to bias said first damper transversely; and
 - said first damper accommodation has corresponding primary and secondary angles, said

first damper accommodation being co-operable with said damper wedge of said first damper.

17. The truck of claim 16 wherein: said second damper accommodation is spaced transversely inboard from said first damper accommodation, said second damper being seated in said second damper accommodation; said second damper includes a second damper wedge having a primary angle oriented to force said second damper against said first sideframe; said second damper wedge has a secondary angle oriented to bias said second damper transversely; and said second damper accommodation is co-operable with said damper wedge of said second damper.

18. The truck of claim 16 wherein: said first end of said truck bolster has a first bolster pocket, said first bolster pocket being the accommodation in which said first damper is seated; said first damper includes a first damper wedge having a primary angle oriented to force said first damper against said first sideframe; said first damper wedge has a secondary angle oriented to bias said first damper transversely; and said first bolster pocket is co-operable with said damper wedge of said first damper.

19. The truck of claim 18 wherein: said first end of said truck bolster has a second bolster pocket formed therein, said second bolster pocket being spaced transversely inboard from said first bolster pocket, said second bolster pocket being the accommodation in which said second damper is seated; said second damper includes a second damper wedge having a primary angle oriented to force said second damper against said first sideframe; said second damper wedge has a secondary angle oriented to bias said second damper transversely; and said second bolster pocket is co-operable with said damper wedge of said second damper.

20. The truck of claim 16 wherein said first group of dampers includes a third damper, said third damper being spaced longitudinally from said first damper, and said first end of said truck bolster has another damper accommodation, said third damper being seated therein.

21. The truck of claim 17 wherein:

said first damper group includes a third damper and a fourth damper, each of said third and fourth dampers being independently biased and including damper wedges having respective primary and secondary wedge angles;

said first end of said truck bolster includes a third damper accommodation and a fourth

damper accommodation, said third damper being seated in said third damper accommodation and said fourth damper being seated in said fourth damper accommodation.

22. The truck of claim 21 wherein each of said accommodations of said first end of said bolster includes a surface oriented to accommodate a primary wedge angle and a secondary wedge angle.

23. The truck of claim 21 wherein said third damper is mounted transversely outboard of said fourth damper, said first and third damper wedges being transversely biased in one direction, said second and fourth damper wedges being transversely biased in the opposite direction.

24. The truck of claim 23 wherein said truck has a first spring group and said first spring group includes first, second third and fourth springs, mounted respectively under each of said first, second, third, and fourth damper wedges.

25. The truck of any one of claims 14 to 24 wherein said first sideframe has a long axis, and said dampers of said first group of dampers bear against said sideframe at planar surface interfaces thereof to which said long axis of said first sideframe is normal

26. The truck of any one of claims 14 to 25 wherein said first sideframe has a long axis, and said first and second dampers bear against said sideframe at surface interfaces thereof that are co-planar.

27. The truck of any one of claims 14 to 26 wherein said dampers include damper wedges having a primary damper angle, α , that is greater than 35 degrees.

28. The truck of any one of claims 14 to 26 wherein said dampers include damper wedges having a transverse damper angle, β , that is in the range of 5 to 20 degrees.

29. A truck for a rail road freight car, said truck comprising:
a pair of first and second sideframes, said sideframes being seated upon wheelsets for rolling motion in a longitudinal direction along railroad tracks;
said first sideframe having a first spring group seat;

said second sideframe having a second spring group seat;
a truck bolster extending cross-wise between the sideframes;
said truck bolster having a first end supported by a first spring group, said first spring group being seated in said first spring group seat of said first sideframe;
said truck bolster having a second end supported by a second spring group, said second spring group being seated in said second spring group seat of said second sideframe, said truck bolster having a long axis running between said first and second ends, said long axis defining a transverse direction;
a first group of dampers mounted to work between said first end of said bolster and said first sideframe;
a second group of dampers mounted to work between said second end of said bolster and said second sideframe;
said first group of dampers including at least a first damper and a second damper, said first damper being mounted transversely outboard relative to said second damper,
said first and second dampers each being mounted in an accommodation having a transversely inboard wall and a transversely outboard wall;
said first damper being biased to work between said first end of said truck bolster and said first sideframe by a first spring;
said second damper being biased to work between said first end of said truck bolster and said first sideframe by a second spring;
said first spring being mounted transversely outboard of said second spring; and
each of said first and second dampers also being independently biased in the transverse direction directly by its mounting in its accommodation in said truck bolster to bear respectively against one of (a) said outboard wall; and (b) said inboard wall.

30. The truck of claim 29 wherein said first and second springs are members of said first spring group.
31. The truck of claim 30 wherein said first damper group includes a third damper.
32. The truck of claim 31 wherein said first damper group includes a fourth damper.
33. The truck of claim 32 wherein said third damper is mounted transversely outboard of said fourth damper.

34. The truck of claim 32 wherein said third damper is mounted transversely outboard of said fourth damper and said third and fourth dampers are also biased in the transverse direction.
35. The truck of claim 34 wherein said third damper is biased transversely outboard and said fourth damper is biased transversely inboard.
36. The truck of claim 32 wherein said third damper is biased by a third spring, and said fourth damper is biased by a fourth spring, said third and fourth springs being offset sideways from each other.
37. The truck of any one of claims 29 to 36 wherein said first sideframe has a long axis, and said dampers of said first group of dampers bear against said sideframe at planar surface interfaces thereof to which said long axis of said first sideframe is normal
38. The truck of any one of claims 29 to 37 wherein said first sideframe has a long axis, and said first and second dampers bear against said sideframe at surface interfaces thereof that are co-planar.
39. The truck of any one of claims 29 to 38 wherein said dampers include damper wedges having a primary damper angle, α , that is greater than 35 degrees.
40. The truck of any one of claims 29 to 38 wherein said dampers include damper wedges having a transverse damper angle, β , that is in the range of 5 to 20 degrees.
41. A truck for a rail road freight car, said truck comprising:
a pair of first and second sideframes, said sideframes being seated upon wheelsets for rolling motion in a longitudinal direction along railroad tracks;
said first sideframe having a first spring group seat;
said second sideframe having a second spring group seat;
a truck bolster extending cross-wise between the sideframes;
said truck bolster having a first end supported by a first spring group, said first spring group being seated in said first spring group seat of said first sideframe;
said truck bolster having a second end supported by a second spring group, said second spring group being seated in said second spring group seat of said second

sideframe, said truck bolster having a long axis running between said first and second ends, said long axis defining a transverse direction;
a first group of dampers mounted to work between said first end of said bolster and said first sideframe;
a second group of dampers mounted to work between said second end of said bolster and said second sideframe;
said first group of dampers including at least a first damper and a second damper seated in damper pockets, said first damper being located transversely outboard relative to said second damper;
said first damper being biased to work between said first end of said truck bolster and said first sideframe by a first spring;
said first spring being mounted transversely outboard of said second spring;
said first and second dampers also being biased in the transverse direction;
said first and second dampers include damper wedges;
each of said damper wedges has a primary wedge angle, said primary wedge angle being oriented to urge each respective damper to work between said truck bolster and said first sideframe, and
each of said damper wedges and its respective pocket have a secondary wedge angle, said secondary wedge angle being oriented to urge each said damper, respectively, transversely.

42. The truck of claim 41 wherein one of said damper wedges is biased transversely inboard and one of said damper wedges is biased transversely outboard.

43. The truck of claim 41 wherein: said first spring is a member of said first spring group; said second spring is a member of said first spring group; said first and second springs are coil springs, said coil springs being offset from each other in the transverse direction.

44. The truck of claim 43 wherein said first and second springs are side-by-side.

45. The truck of claim 43 wherein said first and second springs are spaced apart from each other, and a third spring is mounted between said first and second springs.

46. The truck of claim 41 wherein said first end of said truck bolster includes a first accommodation for said first damper, a second accommodation for said second damper, and a

land located intermediate said first and second accommodations.

47. The truck of claim 46 wherein said accommodations are first and second bolster pockets.

48. The truck of claim 41 wherein: said first end of said truck bolster includes a first bolster pocket and a second bolster pocket; said first damper seats in said first bolster pocket; said second damper seats in said second bolster pocket; and said first bolster pocket is segregated from said second bolster pocket.

49. The truck of claim 41 wherein: said first end of said truck bolster has an accommodation formed therein for said first damper and for said second damper; said first spring has a first outside diameter; said second damper has a second outside diameter; and said accommodation has ample width to accept said first and second diameters side by side.

50. The truck of claim 49 wherein said accommodation has a first portion and a second portion, said first portion having a width at least as great as said first outside diameter, said second portion having a width at least as great as said second outside diameter; and said first and second portions each being formed with a transverse bias angle matching said first and second dampers respectively.

51. The truck of any one of claims 41 to 50 wherein: said first sideframe includes a pair of first and second sideframe columns, a tension member, and a compression member, said sideframe columns being longitudinally spaced apart; said side frame columns, said tension member and said compression member co-operating to define a sideframe window; said first end of said truck bolster is received in said sideframe window; and said first and second dampers are oriented to work between said first end of said truck bolster and said first sideframe column.

52. The truck of claim 51 wherein said first sideframe column has a planar wear surface, and said first and second dampers both work against said planar wear surface.

53. The truck of claim 52 wherein said first sideframe has a long axis, and long axis is normal to said planar wear surface.

54. The truck of any one of claims 41 to 53 wherein said dampers include damper wedges having a primary damper angle, α , that is greater than 35 degrees.

55. The truck of any one of claims 41 to 53 wherein said dampers include damper wedges having a transverse damper angle, β , that is in the range of 5 to 20 degrees.

56. A truck for a rail road freight car, said truck comprising:
a pair of first and second sideframes, said sideframes being seated upon wheelsets for rolling motion in a longitudinal direction along railroad tracks;
each of said first and second sideframes having a tension member, a compression member and a pair of first and second sideframe columns, said first and second sideframe columns being longitudinally spaced apart, said tension member having a spring seat, and said compression member, said tension member, and said first and second sideframe columns defining a sideframe window therebetween;
respective first and second spring groups seated on said spring seats of said first and second sideframes;
a truck bolster extending cross-wise between the sideframes;
said truck bolster having a first end received in said sideframe window of said first sideframe, said first end being supported by said first spring group;
said truck bolster having a second end received in said sideframe window of said second sideframe, said second end being supported by said second spring group;
said truck bolster having a long axis running between said first and second ends, said long axis defining a transverse direction;
a first group of dampers mounted to work between said first end of said bolster and said first sideframe, said bolster having a first group of bolster pockets, and said first group of dampers being accommodated therein;
a second group of dampers mounted to work between said second end of said bolster and said second sideframe, said second end of said bolster including a second group of bolster pockets, and said second group of dampers being accommodated therein;
said bolster pockets having respective inboard and outboard bolster pocket side walls;
said first group of dampers including at least a first damper, a second damper, and a third damper, said first damper being mounted transversely outboard relative to said second damper, and said first and second dampen being oriented to work

between said first end of said truck bolster and said first sideframe column of said first sideframe, said third damper being oriented to work against said second sideframe column of said first sideframe;
said first damper being biased to work between said first end of said track bolster and said first sideframe by a first spring;
said second damper being biased to work between said first end of said truck bolster and said first sideframe by a second spring;
said first spring being mounted transversely outboard of said second spring; and
each of said first and second dampers also being independently biased in the transverse direction directly by its interaction with said bolster to bear against respective ones of said inboard and outboard bolster pocket side walls.

57. The truck of claim 56 wherein said first and second dampers are biased in opposite transverse directions.

58. The truck of claim 57 wherein said first damper is biased transversely outboard and said second damper is biased transversely inboard.

59. The truck of claim 56 wherein each of said first and second dampers includes a damper wedge, each said damper wedge having a primary angle oriented to urge the respective damper against said first sideframe column of said first sideframe, and a second angle oriented to bias said wedge transversely.

60. The truck of claim 59 wherein said secondary angle of said wedge of said first damper is opposite to said secondary angle of said wedge of said second damper.

61. The truck of claim 59 wherein said first end of said bolster has a first portion accommodating said primary and secondary angles of said wedge of said first damper, and a second portion accommodating said primary and said secondary angles of said second damper.

62. The truck of claim 59 wherein said first end of said bolster has a first bolster pocket accommodating said first damper, and a second bolster pocket accommodating said second damper.

63. The truck of claim 62 wherein: said truck has a fourth damper mounted transversely

inboard of said third damper; said third and fourth dampers have damper wedges having respective primary and secondary angles; and said first end of said bolster has bolster pockets accommodating said third and fourth dampers.

64. The truck of claim 62 wherein there is an intermediate land between said first and second dampers.

65. The truck of any one of claims 56 to 64 wherein said first sideframe of said truck has rocking pedestal mounts permitting transverse rocking of said first sideframe, said first sideframe having a natural frequency in transverse rocking of less than 1.4 Hz.

66. The truck of any one of claims 56 to 65 wherein said first spring has a diameter of greater than 5 inches.

67. The truck of any one of claims 56 to 66 wherein said first spring group has an overall vertical spring rate and said first group of dampers is biased by springs having a combined spring rate that is at least 20% of said overall vertical spring rate of said first spring group.

68. The truck of any one of claims 56 to 67 wherein said truck has an AAR rating of at least "70 Ton".

69. The truck of any one of claims 56 to 68 wherein said truck has wheels of greater than 33" diameter.

70. The truck of claim 59 wherein said primary angle is in the range of 35 to 60 degrees.

71. The truck of claim 59 wherein said secondary angle is greater than 5 degrees and up to 20 degrees.

72. The truck of claim 59 wherein said wedges also have a tertiary angle working in opposition to said secondary angle.

73. The truck of any one of claims 56 to 72 wherein said truck has gibs mounted to give a range of lateral travel of said truck bolster relative to said sideframes of at least 3/4" to either side of a neutral position.

74. The truck of any one of claims 56 to 73 wherein said first sideframe has a long axis, and said dampers of said first group of dampers bear against said sideframe at planar surface interfaces thereof to which said long axis of said first sideframe is normal.

75. The truck of any one of claims 56 to 74 wherein said first sideframe has a long axis, and said first and second dampers bear against said sideframe at surface interfaces thereof that are co-planar.

76. A three piece railroad freight car truck comprising:
a pair of spaced apart first and second sideframes mounted on wheelsets for rolling in a longitudinal direction along railroad tracks, and a truck bolster extending cross-wise between said sideframes;
said truck bolster having a first end mounted on a first spring group, the first spring group being seated on the first sideframe;
said truck bolster having a second end mounted on a second spring group, the second spring group being seated on the second sideframe;
said truck bolster having four bolster pockets at said first end, and four bolster pockets at said second end;
a first group of dampers mounted to work between said first end of said bolster and said first sideframe, said first group of dampers including a damper in mating engagement with each of said bolster pockets of said first end of said truck bolster;
a second group of dampers mounted to work between said second end of said bolster and said second sideframe, said second group of dampers including a damper in mating engagement with each of said bolster pockets of said second end of said truck bolster;
said dampers and damper pockets having respective primary and secondary angles;
said respective primary angles being oriented to urge said dampers to work longitudinally against said sideframes, said secondary angles being oriented to urge said dampers to work transversely relative to said primary angles; and
said dampers being driven by springs of said spring groups; and
each of said dampers being independently driven.

77. The truck of claim 76 wherein one of said dampers includes a first face for engagement of the sideframe and a second face for engagement of the accommodation, and said first face has an at least partially non-metallic surface.

78. The truck of any one of claims 76 and 77 wherein one of said dampers includes a first face for engagement of the sideframe and a second face for engagement of the accommodation, and said second face has an at least partially non-metallic surface.

79. The truck of any one of claims 76 to 78 wherein said dampers accommodations include a low friction wear member mounted therein.

80. The truck of any one of claims 76 to 79, said dampers having a primary angle of at least 37 deg.

81. The truck of any one of claims 76 to 80 wherein lateral motion of said bolster relative to said sideframes is limited by rigid abutments, said abutments being spaced to allow lateral travel of said bolster of at least 3/4 to either side of a neutral position.

82. The truck of any one of claims 76 to 81 wherein each of said first and second dampers is driven by a damper spring, and said damper spring has a larger diameter than an AAR B432 spring.

83. The truck of any one of claims 76 to 82 wherein each damper is driven by a respective spring of a first spring group upon which a first end of the bolster seats; each spring of said spring group has a vertical spring rate; and the sum of the spring rates of all springs driving dampers is at least 20% of the overall spring rate of the entire first spring group.

84. The truck of claim 80, said primary wedge angle being at least 40 deg.

85. The truck of any one of claims 76 to 84 wherein said first sideframe has a long axis, and said dampers of said first group of dampers bear against said sideframe at planar surface interfaces thereof to which said long axis of said first sideframe is normal.

86. The truck of any one of claims 76 to 85 wherein said first sideframe has a long axis, and said first and second dampers bear against said sideframe at surface interfaces thereof that are co-planar.

87. The truck of any one of claims 76 to 86 wherein said dampers include damper wedges having a primary damper angle, alpha, that is greater than 35 degrees.

88. The truck of any one of claims 76 to 87 wherein said dampers include damper wedges having a transverse damper angle, β , that is in the range of 5 to 20 degrees.
89. The combination of a railroad car truck bolster; a railroad car truck sideframe; and a set of dampers mounted to work between the truck bolster and the sideframe, wherein:
said bolster has a first end and a second end distant therefrom;
said sideframe has a sideframe window through which to admit said first end of said bolster;
said sideframe window is bounded by first and second sideframe columns, said sideframe columns having respective surfaces that face toward said bolster, said surfaces being spaced apart and parallel to each other;
said bolster has a set of damper pockets defining accommodations for said dampers;
said first end of said bolster having a first damper pocket facing said first sideframe column;
said first end of said bolster having a second damper pocket facing said first sideframe column;
said first damper pocket being transversely outboard of said second damper pocket;
said dampers including at least a first damper and a second damper;
said first damper being accommodated in said first damper pocket;
said second damper being accommodated in said second damper pocket;
said first and second dampers each having a friction face oriented to work against said first sideframe column; and
said first and second dampers each being biased transversely.
90. The combination of claim 89 wherein said first and second dampers are biased transversely away from each other.
91. The combination of any one of claims 89 and 90 wherein said first bolster pocket has a side face, and said first damper is biased transversely against said side face.
92. The combination of any one of claims 89 and 90 wherein each of said first and second dampers has a transverse biasing angle, β .
93. The combination of claim 92 wherein β lies in the range of 5 to 20 degrees.

94. The combination of any one of claims 89 to 93 wherein each of said first and second dampers has a wedge shape, and said wedge shape includes an angled face that interacts with the bolster to bias the wedge against the first sideframe column.

95. The combination of claim 94 wherein said angled face has a primary wedge angle of greater than 35 degrees.

96. The combination of any one of claims 89 to 94 wherein said combination includes a spring group mounted to said sideframe, said first end of said bolster being mounted to said spring group, and said first and second dampers being independently driven by members of said spring group.

97. The combination of claim 96 wherein said bolster includes a land between said first pocket and said second pocket, said land defining a spring seat for a spring of said spring group.

98. The combination of any one of claims 89 – 97 wherein said bolster has first, second, third, and fourth damper pockets at said first end thereof, and respective first, second, third and fourth dampers mounted in said bolster pockets; said first and second dampers are mounted to work against a first planar friction surface of said first sideframe column; said third and fourth dampers are mounted to work against a second planar friction surface of said second sideframe column; said first and second dampers are biased transversely away from each other; and said third and fourth dampers are biased away from each other; said first, second, third, and fourth dampers have respective transverse angles, β ; and β is in the range of 5 to 20 degrees.




Figure 1a






Figure 1b



Section Outboard of Main Bolster
with Bolster Removed

Section at Main Bolster

Figure 1c



Partial Section at Railcar & Truck
with Springs Removed

Half Side View

Figure 1d




Figure 2b




Figure 2a




Figure 3b





Figure 3a






Figure 4a




Figure 4b




Figure 5a




Figure 5b




Figure 5d




Figure 5e




Figure 5f




Figure 6a




Figure 6b





Figure 6c

FIGURE 7.






Figure 8a

Figure 8b




Figure 8c










Figure 8d

Figure 9










Figure 12a




Figure 12b




Figure 12c




Figure 12d




Figure 12e




Figure 12f




Figure 12g




Figure 13a




Figure 13b




Figure 14a




Figure 14b




Figure 15




Figure 16a




Figure 16d




Figure 16e




Figure 16b




Figure 16c

