

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2015202808 B2**

(54) Title
Transforming sensory representations

(51) International Patent Classification(s)
G06F 3/0481 (2013.01) **G06Q 50/00** (2012.01)

(21) Application No: **2015202808** (22) Date of Filing: **2015.05.25**

(30) Priority Data

| | | |
|-------------------|-------------------|--------------|
| (31) Number | (32) Date | (33) Country |
| 14/334,939 | 2014.07.18 | US |

(43) Publication Date: **2016.02.04**

(43) Publication Journal Date: **2016.02.04**

(44) Accepted Journal Date: **2020.04.16**

(71) Applicant(s)
The Boeing Company

(72) Inventor(s)
Howard, Emily Louise; Laughlin, Brian Dale; Howe, Wayne Richard

(74) Agent / Attorney
Spruson & Ferguson, GPO Box 3898, Sydney, NSW, 2001, AU

(56) Related Art
US 20090190857 A1

2015202808 25 May 2015

TRANSFORMING SENSORY REPRESENTATIONS

ABSTRACT

5 A computer-implemented method and apparatus for modifying
an entity sensory representation (102). An entity sensory
representation (102) representing an entity (108) is received.
The entity sensory representation (102) comprises a plurality of
sensory representations (112) that represent a plurality of
0 items (110) that are part of the entity (108). Each of the
plurality of items (110) is associated with a set of values
(130) for a set of measurable factors of interest (124). A set
of scale factors (138) is calculated for each of the plurality
of sensory representations (112) based on the set of values
5 (130) associated with the each of the plurality of items (110).
The plurality of sensory representations (112) is modified using
the set of scale factors (138) to form a plurality of modified
sensory representations (132) that establish a relative
relationship between the plurality of items (110) represented by
0 the plurality of modified sensory representations (132) with
respect to the set of measurable factors of interest (124).

TRANSFORMING SENSORY REPRESENTATIONS**TECHNICAL FIELD**

5 The present disclosure relates generally to representing
entities in a manner recognizable by the human senses. More
particularly, the present disclosure relates to a method and
apparatus for modifying an entity sensory representation to
establish a relative relationship between the items in an entity
0 represented by the entity sensory representation with respect to
one or more factors of interest.

BACKGROUND

5 In some situations, understanding or analyzing an entity
that is made up of multiple items may require understanding or
analyzing a relative relationship between the items with respect
to some category of interest. For example, understanding how
the different regions of the human body are seen from the
0 perspective of the brain may require understanding how richly
innervated the different regions are by the brain.

 The term "homunculus" is generally used to mean any
representation of a small or miniature human being. For
example, the homunculus may take the form of a three-dimensional
25 physical model, a two-dimensional image, a three-dimensional
computer-aided design model, or some other type of
representation. A cortical homunculus is a modified version of
a typical homunculus. With a cortical homunculus, the sizes of
the different anatomical regions of the human body are in
30 proportion to the amount of brain tissue associated with the
anatomical regions in the sensorimotor cortex. This type of
visual representation of the human body provides an
understanding of how the various anatomical regions are weighted
in terms of their relative significance in the human brain.

In some situations, it may be desirable to apply this concept of providing a visual representation of the relative relationship of the different anatomical regions of the human body with respect to the amount of sensorimotor cortical tissue designated for the different anatomical regions to other disciplines. Therefore, it would be desirable to have a method and apparatus that take into account the natural sensory processing and understanding capabilities of humans, as well as other possible aspects, and apply these capabilities to other disciplines.

SUMMARY

According to one aspect of the present invention, there is provided an entity representation apparatus that comprises: a processor coupled to a memory; a transformer in communication with the processor and configured to receive, dynamically in real time, a sensory representation of an entity that comprises a set of measurable factors of interest, such that the sensory representation comprises: at least one of a sense of: sound, smell, touch, sight, and taste, that represent, dynamically in real-time, a significance of each factor, in the set of measurable factors of interest, relative to other factors in the set of measurable factors of interest of the entity; and a plurality of sensory representations that represent a plurality of items that are part of the entity, in which each of the plurality of items is associated with a set of values for a set of measurable factors of interest of the entity; the transformer further configured to continuously calculate in real-time, based on the set of values associated with the each of the plurality of items, a set of scale factors for the each of the plurality of sensory representations; and the transformer further configured to dynamically modify in real-time the plurality of sensory representations, based on the set of scale factors, to form a plurality of modified sensory representations that dynamically in real-time establish the significance of each factor in the set of measurable factors of interest relative to other factors in the set of measurable factors of interest.

According to another aspect of the present invention, there is provided a computer-implemented method for modifying a sensory representation that represents an entity, the method comprising a transformer: receiving the sensory representation as at least one of a sense of: sound, smell, touch, sight, and taste, the sensory representation comprising a plurality of sensory representations dynamically representing in real-time a plurality of items that are part of the entity; associating each of the plurality of items with a set of values for a set of measurable factors of interest of the entity; dynamically calculating in real time, using the set of values, a set of scale factors for each of the plurality of sensory representations; and dynamically modifying in real-time, using the set of scale factors and forming a plurality of modified sensory representations establishing continuously in real-time a significance between the plurality of items represented by the plurality of modified sensory representations dynamically indicating in real-time a significance of each factor, in the set of measurable factors of interest, relative to other factors in the set of measurable factors of interest of the entity, the plurality of sensory representations.

According to another aspect of the present invention, there is provided a computer-implemented method for automating a transformation of a sensory representation of an entity into a transformed sensory representation of the entity, the computer-implemented method comprising a transformer: forming a sensory representation of the entity, the sensory representation being at least one of a sense of: a sound, a smell, a touch, a sight, and a taste; receiving the sensory representation comprising a plurality of portions that represent a plurality of items forming the entity; identifying, for each of the plurality of items, a set of values for a set of measurable factors of interest of the entity; dynamically calculating, in real-time, using the set of values associated with the each of the plurality of items, a set of scale factors for each of the plurality of portions; forming a plurality of modified portions, comprising sensory representations for each of the plurality of portions, via modifying, using the set of scale factors identified for the each of the plurality of portions; and dynamically forming, in real-time, the transformed sensory representation of the entity via adjusting, for each of the plurality of modified portions, a center point of a boundary of a dimension for each modified portion relative to each other modified portion with respect to a total output range for the transformed sensory representation of the entity, wherein the transformed sensory representation of the entity dynamically establishes, in real-time, a relative relationship between the plurality of items, of the entity, represented by the plurality of modified portions with respect to the set of measurable factors of interest of the entity.

In one illustrative embodiment, an apparatus comprises a transformer. The transformer receives an entity sensory representation that represents an entity. The entity sensory representation comprises a plurality of sensory representations that represent a plurality of items that are part of the entity. Each of the plurality of items is associated with a set of values for a set of measurable factors of interest. The transformer calculates a set of scale factors for each of the plurality of sensory representations based on the set of values associated with the each of the plurality of items. The transformer modifies the plurality of sensory representations using the set of scale factors to form a plurality of modified sensory representations that establish a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the set of measurable factors of interest.

In another illustrative embodiment, a computer-implemented method for modifying an entity sensory representation that represents an entity is provided. The entity sensory representation that represents the entity is received. The entity sensory representation comprises a plurality of

sensory representations that represent a plurality of items that are part of the entity. Each of the plurality of items is associated with a set of values for a set of measurable factors of interest. A set of scale factors is calculated for each of the plurality of sensory representations based on the set of values associated with the each of the plurality of items. The plurality of sensory representations is modified using the set of scale factors to form a plurality of modified sensory representations that establish a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the set of measurable factors of interest.

In yet another illustrative embodiment, a computer-implemented method for automating the transformation of an entity image into a transformed entity image is provided. The entity image representing an entity is received. The entity image comprises a plurality of image portions that represent a plurality of items that are part of the entity. A set of values for a set of measurable factors of interest is identified for each of the plurality of items. A set of scale factors is calculated for the each of the plurality of image portions based on the set of values associated with the each of the plurality of items. The plurality of image portions is modified using the set of scale factors identified for the each of the plurality of image portions to form a plurality of modified image portions. A position of the plurality of modified image portions is adjusted relative to each other with respect to a total display area to form the transformed entity image. The transformed entity image visually establishes a relative relationship between the plurality of items represented by the plurality of modified image portions with respect to the set of measurable factors of interest.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of a transformer in the form of a block diagram in accordance with an illustrative embodiment;

Figure 2 is an illustration of a set of entities and a set of entity sensory representations in the form of a block diagram in accordance with an illustrative embodiment;

Figure 3 is an illustration of a display of an aircraft image that visually represents an aircraft in accordance with an illustrative embodiment;

Figure 4 is an illustration of display areas for the image portions of an aircraft image in accordance with an illustrative embodiment;

Figure 5 is an illustration of a table indicating the energy usage of the different aircraft sections of an aircraft in accordance with an illustrative embodiment;

Figure 6 is an illustration of a display of a transformed aircraft image in accordance with an illustrative embodiment;

Figure 7 is an illustration of a display of a picture cloud representing a social networking group in accordance with an illustrative embodiment;

Figure 8 is an illustration of a table indicating the social networking activity of members in a social networking group in accordance with an illustrative embodiment;

Figure 9 is an illustration of a display of a transformed picture cloud in accordance with an illustrative embodiment;

Figure 10 is an illustration of an audio recording group representing an alert system in accordance with an illustrative embodiment;

Figure 11 is an illustration of a table indicating the threat level for alerts in an alert system in accordance with an illustrative embodiment;

Figure 12 is an illustration of a transformed audio recording group in accordance with an illustrative embodiment;

Figure 13 is an illustration of an audio recording representing manufacturing instructions in accordance with an illustrative embodiment;

Figure 14 is an illustration of a table indicating the importance of the different steps for performing a manufacturing operation in accordance with an illustrative embodiment;

Figure 15 is an illustration of a transformed audio recording in accordance with an illustrative embodiment;

Figure 16 is an illustration of a process for modifying an entity sensory representation that represents an entity in the form of a flowchart in accordance with an illustrative embodiment;

Figure 17 is an illustration of a process for creating an entity sensory representation in the form of a flowchart in accordance with an illustrative embodiment;

Figure 18 is an illustration of a process for calculating a set of scale factors for each of a plurality of sensory representations that form an entity sensory representation in the form of a flowchart in accordance with an illustrative embodiment;

Figure 19 is an illustration of a process for creating a transformed entity sensory representation in the form of a flowchart in accordance with an illustrative embodiment;

Figure 20A and **Figure 20B** are illustrations of a process for creating a transformed entity image in the form of a flowchart in accordance with an illustrative embodiment;

Figure 21 is an illustration of a process for creating a transformed entity sensory representation in the form of a flowchart in accordance with an illustrative embodiment; and

Figure 22 is an illustration of a data processing system in the form of a block diagram in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

The illustrative embodiments recognize and take into account different considerations. For example, the illustrative
5 embodiments recognize and take into account that it may be
desirable to apply the concept of visually representing the
relative relationship between the different anatomical regions
of the human body with respect to their relative significance in
the brain to other disciplines. In particular, the general
0 concept of creating a visual representation that provides the
relative significance between a plurality of items with respect
to some factor of interest may be applied to the aerospace
industry, corporate management, emergency alert systems,
training programs, and any other number of disciplines or
5 applications.

The illustrative embodiments also recognize and take into
account that it may be desirable to transform a visual
representation of an entity based on more than one factor of
interest. Further, the illustrative embodiments recognize and
0 take into account that it may be desirable to transform a
sensory representation corresponding to some other sense other
than the sense of sight. For example, transforming an audio
recording such that the decibel levels of different sections of
the audio recording are adjusted to reflect the relative
25 importance between the different sections of the audio
recordings may be desirable.

Additionally, the illustrative embodiments recognize and
take into account that using a computer system to automate the
process by which a sensory representation is transformed may
30 reduce the time, expense, and labor associated with the
transformation. For example, it may be desirable to automate
the transformation process such that a same visual
representation may be transformed multiple times to form
multiple transformed visual representations corresponding to

different factors of interest. Automating this type of process may significantly reduce the time, expense, and labor needed to create these transformed visual representations as compared to hand-drawing each of the transformed visual representations or manually calculating the needed modifications for each transformation of the visual representation.

Thus, the illustrative embodiments provide a method and apparatus for modifying an entity sensory representation that represents an entity using at least one of the five human senses. In particular, the entity sensory representation may be comprised of a plurality of sensory representations that represent a plurality of items that make up the entity. The entity sensory representation may be modified to create a transformed sensory representation that establishes a relative relationship between the plurality of items represented by the entity sensory representation with respect to a set of measurable factors of interest.

For example, the transformed entity sensory representation may establish the relative significance of the plurality of items in a manner that can be easily understood. When the transformed entity sensory representation is a transformed entity image, the transformed entity image may provide, at a glance, the relative significance of the plurality of items in a manner that can be easily recognized. In some cases, the transformed entity image may be referred to as providing a "snapshot understanding" of the relative significance of the plurality of items. When the transformed entity sensory representation is some other form of sensory output, the human may receive the sensory output as a simple perceptual input that provides a quick, and in some cases, near-instantaneous understanding of the relative significance of the plurality of items.

Referring now to the figures and, in particular, with reference to **Figure 1**, an illustration of a transformer is

depicted in the form of a block diagram in accordance with an illustrative embodiment. In this illustrative example, transformer 100 may be implemented using software, hardware, firmware, or a combination thereof.

When software is used, the operations performed by transformer 100 may be implemented using, for example, without limitation, program code configured to run on a processor unit. When firmware is used, the operations performed by transformer 100 may be implemented using, for example, without limitation, program code and data and stored in persistent memory to run on a processor unit.

When hardware is employed, the hardware may include one or more circuits that operate to perform the operations performed by transformer 100. Depending on the implementation, the hardware may take the form of a circuit system, an integrated circuit, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware device configured to perform any number of operations.

A programmable logic device may be configured to perform certain operations. The device may be permanently configured to perform these operations or may be reconfigurable. A programmable logic device may take the form of, for example, without limitation, a programmable logic array, a programmable array logic, a field programmable logic array, a field programmable gate array, or some other type of programmable hardware device.

In some illustrative examples, the operations and processes performed by transformer 100 may be performed using organic components integrated with inorganic components. In some cases, the operations and processes may be performed by entirely organic components, excluding a human being. As one illustrative example, circuits in organic semiconductors may be used to perform these operations and processes.

As depicted in **Figure 1**, transformer **100** may be implemented using computer system **106** in one illustrative example. Computer system **106** may include one or more computers that are in communication with each other.

Transformer **100** may transform entity sensory representation **102** into transformed entity sensory representation **104**. As used herein, a "sensory representation" is a representation that can be understood by a person using at least one of the five human senses. These five senses include the sense of sight **114**, the sense of sound **116**, the sense of smell **118**, the sense of touch **120**, and the sense of taste **122**.

A sensory representation corresponding to the sense of sight **114** may be referred to as a visual representation. A visual representation may take the form of, for example, without limitation, an image, a three-dimensional physical model, alphanumeric text, an icon, or other type of visual representation.

A sensory representation corresponding to the sense of sound **116** may be referred to as an audible representation. An audible representation may take the form of, for example, without limitation, an audio recording, a sound, music, or some other type of audible representation.

Further, a sensory representation corresponding to the sense of smell **118** may be referred to as an olfactory representation. A sensory representation corresponding to the sense of touch **120** may be referred to as a tactile representation. The tactile representation may take the form of, for example, without limitation, a texture, a temperature, or some other type of representation that may be perceived through touch. A sensory representation corresponding to the sense of taste **122** may be referred to as a gustatory representation.

Entity sensory representation **102** represents entity **108**. As used herein, entity sensory representation may "represent"

entity **108** by symbolizing, presenting a meaning for, presenting an understanding of, standing in for, being an equivalent of, serving as an example of, or providing some other type of indication of entity **108**.

Entity **108** is the whole formed by plurality of items **110**. Entity **108** may take a number of different forms. For example, entity **108** may take the form of a body, a group, a collection, or some other type of "whole" that is comprised of plurality of items **110**. As used herein, an "item" may take the form of a part, a portion of an object or structure, a person, a group of people, a time interval, an alert, a security level, a building, a floor of a building, a section of a shop floor area, a title, an employee number, a social security number, a phone number, an aircraft component, an electronic component, a hardware component, a software component, or some other type of item.

As depicted, entity sensory representation **102** comprises plurality of sensory representations **112** that represent plurality of items **110**. In these illustrative examples, plurality of sensory representations **112** may be individual sensory representations that are collectively referred to as entity sensory representation **102**. In other illustrative examples, plurality of sensory representations **112** may be portions of a single entity sensory representation **102**. Examples of different types of entities and entity sensory representations corresponding to these entities are described in **Figure 2** below.

Set of measurable factors of interest **124** may be used to evaluate or analyze plurality of items **110**. As used herein, a "set of" items may include one or more items. For example, set of measurable factors of interest **124** may include one or more measurable factors of interest.

Measurable factor of interest **126** is an example of one of set of measurable factors of interest **124**. Measurable factor of interest **126** may be an attribute, parameter, characteristic, or

other type of factor that can be measured quantitatively, qualitatively, or both. For example, measurable factor of interest **126** may be, but is not limited to, a level of importance, a salary amount, a level of activity, energy usage, surface area, intensity, amplitude, phase, price, a physical dimension such as width, length, or height, or some other type of factor that can be measured as having a value with some range of values.

Item **127** may be an example of one of plurality of items **110**. With respect to measurable factor of interest **126**, item **127** may have value **128**. Value **128** may be a nominal value, a numeric value, a range of values, a level, a category, a color, a physical quantity, a measure of amount, or some other type of qualitative or quantitative measurement. In other illustrative examples, value **128** may be an audible tone, an audible frequency, an odor, an odor intensity, a texture, a roughness of texture, a taste, or a quality of taste such as saltiness or sweetness.

For example, measurable factor of interest **126** may be length and item **127** may be a structure having a value for the length of about 10 inches. In another example, measurable factor of interest **126** may be a salary amount and item **127** may be an employee having a value for the salary amount of about \$100,000. In yet another example, measurable factor of interest **126** may be energy usage and item **127** may be an aircraft engine having a value for energy usage equal to one of a very low level, a low level, a normal level, a high level, or a very high level.

Each of plurality of items **110** may be associated with a set of values, similar to value **128** described above, for set of measurable factors of interest **124**. For example, item **127** may be associated with set of values **130** for set of measurable factors of interest **124**. In these illustrative examples, transformer **100** may receive input that includes set of values

130 for set of measurable factors of interest 124 for each of
plurality of items 110. In other illustrative examples,
transformer 100 may be configured to identify set of values 130
for set of measurable factors of interest 124 for each of
5 plurality of items 110 based on input data received by
transformer 100.

Transformer 100 is configured to modify plurality of
sensory representations 112 in a manner that establishes a
relative relationship between plurality of items 110 represented
0 by plurality of sensory representations 112 with respect to set
of measurable factors of interest 124. In particular,
transformer 100 may calculate a set of scale factors for each of
plurality of sensory representations 112 based on the set of
values associated with each of plurality of items 110. The set
5 of scale factors may be used to adjust a set of parameters for
each of plurality of sensory representations 112 to form
plurality of modified sensory representations 132. Plurality of
modified sensory representations 132 together form transformed
entity sensory representation 104.

0 In this manner, entity sensory representation 102 may be
homuncularly transformed using the different sets of scale
factors for each of plurality of sensory representations 112 to
form transformed entity sensory representation 104. In other
words, entity sensory representation 102 may be transformed in a
25 manner similar to the manner in which a cortical homunculus is
formed. Transformed entity sensory representation 104 may be
referred to as a homuncularized entity sensory representation.

For example, sensory representation 134 may be one of
plurality of sensory representations 112 and may represent item
30 127. Sensory representation 134 may be associated with set of
parameters 136. A parameter in set of parameters 136 may take a
number of different forms. For example, the parameter may be a
width, a height, a center point, a center point distance, a
transparency value, a contrast value, a decibel level, a speed,

a pitch, a bandwidth, a start time, an end time, a total time, a texture, a thickness, a spiciness level, a sweetness level, or some other type of parameter.

Each of set of parameters **136** may be scalable. In particular, each of set of parameters **136** may be scalable using a linear scale factor, a nonlinear scale factor, or both. The nonlinear scale factor may be, for example, without limitation, an exponential factor, a logarithmic scale factor, or some other type of nonlinear scale factor. In this manner, set of parameters **136** may be referred to as a set of scalable parameters.

Transformer **100** calculates set of scale factors **138** for sensory representation **134** based on set of values **130** for set of measureable factors of interest **124** for item **127** represented by sensory representation **134**. Transformer **100** uses set of scale factors **138** to adjust set of parameters **136** for sensory representation **134** to form modified sensory representation **140**. Depending on set of scale factors **138**, modified sensory representation **140** may be the same or different from sensory representation **134**.

In one illustrative example, set of scale factors **138** may have a one-to-one correspondence with set of parameters **136**. For example, transformer **100** may linearly scale each parameter in set of parameters **136** by a corresponding scale factor in set of scale factors **138**. In other illustrative examples, set of scale factors **138** may include a single scale factor that is used to linearly scale each of set of parameters **136**.

Transformer **100** adjusts set of parameters **136** using set of scale factors **138** to form scaled set of parameters **141**.

Transformer **100** may then use scaled set of parameters **141** to create modified sensory representation **140**.

In one illustrative example, entity sensory representation **102** may take the form of entity image **142**. Entity image **142** may take the form of, for example, without limitation, an aircraft

image, a spacecraft image, a watercraft image, an engine system image, or an image of some other type of entity. In some illustrative examples, entity image **142** may be a combined image formed by multiple images or a single image divisible into image portions. Entity image **142** may represent entity **108**.

When entity sensory representation **102** takes the form of entity image **142**, plurality of sensory representations **112** may take the form of plurality of image portions **144**. Each of plurality of image portions **144** may take the form of a portion of entity image **142** or an individual image used to form entity image **142**. Further, each of plurality of image portions **144** may represent a corresponding item in plurality of items **110**.

Set of parameters **136** for each image portion in plurality of image portions **144** may take the form of, for example, a set of dimensions for each image portion. For example, the set of dimensions for an image portion may include a width and a height for the image portion.

Transformer **100** calculates a set of scale factors for each image portion in plurality of image portions **144** based on the set of values for set of measurable factors of interest **124** associated with the corresponding item in plurality of items **110** represented by each image portion. Transformer **100** then uses these sets of scale factors to adjust the set of parameters for each of plurality of image portions **144** to form scaled sets of parameters. These scaled sets of parameters may then be used to create plurality of modified image portions **146**, which may be an example of plurality of modified sensory representations **132**.

Plurality of modified image portions **146** may form transformed entity image **148**. Transformed entity image **148** with plurality of modified image portions **146** may visually establish the relative relationship between plurality of items **110** represented by plurality of modified image portions **146** with respect to set of measurable factors of interest **124**. Transformed entity image **148** with plurality of modified image

portions **146** may provide a "snapshot understanding," or an understanding at a glance, of the relative relationship between plurality of items **110** with respect to set of measurable factors of interest **124**.

In these illustrative examples, transformer **100** may send transformed entity sensory representation **104** to output device **150**. Output device **150** may output transformed entity sensory representation **104** in a manner that can be understood using at least one of the five human senses.

For example, when transformed entity sensory representation **104** is a transformed visual representation, output device **150** may take the form of display device **152**. Display device **152** may visually present a display of the transformed visual representation. In particular, when transformed entity sensory representation **104** takes the form of transformed entity image **148**, display device **152** may be used to visually present a display of transformed entity image **148**. Display device **152** may take the form of a monitor, a screen, a liquid crystal display device, a plasma display device, a touch screen device, a projection system, or some other type of display device.

Thus, transformer **100** allows entity sensory representation **102** of entity **108** to be transformed in a manner that reflects a relative measure of set of measurable factors of interest **124** for plurality of items **110** that make up entity **108**. This type of transformed entity sensory representation **104** may provide a user with a way to quickly and easily understand the relative relationship between plurality of items **110** with respect to set of measurable factors of interest **124** without needing to rely on the sets of values identified for plurality of items **110**.

This type of understanding may be preferable for a user that does not have the training to understand or process the sets of values for the plurality of items. For example, a user may need to understand a relative significance of each of plurality of items **110** with respect to some measurable factor of

interest for performing a type of operation. However, the user may not have the training, knowledge, or skill to understand, interpret, or process the data to identify the value for the measurable factor of interest for each of plurality of items **110**. Transformed entity sensory representation **104** may provide the user with the relative significance of each of plurality of items **110** without the user needing to understand, interpret, or process the data.

Further, implementing this type of evaluation or analysis within a computer system, such as computer system **106**, allows the process to be automated. For example, a new transformed entity sensory representation may be quickly and easily created by transformer **100** when transformer **100** receives new input that includes a new set of values for set of measurable factors of interest **124** for at least one of plurality of items **110**.

Further, transformer **100** may be capable of quickly and easily creating a new transformed entity sensory representation for different sets of measurable factors of interest. In this manner, entity sensory representation **102** may be transformed from a baseline for entity sensory representation in any number of ways and any number of times. This baseline may be the initial or original values for the set of parameters for each of plurality of sensory representations that make up entity sensory representation **102**.

Depending on the implementation, the sets of values for set of measurable factors of interest **124** for plurality of items **110** may be static or dynamic. When the sets of values are dynamic, transformer **100** may, in some cases, be configured to update the sets of scale factors calculated for plurality of sensory representations **112** in correspondence with changes to the sets of values. Further, transformer **100** may update transformed entity sensory representation **104** in correspondence with the updates to the sets of scale factors. In this manner, the

changing relative relationship between plurality of items 110 may be reflected in substantially real-time or near real-time.

As one illustrative example, transformer 100 may acquire the sets of values for plurality of items 110 in sensor data generated by one or more sensor systems configured to monitor set of measurable factors of interest 124 for plurality of items 110. The sets of values may be dynamic in that the sensor data may be received continuously over time. Transformer 100 may adjust the sets of scale factors for plurality of sensory representations 112 to update plurality of modified sensory representations 132 as the sets of values change. Computer system 106 may allow these adjustments and updates to be performed in substantially real-time.

With reference now to **Figure 2**, an illustration of a set of entities and a set of entity sensory representations is depicted in the form of a block diagram in accordance with an illustrative embodiment. Set of entities 200 and set of entity sensory representations 202 are depicted.

Set of entities 200 includes aircraft 204, corporate management team 206, manufacturing instructions 208, and alert system 210. Each of aircraft 204, corporate management team 206, manufacturing instructions 208, and alert system 210 is an example of one implementation for entity 108 in **Figure 1**.

Aircraft 204 is comprised of plurality of aircraft sections 212. Corporate management team 206 is comprised of plurality of employees 214. Manufacturing instructions 208 is comprised of plurality of steps 216. Alert system 210 is comprised of plurality of alerts 218. Each of plurality of aircraft sections 212, plurality of employees 214, plurality of steps 216, and plurality of alerts 218 is an example of one implementation for plurality of items 110 in **Figure 1**.

As depicted, set of entity sensory representations 202 includes aircraft image 220, picture cloud 222, audio recording 224, and audio recording group 226. Each of aircraft image 220,

picture cloud 222, audio recording 224, and audio recording group 226 may be an example of one implementation for entity sensory representation 102 in **Figure 1**. Aircraft image 220, picture cloud 222, audio recording 224, and audio recording group 226 are sensory representations of aircraft 204, corporate management team 206, manufacturing instructions 208, and alert system 210, respectively.

In this illustrative example, aircraft image 220 may be comprised of plurality of image portions 228. Picture cloud 222 may be comprised of plurality of employee pictures 230. Further, audio recording 224 may be comprised of plurality of audio sections 232. Audio recording group 226 may be comprised of plurality of audio recordings 234.

Each of plurality of image portions 228, plurality of employee pictures 230, plurality of audio sections 232, and plurality of audio recordings 234 may be an example of one implementation for plurality of sensory representations 112 in **Figure 1**. Further, plurality of image portions 228, plurality of employee pictures 230, plurality of audio sections 232, and plurality of audio recordings 234 represent plurality of aircraft sections 212, plurality of employees 214, plurality of steps 216, and plurality of alerts 218, respectively.

In this illustrative example, the set of parameters that are scalable for each of plurality of image portions 228 may be set of dimensions 236. In one illustrative example, set of dimensions 236 includes a width and a height of an image portion. The set of parameters that are scalable for each of plurality of employee pictures 230 may be set of dimensions 238.

As depicted, each of plurality of audio sections 232 may have a single scalable parameter, which is decibel level 240. Similarly, each of plurality of audio recordings 234 may have a single scalable parameter, which is decibel level 242.

Although only sensory representations corresponding to the sense of sight and sound are depicted in set of entity sensory

representations **202**, set of entity sensory representations **202** may include other types of sensory representations in other illustrative examples. For example, other entity sensory representations may be tactile, olfactory, or gustatory. In yet other illustrative examples, an entity sensory representation may correspond to more than one human sense.

The illustrations of transformer **100** in **Figure 1** and set of entities **200** and set of entity sensory representations **202** in **Figure 2** are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

In some cases, transformer **100** may normalize the set of parameters for each of plurality of sensory representations **112** prior to adjusting these parameters. For example, set of parameters **136** may be normalized to form normalized set of parameters **154**. Normalized set of parameters **154** may then be adjusted using set of scale factors **138** to form scaled set of parameters **141**.

In other illustrative examples, set of entities **200** may include other types of entities. For example, set of entities **200** may include a spacecraft, a building, a corporate infrastructure, a financial portfolio, a safety manual, or some other type of entity.

With reference now to **Figure 3**, an illustration of a display of an aircraft image that visually represents an aircraft is depicted in accordance with an illustrative embodiment. In this illustrative example, display **300** of aircraft image **301** may be visually presented by a display device such as, for example, without limitation, display device **152** in

Figure 1. In particular, aircraft image **301** is an example of one implementation for transformed entity image **148**.

Aircraft image **301** in display **300** is a visual representation of an aircraft. The aircraft is an example of an entity, such as entity **108** in **Figure 1**.

As depicted, aircraft image **301** may be comprised of plurality of image portions **303**. Plurality of image portions **303** includes fuselage portion **302**, cockpit portion **304**, tail portion **306**, rudder portion **307**, right wing portion **308**, left wing portion **310**, right aileron portion **312**, left aileron portion **314**, right engine portion **316**, and left engine portion **318**. Plurality of image portions **303** represents the different aircraft sections or aircraft regions of an aircraft that are of interest.

In this illustrative example, a total display area for display **300** may be defined by identifying top boundary **320**, left boundary **322**, bottom boundary **324**, and right boundary **326** of display **300**. Identifying the boundaries of display **300** allows the coordinates for the four corners formed by these boundaries to be identified. In particular, the x,y-coordinates for each corner may be identified. In particular, the coordinates for first corner **328**, second corner **330**, third corner **332**, and fourth corner **334** may be identified. With these corner coordinates, the x,y-coordinates for center point **336** may also be identified. Center point **336** is the x,y center of display **300**.

In some illustrative examples, the total display area for display **300** may also be three-dimensional and may have three-dimensional boundaries. In this manner, center point **336** may comprise three-dimensional coordinates, such as x,y,z-coordinates. In other illustrative examples, when other senses are being used, the total output area for the output device may be n-dimensional and have n-dimensional boundaries.

Consequently, a center point of this total output area may comprise n -dimensional coordinates.

All of this information may be used to define a plurality of display areas within display **300** corresponding to plurality of image portions **303** of aircraft image **301**. These display areas are outlined in **Figure 4** below.

With reference now to **Figure 4**, an illustration of display areas for the image portions of aircraft image **301** from **Figure 3** is depicted in accordance with an illustrative embodiment. In this illustrative example, plurality of display areas **400** has been defined within display **300**.

As depicted, plurality of display areas **400** includes fuselage display area **402**, cockpit display area **404**, tail display area **406**, rudder display area **407**, right wing display area **408**, left wing display area **410**, right aileron display area **412**, left aileron display area **414**, right engine display area **416**, and left engine display area **418**. Fuselage display area **402**, cockpit display area **404**, tail display area **406**, rudder display area **407**, right wing display area **408**, left wing display area **410**, right aileron display area **412**, left aileron display area **414**, right engine display area **416**, and left engine display area **418** contain fuselage portion **302**, cockpit portion **304**, tail portion **306**, rudder portion **307**, right wing portion **308**, left wing portion **310**, right aileron portion **312**, left aileron portion **314**, right engine portion **316**, and left engine portion **318**, respectively.

In one illustrative example, coordinates may be identified for each of the display areas identified. For example, without limitation, a leftmost x-coordinate, a rightmost x-coordinate, a topmost y-coordinate, and a bottommost y-coordinate may be identified for each of the display areas. These coordinates may be used to establish a width and a height for each of the display areas.

A reference center point for each of the display areas may then be identified using the coordinates, the width and height, or both. For example, cockpit center point **420** may be identified for cockpit display area **404**. Thereafter, a distance from the reference center point identified for each of the display areas to center point **336** is identified.

With reference now to **Figure 5**, an illustration of a table indicating the energy usage of the different aircraft sections of an aircraft is depicted in accordance with an illustrative embodiment. Table **500** has column **502**, column **503**, and column **504**.

Column **502** identifies the different aircraft sections of the aircraft represented by aircraft image **301** in **Figures 3-4**. Column **503** identifies the energy usage for each of the aircraft sections. In this illustrative example, energy usage is an example of a measurable factor of interest, such as measurable factor of interest **126** in **Figure 1**. Column **504** identifies the scale factor that may be calculated for the image portions corresponding to the aircraft sections identified in column **502**.

Row **506** indicates that the fuselage of the aircraft has an energy usage with a value of low. Row **506** further indicates that the corresponding scale factor to be used for fuselage portion **302** of aircraft image **301** in **Figures 3-4** is 1.

Row **508** indicates that the cockpit of the aircraft has an energy usage with a value of high. Row **508** further indicates that the corresponding scale factor to be used for cockpit portion **304** of aircraft image **301** in **Figures 3-4** is 2.

Row **510** indicates that the right engine of the aircraft has an energy usage with a value of very high. Row **510** further indicates that the corresponding scale factor to be used for right engine portion **316** of aircraft image **301** in **Figures 3-4** is 3.

The scale factors identified in column **504** may be used to modify the corresponding image portions of aircraft image **301** in

Figures 3-4. In particular, these scale factors may be used to resize the display areas of display **300** corresponding to these image portions to resize the image portions.

With reference now to **Figure 6**, an illustration of a display of a transformed aircraft image is depicted in accordance with an illustrative embodiment. In this illustrative example, aircraft image **301** in **Figures 3-4** has been transformed into transformed aircraft image **600** within display **300**. In particular, scale factors identified in column **504** of table **500** in **Figure 5** have been used to modify the image portions of aircraft image **301** in **Figures 3-4** to form transformed aircraft image **600**.

Transformed aircraft image **600** includes plurality of modified image portions **601** that have been modified based on the scale factors identified in column **504** in table **500** in **Figure 5**. In particular, each of plurality of image portions **303** from **Figure 3** has been increased in size by the corresponding scale factor in **Figure 5**.

In this illustrative example, the width and height of each of plurality of display areas **400** in **Figure 4** may be linearly scaled by the corresponding scale factor to form the corresponding modified image portion. Further, in this illustrative example, each modified image portion may be centered within display **300** at the previously calculated reference center point for the corresponding original display area. The type of transformed entity image that results may be referred to as an overlapping transformed entity image.

In other illustrative examples, the new modified image portion may be centered about a new center point within display **300**. For example, the distance from the previously calculated reference center point for the original display area to display center point **336** may be scaled by the corresponding scale factor. The new modified image portion may be centered at a new center point having the scaled distance away from center point

336. The type of transformed entity image that results by performing this process for each of the modified image portions may be referred to as an exploded, transformed entity image.

In some cases, this type of process may result in transformed aircraft image 600 requiring a larger display area. Consequently, transformed aircraft image 600 may then be adjusted in the entirety such that transformed aircraft image 600 may be displayed within the original total display area of display 300. In particular, transformed aircraft image 600 may be scaled to fit within the original total display area of display 300.

Plurality of modified image portions 601 include modified fuselage portion 602, modified cockpit portion 604, modified tail portion 606, modified rudder portion 607, modified right wing portion 608, modified left wing portion 610, modified right aileron portion 612, modified left aileron portion 614, modified right engine portion 616, and modified left engine portion 618. As depicted, modified cockpit portion 604 is larger than cockpit portion 304 in Figure 3. Further, modified right engine portion 616 and modified left engine portion 618 are larger than right engine portion 316 and left engine portion 318, respectively, in Figure 3.

Modified cockpit portion 604, modified right engine portion 616, and modified left engine portion 618 are larger, proportionally, than the other modified portions of transformed aircraft image 600. The proportionally increased size of modified cockpit portion 604, modified right engine portion 616, and modified left engine portion 618 provides an understanding, at a glance, that the cockpit, right engine, and left engine, respectively, have increased energy usage as compared to the other aircraft sections of the aircraft. In this manner, the relative significance of the aircraft sections represented by plurality of modified image portions 601 with respect to energy

usage may be quickly and easily understood using transformed aircraft image 600.

With reference now to **Figure 7**, an illustration of display of a picture cloud representing a social networking group is depicted in accordance with an illustrative embodiment. In this illustrative example, picture cloud 700 is an example of one implementation for entity sensory representation 102 in **Figure 1**. In particular, picture cloud 700 may be an example of one implementation for entity image 142 in **Figure 1**.

Picture cloud 700 visually represents a social networking group. This social networking group may be a singular group in which the members of the social networking group are grouped based on one or more factors. As one illustrative example, the social networking group may be comprised of members that have signed up on a dating website, a group of buyers, a group of sellers, or some other type of group. As depicted, picture cloud 700 includes plurality of member pictures 702, which may be an example of one implementation for plurality of image portions 144 in **Figure 1**. Plurality of member pictures 702 includes member pictures 704, 706, 708, 710, 712, 714, 716, and 718.

Plurality of member pictures 702 represents the plurality of members in the social networking group. The measurable factor of interest for each of the plurality of members may be a level of social networking activity for each member. The value for this level of social networking activity may be the number of posts created by each member.

In this illustrative example, each of plurality of member pictures 702 may be considered at "baseline." In particular, each of plurality of member pictures 702 has a same width 720 and height 722.

With reference now to **Figure 8**, an illustration of a table indicating the social networking activity of members in a social networking group is depicted in accordance with an illustrative

embodiment. In this illustrative example, table 800 has column 802, column 803, and column 804.

Column 802 identifies the different members of the social network group represented by plurality of member pictures 702 in Figure 7. Column 803 identifies the social networking activity of each of the members based on the number of posts created by each member. Column 804 identifies the scale factor calculated for each of plurality of member pictures 702 based on the values for social networking activity of the members represented by plurality of member pictures 702 identified in column 803.

With reference now to Figure 9, an illustration of a display of a transformed picture cloud is depicted in accordance with an illustrative embodiment. In this illustrative example, picture cloud 700 from Figure 7 has been transformed using the scale factors identified in column 804 in Figure 8 to form transformed picture cloud 900. Transformed picture cloud 900 may be an example of one implementation for transformed entity image 148 in Figure 1.

Transformed picture cloud 900 includes plurality of modified member pictures 902. In this illustrative example, each of plurality of member pictures 702 from Figure 7 has been resized using the corresponding scale factor identified in column 804 to form plurality of modified member pictures 902. Plurality of modified member pictures 902 includes modified member pictures 904, 906, 908, 910, 912, 914, 916, and 918, which are the modified versions of member pictures 704, 706, 708, 710, 712, 714, 716, and 718, respectively, in Figure 7.

In some cases, the relative position of each of plurality of modified member pictures 902 within transformed picture cloud 900 may be determined based on scale factors used to perform the transformation. For example, plurality of modified member pictures 902 may be arranged from largest scale factor to smallest scale factor in a left to right direction, in a clockwise manner, or in some other manner.

With reference now to **Figure 10**, an illustration of an audio recording group representing an alert system is depicted in accordance with an illustrative embodiment. In this illustrative example, audio recording group **1000** is an example of one implementation for entity sensory representation **102** in **Figure 1**. Audio recording group **1000** may represent an alert system.

As depicted, audio recording group **1000** includes plurality of audio recordings **1001** that represent a plurality of alerts that form the alert system. Plurality of audio recordings **1001** may be an example of one implementation for plurality of sensory representations **112** in **Figure 1**.

Each of the plurality of alerts may be an alert that indicates a threat to a particular room in a building as identified by a security system. The measurable factor of interest for these alerts may be the threat level. The value for the threat level may be selected from one of very minor, minor, moderate, serious, and very serious.

Plurality of audio recordings **1001** includes audio recordings **1002**, **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, **1016**, and **1018**. In this illustrative example, each of plurality of audio recordings **1001** is at a baseline at which each audio recording is configured to play with a same loudness or decibel level. This baseline may be set to, for example, a moderate threat level.

With reference now to **Figure 11**, an illustration of a table indicating the threat level for alerts in an alert system is depicted in accordance with an illustrative embodiment. In this illustrative example, table **1100** includes column **1102**, column **1103**, and column **1104**.

Column **1102** identifies the different alerts represented by plurality of audio recordings **1001** in **Figure 10**. Column **1103** identifies a current threat level for each of these alerts. Column **1104** identifies the scale factor calculated for use in

modifying each of plurality of audio recordings **1001** in **Figure 10** based on the threat level of the corresponding alert.

With reference now to **Figure 12**, an illustration of a transformed audio recording group is depicted in accordance with an illustrative embodiment. In this illustrative example, audio recording group **1000** from **Figure 10** has been transformed into transformed audio recording group **1200**. Transformed audio recording group **1200** is another example of one implementation for transformed entity sensory representation **104** in **Figure 1**.

Transformed audio recording group **1200** includes plurality of modified audio recordings **1201**, which may be another example of one implementation for plurality of modified sensory representations **132** in **Figure 1**. Each of plurality of audio recordings **1001** in **Figure 10** has been modified using the corresponding scale factor identified in **Figure 11** to form plurality of modified audio recordings **1201**.

As depicted, plurality of modified audio recordings **1201** includes modified audio recordings **1202**, **1204**, **1206**, **1208**, **1210**, **1212**, **1214**, **1216**, and **1218**. Modified audio recordings **1202**, **1204**, **1206**, **1208**, **1210**, **1212**, **1214**, **1216**, and **1218** may be the modified versions of audio recordings **1002**, **1004**, **1006**, **1008**, **1010**, **1012**, **1014**, **1016**, and **1018**, respectively.

Plurality of modified audio recordings **1201** may be played in succession, one after the other. A user, listening to plurality of modified audio recordings **1201**, may be able to quickly and easily understand the relative significance with respect to the threat level of each of the alerts represented by plurality of modified audio recordings **1201**. For example, alerts corresponding to higher threat levels may be played at higher volumes as compared to alerts corresponding to lower threat levels. With this type of understanding, a user may, for example, be able to quickly and easily determine which of the alerts, and thereby rooms in the building, may need to be addressed first.

In another illustrative example, a particular modified audio recording in plurality of modified audio recordings **1201** may be played throughout an entire building or other area when the corresponding alert is appropriate. The volume at which the modified audio recording is played may provide an understanding of the threat level associated with that alert.

With reference now to **Figure 13**, an illustration of an audio recording representing manufacturing instructions is depicted in accordance with an illustrative embodiment. In this illustrative example, audio recording **1300** may be an example of one implementation for entity sensory representation **102** in **Figure 1**.

Audio recording **1300** represents manufacturing instructions. In particular, audio recording **1300** may be a recording of a human operator providing verbal instructions for performing a manufacturing operation.

As depicted, audio recording **1300** includes plurality of sections **1301**. Plurality of sections **1301** may be an example of one implementation for plurality of sensory representations **112** in **Figure 1**. Each of plurality of sections **1301** may represent the instructions for performing a different step of the manufacturing operation.

In this illustrative example, plurality of sections **1301** includes sections **1302**, **1304**, **1306**, **1308**, **1310**, **1312**, **1314**, and **1316**. Each of plurality of sections **1301** is at baseline in this example. In particular, each of plurality of sections **1301** is configured to play at a same loudness or similar decibel level.

With reference now to **Figure 14**, an illustration of a table indicating the importance of the different steps for performing a manufacturing operation is depicted in accordance with an illustrative embodiment. In this illustrative example, table **1400** includes column **1402**, column **1403**, and column **1404**.

Column **1402** identifies the different steps for which instructions are provided by audio recording **1300** in **Figure 13**.

Column **1403** identifies the importance assigned to the different steps. Column **1404** identifies the scale factors calculated for plurality of sections **1301** representing the instructions for the different steps. These scale factors may be used to modify a loudness of each of plurality of sections **1301**.

With reference now to **Figure 15**, an illustration of a transformed audio recording is depicted in accordance with an illustrative embodiment. In this illustrative example, audio recording **1300** from **Figure 13** has been transformed into transformed audio recording **1500**. Transformed audio recording **1500** is yet another example of one implementation for transformed entity sensory representation **104** in **Figure 1**.

Transformed audio recording **1500** includes plurality of modified sections **1501**. Plurality of modified sections **1501** includes modified sections **1502**, **1504**, **1506**, **1508**, **1510**, **1512**, **1514**, and **1516**. The loudness of each of plurality of sections **1301** has been adjusted based on the corresponding scale factor identified in **Figure 14** for the corresponding step represented by each section to form plurality of modified sections **1501**.

When transformed audio recording **1500** is played to a user, the user may be able to quickly and easily understand which portions of the audio instructions to which the user should pay close attention. Plurality of modified sections **1501** provides the user with a sensory understanding of the relative importance of the plurality of steps represented by plurality of modified sections **1501**.

The illustrations in **Figures 2-15** are not meant to imply physical, architectural, or logical limitations to the manner in which an illustrative embodiment may be implemented. Other elements in addition to or in place of the ones illustrated may be used. Some elements may be optional. For example, other graphical features may be added to display **300** in **Figure 6** to indicate the relative energy usage of the different aircraft sections in addition to the resizing of the image portions.

With reference now to **Figure 16**, an illustration of a process for modifying an entity sensory representation that represents an entity is depicted in the form of a flowchart in accordance with an illustrative embodiment. The process illustrated in **Figure 16** may be implemented using transformer 100 in **Figure 1** to transform an entity sensory representation, such as entity sensory representation 102 in **Figure 1**.

The process may begin by receiving an entity sensory representation that represents an entity (operation 1600). In operation 1600, the entity sensory representation comprises a plurality of sensory representations that represent a plurality of items that are part of the entity. Each of the plurality of items may be associated with a set of values for a set of measurable factors of interest.

Next, a set of scale factors is calculated for each of the plurality of sensory representations based on the set of values associated with each of the plurality of items (operation 1602). The plurality of sensory representations may then be modified using the set of scale factors calculated for each of the plurality of sensory representations to form a plurality of modified sensory representations that establish a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the set of measurable factors of interest (operation 1604), with the process terminating thereafter.

With reference now to **Figure 17**, an illustration of a process for creating an entity sensory representation is depicted in the form of a flowchart in accordance with an illustrative embodiment. The process illustrated in **Figure 17** may be implemented to form an entity sensory representation, such as entity sensory representation 102 in **Figure 1**.

The process begins by identifying an entity comprising a plurality of items (operation 1700). In one illustrative example, the entity may be identified in operation 1700 by a

computer system, such as computer system 106 in **Figure 1**, receiving input comprising one or more n -dimensional arrays of items. In operation 1700, the one or more n -dimensional arrays of items may be stored in the computer system using one or more data structures.

Next, a sensory representation is obtained for each of the plurality of items (operation 1702). In operation 1702, the sensory representations may be obtained by receiving the sensory representations as input at the computer system, retrieving the sensory representations from a database or cloud storage, creating new sensory representations, or in some other manner.

As one illustrative example, the sensory representations obtained in operation 1702 may take the form of images. The images may be received as input from an imaging system; retrieved from a database, server system, or cloud storage; created based on predetermined criteria or specifications; created by a user using a graphics program; or obtained in some other manner.

Thereafter, a set of parameters is quantified for each of the sensory representations (operation 1704). In operation 1704, a value for each of the set of parameters may be acquired, measured, or quantified in some other manner for each of the plurality of sensory representations. When the sensory representations are images, the set of parameters may include a width and height in pixels.

Next, the quantified set of parameters may be normalized to form a normalized set of parameters for each of the sensory representations (operation 1706). The sensory representations are then modified using the normalized set of parameters to form a plurality of sensory representations that together form an entity sensory representation (operation 1708), with the process terminating thereafter.

In operation 1708, each of the plurality of sensory representations may be set to a same baseline. When the

plurality of sensory representations take the form of images, the width and height of the images may be normalized in operation **1706** such that each of the images may be modified in operation **1708** to have a baseline width and a baseline height in pixels.

With reference now to **Figure 18**, an illustration of a process for calculating a set of scale factors for each of a plurality of sensory representations that form an entity sensory representation is depicted in the form of a flowchart in accordance with an illustrative embodiment. The process illustrated in **Figure 18** may be implemented to identify a set of scale factors for, for example, each of plurality of sensory representations **112** in **Figure 1**.

The process begins by identifying a factor of interest for a plurality of items that form an entity (operation **1800**). In other illustrative examples, more than one factor of interest may be identified in operation **1800**.

The factor of interest identified in operation **1800** may be measurable. Further, the factor of interest may be static or dynamic. When the factor of interest is static, a value measured for the factor of interest may not change over time. When the factor of interest is dynamic, a value measured for the factor of interest may change over time. Depending on the implementation, the factor of interest may be multi-dimensional. For example, the factor of interest may be a position that comprises three coordinates.

Next, a value for the factor of interest may be identified for each of the plurality of items (operation **1802**). In operation **1802**, the value may be quantified by at least one of performing a measurement, interpreting sensor data, converting subjective information into a value, or performing some other type of quantification.

As used herein, the phrase "at least one of," when used with a list of items, means different combinations of one or

more of the listed items may be used and only one of each item in the list may be needed. In other words, "at least one of" means any combination of items and number of items may be used from the list but not all of the items in the list are required. The item may be a particular object, thing, or a category.

For example, "at least one of item A, item B, or item C" or "at least one of item A, item B, and item C" may include, without limitation, item A, item A and item B, or item B. This example also may include item A, item B, and item C or item B and item C. Of course, any combinations of these items may be present. In other examples, "at least one of" may be, for example, without limitation, two of item A; one of item B; and ten of item C; four of item B and seven of item C; or other suitable combinations.

Thereafter, an initial scale factor may be calculated for each of the plurality of items (operation **1804**). In one illustrative example, the initial scale factor for a particular item may be calculated by dividing the value identified for the factor of interest for the particular item in operation **1802** by a sum of all of the values identified for the plurality of items. Of course, the initial scale factor may be computed in some other manner in other illustrative examples. In some cases, the scale factor may be referred to as a computed relative significance.

Next, a final scale factor may be calculated for each of the plurality of sensory representations corresponding to the plurality of items using a nonlinear factor (operation **1806**), with the process terminating thereafter. In one illustrative example, the nonlinear factor may be a logarithmic factor.

Operation **1806** may be performed by multiplying the initial scale factor identified for a particular item by the logarithmic factor and setting the product of this multiplication as the final scale factor for the corresponding sensory representation.

With reference now to **Figure 19**, an illustration of a process for creating a transformed entity sensory representation is depicted in the form of a flowchart in accordance with an illustrative embodiment. The process illustrated in **Figure 19** may be implemented to transform the entity sensory representation formed by the process described in **Figure 17** using the scale factors identified for the plurality of sensory representations in the entity sensory representation as described in **Figure 18**.

The process may begin by scaling the normalized set of parameters for each of the plurality of sensory representations to form a scaled set of parameters for each of the plurality of sensory representations (operation **1900**). A plurality of modified sensory representations may be created using the scaled set of parameters formed for each of the plurality of sensory representations (operation **1902**).

Then, a transformed entity sensory representation may be created using the plurality of modified sensory representations (operation **1904**). Operation **1904** may be performed in any number of ways. For example, the plurality of modified sensory representations may be combined, overlapped, sequenced, positioned relative to each other, or manipulated in any number of ways to form transformed entity sensory representation.

The transformed entity sensory representation may then be output to establish, using at least one human sense, a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the factor of interest (operation **1906**), with the process terminating thereafter. In other illustrative examples, the factor of interest may be a set of measurable factors of interest.

With reference now to **Figures 20A** and **20B**, an illustration of a process for creating a transformed entity image is depicted in the form of a flowchart in accordance with an illustrative

embodiment. The process illustrated in **Figures 20A** and **20B** may be implemented to create, for example, without limitation, transformed entity image **148** in **Figure 1**.

The process may begin by identifying a plurality of image portions of an entity image (operation **2000**). Next, boundaries of a total display area for displaying the entity image are identified (operation **2002**).

Coordinates for the boundaries of the total display area are then identified (operation **2004**). Depending on the shape of the total display area, these coordinates may be for the corners of the total display area, starting end points and ending end points for the boundaries of the total display area, or for other types of points along the boundaries of the total display area. Then, a center point of the total display area is identified (operation **2006**).

Thereafter, a plurality of display areas for the plurality of image portions is identified in the total display area (operation **2008**). A set of size parameters are quantified for each of the plurality of display areas (operation **2010**). In operation **2010**, the set of size parameters for each of the plurality of display areas may include, for example, a width in pixels and a height in pixels for each display area.

Next, a reference center point may be identified for each of the plurality of display areas (operation **2012**). A distance from each reference center point identified to the center point of the total display area is computed (operation **2014**). In operation **2014**, this distance may be calculated using Cartesian point-coordinates such as x,y-coordinates, or x,y,z-coordinates. In other examples, the distance may be calculated using distance-angle vectors in two dimensions, three dimensions, *n*-dimensions, or some combination thereof using some other type of distance measurement technique.

Each of the set of size parameters for each of the plurality of display areas is multiplied by a scale factor

computed for the image portion corresponding to each display area to form a plurality of modified display areas and thereby, a plurality of modified image portions (operation **2016**). In some cases, the resizing may be a one-to-one resizing. For example, resizing a display area by a scale factor of 1 may not change a size of the display area. Thus, the size of the corresponding image portion may not be changed.

A determination is then made as to whether an overlapping transformed entity image or an exploded transformed entity image is to be created (operation **2018**). If an overlapping transformed entity image is to be created, the process then creates the overlapping transformed entity image by centering each of the plurality of modified display areas, and thereby the plurality of modified image portions, at the reference center points originally calculated for the plurality of display areas (operation **2020**), with the process terminating thereafter.

In operation **2020**, one or more of the plurality of modified image portions may overlap over other modified image portions. In some illustrative examples, the modified display areas, and thereby the modified image portions, may be added to the total display area starting from the modified image portion associated with the smallest scale factor and ending with the modified image portion associated with the largest scale factor. In this manner, a modified image portion representing an item with greater relative significance may overlap another modified image portion representing an item with lesser relative significance.

With reference again to operation **2018**, if the exploded transformed entity image is to be created, the process computes a new reference center point for each of the plurality of modified display areas by multiplying the distance from the center point of the total display area to the reference center point for each modified display area by the corresponding scale factor (operation **2022**). Next, each of the plurality of modified display areas, and thereby the plurality of modified

image portions, may be centered at the corresponding new reference center point to create the exploded transformed entity image (operation **2024**).

Thereafter, the new total display area for the exploded transformed entity image may be adjusted to have a same size as the original total display area (operation **2026**), with the process terminating thereafter. In some illustrative examples, operation **2024** or operation **2026** may include adding lines to reconnect the plurality of modified image portions.

In some cases, a continuous relationship may be present between the sensory representations that make up an entity sensory representation. As one illustrative example, a continuous relationship may be present between the plurality of image portions identified in operation **2000** when the entity image is an aircraft and the plurality of image portions are parts of the aircraft. As another example, a continuous relationship may be present between segments of speech in an audio recording. When this type of continuous relationship is present in an entity image, it may be desirable to preserve this continuity between the plurality of modified portions that form an exploded transformed entity image.

For example, one or more techniques or algorithms may be used to create intermediary sensory representation content to preserve continuity between the plurality of modified image portions in the exploded transformed entity image formed in operation **2024** after the plurality of modified image portions have been centered at the corresponding new reference center points in operation **2024**. The one or more techniques or algorithms used may include, for example, without limitation, an interpolation technique, a smoothing algorithm, a filling algorithm, an extrapolation technique, a linear extrapolation technique, a drawing technique, some other type of algorithm or technique, or some combination thereof.

In some illustrative examples, an operation similar to operation **2026** may be performed after operation **2020**. In other words, in some cases, the new total display area for the overlapping transformed entity image may be adjusted to have a same size as the original total display area. In other illustrative examples, operation **2026** may be performed to adjust the new total display area to some other size.

With reference now to **Figure 21**, an illustration of a process for creating a transformed entity sensory representation is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 21** may be used to create, for example, without limitation, transformed entity sensory representation **104** in **Figure 1**.

The process may begin by identifying a plurality of sensory representations that make up an entity sensory representation (operation **2100**). Next, boundaries of a total output range for outputting the entity sensory representation are identified (operation **2102**). Coordinates of the boundaries of the total output range are then identified (operation **2104**). Then, a center point of the total output range is identified (operation **2106**).

With respect to operations **2102**, **2104**, and **2106**, the total output range may take different forms, depending on the type of entity sensory representation being processed. When the entity sensory representation takes the form of audio, the boundaries of the total output range may correspond to one or more dimensions such as, for example, without limitation, time, frequency, sound pressure, and intensity.

As one illustrative example, the boundaries of the total output range for an audio recording, such as audio recording **1300** in **Figure 13**, may take the form of parameters such as time and sound pressure. The coordinates for these boundaries may include, for example, a start time, and end time, and a maximum sound pressure level and minimum sound pressure level for the

boundary corresponding to sound pressure. A center point for the total output range may be comprised of the middle time between the start and end times and the mid-point between the maximum and minimum sound pressure levels.

In another illustrative example, the boundaries for the audio recordings may take the form of parameters, such as frequency and one of volume, intensity, or sound pressure. When the boundaries are frequency and volume, the coordinates for these boundaries may include, for example, a lowest frequency and highest frequency and a maximum volume level and minimum volume level. The center point for the total output range may then be comprised of the mid-frequency point and the middle volume level. The mid-frequency point may be computed using linear or logarithmic measurements of the frequencies.

Thereafter, a plurality of outputs for the plurality of sensory representations is identified within the total output range (operation **2108**). When the entity sensory representation is an audio recording and the plurality of sensory representations are sections of the audio recording, the plurality of outputs may be the corresponding sections of the total output range.

A set of parameters are quantified for each of the plurality of outputs (operation **2110**). In operation **2110**, the set of parameters for each of the plurality of outputs may include, for example, a frequency range, a volume range, a time interval, an intensity range, or some other type of parameter.

Next, a reference center point may be identified for each of the plurality of outputs (operation **2112**). A distance from each reference center point identified to the center point of the total output range is computed (operation **2114**). As one illustrative example, this distance may be a temporal distance in the case of audio.

Each of the set of parameters for each of the plurality of outputs is multiplied by a scale factor computed for the sensory

representation corresponding to each output to form a plurality of modified outputs and thereby, a plurality of modified sensory representations (operation **2116**). In operation **2116**, when the sensory representation is audio, each output may be scaled in frequency, volume, time, intensity, sound pressure, or some other parameter.

A new reference center point may be computed for each of the plurality of modified outputs by multiplying the distance from the center point of the total output range to the reference center point for each modified output by the corresponding scale factor (operation **2118**). Next, the plurality of modified outputs, and thereby the plurality of sensory representations, may be reconfigured using the corresponding new reference center points identified to create the transformed entity sensory representation (operation **2120**), with the process terminating thereafter.

The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent a module, a segment, a function, a portion of an operation or step, some combination thereof.

In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

In some illustrative examples, operation **1706** in **Figure 17** may be an optional step. In this manner, the normalized set of parameters formed in operation **1706** may be referred to as an

optionally normalized set of parameters. In one illustrative example, the process described in **Figure 17** above may be made to terminate after operation **1704** such that the sensory representations with the quantified sets of parameters are used to form the entity sensory representation. In other illustrative examples, operation **1806** in **Figure 18** may be an optional step. When operation **1806** is not performed, the initial scale factor computed in operation **1804** for each of plurality of items may be used as the final scale factor for each corresponding sensory representation.

Turning now to **Figure 22**, an illustration of a data processing system is depicted in the form of a block diagram in accordance with an illustrative embodiment. Data processing system **2200** may be used to implement computer system **106** in **Figure 1**. As depicted, data processing system **2200** includes communications framework **2202**, which provides communications between processor unit **2204**, storage devices **2206**, communications unit **2208**, input/output unit **2210**, and display **2212**. In some cases, communications framework **2202** may be implemented as a bus system.

Processor unit **2204** is configured to execute instructions for software to perform a number of operations. Processor unit **2204** may comprise at least one of a number of processors, a multi-processor core, or some other type of processor, depending on the implementation. In some cases, processor unit **2204** may take the form of a hardware unit, such as a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware unit.

Instructions for the operating system, applications and programs run by processor unit **2204** may be located in storage devices **2206**. Storage devices **2206** may be in communication with processor unit **2204** through communications framework **2202**. As used herein, a storage device, also referred to as a computer readable storage device, is any piece of hardware capable of

storing information on a temporary basis, a permanent basis, or both. This information may include, but is not limited to, data, program code, other information, or some combination thereof.

Memory **2214** and persistent storage **2216** are examples of storage devices **2206**. Memory **2214** may take the form of, for example, a random access memory or some type of volatile or non-volatile storage device. Persistent storage **2216** may comprise any number of components or devices. For example, persistent storage **2216** may comprise a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **2216** may or may not be removable.

Communications unit **2208** allows data processing system **2200** to communicate with other data processing systems, devices, or both. Communications unit **2208** may provide communications using physical communications links, wireless communications links, or both.

Input/output unit **2210** allows input to be received from and output to be sent to other devices connected to data processing system **2200**. For example, input/output unit **2210** may allow user input to be received through a keyboard, a mouse, some other type of input device, or a combination thereof. As another example, input/output unit **2210** may allow output to be sent to a printer connected to data processing system **2200**.

Display **2212** is configured to display information to a user. Display **2212** may comprise, for example, without limitation, a monitor, a touch screen, a laser display, a holographic display, a virtual display device, some other type of display device, or a combination thereof. Display **2212** may be an example of one manner in which display device **152** in **Figure 1** may be implemented.

In this illustrative example, the processes of the different illustrative embodiments may be performed by processor

unit **2204** using computer-implemented instructions. These instructions may be referred to as program code, computer usable program code, or computer readable program code and may be read and executed by one or more processors in processor unit **2204**.

5 In these examples, program code **2218** is located in a functional form on computer readable media **2220**, which is selectively removable, and may be loaded onto or transferred to data processing system **2200** for execution by processor unit **2204**. Program code **2218** and computer readable media **2220** 0 together form computer program product **2222**. In this illustrative example, computer readable media **2220** may be computer readable storage media **2224** or computer readable signal media **2226**.

Computer readable storage media **2224** is a physical or 5 tangible storage device used to store program code **2218** rather than a medium that propagates or transmits program code **2218**. Computer readable storage media **2224** may be, for example, without limitation, an optical or magnetic disk or a persistent storage device that is connected to data processing system **2200**.

0 Alternatively, program code **2218** may be transferred to data processing system **2200** using computer readable signal media **2226**. Computer readable signal media **2226** may be, for example, a propagated data signal containing program code **2218**. This data signal may be an electromagnetic signal, an optical signal, 25 or some other type of signal that can be transmitted over physical communications links, wireless communications links, or both.

The illustration of data processing system **2200** in **Figure 22** is not meant to provide architectural limitations to the 30 manner in which the illustrative embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system that includes components in addition to or in place of those illustrated for data processing system

2200. Further, components shown in **Figure 22** may be varied from the illustrative examples shown.

With this type of data processing system 2200, a computer-implemented method for automating a transformation of an entity image (142) into a transformed entity image (148), is enabled that includes the following steps of:

receiving the entity image (142) representing an entity (108), wherein the entity image (142) comprises a plurality of image portions (144) that represent a plurality of items (110) that are part of the entity (108);

identifying a set of values (130) for a set of measurable factors of interest (124) for each of the plurality of items (110);

calculating a set of scale factors (138) for each of the plurality of image portions (144) based on the set of values (130) associated with the each of the plurality of items (110);

modifying the plurality of image portions (144) using the set of scale factors (138) identified for the each of the plurality of image portions (144) to form a plurality of modified image portions (146); and

adjusting a position of the plurality of modified image portions (146) relative to each other with respect to a total display area to form the transformed entity image (148),

wherein the transformed entity image (148) visually establishes a relative relationship between the plurality of items (110) represented by the plurality of modified image portions (146) with respect to the set of measurable factors of interest (124).

Thus, the illustrative embodiments provide a method and apparatus for using a sensory representation to provide an understanding of the relative significance of items in an entity with respect to one or more measurable factors of interest. In particular, transformed entity sensory representation 104 described in **Figure 1** may allow a user to more quickly and

easily understand the relative significance of items, the relative importance of items, or some other relative measure of items without needing to interpret, understand, or process the underlying data.

5 The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different features as compared to other desirable embodiments. 0 The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in 5 the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

In the context of this specification, the word "comprising" means "including principally but not necessarily solely" or 0 "having" or "including", and not "consisting only of". Variations of the word "comprising", such as "comprise" and "comprises" have correspondingly varied meanings.

CLAIMS

1. An entity representation apparatus that comprises: a processor coupled to a memory; a transformer in communication with the processor and configured to receive, dynamically in real time, a sensory representation of an entity that comprises a set of measurable factors of interest, such that the sensory representation comprises: at least one of a sense of: sound, smell, touch, sight, and taste, that represent, dynamically in real-time, a significance of each factor, in the set of measurable factors of interest, relative to other factors in the set of measurable factors of interest of the entity; and a plurality of sensory representations that represent a plurality of items that are part of the entity, in which each of the plurality of items is associated with a set of values for a set of measurable factors of interest of the entity; the transformer further configured to continuously calculate in real-time, based on the set of values associated with the each of the plurality of items, a set of scale factors for the each of the plurality of sensory representations; and the transformer further configured to dynamically modify in real-time the plurality of sensory representations, based on the set of scale factors, to form a plurality of modified sensory representations that dynamically in real-time establish the significance of each factor in the set of measurable factors of interest relative to other factors in the set of measurable factors of interest.
2. The entity representation apparatus of claim 1, wherein the transformer creates a transformed entity sensory representation using the plurality of modified sensory representations.
3. The entity representation apparatus of claim 2 further comprising: an output device that outputs the transformed entity sensory representation to a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the set of measurable factors of interest.
4. The entity representation apparatus of claim 1, wherein each sensory representation in the plurality of sensory representations is associated with a set of parameters and wherein each of the set of parameters is scalable.
5. The entity representation apparatus of claim 4, wherein the transformer adjusts the set of parameters for the each of the plurality of sensory representations using the set of scale factors corresponding to the each of the plurality of sensory representations to form the plurality of modified sensory representations.

6. The entity representation apparatus of claim 1, further comprising the sensory representation comprising an entity image and the plurality of sensory representations comprising a plurality of image portions and the transformer configured to modify the plurality of image portions using the set of scale factors to create a transformed entity image.
7. The entity representation apparatus of claim 6, further comprising the transformer configured to identify a total display area that: presents the transformed entity image, identifies a plurality of display areas for each of the plurality of image portions, and adjusts the plurality of display areas for the each of the plurality of image portions, based upon the set of scale factors identified for the plurality of image portions to form a plurality of modified display areas.
8. The entity representation apparatus of claim 7, wherein the transformer generates a plurality of modified image portions using the plurality of modified display areas and adjusts a position of the plurality of modified image portions relative to each other within the total display area to form the transformed entity image.
9. The entity representation apparatus of claim 7 further comprising: a display device that visually presents a display of the transformed entity image, wherein the transformed entity image visually establishes a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the set of measurable factors of interest.
10. The entity representation apparatus of claim 1, further comprising the transformer configured to: identify a boundary, coordinates of the boundary, and a center point of the coordinates, of dimensions for a total output range for outputting the sensory representation of the entity, such that the total output range comprises different forms, based upon a type of sensation that represents the entity; identify a plurality of outputs for the plurality of sensory representations the total output range of the sensory representation of the entity; quantify a set of parameters for each of the plurality of outputs, and a reference center point for each of the plurality of outputs; compute a distance from each reference center point identified for each of the plurality of outputs to the center point of the total output range; dependent upon modifications of each of the set of parameters for each of the plurality of outputs, forming a plurality of modified outputs, compute a new reference center point for each of the plurality of modified outputs; and reconfigure, using the new reference center point for each of the plurality

of modified outputs, the plurality of modified outputs, and thereby the plurality of sensory representations, to create a transformed entity sensory representation.

11. The entity representation apparatus of claim 10, further comprising: the sensory representation comprising an audio representation, such that the boundaries of the total output range correspond to dimensions selected from a group that comprises: time, frequency, sound pressure, and intensity, such that the coordinates for the boundaries comprise: a start time, and end time, a maximum sound pressure level, and minimum sound pressure level; and a center point for the total output range that comprises: a middle time between a start time and an end time of the audio representation, and a mid-point between a maximum and a minimum sound pressure levels.

12. A computer-implemented method for modifying a sensory representation that represents an entity, the method comprising a transformer: receiving the sensory representation as at least one of a sense of: sound, smell, touch, sight, and taste, the sensory representation comprising a plurality of sensory representations dynamically representing in real-time a plurality of items that are part of the entity; associating each of the plurality of items with a set of values for a set of measurable factors of interest of the entity; dynamically calculating in real time, using the set of values, a set of scale factors for each of the plurality of sensory representations; and dynamically modifying in real-time, using the set of scale factors and forming a plurality of modified sensory representations establishing continuously in real-time a significance between the plurality of items represented by the plurality of modified sensory representations dynamically indicating in real-time a significance of each factor, in the set of measurable factors of interest, relative to other factors in the set of measurable factors of interest of the entity, the plurality of sensory representations.

13. The computer-implemented method of claim 12, wherein receiving the sensory representation comprises: receiving the sensory representation comprising the plurality of sensory representations, wherein the each of the plurality of sensory representations is associated with a set of parameters.

14. The computer-implemented method of claim 13 further comprising: normalizing the set of parameters for the each of the plurality of sensory representations.

15. The computer-implemented method of claim 13, wherein modifying the plurality of sensory representations comprises: adjusting the set of parameters for the each of the plurality of sensory representations using the set of scale factors corresponding to the each of the plurality of sensory representations to form the plurality of modified sensory representations.

16. The computer-implemented method of claim 12 further comprising: creating a transformed entity sensory representation using the plurality of modified sensory representations; and outputting the transformed entity sensory representation to establish a relative relationship between the plurality of items represented by the plurality of modified sensory representations with respect to the set of measurable factors of interest.

17. The computer-implemented method of claim 12, further comprising the transformer: identifying: a boundary, coordinates of the boundary, and a center point of the coordinates, of dimensions for a total output range for outputting the sensory representation of the entity, such that the total output range comprises different forms, based upon a type of sensation that represents the entity; identifying a plurality of outputs for the plurality of sensory representations the total output range of the sensory representation of the entity; quantifying a set of parameters for each of the plurality of outputs, and a reference center point for each of the plurality of outputs; computing a distance from each reference center point identified for each of the plurality of outputs to the center point of the total output range; dependent upon modifications of each of the set of parameters for each of the plurality of outputs, forming a plurality of modified outputs, computing a new reference center point for each of the plurality of modified outputs; and reconfiguring, using the new reference center point for each of the plurality of modified outputs, the plurality of modified outputs, and thereby the plurality of sensory representations creating a transformed entity sensory representation.

18. The computer-implemented method of claim 12, further comprising: receiving an entity image, wherein the entity image comprises a plurality of image portions; and modifying the plurality of image portions using the set of scale factors identified for each of the plurality of image portions to create a transformed entity image.

19. The computer-implemented method of claim 18, wherein modifying the plurality of image portions comprises: identifying a total display area for visually presenting the transformed entity image; identifying a plurality of display areas for the each of the plurality of image portions with

respect to the total display area; adjusting the plurality of display areas for the each of the plurality of image portions using the set of scale factors identified for the plurality of image portions to form a plurality of modified display areas; generating a plurality of modified image portions using the plurality of modified display areas; and adjusting a position of the plurality of modified image portions relative to each other within the total display area to form the transformed entity image.

20. A computer-implemented method for automating a transformation of a sensory representation of an entity into a transformed sensory representation of the entity, the computer-implemented method comprising a transformer: forming a sensory representation of the entity, the sensory representation being at least one of a sense of: a sound, a smell, a touch, a sight, and a taste; receiving the sensory representation comprising a plurality of portions that represent a plurality of items forming the entity; identifying, for each of the plurality of items, a set of values for a set of measurable factors of interest of the entity; dynamically calculating, in real-time, using the set of values associated with the each of the plurality of items, a set of scale factors for each of the plurality of portions; forming a plurality of modified portions, comprising sensory representations for each of the plurality of portions, via modifying, using the set of scale factors identified for the each of the plurality of portions; and dynamically forming, in real-time, the transformed sensory representation of the entity via adjusting, for each of the plurality of modified portions, a center point of a boundary of a dimension for each modified portion relative to each other modified portion with respect to a total output range for the transformed sensory representation of the entity, wherein the transformed sensory representation of the entity dynamically establishes, in real-time, a relative relationship between the plurality of items, of the entity, represented by the plurality of modified portions with respect to the set of measurable factors of interest of the entity.

The Boeing Company

Patent Attorneys for the Applicant/Nominated Person

SPRUSON & FERGUSON




FIG. 1




FIG. 2




FIG. 3




FIG. 4

| 500 | | |
|---------------------|-----------------|-----------------|
| 502 | 503 | 504 |
| AIRCRAFT SECTION | ENERGY USAGE | SCALE FACTOR |
| 508 COCKPIT | HIGH | 2 |
| 506 FUSELAGE | LOW | 1 |
| LEFT WING | LOW | 1 |
| RIGHT WING | LOW | 1 |
| LEFT AILERON | LOW | 1 |
| RIGHT AILERON | LOW | 1 |
| LEFT ENGINE | VERY HIGH | 3 |
| 510 RIGHT ENGINE | VERY HIGH | 3 |
| TAIL | LOW | 1 |
| RUDDER | LOW | 1 |

FIG. 5




FIG. 6




FIG. 7

800

802

803

804

| MEMBERS | SOCIAL NETWORKING ACTIVITY (NUMBER OF POSTS) | SCALE FACTOR |
|----------|--|-----------------|
| MEMBER A | 600 | 3 |
| MEMBER B | 150 | 0.75 |
| MEMBER C | 350 | 1.75 |
| MEMBER D | 500 | 2.5 |
| MEMBER E | 100 | 1 |
| MEMBER F | 500 | 2.5 |
| MEMBER G | 150 | 0.75 |
| MEMBER H | 350 | 1.75 |

FIG. 8




FIG. 9




FIG. 10

| ALERT | THREAT LEVEL | SCALE FACTOR |
|-------------------|--------------|--------------|
| ALERT #1 - ROOM 1 | SERIOUS | 2 |
| ALERT #2 - ROOM 2 | MODERATE | 1 |
| ALERT #3 - ROOM 3 | VERY MINOR | 0.5 |
| ALERT #4 - ROOM 4 | MODERATE | 1 |
| ALERT #5 - ROOM 5 | MINOR | 0.75 |
| ALERT #6 - ROOM 6 | MODERATE | 1 |
| ALERT #7 - ROOM 7 | MODERATE | 1 |
| ALERT #8 - ROOM 8 | SERIOUS | 2 |
| ALERT #9 - ROOM 9 | MODERATE | 1 |

FIG. 11




FIG. 12




FIG. 13

1400

| 1402 STEP IN PERFORMING MANUFACTURING OPERATION | 1403 IMPORTANCE | 1404 SCALE FACTOR |
|---|--------------------|-------------------------|
| INSTRUCTIONS FOR STEP #1 | VERY IMPORTANT | 2 |
| INSTRUCTIONS FOR STEP #2 | IMPORTANT | 1 |
| INSTRUCTIONS FOR STEP #3 | NOT IMPORTANT | 0.5 |
| INSTRUCTIONS FOR STEP #4 | EXTREMELY CRITICAL | 3 |
| INSTRUCTIONS FOR STEP #5 | IMPORTANT | 1 |
| INSTRUCTIONS FOR STEP #6 | IMPORTANT | 1 |
| INSTRUCTIONS FOR STEP #7 | NOT IMPORTANT | 0.5 |
| INSTRUCTIONS FOR STEP #8 | IMPORTANT | 1 |

FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 21




FIG. 22