



US010288896B2

(12) **United States Patent**
Shabtay et al.

(10) **Patent No.:** **US 10,288,896 B2**
(45) **Date of Patent:** ***May 14, 2019**

(54) **THIN DUAL-APERTURE ZOOM DIGITAL CAMERA**

(71) Applicant: **Corephotonics Ltd.**, Tel-Aviv (IL)

(72) Inventors: **Gal Shabtay**, Tel-Aviv (IL); **Ephraim Goldenberg**, Ashdod (IL)

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **15/456,506**

(22) Filed: **Mar. 11, 2017**

(65) **Prior Publication Data**

US 2017/0184871 A1 Jun. 29, 2017

Related U.S. Application Data

(63) Continuation of application No. 14/973,753, filed on Dec. 18, 2015, now Pat. No. 9,599,796, which is a (Continued)

(51) **Int. Cl.**
G02B 27/64 (2006.01)
G02B 13/18 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G02B 27/646** (2013.01); **G02B 1/041** (2013.01); **G02B 9/60** (2013.01); **G02B 13/009** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04N 5/2258; H04N 5/23296; H04N 5/2254; H04N 5/23287; H04N 5/238;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,354,503 A 7/1944 Cox
2,378,170 A 6/1945 Aklin
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101276415 A 10/2008
CN 102739949 A 10/2012
(Continued)

OTHER PUBLICATIONS

Extended European Search Report in related EP patent application 17194753.4, dated May 24, 2018, 9 pages.

(Continued)



Primary Examiner — Luong T Nguyen

(74) *Attorney, Agent, or Firm* — Nathan & Associates; Menachem Nathan

(57) **ABSTRACT**

A dual-aperture zoom camera comprising a Wide camera with a respective Wide lens and a Tele camera with a respective Tele lens, the Wide and Tele cameras mounted directly on a single printed circuit board, wherein the Wide and Tele lenses have respective effective focal lengths EFL_W and EFL_T and respective total track lengths TTL_W and TTL_T and wherein $TTL_W/EFL_W > 1.1$ and $TTL_T/EFL_T < 1.0$. Optionally, the dual-aperture zoom camera may further comprise an optical OIS controller configured to provide a compensation lens movement according to a user-defined zoom factor (ZF) and a camera tilt (CT) through $LMV = CT * EFL_{ZF}$, where EFL_{ZF} is a zoom-factor dependent effective focal length.

23 Claims, 9 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/373,500, filed as application No. PCT/IB2014/062854 on Jul. 4, 2014, now Pat. No. 9,413,972.

- (60) Provisional application No. 61/842,987, filed on Jul. 4, 2013.
- (51) **Int. Cl.**
G02B 13/02 (2006.01)
G02B 9/60 (2006.01)
H04N 5/232 (2006.01)
G02B 13/00 (2006.01)
H04N 5/225 (2006.01)
H04N 9/04 (2006.01)
H04N 9/097 (2006.01)
G02B 1/04 (2006.01)
G02B 27/00 (2006.01)
G02B 9/62 (2006.01)
G02B 5/00 (2006.01)
G02B 9/64 (2006.01)
G02B 9/12 (2006.01)
H04N 101/00 (2006.01)
- (52) **U.S. Cl.**
 CPC *G02B 13/0045* (2013.01); *G02B 27/0025* (2013.01); *H04N 5/2254* (2013.01); *H04N 5/2257* (2013.01); *H04N 5/2258* (2013.01); *H04N 5/23296* (2013.01); *H04N 9/045* (2013.01); *H04N 9/097* (2013.01); *G02B 5/005* (2013.01); *G02B 9/12* (2013.01); *G02B 9/62* (2013.01); *G02B 9/64* (2013.01); *G02B 13/00* (2013.01); *G02B 13/004* (2013.01); *G02B 13/02* (2013.01); *G02B 13/18* (2013.01); *H04N 2101/00* (2013.01); *Y10T 29/4913* (2015.01)
- (58) **Field of Classification Search**
 CPC H04N 9/097; H04N 9/045; H04N 2101/00; H04N 5/2257; G02B 27/646; G02B 13/009; G02B 13/0045; G02B 7/021; G02B 7/08; G02B 9/60; G02B 1/041; G02B 27/0025; G02B 13/00; G02B 13/18; G02B 9/62; G02B 5/005; G02B 9/64; G02B 13/004; G02B 9/12; G02B 13/02; Y10T 29/4913
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,441,093 A	5/1948	Aklin	7,869,142 B2	1/2011	Chen et al.
3,388,956 A	6/1968	Eggert et al.	7,880,776 B2	2/2011	LeGall et al.
3,524,700 A	8/1970	Eggert et al.	7,898,747 B2	3/2011	Tang
3,864,027 A	2/1975	Harada	7,916,401 B2	3/2011	Chen et al.
3,942,876 A	3/1976	Betensky	7,918,398 B2	4/2011	Li et al.
4,134,645 A	1/1979	Sugiyama et al.	7,957,075 B2	6/2011	Tang
4,199,785 A	4/1980	McCullough et al.	7,957,076 B2	6/2011	Tang
4,338,001 A	7/1982	Matsui	7,957,079 B2	6/2011	Tang
4,465,345 A	8/1984	Yazawa	7,961,406 B2	6/2011	Tang et al.
5,000,551 A	3/1991	Shibayama	7,964,835 B2	6/2011	Olsen et al.
5,005,083 A	4/1991	Grage et al.	7,978,239 B2	7/2011	Deever et al.
5,032,917 A	7/1991	Aschwanden	8,000,031 B1	8/2011	Tsai
5,051,830 A	9/1991	von Hoessle	8,004,777 B2	8/2011	Souma
5,172,235 A	12/1992	Wilm et al.	8,046,026 B2	10/2011	Koa
5,248,971 A	9/1993	Mandl	8,077,400 B2	12/2011	Tang
5,287,093 A	2/1994	Amano et al.	8,115,825 B2	2/2012	Culbert et al.
5,436,660 A	7/1995	Sakamoto	8,149,327 B2	4/2012	Lin et al.
5,444,478 A	8/1995	Lelong et al.	8,149,523 B2	4/2012	Ozaki
5,459,520 A	10/1995	Sasaki	8,154,610 B2	4/2012	Jo et al.
			5,657,402 A	8/1997	Bender et al.
			5,682,198 A	10/1997	Katayama et al.
			5,768,443 A	6/1998	Michael et al.
			5,926,190 A	7/1999	Turkowski et al.
			5,940,641 A	8/1999	McIntyre et al.
			5,982,951 A	11/1999	Katayama et al.
			6,101,334 A	8/2000	Fantone
			6,128,416 A	10/2000	Oura
			6,148,120 A	11/2000	Sussman
			6,208,765 B1	3/2001	Bergen
			6,268,611 B1	7/2001	Pettersson et al.
			6,549,215 B2	4/2003	Jouppi
			6,611,289 B1	8/2003	Yu et al.
			6,643,416 B1	11/2003	Daniels et al.
			6,650,368 B1	11/2003	Doron
			6,654,180 B2	11/2003	Ori
			6,680,748 B1	1/2004	Monti
			6,693,750 B2*	2/2004	Sato G02B 27/646 359/687
			6,714,665 B1	3/2004	Hanna et al.
			6,724,421 B1	4/2004	Glatt
			6,738,073 B2	5/2004	Park et al.
			6,741,250 B1	5/2004	Furlan et al.
			6,750,903 B1	6/2004	Miyatake et al.
			6,778,207 B1	8/2004	Lee et al.
			7,002,583 B2	2/2006	Rabb, III
			7,015,954 B1	3/2006	Foote et al.
			7,038,716 B2	5/2006	Klein et al.
			7,187,504 B2	3/2007	Horiuchi
			7,199,348 B2	4/2007	Olsen et al.
			7,206,136 B2	4/2007	Labaziewicz et al.
			7,248,294 B2	7/2007	Slatter
			7,256,944 B2	8/2007	Labaziewicz et al.
			7,305,180 B2	12/2007	Labaziewicz et al.
			7,339,621 B2	3/2008	Fortier
			7,346,217 B1	3/2008	Gold, Jr.
			7,365,793 B2	4/2008	Cheatle et al.
			7,411,610 B2	8/2008	Doyle
			7,424,218 B2	9/2008	Baudisch et al.
			7,509,041 B2	3/2009	Hosono
			7,515,351 B2	4/2009	Chen et al.
			7,533,819 B2	5/2009	Barkan et al.
			7,564,635 B1	7/2009	Tang
			7,619,683 B2	11/2009	Davis
			7,643,225 B1	1/2010	Tsai
			7,660,049 B2	2/2010	Tang
			7,684,128 B2	3/2010	Tang
			7,688,523 B2	3/2010	Sano
			7,692,877 B2	4/2010	Tang et al.
			7,697,220 B2	4/2010	Iyama
			7,738,016 B2	6/2010	Toyofuku
			7,738,186 B2	6/2010	Chen et al.
			7,773,121 B1	8/2010	Huntsberger et al.
			7,777,972 B1	8/2010	Chen et al.
			7,813,057 B2	10/2010	Lin
			7,821,724 B2	10/2010	Tang et al.
			7,826,149 B2	11/2010	Tang et al.
			7,826,151 B2	11/2010	Tsai
			7,859,588 B2*	12/2010	Parulski H04N 5/2258 348/349
			7,869,142 B2	1/2011	Chen et al.
			7,880,776 B2	2/2011	LeGall et al.
			7,898,747 B2	3/2011	Tang
			7,916,401 B2	3/2011	Chen et al.
			7,918,398 B2	4/2011	Li et al.
			7,957,075 B2	6/2011	Tang
			7,957,076 B2	6/2011	Tang
			7,957,079 B2	6/2011	Tang
			7,961,406 B2	6/2011	Tang et al.
			7,964,835 B2	6/2011	Olsen et al.
			7,978,239 B2	7/2011	Deever et al.
			8,000,031 B1	8/2011	Tsai
			8,004,777 B2	8/2011	Souma
			8,046,026 B2	10/2011	Koa
			8,077,400 B2	12/2011	Tang
			8,115,825 B2	2/2012	Culbert et al.
			8,149,327 B2	4/2012	Lin et al.
			8,149,523 B2	4/2012	Ozaki
			8,154,610 B2	4/2012	Jo et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,218,253 B2	7/2012	Tang	2002/0063711 A1	5/2002	Park et al.
8,228,622 B2	7/2012	Tang	2002/0075258 A1	6/2002	Park et al.
8,233,224 B2	7/2012	Chen	2002/0122113 A1	9/2002	Foote
8,238,695 B1	8/2012	Davey et al.	2003/0030729 A1	2/2003	Prentice et al.
8,253,843 B2	8/2012	Lin	2003/0093805 A1	5/2003	Gin
8,274,552 B2	9/2012	Dahi et al.	2003/0160886 A1	8/2003	Misawa et al.
8,279,537 B2	10/2012	Sato	2003/0202113 A1	10/2003	Yoshikawa
8,363,337 B2	1/2013	Tang et al.	2004/0008773 A1	1/2004	Itokawa
8,390,729 B2	3/2013	Long et al.	2004/0017386 A1	1/2004	Liu et al.
8,391,697 B2	3/2013	Cho et al.	2004/0027367 A1	2/2004	Pilu
8,395,851 B2	3/2013	Tang et al.	2004/0061788 A1	4/2004	Bateman
8,400,555 B1	3/2013	Georgiev et al.	2004/0240052 A1	12/2004	Minefuji et al.
8,400,717 B2	3/2013	Chen et al.	2005/0013509 A1	1/2005	Samadani
8,439,265 B2	5/2013	Ferren et al.	2005/0046740 A1	3/2005	Davis
8,446,484 B2	5/2013	Muukki et al.	2005/0141103 A1	6/2005	Nishina
8,451,549 B2	5/2013	Yamanaka et al.	2005/0157184 A1	7/2005	Nakanishi et al.
8,483,452 B2	7/2013	Ueda et al.	2005/0168840 A1	8/2005	Kobayashi et al.
8,503,107 B2	8/2013	Chen et al.	2005/0200718 A1	9/2005	Lee
8,514,491 B2	8/2013	Duparre	2006/0054782 A1	3/2006	Olsen et al.
8,514,502 B2	8/2013	Chen	2006/0056056 A1	3/2006	Ahiska et al.
8,547,389 B2	10/2013	Hoppe et al.	2006/0125937 A1	6/2006	LeGall et al.
8,553,106 B2	10/2013	Scarff	2006/0170793 A1	8/2006	Pasquarette et al.
8,587,691 B2	11/2013	Takane	2006/0175549 A1	8/2006	Miller et al.
8,619,148 B1	12/2013	Watts et al.	2006/0187310 A1	8/2006	Janson et al.
8,731,390 B2	5/2014	Goldenberg et al.	2006/0187312 A1	8/2006	Labaziewicz et al.
8,780,465 B2	7/2014	Chae	2006/0187322 A1	8/2006	Janson et al.
8,803,990 B2	8/2014	Smith	2006/0187338 A1	8/2006	May et al.
8,810,923 B2	8/2014	Shinohara	2007/0024737 A1	2/2007	Nakamura et al.
8,854,745 B1	10/2014	Chen	2007/0177025 A1	8/2007	Kopet et al.
8,896,655 B2	11/2014	Mauchly et al.	2007/0188653 A1	8/2007	Pollock et al.
8,958,164 B2	2/2015	Kwon et al.	2007/0189386 A1	8/2007	Imagawa et al.
8,976,255 B2	3/2015	Matsuoto et al.	2007/0229983 A1	10/2007	Saori
9,019,387 B2	4/2015	Nakano	2007/0257184 A1	11/2007	Olsen et al.
9,025,073 B2	5/2015	Attar et al.	2007/0285550 A1	12/2007	Son
9,025,077 B2	5/2015	Attar et al.	2008/0017557 A1	1/2008	Witdouck
9,041,835 B2	5/2015	Honda	2008/0024614 A1	1/2008	Li et al.
9,137,447 B2	9/2015	Shibuno	2008/0025634 A1	1/2008	Border et al.
9,143,664 B2 *	9/2015	Phoon G02B 7/04	2008/0030592 A1	2/2008	Border et al.
9,185,291 B1	11/2015	Shabtay et al.	2008/0030611 A1	2/2008	Jenkins
9,215,377 B2	12/2015	Sokeila et al.	2008/0084484 A1	4/2008	Ochi et al.
9,215,385 B2	12/2015	Luo	2008/0117316 A1	5/2008	Orimoto
9,229,194 B2	1/2016	Yoneyama et al.	2008/0166115 A1	7/2008	Sachs et al.
9,235,036 B2	1/2016	Kato et al.	2008/0218611 A1	9/2008	Parulski et al.
9,270,875 B2	2/2016	Brisedoux et al.	2008/0218612 A1	9/2008	Border et al.
9,279,957 B2	3/2016	Kanda et al.	2008/0218613 A1	9/2008	Janson et al.
9,286,680 B1	3/2016	Jiang et al.	2008/0219654 A1	9/2008	Border et al.
9,344,626 B2	5/2016	Silverstein et al.	2008/0247055 A1 *	10/2008	Chang G02B 13/0045 359/687
9,360,671 B1	6/2016	Zhou	2008/0304161 A1	12/2008	Souma
9,369,621 B2	6/2016	Malone et al.	2009/0002839 A1	1/2009	Sato
9,402,032 B2 *	7/2016	Dror G02B 9/60	2009/0086074 A1	4/2009	Li et al.
9,405,099 B2	8/2016	Jo et al.	2009/0122195 A1	5/2009	Van Baar et al.
9,413,930 B2	8/2016	Geerds	2009/0122406 A1	5/2009	Rouvinen et al.
9,413,972 B2 *	8/2016	Shabtay G02B 9/60	2009/0122423 A1	5/2009	Park et al.
9,413,984 B2	8/2016	Attar et al.	2009/0128644 A1	5/2009	Camp et al.
9,420,180 B2	8/2016	Jin	2009/0219547 A1	9/2009	Kauhanen et al.
9,438,792 B2	9/2016	Nakada et al.	2009/0252484 A1	10/2009	Hasuda et al.
9,485,432 B1	11/2016	Medasani et al.	2009/0295949 A1	12/2009	Ojala
9,488,802 B2	11/2016	Chen et al.	2010/0013906 A1	1/2010	Border et al.
9,568,712 B2	2/2017	Dror et al.	2010/0020221 A1	1/2010	Tupman et al.
9,578,257 B2	2/2017	Attar et al.	2010/0060746 A9	3/2010	Olsen et al.
9,599,796 B2 *	3/2017	Shabtay G02B 9/60	2010/0103194 A1	4/2010	Chen et al.
9,618,748 B2	4/2017	Munger et al.	2010/0238327 A1	9/2010	Griffith et al.
9,678,310 B2	6/2017	Iwasaki et al.	2010/0283842 A1	11/2010	Guissin et al.
9,681,057 B2	6/2017	Attar et al.	2010/0328471 A1 *	12/2010	Boland G02B 13/004 348/207.99
9,723,220 B2	8/2017	Sugie	2011/0001838 A1	1/2011	Lee
9,736,365 B2	8/2017	Laroia	2011/0064327 A1	3/2011	Dagher et al.
9,736,391 B2	8/2017	Du et al.	2011/0080487 A1	4/2011	Venkataraman et al.
9,768,310 B2	9/2017	Ahn et al.	2011/0115965 A1	5/2011	Engelhardt et al.
9,800,798 B2	10/2017	Ravirala et al.	2011/0128288 A1	6/2011	Petrou et al.
9,817,213 B2	11/2017	Mercado	2011/0164172 A1	7/2011	Shintani et al.
9,851,803 B2	12/2017	Fisher et al.	2011/0229054 A1	9/2011	Weston et al.
9,894,287 B2	2/2018	Qian et al.	2011/0234853 A1	9/2011	Hayashi et al.
9,900,522 B2	2/2018	Lu	2011/0234881 A1	9/2011	Wakabayashi et al.
9,927,600 B2	3/2018	Goldenberg et al.	2011/0242286 A1	10/2011	Pace et al.
2002/0005902 A1	1/2002	Yuen	2011/0242346 A1	10/2011	Ego
			2011/0242355 A1	10/2011	Goma et al.
			2012/0026366 A1	2/2012	Golan et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS

2012/0062780	A1	3/2012	Morihisa	
2012/0069235	A1	3/2012	Imai	
2012/0075489	A1	3/2012	Nishihara	
2012/0092777	A1	4/2012	Tochigi et al.	
2012/0105579	A1	5/2012	Jeon et al.	
2012/0105708	A1	5/2012	Hagiwara	
2012/0154929	A1	6/2012	Tsai et al.	
2012/0196648	A1	8/2012	Havens et al.	
2012/0218649	A1*	8/2012	Konishi	G02B 7/08 359/813
2012/0229663	A1	9/2012	Nelson et al.	
2012/0249815	A1	10/2012	Bohn et al.	
2012/0287315	A1	11/2012	Huang et al.	
2012/0320467	A1	12/2012	Baik et al.	
2013/0002928	A1	1/2013	Imai	
2013/0050536	A1	2/2013	Suzuki et al.	
2013/0093842	A1	4/2013	Yahata	
2013/0135445	A1	5/2013	Dahl et al.	
2013/0182150	A1	7/2013	Asakura	
2013/0201360	A1	8/2013	Song	
2013/0202273	A1	8/2013	Duedraogo et al.	
2013/0208178	A1	8/2013	Park	
2013/0235224	A1	9/2013	Park et al.	
2013/0250150	A1	9/2013	Malone et al.	
2013/0258044	A1	10/2013	Betts-LaCroix	
2013/0286488	A1	10/2013	Chae	
2013/0321668	A1	12/2013	Kamath	
2014/0022436	A1	1/2014	Kim et al.	
2014/0049615	A1	2/2014	Uwagawa	
2014/0118584	A1	5/2014	Lee et al.	
2014/0192238	A1	7/2014	Attar et al.	
2014/0192253	A1	7/2014	Laroia	
2014/0204480	A1	7/2014	Jo et al.	
2014/0285907	A1	9/2014	Tang	
2014/0293453	A1	10/2014	Ogino et al.	
2014/0313316	A1	10/2014	Olsson et al.	
2014/0362242	A1	12/2014	Takizawa	
2014/0362274	A1	12/2014	Christie et al.	
2015/0002683	A1	1/2015	Hu et al.	
2015/0029601	A1	1/2015	Dror et al.	
2015/0042870	A1	2/2015	Chan et al.	
2015/0085174	A1	3/2015	Shabtay et al.	
2015/0092066	A1	4/2015	Geiss et al.	
2015/0116569	A1	4/2015	Mercado	
2015/0154776	A1	6/2015	Zhang et al.	
2015/0162048	A1	6/2015	Hirata et al.	
2015/0195458	A1	7/2015	Nakayama et al.	
2015/0215516	A1	7/2015	Dolgin	
2015/0237280	A1	8/2015	Choi et al.	
2015/0242994	A1	8/2015	Shen	
2015/0253647	A1	9/2015	Mercado	
2015/0271471	A1	9/2015	Hsieh et al.	
2015/0316744	A1	11/2015	Chen	
2015/0334309	A1	11/2015	Peng et al.	
2016/0044250	A1	2/2016	Shabtay et al.	
2016/0070088	A1	3/2016	Koguchi	
2016/0085089	A1	3/2016	Mercado	
2016/0154202	A1	6/2016	Wippermann et al.	
2016/0154204	A1	6/2016	Lim et al.	
2016/0187631	A1	6/2016	Choi et al.	
2016/0212358	A1	7/2016	Shikata	
2016/0301840	A1	10/2016	Du et al.	
2016/0313537	A1	10/2016	Mercado	
2016/0353012	A1	12/2016	Kao et al.	
2017/0019616	A1	1/2017	Zhu et al.	
2017/0102522	A1	4/2017	Jo	
2017/0115471	A1	4/2017	Shinohara	
2017/0214846	A1	7/2017	Du et al.	
2017/0214866	A1	7/2017	Zhu et al.	
2017/0289458	A1	10/2017	Song et al.	
2018/0120674	A1	5/2018	Avivi et al.	
2018/0150973	A1	5/2018	Tang et al.	
2018/0224630	A1	8/2018	Lee et al.	
2018/0241922	A1	8/2018	Baldwin et al.	
2018/0295292	A1	10/2018	Lee et al.	

CN	102981239	A	3/2013
CN	103024272	A	4/2013
CN	104297906	A	1/2015
EP	1536633	A1	6/2005
EP	2523450	A1	11/2012
JP	S54157620	A	12/1979
JP	S59121015	A	7/1984
JP	04211230	A	8/1992
JP	H07318864	A	12/1995
JP	08271976	A	10/1996
JP	2003298920	A	10/2003
JP	2004133054	A	4/2004
JP	2005099265	A	4/2005
JP	2006238325	A	9/2006
JP	2007228006	A	9/2007
JP	2007306282	A	11/2007
JP	2008076485	A	4/2008
JP	2012203234	A	10/2012
JP	2013106289	A	5/2013
KR	20100008936	A	1/2010
KR	20140014787	A	2/2014
KR	20140023552	A	2/2014
KR	101477178	B1	12/2014
WO	2013058111	A1	4/2013
WO	2013063097	A1	5/2013
WO	2013105012	A2	7/2013
WO	2014199388	A2	12/2014
WO	2015015383	A2	2/2015

OTHER PUBLICATIONS

Office Action issued in related CN patent application 201480036855.8 dated Apr. 18, 2018.

Statistical Modeling and Performance Characterization of a Real-Time Dual Camera Surveillance System, Greenhagen et al., Publisher: IEEE, 2000, 8 pages.

A 3MPixel Multi-Aperture Image Sensor with 0.7 μm Pixels in 0.11 μm CMOS, Fife et al., Stanford University, 2008, 3 pages.

Dual camera intelligent sensor for high definition 360 degrees surveillance, Scotti et al., Publisher: IEE, Apr. 2005, 8 pages.

Dual-sensor foveated imaging system, Hua et al., Publisher: Optical Society of America, Jan. 14, 2008, 11 pages.

Defocus Video Matting, McGuire et al., Publisher: ACM SIGGRAPH, Jul. 31, 2005, 11 pages.

Compact multi-aperture imaging with high angular resolution, Santacana et al., Publisher: Optical Society of America, 2015, 10 pages.

Multi-Aperture Photography, Green et al., Publisher: Mitsubishi Electric Research Laboratories, Inc., Jul. 2007, 10 pages.

Multispectral Bilateral Video Fusion, Bennett et al., Publisher: IEEE, May 2007, 10 pages.

Super-resolution imaging using a camera array, Santacana et al., Publisher: Optical Society of America, 2014, 6 pages.

Optical Splitting Trees for High-Precision Monocular Imaging, McGuire et al., Publisher: IEEE, 2007, 11 pages.

High Performance Imaging Using Large Camera Arrays, Wilburn et al., Publisher: Association for Computing Machinery, Inc., 2005, 12 pages.

Superimposed multi-resolution imaging, Carles et al., Publisher: Optical Society of America, 2017, 13 pages.

Viewfinder Alignment, Adams et al., Publisher: Eurographics, 2008, 10 pages.

Dual-Camera System for Multi-Level Activity Recognition, Bodor et al., Publisher: IEEE, 6 pages.

Engineered to the task: Why camera-phone cameras are different, Giles Humpston, Publisher: Solid State Technology Jun. 2009, 3 pages.

A compact and cost effective design for cell phone zoom lens, Chang et al., Sep. 2007, 8 pages.

Consumer Electronic Optics: How small a lens can be? the case of panomorph lenses, Thibault et al. 2014, 7 pages.

(56)

References Cited

OTHER PUBLICATIONS

Optical design of camera optics for mobile phones, Steinich et al., 2012, pp. 51-58 (8 pages).

The Optics of Miniature Digital Camera Modules, Bateau et al., 2006, 11 pages.

Modeling and measuring liquid crystal tunable lenses, Peter P. Clark, 2014, 7 pages.

Mobile Platform Optical Design, Peter R Clark, 2014, 7 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5A



Polychromatic Diffraction Through Focus MTF
Angle 6/2/2013
Data for 0.4350 to 0.6560 μm .
Spatial Frequency: 180.0000 cycles/mm.

FIG. 5B



30/06/2013
Maximum distortion = 1.3%

FIG. 5C





FIG. 6A




Polychromatic Diffraction Through Focus MTF

Angle 6/2/2013

Data for 0.4350 to 0.6560 μm .

Spatial Frequency: 180.0000 cycles/mm.


FIG. 6B



30/06/2013

Maximum distortion = 1.5%

FIG. 6C




Polychromatic Diffraction Through Focus MTF

Angle 6/9/2013

Data for 0.4350 to 0.6560 μm .

Spatial Frequency: 180.0000 cycles/mm.

FIG. 7B



30/06/2013

Maximum distortion = 1.3%

FIG. 7C

THIN DUAL-APERTURE ZOOM DIGITAL CAMERA

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a Continuation application of U.S. patent application Ser. No. 14/973,753 filed Dec. 18, 2015 (now allowed) which was a Continuation application of U.S. patent application Ser. No. 14/373,500 filed Jul. 21, 2014 (issued as U.S. Pat. No. 9,413,972) which was a U.S. National Stage application under 35 USC 371 from international patent application PCT/IB2014/062854 filed Jul. 4, 2014, and is related to and claims priority from U.S. Provisional Patent Application No. 61/842,987 titled "Miniature telephoto lens assembly" and filed Jul. 4, 2013, which is incorporated herein by reference in its entirety.

FIELD

Embodiments disclosed herein relate in general to digital cameras, and more particularly, to thin dual-aperture zoom digital cameras that can be incorporated in a portable electronic product such as a mobile phone.

BACKGROUND

Compact multi-aperture and in particular dual-aperture (also referred to as "dual-lens" or "dual-camera") digital cameras are known. Miniaturization technologies allow incorporation of such cameras in compact portable electronic devices such as tablets and mobile phones (the latter referred to hereinafter generically as "smartphones"), where they provide advanced imaging capabilities such as zoom, see e.g. co-owned PCT patent application No. PCT/IB2013/060356 titled "High-resolution thin multi-aperture imaging systems", which is incorporated herein by reference in its entirety. A two-camera system (exemplarily including a wide-angle (or "Wide") camera and a telephoto (or "Tele") camera) is calibrated in an end product (e.g. in a smartphone) after manufacturing.

System calibration matches Tele and Wide image pixels by capturing in both cameras known objects. This enables faster and more reliable application of fusion between the two cameras, as described in PCT/IB2013/060356. One problem with such cameras may arise from mishaps such as drop impact. The latter may cause a relative movement between the two cameras after system calibration, changing the pixel matching between Tele and Wide images and thus preventing fast reliable fusion of the Tele and Wide images.

Another problem with dual-aperture zoom cameras relates to their height. There is a large difference in the height (also known as total track length or "TTL") of the Tele and Wide cameras. The TTL, see FIG. 1, is defined as the maximal distance between the object-side surface of a first lens element and a camera image sensor plane. In the following, "W" and "T" subscripts refer respectively to Wide and Tele cameras. In most miniature lenses, the TTL is larger than the lens effective focal length (EFL), which has a meaning well known in the art, see FIG. 1. A typical TTL/EFL ratio for a given lens (or lens assembly) is around 1.3. In a single-aperture smartphone camera, EFL is typically 3.5 mm, leading to a field of view of 70-80. Assuming one wishes to achieve a dual-aperture $\times 2$ optical zoom in a smartphone, it would be natural to use $EFL_W=3.5$ mm and $EFL_T=2 \times EFL_W=7$ mm. However, without spatial restrictions, the Wide lens will have an $EFL_W=3.5$ mm and a TTL_W

of $3.5 \times 1.3=4.55$ mm, while the Tele lens will have $EFL_T=7$ mm and TTL_T of $7 \times 1.3=9.1$ mm. The incorporation of a 9.1 mm lens in a smartphone camera would lead to a camera height of around 9.8 mm, which is unacceptable for many smartphone makers. Also the large height difference (approx. 4.55 mm) between the Wide and Tele cameras can cause shadowing and light-blocking problems, see FIG. 2.

A third problem relates to the implementation of standard optical image stabilization (OIS) in a dual-aperture zoom camera. Standard OIS compensates for camera tilt ("CT") by a parallel-to-the image sensor (exemplarily in the X-Y plane) lens movement ("LMV"). Camera tilt causes image blur. The amount of LMV (in mm) needed to counter a given camera tilt depends on the camera's lens EFL, according to the relation $LMV=CT \times EFL$ where "CT" is in radians and EFL is in mm. Since as shown above a dual-aperture zoom camera may include two lenses with significantly different EFL_S , it is impossible to move both lenses together and achieve optimal tilt compensation for both Tele and Wide cameras. That is, since the tilt is the same for both cameras, a movement that will cancel the tilt for the Wide camera will be insufficient to cancel the tilt for the Tele camera. Similarly, a movement that will cancel the tilt for the Tele camera will over-compensate the tilt cancellation for the Wide camera. Assigning a separate OIS actuator to each camera can achieve simultaneous tilt compensation, but at the expense of a complicated and expensive camera system.

SUMMARY

Embodiments disclosed herein refer to thin dual-aperture zoom cameras with improved drop impact resistance, smaller total thickness, smaller TTL difference between Wide and Tele cameras and improved OIS compensation.

In some embodiments there are provided dual-aperture zoom cameras comprising a Wide camera with a respective Wide lens and a Tele camera with a respective Tele lens, the Wide and Tele cameras mounted directly on a single printed circuit board, wherein the Wide and Tele lenses have respective effective focal lengths EFL_W and EFL_T and respective total track lengths TTL_W and TTL_T and wherein $TTL_W/EFL_W > 1.1$ and $TTL_T/EFL_T < 1.0$.

In some embodiments, a dual-aperture zoom camera disclosed herein further comprises an OIS controller configured to provide a compensation lens movement according to a camera tilt input and a user-defined zoom factor through $LMV=CT \times EFL_{ZF}$, wherein EFL_{ZF} is a "zoom-factor dependent EFL".

In some embodiments, the Tele lens is a lens as described in detail in U.S. provisional patent application No. 61/842,987 and in U.S. patent application Ser. No. 14/367,924, titled "Miniature telephoto lens assembly", both of which are incorporated herein by reference in their entirety.

In some embodiments there are provided methods for manufacturing a dual-aperture zoom camera comprising the steps of providing a Wide camera having a Wide lens with an effective focal length EFL_W and a total track length TTL_W , providing a Tele camera having a Tele lens with an effective focal length EFL_T and a total track length TTL_T , wherein $TTL_W/EFL_W > 1.1$ and wherein $TTL_T/EFL_T < 1.0$, and mounting the Wide and Tele cameras directly on a single printed circuit board.

In some embodiments, the methods further comprise the step of configuring an OIS controller of the dual-aperture

zoom camera to compensate lens movement of the Wide and Tele lenses according to a camera tilt input and a user-defined zoom factor.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting embodiments are herein described, by way of example only, with reference to the accompanying drawings, wherein:

FIG. 1 shows definitions of TTL and EFL;

FIG. 2 shows shadowing and light-blocking problems caused by height differences between Wide and Tele cameras in a dual-aperture camera;

FIG. 3 shows an embodiment of a dual-aperture camera disclosed herein;

FIG. 4 shows schematically in a block diagram details of the camera embodiment of FIG. 3;

FIG. 5A shows a first embodiment of an optical lens system disclosed herein;

FIG. 5B shows the modulus of the optical transfer function (MTF) vs. focus shift of the entire optical system for various fields in the first embodiment;

FIG. 5C shows the distortion vs. field angle (+Y direction) in percent in the first embodiment;

FIG. 6A shows a second embodiment of an optical lens system disclosed herein;

FIG. 6B shows the MTF vs. focus shift of the entire optical system for various fields in the second embodiment;

FIG. 6C shows the distortion +Y in percent in the second embodiment;

FIG. 7A shows a third embodiment of an optical lens system disclosed herein;

FIG. 7B shows the MTF vs. focus shift of the entire optical system for various fields in the third embodiment;

FIG. 7C shows the distortion +Y in percent in the third embodiment.

DETAILED DESCRIPTION

The present inventors have determined that camera movement (due to exemplarily, but not limited to mishaps such as drop impact) can be avoided or minimized by mounting the two cameras directly on a single printed circuit board and by minimizing a distance “d” therebetween. FIG. 3 shows an embodiment of a dual-aperture camera **300** that includes two cameras **302** and **304** mounted directly on a single printed circuit board **305**. Each camera includes a lens assembly (respectively **306** and **308**), an actuator (respectively **310** and **312**) and an image sensor (respectively **314** and **316**). The two actuators are rigidly mounted on a rigid base **318** that is flexibly connected to the printed board through flexible elements **320**. Base **318** is movable by an OIS mechanism (not shown) controlled by an OIS controller **402** (FIG. 4). The OIS controller is coupled to, and receives camera tilt information from, a tilt sensor (exemplarily a gyroscope) **404** (FIG. 4). More details of an exemplary OIS procedure as disclosed herein are given below with reference to FIG. 4. The two cameras are separated by a small distance “d”, typically 1 mm. This small distance between cameras also reduces the perspective effect, enabling smoother zoom transition between cameras.

In some embodiments and optionally, a magnetic shield plate as described in co-owned U.S. patent application Ser. No. 14/365,718 titled “Magnetic shielding between voice coil motors in a dual-aperture camera”, which is incorporated herein by reference in its entirety, may be inserted in the gap with width d between the Wide and Tele cameras.

In general, camera dimensions shown in FIG. 3 may be as follows: a length L of the camera (in the Y direction) may vary between 13-25 mm, a width W of the camera (in the X direction) may vary between 6-12 mm, and a height H of the camera (in the Z direction, perpendicular to the X-Y plane) may vary between 4-12 mm. More typically in a smartphone camera disclosed herein, L=18 mm. W=8.5 mm and H=7 mm.

The present inventors have further determined that in some embodiments, the problem posed by the large difference in the TTL/EFL ratio of known dual-aperture camera Tele and Wide lenses may be solved through use of a standard lens for the Wide camera ($TTL_W/EFL_W > 1.1$, typically 1.3) and of a special Tele lens design for the Tele camera ($TTL_T/EFL_T < 1$, typically 0.87). Exemplarily, the special Tele lens design may be as described in co-owned U.S. patent application Ser. No. 14/367,924, titled “Miniature telephoto lens assembly”, which is incorporated herein by reference in its entirety. A Tele lens assembly described in detail below comprises five lenses that include, in order from an object side to an image side: a first lens element with positive refractive power having a convex object-side surface, a second lens element with negative refractive power having a thickness d_2 on an optical axis and separated from the first lens element by a first air gap, a third lens element with negative refractive power and separated from the second lens element by a second air gap, a fourth lens element having a positive refractive power and separated from the third lens element by a third air gap, and a fifth lens element having a negative refractive power, separated from the fourth lens element by a fourth air gap, the fifth lens element having a thickness d_5 on the optical axis. The shape (convex or concave) of a lens element surface is defined as viewed from the respective side (i.e. from an object side or from an image side). The lens assembly may exemplarily have a F number ($F\#$) < 3.2. In an embodiment, the focal length of the first lens element f_1 is smaller than $TTL_T/2$, the first, third and fifth lens elements have each an Abbe number greater than 50, the second and fourth lens elements have each an Abbe number smaller than 30, the first air gap is smaller than $d_2/2$, the third air gap is greater than $TTL_T/5$ and the fourth air gap is smaller than $1.5 d_5$. In some embodiments, the surfaces of the lens elements may be aspheric.

FIG. 5A shows a first embodiment of an optical lens system disclosed in incorporated by reference U.S. provisional patent application Ser. No. 14/367,924 and marked **100**. FIG. 5B shows the MTF vs. focus shift of the entire optical system for various fields in embodiment **100**. FIG. 5C shows the distortion +Y in percent vs. field. Embodiment **100** comprises in order from an object side to an image side: an optional stop **101**; a first plastic lens element **102** with positive refractive power having a convex object-side surface **102a** and a convex or concave image-side surface **102b**; a second plastic lens element **104** with negative refractive power and having a meniscus convex object-side surface **104a**, with an image side surface marked **104b**; a third plastic lens element **106** with negative refractive power having a concave object-side surface **106a** with an inflection point and a concave image-side surface **106b**; a fourth plastic lens element **108** with positive refractive power having a positive meniscus, with a concave object-side surface marked **108a** and an image-side surface marked **108b**; and a fifth plastic lens element **110** with negative refractive power having a negative meniscus, with a concave object-side surface marked **110a** and an image-side surface marked **110b**. The optical lens system further comprises an

optional glass window **112** disposed between the image-side surface **110b** of fifth lens element **110** and an image plane **114** for image formation of an object. Moreover, an electronic sensor is disposed at image plane **114** for the image formation.

In embodiment **100**, all lens element surfaces are aspheric. Detailed optical data is given in Table 1, and the aspheric surface data is given in Table 2, wherein the units of the radius of curvature (R), lens element thickness and/or

TABLE 1-continued

#	Comment	Radius R [mm]	Distances [mm]	Nd/Vd	Diameter [mm]	
5	10	L51	-1.8100	0.293	1.5345/57.095	3.9
	11	L52	-5.2768	0.617		4.3
	12	Window	Infinite	0.210	1.5168/64.17	3.0
	13		Infinite	0.200		3.0

TABLE 2

#	Conic coefficient k	α_2	α_3	α_4	α_5	α_6
2	-0.4668	7.9218E-03	2.3146E-02	-3.3436E-02	2.3650E-02	-9.2437E-03
3	-9.8525	2.0102E-02	2.0647E-04	7.4394E-03	-1.7529E-02	4.5206E-03
4	10.7569	-1.9248E-03	8.6003E-02	1.1676E-02	-4.0607E-02	1.3545E-02
5	1.4395	5.1029E-03	2.4578E-01	-1.7734E-01	2.9848E-01	-1.3320E-01
6	0.0000	2.1629E-01	4.0134E-02	1.3615E-02	2.5914E-03	-1.2292E-02
7	-9.8953	2.3297E-01	8.2917E-02	-1.2725E-01	1.5691E-01	-5.9624E-02
8	0.9938	-1.3522E-02	-7.0395E-03	1.4569E-02	-1.5336E-02	4.3707E-03
9	-6.8097	-1.0654E-01	1.2933E-02	2.9548E-04	-1.8317E-03	5.0111E-04
10	-7.3161	-1.8636E-01	8.3105E-02	-1.8632E-02	2.4012E-03	-1.2816E-04
11	0.0000	-1.1927E-01	7.0245E-02	-2.0735E-02	2.6418E-03	-1.1576E-04

distances between elements along the optical axis and diameter are expressed in mm. “Nd” is the refraction index. The equation of the aspheric surface profiles is expressed by:

$$z = \frac{cr^2}{1 + \sqrt{1 - (1+k)c^2r^2}} + \alpha_1 r^2 + \alpha_2 r^4 + \alpha_3 r^6 + \alpha_4 r^8 + \alpha_5 r^{10} + \alpha_6 r^{12} + \alpha_7 r^{14}.$$

where r is distance from (and perpendicular to) the optical axis, k is the conic coefficient, c=1/R where R is the radius of curvature, and α are coefficients given in Table 2. In the equation above as applied to embodiments of a lens assembly disclosed in co-owned U.S. patent application Ser. No. 14/367,924, coefficients α_1 and α_7 are zero. Note that the maximum value of r “max r”=Diameter/2. Also note that Table 1 (and in Tables 3 and 5 below), the distances between various elements (and/or surfaces) are marked “Lmn” (where m refers to the lens element number, n=1 refers to the element thickness and n=2 refers to the air gap to the next element) and are measured on the optical axis z, wherein the stop is at z=0. Each number is measured from the previous surface. Thus, the first distance -0.466 mm is measured from the stop to surface **102a**, the distance L11 from surface **102a** to surface **102b** (i.e. the thickness of first lens element **102**) is 0.894 mm, the gap L12 between surfaces **102b** and **104a** is 0.020 mm, the distance L21 between surfaces **104a** and **104b** (i.e. thickness d_2 of second lens element **104**) is 0.246 mm, etc. Also, L21= d_2 and L51= d_5 .

TABLE 1

#	Comment	Radius R [mm]	Distances [mm]	Nd/Vd	Diameter [mm]
1	Stop	Infinite	-0.466		2.4
2	L11	1.5800	0.894	1.5345/57.095	2.5
3	L12	-11.2003	0.020		2.4
4	L21	33.8670	0.246	1.63549/23.91	2.2
5	L22	3.2281	0.449		1.9
6	L31	-12.2843	0.290	1.5345/57.095	1.9
7	L32	7.7138	2.020		1.8
8	L41	-2.3755	0.597	1.63549/23.91	3.3
9	L42	-1.8801	0.068		3.6

25

Embodiment **100** provides a field of view (FOV) of 44 degrees, with EFL=6.90 mm, F#=2.80 and TTL of 5.904 mm. Thus and advantageously, the ratio TTL/EFL=0.855. Advantageously, the Abbe number of the first, third and fifth lens element is 57.095. Advantageously, the first air gap between lens elements **102** and **104** (the gap between surfaces **102b** and **104a**) has a thickness (0.020 mm) which is less than a tenth of thickness d_2 (0.246 mm). Advantageously, the Abbe number of the second and fourth lens elements is 23.91. Advantageously, the third air gap between lens elements **106** and **108** has a thickness (2.020 mm) greater than TTL/5 (5.904/5 mm). Advantageously, the fourth air gap between lens elements **108** and **110** has a thickness (0.068 mm) which is smaller than $d_5/2$ (0.293/2 mm).

The focal length (in mm) of each lens element in embodiment **100** is as follows: f1=2.645, f2=-5.578, f3=-8.784, f4=9.550 and f5=-5.290. The condition $1.2 \times |f3| > |f2| > 1.5 \times f1$ is clearly satisfied, as $1.2 \times 8.787 > 5.578 > 1.5 \times 2.645$, f1 also fulfills the condition $f1 < TTL/2$, as $2.645 < 2.952$.

FIG. 6A shows a second embodiment of an optical lens system disclosed in incorporated by reference U.S. provisional patent application Ser. No. 14/367,924 and marked **200**. FIG. 6B shows the MTF vs. focus shift of the entire optical system for various fields in embodiment **200**. FIG. 6C shows the distortion +Y in percent vs. field. Embodiment **200** comprises in order from an object side to an image side: an optional stop **201**; a first plastic lens element **202** with positive refractive power having a convex object-side surface **202a** and a convex or concave image-side surface **202b**; a second glass lens element **204** with negative refractive power, having a meniscus convex object-side surface **204a**, with an image side surface marked **204b**; a third plastic lens element **206** with negative refractive power having a concave object-side surface **206a** with an inflection point and a concave image-side surface **206b**; a fourth plastic lens element **208** with positive refractive power having a positive meniscus, with a concave object-side surface marked **208a** and an image-side surface marked **208b**; and a fifth plastic lens element **210** with negative refractive power having a negative meniscus, with a concave object-side surface marked **110a** and an image-side surface marked **210b**. The

optical lens system further comprises an optional glass window **212** disposed between the image-side surface **210b** of fifth lens element **210** and an image plane **214** for image formation of an object. Moreover, an electronic sensor is disposed at image plane **214** for the image formation.

In embodiment **200**, all lens element surfaces are aspheric. Detailed optical data is given in Table 3, and the aspheric surface data is given in Table 4, wherein the markings and units are the same as in, respectively, Tables 1 and 2. The equation of the aspheric surface profiles is the same as for embodiment **100**.

TABLE 3

#	Comment	Radius R [mm]	Distances [mm]	Nd/Vd	Diameter [mm]
1	Stop	Infinite	-0.592		2.5
2	L11	1.5457	0.898	1.53463/56.18	2.6
3	L12	-127.7249	0.129		2.6
4	L21	6.6065	0.251	1.91266/20.65	2.1
5	L22	2.8090	0.443		1.8
6	L31	9.6183	0.293	1.53463/56.18	1.8
7	L32	3.4694	1.766		1.7
8	L41	-2.6432	0.696	1.632445/23.35	3.2
9	L42	-1.8663	0.106		3.6
10	L51	-1.4933	0.330	1.53463/56.18	3.9
11	L52	-4.1588	0.649		4.3
12	Window	Infinite	0.210	1.5168/64.17	5.4
13		Infinite	0.130		5.5

TABLE 4

#	Conic coefficient k	α_2	α_3	α_4	α_5	α_6
2	0.0000	-2.7367E-03	2.8779E-04	-4.3661E-03	3.0069E-03	-1.2282E-03
3	40.0119	4.0790E-02	-1.8379E-02	2.2562E-02	-1.7706E-02	4.9640E-03
4	10.0220	4.6151E-02	5.8320E-02	-2.0919E-02	-1.2846E-02	8.8283E-03
5	7.2902	3.6028E-02	1.1436E-01	-1.9022E-02	4.7992E-03	-3.4079E-03
6	0.0000	1.6639E-01	5.6754E-02	-1.2238E-02	-1.8648E-02	1.9292E-02
7	8.1261	1.5353E-01	8.1427E-02	-1.5773E-01	1.5303E-01	-4.6064E-02
8	0.0000	-3.2628E-02	1.9535E-02	-1.6716E-02	-2.0132E-03	2.0112E-03
9	0.0000	1.5173E-02	-1.2252E-02	3.3611E-03	-2.5303E-03	8.4038E-04
10	-4.7688	-1.4736E-01	7.6335E-02	-2.5539E-02	5.5897E-03	-5.0290E-04
11	0.00E+00	-8.3741E-02	4.2660E-02	-8.4866E-03	1.2183E-04	7.2785E-05

Embodiment **200** provides a FOV of 43.48 degrees, with EFL=7 mm, F#=2.86 and TTL=5.90 mm. Thus and advantageously, the ratio TTL/EFL=0.843. Advantageously, the Abbe number of the first, third and fifth lens elements is 56.18. The first air gap between lens elements **202** and **204** has a thickness (0.129 mm) which is about half the thickness d_2 (0.251 mm). Advantageously, the Abbe number of the second lens element is 20.65 and of the fourth lens element is 23.35. Advantageously, the third air gap between lens elements **206** and **208** has a thickness (1.766 mm) greater than TTL/5 (5.904/5 mm). Advantageously, the fourth air gap between lens elements **208** and **210** has a thickness (0.106 mm) which is less than $d_5/2$ (0.330/2 mm).

The focal length (in mm) of each lens element in embodiment **200** is as follows: $f_1=2.851$, $f_2=-5.468$, $f_3=-10.279$, $f_4=7.368$ and $f_5=-4.536$. The condition $1.2 \times |f_3| > |f_2| > 1.5 \times f_1$ is clearly satisfied, as $1.2 \times 10.279 > 5.468 > 1.5 \times 2.851$. f_1 also fulfills the condition $f_1 < \text{TTL}/2$, as $2.851 < 2.950$.

FIG. 7A shows a third embodiment of an optical lens system disclosed in incorporated by reference U.S. provisional patent application Ser. No. 14/367,924 and marked

700. FIG. 7B shows the MTF vs. focus shift of the entire optical system for various fields in embodiment **700**. FIG. 7C shows the distortion+Y in percent vs. field. Embodiment **700** comprises in order from an object side to an image side: an optional stop **701**; a first glass lens element **702** with positive refractive power having a convex object-side surface **702a** and a convex or concave image-side surface **702b**; a second plastic lens element **704** with negative refractive power, having a meniscus convex object-side surface **304a**, with an image side surface marked **704b**; a third plastic lens element **706** with negative refractive power having a concave object-side surface **706a** with an inflection point and a concave image-side surface **706b**; a fourth plastic lens element **708** with positive refractive power having a positive meniscus, with a concave object-side surface marked **708a** and an image-side surface marked **708b**; and a fifth plastic lens element **710** with negative refractive power having a negative meniscus, with a concave object-side surface marked **710a** and an image-side surface marked **710b**. The optical lens system further comprises an optional glass window **712** disposed between the image-side surface **710b** of fifth lens element **710** and an image plane **714** for image formation of an object. Moreover, an electronic sensor is disposed at image plane **714** for the image formation.

In embodiment **700**, all lens element surfaces are aspheric. Detailed optical data is given in Table 5, and the aspheric surface data is given in Table 6, wherein the markings and units are the same as in, respectively, Tables

1 and 2. The equation of the aspheric surface profiles is the same as for embodiments **100** and **200**.

TABLE 5

#	Comment	Radius R [mm]	Distances [mm]	Nd/Vd	Diameter [mm]
1	Stop	Infinite	-0.38		2.4
2	L11	1.5127	0.919	1.5148/63.1	2.5
3	L12	43.3831	0.029		2.3
4	L21	8.4411	0.254	1.63549/23.91	2.1
5	L22	2.6181	0.426		1.8
6	L31	-17.9618	0.265	1.5345/57.09	1.8
7	L32	4.5841	1.998		1.7
8	L41	-2.8827	0.514	1.63549/23.91	3.4
9	L42	-1.9771	0.121		3.7
10	L51	-1.8665	0.431	1.5345/57.09	4.0
11	L52	-6.3670	0.538		4.4
12	Window	Infinite	0.210	1.5168/64.17	3.0
13		Infinite	0.200		3.0

TABLE 6

#	Conic coefficient					
	k	α_2	α_3	α_4	α_5	α_6
2	-0.534	1.3253E-02	2.3699E-02	-2.8501E-02	1.7853E-02	-4.0314E-03
3	-13.473	3.0077E-02	4.7972E-03	1.4475E-02	-1.8490E-02	4.3565E-03
4	-10.132	7.0372E-04	1.1328E-01	1.2346E-03	-4.2655E-02	8.8625E-03
5	5.180	-1.9210E-03	2.3799E-01	-8.8055E-02	2.1447E-01	-1.2702E-01
6	0.000	2.6780E-01	1.8129E-02	-1.7323E-02	3.7372E-02	-2.1356E-02
7	10.037	2.7660E-01	-1.0291E-02	-6.0955E-02	7.5235E-02	-1.6521E-02
8	1.703	2.6462E-02	-1.2633E-02	-4.7724E-04	-3.2762E-03	1.6551E-03
9	-1.456	5.7704E-03	-1.8826E-02	5.1593E-03	-2.9999E-03	8.0685E-04
10	-6.511	-2.1699E-01	1.3692E-01	-4.2629E-02	6.8371E-03	-4.1415E-04
11	0.000	-1.5120E-01	8.6614E-02	-2.3324E-02	2.7361E-03	-1.1236E-04

15

Embodiment **700** provides a FOV of 44 degrees, EFL=6.84 mm. F#=2.80 and TTL=5.904 mm. Thus and advantageously, the ratio TTL/EFL=0.863. Advantageously, the Abbe number of the first lens element is 63.1, and of the third and fifth lens elements is 57.09. The first air gap between lens elements **702** and **704** has a thickness (0.029 mm) which is about $\frac{1}{10}^{th}$ the thickness d_2 (0.254 mm). Advantageously, the Abbe number of the second and fourth lens elements is 23.91. Advantageously, the third air gap between lens elements **706** and **708** has a thickness (1.998 mm) greater than TTL/5 (5.904/5 mm). Advantageously, the fourth air gap between lens elements **708** and **710** has a thickness (0.121 mm) which is less than $d_5/2$ (0.431/2 mm).

The focal length (in mm) of each lens element in embodiment **700** is as follows: f1=2.687, f2=-6.016, f3=-6.777, f4=8.026 and f5=-5.090. The condition $1.2 \times |f3| > |f2| > 1.5 \times f1$ is clearly satisfied, as $1.2 \times 6.777 > 6.016 > 1.5 \times 2.687$. f1 also fulfills the condition $f1 < TTL/2$, as $2.687 < 2.952$.

Using a Tele lens designed as above, TTLr is reduced to $7 \times 0.87 = 6.09$ mm, leading to a camera height of less than 7 mm (acceptable in a smartphone). The height difference (vs. the Wide camera) is also reduced to approximately 1.65 mm, causing less shadowing and light blocking problems.

In some embodiments of a dual-aperture camera disclosed herein, the ratio "e"= EFL_T/EFL_W is in the range 1.3-2.0. In some embodiments, the ratio $TTL_T/TTL_W < 0.8e$. In some embodiments, TTL_T/TL_W is in the range 1.0-1.25. In general, in camera embodiments disclosed herein, EFL_W may be in the range 2.5-6 mm and EFL_T may be in the range 5-12 mm.

With reference now to FIG. 4, in operation, tilt sensor **404** dynamically measures the camera tilt (which is the same for both the Wide and Tele cameras). OIS controller **402**, which is coupled to the actuators of both cameras through base **318**, receives a CT input from the tilt sensor and a user-defined zoom factor, and controls the lens movement of the two cameras to compensate for the tilt. The LMV is exemplarily in the X-Y plane. The OIS controller is configured to provide a LMV equal to $CT \times EFL_{ZF}$, where "EFL_{ZF}" is chosen according to the user-defined ZF. In an exemplary OIS procedure, when ZF=1, LMV is determined by the Wide camera EFL_W (i.e. $EFL_{ZF} = EFL_W$ and $LMV = CT \times EFL_W$). Further exemplarily, when $ZF > e$ (i.e. $ZF > EFL_T/EFL_W$), LMV is determined by EFL_T (i.e. $EFL_{ZF} = EFL_T$ and $LMV = CT \times EFL_T$). Further exemplarily yet, for a ZF between 1 and e, the EFL_{ZF} may shift gradually from EFL_W to EFL_T according to $EFL_{ZF} = ZF \times EFL_W$. As mentioned, the OIS procedure above is exemplary, and other OIS procedures may use other relationships between EFL_{ZF} and ZF to provide other type of LMV.

While this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of the embodiments and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited by the specific embodiments described herein, but only by the scope of the appended claims.

What is claimed is:

1. A dual-aperture zoom camera, comprising:

a) a Wide camera that includes a Wide lens with an effective focal length EFL_W and a total track length TTL_W ; and

b) a Tele camera that includes a Tele lens with five lens elements and with an effective focal length EFL_T , a total track length TTL_T and a F number smaller than 3.2,

wherein the respective Wide and Tele lens total track lengths and effective focal lengths fulfill the conditions $TTL_W/EFL_W > 1.1$ and $TTL_T/EFL_T < 1.0$, wherein the Tele lens comprises, in order from an object side to an image side of the Tele lens and along an optical axis of the Tele lens, first, second, third, fourth and fifth lens elements, wherein a focal length f_1 of the first lens element of the Tele lens is smaller than $TTL_T/2$.

2. The dual-aperture zoom camera of claim 1, wherein a height difference between the Tele and Wide cameras is equal to or smaller than 1.65 mm.

3. The dual-aperture zoom camera of claim 1, wherein a ratio $e = EFL_T/EFL_W$ between the effective focal lengths of the Tele and Wide cameras is in the range 1.3-2.0.

4. The dual-aperture zoom camera of claim 3, wherein a ratio TTL_T/TTL_W between the total track lengths of the Tele and Wide cameras is smaller than 0.8e.

5. The dual-aperture zoom camera of claim 1, wherein a height of the dual-aperture zoom camera has a value between 4 mm and 8 mm.

6. The dual-aperture zoom camera of claim 1, wherein an air gap between the third lens element and the fourth lens element is greater than $TTL_T/5$.

7. The dual-aperture zoom camera of claim 1, wherein an air gap between the first lens element and the second lens element is smaller than half a width of the second lens element.

8. The dual-aperture zoom camera of claim 1, wherein an air gap between the fourth lens element and the fifth lens element is smaller than 1.5 times a width of the fifth lens element.

9. The dual-aperture zoom camera of claim 1, wherein the F number is substantially equal to 2.8.

11

10. The dual-aperture zoom camera of claim 1, wherein the fourth lens element and the fifth lens element have different dispersions.

11. The dual-aperture zoom camera of claim 1, wherein the fourth and fifth lens elements have opposite refractive power signs.

12. The dual-aperture zoom camera of claim 1, wherein the third lens element has negative refractive power.

13. The dual-aperture zoom camera of claim 5, wherein the fourth lens element and the fifth lens element have opposite refractive power signs.

14. The dual-aperture zoom camera of claim 5, wherein the third lens element has negative refractive power.

15. A dual-aperture zoom camera, comprising:

a) a Wide camera that includes a Wide lens with an effective focal length EFL_W and a total track length TTL_W , wherein $TTL_W/EFL_W > 1.1$, and

b) a Tele camera that comprises a Tele lens with an effective focal length EFL_T , a total track length TTL_T of 6 millimeters or less and a ratio $TTL_T/EFL_T < 1.0$, wherein the Tele lens includes, in order from an object side to an image side, a first lens element L_1 with positive refractive power and a focal length f_1 , a second lens element L_2 with negative refractive power and a focal length f_2 , a third lens element L_3 with negative refractive power and a focal length f_3 , a fourth lens element L_4 , and a fifth lens element L_5 , and wherein $1.2 \times |f_3| > |f_2| > 1.5 \times f_1$.

16. The dual-aperture zoom camera of claim 15, wherein the Tele lens has a F number smaller than 2.9.

17. The dual-aperture zoom camera of claim 15, wherein lens element L_1 has a convex image-side surface.

12

18. The dual-aperture zoom camera of claim 15, wherein lens element L_1 has a concave image-side surface.

19. The dual-aperture zoom camera of claim 15, wherein lens element L_1 has an image-side surface diameter between 2.3 mm and 2.5 mm.

20. A dual-aperture zoom camera, comprising:

a) a Wide camera that includes a Wide lens with an effective focal length EFL_W and a total track length TTL_W , wherein $TTL_W/EFL_W > 1.1$; and

b) a Tele camera that comprises a Tele lens having, in order from an object side to an image side, a first lens element L_1 with positive refractive power and a focal length f_1 , a second lens element L_2 with negative refractive power, a third lens element L_3 , a fourth lens element L_4 , and a fifth lens element L_5 ,

wherein the Tele lens has an effective focal length EFL_T , a total track length TTL_T of 6.0 millimeters or less and a ratio $TTL_T/EFL_T < 1.0$, wherein a F number of the Tele lens is smaller than 2.9, wherein f_1 is smaller than $TTL_T/2$, wherein lens elements L_3 and L_4 are separated by a gap greater than $TTL_T/5$, wherein lens elements L_4 and L_5 are separated by a gap smaller than $TTL_T/20$, and wherein the five lens elements are made of plastic.

21. The dual-aperture zoom camera of claim 20, wherein F number=2.8.

22. The dual-aperture zoom camera of claim 20, wherein the ratio TTL_T/EFL_T is between 0.85 and 0.95.

23. The dual-aperture zoom camera of claim 20, wherein a combined power of lens elements L_2 and L_3 is negative.

* * * * *