




US 20070173835A1

(19) **United States**(12) **Patent Application Publication**
Medoff(10) **Pub. No.: US 2007/0173835 A1**(43) **Pub. Date: Jul. 26, 2007**(54) **INTRAMEDULLARY IMPLANT FOR
FRACTURE FIXATION AND METHOD OF
USING THE SAME**(52) **U.S. Cl. 606/62**(57) **ABSTRACT**(76) **Inventor: Robert J. Medoff, Kailau, HI (US)**

Correspondence Address:

PATZIK, FRANK & SAMOTNY LTD.
150 SOUTH WACKER DRIVE
SUITE 1500
CHICAGO, IL 60606 (US)(21) **Appl. No.: 11/331,738**(22) **Filed: Jan. 13, 2006****Publication Classification**(51) **Int. Cl.**
A61F 2/30 (2006.01)

An intramedullary implant, useful particularly for the fixation of fractures of the radius, the implant comprising a first and second end, both ends configured for entry into the intramedullary canal through an entry point on the bone, such as the fracture site, and configured for positioning within the intramedullary canal of the fractured bone, the first end positioned in the intramedullary space of a first bone fragment and the second end positioned in the intramedullary space of a second bone fragment on the opposite side of the fracture. The first end is positioned by displacing the implant in a first direction and the second end is positioned by displacing the implant in a second direction, substantially opposite to the first direction. The implant further comprises a tip configured to abut an end surface of the second fragment to provide axial support to second fragment.






FIGURE 1




FIGURE 2




FIGURE 3



FIGURE 4



FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10




FIGURE 11




FIGURE 12




FIGURE 13




FIGURE 14




FIGURE 15




FIGURE 16




FIGURE 17




FIGURE 18




FIGURE 19




FIGURE 20




FIGURE 21




FIGURE 22




FIGURE 23




FIGURE 24




FIGURE 25




FIGURE 26




FIGURE 27




FIGURE 28




FIGURE 29




FIGURE 30




FIGURE 31




FIGURE 32

INTRAMEDULLARY IMPLANT FOR FRACTURE FIXATION AND METHOD OF USING THE SAME

FIELD OF THE INVENTION

[0001] This invention relates to an intramedullary fracture fixation implant and particularly to a fracture fixation implant for fixation of distal fractures of the radius in which the implant is adopted to be axially inserted and secured within the intramedullary canal portions of the bone segments on opposing sides of the fracture. The invention further comprises a method of fracture fixation with the intramedullary fracture fixation implant of the present invention.

BACKGROUND AND PRIOR ART

[0002] Fractures that occur in proximity to a joint can be difficult to treat. Although plates, screws and pins on the surface of the bone can provide fracture stability, often the close proximity of tendons to the surface of the bone can result in soft tissue irritation and even tendon rupture that can compromise the outcome. Intramedullary fixation of fractures, with or without cross-locking screws, is well known to reduce the problem of soft tissue irritation by placing the bulk of the implant within the bone itself.

[0003] Furthermore, intramedullary fixation can provide fracture stability because of either a tight fit of the rod within the bone or fixation from locking screws that cross through the bone and rod. Traditional intramedullary rods, however, are not well suited for fixation of a fracture in proximity to the end of the bone. For example, in the case of fractures of the distal radius, the distal end of the radius is extremely wide with soft cancellous bone within the intraosseous space and only thin weak cortical bone that surrounds the tubular structure; the strongest bone at the distal end of the radius is the thick subchondral bone that extends behind the articular surface and is under the tip of the radial styloid. In the case of fractures of the distal radius, insertion of the implant is not possible through the tubular proximal fragment because of its deep location and the narrow, cylindrical nature of the morphology that makes it impossible to direct an intramedullary implant down the center of the bone. Because of this, intramedullary fixation of distal radius fractures has always inserted the device directly through the soft radial surface of the radial styloid in order to direct the implant within the intramedullary canal. This necessarily results in creation of a large additional hole that is at least the diameter of the implant in the small distal fragment, which can easily result in creation of additional fragmentation, collapse of the fragment and resultant loss of fixation.

[0004] In addition, since the implant is inserted through this large defect in the distal fragment, it is not possible for the end of the implant to be used to provide axial support to the fragment; instead, the implant is totally dependent on the resistance of the thin cortical bone to translational movement and the purchase of transverse locking screws in the soft, often osteoporotic, metaphyseal bone. As a result, loss of radial length can easily occur, resulting in protrusion of the nail from the insertion site as well as deformity and loss of function. Finally, because the end of the bone is often covered with articular cartilage which is damaged if a nail is inserted through it, standard intramedullary implants are unable to provide support to the end of the bone as they must be placed more proximal to this area to prevent damage to the joint.

[0005] Standard intramedullary rods use cross locking screws to prevent the small distal fragment from losing length. Examples of standard intramedullary rods are shown in U.S. patent application Ser. No. 10/377,255 to Warburton and entitled Intramedullary Interlocking Fixation Device for the Distal Radius (U.S. Publication No. 2004/0010255) and U.S. patent application Ser. No. 09/975,514 to Putnam and entitled Intramedullary Rod for Wrist Fixation (U.S. Publication No. 2003/0073999). Because these screws are placed across the nail into the metaphyseal bone of the distal fragment, they are loaded at their tip by the compressive loads that occur across the wrist. This places a significant torque on the screw, which can lead to increased implant loads and can result in breakage, cutout through the bone, or loosening of the screw. In turn these can result in loss of length, deformity, and impaired function of the wrist.

[0006] Since the distal radius is made of relatively soft cancellous bone, there is little resistance to side-to-side translational displacements by a standard intramedullary nail, particularly since the nail is placed through a hole made in the bone and courses to lie entirely within the metaphyseal cavity. This results in poor support of the fragment by the nail itself, requiring the majority of resistance to displacement to be taken up by the distal crossing screws.

[0007] In copending U.S. patent application Ser. No. 10/675,864 to Medoff and entitled Intramedullary Implant for Fracture Fixation (U.S. Publication No. 2005/0070902), an approach was described that provides axial support of the radial styloid by the tip of an implant that is placed intramedullary into the distal fragment. Since the implant lies on the extraosseous surface proximally, the implant enters the fracture site and can be placed with a single longitudinal insertion into the distal fragment. However, this design requires a more extensive dissection for placement of the extramedullary portion of the implant in addition to resulting in an implant that is still fixed on the surface of the bone over one part, with the possibility of further soft tissue irritation. In addition, since the surface portion of the implant must be thin to avoid prominence and soft tissue irritation, this creates a stress riser at the junction of the extramedullary and intramedullary portions of the implant that can result in breakage.

[0008] Current intramedullary implants are inserted into a tubular bone from one end and driven to the opposite end. In some applications, the implant is inserted at the proximal end of the bone and driven in an ante grade direction into the distal end of the long bone. In other applications, the implant is inserted at the distal end of a long bone and driven in a retrograde direction into the proximal end. Because the direction of insertion is always uni-directional, current intramedullary designs do not permit fixation both above and below the site of insertion of the implant. In addition, since existing intramedullary implants are designed for insertion in a single direction only (either ante grade or retrograde), these implants are always connected to a driver at one end.

SUMMARY OF THE INVENTION

[0009] An object of the current invention is to provide an intramedullary implant that can be inserted without the creation of a new, large defect in either fragment, but particularly the small distal fragment, thereby avoiding the risk of additional fracture comminution caused from the insertion procedure itself.

[0010] A further object of the invention is to provide an intramedullary implant that can be inserted without the necessity of driving the implant along a single axis into the bone from one end, thereby avoiding the problem of positioning the insertion hole in the bone directly over the end of the implant and resulting in the inability of the implant to support the distal fragment axially and poor resistance to shortening.

[0011] A further object of the invention is to provide an intramedullary implant that resists loss of length by providing axial support along its tip to the strong subcortical bone at the end of a fragment.

[0012] A further object of the invention is to provide an intramedullary implant that can both resist loss of length through axial support of an unstable bone fragment as well as achieve rotational support from cross locking screws in the unstable fragment.

[0013] A further object of the invention is to allow a provision for a relatively smooth tip to be situated centrally within the conical morphology of the tip of the radial styloid, abutting the strong subchondral surface at the end of the bone. In addition to the load support by the tip, the tip is captured by the concave conical bone at the radial styloid, thereby resisting translational movement of the distal fragment by the nail itself. This is comparable to the way a tent is supported by a tent pole.

[0014] A further object of the invention is to provide a method of fixation that is simple to apply, allows insertion of an intramedullary implant to span a fracture defect by insertion of the implant through the fracture site itself, with a minimal incision or even subcutaneous approach.

[0015] A further object of the invention is to provide instrumentation that allows an intramedullary implant to be inserted through a fracture defect into an intramedullary position, spanning the fracture defect and achieve purchase in the fragments on both sides of a fracture.

[0016] A further object of the invention is to provide a means of insertion that allows an intramedullary implant to be inserted in one direction through a relatively central insertion site in the bone, and then displaced in the opposite direction to allow bone purchase on both sides of the insertion site.

[0017] A further object of the present invention is to provide instrumentation that cooperates with areas of connection on an intramedullary implant in order to allow the implant to be axially displaced in a direction that is opposite of the initial insertion of the implant into the bone.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0019] FIG. 2 is a front elevation view of the intramedullary fixation device according to the present invention;

[0020] FIG. 3 is a side elevation view of the intramedullary fixation device according to the present invention;

[0021] FIG. 4 is a cross-section view of the intramedullary fixation device according to the present invention taken along section line 4-4 in FIGS. 2 and 17;

[0022] FIG. 5 is a cross-section view of the intramedullary fixation device according to the present invention taken along section line 5-5 in FIGS. 2 and 17;

[0023] FIG. 6 is an elevation view of a component of the intramedullary fixation device of the present invention;

[0024] FIG. 7 is an elevation view of a component of the intramedullary fixation device of the present invention;

[0025] FIG. 8 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0026] FIG. 9 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0027] FIG. 10 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0028] FIG. 11 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0029] FIG. 12 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0030] FIG. 13 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0031] FIG. 14 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0032] FIG. 15 is a schematic view of an x-ray showing the intramedullary fixation device of the present invention inserted within an intramedullary canal;

[0033] FIG. 16 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0034] FIG. 17 is a front elevation view of another preferred embodiment of an intramedullary fixation device according to the present invention;

[0035] FIG. 18 is a side elevation view of another preferred embodiment of an intramedullary fixation device according to the present invention;

[0036] FIG. 19 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0037] FIG. 20 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0038] FIG. 21 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0039] FIG. 22 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0040] FIG. 23 is a schematic view of a step in a method for fixing a bone fracture using the intramedullary fixation device of the present invention;

[0041] FIG. 24 is a schematic view of an x-ray showing the intramedullary fixation device of the present invention inserted within an intramedullary canal;

[0042] FIGS. 25-28 are elevation views of a second preferred embodiment of the present invention; and

[0043] FIGS. 29-32 are elevation views of mechanisms for positioning the implant of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

[0044] In accordance with the present invention, a fracture fixation device is provided which comprises an intramedullary rod for placement into a fracture defect. Referring to FIG. 1, a bone 10, such as the radius, is shown in which a fracture 12 is present at its distal end and forms a stable first, proximal bone fragment 14, and an unstable second, distal bone fragment 16. The second bone fragment 16 has an end portion 18, comprising, for example, the radial styloid 20 when the fracture is a distal radius fracture. The fracture 12, as illustrated in FIG. 1, is in proximity to the end portion 18 of the second fragment 16 of the bone 10. However, the fracture can also be displaced proximally or centrally on the bone without altering the inventive concept. It should also be noted that the general design of the present fracture fixation implant is applicable to other locations, such as the end of the humerus, ulna, tibia, fibula, femur or other long bones comprising an intramedullary canal, without restricting the spirit or scope of the invention.

[0045] Referring to FIGS. 2-5, an intramedullary fracture fixation implant 22 is shown. The implant 22 comprises a first end 24 and a second end 26. In the embodiment of the present invention shown in FIG. 2, the implant 22 is largely banana-shaped and has a curvilinear profile when viewed from the anterior-posterior view and a generally linear profile when viewed from the lateral view (FIG. 3). The implant 22 is composed of any suitable material that exhibits the appropriate mechanical and biological compatibility with the fracture fixation. In a preferred embodiment, the implant is composed of surgical grade stainless steel, surgical grade titanium, or a surgical grade titanium alloy. In other preferred embodiments, any surgical grade implantable material with sufficient strength and stiffness characteristics can be used.

[0046] The first end 24 of the implant 22 may comprise at least a first receptor configured to receive a fastener for securely and releasably mating the implant to the shaft of the bone 10. In the embodiment of the present invention shown in FIG. 2, a plurality of receptors 34, 36, 38, 40, are used, each of the plurality of receptors comprising a screw hole having an open-ended channel extending across the width of the first end 24 of the implant 22. The number of receptors required can vary and is dependent on the particular application for the implant and desired or required amount of the fixation of the first end to the first fragment.

[0047] In a preferred embodiment, the cross section of the first end 24 is in the form of a square with curved corner portions (FIG. 4). The first, second, third, and fourth screw holes 34, 36, 38, 40 are all disposed on the same surface of the implant 22. This configuration enables the insertion of fasteners into the receptors from a dorsal approach, enabling avoidance of tendons, nerves, or major arteries in the area. The fasteners are captured by and extend through the

receptors 34, 36, 38, 40 and into the shaft of the first fragment 14 (FIG. 1) to secure the implant 22 to the bone 10. The modified square cross-section also assists in centering a fastener into a corresponding receptor.

[0048] It is also contemplated that the first end 24 can be formed into a square or circular cross-section. In addition, a means for self-centering the fasteners may be incorporated with each receptor, such as a counter bore surrounding each receptor or a concave entry portion for each receptor. In addition, in other preferred embodiments of the present invention, the receptors are disposed radially around the perimeter of the first end 24. Alternatively, receptors 34, 36, 38, 40 can be angled medial to lateral, arranged in an oblique orientation, or a combination of these configurations. The number of receptors may also vary to provide for secure fixation of a longer fracture, or a smaller implant for simplified fixation in simple fractures.

[0049] In the embodiment of the present invention shown in FIG. 2, the receptors 34, 36, 38, 40 are threaded and are configured to receive and capture fasteners comprising bone screws. However, it is contemplated that unthreaded receptors 34, 36, 38, 40 can be utilized without affecting the performance of the implant 22. When the receptors 34, 36, 38, 40 are unthreaded, it is contemplated that the fasteners comprise a peg, rivet, screw, or any other suitable fastener for engaging an unthreaded receptor.

[0050] The second end 26 of the implant 22 has a substantially round cross-section (FIG. 5) and may comprise a longitudinal receptor 46 at the tip 32 for receiving and capturing a fastener configured to mate the implant to the strong cortical bone at the end portion 18, and specifically in the radial styloid 20 of the second fragment 16 when the implant 22 is used in the fixation of a distal radius fracture. In accordance with the intended placement of the tip 32 of the implant 22, the tip 32 is contoured to largely conform to the contour of the endosteal surface of the radial styloid 20 of the radius 10. In addition, the surface contour of the tip 32 is large enough to spread the axial load on the implant at the tip 32 over a large contact area. This provides excellent support and strength to the second fragment 16 to resist loss of length of the bone 10 during the healing of the fracture, as well as the biomechanical advantage of avoiding excessive loading on the implant 22, that could result in breakage or cut-out.

[0051] This is in contrast to a standard intramedullary implant, in which the resistance to loss of length is borne by bone screws that extend through the width of the implant and are subject to high torque and implant loads that may lead to failure of the implant. In addition to its axial loading function or end-bearing function, the tip 32 is further configured to comprise a leading edge for driving the implant into position within the intramedullary space 52b of the bone 10. When the implant 22 is used for fracture fixation in bones other than the radius, the tip 32 is configured to largely conform to the endosteal surface or end portion of the second fragment of the bone to be fixed by the implant 22.

[0052] The longitudinal receptor 46 comprises a threaded screw hole comprising an aperture and threaded channel bored into the tip 32. In the preferred embodiment of the present invention, the longitudinal fastener is a radial styloid bone screw 49 (FIG. 14). However, other suitable fasteners may also be used. The diameter of the second end 26 of the

implant is significantly larger than the diameter of the longitudinal receptor 46 in order to allow the implant to support axial loading at the tip 32 during fracture reduction and fixation. After placement of the second end 26 of the implant 22 within the intramedullary space 52b and abutment of the tip 32 against the endosteal surface of the cortical bone of the radial styloid 20 (FIG. 1), the longitudinal fastener 49 (FIG. 14) is used to hold the implant in position against the cortical bone of the radial styloid 20.

[0053] As is seen in FIGS. 15, the tip 32 may also comprise a cannulated channel 47 that extends from the tip 32 through a segment of the second end 26 of the implant 22. The channel 47 is configured to receive and enable passage of a guide wire 64 (FIG. 16) from the radial styloid 20 of the second fragment 16 to guide the implant 22 into proper position. The cannulated channel 47 is integrally formed and coaxially aligned with the longitudinal receptor 46. However, the cannulated channel 47 may also be formed independent of the longitudinal receptor 46.

[0054] In the preferred embodiment of the present invention, the second end 26 may also comprise at least one cross-locking receptor for securely and releasably mating the implant 22 to the second fragment 16. In the embodiment shown in FIG. 3, a first and second cross-locking receptor 42, 44 are used for receiving and capturing a fastener. Each receptor 42, 44 comprises a screw hole having an open-ended channel extending diametrically through the second end 26 of the implant 22. The cross-locking receptors 42, 44 are preferentially, but not necessarily, radially spaced apart at an angular distance from each other. In one embodiment, the cross-locking receptor 42 is directed volarly at angle of approximately 17 degrees to the palm in respect to the coronal plan, and is approximately 10 degrees proximally inclined. The cross-locking receptor 44 is directed dorsally at an angle of approximately 12 degrees with respect to the coronal plan and is approximately 8 degrees proximally inclined. However, this specific angular displacement of the cross-locking receptors 42, 44 is disclosed for exemplary purposes only. This arrangement enables engagement of the volar subchondral bone of the second fragment 16 by a fastener that is captured by and extending through the first receptor 42 and engagement of the dorsal subchondral bone of the second fragment 16 by a fastener that is captured by and extends through the second receptor 44.

[0055] Referring to FIGS. 1, 6-7, and 10-12, the implant 22 is also provided with a radial driver assembly configured to attach a driver 58 or alignment jig to the implant 22 to facilitate insertion of the implant 22 through an entry point 48 on the bone 10 and into the intramedullary space 52a of the first fragment 14, and to allow for positioning of the implant 22 within the intramedullary space 52a. In a preferred embodiment of the present invention, the cross-locking receptor 42 is also configured to releasably capture the driver 58, as will be described below. The externally threaded end 60 of the driver 58 releasably engages the corresponding internal threads in the receptor 42 to provide a handle for insertion of the implant 22 into the intramedullary space 52a. In other preferred embodiments, the driver can take the form of a peg that is received by a corresponding receptor on the second end 26, or alternatively, the driver can include a tongue-like end that is received by a groove in the second end 26.

[0056] An axial driver assembly is provided to enable the implant to be displaced across the fracture site 12 from the first intramedullary space 52a into the intramedullary space 52b of the second fragment 16 until the tip 32 abuts the end portion 18 of the second fragment 16, e.g. the endosteal surface of the radial styloid 20 when the implant 22 is used during fixation of a distal radius fracture. In the first preferred embodiment of the present invention, the longitudinal receptor 46 is also configured to receive and capture a driver 50 (FIG. 6) or alignment jig to facilitate drawing the implant into the intramedullary space 52b. The externally threaded end 56 of the driver 50 releasably mates with the corresponding internal threading of the longitudinal receptor 46.

[0057] The driver 50 is used as a handle to draw the implant 22 towards the radial styloid 20 (FIG. 12). The driver 50 has a section of reduced diameter above the terminal thread enabling angular adjustment of driver 50 within the hole drilled through the radial styloid 20 to enable alignment of the driver tip 56 with the threads in longitudinal receptor 46 and to allow the two pieces to be connected and screwed together. Once the implant is in position, the driver 50 is removed from the longitudinal receptor 46 and can be replaced by a fastener, such as a radial styloid screw, as described above. In other preferred embodiments, the driver can take the form of a peg that is received by a corresponding receptor on the second end 26, or alternatively, the driver can include a tongue-like end that is received by a groove in the tip 32.

[0058] FIGS. 17 and 18 show a second preferred embodiment of the present invention wherein the general shape of implant 22 is S-shaped (FIG. 17) when viewed from the anterior-posterior view and generally linear when viewed from the lateral view (FIG. 18). As is shown in FIGS. 4 and 5, the implant of the second preferred configuration has the same cross-sectional geometry as the banana-shaped implant previously described. The use and configuration of: at least a first receptor, and preferably a plurality of receptors 34, 36, 38, 40, disposed on the first end 24 of the implant 22; zero, one or more cross-locking receptors at the second end 26 of the implant 22, and preferably a plurality of cross-locking receptors 42, 44; a longitudinal receptor 46 at the tip 32 of the second end 26; and receptors for axial and radial driver assemblies is also the same as described above.

[0059] FIGS. 1, 8-15, and 19-24 show a method of the using the intramedullary fracture fixation implant 22 of both the first and second preferred embodiments of the present invention for reduction and fixation of a distal radius fracture. The same methodology may be used to reduce and fix fractures of bones other than the radius. First, an entry site 48 for the implant 22 is formed in the bone 10. In FIG. 1, a biting tool or reamer (not shown) is used to extend an opening 48 from the fracture site 12 proximally to allow insertion of the implant 22. While extending the opening 48 from the fracture site 12 extends the already unstable fracture site, it does not add a new hole in the first fragment 14. Accordingly, its effect on weakening the bone 10 is relatively minor. In addition, no additional defect is created in the small, peri-articular distal fragment 16 as would occur if a traditional insertion technique from the end of the bone was used. In other embodiments of the invention, a new point of entry 48 of the implant into the intramedullary canal 52 may be formed in the bone 10.

[0060] As is shown in FIG. 8, an aperture 62 is then formed in the tip of the radial styloid 20 of the second fragment 16. The aperture 62 is formed by a drill, awl or pin 63. A guide 65 may also be used to confirm the positioning of the drill, awl, or pin 63 at the proper entry location and to prevent wrapping of soft tissues structures as the aperture 62 is formed. The aperture 62 is at least of a diameter to accommodate the driver 50 (FIG. 6) and longitudinal fastener 49 (FIG. 14) that are received and captured by the longitudinal receptor 46, as was described previously; typically this may range in size between 0.5 mm to 5 mm. If required, a guide wire or ribbon 64 is inserted through the aperture 62 and into the intramedullary space 52b (FIG. 9). As is seen in FIG. 16, the guide wire or ribbon 64 is received by the cannulated channel 47. FIG. 9 also shows the use of an impactor or cannulated flexible reamer 66 to develop a pathway in the intramedullary space 52b of the second fragment 16. A path 68 through the soft metaphyseal bone is made to enable abutment of the tip 32 of the implant 22 against the strong subchondral bone surface of the radial styloid 20.

[0061] Next, as is shown in FIGS. 10 and 19, a driver 58 or alignment jig is releasably mated with the implant 22 at the cross-locking receptor 42 and the implant 22 is inserted through the entry point 48 into the intramedullary space 52a of the first fragment 14. As shown in FIGS. 11 and 20, once the implant 22 is inserted into the intramedullary space 52a, the second driver 50 is inserted through the aperture 62 in the radial styloid 20, through the path 68, and is releasably mated with the implant at the longitudinal receptor 46 in the tip 32. The driver 58 can be used to stabilize the implant and prevent rotation of the implant 22 as the driver 50 is screwed into place. The driver 58 or alignment jig is then removed from the cross-locking receptor 42 to enable the implant to be displaced across the fracture site 12.

[0062] Referring to FIGS. 12 and 21, the implant 22 is then drawn into the intramedullary space 52b of the second fragment 16 until the tip 32 of the implant 22 abuts the endosteal surface of the subchondral bone under the radial styloid 20. Since the tip 32 is larger than the aperture 62 in the radial styloid 20, the tip 32 of the implant provides axial support to maintain radial length without the oblique torque that occurs when the resistance to loss of radial length is provided exclusively by cross fixation members. In addition, the congruence of the surface contour of the tip 32 to the endosteal surface of the radial styloid 20 adds further constraint to resist side-to-side movement of the second fragment 16. As is seen in these figures, the implant 22 is positioned with the intramedullary space 52a of the first fragment 14 by displacing the first end 24 in a first direction and then displacing the implant in a second direction, substantially opposite the first direction, to place the second end 26 into the intramedullary space 52b of the second fragment 16.

[0063] As is shown in FIGS. 13 and 22, the implant 22 is positioned at the proper angular position and a drill guide 60 having a first and second end 62, 64 is positioned where the first end 62 of the drill guide 60 overlaps the first end 24 of the implant 22 on the exterior of the bone 10 and the second end 64 of the drill guide 60 is aligned with the second end 26 of the implant 22. The first end 62 of the drill guide 60 comprises apertures 66, 68, 70, 72 that align with the receptors 34, 36, 38, 40 at the first end 24 of the implant 22.

The second end 64 comprises drill guides 74, 76 that may be used to bore holes in the bone 10 and/or form the cross-locking receptors 42, 44.

[0064] In one embodiment, the implant 22 may comprise an alignment mechanism to orientate the drill guide 60 and align apertures 66, 68, 70, 72 and receptors 34, 36, 38, 40 and properly position the drill guides 74, 76. As shown in FIGS. 3 and 18, the orientation mechanism for the alignment jig may be integrally formed with one of the cross-locking receptors 42 when the cross-locking receptors 42, 44 are formed in the implant 22 prior to insertion of the implant within the bone 10 and comprises diametrically spaced slots on 54a, 54b opposing sides of the cross-locking receptor 44. Alternatively, the orientation mechanism may be a receptor on the side of the implant or may be attached to second driver 58.

[0065] Drilling holes into the bone through the apertures 66, 68, 70, 72 will form concentric channels with the receptors 34, 36, 38, 40 for receiving fasteners to secure the implant 22 to the first fragment 14. The first guide 74 is used to bore the first receptor 42 into the second end 26, and the second guide 76 aligns to form the second receptor 44.

[0066] As is shown in FIGS. 14 and 23, the drill guide is removed and the cross-locking fasteners 78, 80 are secured in place. Although in FIGS. 14 and 23, the cross-locking fasteners 78, 80 are shown to extend through the implant and across the intramedullary space 52b of the second fragment 16, this configuration is for exemplary purposes only. Depending on the nature of the fracture and preference of the medical professional using the implant 22, fasteners that only extend into the second end 26 of the implant 22, such as pegs, rivets, and/or shorter bone screws, can be utilized. The axial driver is removed from the longitudinal receptor 46 either before or after placement of the cross-locking screws, and replaced by the longitudinal fastener 49, e.g. radial styloid bone screw, when fixing a distal radius fracture. This locks the tip 32 of the implant 22 into abutment with the subchondral bone under the radial styloid 20 and secures the second end 26 of the implant 22 to the end portion 18 of the second fragment 16. With firm fixation of the implant 22 in the second fragment 16, the fracture is brought out to length and reduced.

[0067] Once the position of the fracture reduction is confirmed, the fracture reduction is secured by insertion of fasteners 84, 86, 88, 90 through the bone 10, and into engagement with the receptors 34, 36, 38, 40 in the first end 24. Depending on the type of fasteners used, the fasteners 84, 86, 88, 90 may extend through the receptors 34, 36, 38, 40 and into the surrounding bone of the first fragment 14. Alternatively, receptors 34, 36, 38, 40 may be threaded and allow the use of unicortical locking screws. Fixation of the implant 22 to the first fragment 14 results in the support of the second fragment 16, in a manner similar to a tent pole supporting a tent; this prevents collapse of the second fragment 16, with resultant loss of length of the bone 10.

[0068] Although shown with two cross-locking receptors 42, 44 in the second end 26, any number of fixation members placed in the second end may be applicable depending on the site of application and the size of the implant. In addition, the fixation members may be torsionally disposed to one another to allow more spread to the fixation of the second fragment. In a preferred embodiment, the first receptor 42 is

angled to purchase the volar rim of the second fragment 16, placing its entry site dorsally and avoiding contact with the first dorsal compartment tendons; the second receptor 44 is angled distally and dorsally to engage the dorsal ulnar corner of the second fragment 16. In addition, although four fasteners are shown to secure the implant 22 to the first fragment 14, any number of fasteners could be used and would not depart from the spirit and scope of the invention.

[0069] The implant may be removed once the fracture site has healed by using a hollow drill bit to core out a section of the radial styloid to enable extraction through the hole. Because the fracture site will have healed over, the implant cannot usually be extracted through the entry site.

[0070] FIGS. 25-28 show a third preferred embodiment of the present invention, where the implant 22 comprises a first and second portion 92, 94 that secured together to form a single unit. Once secured together, the first portion 92 comprises the first end 24 of the implant 22 and the second portion 94 comprises the second end 26 of the implant. The first portion 92 has a concave, bent curvature with at least a first receptor 96 for receiving a fastener.

[0071] In the embodiment shown in FIG. 25-28 the first end 24 comprises a plurality of receptors 96, 98, 100. The first receptor 96 comprises a slotted aperture enabling fixation of the first end 24 of the implant 22 with a fastener, but also enabling proximal or distal fine-tuning of the fracture reduction when the fastener is only loosely placed within the receptor 96. The second and third 98, 100 receptors consist of screw holes comprising an open-ended channel extending through the width of the implant 22. As is seen in FIG. 25, the plurality of receptors 96, 98, 100 are linearly aligned. However, the receptors 96, 98, 100 may also be radially disposed around the perimeter of the first end 24 to facilitate a cross-locking arrangement. The head 102 of the first end 24 is configured to be the leading edge or drive surface of the first end 24 as it enters the bone through the extended portion 48 of the fracture site 12 (FIG. 1) and is positioned within the intramedullary space 52a.

[0072] The second end 26 of the implant 22 comprises a support peg 103 configured to abut and support the endosteal surface of the radial styloid portion 20 of the bone 10. As was described with the second end of the implant of the first and second embodiments, the support peg 103 has a substantially round cross-section and a tip 32 having the same general shape and contour of the endosteal surface of the cortical bone at the radial styloid 20. The tip 32 has a generally cone-like shape with a flattened or rounded end. This provides excellent support and strength to the second fragment 16 to resist loss of length of the bone 10 during the healing of the fracture 12.

[0073] The tip 32 of the support peg 103 comprises the leading edge or drive surface of the second end 26 when the second end 26 is inserted through the entry point 48, which in this figure comprises the extended portion of the fracture site 12 (FIG. 1) and into the intramedullary space 52b of the second fragment 16, as well as serving the load bearing function described above. The second end 26 also comprises an interface for engaging the first end 24 of the implant 22 to form a unitary component.

[0074] In the embodiment of the present invention shown in FIGS. 25-28, the interface between the first and second

ends 24, 26 of the implant 22 is a tongue and groove assembly. The first end 24 comprises a flattened, tongue portion 106 with a bore 108 extending there through. The second end 26 comprises a first and second arm 110, 112 equidistantly spaced apart across their lengths to form a channel 114 configured to receive the tongue portion 106 of the first end 24. Each arm 110, 112 comprises a concentrically aligned bore 116, 118 for receiving a fastener.

[0075] When the tongue portion 106 engages the channel 114, the bores 108, 116, 118 align to form a through hole 120 for receiving a fastener 121 to secure the first and second ends 24, 26 together. In one embodiment, the bores 108, 116, and 118 are threaded and configured to receive a threaded fastener such as a screw. A peg or rivet may also be used to secure the first and second ends 24, 26. In addition, the bores 116, 118 may be slotted to provide for additional distal or proximal fine tuning of the placement of the implant 22 when a fastener 121 is loosely placed within the through hole 120. Other connections are also possible, such as a conical trunion that mates with a morse taper assembly (not shown) as is commonly known and used with modular prosthetic implants, or a captured channel or slot as is commonly known and used with sliding compression hip screws.

[0076] The second end 26 may also comprise a longitudinal receptor 46 at the tip 32 for receiving and capturing a fastener configured to mate the implant to the strong cortical bone in radial styloid 20 of the distal fragment 16. In one embodiment of the present invention, the longitudinal receptor 46 comprises a threaded screw hole comprising an aperture and threaded channel bored into the tip 32. In the preferred embodiment of the present invention, the longitudinal fastener is a radial styloid bone screw, such as the radial styloid bone screw 49 shown in FIG. 14. However, other suitable fasteners may also be used, such as pegs or rivets. The diameter of the second end 26 of the implant is significantly larger than the diameter of the longitudinal receptor 46 in order to allow the implant to support axial loading during fracture reduction and fixation. After placement of the implant within the intramedullary space 52b and abutment of the tip 32 against the endosteal surface of the cortical bone of the radial styloid 20, the radial styloid screw is used to hold the implant in position against the cortical bone.

[0077] The tip 32 may also comprise a cannulated channel 47 that extends from the tip 32 through a segment of the second end 26 of the implant 10. The channel 47 is configured to receive and enable passage of a guide wire extending from the radial styloid of the second fragment to guide the implant 22 into proper position. In a preferred embodiment of the present invention, the cannulated channel 47 is integrally formed and coaxially aligned with the longitudinal receptor 46. However, the cannulated channel 47 may also be formed independent of the longitudinal receptor 46.

[0078] In this embodiment of the present invention, the second end 26 may also comprise a first and second cross-locking receptor 42, 44 for receiving and capturing a fastener. Each receptor 42, 44 comprises a screw hole having an open-ended channel extending diametrically through the second end of the implant 22. The first and second cross-locking receptors 42, 44 are radially spaced apart from each other. This arrangement enables engagement of the volar

subchondral bone of the second fragment **16** by a fastener that is captured by and extending through the first receptor **42** and engagement of the dorsal subchondral bone of the second fragment **16** by a fastener that is captured by and extends through the second receptor **44**.

[0079] In operation, the implant **22** according to the third preferred embodiment of the present invention is inserted within the intramedullary space of the bone in a similar manner to methodology described with respect to the first and second embodiments, with the added step of placing and inserting the first and second ends **24**, **26** of the implant **22** into the intramedullary space of the bone **52** in two separate steps and then securing the components together to form a unitary structure. In a first step, the first end is **24** is inserted through the entry site **48** into the intramedullary space **52a** of the first fragment **14**. A fastener is placed loosely from dorsal to volar in the first, slotted receptor **96** in the first end **24** to fix the first end **24** to the first fragment **14**, but still enabling fine-tuning of the implant, and consequently the fracture reduction.

[0080] In the next step, the second end **26** is inserted through the entry point **48** and into the intramedullary space **52b** of the second fragment **16**. Once the second end **26** is properly positioned with respect to the endosteal surface of the radial styloid and the bores **116**, **118** of the second end **26** are aligned with the bore **108** of the first end **24** to form the through hole **120**, a fastener **122** is inserted within the through hole **120** and loosely placed to enable additional fine tuning of the fracture reduction. Fasteners are then placed within the receptors in the second end **26** to secure the second end **26** to the second fragment **16**. Once the fracture has been properly reduced, the fastener loosely placed in the first receptor **96** is tightened and additional fasteners may be placed within the second and third receptors **98**, **100**, to securely fasten the first end **24** to the first fragment **14**.

[0081] In the preferred embodiments of the invention described herein, the implant **22** has been positioned within the intramedullary space of the bone by utilizing a plurality of drivers with threaded ends to engage threaded receptors disposed on the implant. FIGS. 29-32 show alternative, yet preferred assemblies and structures for properly positioning the implant of the present invention by advancing the implant across the intramedullary space of the fractured bone.

[0082] Referring first to FIGS. 29 and 30, the periphery of the implant **22** comprises a serrated surface **110** for engaging the teeth **112**, **114** of a ratcheting mechanism **116**. The serrated surface **110** comprises a plurality of teeth each having an angled wall **120a** orientated upwards towards the tip **32** of the implant **22** and a base wall **120b**. In FIG. 21, when the ratcheting mechanism **116** is in the open position, its teeth **112**, **114** engage a first and second tooth of the serrated edge **110** where the first and second tooth are separated by an intervening tooth. The ratcheting mechanism **116** closes by drawing handle **117b** towards handle **117a** along the direction shown by arrow **123b**. This causes the teeth **112**, **114** to close. As the ratcheting mechanism **116** is closing, the tooth **112** of the ratcheting mechanism **116** will slide off of an angled surface **120a** and re-engage the angled surface **120a** of the tooth immediately below. Repeating this procedure will gradually displace the implant **22** in the direction of arrow **122**.

[0083] Referring to FIG. 31, the implant **22** comprises a ribbed surface **124**. A positioning instrument **125** with a rotating gear **126** is used to advance the implant in the direction of arrow **128a**. As the gear **126** rotates in the direction of arrow **128b**, the implant is advanced. The implant **22** also includes at least a first channel **130** extending in a parallel direction to the ribbed surface **124**. The channel **130** is configured to receive a guide **132** on the positioning instrument **125** that aids in keeping the positioning instrument **125** in engagement with the implant **22**.

[0084] FIG. 32 shows an assembly wherein the implant **22** comprises at a first track disposed longitudinally on the implant. In this embodiment, a first **134** and second (not shown) track on opposing sides of the implant **22** are utilized. Alternatively, this may be a single track with a tongue in groove surface (not shown). The tracks are configured to receive at least a first tongue member **136** of a positioning instrument **138**. Closing the positioning instrument by drawing handle **139b** towards handle **139a** causes the tongue member **136** to engage the track **134** and hold the implant **22**. A hole or slot **140** is disposed on the surface of the implant and is configured to receive a suture or flexible wire or ribbon **142** associated with positioning instrument **138**. The suture or wire **142** overlies a pulley **144** and is attached to a lever **141**. When the lever **141** is moved from a first position to a second position, the suture or wire **142** is pulled and displaces the implant **22** across the fracture site **12** into position in the second fragment **16**.

[0085] It will be understood that modifications and variations may be effected without departing from the spirit and scope of the present invention. It will be appreciated that the present disclosure is intended as an exemplification of the invention and is not intended to limit the invention to the specific embodiments illustrated and described. The disclosure is intended to cover, by the appended claims, all such modifications as fall within the scope of the claims.

I claim:

1) A fracture fixation implant for fixation of a broken bone comprising a fracture site, a first and second fragment on opposing sides of the fracture site, and an intramedullary space within the bone with portions on opposing sides of the fracture site, the implant comprising:

a first end configured to be placed in the intramedullary space of the first fragment;

a second end configured to be placed in the intramedullary space of the second fragment; and

a form configured to enable placement of the first end in a first direction into the intramedullary space of the first fragment through an entry point on the broken bone and further configured to enable displacement of the implant in a second direction substantially opposite the first direction and across the fracture site to enable placement of the second end into the intramedullary space of the second fragment.

2) The implant of claim 1 wherein the first fragment is at a central portion of the bone and the second fragment is at an end portion of the bone, wherein the implant further comprises a tip at the second end configured to abut the end portion of the second fragment and to enable axial loading of the implant at the tip.

3) The implant of claim 2 wherein the tip resists side-to-side displacement of the second fragment.

4) The implant of claim 2 wherein the end portion comprises an endosteal surface having a contour and the tip is contoured to largely conform to the contour of the endosteal surface.

5) The implant of claim 4 wherein the surface contour of the tip is large enough to spread the axial load on the implant at the second end over a large contact area.

6) The implant of claim 2 further comprising a longitudinal receptor disposed at the tip and configured to capture a fastener to releasably mate the implant to the end portion and fix the bone to the tip.

7) The implant of claim 6 wherein the fastener comprises a bone screw.

8) The implant of claim 6 wherein the longitudinal receptor is further configured to receive a driver configured to facilitate movement of the implant within the intramedullary space.

9) The implant of claim 1 wherein the bone comprises the radius and the fracture is a distal radius fracture.

10) The implant of claim 1 further comprising at least one cross-locking receptor disposed on the second end.

11) The implant of claim 10 wherein the cross locking receptor is directed volarly.

12) The implant of claim 11 wherein the direction is approximately 17 degrees volar.

13) The implant of claim 10 wherein the cross locking receptor is directed dorsally.

14) The implant of claim 13 wherein the direction is approximately 12 degrees.

15) The implant of claim 10 in which said cross locking receptor is angled distally.

16) The implant of claim 10 in which said cross locking receptor is angled proximally.

17) The implant of claim 10 wherein the cross-locking receptor is configured to capture a fastener, the fastener configured to extend through the cross-locking receptor and engage the bone of the second fragment to securely position the implant within the second fragment.

18) The implant of claim 17 in which the cross-locking receptor is threaded and the fastener is threaded to threadably engage the cross-locking receptor.

19) The implant of claim 10 wherein the second end has a receptor configured to receive a driver configured to facilitate insertion of the implant into the intramedullary space.

20) The implant of claim 19 wherein the cross-locking receptor and the receptor configured to receive the driver configured to facilitate insertion of the implant into the intramedullary space are the same.

21) The implant of claim 1 further comprising a receptor for receiving a driver configured to facilitate movement of the implant within the intramedullary space.

22) The implant of claim 21 wherein the implant further comprises a tip at the second end and the receptor is disposed on the tip.

23) The implant of claim 21 wherein the receptor is disposed on the periphery of the second end of the implant.

24) The implant of claim 1 further comprising at least one receptor disposed on a peripheral surface of the first end of the implant, the receptor configured to capture a fastener, said fastener configured to extend through the receptor and

engage the bone of the proximal fragment to securely position the implant within the first fragment.

25) The implant of claim 1 wherein the implant has largely a banana shape.

26) The implant of claim 1 wherein the implant has a largely S shape.

27) The implant of claim 1 wherein the entry point comprises an extended opening from the fracture site.

28) The implant of claim 1 wherein the first end and the second end are formed as a single piece.

29) The implant of claim 1 wherein the first end and the second end are formed separate pieces adjoined together to form a unitary implant.

30) The implant of claim 29 wherein the first end comprises a tongue and the second end comprises a groove configured to receive and capture the tongue of the first end.

31) The implant of claim 29 wherein the first end and the second end are secured together by a fastener.

32) The implant of claim 31 wherein the fastener comprises a screw.

33) The implant of claim 1 wherein the second end further comprises a cannulated receptor extending through the second end and configured to receive a guide wire for facilitating positioning of the implant.

34) A fracture fixation implant for fixation of a broken bone comprising a fracture site, a first and a second fragment on opposing sides of the fracture site, the second fragment comprising an end portion, and an intramedullary space within the bone with portions on opposing sides of the fracture site, the implant comprising:

a first end configured to be placed in the intramedullary space of the first fragment;

a second end configured to be placed in the intramedullary space of the second fragment and configured to abut the end portion of the second fragment to enable axial loading of the implant at the second end.

35) The implant of claim 34 further comprising a form configured to enable placement of the first end into the intramedullary space of the first fragment through an entry point on the bone and further configured to enable displacement of the implant across the fracture site to enable positioning of the second end into the intramedullary space of the second fragment.

36) The implant of claim 34 wherein the implant further comprises a tip at the second end configured to provide support to an axial load on the implant from abutment of the tip against the end portion of the second fragment.

37) The implant of claim 36 wherein the tip resists side-to-side displacement of the second fragment.

38) The implant of claim 36 wherein the end portion has an endosteal surface having a contour and the tip has a contour configured to largely conform to the contour of the endosteal surface.

39) The implant of claim 38 wherein the surface contour of the tip is large enough to spread the axial load on the implant at the second end over a large contact area.

40) The implant of claim 36 further comprising a longitudinal receptor disposed at the tip and configured to capture a fastener to releasably mate the implant to the end portion and fix the end portion to the tip.

41) The implant of claim 40 wherein the fastener comprises a bone screw.

42) The implant of claim 40 further comprising a receptor for receiving a driver configured to facilitate movement of the implant within the intramedullary space wherein the longitudinal receptor and receptor configured to receive the driver are the same.

43) The implant of claim 34 further comprising a receptor on the second end for receiving a driver configured to facilitate movement of the implant within the intramedullary space.

44) The implant of claim 43 wherein the receptor is disposed on the periphery of the second end of the implant.

45) The implant of claim 34 further comprising at least one cross-locking receptor disposed on the second end.

46) The implant of claim 45 in which said cross locking receptor is directed volarly.

47) The implant of claim 46 in which the direction is approximately 17 degrees volar.

48) The implant of claim 45 in which the cross locking receptor is directed dorsally.

49) The implant of claim 48 in which the direction is approximately 12 degrees.

50) The implant of claim 45 in which the cross locking receptor is angled distally.

51) The implant of claim 45 in which the cross locking receptor is angled proximally.

52) The implant of claim 45 wherein the cross-locking receptor is configured to capture a fastener, the fastener configured to extend through the cross-locking receptor and engage the bone of the second fragment to securely position the implant within the second fragment.

53) The implant of claim 52 in which the cross-locking receptor is threaded and the fastener is threaded to threadably engage the cross-locking receptor.

54) The implant of claim 45 wherein the second end has a receptor configured to receive a driver configured to facilitate insertion of the implant into the intramedullary space.

55) The implant of claim 54 wherein the cross-locking receptor and the receptor is configured to receive the driver configured to facilitate insertion of the implant into the intramedullary space are the same.

56) The implant of claim 45 wherein the cross-locking receptor is configured to receive a driver configured to facilitate insertion of the implant into the intramedullary space configured to facilitate longitudinal displacement of the implant within the intramedullary space.

57) The implant of claim 34 further comprising a receptor for receiving a driver configured to facilitate movement of the implant within the intramedullary space.

58) The implant of claim 57 the receptor is disposed on the tip.

59) The implant of claim 34 wherein the first end and the second end are formed as a single piece.

60) The implant of claim 34 wherein the first end and the second end are formed separate pieces adjoined together to form a unitary implant.

61) The implant of claim 60 wherein the first end comprises a tongue and the second end comprises a groove configured to receive and capture the tongue of the first end.

62) The implant of claim 60 wherein the first end and the second end are secured together by a fastener.

63) The implant of claim 62 wherein the fastener comprises a screw.

64) The implant of claim 34 wherein the second end further comprises a cannulated receptor extending through the second end and configured to receive a guide wire for facilitating positioning of the implant.

65) The implant of claim 34 wherein the bone comprises the radius and the fracture is a distal radius fracture.

66) A fracture fixation implant for fixation of a broken bone, the implant comprising a form that enables insertion of the implant in a first direction through an entry point in the bone and a form that further enables displacement of the implant in a second direction, substantially opposite to the first direction to allow bone purchase on both sides of the insertion site.

67) The implant of claim 66 wherein the broken bone comprises a second fragment having an end portion and the implant comprises a tip configured to abut the end portion and enable axial loading of the implant at the tip.

68) The implant of claim 67 wherein the end portion comprises an endosteal surface having a contour and the tip is contoured to largely conform to the contour of the endosteal surface.

69) The implant of claim 67 further comprising a longitudinal receptor disposed at the tip and configured to capture a fastener to releasably mate the implant to the end portion and fix the bone to the tip.

70) The implant of claim 69 wherein the fastener comprises a bone screw.

71) The implant of claim 69 further comprising a receptor for receiving a driver configured to facilitate movement of the implant within the intramedullary space wherein the receptor for longitudinal fixation and the receptor for the driver are the same.

72) The implant of claim 66 wherein the bone comprises the radius and the fracture is a distal radius fracture.

73) The implant of claim 66 further comprising a first and a second end, the first end configured to be positioned in the intramedullary space of a first fragment of the bone and the second fragment configured to be positioned in the intramedullary space of the second fragment of the bone.

74) The implant of claim 67 wherein the tip resists side-to-side displacement of the second fragment.

75) The implant of claim 68 wherein the surface contour of the tip is large enough to spread the axial load on the implant at the second end over a large contact area.

76) A fracture fixation implant for fixation of a broken bone comprising a fracture site, a first and second fragment on opposing sides of the fracture site, the second fragment having an end portion with, and an intramedullary space within the bone with portions on opposing sides of the fracture site, the implant comprising:

a first end configured to be positioned in the intramedullary space of the first fragment;

a second end configured to be positioned in the intramedullary space of the second fragment, second end having a tip configured to abut the end portion of the second fragment and configured to enable axial loading of the implant at the tip; and

a form that enables insertion of the implant in a first direction through an entry point in the bone and a form that further enables displacement of the implant in a second direction, substantially opposite to the first direction to allow bone purchase on both sides of the insertion site.

77) The implant of claim 76 wherein the end portion comprises an endosteal surface having a contour and the tip is contoured to largely conform to the contour of the endosteal surface.

78) The implant of claim 76 further comprising a longitudinal receptor disposed at the tip and configured to capture a fastener to releasably mate the implant to the end portion and fix the bone to the tip.

79) The implant of claim 78 wherein the fastener comprises a bone screw.

80) The implant of claim 78 wherein the longitudinal receptor is further configured to receive a driver configured to facilitate movement of the implant within the intramedullary space.

81) The implant of claim 76 further comprising at least one cross-locking receptor disposed on the second end.

82) The implant of claim 81 wherein the cross locking receptor is directed volarly.

83) The implant of claim 82 wherein the direction is approximately 17 degrees volar.

84) The implant of claim 81 wherein the cross locking receptor is directed dorsally.

85) The implant of claim 84 wherein the direction is approximately 12 degrees.

86) The implant of claim 81 in which said cross locking receptor is angled distally.

87) The implant of claim 81 in which said cross locking receptor is angled proximally.

88) The implant of claim 81 wherein the cross-locking receptor is configured to capture a fastener, the fastener configured to extend through the cross-locking receptor and engage the bone of the second fragment to securely position the implant within the second fragment.

89) The implant of claim 88 in which the cross-locking receptor is threaded and the fastener is threaded to threadably engage the cross-locking receptor.

90) The implant of claim 81 wherein the second end has a receptor configured to receive a driver configured to facilitate insertion of the implant into the intramedullary space.

91) The implant of claim 90 wherein the cross-locking receptor and the receptor configured to receive the driver configured to facilitate insertion of the implant into the intramedullary space are the same.

92) The implant of claim 76 further comprising a receptor for receiving a driver configured to facilitate movement of the implant within the intramedullary space.

93) The implant of claim 92 wherein receptor is disposed on the tip.

94) The implant of claim 92 wherein the receptor is disposed on the periphery of the second end of the implant.

95) The implant of claim 76 further comprising at least one receptor disposed on a peripheral surface of the first end of the implant, the receptor configured to capture a fastener, said fastener configured to extend through the receptor and engage the bone of the proximal fragment to securely position the implant within the first fragment.

96) The implant of claim 76 wherein the implant has largely a banana shape.

97) The implant of claim 76 wherein the implant has a largely S shape.

98) The implant of claim 76 wherein the entry point comprises an extended opening from the fracture site.

99) The implant of claim 76 wherein the first end and the second end are formed as a single piece.

100) The implant of claim 76 wherein the first end and the second end are formed separate pieces adjoined together to form a unitary implant.

101) The implant of claim 100 wherein the first end comprises a tongue and the second end comprises a groove configured to receive and capture the tongue of the first end.

102) The implant of claim 100 wherein the first end and the second end are secured together by a fastener.

103) The implant of claim 102 wherein the fastener comprises a screw.

104) The implant of claim 76 wherein the second end further comprises a cannulated receptor extending through the second end and configured to receive a guide wire for facilitating positioning of the implant.

105) The implant of claim 76 wherein the tip is configured to resist side-to-side displacement of the second fragment.

106) The implant of claim 77 wherein the surface contour of the tip is large enough to spread the axial load on the implant at the second end over a large contact area.

107) A method of fracture fixation for fixation of a broken bone using an intramedullary implant having a first end and a second end, the broken bone comprising a fracture site, a first and second fragment on opposing sides of the fracture site, and an intramedullary space within the bone with portions on opposing sides of the fracture site, the method comprising:

forming a pathway in the intramedullary space of the second fragment to receive the second end of the implant;

inserting the implant into the intramedullary space of the first fragment through an entry point on the bone;

displacing the implant across the fracture site to position the second end of the implant in the intramedullary space of the second fragment;

adjusting the angular positioning of the implant within the second fragment;

affixing the second end to the second fragment;

reducing the fracture; and

affixing the first end to the first fragment.

108) The method of claim 107 wherein the second fragment comprises an end portion with an endosteal surface having a contour.

109) The method of claim 108 further comprising providing the second end of the implant with a tip comprising a contour that largely corresponds to the contour of the endosteal surface and displacing the implant across the fracture site and into the intramedullary space of the second fragment until the tip abuts the endosteal surface.

110) A method of fracture fixation for fixation of a broken bone using an intramedullary implant having a first end and a second end, the broken bone comprising a fracture site, a first and second fragment on opposing sides of the fracture site, and an intramedullary space within the bone with portions on opposing sides of the fracture site, the method comprising:

inserting the implant into the intramedullary space of the first fragment through an entry point on the bone;

providing the implant with an operative surface configured to be engaged by a positioning instrument;

engaging the implant with the positioning instrument;

actuating the positioning instrument; and

displacing the second end of the implant across the fracture site and into the second fragment.

111) The method of claim 110 wherein the operative surface comprises a serrated surface having a plurality of teeth.

112) The method of claim 111 wherein the positioning instrument comprises a ratcheting mechanism transformable between a first, open position and second, closed position, and having a first and second tooth configured to engage the teeth of the serrated surface of the implant.

113) The method of claim 12 further comprising the step of closing the ratcheting mechanism and displacing the second end of the implant across the fracture site and into the second end.

114) The method of claim 110 wherein the operative surface comprises a plurality of ribs configured to be engaged by a positioning instrument.

115) The method of claim 114 wherein the positioning instrument comprises a gear having a plurality of teeth configured to engage the ribs of the implant.

116) The method of claim 115 further comprising the step actuating the positioning instrument, whereby said actuation causes the gear to rotate and displace the second end of the implant into the second fragment.

117) The method of claim 110 further comprising the steps of:

providing the implant with at least a first track;

providing the positioning instrument with at least a first tongue configured to engage the first track on the implant; and

actuating the positioning instrument to cause the first tongue to engage the first track on the implant.

118) A method of fracture fixation for fixation of a broken bone using an intramedullary implant having a first end and a second end, the broken bone comprising a fracture site, a first and second fragment on opposing sides of the fracture site, and an intramedullary space within the bone with portions on opposing sides of the fracture site, the method comprising:

inserting the implant into the intramedullary space of the first fragment through the fracture site;

providing the implant with a receptor configured to receive a displacement means operatively associated with a positioning instrument for displacing the second end of the implant across the fracture site and into the second fragment;

engaging the displacement means and receptor;

actuating the positioning instrument; and

displacing the second end of the implant across the fracture site and into the second fragment.

119) The method of claim 118 wherein the displacement means comprises flexible wire, ribbon or suture.

120) The method of claim 118 further comprising the steps of:

providing the implant with at least a first track extending longitudinally on the periphery of the implant;

providing the positioning instrument with at least a first tongue configured to engage the first track on the implant; and

actuating the positioning instrument to cause the first tongue to engage the first track on the implant.

* * * * *