

(19)



(11)

EP 3 456 802 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

20.03.2019 Bulletin 2019/12

(51) Int Cl.:

C11D 1/83 (2006.01)

C11D 1/94 (2006.01)

C11D 3/00 (2006.01)

C11D 1/14 (2006.01)

C11D 1/29 (2006.01)

C11D 1/75 (2006.01)

C11D 1/88 (2006.01)

(21) Application number: **17191354.4**

(22) Date of filing: **15.09.2017**

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

Designated Extension States:

BA ME

Designated Validation States:

MA MD

(72) Inventors:

- **BILLIAUW, Jan Julien Marie-Louise**
1853 Strombeek-Bever (BE)
- **KROLS, Roel**
1853 Strombeek-Bever (BE)
- **JONES, Christopher Stephen**
1853 Strombeek-Bever (BE)

(71) Applicant: **The Procter & Gamble Company**
Cincinnati, OH 45202 (US)

(74) Representative: **Kellenberger, Jakob**
NV Procter & Gamble
Services Company S.A.
Temseleaan 100
1853 Strombeek-Bever (BE)

(54) **LIQUID HAND DISHWASHING CLEANING COMPOSITION**

(57) The present invention relates to a liquid hand dishwashing cleaning composition including a surfactant system, wherein the surfactant system includes an anionic surfactant and a co-surfactant, wherein the anionic surfactant includes a mixture of a linear anionic surfactant and a branched anionic surfactant with a defined degree of branching on an alkyl ethoxy sulfate surfactant. Such compositions exhibit surprising and unexpected improved sudsing profile, preferably stable suds, especially when the manual dishwashing is performed in a sink full of water with the cleaning composition diluted in it.

EP 3 456 802 A1

Description

FIELD OF THE INVENTION

[0001] The present invention relates to a liquid hand dishwashing cleaning composition comprising a surfactant system comprising an anionic surfactant and a co-surfactant, wherein the anionic surfactant is selected from a mixture of a linear anionic surfactant and a branched anionic surfactant with a defined degree of branching on branched alkyl sulfate surfactant and branched alkyl ethoxy sulfate surfactant. The composition provides good sudsing profile, in particular suds stabilization benefit in the presence of greasy soils. The composition also provides good cleaning of greasy soils.

BACKGROUND OF THE INVENTION

[0002] Traditionally, manual dishwashing is performed in a sink full of water with the cleaning composition diluted in it. Accordingly, with this method of hand dishwashing, the user relies on the sudsing profile as an indicator of the composition's cleaning ability. To qualify a dishwashing detergent as having a good sudsing profile, the generated suds must produce high suds volume and/or longevity (*i.e.*, mileage) of the suds (*i.e.*, stable suds), preferably with sustained suds aesthetics throughout dilution during the wash process (*i.e.*, suds whiteness and consistency) to indicate to the user that sufficient active ingredients (*e.g.*, surfactants) are present to perform the desired cleaning. Previous attempts to improve sudsing profile have not focused on the use of the defined mixture according to the invention of linear and branched anionic surfactant, wherein the branched anionic surfactant comprises a defined branching split between branched alkyl sulfate and branched alkyl ethoxy sulfate anionic surfactant to improve suds generation and/or suds stabilization in the presence of greasy soils.

[0003] Thus, the need remains for a cleaning composition having a good sudsing profile, in particular increased suds volume and/or increased suds stabilization benefits in the presence of greasy soils, particularly through-out the entire manual dishwashing operation. The need also exists for a cleaning composition, particularly a hand dishwashing cleaning composition, that sustains suds aesthetics throughout the dilution and the wash process provides good product dissolution and cleaning, particularly good cleaning of greasy soils. The Applicant has discovered that some or all of the above-mentioned needs can be at least partially fulfilled through cleaning compositions as described herein below.

SUMMARY OF THE INVENTION

[0004] The present invention meets one or more of these needs based on the surprising discovery that by formulating a cleaning composition having a surfactant system comprising an anionic surfactant selected from a mixture of a linear anionic surfactant and a branched anionic surfactant, with a defined degree of branching between a branched alkyl sulfate surfactant and a branched alkyl ethoxy sulfate surfactant, such a composition exhibits good sudsing profile, particularly desirable suds volume and sustained suds stabilization in the presence of greasy soils.

[0005] In one aspect, the present invention is directed to a liquid hand dishwashing comprising from 1% to 60%, preferably from 5% to 50%, more preferably from 8% to 45%, most preferably from 15% to 40%, by weight of the total composition of a surfactant system comprising an anionic surfactant and a co-surfactant. The anionic surfactant has an average alkyl chain length of from 8 to 18, preferably from 10 to 14, more preferably from 12 to 14, most preferably from 12 to 13 carbon atoms. The anionic surfactant has a weight average degree of branching of from 5% to 17%, preferably from 10% to 15%, and an average degree of ethoxylation of less than 5, preferably less than 3, more preferably less than 2 and more than 0.5, most preferably between 0.5 and 0.9. The anionic surfactant comprises an alkyl sulfate, an alkyl alkoxy sulfate preferably an alkyl ethoxy sulfate, or mixtures thereof, preferably the alkyl sulfate, the alkyl alkoxy sulfate preferably the alkyl ethoxy sulfate, or mixtures thereof is a mixture of a linear anionic surfactant and a branched anionic surfactant. The branched anionic surfactant is selected from 5% to 100%, preferably from 10% to 75%, more preferably from 10% to 60%, even more preferably from 12% to 45%, most preferably from 15% to 30%, by weight of the total branched anionic surfactant of a branched alkyl ethoxy sulfate surfactant and from 0% to 95%, preferably from 25% to 90%, more preferably from 40% to 90%, even more preferably from 55% to 88%, most preferably from 70% to 85%, by weight of the total branched anionic surfactant of a branched alkyl sulfate surfactant. The co-surfactant is selected from the group consisting of an amphoteric surfactant, a zwitterionic surfactant and mixtures thereof, preferably an amphoteric surfactant, more preferably an amine oxide surfactant. The weight ratio of the anionic surfactant to the co-surfactant is from 1:1 to 8:1, preferably from 2:1 to 5:1, more preferably from 2.5:1 to 4:1.

[0006] In another aspect, the present invention is directed to a liquid hand dishwashing cleaning composition comprising from 15% to 40% by weight of the total composition of a surfactant system comprising an anionic surfactant, and an amine oxide co-surfactant. The anionic surfactant has a weight average degree of branching of from 10% to 15%, and an average degree of ethoxylation of between 0.5 and 0.9. The anionic surfactant is selected from a mixture of a linear anionic and a branched anionic surfactant. The linear anionic surfactant is a mixture of a linear alkyl sulfate surfactant

and a linear alkyl ethoxy sulfate surfactant. The branched anionic surfactant is a mixture of from 15% to 30% by weight of the total branched anionic surfactant of a branched alkyl ethoxy sulfate surfactant and from 70% to 85% by weight of the total branched anionic surfactant of a branched alkyl sulfate surfactant. The weight ratio of the anionic surfactant to the amine oxide co-surfactant is between 2.5:1 and 4:1.

[0007] According to another aspect of the invention there is provided a method of manually washing dishware using the composition of the invention. The method comprises the steps of: delivering a composition of the invention to a volume of water to form a wash solution and immersing the dishware in the solution.

[0008] There is also provided the use of the composition of the invention for the stabilization of suds in the presence of greasy soils.

[0009] It is an object of the composition of the present invention to exhibit good sudsing profile, preferably high suds volume and sustained suds aesthetics (i.e. whiteness and/or consistency) throughout dilution and the wash process.

[0010] It is an object of the composition of the present invention to exhibit good sudsing profile, preferably stable suds during a substantial portion of or for the entire manual dishwashing process.

[0011] It is an object of the composition to provide good product dissolution and cleaning, preferably good tough food cleaning (e.g., cooked-, baked- and burnt-on soils) and/or good grease cleaning.

[0012] These and other features, aspects and advantages of the present invention will become evident to those skilled in the art from the detailed description which follows.

DETAILED DESCRIPTION OF THE INVENTION

Definitions

[0013] As used herein, articles such as "a" and "an" when used in a claim, are understood to mean one or more of what is claimed or described.

[0014] The term "comprising" as used herein means that steps and ingredients other than those specifically mentioned can be added. This term encompasses the terms "consisting of" and "consisting essentially of." The compositions of the present invention can comprise, consist of, and consist essentially of the essential elements and limitations of the invention described herein, as well as any of the additional or optional ingredients, components, steps, or limitations described herein.

[0015] The term "dishware" as used herein includes cookware and tableware made from, by non-limiting examples, ceramic, china, metal, glass, plastic (e.g., polyethylene, polypropylene, polystyrene, etc.) and wood.

[0016] The term "grease" or "greasy" as used herein means materials comprising at least in part (i.e., at least 0.5 wt% by weight of the grease) saturated and unsaturated fats and oils, preferably oils and fats derived from animal sources such as beef, pig and/or chicken.

[0017] The terms "include", "includes" and "including" are meant to be non-limiting.

[0018] The term "sudsing profile" as used herein refers to the properties of a cleaning composition relating to suds character during the dishwashing process. The term "sudsing profile" of a cleaning composition includes suds volume generated upon dissolving and agitation, typically manual agitation, of the cleaning composition in the aqueous washing solution, and the retention of the suds during the dishwashing process. Preferably, hand dishwashing cleaning compositions characterized as having "good sudsing profile" tend to have high suds volume and/or sustained suds volume, particularly during a substantial portion of or for the entire manual dishwashing process. This is important as the consumer uses high suds as an indicator that sufficient cleaning composition has been dosed. Moreover, the consumer also uses the sustained suds volume as an indicator that sufficient active cleaning ingredients (e.g., surfactants) are present, even towards the end of the dishwashing process. The consumer usually renews the washing solution when the sudsing subsides. Thus, a low sudsing cleaning composition will tend to be replaced by the consumer more frequently than is necessary because of the low sudsing level.

[0019] It is understood that the test methods that are disclosed in the Test Methods Section of the present application must be used to determine the respective values of the parameters of Applicants' inventions as described and claimed herein.

[0020] In all embodiments of the present invention, all percentages are by weight of the total composition, as evident by the context, unless specifically stated otherwise. All ratios are weight ratios, unless specifically stated otherwise, and all measurements are made at 25°C, unless otherwise designated.

Cleaning Composition

[0021] The present invention relates to liquid hand dishwashing cleaning compositions having a good sudsing profile, including high suds volume generation and/or sustained suds stabilization through-out a substantial portion of, or the entire dishwashing process. This signals to the user that there are still sufficient active ingredients present to provide

good cleaning performance, as such triggering less re-dosing and overconsumption of the product by the user.

[0022] The Applicant has surprisingly found that by selecting a surfactant system with the defined degree of branching and branching split sustained suds stabilization and/or high suds volume can be achieved. The results are unexpected since previous attempts to improve sudsing profile have not focused on the use of such branched anionic surfactant systems.

[0023] Furthermore, the compositions of the present invention present good stability due to the compatibility of the surfactant system with the remaining ingredients of the composition. The composition can also be aesthetically pleasant because the presence of the surfactant system does not alter the appearance of the composition, *i.e.*, transparent, translucent, etc. The composition of the present invention can also provide good grease removal, in particular good uncooked grease removal.

[0024] The cleaning composition is a hand dishwashing cleaning composition in liquid form. Preferably, the composition contains from 50% to 85%, preferably from 50% to 75%, by weight of the total composition of a liquid carrier in which the other essential and optional components are dissolved, dispersed or suspended. One preferred component of the liquid carrier is water.

[0025] Preferably, the pH of the composition is from about 6 to about 14, preferably from about 7 to about 12, or more preferably from about 7.5 to about 10, as measured at 10 dilution in distilled water at 20°C. The pH of the composition can be adjusted using pH modifying ingredients known in the art.

[0026] The composition of the present invention can be Newtonian or non-Newtonian, preferably Newtonian. Preferably, the composition has an initial viscosity of from 10 mPa·s to 10,000 mPa·s, preferably from 100 mPa·s to 5,000 mPa·s, more preferably from 300 mPa·s to 2,000 mPa·s, or most preferably from 500 mPa·s to 1,500 mPa·s, alternatively combinations thereof. Viscosity is measured with a Brookfield RT Viscometer using spindle 21 at 20 RPM at 25°C.

[0027] The cleaning composition of the invention is especially suitable for use as a hand dishwashing detergent. Due to its desirable sudsing profile, it is extremely suitable for use in diluted form in a full sink of water to wash dishes.

Surfactant System

[0028] The cleaning composition comprises from 1% to 60%, preferably from 5% to 50%, more preferably from 8% to 45%, most preferably from 15% to 40%, by weight of the total composition of a surfactant system comprising an anionic surfactant and a co-surfactant.

Anionic Surfactant

[0029] Preferably, the surfactant system for the cleaning composition of the present invention comprises from 60% to 90%, preferably from 65% to 85%, more preferably from 70% to 80%, by weight of the surfactant system of an anionic surfactant. The anionic surfactant comprises an alkyl sulfate, an alkyl alkoxy sulfate preferably an alkyl ethoxy sulfate, or mixtures thereof, preferably the alkyl sulfate, the alkyl alkoxy sulfate preferably the alkyl ethoxy sulfate, or mixtures thereof is a mixture of linear anionic surfactant and branched anionic surfactant. The preferred average alkyl chain length of the linear anionic surfactant is from 12 to 14 carbon atoms. Preferably, the surfactant system comprises from 80% to 95%, more preferably from 85% to 95%, by weight of the anionic surfactant of a linear anionic surfactant.

[0030] The branched anionic surfactant is selected from 5% to 100%, preferably from 10% to 75%, more preferably from 10% to 60%, even more preferably from 12% to 45%, most preferably from 15% to 30%, by weight of the total branched anionic surfactant of a branched alkyl ethoxy sulfate surfactant and from 0% to 95%, preferably from 25% to 90%, more preferably from 40% to 90%, even more preferably from 55% to 88%, most preferably from 70% to 85% by weight of the total branched anionic surfactant of a branched alkyl sulfate surfactant. This degree of branching and branching split contributes to enhanced suds longevity of the composition. It also contributes to the stability of the detergent. The preferred average alkyl chain length of the branched anionic surfactant is from 12 to 15, more preferably from 12 to 13 carbons. Preferably, the surfactant system comprises from 5% to 20%, more preferably from 5% to 15%, by weight of the anionic surfactant of a branched anionic surfactant.

[0031] Preferably, the composition of the present invention wherein no further anionic surfactant, other than the alkyl sulfate, the alkyl alkoxy sulfate preferably the alkyl ethoxy sulfate, or mixtures thereof, is added to the composition.

[0032] The weight average degree of branching of the anionic surfactant is from 5% to 17%, preferably from 10% to 15%. The weight average degree of branching for an anionic surfactant mixture is defined according to the following formula:

$$\text{Weight average of branching (\%)} = [(x_1 * \text{wt\% branched alcohol 1 in alcohol 1} + x_2 * \text{wt\% branched alcohol 2 in alcohol 2} + \dots) / (x_1 + x_2 + \dots)] * 100$$

wherein x_1 , x_2 , are the weight in grams of each alcohol in the total alcohol mixture of the alcohols which were used as starting material for the anionic surfactant for the detergent of the invention. In the weight average branching degree calculation, the weight of anionic surfactant components not having branched groups should also be included.

[0033] The average degree of ethoxylation of the anionic surfactant mixture is less than 5, preferably less than 3, more preferably less than 2 and more than 0.5, most preferably between 0.5 and 0.9. The average alkoxylation degree is the mol average alkoxylation degree of all the components of the mixture (*i.e.*, mol average alkoxylation degree) of the anionic surfactant. In the mol average alkoxylation degree calculation the weight of sulfate anionic surfactant components not having alkoxyate groups should also be included.

$$\text{Mol average alkoxylation degree} = (x_1 * \text{alkoxylation degree of surfactant 1} + x_2 * \text{alkoxylation degree of surfactant 2} + \dots) / (x_1 + x_2 + \dots)$$

wherein x_1 , x_2 , ... are the number of moles of each sulfate anionic surfactant of the mixture and alkoxylation degree is the number of alkoxy groups in each sulfate anionic surfactant.

[0034] To define the branching split between branched alkyl sulfate and branched alkyl ethoxy sulfate, the formulator will have to define this based on the formulated molecules within the final formulation rather than the added raw materials. A commercially available branched alkyl ethoxy sulfate raw material will comprise a mixture of linear alkyl sulfate, branched alkyl sulfate, linear alkyl ethoxy sulfate and branched alkyl ethoxy sulfate. Accordingly, the branched alkyl sulfate fraction will have to be considered to calculate the degree of branched alkyl sulfate by weight of the total branched anionic surfactant, while the branched alkyl ethoxy sulfate fraction will have to be considered to calculate the degree of branched alkyl ethoxy sulfate by weight of the total branched anionic surfactant in the final formulation. The actual calculation will have to be executed based on the starting alcohol and ethoxylated alcohols, rather than on the final sulfated materials, as explained in the weight average degree of branching calculation above.

[0035] Suitable counterions include alkali metal cation earth alkali metal cation, alkanolammonium or ammonium or substituted ammonium, but preferably sodium.

[0036] Suitable examples of commercially available sulfates include, those based on Neodol alcohols ex the Shell company, Lial - Isalchem and Safol® ex the Sasol company, natural alcohols ex The Procter & Gamble Chemicals company. The skilled person in the art can create mixtures of these starting materials to achieve the anionic surfactant composition according to the invention, considering the relative fractions of linear alkyl sulfate, linear alkyl ethoxy sulfate, branched alkyl sulfate and branched alkyl ethoxy sulfate, as obtained from the technical data sheets from the relative suppliers or analytically analyzed.

[0037] Preferably, the branched alkyl ethoxy sulfate surfactant of the present invention comprises at least 5%, more preferably at least 10%, by weight of the branched alkyl ethoxy sulfate surfactant of an alkyl ethoxy sulfate surfactant with the branching on the C2 position. Preferably, the branched alkyl ethoxy sulfate surfactant comprises at least 90%, more preferably 100%, by weight of the branched alkyl ethoxy sulfate surfactant of an alkyl ethoxy sulfate surfactant with the branching on the C2 position.

[0038] Preferably, the branched alkyl sulfate surfactant preferably comprises at least 5%, more preferably at least 10%, even more preferably at least 20%, most preferably at least 30%, by weight of the branched alkyl sulfate surfactant of a branched alkyl sulfate surfactant with the branching on the C2 position. Preferably, the branched alkyl sulfate surfactant comprises at least 90%, more preferably 100% by weight of the branched alkyl sulfate surfactant of a branched alkyl sulfate surfactant with the branching on the C2 position.

[0039] The branching group on the branched anionic surfactant is preferably greater than 75%, more preferably greater than 90%, of the total branched alkyl content, of a C1-C5 alkyl moiety, preferably a C1-C2 alkyl moiety.

Co-Surfactant

[0040] The surfactant system of the composition of the present invention comprises a co-surfactant. The composition preferably comprises from 0.1% to 20%, more preferably from 0.5% to 15% and especially from 2% to 10%, by weight of the cleaning composition of the co-surfactant. Preferably, the surfactant system for the cleaning composition of the present invention comprises from 10% to 40%, preferably from 15% to 35%, more preferably from 20% to 30%, by weight of the surfactant system of a co-surfactant. The co-surfactant is selected from the group consisting of an amphoteric surfactant, a zwitterionic surfactant, and mixtures thereof.

[0041] The composition of the present invention will preferably comprise an amine oxide as the amphoteric surfactant. Preferably, the amine oxide surfactant is selected from the group consisting of a linear or branched alkyl amine oxide surfactant, a linear or branched alkyl amidopropyl amine oxide surfactant, and mixtures thereof, more preferably a linear alkyl dimethyl amine oxide surfactant, even more preferably a linear C10 alkyl dimethyl amine oxide surfactant, a linear

C12-C14 alkyl dimethyl amine oxide surfactant, and mixtures thereof, most preferably a linear C12-C14 alkyl dimethyl amine oxide surfactant

[0042] Preferably, the amine oxide surfactant is alkyl dimethyl amine oxide or alkyl amido propyl dimethyl amine oxide, preferably alkyl dimethyl amine oxide and especially coco dimethyl amino oxide, most preferably C12-C14 alkyl dimethyl amine oxide. Typical linear amine oxides include water-soluble amine oxides containing one R1 C8-18 alkyl moiety and 2 R2 and R3 moieties selected from the group consisting of C1-3 alkyl groups and C1-3 hydroxyalkyl groups. Preferably amine oxide is characterized by the formula $R1 - N(R2)(R3)O$ wherein R1 is a C8-18 alkyl and R2 and R3 are selected from the group consisting of methyl, ethyl, propyl, isopropyl, 2-hydroxyethyl, 2-hydroxypropyl and 3-hydroxypropyl. The linear amine oxide surfactants in particular may include linear C10-C18 alkyl dimethyl amine oxides and linear C8-C12 alkoxy ethyl dihydroxy ethyl amine oxides. Preferred amine oxides include linear C10, linear C10-C12, and linear C12-C14 alkyl dimethyl amine oxides. As used herein "mid-branched" means that the amine oxide has one alkyl moiety having n1 carbon atoms with one alkyl branch on the alkyl moiety having n2 carbon atoms. The alkyl branch is located on the α carbon from the nitrogen on the alkyl moiety. This type of branching for the amine oxide is also known in the art as an internal amine oxide. The total sum of n1 and n2 is from 10 to 24 carbon atoms, preferably from 12 to 20, and more preferably from 10 to 16. The number of carbon atoms for the one alkyl moiety (n1) should be approximately the same number of carbon atoms as the one alkyl branch (n2) such that the one alkyl moiety and the one alkyl branch are symmetric. As used herein "symmetric" means that $|n1 - n2|$ is less than or equal to 5, preferably 4, most preferably from 0 to 4 carbon atoms in at least 50 wt%, more preferably at least 75 wt% to 100 wt% of the mid-branched amine oxides for use herein. The amine oxide further comprises two moieties, independently selected from a C1-3 alkyl, a C1-3 hydroxyalkyl group, or a polyethylene oxide group containing an average of from about 1 to about 3 ethylene oxide groups. Preferably, the two moieties are selected from a C1-3 alkyl, more preferably both are selected as a C1 alkyl.

[0043] Alternatively, the amine oxide surfactant is a mixture of amine oxides comprising a low-cut amine oxide and a mid-cut amine oxide. The amine oxide of the composition of the invention then comprises:


a) from about 10% to about 45% by weight of the amine oxide of low-cut amine oxide of formula $R1R2R3AO$ wherein R1 and R2 are independently selected from hydrogen, C1-C4 alkyls or mixtures thereof, and R3 is selected from C10 alkyls or mixtures thereof; and

b) from 55% to 90% by weight of the amine oxide of mid-cut amine oxide of formula $R4R5R6AO$ wherein R4 and R5 are independently selected from hydrogen, C1-C4 alkyls or mixtures thereof, and R6 is selected from C12-C16 alkyls or mixtures thereof

[0044] In a preferred low-cut amine oxide for use herein R3 is n-decyl. In another preferred low-cut amine oxide for use herein R1 and R2 are both methyl. In an especially preferred low-cut amine oxide for use herein R1 and R2 are both methyl and R3 is n-decyl.

[0045] Preferably, the amine oxide comprises less than about 5%, more preferably less than 3%, by weight of the amine oxide of an amine oxide of formula $R7R8R9AO$ wherein R7 and R8 are selected from hydrogen, C1-C4 alkyls and mixtures thereof and wherein R9 is selected from C8 alkyls and mixtures thereof. Compositions comprising $R7R8R9AO$ tend to be unstable and do not provide very suds mileage.

[0046] Preferably, the zwitterionic surfactant is a betaine surfactant. Suitable betaine surfactant includes alkyl betaines, alkylamidobetaine, amidazoliniumbetaine, sulfobetaine (INCI Sultaines) as well as the Phosphobetaine and preferably meets Formula (I):



wherein

R1 is a saturated or unsaturated C6-22 alkyl residue, preferably C8-18 alkyl residue, in particular a saturated C10-16 alkyl residue, for example a saturated C12-14 alkyl residue;

X is NH, NR4 with C1-4 Alkyl residue R4, O or S,

n is a number from 1 to 10, preferably 2 to 5, in particular 3,

x is 0 or 1, preferably 1,

R2 and R3 are independently a C1-4 alkyl residue, potentially hydroxy substituted such as a hydroxyethyl, preferably a methyl,




m is a number from 1 to 4, in particular 1, 2 or 3,

y is 0 or 1, and

Y is COO, SO3, OPO(OR5)O or P(O)(OR5)O, whereby R5 is a hydrogen atom H or a C1-4 alkyl residue.

[0047] Preferred betaines are the alkyl betaines of the Formula (Ia), the alkyl amido propyl betaine of the Formula (Ib),

the Sulfo betaines of the Formula (Ic) and the Amido sulfobetaine of the Formula (Id):



in which R1 as the same meaning as in Formula (I). Particularly preferred betaines are the Carbobetaine [wherein Y=COO-], in particular the Carbobetaine of the Formulae (Ia) and (Ib), more preferred are the Alkylamidobetaine of the Formula (Ib).

[0048] Examples of suitable betaines and sulfobetaine are the following [designated in accordance with INCI]: Almondamidopropyl of betaines, Apricotamidopropyl betaines, Avocadamidopropyl of betaines, Babassuamidopropyl of betaines, Behenamidopropyl betaines, Behenyl of betaines, betaines, Canolamidopropyl betaines, Capryl/Capramidopropyl betaines, Carnitine, Cetyl of betaines, Cocamidodethyl of betaines, Cocamidopropyl betaines, Cocamidopropyl Hydroxysultaine, Coco betaines, Coco Hydroxysultaine, Coco/Oleamidopropyl betaines, Coco Sultaine, Decyl of betaines, Dihydroxyethyl Oleyl Glycinate, Dihydroxyethyl Soy Glycinate, Dihydroxyethyl Stearyl Glycinate, Dihydroxyethyl Tallow Glycinate, Dimethicone Propyl of PG-betaines, Erucamidopropyl Hydroxysultaine, Hydrogenated Tallow of betaines, Isostearamidopropyl betaines, Lauramidopropyl betaines, Lauryl of betaines, Lauryl Hydroxysultaine, Lauryl Sultaine, Milkamidopropyl betaines, Minkamidopropyl of betaines, Myristamidopropyl betaines, Myristyl of betaines, Oleamidopropyl betaines, Oleamidopropyl Hydroxysultaine, Oleyl of betaines, Olivamidopropyl of betaines, Palmamidopropyl betaines, Palm itamidopropyl betaines, Palmitoyl Carnitine, Palm Kernelamidopropyl betaines, Polytetrafluoroethylene Acetoxypropyl of betaines, Ricinoleamidopropyl betaines, Sesamidopropyl betaines, Soyamidopropyl betaines, Stearamidopropyl betaines, Stearyl of betaines, Tallowamidopropyl betaines, Tallowamidopropyl Hydroxysultaine, Tallow of betaines, Tallow Dihydroxyethyl of betaines, Undecylenamidopropyl betaines and Wheat Germamidopropyl betaines.

[0049] A preferred betaine is, for example, cocoamidopropylbetaine.

Non-Ionic Surfactant

[0050] Preferably, the surfactant system of the composition of the present invention further comprises from 1% to 25%, preferably from 1.25% to 20%, more preferably from 1.5% to 15%, most preferably from 1.5% to 5%, by weight of the surfactant system, of a non-ionic surfactant. Preferably, the non-ionic surfactant is a linear or branched, primary or secondary alkyl alkoxylated non-ionic surfactant, preferably an alkyl ethoxylated non-ionic surfactant, preferably comprising on average from 9 to 15, preferably from 10 to 14 carbon atoms in its alkyl chain and on average from 5 to 12, preferably from 6 to 10, most preferably from 7 to 8, units of ethylene oxide per mole of alcohol.

Alkyl Polyglucoside Surfactant

[0051] Preferably, the composition of the present invention further comprises from 0.5% to 20%, more preferably from 0.75% to 15%, more preferably from 1% to 10%, most preferably from 1% to 5% by weight of the surfactant system of alkyl polyglucoside ("APG") surfactant. Preferably the alkyl polyglucoside surfactant is a C8-C16 alkyl polyglucoside surfactant, preferably a C8-C14 alkyl polyglucoside surfactant, preferably with an average degree of polymerization of between 0.1 and 3, more preferably between 0.5 and 2.5, even more preferably between 1 and 2. Most preferably the alkyl polyglucoside surfactant has an average alkyl carbon chain length between 10 and 16, preferably between 10 and 14, most preferably between 12 and 14, with an average degree of polymerization of between 0.5 and 2.5 preferably between 1 and 2, most preferably between 1.2 and 1.6. C8-C16 alkyl polyglucosides are commercially available from several suppliers (e.g., Simusol® surfactants from Seppic Corporation; and Glucopon® 600 CSUP, Glucopon® 650 EC, Glucopon® 600 CSUP/MB, and Glucopon® 650 EC/MB, from BASF Corporation).

[0052] Preferably, when comprising alkyl polyglucoside surfactant, the composition of the present invention wherein composition comprises a surfactant system comprising:

- i) from 70% to 80% by weight of the surfactant system of an alkoxy ethoxy sulfate surfactant;
- ii) from 18% to 26% by weight of the surfactant system of an amine oxide surfactant; and
- iii) from 1 % to 5% by weight of the surfactant system of an alkyl polyglucoside surfactant.

Amphiphilic Polymer

[0053] The composition of the present invention may further comprise from about 0.01% to about 5%, preferably from about 0.05% to about 2%, more preferably from about 0.07% to about 1% by weight of the total composition of an amphiphilic polymer selected from the groups consisting of amphiphilic alkoxyated polyalkyleneimine and mixtures thereof, preferably an amphiphilic alkoxyated polyalkyleneimine.


[0054] Preferably, the amphiphilic alkoxyated polyalkyleneimine is an alkoxyated polyethyleneimine polymer comprising a polyethyleneimine backbone having average molecular weight range from 100 to 5,000, preferably from 400 to 2,000, more preferably from 400 to 1,000 Daltons and the alkoxyated polyethyleneimine polymer further comprising:

- (i) one or two alkoxylation modifications per nitrogen atom by a polyalkoxylene chain having an average of about 1 to about 50 alkoxy moieties per modification, wherein the terminal alkoxy moiety of the alkoxylation modification is capped with hydrogen, a C1-C4 alkyl or mixtures thereof;
- (ii) an addition of one C1-C4 alkyl moiety and one or two alkoxylation modifications per nitrogen atom by a polyalkoxylene chain having an average of about 1 to about 50 alkoxy moieties per modification wherein the terminal alkoxy moiety is capped with hydrogen, a C1-C4 alkyl or mixtures thereof; or
- (iii) a combination thereof; and


wherein the alkoxy moieties comprises ethoxy (EO) and/or propoxy (PO) and/or butoxy (BO) and wherein when the alkoxylation modification comprises EO it also comprises PO or BO.

[0055] Preferred amphiphilic alkoxyated polyethyleneimine polymers comprise EO and PO groups within their alkoxylation chains, the PO groups preferably being in terminal position of the alkoxy chains, and the alkoxylation chains preferably being hydrogen capped. Hydrophilic alkoxyated polyethyleneimine polymers solely comprising ethoxy (EO) units within the alkoxylation chain could also optionally be formulated within the scope of this invention.

[0056] For example, but not limited to, below is shown possible modifications to terminal nitrogen atoms in the polyethyleneimine backbone where R represents an ethylene spacer and E represents a C1-C4 alkyl moiety and X- represents a suitable water soluble counterion.



[0057] Also, for example, but not limited to, below is shown possible modifications to internal nitrogen atoms in the polyethyleneimine backbone where R represents an ethylene spacer and E represents a C₁-C₄ alkyl moiety and X- represents a suitable water soluble counterion.




[0058] The alkoxylation modification of the polyethyleneimine backbone consists of the replacement of a hydrogen atom by a polyalkoxylene chain having an average of about 1 to about 50 alkoxy moieties, preferably from about 20 to about 45 alkoxy moieties, most preferably from about 30 to about 45 alkoxy moieties. The alkoxy moieties are selected from ethoxy (EO), propoxy (PO), butoxy (BO), and mixtures thereof. Alkoxy moieties solely comprising ethoxy units are outside the scope of the invention though. Preferably, the polyalkoxylene chain is selected from ethoxy/propoxy block moieties. More preferably, the polyalkoxylene chain is ethoxy/propoxy block moieties having an average degree of ethoxylation from about 3 to about 30 and an average degree of propoxylation from about 1 to about 20, more preferably ethoxy/propoxy block moieties having an average degree of ethoxylation from about 20 to about 30 and an average degree of propoxylation from about 10 to about 20.

[0059] More preferably the ethoxy/propoxy block moieties have a relative ethoxy to propoxy unit ratio between 3 to 1

and 1 to 1, preferably between 2 to 1 and 1 to 1. Most preferably the polyalkoxy chain is the ethoxy/propoxy block moieties wherein the propoxy moiety block is the terminal alkoxy moiety block.

[0060] The modification may result in permanent quaternization of the polyethyleneimine backbone nitrogen atoms. The degree of permanent quaternization may be from 0% to about 30% of the polyethyleneimine backbone nitrogen atoms. It is preferred to have less than 30% of the polyethyleneimine backbone nitrogen atoms permanently quaternized. Most preferably the degree of quaternization is about 0%.

[0061] A preferred polyethyleneimine has the general structure of Formula (II):



wherein the polyethyleneimine backbone has a weight average molecular weight of about 600, n of formula (II) has an average of about 10, m of formula (II) has an average of about 7 and R of formula (II) is selected from hydrogen, a C₁-C₄ alkyl and mixtures thereof, preferably hydrogen. The degree of permanent quaternization of formula (II) may be from 0% to about 22% of the polyethyleneimine backbone nitrogen atoms. The molecular weight of this polyethyleneimine preferably is between 10,000 and 15,000.

[0062] An alternative polyethyleneimine has the general structure of Formula (II) but wherein the polyethyleneimine backbone has a weight average molecular weight of about 600, n of Formula (II) has an average of about 24, m of Formula (II) has an average of about 16 and R of Formula (II) is selected from hydrogen, a C₁-C₄ alkyl and mixtures thereof, preferably hydrogen. The degree of permanent quaternization of Formula (II) may be from 0% to about 22% of the polyethyleneimine backbone nitrogen atoms. The molecular weight of this polyethyleneimine preferably is between 25,000 and 30,000.


[0063] Most preferred polyethyleneimine has the general structure of Formula (II) wherein the polyethyleneimine backbone has a weight average molecular weight of about 600, n of Formula (II) has an average of about 24, m of Formula (II) has an average of about 16 and R of Formula (II) is hydrogen. The degree of permanent quaternization of Formula (II) is 0% of the polyethyleneimine backbone nitrogen atoms. The molecular weight of this polyethyleneimine preferably is about from about 25,000 to 30,000, most preferably about 28,000.

[0064] These polyethyleneimines can be prepared, for example, by polymerizing ethyleneimine in the presence of a catalyst such as carbon dioxide, sodium bisulfite, sulfuric acid, hydrogen peroxide, hydrochloric acid, acetic acid, and the like, as described in more detail in PCT Publication No. WO 2007/135645.

Cyclic Polyamine

[0065] The cyclic polyamine of the invention is a cleaning polyamine. The cleaning polyamine comprises amine functionalities that helps cleaning as part of a cleaning composition. The composition of the invention preferably comprises from about 0.1 % to about 10%, more preferably from about 0.2% to about 5%, and especially from about 0.3% to about 2%, by weight of the composition, of the cyclic polyamine.

[0066] The term "cyclic amine" herein encompasses a single amine and a mixture thereof. The amine can be subjected to protonation depending on the pH of the cleaning medium in which it is used. The cyclic polyamine of the invention conforms to the following Formula (I):



(I)

wherein R_1 , R_2 , R_3 , R_4 and R_5 are independently selected from the group consisting of NH_2 , $-\text{H}$, linear or branched alkyl having from 1 to 10 carbon atoms, and linear or branched alkenyl having from 1 to 10 carbon atoms, n is from 0 to 3, preferably n is 1, and wherein at least one of the R s is NH_2 and the remaining " R s" are independently selected from the group consisting of NH_2 , $-\text{H}$, linear or branched alkyl having 1 to 10 carbon atoms, and linear or branched alkenyl having from 1 to 10 carbon atoms. Preferably, the cyclic polyamine is a diamine, wherein n is 1, R_2 is NH_2 , and at least one of R_1 , R_3 , R_4 and R_5 is CH_3 and the remaining R s are H .

[0067] The amine of the invention is a cyclic amine with at least two primary amine functionalities. The primary amines can be in any position in the cyclic amine but it has been found that in terms of grease cleaning, better performance is obtained when the primary amines are in positions 1,3. It has also been found that cyclic amines in which one of the substituents is $-\text{CH}_3$ and the rest are H provided for improved grease cleaning performance.

[0068] Accordingly, the most preferred cyclic polyamine for use with the cleaning composition of the present invention are cyclic polyamine selected from the group consisting of 2-methylcyclohexane-1,3-diamine, 4-methylcyclohexane-1,3-diamine and mixtures thereof. The inventors have surprisingly found that these specific cyclic polyamine works to improve suds profile through-out the dishwashing process when formulated together with the specific surfactant system according to the present invention.

[0069] The composition of the present invention may comprise at least one active selected from the group consisting of: i) a salt, ii) a hydrotrope, iii) an organic solvent, and mixtures thereof.

Salt

[0070] The composition of the present invention may comprise from about 0.05% to about 2%, preferably from about 0.1% to about 1.5%, or more preferably from about 0.5% to about 1%, by weight of the total composition of a salt, preferably a monovalent, divalent inorganic salt or a mixture thereof, more preferably sodium chloride, sodium sulfate or a mixture thereof, most preferably sodium chloride.

Hydrotrope

[0071] The composition of the present invention may comprise from about 0.1 % to about 10%, or preferably from about 0.5% to about 10%, or more preferably from about 1% to about 10% by weight of the total composition of a hydrotrope or a mixture thereof, preferably sodium cumene sulfonate.

Organic Solvent

[0072] The composition of the present invention may comprise an organic solvent. Suitable organic solvents include C4-14 ethers and diethers, polyols, glycols, alkoxyated glycols, C6-C16 glycol ethers, alkoxyated aromatic alcohols, aromatic alcohols, aliphatic linear or branched alcohols, alkoxyated aliphatic linear or branched alcohols, alkoxyated C1-C5 alcohols, C8-C14 alkyl and cycloalkyl hydrocarbons and haloalkyl hydrocarbons, and mixtures thereof. Preferably the organic solvents include alcohols, glycols, and glycol ethers, alternatively alcohols and glycols. The composition comprises from 0% to less than about 50%, preferably from about 0.01% to about 25%, more preferably from about 0.1% to about 10%, or most preferably from about 0.5% to about 5%, by weight of the total composition of an organic solvent, preferably an alcohol, more preferably ethanol, a polyalkyleneglycol, more preferably polypropyleneglycol, and mixtures thereof.

Adjunct Ingredients

[0073] The cleaning composition herein may optionally comprise a number of other adjunct ingredients such as builders (e.g., preferably citrate), chelants, conditioning polymers, cleaning polymers, surface modifying polymers, soil flocculating polymers, structurants, emollients, humectants, skin rejuvenating actives, enzymes, carboxylic acids, scrubbing particles, bleach and bleach activators, perfumes, malodor control agents, pigments, dyes, opacifiers, beads, pearlescent particles, microcapsules, inorganic cations such as alkaline earth metals such as Ca/Mg-ions, antibacterial agents, preservatives, viscosity adjusters (e.g., salt such as NaCl, and other mono-, di- and trivalent salts) and pH adjusters and buffering means (e.g. carboxylic acids such as citric acid, HCl, NaOH, KOH, alkanolamines, phosphoric and sulfonic acids, carbonates such as sodium carbonates, bicarbonates, sesquicarbonates, borates, silicates, phosphates, imidazole and alike).

[0074] The elements of the composition of the invention described in connexion with the first aspect of the invention apply *mutatis mutandis* to the other aspects of the invention.

Method of Washing

[0075] In another aspect, the invention is directed to a method of manually washing dishware with the composition of the present invention. The method comprises the steps of delivering a composition of the present invention to a volume of water to form a wash solution and immersing the dishware in the solution. The dishware can be cleaned with the composition in the presence of water. Optionally, the dishware can be rinsed. By "rinsing", it is meant herein contacting the dishware cleaned with the process according to the present invention with substantial quantities of appropriate solvent, typically water. By "substantial quantities", it is meant usually about 1 to about 20 L.

[0076] The composition herein can be applied in its diluted form. Soiled dishware are contacted with an effective amount, typically from about 0.5 mL to about 20 mL (per about 25 dishes being treated), preferably from about 3 mL to about 10 mL, of the cleaning composition, preferably in liquid form, of the present invention diluted in water. The actual amount of cleaning composition used will be based on the judgment of the user, and will typically depend upon factors such as the particular product formulation of the cleaning composition, including the concentration of active ingredients in the cleaning composition, the number of soiled dishes to be cleaned, the degree of soiling on the dishes, and the like. Generally, from about 0.01 mL to about 150 mL, preferably from about 3 mL to about 40 mL of a cleaning composition of the invention is combined with from about 2,000 mL to about 20,000 mL, more typically from about 5,000 mL to about 15,000 mL of water in a sink having a volumetric capacity in the range of from about 1,000 mL to about 20,000 mL, more typically from about 5,000 mL to about 15,000 mL. The soiled dishware are immersed in the sink containing the diluted cleaning compositions then obtained, where contacting the soiled surface of the dishware with a cloth, sponge, or similar cleaning implement cleans them. The cloth, sponge, or similar cleaning implement may be immersed in the cleaning composition and water mixture prior to being contacted with the dishware, and is typically contacted with the dishware for a period of time ranged from about 1 to about 10 seconds, although the actual time will vary with each application and user. The contacting of cloth, sponge, or similar cleaning implement to the dishware is preferably accompanied by a concurrent scrubbing of the dishware.

[0077] Another aspect of the present invention is directed to use of a hand dishwashing cleaning composition of the present invention for providing good sudsing profile, including suds stabilization in the presence of greasy soils.

TEST METHODS

[0078] The following assays set forth must be used in order that the invention described and claimed herein may be more fully understood.

Test Method 1: Suds Mileage Index

[0079] The objective of the Suds Mileage Index test is to compare the evolution over time of suds volume generated for different test formulations at specified water hardness, solution temperatures and formulation concentrations, while under the influence of periodic soil injections. Data are compared and expressed versus a reference composition as a suds mileage index (reference composition has suds mileage index of 100). The steps of the method are as follows:

1. A defined amount of a test composition, depending on the targeted composition concentration (here : 0.24 wt%), is dispensed through a plastic pipette at a flow rate of 0.67 mL/ sec at a height of 37 cm above the bottom surface of a sink (dimension: 300 mm diameter and 288 mm height) into a water stream (here : water hardness: 15 gpg, water temperature : 35°C) that is filling up the sink to 4 L with a constant pressure of 4 bar.
2. An initial suds volume generated (measured as average foam height X sink surface area and expressed in cm³)

EP 3 456 802 A1

is recorded immediately after end of filling.

3. A fixed amount (6 mL) of soil is immediately injected into the middle of the sink.

4. The resultant solution is mixed with a metal blade (10 cm x 5 cm) positioned in the middle of the sink at the air liquid interface under an angle of 45 degrees rotating at 85 RPM for 20 revolutions.

5. Another measurement of the total suds volume is recorded immediately after end of blade rotation.

6. Steps 3-5 are repeated until the measured total suds volume reaches a minimum level of 400 cm³. The amount of added soil that is needed to get to the 400 cm³ level is considered as the suds mileage for the test composition.

7. Each test composition is tested 4 times per testing condition (i.e., water temperature, composition concentration, water hardness, soil type).

8. The average suds mileage is calculated as the average of the 4 replicates for each sample.

9. Calculate a Suds Mileage Index by comparing the average mileage of a test composition sample versus a reference composition sample. The calculation is as follows:

$$\text{Suds Mileage Index} = \frac{\text{Average number of soil additions of test composition}}{\text{Average number of soil additions of reference composition}} \times 100$$

[0080] Soil composition is produced through standard mixing of the components described in Table 1.

Table 1: Greasy Soil

Ingredient	Weight %
Crisco Oil	12.730
Crisco shortening	27.752
Lard	7.638
Refined Rendered Edible Beef Tallow	51.684
Oleic Acid, 90% (Techn)	0.139
Palmitic Acid, 99+%	0.036
Stearic Acid, 99+%	0.021

EXAMPLE

[0081] The following examples are provided to further illustrate the present invention and are not to be construed as limitations of the present invention, as many variations of the present invention are possible without departing from its spirit or scope.

Example 1: Inventive and Comparative Compositions

[0082] The ability of a cleaning composition to maintain its suds mileage is assessed for a cleaning composition comprising an average degree of branching (15%) and a branched AES over branched AS ratio (16/84) according to the invention (Inventive Composition 1). In parallel, Comparative Composition 1 having a branched AES over branched AS ratio (0/100) or Comparative Composition 2 having an average degree of branching (45%) outside the scope of the present invention are also assessed. The foregoing compositions are produced through standard mixing of the components described in Table 2.

Table 2 - Inventive and Comparative Compositions

	Inventive Composition 1	Comparative Composition 1	Comparative Composition 2
AE0.6S	14.35%	14.35%	14.35%
C12-14 Dimethyl Amine Oxide	3.59%	3.59%	3.59%
NaCl	0.70%	0.70%	0.70%

(continued)

	Inventive Composition 1	Comparative Composition 1	Comparative Composition 2
Polypropylene Glycol (MW 2000)	0.70%	0.70%	0.70%
Ethanol	2.00%	2.00%	2.00%
Sodium Citrate	0.50%	0.50%	0.50%
HCl (pH adjust)	To pH=9.0	To pH=9.0	To pH=9.0
Water + Minor ingredients (perfume, dye, preservatives)	Balance to 100%	Balance to 100%	Balance to 100%
pH (at 10% product concentration in demineralized water)	9.04	8.96	8.97
AES : starting alcohol blend composition	16.5% Natural AE3 16.7% Neodol 23 AE2 66.8% Neodol 23 A	29.6% Natural AE3 43.1% Natural A 27.3% Lial 123 A	21.0% Natural AE3 11.0% Isalchem 123 AE2 7.0% Natural A 30.0% Neodol 23 A 31.0% Isalchem 123 A
Avg. degree of branching	15%	15%	45%
Branched AES - Branched AS ratio	16/84	0/100	18/82

Example 1a: Suds Mileage Index of Inventive and Comparative Compositions

[0083] The resultant compositions including the Inventive Composition 1 and Comparative Compositions 1-2 are assessed according to the Suds Mileage Index test method as described herein. The Suds Mileage Index results of the test are summarized in Table 3. The higher the Suds Mileage Index value, the better in maintain suds mileage. The data shows that the inventive composition (Inventive Composition 1) according to the invention has a stronger suds robustness in the presence of greasy soils compared to comparative compositions (Comparative Composition 1 & 2) outside the scope of the invention.

Table 3 - Suds Mileage Index Results

	Inventive Composition 1	Comparative Composition 1	Comparative Composition 2
Avg. degree of branching	15%	15%	45%
Branched AES - Branched AS ratio	16/84	0/100	18/82
Suds mileage index	100	96.6	97.3

[0084] The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Claims

1. A liquid hand dishwashing cleaning composition comprising:

A) from 1% to 60%, preferably from 5% to 50%, more preferably from 8% to 45%, most preferably from 15%

to 40%, by weight of the total composition of a surfactant system comprising an anionic surfactant and a co-surfactant, wherein:

(i) the average alkyl chain length of the anionic surfactant is from 8 to 18, preferably from 10 to 14, more preferably from 12 to 14, most preferably from 12 to 13 carbon atoms;

(ii) the anionic surfactant has a weight average degree of branching of from 5% to 17%, preferably from 10% to 15%, and an average degree of ethoxylation of less than 5, preferably less than 3, more preferably less than 2 and more than 0.5, most preferably between 0.5 and 0.9;

(iii) the anionic surfactant comprises an alkyl sulfate, an alkyl alkoxy sulfate preferably an alkyl ethoxy sulfate, or mixtures thereof, preferably the alkyl sulfate, the alkyl alkoxy sulfate preferably the alkyl ethoxy sulfate, or mixtures thereof is a mixture of linear anionic surfactant and branched anionic surfactant, wherein:

a. the branched anionic surfactant is selected from 5% to 100%, preferably from 10% to 75%, more preferably from 10% to 60%, even more preferably from 12% to 45%, most preferably from 15% to 30% by weight of the total branched anionic surfactant of a branched alkyl ethoxy sulfate surfactant and from 0% to 95%, preferably from 25% to 90%, more preferably from 40% to 90%, even more preferably from 55% to 88%, most preferably from 70% to 85%, by weight of the total branched anionic surfactant of a branched alkyl sulfate surfactant; and

(iv) the co-surfactant is selected from the group consisting of an amphoteric surfactant, a zwitterionic surfactant and mixtures thereof, preferably an amphoteric surfactant, more preferably an amine oxide surfactant;

wherein the weight ratio of the anionic surfactant to the co-surfactant is from 1:1 to 8:1, preferably from 2:1 to 5:1, more preferably from 2.5:1 to 4:1.

2. The composition according to claim 1, wherein the branched alkyl ethoxy sulfate surfactant comprises at least 5%, preferably at least 10%, by weight of the branched alkyl ethoxy sulfate surfactant of an alkyl ethoxy sulfate surfactant with the branching on the C2 position.

3. The composition according to any of the preceding claims, wherein the branched alkyl sulfate surfactant comprises at least 5%, preferably at least 10%, more preferably at least 20%, even more preferably at least 30%, by weight of the branched alkyl sulfate surfactant of a branched alkyl sulfate surfactant with the branching on the C2 position.

4. The composition according to any of the preceding claims, wherein the branching group on the branched anionic surfactant is preferably greater than 75%, more preferably greater than 90%, by weight of the total branched alkyl content, of a C1-C5 alkyl moiety, preferably a C1-C2 alkyl moiety.

5. The composition according to any of the preceding claims, wherein no further anionic surfactant, other than the alkyl sulfate, the alkyl alkoxy sulfate preferably the alkyl ethoxy sulfate, or mixtures thereof, is added to the composition.

6. The composition according to any of the preceding claims, wherein the amine oxide surfactant is selected from the group consisting of a linear or branched alkyl amine oxide surfactant, a linear or branched alkyl amidopropyl amine oxide surfactant, and mixtures thereof, preferably a linear alkyl dimethyl amine oxide surfactant, more preferably a linear C10 alkyl dimethyl amine oxide surfactant, a linear C12-C14 alkyl dimethyl amine oxide surfactant, and mixtures thereof, most preferably a linear C12-C14 alkyl dimethyl amine oxide surfactant.

7. The composition according to any of the preceding claims, further comprising from 1% to 25%, preferably from 1.25% to 20%, more preferably from 1.5% to 15%, most preferably from 1.5% to 5%, by weight of the surfactant system of a non-ionic surfactant, preferably an alkyl ethoxylated non-ionic surfactant, preferably comprising on average from 9 to 15, preferably from 10 to 14, carbon atoms in its alkyl chain and on average from 5 to 12, preferably from 6 to 10, most preferably from 7 to 8, units of ethylene oxide per mole of alcohol.


8. The composition according to any of the preceding claims, further comprising from 0.5% to 20%, preferably from 0.75% to 15%, more preferably from 1% to 10%, most preferably from 1% to 5% by weight of the surfactant system of an alkyl polyglucoside surfactant, wherein the alkyl polyglucoside surfactant is a C8-C16 alkyl polyglucoside surfactant, preferably a C8-C14 alkyl polyglucoside surfactant, preferably with an average degree of polymerization of between 0.1 and 3, preferably between 0.5 and 2.5, preferably between 1 and 2.

9. The composition according to any of the preceding claims, further comprising from 0.05% to 2% by weight of the total composition of an amphiphilic alkoxyated polyalkyleneimine and mixtures thereof, wherein the amphiphilic alkoxyated polyalkyleneimine is an alkoxyated polyethyleneimine polymer comprising a polyethyleneimine backbone having average molecular weight range from 100 to 5,000, preferably from 400 to 2,000, more preferably from 400 to 1,000 Daltons and the alkoxyated polyethyleneimine polymer further comprising:

- i) one or two alkoxylation modifications per nitrogen atom by a polyalkoxyene chain having an average of about 1 to about 50 alkoxy moieties per modification, wherein the terminal alkoxy moiety of the alkoxylation modification is capped with hydrogen, a C1-C4 alkyl or mixtures thereof;
- ii) an addition of one C1-C4 alkyl moiety and one or two alkoxylation modifications per nitrogen atom by a polyalkoxyene chain having an average of about 1 to about 50 alkoxy moieties per modification wherein the terminal alkoxy moiety is capped with hydrogen, a C1-C4 alkyl or mixtures thereof; or
- iii) a combination thereof; and

wherein the alkoxy moieties comprises ethoxy (EO) and/or propoxy (PO) and/or butoxy (BO) and wherein when the alkoxylation modification comprises EO it also comprises PO or BO.

10. The composition according to any of the preceding claims, further comprising a cyclic polyamine of Formula (I):



(I)

wherein R_1 , R_2 , R_3 , R_4 and R_5 are independently selected from the group consisting of NH_2 , -H, linear or branched alkyl having from 1 to 10 carbon atoms, and linear or branched alkenyl having from 1 to 10 carbon atoms, n is from 0 to 3, preferably n is 1, and wherein at least one of the R_s is NH_2 and the remaining R_s are independently selected from the group consisting of NH_2 , -H, linear or branched alkyl having 1 to 10 carbon atoms, and linear or branched alkenyl having from 1 to 10 carbon atoms; preferably wherein the cyclic polyamine is a diamine, wherein n is 1, R_2 is NH_2 and at least one of R_1 , R_3 , R_4 and R_5 is CH_3 and the remaining R_s are H, most preferably wherein the cyclic polyamine is selected from the group consisting of 2-methylcyclohexane-1,3-diamine, 4-methylcyclohexane-1,3-diamine and mixtures thereof.

11. The composition according to any of the preceding claims, further comprising at least one active selected from the group consisting of:

- (i) from 0.05% to 2%, preferably from 0.1% to 1.5%, more preferably from 0.5% to 1%, by weight of the total composition of a salt, preferably a monovalent, divalent inorganic salt or a mixture thereof, more preferably sodium chloride, sodium sulphate or a mixture thereof, most preferably sodium chloride;
- (ii) from 1% to 10% by weight of the total composition of a hydrotrope, preferably sodium cumene sulfonate;
- (iii) from 0.01% to 25% by weight of the total composition of an organic solvent, preferably an alcohol, more preferably ethanol, a polyalkyleneglycol, more preferably polypropyleneglycol; and
- (iv) mixtures thereof.

12. The composition according to any of the preceding claims, wherein the composition has an initial viscosity of from 10 mPa·s to 10,000 mPa·s, preferably from 100 mPa·s to 5,000 mPa·s, more preferably from 300 mPa·s to 2,000 mPa·s, most preferably from 500 mPa·s to 1,500 mPa·s, as measured on a Brookfield RVT Viscometer using spindle 21 at 20 RPM at 25°C.

13. A liquid hand dishwashing cleaning composition comprising:

A) from 15% to 40% by weight of the total composition of a surfactant system comprising an anionic surfactant and an amine oxide co-surfactant, wherein:

- i) the anionic surfactant has a weight average degree of branching of from 10% to 15% and an average degree of ethoxylation of between 0.5 and 0.9;
- ii) the anionic surfactant and amine oxide co-surfactant are in weight ratio of between 2.5: and 4:1; and
- iii) the anionic surfactant is selected from a mixture of a linear anionic surfactant and a branched anionic surfactant, wherein:

- a. the linear anionic surfactant is a mixture of a linear alkyl sulfate and a linear alkyl ethoxy sulfate; and
- b. the branched anionic surfactant is a mixture of from 15% to 30% by weight of the total branched anionic surfactant of a branched alkyl ethoxy sulfate surfactant and from 70% to 85% by weight of the total branched anionic surfactant of a branched alkyl sulfate surfactant.

14. A method of manually washing dishware comprising the steps of: delivering a composition according to any of claims 1 to 13 to a volume of water to form a wash solution and immersing the dishware in the solution.

15. Use of a composition according to any of claims 1 to 13 for the stabilization of suds in the presence of greasy soils.



EUROPEAN SEARCH REPORT

 Application Number
 EP 17 19 1354

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 2 757 144 A1 (PROCTER & GAMBLE [US]) 23 July 2014 (2014-07-23) * paragraphs [0001], [0006] * * examples * * claims *	1-15	INV. C11D1/83 C11D1/94 C11D3/00
X	EP 2 264 136 A1 (PROCTER & GAMBLE [US]) 22 December 2010 (2010-12-22) * paragraphs [0001], [0008] * * examples 1, 4, 7, 9, 11, 16, 18 * * claims *	1-15	ADD. C11D1/14 C11D1/29 C11D1/75 C11D1/88
X	WO 2017/079960 A1 (PROCTER & GAMBLE [US]) 18 May 2017 (2017-05-18) * page 4, lines 18-22 * * page 13, paragraph 2 * * example 5 * * claims *	1-15	
X	WO 02/44312 A2 (PROCTER & GAMBLE [US]) 6 June 2002 (2002-06-06) * page 2, paragraph 3 * * example 1 * * claims *	1-7, 11-14	TECHNICAL FIELDS SEARCHED (IPC) C11D
X	WO 99/19440 A1 (PROCTER & GAMBLE [US]) 22 April 1999 (1999-04-22) * page 3, paragraph 2 - page 4, paragraph 1 * * example VIII; table VIII * * claims *	1-15	
X	WO 97/39089 A1 (PROCTER & GAMBLE [US]) 23 October 1997 (1997-10-23) * page 91; examples 10, 11, 14 * ----- -/--	1-5,11, 12	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 15 March 2018	Examiner Bertran Nadal, Josep
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)



EUROPEAN SEARCH REPORT

Application Number
EP 17 19 1354

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
E	EP 3 243 895 A1 (PROCTER & GAMBLE [US]) 15 November 2017 (2017-11-15) * paragraph [0005] * * examples * * claims *	1-7, 11-14	
E	WO 2018/017335 A1 (PROCTER & GAMBLE [US]) 25 January 2018 (2018-01-25) * page 1, line 18 - page 2, line 9 * * examples * * claims *	1-6, 11-14	
			TECHNICAL FIELDS SEARCHED (IPC)
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 15 March 2018	Examiner Bertran Nadal, Josep
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 17 19 1354

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-03-2018

10

15

20

25

30

35

40

45

50

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
EP 2757144	A1	23-07-2014	AR	094539 A1	12-08-2015
			CA	2898826 A1	24-07-2014
			CN	104937089 A	23-09-2015
			EP	2757144 A1	23-07-2014
			JP	2016503124 A	01-02-2016
			RU	2015124374 A	22-02-2017
			US	2014221266 A1	07-08-2014
			WO	2014113560 A1	24-07-2014

EP 2264136	A1	22-12-2010	CA	2765952 A1	23-12-2010
			EP	2264136 A1	22-12-2010
			ES	2412684 T3	12-07-2013
			JP	5926330 B2	25-05-2016
			JP	2012530183 A	29-11-2012
			JP	2014196514 A	16-10-2014
			MX	317917 B	10-02-2014
			RU	2011148022 A	27-07-2013
			US	2010323942 A1	23-12-2010
			WO	2010147916 A1	23-12-2010

WO 2017079960	A1	18-05-2017	US	2017137747 A1	18-05-2017
			WO	2017079960 A1	18-05-2017

WO 0244312	A2	06-06-2002	AU	3037802 A	11-06-2002
			AU	3051102 A	11-06-2002
			CN	1478141 A	25-02-2004
			EP	1337612 A2	27-08-2003
			JP	2004522817 A	29-07-2004
			WO	0244311 A2	06-06-2002
			WO	0244312 A2	06-06-2002

WO 9919440	A1	22-04-1999	AR	012525 A1	18-10-2000
			AT	288955 T	15-02-2005
			AU	9181698 A	03-05-1999
			BR	9813065 A	28-05-2002
			CN	1281500 A	24-01-2001
			CZ	20001355 A3	12-09-2001
			DE	69828989 D1	17-03-2005
			DE	69828989 T2	30-03-2006
			EP	1023426 A1	02-08-2000
			ES	2237848 T3	01-08-2005
			JP	4069968 B2	02-04-2008
			JP	2001520265 A	30-10-2001
			US	6281181 B1	28-08-2001
			WO	9919440 A1	22-04-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

55

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 17 19 1354

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-03-2018

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9739089 A1	23-10-1997	AR 006679 A1	08-09-1999
		AT 221569 T	15-08-2002
		BR 9710430 A	17-08-1999
		CA 2252434 A1	23-10-1997
		CN 1222185 A	07-07-1999
		DE 69714432 D1	05-09-2002
		DE 69714432 T2	03-04-2003
		DK 0898607 T3	02-09-2002
		EP 0898607 A1	03-03-1999
		ES 2185936 T3	01-05-2003
		JP 4509222 B2	21-07-2010
		JP 2000503699 A	28-03-2000
		MX 217016 B	20-10-2003
		US 6046152 A	04-04-2000
		US 6087309 A	11-07-2000
		WO 9739089 A1	23-10-1997
EP 3243895 A1	15-11-2017	EP 3243895 A1	15-11-2017
		US 2017327771 A1	16-11-2017
		WO 2017196788 A1	16-11-2017
WO 2018017335 A1	25-01-2018	US 2018023036 A1	25-01-2018
		WO 2018017335 A1	25-01-2018

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- WO 2007135645 A [0064]