



(22) Date de dépôt/Filing Date: 2003/11/13

(41) Mise à la disp. pub./Open to Public Insp.: 2004/05/13

(45) Date de délivrance/Issue Date: 2008/12/30

(30) Priorité/Priority: 2002/11/13 (US10/293,878)

(51) Cl.Int./Int.Cl. *B65D 5/44* (2006.01),
B65D 5/46 (2006.01), *B65D 5/50* (2006.01),
B65D 5/72 (2006.01), *B65D 77/06* (2006.01)


(72) Inventeurs/Inventors:
DICKERSON, DAN C., US;
CROSLAND, R. JAMES, US;
CHIERA, KAREN M., US;
ROCHEFORT, OSCAR, US

(73) Propriétaire/Owner:
SMURFIT-STONE CONTAINER ENTERPRISES, INC.,
US

(74) Agent: GOWLING LAFLEUR HENDERSON LLP

(54) Titre : CAISSE-OUTRE

(54) Title: BAG-IN-BOX BEVERAGE CONTAINER



(57) Abrégé/Abstract:

A bag-in-box beverage container and dispenser is provided, incorporating an outer shell fabricated preferably from corrugated paperboard material, and an inner liquid containing bag, fabricated from a suitable plastic material. The carton includes ready

(57) **Abrégé(suite)/Abstract(continued):**

assembly features, as well as an internal ramp structure for prompting flow of liquid toward the dispensing aperture of the outer shell. A recessed handle structure is also provided, as are alternative embodiments of the internal ramp structure.

ABSTRACT OF THE DISCLOSURE

A bag-in-box beverage container and dispenser is provided, incorporating an outer shell fabricated preferably from corrugated paperboard material, and an inner liquid containing bag, fabricated from a suitable plastic material. The carton includes ready assembly features, as well as an internal ramp structure for prompting flow of liquid toward the dispensing aperture of the outer shell. A recessed handle structure is also provided, as are alternative embodiments of the internal ramp structure.

TITLE OF THE INVENTION

Bag-in-Box Beverage Container

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 **[0001]** The present invention relates to bag-in-box style cartons and containers, of the type in which a non-self-supporting plastic bag or the like is positioned in a surrounding, supporting container structure, the entire package being disposable after a single use. The present invention also relates to large volume urn-style beverage containers.

10 2. The Prior Art

[0002] Urn-style beverage containers, for the containment and controlled incremental dispensing of a relatively large volume (2+ gallons) of liquid are known. Typically, such urn-style beverage containers are reusable devices of metal and plastic, which can be heavy, and which, of course, require cleaning after each use. Various
15 versions of such devices are known as "pump pots"; "air pots"; various all-plastic urns (sold under the registered trademark "CamServers") and buckets with spigots, both manufactured by Cambro Manufacturing Company of Huntington Beach, California. There are also known in the art octagonal and rectangular cross-section bag-in-corrugated paperboard box configurations, such as those sold by BIB Pak, Inc., of
20 Racine, Wisconsin. The rectangular bag-in-box construction is also shown in Geshay, U.S. Pat. No. 6,062,431, owned by BIB Pak, Inc., of Racine, Wisconsin.

[0003] Retail and wholesale (catering) food service operators typically have need of such large volume beverage containers. However, permanent, reusable urns may be subject to various disadvantages and/or impose certain costs of operation, upon retail
25 customers and/or retail and wholesale food service operators. For example, caterers must address the need to physically retrieve the urns, requiring expenditures of labor and fuel. The urns must be cleaned and stored, again requiring expenditures of labor, cleaning supplies, and storage space. Reusable urns are often the subject of theft or "mysterious" disappearance, imposing unscheduled replacement costs, as well as the
30 replacement costs associated with the cycling out of units as a result of normal wear

and tear. If units are lost/stolen or in disrepair, the business operator runs the risk of lost sales.

[0004] Accordingly, it would be desirable to provide a large volume beverage dispenser which addresses the foregoing issues.

- 5 **[0005]** It would be desirable to provide a large volume dispenser which is disposable, and preferably fabricated in large part from recyclable materials, and which is configured for easy knock-down for recycling and disposal.

- [0006]** It would also be desirable to provide a large volume dispenser which provides areas for placement of advertising copy, images or indicia, which promote
10 brand identity, products and services, and/or "fitness for use" safety precaution instructions.

[0007] These and other desirable characteristics of the present invention will become apparent in view of the present specification and drawings.

SUMMARY OF THE INVENTION

[0008] The present invention is directed to a dispensing container, operably configured to be positioned upon a substantially flat, horizontal surface, for the facilitated dispensing of fluent material. The dispensing container comprises a generally tubular body, having a vertical axis, a depth axis and a transverse axis. A closure structure is disposed proximate an opening in an upper portion of the tubular body. The closure structure includes a handle structure, which is disposed in a recessed position within an upper opening of the generally tubular body and extending no higher than an upper edge region of the generally tubular body. The generally tubular body further has a plurality of sidewalls. A nozzle receiving aperture is operably disposed in one of the plurality of sidewalls.

[0009] An inner flow prompting ramp is operably positioned within the generally tubular body. The inner flow prompting ramp has a lower end, disposed adjacent the sidewall of the generally tubular body in which the nozzle receiving aperture is disposed, and a higher end, disposed adjacent an opposite sidewall thereto, and an inclined surface extending between the lower end and the upper end. The lower end of the inner flow prompting ramp is disposed at a distance above the bottom of the generally tubular body approximately equal to the distance between the bottom of the generally tubular body and a bottom peripheral region of the nozzle receiving aperture.

[0010] The generally tubular body is preferably formed from a first blank of at least one of the following materials: paper; paperboard; corrugated paperboard.

[0011] In a preferred embodiment, the generally tubular body comprises a front wall, a rear wall disposed parallel to the front wall, and two sidewalls, disposed parallel to one another, perpendicular to the front and rear walls and extending therebetween.

[0012] The closure structure preferably comprises first and second foldable sidewall top flaps, emanating from top edge regions of the sidewalls. Each of the first and second foldable sidewall top flaps preferably includes a first panel, foldably connected to one of the sidewalls, and positioned at an acute included angle relative thereto. Each of the first and second foldable sidewall top flaps preferably includes a second panel, foldably connected to one of the first panels, each of the second panels

being folded upwardly, parallel to the sidewalls and in juxtaposed overlying relation to one another, the second panels having top edges that are disposed no higher than the upper edge region of the generally tubular body. A foldable front wall top flap emanates from a top edge region of the front wall. A foldable rear wall top flap emanates from a top edge region of the rear wall. The foldable front and rear wall top flaps each includes first panels, foldably connected to the front and rear walls, respectively, and positioned substantially perpendicular thereto. The foldable front and rear wall top flaps each further include second panels, foldably connected to the respective first panels of the front and rear wall top flaps, and emanating downwardly therefrom, the second panels of the front and rear wall top flaps being disposed in positions interengaging with the second panels of the first and second sidewall top flaps, to preclude undesired dislodgement of the second panels of the first and second sidewall top flaps.

[0013] The closure structure preferably further comprises at least one slot in each of the first panels of the first and second sidewall top flaps. Preferably, at least one hooked tab emanates from each of the first panels of the front and rear wall top flaps. The hooked tabs are preferably configured to be engagingly received in the slots, when the second panels of the front and rear wall top flaps are folded over into interengagement with the second panels of the first and second sidewall top flaps.

[0014] Preferably, the closure structure further comprises at least one notch in each of the second panels of the first and second sidewall top flaps, the notches being aligned with one another when the second panels of the first and second sidewall top flaps are parallel to the sidewalls and in juxtaposed overlying relation to one another. A notch in at least one of the front and rear wall top flaps is operably configured to interengage with the aligned notches in the second panels of the first and second sidewall top flaps, when the second panels of the front and rear wall top flaps are folded over into interengagement with the second panels of the first and second sidewall top flaps.

[0015] Preferably, the handle structure comprises a hand opening aperture disposed in one of the second panels of the first and second sidewall top flaps. A

hingedly connected push-out flap is preferably disposed in the other of the second panels of the first and second sidewall top flaps. The push-out flap preferably has a peripheral contour substantially conforming to the peripheral contour of the hand opening aperture. The push out flap is configured to be pushed through the hand opening aperture, and upwardly relative thereto, to provide a grasping opening.

[0016] The inner flow prompting ramp preferably is formed from a second blank fabricated from at least one of the following materials: paper; paperboard; corrugated paperboard.

[0017] In a preferred embodiment of the invention, the inner flow prompting ramp is formed from a separate second blank of foldable material, which is insertably received into the generally tubular body. In one embodiment of the invention, the inner flow prompting ramp is formed from a substantially cruciform blank having a central rectangular panel, rectangular panels emanating from front and rear edge regions of the central panel, and trapezoidal panels emanating from side edges of the central panel. In one embodiment of the invention, the substantially cruciform blank further includes foldable support panels emanating from side edges of the panels emanating from the front and rear edge regions of the central panel. In another embodiment of the invention, the substantially cruciform blank further includes interlocking bottom panels emanating from side edge regions of the trapezoidal panels. In another embodiment of the invention, the substantially cruciform blank further includes inwardly folding triangular gusset panel pairs foldably connecting side edge regions of the rectangular panels emanating from the front and rear edge regions of the central panel to end edge regions of the trapezoidal panels emanating from the side edge regions of the central panel.

[0018] In an embodiment of the invention, the inner flow prompting ramp is formed from a blank comprising a central rectangular panel; trapezoidal side panels emanating from outside edges of the central panel; rectangular bottom panels, emanating from outside edges of the trapezoidal side panels; center support panels emanating from outside edges of the rectangular bottom panels; and inside inclined panels emanating from outside edges of the rectangular bottom panels. The ramp is

formed upon successive inward folding of outermost ones of the panels, so that the trapezoidal side panels are folded perpendicular to the central rectangular panel, the rectangular bottom panels are folded perpendicular to the trapezoidal side panels, the center support panels are folded perpendicular to the rectangular bottom panels, and the inside inclined panels are folded perpendicular to the center support panels, and in underlying parallel juxtaposed relation to the central rectangular panel. A pivotable interlocking tab is disposed in one of the rectangular bottom panels and an aperture disposed in the other of the rectangular bottom panels for receiving the pivotable interlocking tab, for maintaining the blank in its articulated configuration.

10 **[0019]** In an embodiment of the invention, the inner flow prompting ramp comprises a member foldably formed from at least one extension of, and connected to, the first blank.

[0020] The dispensing container preferably further comprises front and rear wall bottom flaps, connected to bottom edge regions of the front and rear walls, respectively. First and second sidewall bottom flaps are connected to bottom edge regions of the first and second sidewalls, respectively. Each of the first and second sidewall bottom flaps preferably includes a pivotable engagement flap, which is affixed to an outside surface of one of the front and rear bottom wall flaps. The generally tubular body in a preferred embodiment is operably configured such that when the closure structure is open, the generally tubular body may be articulated between a collapsed configuration, in which the front wall and one sidewall are disposed in juxtaposed overlying adjacent orientation to the other sidewall and the rear wall, with the front and rear wall bottom flaps being folded up inside a bottom opening region of the generally tubular body, in juxtaposed relation to inside bottom surfaces of the front and rear walls, respectively, and the respective pivotable engagement flaps are folded back upon their respective first and second sidewall bottom flaps; and an articulated position, wherein the front and rear walls are parallel to each other and perpendicular to the sidewalls, whereupon articulation from the collapsed configuration, the first and second sidewall bottom flaps and their respective attached front and rear wall bottom panels are automatically prompted to move into partial overlapping relation to the

15
20
25
30

front and rear wall bottom flaps to define a bottom for the articulated dispensing container.

[0021] Preferably, the first and second sidewall bottom flaps further each include engagement tabs which interlock, upon articulation, to maintain the first and second
5 sidewall bottom flaps and the front and rear bottom flaps in their partially overlapping, bottom defining orientation.

[0022] The dispensing container preferably further comprises an inner bag, operably configured for containing a liquid, and a spout structure, operably associated with the bag, configured to be passed through the spout aperture, upon placement of
10 the inner bag within the generally tubular body. A dispensing spigot preferably is operably configured to be positioned on the spout structure, after passage of the spout structure through the spout aperture of the generally tubular body.

[0023] In a preferred embodiment, at least one locking member is operably configured for engaging the spout structure, after placement of the spout structure
15 through the spout aperture of the generally tubular body, for precluding removal of the spout structure from the spout aperture.

[0024] In an alternative preferred embodiment of the invention, at least one further nozzle receiving aperture is operably disposed in one of the plurality of
sidewalls.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] Fig. 1 is a plan view for the blank for the outer shell for the bag-in-box beverage container of the present invention.

[0026] Fig. 2 is a plan view for the blank of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention.

[0027] Fig. 3 is a plan view for the blank of an alternative embodiment of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention.

10 **[0028]** Fig. 4 is a plan view for the blank of an alternative embodiment of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention.

[0029] Fig. 5 is a photographic step-by-step illustration of the assembly of a bag-in-box beverage container of the present invention.

15 **[0030]** Fig. 6 is a photographic step-by-step illustration of the filling of a bag-in-box beverage container of the present invention.

[0031] Fig. 7A is a plan view for the blank of an alternative embodiment of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention.

20 **[0032]** Fig. 7B is a view of the inner flow prompting ramp erected from the blank of Fig. 7A, as seen from underneath.

[0033] Fig. 7B is a view of the inner flow prompting ramp erected from the blank of Fig. 7A, as seen from above.

25 **[0034]** Fig. 8 is a plan view for the blank of an alternative embodiment of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention.

[0035] Fig. 9 is a composite illustration of two perspective views of the ramp structure that is formed from the blank of Fig. 8.

[0036] Fig. 10 is a plan view for the blank of an alternative embodiment of the invention, wherein the inner flow prompting ramp is integrally formed into the blank for the outer shell.

5 **[0037]** Fig. 11 is a perspective view of an outer shell according to the blank of Fig. 10, wherein the inner flow prompting ramp is integrally formed into the blank for the outer shell.

[0038] Fig. 12 is a plan view of a blank for an outer shell according to an alternative embodiment of the invention, wherein spout apertures are provided on both front and sidewalls.

10 **[0039]** Fig. 13 is a plan view of a blank for an outer shell according to another alternative embodiment of the invention, wherein two spout apertures are provided on the front wall, so that, if desired, the outer shell may be inverted when in use.

[0040] Fig. 14 is a plan view for a blank for an inner flow prompting ramp, to be used in combination with the outer shell according to the blank of Fig. 12.

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0041] While this invention is susceptible of embodiment in many different forms, there are shown in the drawings and will be described in detail, several specific embodiments, with the understanding that the present disclosure is to be considered
 5 as an exemplification of the principles of the invention and is not intended to limit the invention to the embodiments illustrated.

[0042] In preferred embodiments of the invention, each of the blanks illustrated herein, in Figs. 1 – 4, are fabricated from corrugated paperboard material, although
 10 similar paper-based materials, having similar performance characteristics, may be employed if desired.

[0043] In accordance with the usual conventions regarding the illustration of blanks of foldable material, unless otherwise expressly indicated, solid lines within the interior of a blank represent through-cuts or apertures, and broken or dotted lines represent lines of weakness, such as score lines, perforations, or the like.

[0044] A blank 10 for the outer shell for the bag-in-box of the present invention is illustrated in Fig. 1. Blank 10 includes front wall 12; front bottom flap 14; and top handle flap 16, which in turn includes panels 18 and 20. Spout aperture 22 is defined by cut flaps 24a – 24h and central aperture 26. Blank 10 also includes first sidewall 28 (foldably connected to front wall 12); sidewall bottom flap 30 with scored tabs 32, 34;
 20 and first sidewall handle flap 36, including panels 38, 40, with slots 42, 44, and notches 46, 48, and die cut push out flap 50. Rear panel 52 is foldably connected to first sidewall 28. Rear bottom flap 54 emanates from rear panel 52, as does rear handle flap 56, which includes, in turn, panels 58 and 60. Frangibly attached to panel 60 are foldably connected spout locking tabs 62, 64, each having keyhole shaped
 25 apertures therein. Second sidewall 66 is foldably connected to rear panel 52. Second sidewall bottom flap 68 emanates from second sidewall 66, and includes foldably connected tabs 70, 72. Second sidewall handle flap 74 includes panels 76, 78, slots 80, 82, notches 84, 86 and opening 88. Glue flap 90 is provided, which is affixed to an outside or inside surface of front panel 12.

[0045] To form the outer shell of the bag-in-box beverage container of the present invention, when blank 10 is formed into a tube by gluing flap 90 to front panel 12, front bottom flap 14, first sidewall bottom flap 30, rear bottom flap 54 and second sidewall bottom flap 68 are folded inwardly, and upwardly of the bottom edges of front wall 12, first sidewall 28, rear wall 52 and second sidewall 66. Tabs 72 and 34 are glued to adjacent panels 54 and 14, respectively. When set up, opposing flaps 68 and 30 are interlocked at the notches formed between tabs 32, 34 and 20, 72, respectively. Tabs 32, 70 are on the "inside" facing the interior of the resulting shell structure. See also subfigs. 3 and 4 of Fig. 5.

[0046] Because the interior liquid holding structure is a non-self-supporting flexible bag, a structure is required to prompt the liquid to flow toward the spout (see Figs. 5-15 and 6-1 through 6-4). To form the flow prompting structure, an inner flow prompting ramp is formed from blank 100 (see Fig. 2). Blank 100 includes inclined panel 102, short front panel 104 (which has a height approximately equal to the distance between the bottom edge of front panel 12 and the lower periphery of spout aperture 22, tall rear panel 106, and trapezoidal side panels 108, 110, all of which will be folded to be parallel to respective front wall 12, rear wall 52, and first and second sidewalls 28 and 66, respectively, upon insertion of the inner flow prompting ramp into the top opening of the shell (see Figs. 5-5 and 5-6). Finger notch 112 is provided, to facilitate removal and/or replacement of the inner flow prompting ramp formed from blank 100, during assembly and knockdown of the beverage container.

[0047] Once the inner flow promoting ramp has been inserted into the outer shell, the inner containment bag/closure assembly, which may be of any suitable design, is prepared for insertion into the outer shell. In one embodiment of the invention, the bag/closure assembly will be formed as a polyethylene (or other suitable food-grade plastic material) bag, at one end of which is attached an outwardly-threaded male spout member, which will typically have two axially spaced apart radially extending collars or rings, each of which is small in diameter than the large diameter portion of the keyhole openings of spout locking tabs 62, 64, but which is greater in diameter to the smaller diameter portion of the keyhole openings. Typically,

a dust cap is threaded onto the spout member to prevent contamination of the interior of the bag during shipping and storage. Referring to Figs. 5-7 – 5-10, the bag/closure assembly is prepared by removing the dust cap, expanding or “fluffing” the bag by pulling apart the (typically) folded over bag portion. Fig. 5-7. The spout locking tabs 5 62, 64 are pulled from panel 60, and separated from each other. One of tabs 62, 64 is then placed over the male spout member to a position between the bag and the collar closest to the bag, and slid to one side, so that the smaller diameter portion of the keyhole aperture surrounds the spout, and the collar prevents removal of the spout from the collar. Fig. 5-8. The bag/spout assembly is then placed inside the outer shell, 10 and the spout is pushed through the aperture 22. Fig. 5-9. The collar farthest from the bag will momentarily displace tabs 24a – 24h, as the spout member passes through aperture 22, with tabs 24a – 24h then flipping back down to approximately their original positions, behind the outer collar. To fix the collar in place the second of spout locking tabs 62, 64, is slid onto the spout member, and similarly positioned between 15 the outer collar and the front wall, and then slid to one side so that the narrow diameter portion of the keyhole opening surrounds the spout member, preventing displacement of the spout relative to the front wall. Fig. 5-10.

[0048] The outer shell is then closed by folding panels 38, 76 inwardly and down into the top opening of the outer shell, while folding panels 40 and 78 upwardly. 20 Panels 40 and 78 will be juxtaposed parallel to and against one another, in a vertical orientation. Figs. 5-11 through 5-13. Then, panels 18 and 58 are folded inwardly over the top of the outer shell, to positions coplanar to each other and parallel to the bottom of the outer shell. Panels 20 and 60 are then folded down to positions parallel to each other and to front wall 12. Notch 120 will interdigitate with notches 48 and 84 25 which will be aligned with one another, while hooked tabs 122 and 124 will be inserted into and engage slots 44 and 80, respectively. Notch 130 will interdigitate with notches 46 and 86, while hooked tabs 132, 134 will be inserted into and engage slots 82, 42, respectively. Panel 50 is then pushed through the opening 88 of adjacent panel 78, and folded upward, during carrying, to help hold panels 40, 78 together. Through the 30 use of the hooked tabs, the handle is firmly locked into place, and will be unlikely to

spontaneously dislodge or disassemble, during normal use and loading conditions, in the absence of affirmative, intentional dismantling of the container.

[0049] If the bag-in-box beverage container is not to be immediately used, it may be stored, upon returning the dust cap to its position screwed onto the male spout member. Filling of the container is demonstrated in Figs. 6-1 through 6-4. Once filling has been accomplished, then a female cap, provided with a positive closing tap (which may be of any suitable configuration) is screwed onto the male spout member, the container is uprighted, and rendered ready for dispensing.

[0050] Once the contents have been consumed, the bag-in-box beverage container is broken down for disposal and recycling essentially by reversing the foregoing procedure.

[0051] Fig. 3 illustrates a blank for an alternative embodiment of the flow prompting structure. An inner flow prompting ramp is formed from blank 200. Blank 200 includes inclined panel 202, short front panel 204 (which has a height approximately equal to the distance between the bottom edge of front panel 12 and the lower periphery of spout aperture 22; tall rear panel 206; and trapezoidal side panels 208, 210, all of which will be folded to be parallel to respective front wall 12, rear wall 52, and first and second sidewalls 28 and 66, respectively, upon insertion of the inner flow prompting ramp into the top opening of the shell. Finger notch 212 is provided, to facilitate removal and/or replacement of the inner flow prompting ramp formed from blank 200, during assembly and knockdown of the beverage container. Blank 200 also includes reinforcing corner panels 214, 216, 218 and 220.

[0052] Fig. 4 illustrates a blank for an alternative embodiment of the flow prompting structure. An inner flow prompting ramp is formed from blank 300. Blank 300 includes inclined panel 302, short front panel 304 (which has a height approximately equal to the distance between the bottom edge of front panel 12 and the lower periphery of spout aperture 22; tall rear panel 306; and trapezoidal side panels 308, 310, all of which will be folded to be parallel to respective front wall 12, rear wall 52, and first and second sidewalls 28 and 66, respectively, upon insertion of the inner flow prompting ramp into the top opening of the shell. Finger notch 312 is

provided, to facilitate removal and/or replacement of the inner flow prompting ramp formed from blank 300, during assembly and knockdown of the beverage container. Blank 300 also includes bottom panels 314, 316, which will be folded into interlocking relation to one another underneath inclined panel 302, via notches 318, 320.

5 **[0053]** The bag-in-box beverage container of the present invention is believed to embody a number of advantages over prior art containers, even including prior art corrugated containers, such as facilitated assembly and readiness; facilitated filling of the internal bag; facilitated handling and delivery, via the recessed and locked-in-place handle; easy knock-down for recycling; the ability to employ a wide variety of existing
10 taps and spigots; the provision of a level, flat top profile to permit stacking of stored containers, and even limited stacking of filled containers.

[0054] Fig. 7A is a plan view for the blank of an alternative embodiment of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention, seen from above in Fig. 7C. Blank 400
15 includes inclined panel 402; front panel 404; rear panel 406; side panels 408, 410; die cut grasping aperture 412; and gusset panel pairs 414, 416; 418, 420; 422, 424; 426, 428. When panels 404, 406, 408, 410 are folded down, in a manner similar to the other embodiments described hereinabove, the gusset panel pairs are folded inwardly, underneath inclined panel 402, as seen in Fig. 7B.

20 **[0055]** Fig. 8 is a plan view for the blank of an alternative embodiment of an inner flow prompting ramp, for insertion into the outer shell for the bag-in-box beverage container of the present invention. Blank 500 comprises inclined panel 502; rear panel 504; side panels 506, 508; bottom panels 510, 512 with cell flaps 514, 516; center support panels 518, 520; and inside inclined panels 526, 528. To form the
25 ramp, the panels at the ends of blank 500 are successively folded inwardly (panels 528, 526 folded perpendicular to panels 518, 520; panels 518, 520 are folded perpendicular to panels 510, 512; panels 510, 512 are folded perpendicular to panels 506, 508; and finally panels 506, 508 are folded perpendicular to panel 502, so that panels 526, 528 eventually are positioned underneath panel 502, in juxtaposed
30 underlying parallel relationship thereto. T-shaped tab 522 is pushed out and folded

over and pushed into aperture 524, to lock the ramp into its articulated configuration, as shown in Fig. 9, which is a composite illustration of two perspective views of the ramp structure that is formed from the blank 500 of Fig. 8. Cell flaps 514, 516 are pivotable to enable the storage within the ramp of articles, such as measuring cups or the like. rear panel 504 may be folded downwardly to cover the ends of the wedge-shaped enclosed areas at the end of the ramp, or folded upwardly (both as shown in Fig. 9).

[0056] Fig. 10 is an outside plan view of a portion of the blank 10' of an alternative embodiment of the invention, wherein the inner flow prompting ramp is integrally formed into the blank for the outer shell. Instead of having an automatically deploying bottom, for the outer shell, as shown in Fig. 1 and Fig. 5, panels 14, 30, 54 and 68 may be replaced, respectively, by panels 14', 30' 54' and 68'. Panels 30' and 68' are, in turn, formed by bottom panels 30a', 68a'; inside support panels 30b', 68b'; inclined panels 30c', 68c'; and outside support panels 30d', 68d'. These panels are rolled up, in a manner similar to the separate wedge-shaped ramp of Figs. 8 and 9, as shown in Fig. 11. Thereafter, panels 14' and 54' are folded to the outside of panels 30a' and 68a' and glued thereto. Aside from the foregoing differences, blank 10' preferably may be substantially the same as blank 10 in configuration, with respect to the top end closing and handle structures, and with respect to the spout aperture.

[0057] Fig. 12 illustrates a blank 600 for an outer shell according to an alternative embodiment, wherein the front wall 602 is now located between the sidewalls 604, 606, instead of at the end of the blank, as in the embodiment of Fig. 1, and rear wall 608 is now at the end of the blank, instead of being between the sidewalls as in the embodiment of Fig. 1. In addition, a spout aperture 610 is located on sidewall 604, as well as spout aperture 612 on front wall 602, so that a choice is given as to the location of the spout, and indeed the orientation of the outer shell. The remaining panels and flaps at the top and bottom of the blank, are, as can be seen in a comparison of Figs. 1 and 12, essentially identical in structure and operation. Accordingly, the same method of formation of the top and bottom closures, as described with respect to the embodiment of Fig. 1, applies to the embodiment of Fig.

12. Slightly different spout locking pieces 614, 616 are provided, which emanate from one of the sidewall top flap panels. Locking pieces 614, 616 are not slipped over the spout, but instead are simply slipped in place from the side, relying upon orientation and friction to be maintained in place during use. Aperture 610 permits the container
 5 formed from blank 600 to be inverted or laid on its side (depending upon the size, shape and orientation of the inner flow prompting ramp within the outer shell). For example, if the ramp has a "footprint" that is approximately the same as the top/bottom area (with appropriate inclination), then the outer shell will be inverted, to enable use of aperture 610. Alternatively, if a ramp is provided that has a footprint that
 10 is approximately the same as front wall 602 or rear wall 608, then the outer shell will be laid on its side (i.e., on rear wall 608), to permit dispensing from aperture 610.

[0058] Fig. 13 illustrates a blank 700 for an outer shell according to another alternative embodiment of the invention, having sidewall 702, front wall 706, rear wall 704, and other sidewall 708. Two apertures 710 and 712 are provided at the top
 15 center and bottom center of sidewall 702. Slightly different spout locking pieces 714, 716 are provided, which emanate from one of the sidewall top flap panels. Locking pieces 714, 716 are not slipped over the spout, but instead are simply slipped in place from the side, relying upon orientation and friction to be maintained in place during use. The remaining panels and flaps at the top and bottom of the blank, are, as can be
 20 seen in a comparison of Figs. 1 and 13, essentially identical in structure and operation. Accordingly, the same method of formation of the top and bottom closures, as described with respect to the embodiment of Fig. 1, applies to the embodiment of Fig. 13.

[0059] Fig. 14 illustrates blank 800 for an alternative embodiment of an inner
 25 flow prompting ramp, for use with either of blanks 600 or 700 of Figs. 12 or 13, wherein use of the sidewall apertures is desired. Blank 800 provides for the sloping of the top panel of the ramp from one long edge to the other (i.e., from side to side, instead of front to back).

[0060] The foregoing description and drawings merely explain and illustrate the
 30 invention and the invention is not limited thereto, as those skilled in the art who have

the disclosure before them will be able to make modifications and variations therein without departing from the scope of the invention.

WHAT IS CLAIMED IS:

1. A dispensing container, operably configured to be positioned upon a substantially flat, horizontal surface, for the facilitated dispensing of fluent material, the dispensing container comprising:

a generally tubular body comprising a front wall, a rear wall and two opposing sidewalls, and defining a vertical axis extending substantially parallel with the front wall, a depth axis extending substantially perpendicular to the front wall, and a transverse axis extending substantially parallel with the front wall and substantially perpendicular to the vertical axis, the generally tubular body further comprising an upper portion forming an upper opening;

a closure structure disposed proximate the upper opening;

the closure structure including a handle structure, the handle structure positioned substantially parallel with the depth axis in a recessed position within the upper opening and extending substantially parallel with the vertical axis no higher than an upper edge of the generally tubular body;

a nozzle receiving aperture operably disposed in the front wall;

an inner flow prompting ramp, operably positioned within the generally tubular body, the inner flow prompting ramp having a lower end, disposed adjacent the sidewall of the generally tubular body in which the nozzle receiving aperture is disposed, and a higher end, disposed adjacent an opposite sidewall thereto, and an inclined surface extending between the lower end and the upper end, the lower end of the inner flow prompting ramp being disposed at a distance above the bottom of the generally tubular body approximately equal to the distance between the bottom of the generally tubular body and a bottom peripheral region of the nozzle receiving aperture;

the generally tubular body being formed from a first blank of at least one of the following materials: paper; paperboard; and corrugated paperboard.

2. The dispensing container according to claim 1, wherein the rear wall is disposed parallel to the front wall, and the two sidewalls are disposed parallel to one another and perpendicular to the front wall and the rear wall and extending therebetween.

3. The dispensing container according to claim 2, wherein the closure structure comprises:

first and second foldable sidewall top flaps, emanating from top edge regions of the sidewalls,

each of the first and second foldable sidewall top flaps including a first panel, foldably connected to one of the sidewalls, and positioned at an acute included angle relative thereto,

each of the first and second foldable sidewall top flaps including a second panel, foldably connected to one of the first panels, each of the second panels being folded upwardly, parallel to the sidewalls and in juxtaposed overlying relation to one another, the second panels having top edges that are disposed no higher than the upper edge of the generally tubular body;

a foldable front wall top flap emanating from a top edge region of the front wall;

a foldable rear wall top flap emanating from a top edge region of the rear wall;

the foldable front and rear wall top flaps each including first panels, foldably connected to the front and rear walls, respectively, and positioned substantially perpendicular thereto;

the foldable front and rear wall top flaps each further including second panels, foldably connected to the respective first panels of the front and rear wall top flaps, and emanating downwardly therefrom, the second panels of the front and rear wall top flaps being disposed in positions interengaging with the second panels of the first and second sidewall top flaps, to preclude undesired dislodgement of the second panels of the first and second sidewall top flaps.

4. The dispensing container according to claim 3 wherein the closure structure further comprises:

at least one slot in each of the second panels of the first and second sidewall top flaps;
and

at least one hooked tab emanating from each of the second panels of the front and rear wall top flaps, said at least one hooked tab being configured to be engagingly received in the at least one slot, when the second panels of the front and rear wall top flaps are folded over into interengagement with the second panels of the first and second sidewall top flaps.

5. The dispensing container according to claim 3 wherein the closure structure further comprises:

at least one notch in each of the second panels of the first and second sidewall top flaps, the notches being aligned with one another when the second panels of the first and second sidewall top flaps are parallel to the sidewalls and in juxtaposed overlying relation to one another; and

a notch in at least one of the front and rear wall top flaps which is operably configured to interengage with the aligned notches in the second panels of the first and second sidewall top flaps, when the second panels of the front and rear wall top flaps are folded over into interengagement with the second panels of the first and second sidewall top flaps.

6. The dispensing container according to claim 3, wherein the handle structure comprises. a hand opening aperture disposed in one of the second panels of the first and second sidewall top flaps; a hingedly connected push-out flap, disposed in the other of the second panels of the first and second sidewall top flaps, the push-out flap having a peripheral contour substantially conforming to the peripheral contour of the hand opening aperture, the push out flap being configured to be pushed through the hand opening aperture, and upwardly relative thereto, to provide a grasping opening.

7. The dispensing container according to claim 1, wherein the inner flow prompting ramp is formed from a second blank fabricated from at least one of the following materials: paper; paperboard; corrugated paperboard.

8. The dispensing container according to claim 1, wherein the inner flow prompting ramp is formed from a separate second blank of foldable material, which is insertably received into the generally tubular body.
9. The dispensing container according to claim 8, wherein the inner flow prompting ramp is formed from a substantially cruciform blank having a central rectangular panel, rectangular panels emanating from front and rear edge regions of the central panel, and trapezoidal panels emanating from side edges of the central panel.
10. The dispensing container according to claim 9, wherein the substantially cruciform blank further includes foldable support panels emanating from side edges of the panels emanating from the front and rear edge regions of the central panel.
11. The dispensing container according to claim 9, wherein the substantially cruciform blank further includes interlocking bottom panels emanating from side edge regions of the trapezoidal panels.
12. The dispensing container according to claim 9, wherein the substantially cruciform blank further includes inwardly folding triangular gusset panel pairs foldably connecting side edge regions of the rectangular panels emanating from the front and rear edge regions of the central panel to end edge regions of the trapezoidal panels emanating from the side edge regions of the central panel.
13. The dispensing container according to claim 8, wherein the inner flow prompting ramp is formed from a blank comprising: a central rectangular panel; trapezoidal side panels emanating from outside edges of the central panel; rectangular bottom panels; emanating from outside edges of the trapezoidal side panels; center support panels emanating from outside edges of the rectangular bottom panels; and inside inclined panels emanating from outside edges of the center support panels; the ramp being formed upon successive inward folding of outermost ones of the panels, so that the trapezoidal side panels are folded perpendicular to the central rectangular

panel, the rectangular bottom panels are folded perpendicular to the trapezoidal side panels, the center support panels are folded perpendicular to the rectangular bottom panels, and the inside inclined panels are folded perpendicular to the center support panels, and in underlying parallel juxtaposed relation to the central rectangular panel; a pivotable interlocking tab disposed in one of the rectangular bottom panels and an aperture disposed in the other of the rectangular bottom panels for receiving the pivotable interlocking tab, for maintaining the blank in its articulated configuration.

14. The dispensing container according to claim 1, wherein the inner flow prompting ramp comprises: a member foldably formed from at least one extension of, and connected to, the first blank.

15. The dispensing container according to claim 1, further comprising:

front and rear bottom flaps, connected to bottom edge regions of the front and rear walls, respectively;

first and second sidewall bottom flaps, connected to bottom edge regions of the first and second sidewalls, respectively;

each of the first and second sidewall bottom flaps including a pivotable engagement flap, which is affixed to an outside surface of one of the front and rear bottom wall flaps;

the generally tubular body being operably configured such that when the closure structure is open, the generally tubular body is articulated between a collapsed configuration, in which the front wall and one sidewall are disposed in juxtaposed overlying adjacent orientation to the other sidewall and the rear wall, with the front and rear wall bottom flaps being folded up inside a bottom opening region of the generally tubular body, in juxtaposed relation to inside bottom surfaces of the front and rear walls, respectively, and the respective pivotable engagement flaps are folded back upon their respective first and second sidewall bottom flaps; and an articulated position, wherein the front and rear walls are parallel to each other and perpendicular to the sidewalls, whereupon articulation from the collapsed configuration, the first and second sidewall bottom flaps and their respective attached front and rear wall bottom panels are automatically

prompted to move into partial overlapping relation to the front and rear wall bottom flaps to define a bottom for the articulated dispensing container.

16. The dispensing container according to claim 15, wherein the first and second sidewall bottom flaps further each include engagement tabs which interlock, upon articulation, to maintain the first and second sidewall bottom flaps and the front and rear bottom flaps in their partially overlapping, bottom defining orientation.

17. The dispensing container according to claim 1, further comprising an inner bag, operably configured for containing a liquid, and a spout structure, operably associated with the bag, configured to be passed through the nozzle receiving aperture, upon placement of the inner bag within the generally tubular body.

18. The dispensing container according to claim 17, further comprising a dispensing spigot, operably configured to be positioned on the spout structure, after passage of the spout structure through the nozzle receiving aperture of the generally tubular body.

19. The dispensing container according to claim 17, further comprising at least one locking member, operably configured for engaging the spout structure, after placement of the spout structure through the nozzle receiving aperture of the generally tubular body, for precluding removal of the spout structure from the nozzle receiving aperture.

20. The dispensing container according to claim 1, further comprising at least one further nozzle receiving aperture, operably disposed in one of the plurality of sidewalls.

Application number / numéro de demande: 2449330

Figures: 5, 6,

Pages: _____

Unscannable items
received with this application
(Request original documents in File Prep. Section on the 10th floor)

Documents reçu avec cette demande ne pouvant être balayés
(Commander les documents originaux dans la section de préparation des dossiers au
10ème étage)




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 7A




FIG. 7B




FIG. 7C





FIG. 10

FIG. 8

FIG. 9

**FIG. 11**




FIG. 12




FIG. 13




FIG. 14

