

(12) **United States Patent**  
**Bewlay et al.**

(10) **Patent No.:** **US 11,286,849 B2**  
(45) **Date of Patent:** **Mar. 29, 2022**

- (54) **ULTRASONIC CLEANING SYSTEM AND METHOD**
- (71) Applicant: **GENERAL ELECTRIC COMPANY**, Schenectady, NY (US)
- (72) Inventors: **Bernard Patrick Bewlay**, Niskayuna, NY (US); **Waseem Ibrahim Faidi**, Niskayuna, NY (US); **Peter William Lorraine**, Niskayuna, NY (US); **Mohamed Ahmed Ali**, West Chester, OH (US); **Siavash Yazdanfar**, Niskayuna, NY (US); **Ying Fan**, Niskayuna, NY (US); **Edward James Nieters**, Burnt Hills, NY (US); **David Mills**, Niskayuna, NY (US); **Nicole Jessica Tibbetts, Jr.**, Cardiff (GB)
- (73) Assignee: **GENERAL ELECTRIC COMPANY**, Schenectady, NY (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 135 days.

(21) Appl. No.: **16/000,810**  
(22) Filed: **Jun. 5, 2018**

(65) **Prior Publication Data**  
US 2018/0291803 A1 Oct. 11, 2018

**Related U.S. Application Data**  
(62) Division of application No. 14/938,590, filed on Nov. 11, 2015, now Pat. No. 10,018,113.

(51) **Int. Cl.**  
**F02B 77/04** (2006.01)  
**B08B 3/12** (2006.01)  
(Continued)

(52) **U.S. Cl.**  
CPC ..... **F02B 77/04** (2013.01); **B08B 3/12** (2013.01); **B08B 7/028** (2013.01); **B08B 9/0321** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... B08B 3/12; B08B 7/028; B08B 9/031; B08B 9/00; B08B 2209/005;  
(Continued)

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
2,924,542 A \* 2/1960 Giammaria ..... F02B 77/04 134/1  
3,056,284 A \* 10/1962 Marsh ..... G01N 29/12 73/597  
(Continued)


**FOREIGN PATENT DOCUMENTS**  
CN 1571707 A 1/2005  
CN 101479053 A 7/2009  
(Continued)

**OTHER PUBLICATIONS**  
Machine translation and First Office action and Search issued in connection with corresponding CN Application No. 201610993374.7 dated Sep. 27, 2018.  
(Continued)

*Primary Examiner* — Michael E Barr  
*Assistant Examiner* — Thomas Bucci  
(74) *Attorney, Agent, or Firm* — Fitch, Even, Tabin & Flannery LLP

(57) **ABSTRACT**  
A cleaning system and method use an ultrasound probe, a coupling mechanism, and a controller to clean equipment of a vehicle system. The ultrasound probe enters into an engine. The ultrasound probe emits ultrasound pulses and the coupling mechanism provides an ultrasound coupling medium between the ultrasound probe and one or more components of the engine. The controller drives the ultrasound probe to deliver the ultrasound pulse through the coupling medium to a surface of the one or more components of the engine. The ultrasound probe delivers the ultrasound pulse to remove deposits from the one or more components of the engine.

**14 Claims, 5 Drawing Sheets**





(56)

References Cited

U.S. PATENT DOCUMENTS

6,052,056 A \* 4/2000 Burns ..... B64D 15/20  
250/573  
6,160,340 A \* 12/2000 Guo ..... B06B 1/0629  
310/334  
6,176,135 B1 \* 1/2001 Dubois ..... G01N 29/2418  
372/28  
6,259,653 B1 \* 7/2001 Courson ..... B63B 59/08  
114/222  
6,276,292 B1 \* 8/2001 Soulek ..... B63B 59/04  
114/222  
6,286,370 B1 \* 9/2001 Sinha ..... G01N 5/02  
73/579  
6,324,900 B1 \* 12/2001 Bruno ..... B08B 7/028  
356/928  
6,367,328 B1 \* 4/2002 Gorman ..... G01N 17/006  
73/290 R  
6,378,377 B2 \* 4/2002 Matuseski ..... B64D 15/20  
340/582  
6,391,061 B1 \* 5/2002 Hortel ..... B08B 3/12  
8/137.5  
6,430,996 B1 \* 8/2002 Anderson ..... G01K 13/028  
73/170.26  
6,624,133 B1 \* 9/2003 McKenzie ..... C11D 3/386  
510/392  
6,624,539 B1 \* 9/2003 Hansen ..... B06B 1/085  
310/26  
6,659,365 B2 \* 12/2003 Gipson ..... F23D 11/345  
239/102.2  
6,663,718 B1 \* 12/2003 Mush ..... B08B 9/00  
123/198 A  
6,668,654 B2 \* 12/2003 Dubois ..... G01H 3/00  
356/502  
6,736,784 B1 \* 5/2004 Menne ..... A61B 17/22004  
601/2  
6,789,427 B2 \* 9/2004 Batzinger ..... G01N 29/069  
73/614  
6,880,402 B1 \* 4/2005 Couet ..... B08B 3/12  
73/579  
6,886,406 B1 \* 5/2005 Couet ..... E21B 37/06  
73/579  
6,899,519 B2 \* 5/2005 Bates ..... G01N 29/07  
415/118  
H2127 H \* 10/2005 Byrd ..... 374/121  
6,995,501 B2 \* 2/2006 Fukuda ..... B06B 1/0607  
310/334  
7,084,553 B2 \* 8/2006 Ludwiczak ..... B08B 7/02  
310/321  
7,089,795 B2 \* 8/2006 Bray ..... G01N 29/07  
73/598  
7,302,109 B2 \* 11/2007 Hu ..... G01B 11/25  
358/520  
7,509,878 B2 \* 3/2009 Sato ..... G01F 1/663  
600/439  
7,522,259 B2 \* 4/2009 Hazelton ..... B08B 3/04  
355/30  
7,654,148 B2 \* 2/2010 Tomlinson, Jr. .... G01N 29/07  
73/801  
7,686,500 B2 \* 3/2010 Laugharn, Jr. .... B01F 11/0283  
366/127  
7,710,000 B2 \* 5/2010 Hall ..... G01N 27/308  
310/322  
7,770,453 B2 \* 8/2010 Ludwiczak ..... G01N 29/07  
73/583  
7,799,146 B2 9/2010 McLoughlin et al.  
7,846,096 B2 \* 12/2010 Mast ..... A61B 8/12  
600/437  
8,048,231 B1 \* 11/2011 Eum ..... B08B 3/12  
134/1  
8,087,297 B2 \* 1/2012 Ludwiczak ..... B64D 15/163  
73/584  
8,087,298 B1 \* 1/2012 DiMambro ..... G01N 29/226  
73/629

8,128,568 B2 \* 3/2012 Wang ..... A61B 8/483  
600/459  
8,181,523 B2 \* 5/2012 Batzinger ..... B06B 1/00  
73/579  
8,309,045 B2 \* 11/2012 Zhang ..... F01N 3/206  
423/210  
8,425,435 B2 \* 4/2013 Wing ..... A61B 8/546  
601/2  
8,434,936 B2 \* 5/2013 Cuffe ..... G01K 11/22  
374/119  
D699,359 S \* 2/2014 Lindekugel ..... D24/186  
9,038,557 B2 \* 5/2015 Smith ..... B62D 55/265  
114/222  
9,050,053 B2 \* 6/2015 Morgan ..... A61B 8/4281  
9,121,817 B1 \* 9/2015 Roach ..... G01N 29/28  
9,211,107 B2 \* 12/2015 Cox ..... C08K 5/005  
9,480,863 B2 \* 11/2016 Lewis, Jr. .... A61B 8/4227  
9,492,097 B2 \* 11/2016 Wilkes ..... A61B 34/20  
9,915,633 B2 \* 3/2018 Georgeson ..... G01N 29/28  
10,343,193 B2 7/2019 Ponomarev  
2001/0037537 A1 \* 11/2001 Kitaori ..... B06B 3/02  
15/379  
2002/0134402 A1 \* 9/2002 Madanshetty ..... G10K 15/043  
134/1  
2002/0189633 A1 \* 12/2002 Nichole Powers .. C11D 17/041  
134/1  
2002/0189634 A1 \* 12/2002 Vanhauwermeiren .....  
C11D 3/3947  
134/1  
2003/0028287 A1 \* 2/2003 Puskas ..... B06B 1/0284  
700/266  
2003/0084535 A1 \* 5/2003 DuVal ..... B08B 3/12  
15/339  
2003/0084916 A1 \* 5/2003 Gaaloul ..... A47L 25/08  
134/1  
2004/0005134 A1 \* 1/2004 Sun ..... G02B 6/3866  
385/134  
2004/0035912 A1 \* 2/2004 Li ..... B23K 20/106  
228/110.1  
2004/0250844 A1 \* 12/2004 Kumazaki ..... A47L 13/00  
134/201  
2005/0120756 A1 \* 6/2005 Mah ..... B08B 7/0057  
68/3 SS  
2005/0155622 A1 \* 7/2005 Leis ..... B08B 1/00  
134/1  
2006/0272685 A1 \* 12/2006 Honda ..... B08B 7/02  
134/184  
2007/0068551 A1 \* 3/2007 Garimella ..... B08B 3/02  
134/1  
2009/0189020 A1 \* 7/2009 Bilgram ..... G01B 17/025  
244/134 F  
2009/0223542 A1 \* 9/2009 Lee ..... B08B 3/02  
134/187  
2009/0293906 A1 \* 12/2009 Baddeley ..... B08B 3/12  
134/1  
2010/0031972 A1 \* 2/2010 Royer, Jr. .... B64D 15/00  
134/1  
2010/0275949 A1 \* 11/2010 Ruhge ..... B08B 7/028  
134/1  
2011/0290286 A1 \* 12/2011 Ohata ..... B08B 3/12  
134/184  
2013/0220004 A1 \* 8/2013 Epstein ..... F02C 9/46  
73/112.01  
2016/0023252 A1 \* 1/2016 Kaneda ..... B08B 9/08  
134/1  
2016/0023772 A1 \* 1/2016 Borigo ..... B64D 15/163  
134/1

FOREIGN PATENT DOCUMENTS

CN 201744457 U 2/2011  
CN 102574169 A 7/2012  
CN 103252332 A 8/2013  
CN 203917258 U 11/2014  
CN 104258484 A 1/2015  
CN 204640513 U 9/2015

(56)

**References Cited**

## FOREIGN PATENT DOCUMENTS

DE	19540373	A1	5/1997
EP	2752559	A1	7/2014
JP	S5520673	A	2/1980
JP	2005/128745	A	5/2005
JP	2007/090344	A	4/2007
JP	2007/285181	A	11/2007
JP	2011/078894	A	4/2011
WO	WO97/16263	A1	5/1997
WO	WO2006/084308	A1	8/2006
WO	WO2007/147723	A2	12/2007
WO	WO2015/126585	A1	8/2015

## OTHER PUBLICATIONS

European Search Report Corresponding to Application No. 161996738 dated Mar. 10, 2017.

Canadian Office Action Corresponding to Application No. 2946567 dated Oct. 24, 2017.

Machine Translated Japanese Search Report Corresponding to Application No. 2016214741 dated Jan. 23, 2018.

Machine Translated Japanese Office Action Corresponding to Application No. 2016214741 dated Feb. 5, 2018.

Arab States of the Gulf Search Report Corresponding to Application No. 201632319 dated Nov. 25, 2018.

Machine Translated Chinese Search Report Corresponding to Application No. 201610993374 dated May 6, 2019.

Machine Translated Chinese Search Report Corresponding to Application No. 201610993374 dated Feb. 27, 2020.

Machine Translated Chinese Office Action Corresponding to Application No. 201610993374 dated Mar. 6, 2020.

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

1

## ULTRASONIC CLEANING SYSTEM AND METHOD

### CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional of U.S. patent application Ser. No. 14/938,590, entitled "ULTRASONIC CLEANING SYSTEM AND METHOD," filed on Nov. 11, 2015, the entire disclosure of which is incorporated herein by reference.

### FIELD

Embodiments of the subject matter disclosed herein relate to systems and methods for cleaning equipment such as engines and parts of engines.

### BACKGROUND

Equipment such as engines can accumulate deposits over time. For example, engines coupled with wings of aircraft can accumulate deposits (deposits formed from sand, dust, and/or other materials) on exterior surfaces and/or internal surfaces. These and other types of deposits can degrade engine performance. Eventually, the deposits must be cleaned from the engines and engine parts.

Current cleaning systems and methods remove the engine and/or engine parts from the larger turbine system (e.g., the aircraft) so that the engine and/or engine parts can be cleaned. This type of cleaning can take the turbine system out of operation for a significant period of time. As a result, the system may not be used during this period of time. Additionally, the manual effort involved in decoupling the engine from the system, taking one or more parts of the engine apart for cleaning, re-assembling the engine after cleaning, and re-connecting the engine with the system can be significant. A need exists for an easier and/or more efficient cleaning of equipment such as engines of vehicles.

### BRIEF DESCRIPTION

In one embodiment, a cleaning system includes an ultrasound probe, a coupling mechanism, a scanning mechanism, and a controller. The ultrasound probe is configured to enter into an engine while the engine is one or more of coupled with or disposed within a vehicle. The ultrasound probe also is configured to emit an ultrasound pulse. The coupling mechanism is configured to provide an ultrasound coupling medium between the ultrasound probe and one or more components of the engine. The ultrasound probe is configured to be scanned, manually, automatically, or in a way that combines both manual and automatic scanning, to cover the region of deposits to be cleaned. The controller is configured to drive the ultrasound probe to deliver the ultrasound pulse through the coupling medium to a surface of the one or more components of the engine. The ultrasound probe is configured to deliver the ultrasound pulse to remove deposits from the one or more components of the engine while the engine is one or more of coupled with or disposed within the vehicle.

In another embodiment, a method (e.g., for cleaning equipment of a system) includes inserting an ultrasound probe into an engine while the engine is one or more of coupled with or disposed within a vehicle, delivering an ultrasound coupling medium between the ultrasound probe and one or more components of the engine, and emitting an

2

ultrasound pulse from the ultrasound probe and through the coupling medium to a surface of the one or more components of the engine. The ultrasound pulse removes deposits from the one or more components of the engine while the engine is one or more of coupled with or disposed within the vehicle.

In another embodiment, a system (e.g., a cleaning system) includes an ultrasound probe and a controller. The ultrasound probe is configured to enter into equipment while the engine is coupled with or disposed within a vehicle system. The ultrasound probe also is configured to emit an ultrasound pulse. The controller is configured to drive the ultrasound probe to deliver the ultrasound pulse to a surface of the one or more components of the engine. The ultrasound probe also is configured to deliver the ultrasound pulse to remove deposits from the one or more components of the engine while the engine is one or more of coupled with or disposed within the vehicle.

### BRIEF DESCRIPTION OF THE DRAWINGS

Reference is made to the accompanying drawings in which particular embodiments and further benefits of the invention are illustrated as described in more detail in the description below, in which:

FIG. 1 illustrates one embodiment of an equipment cleaning system;

FIG. 2 illustrates one example of a component of equipment shown in FIG. 1;

FIG. 3 illustrates a probe of the cleaning system shown in FIG. 1 during removal of deposits from an exterior surface of the equipment according to one example;

FIG. 4 illustrates another embodiment of a coupling mechanism;

FIG. 5 illustrates a cross-sectional view of another component of the equipment shown in FIG. 1 according to one embodiment;

FIG. 6 illustrates a flowchart of one embodiment of a method for cleaning equipment of a system;

FIG. 7 illustrates a front view of a combination ultrasound probe according to one embodiment; and

FIG. 8 illustrates a cross-sectional view of the ultrasound probe shown along line 8-8 shown in FIG. 7 according to one embodiment.

### DETAILED DESCRIPTION

One or more embodiments of the inventive subject matter described herein provide systems and methods for cleaning equipment of systems, such as engines of vehicles. The systems and methods can clean the engines and/or parts of the engines while the engines remain connected with the vehicles. The engines and engine parts may be cleaned to remove sand accumulation or other deposits on engine parts, such as turbine blades (e.g., high pressure turbine blades) and nozzles, combustor liners, compressor blades, etc.

In one embodiment, the cleaning systems and methods use delivery mechanisms to apply end effectors described herein to engine parts in-situ while the engine is coupled with the vehicle (e.g., while the engine is on a wing of an aircraft). Alternatively, the systems and methods can clean the engine while the engine is off-wing, such as in a service shop. The techniques described herein can be applied for other ground-based equipment (e.g., turbines) where cleaning is needed. A focused ultrasound probe may be used to emit ultrasound waves that remove deposits from the engine. The deposits that are removed can include sand or other

materials that are not part of the engine. The probe may emit ultrasound waves having frequencies of at least 50 kHz to no more than 100 MHz, but alternatively may have other frequencies. The probe may have a circular or rectangular geometry, and may be acoustically coupled with the engine by a fluid that is disposed on the engine (e.g., by flooding the internal portions of a blade with water or another fluid, by spraying water or another fluid onto the engine, etc.). Optionally, a diaphragm (e.g., a balloon) that is at least partially filled with water or another fluid may be disposed between and engaged with the deposits and the ultrasound probe for acoustically coupling the probe with the deposits.

The ultrasound waves emitted by the probe can be focused on the deposits (e.g., the sand) and not on the materials forming the engine or coatings of the engine. For example, some engines and/or engine parts may be coated with a thermal barrier coating (TBC). The probe can focus the ultrasound waves so that a focal point of the waves is on or inside the deposits, but not inside, on, or beneath the thermal barrier coating on the exterior surface of the engine. The ultrasound waves create bubble oscillations and collapse, which in turn generates shockwaves that destroy and/or disbond the deposit. The size and geometry of the ultrasound probe are selected to permit delivering the probe to the component to be cleaned through engine access channels, which may be relatively small (e.g., several millimeters or centimeters across). The geometric focal length of the probe is selected to increase or maximize the focus gain of the ultrasound beam, while avoiding total reflection of any part of the ultrasound beam. For example, when the access channel is a circular borescope access hole of 0.5-inch diameter, the ultrasound probe may be selected to have a circular aperture of 0.5-inch diameter and a geometric focal length of 1.0-inch. The focal length will increase or maximize the focus gain, while avoiding total reflection of any part of the ultrasound beam.

FIG. 1 illustrates one embodiment of an ultrasonic equipment cleaning system 100. The cleaning system 100 may be used to clean equipment 102, such as an engine, while the equipment is coupled with a turbine system 104 that uses the engine, such as a vehicle (e.g., an aircraft). While the description herein focuses on using the cleaning system 100 to clean an engine of an aircraft while the engine is coupled with a wing of the aircraft, alternatively, the cleaning system 100 may be used to clean another type of equipment, equipment that is not coupled with a vehicle, and/or equipment that is for another type of vehicle or system. FIG. 2 illustrates one example of a component 200 of the equipment 102 shown in FIG. 1. The component 200 shown in FIG. 2 is a portion of high pressure turbocharger blades. The component 200 has several deposits 202 of material, such as sand, on the exterior surface 126 of the component 200.

Returning to the description of the cleaning system 100 shown in FIG. 1, the cleaning system 100 includes a probe 106 that is inserted into the turbine system 104 for cleaning the equipment 102. The probe 106 may be sufficiently small to allow the probe 106 to enter into small locations of the turbine system 104 and/or equipment 102, such as through a borescope inspection holes, or borescope holes, of the equipment 102. For example, some openings through which the probe 106 may extend in order to clean the equipment 102 may be as small as one eighth of an inch (or no larger than 3.175 millimeters). In one embodiment, the probe 106 represents an ultrasound transducer that emits focuses ultrasound pulses to clean the equipment 102. The probe 106 may detect echoes of the ultrasound pulses for investigative and/or diagnostic purposes, as described herein.

A coupling mechanism 108 of the cleaning system 100 provides a coupling medium 110 between the probe 106 and one or more components of the equipment 102. In the illustrated embodiment, the coupling mechanism 108 includes a nozzle 130 that delivers a fluid as the coupling medium 110 by spraying or otherwise directing the fluid onto and/or into the equipment 102. For example, the nozzle 130 may spray water, oil, or the like, onto exterior and/or interior surfaces of the equipment 102. Alternatively, the coupling mechanism 108 may include a diaphragm that is at least partially filled with the coupling medium 110, as described below. The coupling mechanism 108 can include a source 128 of the coupling medium 110, such as a tank or other container that holds water or another fluid.

The probe 106 is connected to an elongated connector 112, such as a cable, that is sufficiently small to allow the probe 106 to be inserted into the turbine system 104 and/or equipment 102 to remove deposits on and/or in the equipment 102 while a power source 116 and/or controller 118 of the cleaning system 100 are disposed outside of the turbine system 104 and/or equipment 102. The power source 116 can represent one or more batteries that supply electric current to power the cleaning system 100 and/or connectors that connect with an external source of electric current, such as a utility grid, to power the cleaning system 100. The controller 118 represents hardware circuitry that includes and/or is connected with one or more processors (e.g., microprocessors, integrated circuits, field programmable gate arrays, or other electronic logic-based devices) that control operation of the cleaning system 100. The controller 118 may operate based off of instructions received from a manual operator and/or software that is stored on a memory 120 of the cleaning system 100. The memory 120 can represent computer readable medium and/or the software instructions stored therein, such as a computer hard drive, flash memory, or the like. An input device 122 of the cleaning system 100 receives input from outside sources (e.g., an operator of the cleaning system 100), and can include a touchscreen, keyboard, electronic mouse, stylus, etc. An output device 124 of the cleaning system 100 provides output to an operator, and can include a touchscreen (e.g., the same or different touchscreen as the input device 122), monitor, speaker, etc.

The controller 118 drives the probe 106 to deliver ultrasound pulses through the coupling medium 110 to a surface 126 of one or more components of the equipment 102. The probe 106 can include piezoelectric elements or bodies that are electronically powered to emit ultrasound pulses and/or that can detect echoes of the pulses. The surface 126 can include an external or internal surface of the equipment 102, as described herein. The distal end or tip of the probe 106 may be placed into contact with the coupling medium 110 on the equipment 102 and emit ultrasound waves. The coupling medium 110 may acoustically conduct the ultrasound waves from the probe 106 to the deposits on the equipment 102. The probe 106 delivers the ultrasound pulses to remove deposits from the equipment 102 while the equipment 102 is coupled with and/or disposed within the turbine system 104 (e.g., the vehicle). In one embodiment, the probe 106 delivers the ultrasound pulses to remove the deposits while the equipment 102 is mounted to a wing of an aircraft. The probe 106 can focus the pulses to clean one or more components of the equipment 102, such as one or more high pressure turbocharger blades, nozzles, combustor liners, compressor blades, etc., of an engine.

In one embodiment, the input device 122 of the cleaning system 100 includes and/or is connected with an optical

sensor **114**, such as a camera. The optical sensor **114** can be inserted into the equipment **102** in order to generate optical data representative of the equipment **102**. For example, a camera may be inserted into the equipment to determine the amount and/or location of deposits on the equipment **102**, which can be presented to an operator of the cleaning system **100** to determine whether a previous cleaning of the equipment **102** removed the deposits, to determine where the deposits are located, etc.

The cleaning system **100** optionally may include a scanning mechanism **132** that moves one or more of the probe **106** and/or the sensor **114**. The scanning mechanism **132** can represent one or more motors, gears, or the like, that translate energy received from the power source into movement of the probe **106** and/or sensor **114** relative to the equipment **102**. The scanning mechanism **132** may be connected with the probe **106** and/or the sensor **114** to allow the controller **118** to automatically move the probe **106** and/or sensor **114** in the equipment **102**, to allow an operator input instructions via the input device **122** to manually move the probe **106** and/or sensor **114** in the equipment **102** (e.g., in locations where the operator is unable to manually reach), and/or to allow for both manual and/or automatic movement of the probe **106** and/or sensor **114**.

FIG. 3 illustrates the probe **106** of the cleaning system **100** shown in FIG. 1 during removal of deposits **202** from an exterior surface **126** of the equipment **102** according to one example. A distal end or tip **300** of the probe **106** is placed into contact with the coupling medium **110**. The coupling medium **110** extends between and is in contact with the probe **106** and the surface **126** of the equipment **102**. The equipment **102** may include an external metal layer **302** and a thermal barrier coating (TBC) **304** beneath the surface **302**. The deposits **202** may be on the metal layer **302** and the controller **118** (shown in FIG. 1) can focus the ultrasound pulses emitted by the probe **106** such that the pulses are focused on the metal layer **302** and/or deposits **202** to remove the deposits **202**, but do not damage and are not focused on the TBC **304**. As a result, the TBC **304** is protected from damage or removal by the ultrasound pulses. The probe **106** can be moved or scanned relative to the equipment **102** in order to remove the deposits **202** from different areas of the equipment **102**. For example, the probe **106** may not be fixed in one location and scanned in a manual, automated, or in a way the combines both manual and automatic scanning.

FIG. 4 illustrates another embodiment of a coupling mechanism **400**. The coupling mechanism **400** can include a diaphragm or other flexible bladder **402** that is at least partially filled with a coupling fluid. The diaphragm **402** may be connected with the distal end **300** of the probe **106**. The probe **106** may be moved toward the equipment **102** so that the diaphragm **402** is compressed between the probe **106** and the equipment **102**, as shown in FIG. 4. The coupling fluid in the diaphragm **402** may then acoustically couple the probe **106** with the equipment **102** such that ultrasound pulses emitted by the probe **106** can propagate through the diaphragm **402** and coupling fluid into the equipment **102** to remove the deposits **202**, as described above.

Optionally, the distal end **300** of the probe **106** may include a low attenuation, high acoustic impedance material, such as gallium or gallium-indium alloy, as the coupling medium or coupling mechanism. For example, a layer or body of gallium, gallium-indium alloy, or another material

may be disposed on the probe **106** and may conduct the ultrasound pulses from the probe **106** into the equipment **102** through the layer or body.

FIG. 5 illustrates a cross-sectional view of another component **500** of the equipment **102** shown in FIG. 1 according to one embodiment. The component **500** can represent a high pressure turbine blade or another component of the equipment **102**. The component **500** includes both exterior surfaces **502** and opposite interior surfaces **504**. The cleaning system **100** shown in FIG. 1 can remove deposits **202** (shown in FIG. 2) from the exterior surfaces **502** (as described above in connection with FIG. 4) and also from the interior surfaces **504**. The interior surfaces **504** at least partially extend around and define one or more interior chambers or internal cavities **506** of the equipment **102**.

In one embodiment, the cleaning system **100** can remove deposits **202** from the interior surfaces **504** without the probe **106** being located inside the component **500** (e.g., without the probe **106** being inside the interior chambers **506**). The probe **106** can be located outside of the interior chambers **506** with the distal end **300** of the probe **106** being in contact with the coupling medium **110**, which also is in contact with the exterior surface **502** of the component **500**. The controller **118** (shown in FIG. 1) can vary the frequency of the ultrasound pulses to change where the ultrasound pulses are focused. The pulses can propagate through the coupling medium **110** in contact with the exterior surface **502**, through the material forming the component **500**, and be focused on the interior surface **504** (or at the interface between the interior surface **504** and the deposits **202** on the interior surface **504**).

Optionally, the coupling medium **110** may be disposed inside the interior chamber **506** of the component **500**. For example, the nozzle **130** (shown in FIG. 1) may spray the coupling medium **110** into the interior chamber **506** to fill and/or partially fill the interior chamber **506** with the coupling medium **110**. The probe **106** may be placed into contact with the exterior surface **502** (and/or in contact with the coupling medium **110** that is between the probe **106** and the exterior surface **502**). The probe **106** can then direct ultrasound pulses toward the interior chamber **506** to cause acoustic effects (e.g., cavitation) about the interior chamber **506**. The acoustic effects can include cavitation, oscillation, and/or vibration, and can remove the deposits **202** from the interior surface **504**. Acoustic effects (e.g., cavitation) can involve the generation and oscillation of bubbles (e.g., vacuum or gas-filled cavities) in the coupling medium **110**. The bubbles can act on and remove the deposits **202** from the surfaces of the equipment. In one aspect, the frequency of the ultrasound pulses may be limited to ensure that the bubbles are sufficiently small to remove the deposits. For example, the ultrasound pulses may be generated to have a frequency of at least 50 kHz (or another value).

In one embodiment, the controller **118** changes the frequency of the ultrasound pulses delivered by the probe **106** such that a thickness dimension **508** of the component **500** is an odd integer multiple of one half of the wavelength of the ultrasound pulse. Alternatively, the thickness dimension **508** may be an odd integer multiple of the wavelength of the ultrasound pulses. The thickness dimension **508** represents the distance between the exterior surface **502** and the interior surface **504**. Matching the wavelengths of the ultrasound pulses to the thickness dimension **508** of the component **500** can increase or maximize the ultrasound energy that is transmitted through the component **500** and create the oscillation strength needed to remove deposits **202** on the interior surfaces **504**. Propagation of the pulses incident on

the component **500** can cause a significant decrease in the pressure generated by the ultrasound pulses, such as the pressure gain decreasing by a factor of at least nine. But, by emitting the pulses such that the thickness dimension **508** is an odd integer multiple of a half wavelength of the pulses, the pressure generated by the pulses decreases, but by a smaller factor. For example, if the thickness dimension **508** is three millimeters, then the ultrasound pulses may have a wavelength of six millimeters in order to clean the interior surfaces **504** without the probe **106** entering into the interior chambers **506** of the equipment **102**. Using a low attenuation, high impedance coupling medium, such as gallium or gallium-indium alloy, reduces the dependence of the transmission coefficient on variations in the equipment wall thickness, due to manufacturing errors, wear during operations, or other factors. For example, if the ultrasound pulse has a wavelength of 6 millimeters and the equipment wall thickness is 2.7 millimeters, which is 10% different than the intended design value of 3 millimeters, the transmission coefficient will be 93% with a gallium-indium alloy used as a coupling medium, compared to 20% for a water coupling medium. The energy of the ultrasound pulses may be sufficiently low to prevent damage to interfaces, coatings, and the like, as described herein.

The controller **118** may direct the probe **106** to emit one or more investigative or diagnostic ultrasound pulses into the equipment **102**. These pulses are ultrasound pulses used for diagnostic and/or investigative purposes. For example, the pulses may be directed into the equipment **102** in order to identify and/or locate the presence of deposits **202** on the exterior and/or interior surfaces **502**, **504** of the equipment **102**. The probe **106** can emit the pulses into the equipment **102** and detect echoes of the pulses. Based on the echoes, the controller **118** can determine where deposits **202** are located. For example, the presence of the deposits **202** can change the echoes such that, for a clean component **500**, the echoes appear different than the echoes reflected off of a component **500** having deposits on the exterior and/or interior surfaces **502**, **504**. Optionally, the controller **118** may determine the thickness dimension **508** of the component **500** using the echoes. Different echoes may represent different thickness dimensions **508**, and the controller **118** can determine the thickness dimension **508** based on the received echoes. The controller **118** may then direct the probe **106** to emit the ultrasound pulses to remove the deposits **202** using the locations of the deposits **202** and/or the thickness dimensions **508** of the component **500** that are determined using the investigative pulses. Optionally, the diagnostic ultrasound pulses may have different frequencies than the cleaning ultrasound probes, which may be more suitable to locate and measure the thickness of the deposits. The diagnostic ultrasound pulses may also be emitted by a smaller probe that is concentric to the cleaning ultrasound probe and operates at the desired diagnostic frequencies. The smaller diagnostic probe may be placed inside a cut-out that is concentric to the cleaning ultrasound probe.

FIG. 6 illustrates a flowchart of one embodiment of a method **600** for cleaning equipment of a system. The method **600** may be used to clean the equipment **102** (e.g., an engine) while the equipment **102** remains coupled with a system, such as a vehicle (e.g., an aircraft). At **602**, an ultrasound probe is inserted into equipment while the equipment remains connected with a system that the equipment operates to power or provide work. For example, the probe **106** may be inserted into an engine while the engine remains connected with a wing of an aircraft or with another vehicle. At **604**, a coupling medium is delivered onto and/or into the

equipment. For example, a fluid may be sprayed onto an exterior surface of the equipment being cleaned, a fluid may be inserted into an interior chamber of the equipment being cleaned, a diaphragm that is at least partially filled with a fluid may be positioned between the probe and the equipment, etc.

At **606**, ultrasound pulses are emitted by the probe through the coupling medium to the equipment in order to remove deposits. The frequency and wavelength of the pulses may be controlled to remove deposits from exterior or interior surfaces of the equipment, as described above. In one embodiment, one or more pulses may be emitted and the echoes of the pulses examined in order to determine if deposits are present, to determine where the deposits are located, and/or to determine a thickness dimension of the equipment. As described above, the wavelength of the ultrasound pulses may be based on the thickness dimension so that the probe can remove the deposits from interior surfaces without the probe being located in the interior chambers of the equipment.

At **608**, a determination is made as to whether the deposit has been removed from the equipment. In one embodiment, an operator of the cleaning system may visually inspect the equipment with or without the aid of an optical sensor to determine if a deposit has been removed. Optionally, the ultrasound probe may emit investigative ultrasound pulses toward the location of a deposit and the echoes of the pulses may be examined to determine if the deposit has been removed. In another example, another type of sensor may be used. For example, a distance sensor (e.g., an eddy-current noncontact displacement position sensor) may be used to measure distances to the surfaces. If the deposits are present, then the measured distance will be smaller (due to the presence of the deposits) than surfaces that do not have the deposits. If the deposit has been removed, then flow of the method **600** may proceed toward **610**. If the deposit has not been removed, then cleaning of the equipment to remove the deposit may continue by flow of the method **600** returning toward **606**. At **610**, the probe may be moved to another location in order to clean one or more additional areas of the equipment. Flow of the method **600** may return toward **606** to clean the one or more additional areas. Alternatively, flow of the method **600** may terminate following **608**.

FIG. 7 illustrates a front view of a combination ultrasound probe **706** according to one embodiment. FIG. 8 illustrates a cross-sectional view of the ultrasound probe **706** shown along line 8-8 shown in FIG. 7 according to one embodiment. The probe **706** may represent one embodiment of the probe **106** shown in FIG. 1. The probe **706** includes different transducer portions **700**, **702**. The portions **700**, **702** represent different ultrasound transducer or groups of transducers that may be separately excited to emit ultrasound waves and to separately receive ultrasound echoes. The inner portion **700** may be smaller (e.g., in terms of surface area shown in FIG. 7) than the outer portion **702**. The inner portion **700** may be disposed inside the outer portion **702**, with the outer portion **702** extending or surrounding the outer perimeter or circumference of the inner portion **700**. The inner portion **700** may be excited to emit diagnostic ultrasound pulses and the outer portion **702** may be excited to emit cleaning ultrasound pulses from a common face or surface **800** of the probe **706**. The diagnostic ultrasound pulses may have different frequencies than the cleaning ultrasound pulses, and may be more suitable to locate and measure the thickness of the deposits. As shown in FIG. 7, the smaller portion **700** may be placed inside a cut-out or void that is concentric to the larger portion **702**.

In one embodiment, a cleaning system includes an ultrasound probe, a coupling mechanism, a scanning mechanism, and a controller. The ultrasound probe is configured to enter into an engine while the engine is one or more of coupled with or disposed within a vehicle. The ultrasound probe also is configured to emit an ultrasound pulse. The coupling mechanism is configured to provide an ultrasound coupling medium between the ultrasound probe and one or more components of the engine. The ultrasound probe is configured to be scanned, manually, automatically, or in a way that combines both manual and automatic scanning, to cover the region of deposits to be cleaned. The controller is configured to drive the ultrasound probe to deliver the ultrasound pulse through the coupling medium to a surface of the one or more components of the engine. The ultrasound probe is configured to deliver the ultrasound pulse to remove deposits from the one or more components of the engine while the engine is one or more of coupled with or disposed within the vehicle.

In one aspect, the ultrasound probe is configured to enter into the engine that is coupled with a wing of an aircraft.

In one aspect, the coupling mechanism is configured to provide the coupling medium between the ultrasound probe and one or more blades, nozzles, combustor liners, or compressor blades of the engine.

In one aspect, the surface of the one or more components of the engine is an external surface. The ultrasound probe can be a focused ultrasound probe configured to focus the ultrasound pulse toward the exterior surface of the one or more components of the engine.

In one aspect, the coupling mechanism includes a nozzle configured to supply the coupling medium onto the one or more components of the engine.

In one aspect, the coupling mechanism includes a diaphragm that is at least partially filled with the ultrasound coupling medium and that is configured to engage the one or more components of the engine between the ultrasound probe and the one or more components.

In one aspect, the ultrasound probe is configured to focus the ultrasound pulse toward the surface of the one or more components of the engine to remove the deposits while preventing removal of a thermal barrier coating on the one or more components of the engine.

In one aspect, the ultrasound probe is configured to be moved relative to the one or more components of the engine to remove the deposits from different areas of the one or more components.

In one aspect, the system also includes an optical sensor configured to generate optical data representative of the one or more components of the engine during removal of the deposits by the ultrasound probe.

In one aspect, the surface of the one or more components of the engine is an internal surface and the one or more components include an opposite external surface. The coupling mechanism can be configured to provide the coupling medium from the ultrasound probe to the external surface and the controller is configured to direct the ultrasound probe to focus the ultrasound pulse on the external surface of the one or more components of the engine to remove the deposits from the external surface.

In one aspect, the surface of the one or more components of the engine is an external surface and the one or more components include an opposite internal surface. The coupling mechanism can be configured to provide the coupling medium from the ultrasound probe to the external surface and the controller is configured to direct the ultrasound probe to focus the ultrasound pulse through the external

surface of the one or more components of the engine and onto the internal surface to remove the deposits from the internal surface.

In one aspect, the one or more components include an internal cavity that is at least partially bounded by the internal surface. The coupling mechanism also can be configured to at least partially fill the internal cavity with the ultrasound coupling medium or a different fluid.

In one aspect, the ultrasound probe is configured to direct the ultrasound pulse toward the internal cavity and cause acoustic effects (e.g., cavitation) about the internal cavity for removing the deposits from the internal surface.

In one aspect, the controller is configured to change a frequency of the ultrasound pulse delivered by the ultrasound probe based on a thickness of the one or more components between the internal surface and the external surface.

In one aspect, the controller is configured to change the frequency of the ultrasound pulse delivered by the ultrasound probe such that the thickness of the one or more components between the internal surface and the external surface is an odd integer multiple of half of an ultrasound wavelength in the ultrasound pulse.

In one aspect, the controller is configured to direct the ultrasound probe to emit an investigative pulse toward the one or more components of the engine and the ultrasound probe is configured to sense one or more echoes of the investigative pulse off of the one or more components of the engine.

In one aspect, the controller is configured to one or more of determine a thickness of the one or more components or determine a presence or absence of the deposits on the one or more components based on the one or more echoes.

In one aspect, the controller is configured to determine a frequency of the ultrasound pulse based on the one or more echoes.

In another embodiment, a method (e.g., for cleaning equipment of a system) includes inserting an ultrasound probe into an engine while the engine is one or more of coupled with or disposed within a vehicle, delivering an ultrasound coupling medium between the ultrasound probe and one or more components of the engine, and emitting an ultrasound pulse from the ultrasound probe and through the coupling medium to a surface of the one or more components of the engine. The ultrasound pulse removes deposits from the one or more components of the engine while the engine is one or more of coupled with or disposed within the vehicle.

In one aspect, the surface of the one or more components of the engine is an external surface, and emitting the ultrasound pulse includes focusing the ultrasound pulse toward the exterior surface of the one or more components of the engine.

In one aspect, delivering the ultrasound coupling medium includes spraying the coupling medium onto the one or more components of the engine.

In one aspect, delivering the ultrasound coupling medium includes engaging the surface of the one or more components of the engine with a diaphragm that is at least partially filled with the ultrasound coupling medium.

In one aspect, emitting the ultrasound pulse removes the deposits from the surface of the one or more components of the engine while preventing removal of a thermal barrier coating on the one or more components of the engine.

In one aspect, the method also includes moving the ultrasound probe relative to the one or more components of the engine to remove the deposits from different areas of the one or more components.

In one aspect, the method also includes obtaining optic data representative of the one or more components of the engine from an optical sensor during removal of the deposits by the ultrasound probe.

In one aspect, the surface of the one or more components of the engine is an internal surface and the one or more components include an opposite external surface. The coupling medium can be delivered onto the external surface and the ultrasound pulse is emitted toward the external surface of the one or more components of the engine to remove the deposits from the external surface.

In one aspect, the surface of the one or more components of the engine is an external surface and the one or more components include an opposite internal surface. The coupling medium can be delivered onto the external surface. Emitting the ultrasound pulse can include focusing the ultrasound pulse through the external surface of the one or more components of the engine and onto the internal surface to remove the deposits from the internal surface.

In one aspect, the one or more components include an internal cavity that is at least partially bounded by the internal surface. The method also can include at least partially filling the internal cavity with the ultrasound coupling medium or a different fluid.

In one aspect, emitting the ultrasound pulse includes directing the ultrasound pulse toward the internal cavity and creating acoustic effects (e.g., cavitation) about the internal cavity for removing the deposits from the internal surface.

In one aspect, the method also includes changing a frequency of the ultrasound pulse delivered by the ultrasound probe based on a thickness of the one or more components between the internal surface and the external surface.

In one aspect, the method also includes changing the frequency of the ultrasound pulse delivered by the ultrasound probe such that the thickness of the one or more components between the internal surface and the external surface is an odd integer multiple of half of an ultrasound wavelength in the ultrasound pulse.

In one aspect, the method also includes emitting an investigative pulse with the ultrasound probe toward the one or more components of the engine and sensing one or more echoes of the investigative pulse off of the one or more components of the engine.

In one aspect, the method includes one or more of determining a thickness of the one or more components or determining a presence or absence of the deposits on the one or more components based on the one or more echoes.

In one aspect, the method also includes determining a frequency of the ultrasound pulse based on the one or more echoes.

In another embodiment, a system (e.g., a cleaning system) includes an ultrasound probe and a controller. The ultrasound probe is configured to enter into equipment while the engine is coupled with or disposed within a vehicle system. The ultrasound probe also is configured to emit an ultrasound pulse. The controller is configured to drive the ultrasound probe to deliver the ultrasound pulse to a surface of the one or more components of the engine. The ultrasound probe also is configured to deliver the ultrasound pulse to remove deposits from the one or more components of the engine while the engine is one or more of coupled with or disposed within the vehicle.

In one aspect, the system also includes a coupling mechanism configured to provide an ultrasound coupling medium between the ultrasound probe and one or more components of the engine.

In one aspect, the ultrasound probe is configured to focus the ultrasound pulse toward the surface of the one or more components of the engine to remove the deposits while preventing removal of a thermal barrier coating on the one or more components of the engine.

In one aspect, the surface of the one or more components of the engine is an external surface and the one or more components include an opposite internal surface. The controller is configured to direct the ultrasound probe to focus the ultrasound pulse through the external surface of the one or more components of the engine and onto the internal surface to remove the deposits from the internal surface.

It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments (and/or aspects thereof) may be used in combination with each other. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the inventive subject matter without departing from its scope. While the dimensions and types of materials described herein are intended to define the parameters of the inventive subject matter, they are by no means limiting and are exemplary embodiments. Many other embodiments will be apparent to one of ordinary skill in the art upon reviewing the above description. The scope of the inventive subject matter should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Moreover, in the following claims, the terms “first,” “second,” and “third,” etc. are used merely as labels, and are not intended to impose numerical requirements on their objects. Further, the limitations of the following claims are not written in means-plus-function format and are not intended to be interpreted based on 35 U.S.C. § 112(f), unless and until such claim limitations expressly use the phrase “means for” followed by a statement of function void of further structure.

This written description uses examples to disclose several embodiments of the inventive subject matter and also to enable a person of ordinary skill in the art to practice the embodiments of the inventive subject matter, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the inventive subject matter may include other examples that occur to those of ordinary skill in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

The foregoing description of certain embodiments of the inventive subject matter will be better understood when read in conjunction with the appended drawings. To the extent that the figures illustrate diagrams of the functional blocks of various embodiments, the functional blocks are not necessarily indicative of the division between hardware circuitry. Thus, for example, one or more of the functional blocks (for example, processors or memories) may be implemented in a single piece of hardware (for example, a general purpose signal processor, microcontroller, random access memory, hard disk, and the like). Similarly, the programs may be stand-alone programs, may be incorporated as subroutines in

an operating system, may be functions in an installed software package, and the like. The various embodiments are not limited to the arrangements and instrumentality shown in the drawings.

As used herein, an element or step recited in the singular and proceeded with the word “a” or “an” should be understood as not excluding plural of said elements or steps, unless such exclusion is explicitly stated. Furthermore, references to “an embodiment” or “one embodiment” of the inventive subject matter are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Moreover, unless explicitly stated to the contrary, embodiments “comprising,” “including,” or “having” an element or a plurality of elements having a particular property may include additional such elements not having that property.

Since certain changes may be made in the above-described systems and methods without departing from the spirit and scope of the inventive subject matter herein involved, it is intended that all of the subject matter of the above description or shown in the accompanying drawings shall be interpreted merely as examples illustrating the inventive concept herein and shall not be construed as limiting the inventive subject matter.

As used herein, a structure, limitation, or element that is “configured to” perform a task or operation is particularly structurally formed, constructed, programmed, or adapted in a manner corresponding to the task or operation. For purposes of clarity and the avoidance of doubt, an object that is merely capable of being modified to perform the task or operation is not “configured to” perform the task or operation as used herein. Instead, the use of “configured to” as used herein denotes structural adaptations or characteristics, programming of the structure or element to perform the corresponding task or operation in a manner that is different from an “off-the-shelf” structure or element that is not programmed to perform the task or operation, and/or denotes structural requirements of any structure, limitation, or element that is described as being “configured to” perform the task or operation.

What is claimed is:

**1.** A system comprising:

- an ultrasound probe configured to enter into an engine;
- a coupling mechanism including a source of an ultrasound coupling medium, the source of the ultrasound coupling medium in fluid communication with an area between the ultrasound probe and a first surface of one or more components of the engine, the source of the ultrasound coupling medium configured to supply the ultrasound coupling medium to the area between the ultrasound probe and the first surface of one or more components of the engine; and

- a controller operably coupled to the ultrasound probe, the controller configured to operate the ultrasound probe to emit an investigative pulse or a diagnostic pulse and receive an echo thereof, the controller configured to determine a thickness between the first surface and a second surface of the one or more components of the engine based at least in part on the echo of the investigative pulse or the echo of the diagnostic pulse, the controller configured to drive the ultrasound probe to deliver an ultrasound pulse through the coupling medium and the first surface of the one or more components of the engine to the second surface of the

one or more components of the engine, the second surface of the one or more components of the engine including deposits, and

wherein the ultrasound probe is configured to remove the deposits from the second surface of the one or more components of the engine via the ultrasound pulse.

**2.** The system of claim **1**, wherein the coupling mechanism is configured to provide the ultrasound coupling medium between the ultrasound probe and one or more blades, nozzles, combustor liners, or compressor blades of the engine.

**3.** The system of claim **1**, wherein the controller is configured to change a frequency of the ultrasound pulse delivered by the ultrasound probe.

**4.** The system of claim **1**, wherein the coupling mechanism includes a diaphragm that is at least partially filled with the ultrasound coupling medium and that is configured to engage the one or more components of the engine between the ultrasound probe and the one or more components.

**5.** The system of claim **1**, wherein the ultrasound probe is configured to focus the ultrasound pulse toward the second surface of the one or more components of the engine to remove the deposits while preventing removal of a thermal barrier coating on the one or more components of the engine.

**6.** The system of claim **1**, further comprising an optical sensor configured to generate optical data representative of the one or more components of the engine during removal of the deposits by the ultrasound probe.

**7.** The system of claim **1**, wherein the ultrasound coupling medium includes a gallium-indium alloy.

**8.** The system of claim **1**, wherein the ultrasound coupling medium is disposed on a distal end of the ultrasound probe, the ultrasound coupling medium comprising gallium, gallium-indium alloy, or combinations thereof.

**9.** The system of claim **1**, wherein the one or more components include an internal cavity that is at least partially bounded by an internal surface, and the internal cavity is at least partially filled with the ultrasound coupling medium or a different fluid.

**10.** The system of claim **9**, wherein the ultrasound probe is configured to direct the ultrasound pulse toward the internal cavity and create acoustic effects about the internal cavity for removing the deposits within the internal cavity.

**11.** The system of claim **1**, wherein the controller is configured to change a frequency of the ultrasound pulse delivered by the ultrasound probe based on the determination of the thickness.

**12.** The system of claim **11**, wherein the controller is configured to change the frequency of the ultrasound pulse such that the thickness of the one or more components is one half of a wavelength of the ultrasound pulse.

**13.** The system of claim **11**, wherein the controller is configured to change the frequency of the ultrasound pulse such that the thickness of the one or more components is an odd integer multiple of a wavelength of the ultrasound pulse.

**14.** The system of claim **1**, wherein the ultrasound probe comprises an inner transducer portion configured to emit a diagnostic pulse and an outer transducer portion configured to emit the ultrasound pulse, and wherein the ultrasound probe is configured to emit a diagnostic pulse from the inner transducer portion at a frequency different from the ultrasound pulse, to locate and measure a thickness of the deposits.