



(51) International Patent Classification:
E01H 4/02 (2006.01)

(21) International Application Number:
PCT/IB2017/052021

(22) International Filing Date:
7 April 2017 (07.04.2017)

(25) Filing Language: Italian

(26) Publication Language: English

(30) Priority Data:
102016000035923 7 April 2016 (07.04.2016) IT

(71) Applicant: PRINOTH S.P.A. [IT/IT]; Via Brennero, 34, 39049 Vipiteno (IT).

(72) Inventors: SAGGIORATO, Luca; c/o PRINOTH S.P.A., Via Brennero, 34, 39049 Vipiteno (IT). UNTERHOLZNER, Markus; c/o PRINOTH S.P.A., Via Brennero, 34, 39049 Vipiteno (IT). BAIER, Stefan; c/o PRINOTH S.P.A., Via Brennero, 34, 39049 Vipiteno (IT).

(74) Agents: ECCETTO, Mauro et al.; c/o Studio Torta S.p.A., Via Viotti, 9, 10121 Torino (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: EQUIPMENT FOR CREATING A CROSS-COUNTRY SKI TRAIL




FIG. 1

(57) Abstract: Equipment for creating a cross-country ski trail for a vehicle; comprising a tracker device (3) to form tracks (4) in a snow cover (N); and a connection structure (19; 119; 219) for coupling the tracker device (3) to a first tiller (2) or to the vehicle (8); the connection structure (19; 119) and the tracker device (3) being connected to each other in a jointed manner around a first axis (V) incident with the snow cover (N) or the ground, preferably transverse to a feed direction (D1).

"EQUIPMENT FOR CREATING A CROSS-COUNTRY SKI TRAIL"TECHNICAL FIELD

The present invention relates to equipment for creating a cross-country ski trail, in particular a classic style cross-country ski trail.

BACKGROUND ART

The known pieces of equipment comprise a tracker device comprising at least one track-setter configured for creating tracks into the snow. A track for cross-country ski is a groove with a flat bottom face, two flared side faces, and having the function of guiding a ski. A track is formed by compressing the track-setter on the snow cover and simultaneously advancing the track-setter along a given path. In essence, the snow cover is locally compacted and deformed at each track by means of the track-setter.

Depending on the characteristics of the snow cover and to facilitate the forming of the tracks, the snow cover can be pre-treated by means of a main tiller having the purpose to groom the snow before the tracker device forms the tracks so as to facilitate the forming of the tracks. Depending on the environmental conditions, sometimes, it may be useful to groom a more or less shallow surface layer of the snow cover before forming the tracks, other times it is not necessary. The characteristics of the snow cover, in fact, vary considerably depending on the environmental conditions. In other words, the snow cover can be soft or compact or with a hard surface crust and relatively soft on the inside, just to name some of the features that the snow cover can assume depending on the temperature, the humidity, and the thermal excursion. The forming of the tracks and the structure thereof can be strongly influenced by the variability of the characteristics of the snow cover.

The known pieces of equipment do not allow a high quality level to be obtained for classic style cross-country ski trails and high advancing speed for all types of snow cover.

5

DISCLOSURE OF INVENTION

An object of the present invention is to provide equipment for creating a cross-country ski trail that would reduce the drawbacks of the known art.

10

According to the present invention equipment for creating a cross-country ski trails for a vehicle is provided; comprising a tracker device to form tracks in a snow cover; and a connection structure for coupling the tracker device to a first tiller or to the vehicle; the connection structure and the tracker device being connected to each other in a jointed manner around a first axis incident with the snow cover or the ground, preferably transverse to a feed direction.

20

Thanks to the present invention, the position of the tracker device is obtained in a jointed manner with respect to the tiller or to the vehicle around the first axis incident with the snow cover and this allows to have the best track quality in particular in a curved direction. In fact, the tracker device can better follow the curves or the inexactness of the snow cover and ensure tracks of better quality.

25

30

In other words, this allows a greater adaptability to the conditions of the snow cover and consequently a better quality for the cross-country ski trails.

In particular, in a first embodiment, the tracker device comprises a slide which forms tracks in the snow cover and an auxiliary tiller connected in a non-revolving manner around the first axis and in a revolving manner around a second axis

35

incident with the first axis and parallel to the snow cover. In this way, the slide forms the tracks where the auxiliary tiller has worked the snow because the revolving movements around the first axis of the auxiliary tiller and the slide are integral one with the other and, at the same time, the slide and auxiliary tiller can adapt to bumps or other snow cover contours in an independent manner.

In another embodiment, the equipment comprises the first slide and the tracker device and is connected in a revolving manner with respect to the first slide around the first axis due to a joint and around a second axis, incident with the first axis and preferably parallel to the snow cover by means of at least another joint.

In an embodiment, the equipment comprises the first tiller; the tracker device is connected to the first tiller by means of a jointed quadrilateral which allows revolving movements around a second axis incident with the first axis and preferably parallel to the snow cover.

In another embodiment, the equipment comprises the first tiller; the tracker device being connected to the first tiller by means of three joints and an actuator connected between two of the three joints; the three joints extend along a second axis incident with the first axis and preferably parallel to the snow cover.

In another embodiment, the equipment comprises the first tiller; the tracker device being connected in a non-revolving manner to the first tiller around a second axis incident with the first axis and preferably parallel to the snow cover.

BRIEF DESCRIPTION OF THE DRAWINGS

Further features and advantages of the present invention will become apparent from the following description of a non-limiting

embodiment thereof, with reference to the figures of the accompanying drawings, wherein:

Figure 1 is a perspective view, with parts removed for clarity, of equipment to form tracks for a cross-country ski trail according to a first embodiment of the present invention;

Figure 2 is a side elevation view, with parts removed for clarity, of the equipment of Figure 1 in a first operating configuration;

Figure 3 is a sectional view according to the section plan III-III, with parts removed for clarity, of Figure 2;

Figure 4 is a side elevation view, with parts removed for clarity, of equipment to form tracks for a cross-country ski trail according to a second embodiment of the present invention; and

Figure 5 is a side elevation view, with parts removed for clarity, of equipment to form tracks for a cross-country ski trail according to a third embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Referring to Figures 1 and 2, 1 denotes as a whole equipment for creating a cross-country ski trail, in particular classic style cross-country ski trail. In the case illustrated in Figure 1, the equipment 1 comprises a support structure 71 configured to support the equipment 1; a snow-tiller 2 supported by the support structure 71; two tracker devices 3 each forming, two tracks 4 parallel to a direction D1 corresponding to the feed direction of the equipment 1; and a connection structure 19 configured to connect the tracker devices 3 to the tiller 2 in a jointed manner so as to allow a rotation around an axis transverse to the direction D1 of the tracker devices 3 with respect to the tiller 2. In particular, the connection structure 19 connects the tracker devices 3 to the tiller 2 in a jointed manner with respect to an axis V which is transverse to the direction D1 and transverse to the snow cover N.

In particular, the axis V forms with the snow cover N or with the ground an angle ranging between 60° and 120° ; preferably between 60° and 90° , in particular between 75° and 90° . In a preferred embodiment, the axis V is perpendicular to the snow cover N or to the ground.

In addition, the connection structure 19 connects the tracker devices 3 to the tiller 2 in a jointed manner with respect to an axis O, which is transverse to the feed direction D1, in particular perpendicular; and parallel to the snow cover N, in particular not transverse to the snow cover N. Accordingly, the connection structure 19 connects the tracker devices 3 to the tiller 2 in a jointed manner around two axes incident one with the other, preferably perpendicular; in particular the two axes are the axis V and the axis O.

For the connection in a jointed manner of two devices around an axis it is meant that the two devices can rotate one with respect to the other around said axis.

The number of two tracker devices is purely indicative and the present invention relates to a single tracker device or to a machine provided with more than two tracker devices.

In greater detail, each track 4 is substantially defined by means of a groove having a cross section substantially shaped as an isosceles trapezoid.

The equipment 1 is towed by a vehicle 8 and is connected to the vehicle 8 by means of the support structure 71. In greater detail, the support structure 71 comprises a connection unit 71a so as to be connected to vehicle 8. The vehicle 8 is preferably, but not limited to, a tracked vehicle, in particular a snow groomer.

With reference to Figure 2, the tiller 2 comprises a frame 5, a

shaft 6, a case 7 arranged around the shaft 6, and a mat 7a made of a flexible material.

5 The shaft 6 is mounted in a revolving manner around an axis A and is provided with teeth 9.

10 The tiller 2 is supported by the support structure 71. In particular, the tiller 2 is connected to the support structure 71 by means of the connection structure 19.

15 The connection structure 19 comprises a joint 19a, a joint 19b, a joint 19c, a joint 19d, an arm 19e which connects the joint 19a and the joint 19b, an arm 19f which connects the joint 19b to the joint 19c, and a guide 10.

20 The joint 19a extends parallel to the axis O and allows revolving movements around the axis O.

The joint 19b extends parallel to the axis O and allows revolving movements around the axis O.

The joint 19c extends parallel to the axis O and allows revolving movements around the axis O.

25 The joint 19d extends along the axis O and allows revolving movements around the axis O.

30 The axis O is parallel to the snow cover N or to the ground, i.e. not transverse to the snow cover N or to the ground.

The axis O is transverse to the feed direction D1 in particular perpendicular to the feed direction D1.

35 The frame 5 of the tiller 2 is directly connected to the support structure 71 by means of the joint 19a. Furthermore, the arm 19e is connected to the joint 19a and to the support structure 71.

The frame 5 of the tiller 2 is connected to the support structure 71, to the joint 19b of the support structure 71.

5 The equipment 1 comprises an actuator 50 which connects the joint 19b to frame 5 of the tiller 2 and is configured to vary its length. In greater detail, the actuator 50 is connected to the joint 19b and to the frame 5 at a connecting point 50a differing from the joint 19a. Consequently, the distance between the frame 5 and the joint 19b can selectively vary depending on
10 the variable length of the actuator 50.

The inclination of the tiller 2 with respect to a snow cover N can be varied by acting on a position of the connecting structure 71 and on the length of the actuator 50 which varies a
15 configuration of the connection structure 19.

With reference to Figure 1, the guide 10 of the connection structure 19 is substantially parallel to the axis A and/or to the axis O. The two tracker devices 3 are mounted in a sliding
20 manner along the guide 10. Furthermore, the guide 10 is connected by means of an arm 10a to the joint 19c and by means of an arm 10b to the joint 19d.

In greater detail, the guide 10 is connected to the tiller 2 in
25 the joint 19d. In particular, the guide 10 is connected to the frame 5 of the tiller 2 by means of the joint 19d of the connection structure 19.

With reference to Figures 1 and 2, each tracker device 3
30 comprises a support structure 11, which is coupled to the connection structure 19; an actuator 15; a slide 16; and a tiller 20.

Referring to Figures 2 and 3, the connection structure 19
35 comprises a joint SV which develops along the axis V and allows rotations around the axis V. In greater detail, the joint SV is

arranged between the support structure 11 of the tracker device 3 and the guide 10 of connection structure 19.

Referring to Figure 3, the connection structure 19 comprises two elastic elements 40 arranged between the tracker device 3 and the connection structure 19 so as to force, due to the elastic force exerted by the same and within the limits thereof, the tracker device 3 in a main position. The main position is preferably in axis with the feed direction. In particular, the two elastic elements 40 are arranged between the support structure 11 and the guide 10 from opposite sides with respect to the joint SV. In particular, the elastic elements 40 are made of an elastomeric material and also have the purpose of acting as a stop device.

The elastic elements can be made with a spring or other element having an elastic force. The elastic elements can also be defined by means of a single elastic element, for example a spring connected between the guide 10 and the support structure 11. The springs can be gas, pneumatic, mechanic actuated or of any other type.

Furthermore, each tracker device 3 is connected to the tiller 2 by means of the connection structure 19 so as to allow a free rotation around the axis O with respect to the tiller 2.

Each tracker device 3 is connected to the support structure 71 by means of the connection structure 19 so as to allow a free rotation around the axis O with respect to the support structure 71.

In addition, each tracker device 3 is connected to the tiller 2 by means of the connection structure 19, in particular by means of the joint SV, so as to allow a rotation around the axis V with respect to the tiller 2.

Each tracker device 3 is connected to the support structure 71

by means of the connection structure 19, in particular by means of the joint SV, so as to allow rotation around the axis V with respect to the support structure 71.

5 Each connection structure 19 comprises a slider 13 engaged with the guide 10.

Each support structure 11 comprises a central body 11a hinged to the slider 13 by means of the joint SV. Each support structure
10 11 comprises an elongated portion 14 hinged to the central body 11a by means of a joint 14a which develops along an axis parallel to the axis O. The actuator 15 is arranged between the central body 11a and the elongated portion 14 to selectively arrange the
15 elongated portion 14 in a working position, in which the tracker device 3 is in contact with the snow cover N and creates the tracks 4; and a rest position in which the tracker device 3 is raised from the snow cover N and does not create the tracks 4. In other words, the actuator 15 controls the rotation of the elongated portion 14 with respect to the central body 11a around
20 the axis O.

In the attached figures, the tracker device 3 is always in the working position. In greater detail, the elongated portion 14 is connected to the central body 11a in a joint 14a. The joint
25 14a is secured to the actuator 15. In other words, the rotation of the elongated portion 14 with respect to the central body 11a is obtained by the intervention of the actuator 15 and is not free.

30 With reference to Figures 1 and 2, the slide 16 is connected to the support structure 11 and is defined by means of a plate having a lower surface 17 flat and slightly curved upwards at the front edge; two track-setters 18, which are connected to the slide 16, protrude downwardly from the lower surface of slide
35 16 and are arranged at the rear edge of the slide 16. The two track-setters 18 define a work surface on which the tracks 4v

are formed. The work plane is parallel to the snow cover and in use it is superimposed on the snow cover N. The axis O is not incident with, in particular is parallel to the work plane. The axis V is incident with the work plane, in particular is perpendicular to the work plane.

The tiller 20 is coupled to the support structure 11. In particular, the tiller 20 is coupled to the elongated portion 14 by means of an arm 12 in a joint 12a and to the central body 11a of the support structure 11 in a joint 11b. The central body 11a is connected to the slider 13. The joints 12a and 11b extend along respective axes parallel to the axis O.

In the embodiment illustrated in Figure 1, the equipment 1 comprises an actuator 22 which is adapted to move the slider 13 along the guide 10 and to adjust the distance between the tracker devices 3 in a direction transverse to the direction D1. In another embodiment, not illustrated in the accompanying figures, the actuator 22 is omitted.

In an optional embodiment of the present invention, the tracker device 3 comprises two blades 23 (illustrated in Figure 2 with dashed lines) connected to a frame 20a of the tiller 20. The blades 23 are arranged between the tiller 20 and the tiller 2 in this case, each blade 23 is aligned with a track-setter 18.

The blade 23 has slightly greater dimensions than the size of the track-setters 18 and separates an elongated and continuous portion of snow cover N from the remaining part of the snow cover N. In use, the tiller 2 works a wide strip of snow cover N at a reduced depth, whereas the tillers 20 work on strips having a reduced width at a greater depth. The separation of the elongated and continuous portion results in a crumbling effect of the elongated and continuous portion which facilitates the forming of the track 4.

Each track-setter 18 is dragged along an elongated and continuous portion and compresses the snow cover N of said elongated and continuous portion thanks to the compression action exerted by the actuator 15.

5

The connection structure 19 defines a jointed quadrilateral for each tracker device 3 which connects the tracker device 3 with the tiller 2 and with the support structure 71. The jointed quadrilateral is formed by the joints 19a, 19b, 19c and 19e, by the elements 19e and 19f, by a frame portion 5 of the tiller 2 interposed between the joint 19a and the joint 19d, and by the arms 10a, 10b and the guide 10 interposed between the joint 19c and the joint 19d. The joints 19a, 19b, 19c and 19e extend parallel to the axis O and allow rotations around the axis O.

10

15

In addition, the connection structure 19 by means of the joint SV allows rotation of the tracker devices 3 comprising the slide 16 and the tiller 20 with respect to the tiller 2 around the axis V.

20

In other words, the slide 16 and the tiller 20 are connected to each other in a revolving manner around an axis parallel to the axis O which in turn is parallel to the snow cover N. The slide 16 and the tiller 20 are connected to each other in a non-revolving manner around the axis V, in other words the revolving movements of the slide 16 and of the tiller 20 around the axis V are integral one with the other.

25

Furthermore, the slide 16 and the tiller 20 are integral one with the other around the axis V and are connected in a revolving manner around the axis V with respect to the tiller 2 or to the vehicle 8. This allows the slide 16 to form the tracks where the tiller 20 has worked the snow cover N and there is no misalignment between the slide 16 and the tiller 20 whereas a misalignment between slide 16 and tiller 2 or between tiller 20 and tiller 2 is allowed. In this way, the slide 16 and the tiller 20 can work better in a curved direction and form tracks 4 with

30

35

better curved profiles with respect to the known art and at the same time ensure that the slide 16 forms the tracks 4 where the tiller 20 has worked the snow cover N. Finally, the tracker device 3 comprising the tiller 20 and the slide 16 does not make abrupt revolving movements around the axis V due to the elastic elements 40.

Furthermore, thanks to the present invention, the position of the tiller 2 with respect to the snow cover N can be varied by means of the actuator 50 and/or the position of the support structure 71 without varying the position of the tiller 20 with respect to the snow cover N. In fact, the position of the tiller 2 can vary from a first operating position to a second operating position based on the position of the support structure 71 and of the actuator 50, but the position of the tiller 20 with respect to the snow cover N does not vary due to the jointed connection around the axis O provided by the connection structure 19. In other words, the connection structure 19 provides a freely jointed connection around the axis O between the tiller 2, the support structure 71, and the tracker device 3. Consequently, the position of the tracker device 3 is not changed by the position of the tiller 2 and can be adjusted by means of the actuator 15 acting on the elongated portion which is connected to the central body 11a of the support structure 11.

The connection structure 19 provides a jointed connection around the axis O and around the axis V, significantly improving the working of the snow cover N so that the tracker device 3 can perfectly follow the conformation of the snow cover N.

Referring to Figure 4, number 101 denotes a second embodiment of equipment for creating a cross-country ski trail, alternative to the equipment 1. In the case illustrated in Figure 4, the equipment 101 comprises a support structure 171 configured to support the equipment 101; a tiller 2 supported by the support

structure 171; four tracker devices 3 (only one visible in Figure 4) each forming, two tracks 4 parallel to a direction D1 corresponding to the feed direction of the equipment 1; and a connection structure 119 configured to connect the tracker devices 3 to the tiller 2 in a jointed manner to allow a rotation around an axis transverse to the direction D1 of the tracker devices 3 with respect to the tiller 2.

In particular, the connection structure 119 connects the tracker devices 3 to the tiller 2 in a jointed manner with respect to an axis V which is transverse to the direction D1, preferably perpendicular; and transverse to the snow cover N, preferably perpendicular to the snow cover.

In addition, the connection structure 119 connects the tracker devices 3 to the tiller 2 in a jointed manner with respect to an axis O which is transverse to the feed direction D1, in particular perpendicular; and parallel to the snow cover N, in particular non-transverse to the snow cover N. Accordingly, the connection structure 119 connects the tracker devices 3 to the tiller 2 in a jointed manner around two axis incident with one another, preferably perpendicular; in particular the two axes are the axis V and the axis O.

The number of four tracker devices is purely indicative and the present invention refers to any number of tracker devices from one to more than four.

The equipment 101 is towed by a vehicle 8 (not shown in Figure 4) and is connected to vehicle 8 by means of the support structure 171.

The tiller 2 and the tracker devices 3 of the equipment 101 are made in the same manner as those of the equipment 1 and are illustrated with the same numbers and not further described.

The equipment 101 differs from the equipment 1 mainly in the connection structure 119.

The tiller 2 is supported directly by the support structure 171.

5 The frame 5 of the tiller 2 is directly connected to the support structure 171 at a connection point.

In addition, the tracker devices 3 are connected to the tiller 2 by means of the connection structure 119 and are not directly
10 connected to the support structure 171. In other words, in the equipment 101, unlike the equipment 1, the tracker devices 3 are only connected to the tiller 2 by means of the connection structure 119.

15 The connection structure 119 comprises a guide 110; and an elongated element 119f connected along the frame 5 of the tiller 2. Furthermore, the connection structure 119 comprises a joint 119a, a joint 119b and a joint 119c. The joint 119a and the joint 119b are connected to the elongated element 119f of the
20 connection structure 119.

The joint 119a extends parallel to the axis O and allows revolving movements around the axis O.

25 The joint 119b extends along the axis O and allows revolving movements around the axis O.

The joint 119c extends parallel to the axis O and allows revolving movements around the axis O.

30

In addition, the equipment 101 comprises an actuator 150 which is interposed between the joint 119a at the joint 119c and connects the same. The actuator 150 is selectively adjustable in length, therefore the distance between the joint 110a and the
35 joint 119c is variable. Thus, the distance between the tiller 2 and the tracker devices 3 can be selectively varied according

to the variable length of the actuator 150.

The inclination of the tiller 2 with respect to a snow cover N can be varied by acting on a position of the support structure 171.

With reference to Figure 4, the guide 110 of the connection structure 119 is substantially parallel to the axis A and/or to the axis O. Along the guide 110, tracker devices 3 are mounted in a sliding manner. In addition, the guide 110 is connected, by means of an arm 110a, to the joint 119c in and from an arm 110b to the joint 119b.

In greater detail, the guide 110 is connected to the tiller 2 directly by means of the joint 119b and by means of the actuator 150 by means of the joint 119c. In particular, the guide 110 is only connected to the frame 5 of the tiller 2.

Moreover, each tracker device 3 is connected to the tiller 2 by means of the connection structure 119 so as to allow a free rotation around the axis O and around the axis V with respect to the tiller 2.

In greater detail, the connection structure 119 comprises a joint SV (equal to the joint SV of the connection structure 19) which extends along the axis V and allows rotations around the axis V.

In greater detail, the joint SV is arranged between the support structure 11 of the tracker device 3 and the guide 110 of the connection structure 119. The connection structure 119 comprises two elastic devices arranged between the tracker 3 and the connection structure 19 and arranged on opposite sides with respect to the joint SV as in the case of the connection structure 19.

The connection structure 119 defines a three-sided structure, in which the length of one of the sides is variable for each tracker device 3 that connects the tracker device 3 with the tiller 2 by means of the guide 110. The three-sided structure is formed by the joints 119a, 119b, 119c, by the elements 119f, by the guide 110, by the arms 110a and 110b of the guide 110, and by the actuator 150.

Consequently, each tracker device 3 is connected to the tiller 2 by means of the connection structure 119 so as to allow revolving movements around the axis O, based on the position of the actuator 150, due to the joints 119a, 119b and 119c.

Furthermore, each tracker device 3 is connected to the tiller 2 by means of the connection structure 119 so as to allow revolving movements around the axis V by means of the joint SV. In particular, as in the case of the equipment 1, the tiller 20 and the slide 16 are connected in a revolving manner around the axis O and in a non-revolving manner one with the other around the axis V. In other words, the revolving movements of the slide 16 and of the tiller 20 around the axis V are integral with each other. In addition, the slide 16 and the tiller 20 can perform revolving movements around the axis V with respect to the tiller 2 of the equipment 101.

Furthermore, the position of the tiller 2 with respect to the snow cover N can be varied due the actuator 150, without changing the position of the tiller 20 with respect to the snow cover N. In fact, the position of the tiller 2 can vary from a first operating position to a second operating position, but the position of the tiller 20 with respect to the snow cover N does not vary due to the variation of the length of the actuator 150 which compensates for the variation in the position of the tiller 2. In other words, the connection structure 119 provides a jointed connection between the tiller 2 and the tracker device 3 around the axis O, based on the position of the actuator 150,

and around the axis V. The distance of the tracker device 3 from the snow cover N, consequently, is not changed by the position of the tiller 2 and can be adjusted by means of the actuator 15 acting on the elongated portion 14 which is connected to the slider 13 of the support structure 11.

In an embodiment of the present invention not illustrated in the accompanying figures, the equipment 101 comprises a control unit which acts on the actuator 150 to adjust the length of the actuator 150 and on the support structure 171 for the position of the support structure 171 and consequently the position of the tiller 2. In other words, the movement of the support structure 171 and the movement of the actuator 150 are controlled by the control unit synchronously to ensure that when the position of the support structure 171 varies, in order to vary the position of the tiller 2, the position of the tracker device 3 does not vary. In other words, due to the control unit which simultaneously controls both the position of the support structure 171 and the actuator 150 the position of the tracker device 3 is independent of the position of the tiller 2.

With reference to Figure 5, number 201 denotes a third embodiment of equipment for creating a cross-country ski trail, as an alternative to the equipment 1. In the case illustrated in Figure 5, the equipment 201 comprises a support structure 271 configured to support the equipment 201; a snow-tiller 2 supported by the support structure 271; Two tracker devices 3 (only one is visible in Figure 5) each forming, two tracks 4 parallel to a direction D1 corresponding to the feed direction of the equipment 1; and a connection structure 219 configured to connect the tracker devices 3 to the tiller 2 in a jointed manner so as to allow a rotation around an axis transverse to the direction D1 of the tracker devices 3 with respect to the tiller 2.

In particular, the connection structure 219 connects the tracker

devices 3 to the tiller 2 in a jointed manner with respect to an axis V which is transverse to the direction D1, preferably perpendicular; and transverse to the snow cover N, preferably perpendicular to the snow cover N.

5

In addition, the connection structure 219 connects the tracker devices 3 to the tiller 2 in a non-jointed manner around the axis A by means of the arm 210b.

10 The equipment 201 is towed by a vehicle 8 (not shown in Figure 5) and is connected to the vehicle 8 by the support structure 271.

The tiller 2 and the tracker devices 3 of the equipment 201 are
15 made in the same manner as those of the equipment 1 and are illustrated with the same numbers and not further described.

The equipment 201 differs from the equipment 1 mainly in connection structure 219.

20

The tiller 2 is supported directly by the support structure 271. The frame 5 of the tiller 2 is directly connected to the support structure 271 at a connection point.

25 In addition, the tracker devices 3 are connected to the tiller 2 by means of the connection structure 219 and are not directly connected to the support structure 271. In other words, in the equipment 201, unlike the equipment 1, the tracker devices 3 are only connected to the tiller 2 by means of the connection
30 structure 219.

The connection structure 219 comprises a guide 210.

The connection structure 219 comprises a joint 219a, a joint
35 219b, an arm 19e which connects the joint 19a and the joint 19b, and the guide 210.

The joint 219a extends parallel to an axis O and allows revolving movements around the axis O.

5 The joint 219b extends parallel to the axis O and allows revolving movements around the axis O.

The axis O is parallel to the snow cover N or the ground, i.e. is not transverse to the snow cover N or to the ground.

10

The axis O is transverse to the feed direction D1 in particular perpendicular to the feed direction D1.

15 The frame 5 of the tiller 2 is directly connected to the support structure 71 by means of the joint 219a. In addition, the arm 219e is connected to the joint 219a and to the support structure 271. The frame 5 of the tiller 2 is connected to the support structure 271 to the joint 219b of the support structure 271.

20 The equipment 1 comprises an actuator 250 which connects the joint 219b to the frame 5 of the tiller 2 and is configured to vary its length. In greater detail, the actuator 250 is connected to the joint 219b and to the frame 5 at a connection point 250a other than the joint 219a. Consequently, the distance between
25 the frame 5 and the joint 219b can vary according to the variable length of the actuator 250.

The inclination of the tiller 2 with respect to a snow cover N can be varied by acting on a position of the support structure
30 271 and on the length of the actuator 250 which varies a configuration of the connection structure 219.

The guide 210 of the connection structure 219 is substantially parallel to the axis A and/or the axis O. The two tracker devices
35 3 are mounted in a sliding manner along the guide 210. The guide 10 is also connected by means of an arm 210b of the connection

structure 219 to the tiller 2.

In particular, the guide 210 is connected to the frame 5 of the tiller 2 by means of the arm 210b of the connection structure 19 in an integral manner.

Furthermore, each tracker device 3 is connected to the tiller 2 by means of the connection structure 119 so as to allow a free rotation around the axis V with respect to the tiller 2.

10

In greater detail, the connection structure 119 comprises a joint SV (equal to the joint SV of the connection structure 19) which develops along the axis V and allows rotations around the axis V.

15

In greater detail, the joint SV is arranged between the support structure 11 of the tracker device 3 and the guide 210 of the connection structure 219. The connection structure 219 comprises two elastic devices arranged between the tracker 3 and the connection structure 219 and arranged on opposite sides with respect to the joint SV as in the case of the connection structure 19.

In addition, each tracker device 3 is connected to the tiller 2 by means of the connection structure 219 so as to allow revolving movements around the axis V, due to the joint SV. In particular, as in the case of the equipment 1, the tiller 20 and the slide 16 are connected to each other in a revolving manner around the axis O and to each other in a non-revolving manner around the axis V. In other words, the revolving movements of the slide 16 and of the tiller 20 around the axis V are integral one with the other. In addition, the slide 16 and the tiller 20 can perform integral and revolving movements together around the axis V with respect to the tiller 2 of the equipment 201.

35

Thanks to the present invention, the tiller 20 and the slide 16

in a curved direction define the tracks 4 having improved profiles with respect to the known art and is ensured that the slide 16 works a portion of the snow cover N which has been previously worked by the tiller 20.

5

As mentioned above and for all the embodiments, the slide 16 defines a work plane (corresponding to a plane on which it forms the tracks 4). In an embodiment, applicable to all the pieces of equipment described above, therefore to the equipment 1, to the equipment 101 and to the equipment 201, the axis V is incident with the work plane defined by the slide 16. In particular, the axis V forms with the work plane an angle of between 60° and 120° ; preferably between 60° and 90° , in particular between 75° and 90° .

15

It is finally apparent that modifications and alternatives can be made to the equipment without departing from the scope of the accompanying claims.

CLAIMS

1. Equipment for creating a cross-country ski trail for a vehicle; the equipment comprising a tracker device (3) to form tracks (4) in a snow cover (N); and a connection structure (19; 119; 219) for coupling the tracker device (3) to a first tiller (2) or to the vehicle (8); the connection structure (19; 119) and the tracker device (3) being connected to each other in a jointed manner around a first axis (V) incident with the snow cover (N) or the ground, preferably transverse to a feed direction (D1).

2. Equipment according to claim 1; wherein the first axis (V) defines with the snow cover (N) or with the ground an angle of between 60° and 120° ; preferably between 60° and 90° , in particular between 75° and 90° .

3. Equipment according to any one of the preceding claims; the tracker device (3) being connected to the connection structure (19; 119; 219) by means of a first joint (SV) which develops along the first axis (V) and which allows revolving movements around the first axis (V).

4. Equipment according to any one of the preceding claims; wherein the connection structure (19; 119; 219) comprises at least one elastic element (40) arranged between the connection structure (19; 119; 219) and the tracker device (3) to force the tracker device (3) into a first position.

5. Equipment according to any one of the preceding claims; wherein the connection structure (19; 119; 219) comprises a fixed element (10); the tracker device (3) having a support structure (11) connected in a jointed manner to the fixed element (10) around the first axis (V); the elastic element (40) being interposed between the fixed element (10) and the support structure (11); preferably the connection structure (19; 119; 219) comprising a further elastic element (40) and the two elastic elements (40) being housed on opposite sides of the first joint (SV).

6. Equipment according to any one of the preceding claims; wherein the tracker device (3) comprises a slide (16)

configured to form tracks (4) in the snow cover (N) and a second tiller (20) connected to each other in a non-revolving manner around the first axis (V).

7. Equipment according to claim 6, wherein the slide (16) and the second tiller (20) are connected to each other in a revolving manner around a second axis (O) incident with the first axis (V), the second axis (O) being preferably parallel to the snow cover (N).

8. Equipment according to any one of the preceding claims, comprising the first tiller (2); wherein the connection structure (19; 119; 219) is connected to the first tiller (2), in particular the connection structure (19; 119; 219) connects the tracker device (3) to the first tiller (2) in a jointed manner around the first axis (V).

9. Equipment according to any one of the preceding claims, comprising the first tiller (2); wherein the connection structure (19; 119; 219) is connected to the first tiller (2), in particular the connection structure (19; 119; 219) connects the tracker device (3) to the first tiller (2) in a jointed manner around a second axis (O) incident with the first axis (V); the second axis being preferably parallel to the snow cover (N).

10. Equipment according to any one of the preceding claims; comprising a support structure (71; 171; 271) configured to connect the equipment (1; 101; 201) to the vehicle; the connection structure (19; 119; 219) comprising a second joint (19a; 119a; 219a) which extends parallel to a second axis (O) incident with the first axis (V); the connection structure (19; 119; 219) being connected to the support structure (71; 171; 271) by means of the second joint (19a; 119a; 219a) in a revolving manner around the second axis (O).

11. Equipment according to any one of the preceding claims; the connection structure (19; 119; 219) comprising a third joint (19d; 119b) which extends along a second axis (O) incident with the first axis (V) and preferably parallel to the snow cover (N) to connect the equipment (1) to the vehicle in a

revolving manner around the second axis (O).

12. Equipment according to any one of the preceding claims; wherein the tracker device (3) comprises a support structure (11) and a slide (16); the support structure (11) being connected to the first tiller (2) or to the vehicle by means of the connection structure (19; 119; 219) in a revolving manner around the first axis (V).

13. Equipment according to claim 12, wherein the slide (16) is connected to an elongated portion (14) of the support structure (11); the elongated portion (14) being connected to a body (11a) of the support structure (11) by means of a fourth joint (14a) which develops parallel to a second axis (O) incident with the first axis (V), and by means of an actuator (15) so as to secure the position of the elongated body (14) with respect to the body (13) in a selectively adjustable manner.

14. Equipment according to any one of the preceding claims, comprising the first tiller (2); the connection structure (219) comprises a first arm (210b); wherein the tracker device (3) is connected to the first tiller (2) by means of the connection structure (219) in an integral manner via the first arm (210b).


15. Equipment according to claim 10, comprising the first tiller (2) comprising a frame (5); the connection structure (19) comprising a fifth joint (19b) and a second arm (19e) which connects the fifth joint (19b) to the second joint (19a); comprising a second actuator (50); the second actuator (50) having a selectively adjustable length which connects the frame (5) of the tiller (2) to the fifth joint (19b) so that a distance between the frame (5) and the fifth joint (19b) is selectively adjustable.


16. Equipment according to any one of the preceding claims, comprising the first tiller (2); wherein the connection structure (19) comprises a jointed quadrilateral having four joints (19a, 19b, 19c, 19d) and connects the tracker device (3) to the tiller (2) so that the tracker device (3) can freely rotate around a second axis (O) incident with the first axis (V)


and preferably parallel to the snow cover (N), with respect to the tiller (3) to assume a position with respect to the snow cover (N) which is independent of the position of the tiller (2) with respect to the snow cover (N).

5 17. Equipment according to claim 10 and 11, comprising the first tiller (2); wherein the connection structure (119) comprises a third actuator (150) having a selectively adjustable length; and wherein the connection structure (119) comprises a sixth joint (119c) connected to the second joint (119a) by means
10 of the actuator (150) so that the distance between the second joint (119a) and the sixth joint (119c) is selectively adjustable; the sixth joint (119c) being connected to the tracker device (3) by means of the first joint (SV).

15










FIG.5

INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2017/052021

A. CLASSIFICATION OF SUBJECT MATTER
INV. E01H4/02
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
E01H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 461 303 A1 (PRINOTH SPA [IT]) 18 December 1991 (1991-12-18)	1-5, 10-17
Y	figure 1	6,7
X	DE 87 08 508 U1 (BÄCHLER) 28 April 1988 (1988-04-28)	1-5,8-17
Y	figure 3	6,7
Y	EP 0 139 959 A2 (KAESSBOHRER FAHRZEUG KARL [DE]) 8 May 1985 (1985-05-08)	6,7
X	US 4 110 919 A (HENRICHON LUCIEN) 5 September 1978 (1978-09-05)	1
	figure 2	
	-/-	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

29 June 2017

Date of mailing of the international search report

10/07/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Saretta, Guido

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2017/052021

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 216 753 A2 (BOMBARDIER ROTAX WIEN [AT]) 1 April 1987 (1987-04-01) figure 1 -----	1
X	EP 1 754 832 A2 (KAESSBOHRER GELAENDEFAHRZEUG [DE]) 21 February 2007 (2007-02-21) figure 3 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2017/052021

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 0461303	A1	18-12-1991	EP	0461303 A1		18-12-1991
			FI	905928 A		14-12-1991
			IT	1248841 B		30-01-1995
			NO	905269 A		16-12-1991

DE 8708508	U1	28-04-1988	CA	1282988 C		16-04-1991
			DE	8708508 U1		28-04-1988
			US	4788783 A		06-12-1988

EP 0139959	A2	08-05-1985	DE	3333941 A1		04-04-1985
			EP	0139959 A2		08-05-1985
			JP	S60144407 A		30-07-1985
			US	4559725 A		24-12-1985

US 4110919	A	05-09-1978	CA	1038681 A		19-09-1978
			US	4110919 A		05-09-1978

EP 0216753	A2	01-04-1987	AT	388308 B		12-06-1989
			EP	0216753 A2		01-04-1987
			FI	863809 A		24-03-1987
			JP	S6268907 A		30-03-1987
			NO	863785 A		24-03-1987

EP 1754832	A2	21-02-2007	DE	102005040222 A1		22-02-2007
			EP	1754832 A2		21-02-2007
