



US009082098B1

(12) **United States Patent**
Adelson

(10) **Patent No.:** **US 9,082,098 B1**

(45) **Date of Patent:** ***Jul. 14, 2015**

(54) **SYSTEMS AND METHODS FOR
MONITORING LOCATION OF A VEHICLE
OR FREIGHT CARRIED BY A VEHICLE**

(58) **Field of Classification Search**
CPC G06Q 10/0833; G08G 1/20; G08G 1/205
USPC 340/988-994, 995.1; 701/1, 2, 32.3,
701/454, 467, 482, 485; 348/116
See application file for complete search history.

(71) Applicant: **MacroPoint LLC**, Cleveland, OH (US)

(56) **References Cited**

(72) Inventor: **Bennett H. Adelson**, Highland Heights, OH (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **MACROPOINT, LLC**, Cleveland, OH (US)

5,774,876 A 6/1998 Woolley et al.
5,794,174 A 8/1998 Janky et al.
6,442,391 B1 8/2002 Johansson et al.
7,366,522 B2 4/2008 Thomas
8,301,158 B1 10/2012 Thomas
8,369,867 B2 2/2013 Van Os et al.
8,649,775 B2 2/2014 Alessio et al.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(Continued)

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Non-final Office Action of corresponding U.S. Appl. No. 13/409,281, dated May 15, 2012.

(Continued)

(21) Appl. No.: **14/661,769**

Primary Examiner — Mark Rushing

(22) Filed: **Mar. 18, 2015**

(74) *Attorney, Agent, or Firm* — Renner, Otto, Boisselle & Sklar, LLP.

Related U.S. Application Data

(57) **ABSTRACT**


(63) Continuation of application No. 14/069,364, filed on Oct. 31, 2013, which is a continuation of application No. 13/613,321, filed on Sep. 13, 2012, now Pat. No. 8,604,943, which is a continuation of application No. 13/429,618, filed on Mar. 26, 2012, now Pat. No. 8,330,626.

Monitoring location of a vehicle or freight includes receiving a request for information regarding the location of the vehicle or the freight, receiving an indication of consent to transmission of location information of the communications device, correlating the vehicle or the freight with the communications device, transmitting a request for location information of the communications device to a location information provider corresponding to a party or device other than the communications device, receiving the location information of the communications device from the location information provider, correlating the location information of the communications device to the location of the vehicle or the freight based on the correlation of the vehicle or the freight to the communications device, and transmitting the location of the vehicle or the freight.

(51) **Int. Cl.**
G08B 21/00 (2006.01)
G06Q 10/08 (2012.01)
G06Q 10/06 (2012.01)

(52) **U.S. Cl.**
CPC **G06Q 10/08** (2013.01); **G06Q 10/0631** (2013.01)

20 Claims, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,718,672	B2	5/2014	Xie et al.
8,755,823	B2	6/2014	Proietti et al.
2006/0187027	A1	8/2006	Smith
2008/0132252	A1	6/2008	Altman et al.
2009/0017803	A1	1/2009	Brillhart et al.
2009/0030770	A1	1/2009	Hersh et al.
2009/0143079	A1	6/2009	Klassen et al.
2010/0228404	A1	9/2010	Link et al.
2011/0001638	A1	1/2011	Pudar
2011/0063138	A1	3/2011	Berkobin et al.
2012/0265433	A1	10/2012	Viola et al.

OTHER PUBLICATIONS

Notice of Allowance of corresponding U.S. Appl. No. 13/409,281, dated Jun. 28, 2012.

Non-final Office Action of corresponding U.S. Appl. No. 13/613,321, dated Jan. 31, 2013.

Final Office Action of corresponding U.S. Appl. No. 13/613,321, dated Jul. 1, 2013.

Notice of Allowance of corresponding U.S. Appl. No. 13/613,321, dated Oct. 4, 2013.

Non-final Office Action of corresponding U.S. Appl. No. 14/069,364, dated Feb. 12, 2015.

Notice of Allowance of corresponding U.S. Appl. No. 13/429,618, dated Mar. 26, 2012.

Hurcom, Stephen; "Tracking to Keep Trucking", www.mapinfo.com; Jun. 27, 2003.

Britton, Diana; "A Mobile Industry: Cell Phones Useful to Stay Connected With Drivers", www.truckinginfo.com; Oct. 2009.




Figure 1

200

220

230

	Active Driver <u>210a</u>	Active Device <u>110a</u>	Backup Driver <u>210b</u>	Backup Device <u>110b</u>	Total Capacity ft ³ / lbs.	Available Capacity ft ³ / lbs.
105b	Gary Fisher	(546) 542-1235			3,931 42,010	2,531 22,010
105d	Colnago Cinelli	(563) 543-5635	Ross Raleigh	(243) 546-5435	2,878 Ref 36,280	2,878 Ref. 36,280
105f	Emilio Bozzi	(507) 543-5475	Murray Schwinn	(548) 243-5433	3,268 41,700	0 0

Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7

800



<u>Start/End Monitoring</u>	<u>Telephone Number</u>	<u>Monitoring Term</u>	<u>Monitoring Interval</u>	<u>Location</u>	<u>Partner / Code</u>	<u>Reference Number</u>	<u>Status</u>
810a	555-555-5555	2 hours	15 mins.	41.396915 -81.662787	NAT	F234	Monitoring
810b	844-484-4844	36 hours	1 hour	31.497925 -71.561777	JBH	2H22	Hidden
810c	333-333-3333	6 hours	30 mins.		JBH	2H56	Ready
810d	543-543-5435	2 hours	15 mins.	21.396915 -41.662787	JBH	2G34	Monitoring
810e							
810f							
810g							

Callout boxes 820, 830, 840, 850, and 860 are positioned below the table. Boxes 820, 830, and 840 are under the Telephone Number, Monitoring Term, and Monitoring Interval columns of row 810e. Boxes 850 and 860 are under the Partner / Code and Reference Number columns of row 810e.

Figure 8




Figure 9




Figure 10

**SYSTEMS AND METHODS FOR
MONITORING LOCATION OF A VEHICLE
OR FREIGHT CARRIED BY A VEHICLE**

TECHNICAL FIELD

The present disclosure relates to systems and methods for monitoring location.

BACKGROUND

Location information is becoming more important and prevalent.

In one example application of the use of location information, carriers, shippers, freight hauling services providers, third-party logistics service providers and courier services providers as well as other logistics and freight service providers (freight hauling) benefit from monitoring the location of vehicles in their fleets or under contract. Monitoring the location of vehicles helps improve efficiency because it allows for real-time or near real-time decision making when matching loads with vehicles. For example, by monitoring the location of fleet vehicles, a dispatcher may better understand which vehicle is the most appropriate (e.g., geographically closest, appropriate size, etc.) to send to a location for a load pickup. Conventional systems for monitoring vehicle location have relied on global positioning systems (GPS) to provide the vehicle's location. These systems require a GPS receiver to be installed in each vehicle. Moreover, some of these systems require the installation of additional dedicated equipment in each vehicle.

In addition, at least in part due to limitations of conventional systems for monitoring vehicle location, a common practice in the vehicle location monitoring services industry is to charge a user a standard flat monthly fee for monitoring services. This practice may represent a substantial cost to a user or organization that, for example, may wish to monitor a relatively small number of vehicles or a relatively small number of loads for a relatively short amount of time.

SUMMARY

Alternative methods for monitoring location of vehicles include radiolocation techniques including triangulation or multilateration methods that are capable of locating devices in a network. These methods involve the measurement of radio signals between a device and radio towers in the network. The technology, originally intended by telecommunication companies to approximate the location of a mobile phone in case of emergencies, provides the location of a device in the network.

The use of all of these location information technologies also raises privacy issues. A user's privacy may be at risk if location information is misused or disclosed without the authorization or knowledge of the user. To address these privacy concerns, various governmental and business organizations have developed rules and guidelines to protect user privacy. For example, the International Association for the Wireless Telecommunications Industry (CTIA) has developed Best Practices and Guidelines for Location-Based Services (the "CTIA Guidelines"), which are hereby incorporated by reference.

The Guidelines provide a framework based on two principles: user notice and consent. Users must receive "meaningful notice about how location information will be used, disclosed and protected so that users can make informed decisions . . . and . . . have control over their location infor-

mation." Users must also "consent to the use or disclosure of location information" and "have the right to revoke consent . . . at any time."

Although, electronic methods have been developed that make use of web browsers and SMS texting capabilities of mobile devices to provide notification and consent, some of these systems have proved inconvenient and may require advanced mobile devices or extensive user training.

A computer implemented method for monitoring location of a vehicle includes receiving a first electronic signal including data representing a request for information regarding the location of the vehicle, correlating the vehicle to a communications device based at least in part on the communications device being associated with a user who is associated with the vehicle, and transmitting a second electronic signal to a location information provider corresponding to a party or device other than the communications device. The second electronic signal includes data representing a request for location information of the communications device. The computer implemented method for monitoring location of a vehicle further includes receiving a third electronic signal from the location information provider. The third electronic signal includes data representing the location information of the communications device. The computer implemented method for monitoring location of a vehicle further includes correlating the location information of the communications device with the location of the vehicle based at least in part on the communications device being associated with the user who is associated with the vehicle, and transmitting a fourth electronic signal including data representing the location of the vehicle.

Another computer implemented method for monitoring location of a vehicle includes transmitting a request signal requesting location information of a communications device. The request signal is transmitted to a party other than the communications device and the communications device is associated with a user of the communications device who is associated with the vehicle. The computer implemented method for monitoring location of a vehicle further includes receiving a location signal including data indicating the location information of the communications device. The location signal is received from a party other than the communications device and the location information of the communications device is originally obtained using a method not requiring a global position system (GPS) satellite receiver to form part of the communications device. The computer implemented method for monitoring location of a vehicle further includes transforming the location information of the communications device into location information regarding the vehicle based at least in part on the communications device being associated with the user of the communications device who is associated with the vehicle.

A system for monitoring location of a vehicle includes a communications interface configured to communicate electronic signals including: a first electronic signal including data representing a request for the location of the vehicle, the first electronic signal received from a requesting party, a second electronic signal including data representing a request for location information of a communications device, wherein the second electronic signal is transmitted to a location information provider corresponding to a party or device other than the communications device, wherein the communications device is associated with a user of the communications device who is associated with the vehicle, a third electronic signal including data representing the location information of the communications device, wherein the third electronic signal is received from the location information provider corresponding to the party or device other than the

communications device, and a fourth electronic signal including data representing the location of the vehicle, the fourth electronic signal transmitted to a receiving party. The system for monitoring location of a vehicle further includes a correlation logic configured to correlate the location information of the communications device to the location of the vehicle based at least in part on the communications device being associated with the user of the communications device who is associated with the vehicle.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate various example systems, methods, and so on, that illustrate various example embodiments of aspects of the invention. It will be appreciated that the illustrated element boundaries (e.g., boxes, groups of boxes, or other shapes) in the figures represent one example of the boundaries. One of ordinary skill in the art will appreciate that one element may be designed as multiple elements or that multiple elements may be designed as one element. An element shown as an internal component of another element may be implemented as an external component and vice versa. Furthermore, elements may not be drawn to scale.

FIG. 1 illustrates an exemplary system for monitoring the location of a vehicle.

FIG. 2 illustrates a simplified exemplary chart illustrating how a correlation logic may correlate a vehicle to a communications device or the location of the vehicle to the location information of the communications device.

FIG. 3 illustrates the exemplary system for monitoring the location of a vehicle with additional details.

FIG. 4 illustrates a flow diagram for an exemplary method for monitoring location of a vehicle.

FIG. 5 illustrates a flow diagram for an exemplary method for monitoring location of a vehicle.

FIG. 6 illustrates a flow diagram for an exemplary method for receiving consent from a user to monitoring the location of a vehicle associated with the user.

FIG. 7 illustrates a flow diagram for an exemplary method for receiving from a user a revocation of consent to monitoring the location of a vehicle associated with the user.

FIG. 8 illustrates an exemplary user interface for use in conjunction with a system for monitoring the location of a vehicle.

FIG. 9 illustrates an application programming interface (API) providing access to a system for monitoring the location of a vehicle.

FIG. 10 illustrates a computer where systems or methods for monitoring the location of a vehicle may be implemented.

DETAILED DESCRIPTION

Some portions of the detailed descriptions that follow are presented in terms of algorithms and symbolic representations of operations on data bits within a memory. These algorithmic descriptions and representations are the means used by those skilled in the art to convey the substance of their work to others. An algorithm is here, and generally, conceived to be a sequence of operations that produce a result. The operations may include physical manipulations of physical quantities. Usually, though not necessarily, the physical quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated in a logic and the like.

It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. It should be borne in mind, however, that these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise, it is appreciated that throughout the description, terms like processing, computing, calculating, determining, displaying, or the like, refer to actions and processes of a computer system, logic, processor, or similar electronic device that manipulates and transforms data represented as physical (electronic) quantities.

In the present disclosure, embodiments are described in the context of location of freight hauling vehicles. It will be appreciated, however, that the exemplary context of freight hauling vehicles is not the only operational environment in which aspects of the disclosed systems and methods may be used. Therefore, the techniques described in this disclosure may be applied to many types of apparatus, vehicles or devices whose location information may be of interest.

FIG. 1 illustrates an exemplary system 100 for monitoring the location of a vehicle 105, which has a communication device 110 within the vehicle 105. The system 100 includes a communications interface 120 that communicates with devices external to the system 100 via electronic signals. For example, the communications logic 120 is configured to communicate with a location information provider 150, a requesting party 160, and a receiving party 165.

The location information provider 150 corresponds to a party or device other than the vehicle 105 and the device 110. The location information provider 150 has access to location of the vehicle 105 or the device 110. In one embodiment, the location information provider 150 is a wireless service provider that provides wireless service in a network 155. In another embodiment, the location information provider 150 is a third party or device that receives the location information of the device 110 from the wireless service provider or from some other party or device. In yet another embodiment, the location information provider 150 is a party other than a wireless service provider or a third party. For example, the party seeking to monitor the location of the vehicle 105, the requesting party 160, may have access to the location information of the device 110. In that case, the requesting party 160 may also be the location information provider 150. In another example, the party operating the system 100 may have access to the location information of the device 110.

The requesting party 160 corresponds to a party or device interested in monitoring the location of the vehicle 105 or on allowing another party to monitor the location of the vehicle 105. The receiving party 165 corresponds to a party or device who receives the location of the vehicle 105 from the system 100 to monitor the location of the vehicle 105. In an example involving freight hauling services providers or freight carriers, a carrier who is interested in monitoring the location of its own vehicles, vehicles under contract, or other vehicles requests the ability to monitor the location of the vehicle 105 for its own consumption. In this case, the carrier is both the requesting party 160 and the receiving party 165. In another example, the requesting party 160 may be a driver interested in sharing the location of his/her vehicle 105 with a carrier to allow the carrier to monitor the location of the vehicle 105. In this case, the driver is the requesting party 160 and the carrier is the receiving party 165. In one embodiment, multiple parties or devices may be interested in monitoring the location of the vehicle 105 or on allowing another party to monitor the location of the vehicle 105. In that case, the communications

5

interface **120** is configured to communicate with multiple requesting parties and/or multiple receiving parties.

The system **100** further includes a correlation logic **170** that correlates the vehicle **105** and the device **110**. In one embodiment, the correlation logic **170** correlates the vehicle **105** and the device **110** based at least in part on the vehicle **105** being associated with at least one user who is also associated with the device **110**. For example, the user may be associated with the vehicle **105** because the user is the designated driver of the vehicle **105** and the user may be associated with the communications device **110** because the user is under contract with a wireless service provider for the provider to provide wireless service to the communications device **110**. In another example, the user is associated with the vehicle **105**, with the device **110**, or with both in a database or in the correlation logic **170**. In another embodiment, the vehicle **105** is directly associated with the communications device **110** without a user being associated with the vehicle **105** or with the device **110**.

In an example of the operation of the system **100**, the requesting party **160** transmits and the communications interface **120** receives data representing a request from the requesting party **160** for the ability to monitor the location of the vehicle **105**. In response to the request from the requesting party **160**, the correlation logic **170** correlates the vehicle **105** to the device **110**. The communications interface **120** transmits to the location information provider **150** data representing one or more requests for location information of the device **110**. In response to a request for location information of the device **110**, the location information provider **150** transmits and the communications interface **120** receives data representing the location information of the device **110**. The correlation logic **170** correlates the location information of the device **110** to the location of the vehicle **105**.

With the location of the vehicle **105** on hand, the communication interface **120** can transmit data representing the location of the vehicle **105** to the receiving party **165** through computer communication. The location of the vehicle **105** may then be displayed in a user interface (not shown). In another embodiment, the communications interface **120** is configured to communicate the location to the receiving party **165** by exposing an application programming interface (API) through which the receiving party **165** can access the location of the vehicle **105**. The receiving party **165** can make use of the API to make the information available to its enterprise software (e.g., SAP, Oracle, etc.) for example.

FIG. 2 illustrates a simplified exemplary chart **200** illustrating how the correlation logic **170** may correlate the vehicle **105** to the device **110** or the location of the vehicle **105** to the location information of the device **110**. In the illustrated embodiment, for each vehicle **105a-g** registered in the system **100**, the correlation logic **170** has data fields corresponding to each vehicle **105a-g**. The data fields include information regarding the vehicles **105a-g**. Potential information that may be included in the data fields include one or more drivers **210a-b** associated with each of the vehicles **105a-g** and one or more devices **110a-b** associated with each of the drivers **210a-b**, respectively. The drivers **210a-b** are identified by name while the devices **110a-b** are identified by an identifier, which in this case corresponds to a telephone number associated with the respective device **110a-b**.

In other embodiments, the identifier corresponds to a number or some other identifying information associated with the device **110** other than a telephone number. For example, the identifier may be a mobile identification number (MIN), an electronic serial number (ESN), an International Mobile Equipment Identity (IMEI), an International Mobile Sub-

6

scriber Identity (IMSI), a Mobile Equipment Identifier (MEID), a Manufacturer's Serial Number (MSN), a Mobile Subscriber Integrated Services Digital Network (MSISDN) number, a Media Access Control (MAC) address, combinations thereof, and so on.

Additional information that may be included in the data fields include the capacity of a vehicle **105a-g** (e.g., total volumetric and weight capacity **220**, available volumetric and weight capacity **230**, etc.), whether the container is refrigerated Ref., and so on.

In the illustrated embodiment, the vehicle **105a** is associated with an active driver **210a** named Bianchi Campagnolo who is associated with an active device **110a** identified by an identifier corresponding to the telephone number (143) 846-5405. The vehicle **105a** may also be associated with a backup driver named Bob Haro who is associated with a backup device **110b** identified by an identifier corresponding to the telephone number (443) 240-5465. The correlation logic **170** correlates the vehicle **105** with the active driver **210a** unless the correlation logic **170** is instructed to instead use the backup driver **210b**. In that case, the active driver **210a** and the backup driver **210b** may switch, with the name listed under backup driver **210b** appearing under active driver **210a** and viceversa. Similarly, the correlation logic **170** correlates the vehicle **105** with the active device **110a** unless the correlation logic **170** is instructed to instead use the backup device **110b**. In that case, the active device **110a** and the backup device **110b** may switch, with the identifier listed under backup device **110b** appearing under active device **110a** and viceversa. In this way, the correlation logic **170** can transform the location information of the communications device **110** into information regarding the location of the vehicle **105** by correlating the location information of the communications device **110** to the location of the vehicle **105** based at least in part on the communications device **110** being associated with the user who is associated with the vehicle **105**. In one embodiment, the correlation logic **170** correlates the vehicle **105** with the active driver **210a** and the backup driver **210b**.

In the illustrated embodiment, the vehicle **105a** has a total capacity of 4,013 pounds and 42,660 cubic feet of which 4,013 pounds and 42,660 cubic feet are currently available. The vehicle **105c** has a total capacity of 2,878 pounds and 36,280 cubic feet. The capacity of the vehicle **105c** is refrigerated capacity. However, none of that capacity is currently available (e.g., the container associated with the vehicle **105c** is full) since the available capacity is indicated as 0 pounds and 0 cubic feet.

FIG. 3 illustrates the exemplary system **100** for monitoring the location of a vehicle **105** with additional details.

As described above, the system **100** receives the location information of the device **110** from a location information provider **150**, which is a party or device other than the device **110**. The location information provider **150** may be a wireless service provider or a party or device that receives the location information from a wireless service provider. Examples of wireless service providers in the United States include Verizon Wireless, AT&T Mobility, Sprint Nextel, T-Mobile, etc. These wireless service providers have technologies deployed that allow them to approximate the location of devices in their network. Some of these technologies were developed and deployed in compliance with E911, a government mandate requiring the wireless service providers to provide the approximate location of a mobile device in case of an emergency.

Location of devices in a cellular network may be described as involving two general positioning techniques: 1) techniques that require the device to incorporate a global posi-

tioning system (GPS) receiver, and 2) techniques that use some form of radiolocation from the device's network and do not require the device to incorporate a GPS receiver.

In one embodiment, the wireless service provider or another party or device originally obtaining or deriving the location information of the device **110** derives the location information of the device **110** at least in part by using a radiolocation technique where the approximated location of the device **110** corresponds to a range of locations corresponding to a transmission range of a single radio tower **155**. In an example of this technology, each radio tower is assigned a unique identification number, a Cell-ID. The Cell-ID is received by all mobile devices in the coverage area of the radio tower **155**, thus the position of the device **110** in the coverage area of the radio tower **155** is derived from the coordinates of the radio tower **155**. Additional techniques, such as measuring signal strength of the device **110** could be used to increase the accuracy of the location information. Accuracy can be further enhanced by including a measurement of Timing Advance (TA) in GSM/GPRS networks or Round Trip Time (RTT) in UMTS networks. TA and RTT use time offset information sent from the radio tower **155** to adjust the communications device's relative transmit time to correctly align the time at which the communications device's signal arrives at the radio tower **155**. These measurements can be used to determine the distance from the communications device to the radio tower **155**, further improving accuracy.

In one embodiment, the wireless service provider or another party or device originally obtaining or deriving the location information of the device **110** derives the location information of the device **110** at least in part using triangulation between multiple radio towers such as tower **155**. The location of the device **110** may be determined by using one or a combination of several techniques including the following:

Angle of Arrival (AOA)—This technique requires at least two radio towers and locates the device **110** at the point where the lines along the angles from each tower intersect.

Time Difference of Arrival (TDOA)—This technique also requires at least two radio towers and determines the time difference between the time of arrival of a signal from the device **110** to the first tower **155**, to a second tower, and so on.

Advanced Forward Link Trilateration (AFLT)—In this technique the communications device measures signals from nearby towers such as radio tower **155**, which are then used to triangulate an approximate location of the device **110**.

Enhanced-observed time difference (E-OTD)—This technique takes data received from the nearby towers such as radio tower **155** to measure the difference in time it takes for the data to reach the device **110**. The time difference is used to calculate where the device **110** is in relation to the radio towers.

In one embodiment, the wireless service provider or another party or device originally obtaining or deriving the location information of the device **110** derives the location information of the device **110** at least in part by using a method including a technique not requiring a GPS satellite receiver to form part of the device **110**. In another embodiment the wireless service provider or another party or device deriving the location information of the device **110** derives the location information of the device **110** at least in part by using a hybrid method including a technique requiring a GPS satellite receiver to form part of the device **110** and a technique not requiring a GPS satellite receiver to form part of the device **110**. In yet another embodiment, the wireless service provider or another party or device deriving the location information of the device **110** derives the location informa-

tion of the device **110** at least in part by using a method including a technique requiring a GPS satellite receiver to form part of the device **110**.

However, since the system **100** obtains the location information from the location information provider **150** and not from the device **110**, the system **100** can be operated to monitor the location of devices incorporating a GPS satellite receiver as well as devices not incorporating a GPS satellite receiver. Thus, the system **100** does not rely on any particular positioning technology for obtaining the location of the vehicle **105**.

In continued reference to FIG. 3, the system **100** provides user notification and receives user consent to the monitoring the location of the vehicle **105**. In this embodiment, the communications interface **120** is further configured for communication with the device **110**. In one embodiment, the communication interface **120** is associated with a toll free number such as a 1-800 number. The driver of the vehicle **105** may initiate a telephone call by dialing the toll free number. In another embodiment, the communications interface is associated with a number other than a toll free number. In yet another embodiment, the communications interface **120** is configured to initiate the telephone call.

In one embodiment, the system **100** further includes a validation logic **130** that is configured to identify the device **110** at least in part by obtaining the identifier associated with the device **110**. Obtaining the identifier associated with the device **110** ensures that the correct party (e.g., the driver of the vehicle **105** or the user associated with the device **110**) is notified that location of the vehicle **105** will be monitored and that the correct party (e.g., the driver of the vehicle **105** or the user associated with the device **110**) consents to the monitoring of the location. In one embodiment, the identifier is a telephone number associated with the device **110**. In one embodiment, where the communications interface **120** is associated with a toll free number as discussed above, the validation logic **130** is configured to identify the device **110** at least in part by obtaining the telephone number associated with the device **110** via automatic number identification (ANI). As discussed above in reference to FIG. 2, in other embodiments, the identifier may be an identifier other than a telephone number.

The system **100** further includes a notification logic **140** that is configured to communicate a signal including data representing an automated voice message. In one embodiment, the automated voice message provides a notice that includes information indicating that consenting to the monitoring of the location of the vehicle **105** would result in the location of the vehicle **105** or the device **110** being disclosed. In another embodiment, the automated voice message provides a location (web address, etc.) where the notice may be found indicating that consenting to the monitoring of the location of the vehicle **105** would result in the location of the vehicle **105** or the device **110** being disclosed. For example, the automated voice message may indicate that the notice may be found at a web address and provide the web address.

The communications interface **120** is configured to transmit the automated voice message to the device **110**. The communications interface **120** is further configured to receive from the device **110** data indicating the user consent to monitoring of the location of the vehicle **105**.

In one embodiment, the automated voice message communicates that user's consent to the monitoring of the location of the vehicle **105** may be indicated by performing an action on the communications device (e.g., "to indicate your consent to revealing your location, please press 1.") In this embodiment, the communications interface **120** is configured to receive

data indicating that an action was performed on the device **110**, which indicates the user's consent (e.g., the user pressed 1).

In another embodiment, the automated voice message communicates that the user's consent to the monitoring of the location of the vehicle **105** may be indicated by speaking a particular word or phrase to be received by the device **110** (e.g., "to indicate your consent to revealing your location, please say 'yes.'") In this embodiment, the communications interface **120** is configured to receive a voice command from the device **110**, which indicates the user's consent (e.g., the user said "yes").

In one embodiment, after receiving the user consent to the monitoring of the location of the device **105**, the communications interface **120** transmits a request for the location information of the device **110** and receives the location information of the communications device **110**. The request for the location information of the device **110** includes the identifier associated with the device **110**.

In the illustrated embodiment, after receiving the user consent to the monitoring of the location of the device **105**, the communications interface **120** transmits a request for the location information of the device **110** to a location information provider **150** and receives the location information of the communications device **110** from the location information provider **150**.

In one embodiment, the notification logic **140** is further configured to communicate a signal including data representing a second automated voice message indicating that consent to the monitoring of the location of the vehicle **105** is revocable via the device **110**. In this embodiment, the communications interface **120** is configured to communicate to the device **110** the second automated voice message and to receive confirmation of consent or revocation of consent to the monitoring of the location of the vehicle **105** from the device **110**.

In one embodiment, the second automated voice message communicates that the user's confirmation of consent or the user's revocation of consent to the monitoring of the location of the vehicle **105** may be indicated by performing an action on the communications device (e.g., "to indicate that you wish to revoke consent to revealing your location, please press 1.") In this embodiment, the communications interface **120** is configured to receive data indicating that an action was performed on the device **110**, which indicates the user's confirmation or revocation of consent (e.g., the user pressed 1).

In another embodiment, the second automated voice message communicates that the user's confirmation of consent or the user's revocation of consent to the monitoring of the location of the vehicle **105** may be indicated by speaking a particular word or phrase to be received by the device **110** (e.g., "to indicate your confirmation of consent to revealing your location, please say 'confirmed.'") In this embodiment, the communications interface **120** is configured to receive a voice command from the device **110**, which indicates the user's confirmation or revocation of consent (e.g., the user said "confirmed").

In one embodiment, the user is given the option to temporarily revoke consent to the disclosure of location information. For example, a driver may wish to make available his location to a carrier during certain hours during the work week, but may not want the carrier to be able to obtain the driver's location during the weekend. The driver may operate the device **110** to indicate a date and time when the driver wishes for the monitoring of the location of the vehicle **105** to end or resume. Or the driver may operate the device **110** to indicate an interval of time (e.g., 2 hours) during which the

driver wishes to hide the location of the vehicle **105**. In this embodiment, the communications interface **120** is configured to receive data indicating a time until which consent to the monitoring of the location of the vehicle **105** is granted or revoked, or an interval of time during which consent to the monitoring of the location of the vehicle **105** is granted or revoked.

In one embodiment, the user is given the option to temporarily revoke consent to the monitoring of the location of the vehicle **105** by texting (e.g., SMS message) the term "hide" using the device **110**. In one embodiment, the user is given the option to indicate consent to the monitoring of the location of the vehicle **105** by texting (e.g., SMS message) the term "share" using the device **110**. In this embodiment, the communications interface **120** is configured to receive the text message as sent by the device **110**, which indicates the user's confirmation or revocation of consent. In another embodiment, the user may speak the terms "hide" or "share" to temporarily revoke consent or to indicate consent to the monitoring of the location of the vehicle **105**, respectively. In this embodiment, the communications interface **120** is configured to receive a voice command from the device **110**, which indicates the user's confirmation or revocation of consent.

In one embodiment, when the location of the vehicle **105** is being disclosed, the notification logic **140** is further configured to periodically generate and the communications interface **120** is further configured to periodically communicate a reminder notification message indicating that the location of the vehicle **105** is currently being disclosed. In one embodiment, the system **100** reminds the user every 30 days that the location of the vehicle **105** is currently being disclosed. In another embodiment, the system **100** reminds the user more or less often than every 30 days that the location of the vehicle **105** is currently being disclosed.

In one embodiment, the communications interface **120** reminds the user in an automated voice message that the location of the vehicle **105** is currently being disclosed. In another embodiment, the communications interface **120** reminds the user in an SMS message that the location of the vehicle **105** is currently being disclosed. In yet another embodiment, the communications interface **120** reminds the user via electronic communication other than an automated voice message or an SMS message that the location of the vehicle **105** is currently being disclosed.

Example methods may be better appreciated with reference to the flow diagrams of FIGS. 4 through 7. While for purposes of simplicity of explanation, the illustrated methodologies are shown and described as a series of blocks, it is to be appreciated that the methodologies are not limited by the order of the blocks, as some blocks can occur in different orders or concurrently with other blocks from that shown or described. Moreover, less than all the illustrated blocks may be required to implement an example methodology. Furthermore, additional or alternative methodologies can employ additional, not illustrated blocks.

In the flow diagrams, blocks denote "processing blocks" that may be implemented with logic. The processing blocks may represent a method step or an apparatus element for performing the method step. A flow diagram does not depict syntax for any particular programming language, methodology, or style (e.g., procedural, object-oriented). Rather, a flow diagram illustrates functional information one skilled in the art may employ to develop logic to perform the illustrated processing. It will be appreciated that in some examples, program elements like temporary variables, routine loops, and so on, are not shown. It will be further appreciated that electronic and software applications may involve dynamic

and flexible processes so that the illustrated blocks can be performed in other sequences that are different from those shown or that blocks may be combined or separated into multiple components. It will be appreciated that the processes may be implemented using various programming approaches like machine language, procedural, object oriented or artificial intelligence techniques.

In one example, methodologies are implemented as processor executable instructions or operations provided on a computer-readable medium. Thus, in one example, a computer-readable medium may store processor executable instructions operable to perform the methods of FIGS. 4 through 7.

While FIGS. 4 through 7 illustrate various actions occurring in serial, it is to be appreciated that various actions illustrated in FIGS. 4 through 7 could occur substantially in parallel. While a number of processes are described, it is to be appreciated that a greater or lesser number of processes could be employed and that lightweight processes, regular processes, threads, and other approaches could be employed. It is to be appreciated that other example methods may, in some cases, also include actions that occur substantially in parallel.

FIG. 4 illustrates a flow diagram for an exemplary method 400 for monitoring location of a vehicle. At 410, the method 400 includes receiving a first electronic signal including data representing a request for information regarding the location of the vehicle. At 420, the method 400 includes correlating the vehicle to a communications device based at least in part on the communications device being associated with a user who is associated with the vehicle. At 430, the method 400 includes transmitting a second electronic signal to a location information provider corresponding to a party or device other than the communications device. The second electronic signal includes data representing a request for location information of the communications device. In one embodiment, the second electronic signal includes data representing a telephone number associated with the communications device.

At 440, the method 400 includes receiving a third electronic signal from the location information provider including data representing the location information of the communications device. At 450, the method 400 includes correlating the location information of the communications device with the location of the vehicle based at least in part on the communications device being associated with the user who is associated with the vehicle. At 460, the method 400 includes transmitting a fourth electronic signal including data representing the location of the vehicle. In one embodiment, the transmitting the fourth electronic signal including data representing the location of the vehicle includes exposing an application programming interface (API) from which the requesting party can access the location of the vehicle.

In one embodiment, the location information of the communications device is originally obtained using a method including a technique other than a technique utilizing a global position system (GPS) satellite receiver that forms part of the communications device. In one embodiment, the location information of the communications device is originally obtained using a method including at least one of: advance forward link trilateration (AFLT), observed time difference (OTD), Cell-ID (CID), and obtaining a range of locations corresponding to a transmission range of a single radio tower.

In one embodiment, the user of the communications device is a driver of the vehicle. In one embodiment, the location information provider corresponds to one of: a wireless service provider providing wireless service to the communications device or a third party that obtains the location information from the wireless service provider providing wireless

service to the communications device. In one embodiment, the requesting party corresponds to one of: a freight service provider wherein the location of the vehicle is transmitted to the freight service provider for the freight service provider to have access to location of freight carried by the vehicle, or the driver of the vehicle requesting that the location of the vehicle be transmitted to a freight service provider for the freight service provider to have access to location of freight carried by the vehicle.

FIG. 5 illustrates a flow diagram for an exemplary method 500 for monitoring location of a vehicle. At 510, the method 500 includes transmitting a request signal requesting location information of a communications device. The request signal is transmitted to a party other than the communications device. The communications device is associated with a user of the communications device who is also associated with the vehicle. At 520, the method 500 includes receiving a location signal including data indicating the location information of the communications device. The location signal is received from a party other than the communications device.

At 530, the method 500 includes transforming the location information of the communications device into location information regarding the vehicle based at least in part on the communications device being associated with the user of the communications device who is also associated with the vehicle.

In one embodiment, the location information of the communications device is originally obtained by a wireless service provider providing wireless service to the communications device. In one embodiment, the location information of the communications device includes location information obtained in compliance with E911. In one embodiment, the location information of the communications device is originally obtained using a method not requiring a global position system (GPS) satellite receiver to form part of the communications device. In one embodiment, the location information of the communications device is originally obtained through triangulation between radio towers. In one embodiment, the location information of the communications device is originally obtained using a range of locations corresponding to a transmission range of a single radio tower.

In one embodiment, the location signal is received from one of: a wireless service provider, or a third party who receives the location information from the wireless service provider.

FIG. 6 illustrates a flow diagram for an exemplary method 600 for receiving consent from a user for monitoring the location of a vehicle associated with the user. At 610, the method 600 includes participating in a telephone call with a communications device associated with the user. In one embodiment, the user of the communications device initiates the telephone call. In another embodiment, the user of the communications device receives the telephone call. At 620, the method 600 includes identifying the communications device at least in part by obtaining an identifier associated with the communications device. In one embodiment, the identifier is a telephone number associated with the communications device. In one embodiment, the communications device user places the telephone call to a toll free number and the identifying the communications device includes obtaining a telephone number associated with the communications device via automatic number identification (ANI).

In other embodiments, the identifier is an identifier other than a telephone number. For example, the identifier may be a mobile identification number (MIN), an electronic serial number (ESN), an International Mobile Equipment Identity (IMEI), an International Mobile Subscriber Identity (IMSI), a

Mobile Equipment Identifier (MEID), a Manufacturer's Serial Number (MSN), a Mobile Subscriber Integrated Services Digital Network (MSISDN) number, a Media Access Control (MAC) address, combinations thereof, and so on.

At **630**, the method **600** includes transmitting to the communications device a signal including data representing an automated voice message. The automated voice message communicates to the user of the communications device at least one of: (a) a notice including information indicating that consenting to the monitoring of the location of the vehicle would result in the location of the vehicle or the location of the communications device being disclosed, or (b) a location at which to find the notice. At **640**, the method **600** includes receiving from the user via the communications device consent for monitoring the location of the vehicle.

In one embodiment, the receiving from the communications device consent for monitoring the location of the vehicle includes receiving data indicating that the user has performed an action on the communications device. For example, the user may have pressed a key in the communications device, touched or swiped a particular portion of the device's screen, shaken the communications device, combinations thereon and so on. In another embodiment, the receiving from the communications device consent for monitoring the location of the vehicle includes receiving a voice command from the communications device.

In one embodiment, once consent has been obtained from the user of the communications device, the method **600** includes periodically communicating to the user via the communications device a notification message indicating that the location is being disclosed.

In one embodiment, after receiving from the user consent for monitoring the location of the vehicle, the method **600** includes transmitting a request for the location information of the communications device and receiving the location information of the communications device.

In one embodiment, after receiving the location information of the communications device, the method **600** includes communicating the location of the vehicle to a receiving party. In one embodiment, communicating the location of the vehicle to a receiving party includes: (a) transmitting the communicating the location of the vehicle to the receiving party through computer communication, or (b) exposing an application programming interface (API) from which the receiving party can access the location of the vehicle.

FIG. 7 illustrates a flow diagram for an exemplary method **700** for receiving from a user a revocation of consent for monitoring the location of a vehicle associated with the user. At **710**, the method **700** includes participating in a telephone call with a communications device associated with the user. In one embodiment, the user initiates the telephone call. In another embodiment, the user receives the telephone call. At **720**, the method **700** includes identifying the communications device at least in part by obtaining an identifier associated with the communications device. In one embodiment, the identifier is a telephone number associated with the communications device. In one embodiment, the user places the telephone call to a toll free number and the identifying the communications device includes obtaining a telephone number associated with the communications device via automatic number identification (ANI). In other embodiments, the identifier is an identifier other than a telephone number as discussed above in reference to method **600**.

At **730**, the method **700** includes communicating to the user via an automated voice message transmitted to the communications device information indicating that consent to the monitoring of the location of the vehicle associated with the

user is revocable via the communications device. At **740**, the method **700** includes receiving from the communications device revocation of the consent to the monitoring of the location of the vehicle associated with the user.

In one embodiment, the receiving from the communications device revocation of consent to the monitoring of the location of the vehicle includes receiving data indicating that the user has performed an action on the communications device. For example, the user may have pressed a key in the communications device, touched or swiped a particular portion of the device's screen, shaken the communications device, combinations thereon and so on. In another embodiment, the receiving from the communications device revocation of consent to the monitoring of the location of the vehicle includes receiving a voice command from the communications device.

In one embodiment, the revocation of consent is temporary, and the receiving from the communications device revocation of the consent to the monitoring of the location of the vehicle includes receiving data indicating (a) a time at which consent to the monitoring of the location of the vehicle is revoked, (b) a time until which the consent to the monitoring of the location of the vehicle is revoked, or (c) an interval of time during which the consent to the monitoring of the location of the vehicle is revoked. Consent is revoked at the time indicated or at the beginning of the indicated interval of time. Consent is unrevoked at the indicated time until which the consent to the monitoring of the location of the vehicle is revoked or upon expiration of the indicated interval of time during which the consent to the monitoring of the location of the vehicle is revoked.

In one embodiment, the user is given the option to temporarily revoke consent to the monitoring of the location of the vehicle by texting (e.g., SMS message) the term "hide" using the device **110**. In one embodiment, the user is given the option to indicate consent to the monitoring of the location of the vehicle by texting (e.g., SMS message) the term "share" using the device **110**. In another embodiment, the user may speak the terms "hide" or "share" to temporarily revoke consent or to indicate consent to the monitoring of the location of the vehicle, respectively. In one embodiment, words other than "hide" or "share" may be used to temporarily revoke consent or to indicate consent to the monitoring of the location of the vehicle, respectively.

FIG. 8 illustrates an exemplary user interface **800** for use in conjunction with a system for monitoring of the location of the vehicle. The user interface **800** is operable by the requesting party or the receiving party to set up monitoring of the location of the vehicle, display information regarding monitoring of the location of the vehicle, and display location of the vehicle.

In the illustrated embodiment, the user interface **800** displays Start/End Monitoring buttons **810a-g** operable by a user to end or start monitoring of the location of the vehicle. The user interface **800** further displays the Telephone Number corresponding to the communications device associated with the user associated with the vehicle. The user interface **800** further displays the Monitoring Term, which corresponds to the total amount of time (e.g., 2 hours) that the location of the associated vehicle will be monitored. The user interface **800** further displays the Monitoring Interval, which corresponds to how often within the Monitoring Term (e.g., every 15 minutes) the location of the vehicle is updated. In the illustrated embodiment, the user interface **800** displays the Location as latitude and longitude coordinates. In another embodiment, the user interface **800** displays the Location in a format other than latitude and longitude coordinates. In one embodi-

ment, a user may click on Location to display a map that includes a mark indicating the location of the vehicle on the map.

In one embodiment, an operator of a system for monitoring location of a vehicle or some other party who provides vehicle location monitoring services to a user charges fees to the user on a per-load basis or a per-time-monitored basis. A common practice in the vehicle location monitoring services industry is to charge a user a standard flat monthly fee for monitoring services. This is, at least in part, due to limitations of conventional systems for monitoring vehicle location. The systems and methods for monitoring location of a vehicle disclosed herein provide the provider of vehicle location monitoring services with the ability to charge for the services on a per-load basis or a per-time-monitored basis. For example, a user may operate the user interface **800** or any other means to interface with the system for monitoring location of vehicles to set a time to start or end monitoring of the location of five vehicles (e.g., Start/End Monitoring buttons **810a-g**).

In one embodiment where the provider of vehicle location monitoring services provides its services on a per-load or a per-time-monitored basis at a set or negotiated rate per load per unit time, the system may keep track of the number of vehicles (i.e., five) whose location is monitored, as well as the total amount of time for which vehicles' location is monitored (i.e., total time \times 5 vehicles \times rate). The operator may use the Monitoring Term to establish the total amount of time (e.g., 2 hours) or the Monitoring Interval to establish the frequency within the Monitoring Term (e.g., every 15 minutes) that the location of the vehicle or vehicles is monitored. With this information available to the operator's billing system, the operator can charge fees to the user on a per-load basis or a per-time-monitored basis.

In the illustrated embodiment, the user interface displays a Partner/Code. The Partner/Code field may display a code corresponding to a partner company or driver. For example, a carrier A may subcontract with another carrier NAT to move freight from location **1** to location **2**. The user interface displays the carrier NAT associated with the Telephone Number 555-555-5555.

The user interface **800** further displays a Reference Number. In one embodiment, the Reference Number field is a customizable field that carriers can use to identify a particular load, a particular vehicle, a particular order, etc. In one embodiment, the Reference Number appears in invoices and other documents to facilitate efficient system administration.

The user interface **800** further displays the Status of the vehicle. For example, the Status may indicate that the system is Monitoring the vehicle. In another example, the Status may display that the vehicle is Hidden to indicate that the user associated with the vehicle has temporarily revoked consent to monitoring of the vehicle's location. Other possible Status indicators include: (a) Ready to monitor, which indicates that the monitoring of the location of the vehicle is setup and the system is awaiting location information data, (b) Expired, which indicates that the Monitoring Term has expired, and (c) Denied, which indicates that the user denied consent to monitoring the location of the vehicle.

In one embodiment, the user interface **800** is used to add vehicles whose location is to be monitored. A user may use field **820** to enter the identifier corresponding to the communications device associated with the vehicle whose location is to be monitored. In one embodiment (not illustrated), the user interface **800** provides a pull-down menu from which the user may choose an identifier. The user may further enter the Monitoring Term in field **830**, the Monitoring Interval in field **840**, the Partner/Code in field **850** and the Reference Number in

field **860**. In one embodiment (not illustrated), the user interface **800** provides each of these fields as pull-down menus.

In some cases, the requesting party may not know the identifier corresponding to the vehicle or the user may know the identifier but not have authorization to monitoring the location of the vehicle associated with the identifier. In one embodiment (not shown), the user may enter a Partner/Code that serves as verification that the user has obtained authorization from the partner to monitor location of the vehicle associated with the identifier. This feature may also serve to keep the user from learning the identifier in cases where the user associated with the vehicle, the partner, or some other party desires not to reveal the identifier to the requesting party.

In one embodiment, the user associated with the vehicle (e.g., driver) may enter the Partner/Code. For example, the user associated with the vehicle may be an independent driver who wishes for the location information of his vehicle to be monitored by a carrier so that the carrier may assign freight for the driver to haul. However, the carrier may not want every driver in the field to do this freely because of the potential costs associated with monitoring the location of a large number of vehicles. The carrier may require the driver to enter a Partner/Code obtained from the carrier that serves as verification that the driver has obtained authorization from the carrier for the location of the driver's vehicle to be monitored by the carrier.

Referring now to FIG. 9, an application programming interface (API) **900** is illustrated providing access to a system **910** for monitoring location of a vehicle to a receiving party. The API **900** can be employed, for example, by a programmer **920** or a process **930** to gain access to processing performed by the system **910**. For example, a programmer **920** can write a program to access the system **910** (e.g., invoke its operation, obtain its operation, set up its operation, monitor location of a vehicle) where writing the program is facilitated by the presence of the API **900**. Rather than programmer **920** having to understand the internals of the system **910**, the programmer **920** merely has to learn the interface to the system **910**. This facilitates encapsulating the functionality of the system **910** while exposing that functionality.

Similarly, the API **900** can be employed to provide data values to the system **910** or retrieve data values from the system **910**. For example, a process **930** that processes location of a vehicle can provide an identifier to the system **910** via the API **900** by, for example, using a call provided in the API **900**. Thus, in one example of the API **900**, a set of application programming interfaces can be stored on a computer-readable medium. The interfaces can be employed by a programmer, computer component, logic, and so on, to gain access to a system **910** for monitoring location of a vehicle.

FIG. 10 illustrates a computer **1000** that includes a processor **1002**, a memory **1004**, and I/O Ports **1010** operably connected by a bus **1008**. In one example, the computer **1000** may include a validation logic **1030** configured to facilitate validation of a communications device. Thus, the validation logic **1030**, whether implemented in computer **1000** as hardware, firmware, software, or a combination thereof may provide means for identifying the communications device at least in part by obtaining an identifier associated with the communications device. In another example, the computer **1000** may include a notification logic **1040** configured to provide notification to the user associated with a vehicle. Thus, the notification logic **1040**, whether implemented in computer **1000** as hardware, firmware, software, or a combination thereof may provide means for communicating a signal including data representing automated voice messages that provide

notices or directs the user of the communications device to notices that include information indicating (a) that consenting to the monitoring of the vehicle will result in the location information of the vehicle or the communications device being disclosed, (b) that the user may revoke notice by operation of the communications device, and so on. In yet another example, the computer **1000** may include a correlation logic **1070** configured to correlate a vehicle to a communications device or the location information of a communications device to the location of a vehicle based at least in part on the communications device being associated with a user of the communications device who is associated with the vehicle. Thus, the correlation logic **1070**, whether implemented in computer **1000** as hardware, firmware, software, or a combination thereof may provide means for correlating a vehicle to a communications device based at least in part on the communications device being associated with the user who is associated with the vehicle, means for correlating the location information of the communications device with the location of the vehicle based at least in part on the communications device being associated with the user who is associated with the vehicle, or means for transforming the location information of the communications device into location information regarding the vehicle based at least in part on the communications device being associated with the user of the communications device who is also associated with the vehicle. The validation logic **1030**, the notification logic **1040**, or the correlation logic **1070** may be permanently or removably attached to the computer **1000**.

The processor **1002** can be a variety of various processors including dual microprocessor and other multi-processor architectures. The memory **1004** can include volatile memory or non-volatile memory. The non-volatile memory can include, but is not limited to, ROM, PROM, EPROM, EEPROM, and the like. Volatile memory can include, for example, RAM, synchronous RAM (SRAM), dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), and direct RAM bus RAM (DRRAM).

A disk **1006** may be operably connected to the computer **1000** via, for example, a communications interface (e.g., card, device) **1018** and an I/O Ports **1010**. The disk **1006** can include, but is not limited to, devices like a magnetic disk drive, a solid state disk drive, a floppy disk drive, a tape drive, a Zip drive, a flash memory card, or a memory stick. Furthermore, the disk **1006** can include optical drives like a CD-ROM, a CD recordable drive (CD-R drive), a CD rewriteable drive (CD-RW drive), or a digital video ROM drive (DVD ROM). The memory **1004** can store processes **1014** or data **1016**, for example. The disk **1006** or memory **1004** can store an operating system that controls and allocates resources of the computer **1000**.

The bus **1008** can be a single internal bus interconnect architecture or other bus or mesh architectures. While a single bus is illustrated, it is to be appreciated that computer **1000** may communicate with various devices, logics, and peripherals using other busses that are not illustrated (e.g., PCIE, SATA, Infiniband, 1394, USB, Ethernet). The bus **1008** can be of a variety of types including, but not limited to, a memory bus or memory controller, a peripheral bus or external bus, a crossbar switch, or a local bus. The local bus can be of varieties including, but not limited to, an industrial standard architecture (ISA) bus, a microchannel architecture (MCA) bus, an extended ISA (EISA) bus, a peripheral component interconnect (PCI) bus, a universal serial (USB) bus, and a small computer systems interface (SCSI) bus.

The computer **1000** may interact with input/output devices via communications interface **1018** and I/O Ports **1010**. Input/output devices can include, but are not limited to, a keyboard, a microphone, a pointing and selection device, cameras, video cards, displays, disk **1006**, network devices **1020**, and the like. The I/O Ports **1010** can include but are not limited to, serial ports, parallel ports, and USB ports.

The computer **1000** can operate in a network environment and thus may be connected to network devices **1020** via the communications interface **1018**, or the I/O Ports **1010**. Through the network devices **1020**, the computer **1000** may interact with a network. Through the network, the computer **1000** may be logically connected to remote computers. The networks with which the computer **1000** may interact include, but are not limited to, a local area network (LAN), a wide area network (WAN), and other networks. The network devices **1020** can connect to LAN technologies including, but not limited to, fiber distributed data interface (FDDI), copper distributed data interface (CDDI), Ethernet (IEEE 802.3), token ring (IEEE 802.5), wireless computer communication (IEEE 802.11), Bluetooth (IEEE 802.15.1), Zigbee (IEEE 802.15.4) and the like. Similarly, the network devices **1020** can connect to WAN technologies including, but not limited to, point to point links, circuit switching networks like integrated services digital networks (ISDN), packet switching networks, LTE networks, GSM networks, GPRS networks, CDMA networks, and digital subscriber lines (DSL). While individual network types are described, it is to be appreciated that communications via, over, or through a network may include combinations and mixtures of communications.

DEFINITIONS

The following includes definitions of selected terms employed herein. The definitions include various examples, forms, or both of components that fall within the scope of a term and that may be used for implementation. The examples are not intended to be limiting. Both singular and plural forms of terms may be within the definitions.

As used in this application, the term “computer component” refers to a computer-related entity, either hardware, firmware, software, a combination thereof, or software in execution. For example, a computer component can be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and a computer. By way of illustration, both an application running on a server and the server can be computer components. One or more computer components can reside within a process or thread of execution and a computer component can be localized on one computer or distributed between two or more computers.

“Computer communication,” as used herein, refers to a communication between two or more computing devices (e.g., computer, personal digital assistant, cellular telephone) and can be, for example, a network transfer, a file transfer, an applet transfer, an email, a hypertext transfer protocol (HTTP) transfer, and so on. A computer communication can occur across, for example, a wireless system (e.g., IEEE 802.11, IEEE 802.15), an Ethernet system (e.g., IEEE 802.3), a token ring system (e.g., IEEE 802.5), a local area network (LAN), a wide area network (WAN), a point-to-point system, a circuit switching system, a packet switching system, combinations thereof, and so on.

“Computer-readable medium,” as used herein, refers to a medium that participates in directly or indirectly providing signals, instructions or data. A computer-readable medium may take forms, including, but not limited to, non-volatile

media, volatile media, and transmission media. Non-volatile media may include, for example, optical or magnetic disks, and so on. Volatile media may include, for example, optical or magnetic disks, dynamic memory and the like. Transmission media may include coaxial cables, copper wire, fiber optic cables, and the like. Transmission media can also take the form of electromagnetic radiation, like that generated during radio-wave and infra-red data communications, or take the form of one or more groups of signals. Common forms of a computer-readable medium include, but are not limited to, a floppy disk, a flexible disk, a hard disk, a magnetic tape, other magnetic media, a CD-ROM, other optical media, punch cards, paper tape, other physical media with patterns of holes, a RAM, a ROM, an EPROM, a FLASH-EPROM, or other memory chip or card, a memory stick, a carrier wave/pulse, and other media from which a computer, a processor or other electronic device can read. Signals used to propagate instructions or other software over a network, like the Internet, can be considered a “computer-readable medium.”

“Data store,” as used herein, refers to a physical or logical entity that can store data. A data store may be, for example, a database, a table, a file, a list, a queue, a heap, a memory, a register, and so on. A data store may reside in one logical or physical entity or may be distributed between two or more logical or physical entities.

A “logic,” as used herein, includes but is not limited to hardware, firmware, software or combinations of each to perform a function(s) or an action(s), or to cause a function or action from another logic, method, or system. For example, based on a desired application or needs, a logic may include a software controlled microprocessor, discrete logic like an application specific integrated circuit (ASIC), a programmed logic device, a memory device containing instructions, or the like. A logic may include one or more gates, combinations of gates, or other circuit components. A logic may also be fully embodied as software. Where multiple logical logics are described, it may be possible to incorporate the multiple logical logics into one physical logic. Similarly, where a single logical logic is described, it may be possible to distribute that single logical logic between multiple physical logics.

An “operable connection,” or a connection by which entities are “operably connected,” is one in which signals, physical communications, or logical communications may be sent or received. Typically, an operable connection includes a physical interface, an electrical interface, or a data interface, but it is to be noted that an operable connection may include differing combinations of these or other types of connections sufficient to allow operable control. For example, two entities can be operably connected by being able to communicate signals to each other directly or through one or more intermediate entities like a processor, operating system, a logic, software, or other entity. Logical or physical communication channels can be used to create an operable connection.

“Signal,” as used herein, includes but is not limited to one or more electrical or optical signals, analog or digital signals, data, one or more computer or processor instructions, messages, a bit or bit stream, or other means that can be received, transmitted or detected.

“Software,” as used herein, includes but is not limited to, one or more computer or processor instructions that can be read, interpreted, compiled, or executed and that cause a computer, processor, or other electronic device to perform functions, actions or behave in a desired manner. The instructions may be embodied in various forms like routines, algorithms, modules, methods, threads, or programs including separate applications or code from dynamically or statically linked libraries. Software may also be implemented in a vari-

ety of executable or loadable forms including, but not limited to, a stand-alone program, a function call (local or remote), a servlet, an applet, instructions stored in a memory, part of an operating system or other types of executable instructions. It will be appreciated by one of ordinary skill in the art that the form of software may depend, for example, on requirements of a desired application, the environment in which it runs, or the desires of a designer/programmer or the like. It will also be appreciated that computer-readable or executable instructions can be located in one logic or distributed between two or more communicating, co-operating, or parallel processing logics and thus can be loaded or executed in serial, parallel, massively parallel and other manners.

Suitable software for implementing the various components of the example systems and methods described herein may be produced using programming languages and tools like Java, Java Script, Java.NET, ASP.NET, VB.NET, Cocoa, Pascal, C#, C++, C, CGI, Perl, SQL, APIs, SDKs, assembly, firmware, microcode, or other languages and tools. Software, whether an entire system or a component of a system, may be embodied as an article of manufacture and maintained or provided as part of a computer-readable medium as defined previously. Another form of the software may include signals that transmit program code of the software to a recipient over a network or other communication medium. Thus, in one example, a computer-readable medium has a form of signals that represent the software/firmware as it is downloaded from a web server to a user. In another example, the computer-readable medium has a form of the software/firmware as it is maintained on the web server. Other forms may also be used.

“User,” as used herein, includes but is not limited to one or more persons, software, computers or other devices, or combinations of these.

To the extent that the term “includes” or “including” is employed in the detailed description or the claims, it is intended to be inclusive in a manner similar to the term “comprising” as that term is interpreted when employed as a transitional word in a claim. Furthermore, to the extent that the term “or” is employed in the detailed description or claims (e.g., A or B) it is intended to mean “A or B or both”. When the applicants intend to indicate “only A or B but not both” then the term “only A or B but not both” will be employed. Thus, use of the term “or” herein is the inclusive, and not the exclusive use. See, Bryan A. Garner, *A Dictionary of Modern Legal Usage* 624 (2d. Ed. 1995).

While example systems, methods, and so on, have been illustrated by describing examples, and while the examples have been described in considerable detail, it is not the intention to restrict or in any way limit the scope of the appended claims to such detail. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the systems, methods, and so on, described herein. Additional advantages and modifications will readily appear to those skilled in the art. Therefore, the invention is not limited to the specific details, and illustrative examples shown or described. Thus, this application is intended to embrace alterations, modifications, and variations that fall within the scope of the appended claims. Furthermore, the preceding description is not meant to limit the scope of the invention. Rather, the scope of the invention is to be determined by the appended claims and their equivalents.

The invention claimed is:

1. A method for a machine or group of machines to monitor location of at least one of a vehicle or freight carried by the vehicle, the method comprising:

receiving a location request signal including data representing a request for information regarding the location of the at least one of the vehicle or the freight carried by the vehicle;

receiving a signal including data that indicates consent to transmission of location information of a communications device; 5

correlating, by a CPU, the at least one of the vehicle or the freight carried by the vehicle with the communications device;

transmitting a location information request signal including data representing a request for location information of the communications device to a location information provider corresponding to a party or device other than the communications device;

receiving a location information signal including data representing the location information of the communications device from the location information provider;

correlating, by the CPU or a second CPU, the location information of the communications device to the location of the at least one of the vehicle or the freight carried by the vehicle based at least in part on the correlation of the at least one of the vehicle or the freight carried by the vehicle to the communications device; and 20

transmitting a location signal including data representing the location of the at least one of the vehicle or the freight carried by the vehicle, the location signal configured to cause a representation of the location of the vehicle or the freight carried by the vehicle. 25

2. The method of claim **1**, wherein the location information provider corresponds to at least one of: 30

- a wireless service provider providing wireless service to the communications device,
- a third party that obtains the location information of the communications device from the wireless service provider providing wireless service to the communications device, and 35
- a party that has access to the location information of the communications device but is other than the wireless service provider or the third party that obtains the location information of the communications device from the wireless service provider. 40

3. The method of claim **1**, wherein the location information of the communications device is originally obtained using a method including a technique utilizing a global position system (GPS) satellite receiver that forms part of the communications device. 45

4. The method of claim **1**, wherein the location information of the communications device is originally obtained using a method including a technique other than a technique utilizing a global position system (GPS) satellite receiver that forms part of the communications device. 50

5. The method of claim **1**, wherein the transmitting the location signal including data representing the location of the at least one of the vehicle or the freight carried by the vehicle includes exposing an application programming interface (API) from which the location of the at least one of the vehicle or the freight carried by the vehicle is transmitted. 55

6. The method of claim **1**, wherein the transmitting the location signal including data representing the location of the at least one of the vehicle or the freight carried by the vehicle includes interfacing with an exposed application programming interface (API) through which the location of the at least one of the vehicle or the freight carried by the vehicle is transmitted. 60

7. The method of claim **1**, wherein the transmitting the location signal including data representing the location of the 65

at least one of the vehicle or the freight carried by the vehicle includes transmitting the location signal to one or more of:

- a freight service provider,
- a party to whom the freight service provider provides freight services, and
- a party that provides location information services to the freight service provider or to the party to whom the freight service provider provides freight services.

8. The method of claim **1**, wherein the location signal is configured to cause display of a visual representation of the location of the vehicle or the freight carried by the vehicle on a remote device's user interface by displaying the location of the vehicle or the freight carried by the vehicle as latitude and longitude coordinates. 10

9. The method of claim **1**, wherein the location signal is configured to cause display of a visual representation of the location of the vehicle or the freight carried by the vehicle on a remote device's user interface by displaying the location of the vehicle or the freight carried by the vehicle as at city/state. 15

10. The method of claim **1**, wherein the location signal is configured to cause display of a visual representation of the location of the vehicle or the freight carried by the vehicle on a remote device's user interface by displaying a map that includes a mark indicating the location of the vehicle on the map. 20

11. A machine or group of machines embodying a system for monitoring location of at least one of a vehicle or freight carried by the vehicle, the system comprising:

- a logic configured to determine whether consent was given to transmit location information of a communications device;
- a correlation logic configured to correlate, by a CPU, the location of the at least one of the vehicle or the freight carried by the vehicle with the location information of the communications device based at least in part on a correlation between the at least one of the vehicle or the freight carried by the vehicle and the communications device; and
- a communications interface configured to communicate electronic signals including: 40

- a location request signal received from a requesting party including data representing a request for information regarding the location of the at least one of the vehicle or the freight carried by the vehicle,
- a location information request signal transmitted to a location information provider corresponding to a party or device other than the communications device including data representing a request for location information of the communications device,
- a location information signal received from the location information provider including data representing the location information of the communications device, and
- a location signal including data representing the location of the at least one of the vehicle or the freight carried by the vehicle to cause a representation of the location of the vehicle or the freight carried by the vehicle by a remote device. 50

12. The system of claim **11**, wherein the location information provider corresponds to at least one of: 55

- a wireless service provider providing wireless service to the communications device,
- a third party that obtains the location information of the communications device from the wireless service provider providing wireless service to the communications device, and
- a party that has access to the location information of the communications device but is other than the wireless 60

23

service provider or the third party that obtains the location information of the communications device from the wireless service provider.

13. The system of claim 11, wherein the location information of the communications device is originally obtained using a method including a technique utilizing a global position system (GPS) satellite receiver that forms part of the communications device.

14. The system of claim 11, wherein the location information of the communications device is originally obtained using a method including a technique other than a technique utilizing a global position system (GPS) satellite receiver that forms part of the communications device.

15. The system of claim 11, wherein the communications interface transmitting the location signal including data representing the location of the at least one of the vehicle or the freight carried by the vehicle includes the communications interface exposing an application programming interface (API) from which the location of the at least one of the vehicle or the freight carried by the vehicle is obtained by the requesting party.

16. The system of claim 11, wherein the communications interface transmitting the location signal including data representing the location of the at least one of the vehicle or the freight carried by the vehicle includes the communications interface interfacing with an exposed application programming interface (API) through which the location of the at least one of the vehicle or the freight carried by the vehicle is transmitted.

24

17. The system of claim 11, wherein the requesting party corresponds to one or more of:

a freight service provider,

a party to whom the freight service provider provides freight services, and

a party that provides location information services to the freight service provider or to the party to whom the freight service provider provides freight services.

18. The system of claim 11, wherein the location signal is configured to cause display of a visual representation of the location of the vehicle or the freight carried by the vehicle on the remote device's user interface by displaying the location of the vehicle or the freight carried by the vehicle as latitude and longitude coordinates.

19. The system of claim 11, wherein the location signal is configured to cause display of a visual representation of the location of the vehicle or the freight carried by the vehicle on the remote device's user interface by displaying the location of the vehicle or the freight carried by the vehicle as city/state.

20. The system of claim 11, wherein the location signal is configured to cause display of a visual representation of the location of the vehicle or the freight carried by the vehicle on the remote device's user interface by displaying a map that includes a mark indicating the location of the vehicle on the map.

* * * * *