



US 20030167733A1

(19) **United States**

(12) **Patent Application Publication**

**Weder et al.**

(10) **Pub. No.: US 2003/0167733 A1**

(43) **Pub. Date: Sep. 11, 2003**

(54) **SINGLE STATION COVERING AND FASTENING SYSTEM**

(76) Inventors: **Donald E. Weder**, Highland, IL (US);  
**Joseph G. Straeter**, Highland, IL (US);  
**Paul Fantz**, Imperial, MO (US)

Correspondence Address:

**DUNLAP, CODDING & ROGERS P.C.**  
**PO BOX 16370**  
**OKLAHOMA CITY, OK 73114 (US)**

5,636,502, which is a continuation of application No. 08/252,876, filed on Jun. 2, 1994, now Pat. No. 5,609,009, which is a continuation-in-part of application No. 08/088,692, filed on Jul. 7, 1993, now Pat. No. 5,481,850.

**Publication Classification**

(51) **Int. Cl.<sup>7</sup>** ..... **B65B 25/02**  
(52) **U.S. Cl.** ..... **53/176**

(21) Appl. No.: **10/390,371**


(22) Filed: **Mar. 17, 2003**

**Related U.S. Application Data**

(60) Continuation of application No. 10/005,005, filed on Dec. 4, 2001, which is a continuation of application No. 09/746,384, filed on Dec. 21, 2000, now Pat. No. 6,370,840, which is a continuation of application No. 09/491,003, filed on Jan. 25, 2000, now Pat. No. 6,178,727, which is a division of application No. 09/035,473, filed on Mar. 5, 1998, now Pat. No. 6,112,500, which is a continuation of application No. 08/796,099, filed on Feb. 5, 1997, now Pat. No. 5,740,656, which is a continuation of application No. 08/462,342, filed on Jun. 5, 1995, now Pat. No.

(57) **ABSTRACT**

An apparatus and method for forming a cover about an article and for automatically fastening the cover to the article, and optionally for automatically placing a label on the covered article. The article may be an article such as a potted plant and the cover may be a decorative cover. The invention satisfies the need for a means for rapidly covering and fastening the cover about an article with a minimal amount of manual effort and in a location having a limited amount of available space. The apparatus comprises a platform having at least one opening sized to receive the article. The apparatus comprises a tying device for automatically applying a band or fastener about a portion of the outer surface of the covered article for fastening the cover about the article after the sheet is formed into a cover about the article.






FIG. 1

FIG. 2




FIG. 3















FIG. 4









**FIG. 14**




**FIG. 15**




**FIG. 16**




**FIG. 17**




**FIG. 18**




**FIG. 19**




**FIG. 20**




**FIG. 21**




**FIG. 22**




**FIG. 23**




**FIG. 24**





**FIG. 25**



**FIG. 26**



**FIG. 27**






FIG. 30






FIG. 31



**FIG. 32**



**FIG. 33**




FIG. 34









FIG. 35







**FIG. 40**

## SINGLE STATION COVERING AND FASTENING SYSTEM

### CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a continuation of U.S. Ser. No. 10/005,005, filed Dec. 4, 2001, which is a continuation of U.S. Ser. No. 09/746,384, filed Dec. 12, 2000, now U.S. Pat. No. 6,370,840, issued Apr. 16, 2002, which is a continuation of Ser. No. 09/491,003, filed Jan. 25, 2000, now U.S. Pat. No. 6,178,727, issued Jan. 30, 2001, which is a divisional of Ser. No. 09/035,473, filed Mar. 5, 1998, now U.S. Pat. No. 6,112,500, issued Sept. 5, 2000, which is a continuation of Ser. No. 08/796,099, filed Feb. 5, 1997, now U.S. Pat. No. 5,740,656, issued Apr. 21, 1998, which is a continuation of Ser. No. 08/462,342, filed Jun. 5, 1995, now U.S. Pat. No. 5,636,502, issued Jun. 10, 1997, which is a continuation of Ser. No. 08/252,876, filed Jun. 2, 1994, now U.S. Pat. No. 5,609,009, issued Mar. 11, 1997, which is a continuation-in-part of U.S. Ser. No. 08/088,692, filed Jul. 7, 1993, now U.S. Pat. No. 5,481,850, issued Jan. 9, 1996, the contents of which are hereby expressly incorporated herein by reference.

### BACKGROUND

[0002] The present invention relates to an apparatus and method for placing a cover about an article, automatically applying a fastener about the covered article and removing the covered article at a single station, and more particularly, but not by way of limitation, to such apparatus and methods wherein the article is a potted plant.

### DESCRIPTION OF THE DRAWINGS

[0003] FIG. 1 is a plan view of a first sheet of material with one end turned up and constructed in accordance with the present invention.

[0004] FIG. 2 is a plan view of a second sheet of material with one end turned up and constructed in accordance with the present invention.

[0005] FIG. 3 is a perspective view showing the first and the second sheets of material disposed adjacent each other.

[0006] FIG. 4 is a perspective view showing bonding areas on the surface of a first sheet or a second sheet which cause bonding of the second sheet and the first sheet.

[0007] FIG. 5 is a cross-sectional view of a modified first and second sheets of material.

[0008] FIG. 6 is another cross-sectional view of a modified first sheet of material connected to a modified second sheet of material.

[0009] FIG. 7 is a cross-sectional view of still another modified first sheet of material connected to a modified second sheet of material.

[0010] FIG. 8 is another cross-sectional view of yet another modified first sheet of material connected to a modified second sheet of material.

[0011] FIG. 9 is a diagrammatic view of a plurality of sheets of material, constructed in accordance with the present invention forming a continuous roll, the roll partially unrolled to reveal a single sheet still attached thereto.

[0012] FIG. 10 is a diagrammatic view of a plurality of sheets of material forming a continuous roll of material disposed in a dispenser.

[0013] FIG. 11 is a diagrammatic view showing a roll of material wherein the roll of material comprises a first and a second sheet of material constructed in accordance with the present invention disposed in a dispenser for dispensing the first and the second sheets of material from the roll of material.

[0014] FIG. 12 is a diagrammatic view of a roll of material for dispensing a first and a second sheet of material constructed in accordance with the present invention from the roll of material.

[0015] FIG. 13 is a side elevational view of a pad of first and second sheets of material constructed in accordance with the present invention.

[0016] FIG. 14 is a perspective view of another embodiment of a sheet of material of the present invention, and a flower pot disposed upon the sheet.

[0017] FIG. 15 is a perspective view of the sheet of material of FIG. 14 shown partially wrapped about the flower pot.

[0018] FIG. 16 is a perspective view of the sheet of material wrapped about the flower pot.

[0019] FIG. 17 is a perspective view of a pre-formed decorative pot cover.

[0020] FIG. 18 is a perspective view of a potted plant wrapped by a sheet of material to form a covered potted plant.

[0021] FIG. 19 is a plan view of a sheet of material with a sheet extension connected thereto constructed in accordance with the present invention.

[0022] FIG. 20 is a perspective view of a flower pot having a floral grouping disposed therein.

[0023] FIG. 21 is a perspective view of the sheet of material of FIG. 19 formed into a pot cover with the sheet extension connected thereto.

[0024] FIG. 22 is a perspective view showing the flower pot of FIG. 20 disposed in the pot cover of FIG. 21 with the sheet extension formed about the floral grouping.

[0025] FIG. 23 is a plan view showing the upper surface of another sheet of material with a sheet extension connected thereto constructed in accordance with the present invention.

[0026] FIG. 24 is a partial sectional view showing the sheet of material of FIG. 23 crimpingly formed about a flower pot and the sheet extension formed about a floral grouping to provide a protective covering.

[0027] FIG. 25 is a sectional view of a portion of the sheet of material crimped to form an overlapping fold.

[0028] FIG. 26 is a plan view of a covering and fastening assembly constructed in accordance with the present invention which applies a band or fastener below a support surface.

[0029] FIG. 27 is an elevational view of the cover and fastening assembly of FIG. 26.

[0030] FIG. 28 is a partial cross-sectional side elevational view of the covering and fastening assembly of FIG. 26.

[0031] FIG. 29 is a plan view of another version of covering and fastening assembly constructed in accordance with the present invention which applies a band or fastener above an upper support assembly.

[0032] FIG. 30 is a partial cross-sectional, front elevational view of the covering and fastening assembly of FIG. 29.

[0033] FIG. 31 is a partial cross-sectional side elevational view of the covering and fastening assembly of FIG. 30.

[0034] FIG. 32 is a plan view of another version of the present invention using another fastener retraction system.

[0035] FIG. 33 is a partial cross-sectional side view of the apparatus of FIG. 32.

[0036] FIG. 34 is a plan view of yet another version of a covering and fastening assembly.

[0037] FIG. 35 is a plan view of the covering and fastening assembly of FIG. 34 at a later operation phase.

[0038] FIG. 36 is an enlarged perspective view of the fastener retraction assembly of FIG. 34.

[0039] FIG. 37 is a side view of another version of a covering and fastening assembly of the present invention in which a sheet of material is provided from a roll of material.

[0040] FIG. 38 is a plan view of another version of a covering and fastening assembly of the present invention using another fastener retraction system.

[0041] FIG. 39 is a partial cross-sectional side view of the covering and fastening assembly of FIG. 38 shown in one stage of operation.

[0042] FIG. 40 is a partial cross-sectional, side view of the covering and fastening assembly of FIG. 38 shown in a stage of operation subsequent to the stage shown in FIG. 39.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0043] The present invention comprises an apparatus for fastening a cover to an article, such as a potted plant.

[0044] In a preferred embodiment, the apparatus comprises a platform having an upper support surface formed thereon and at least one opening extending through the upper support surface. The upper support surface is adapted to support at least one sheet of material in a cover forming position over the opening. The opening is sized to accommodate a cover forming mold.

[0045] The apparatus further comprises a cover forming mold disposed below the opening in the support surface. The cover forming mold has contacting portions for contacting the sheet of material. The opening and the cover forming mold are adapted for receiving an article such as a flower pot having an upper end, a lower end, an upper opening and an outer peripheral surface such that when the article is moved in a predetermined direction, such as downward, the lower end of the article is caused to engage a portion of the sheet of material disposed over the opening. The article and portions of the sheet of material thus pass into the cover forming mold causing the sheet of material to engage the outer peripheral surface of the article and the contacting

portions of the cover forming mold as the article is moved. As this happens, portions of the sheet contactingly engage or nearly engage the outer peripheral surface of the article forming a cover about the article and thereby forming a covered article. The cover of the covered article then has an inner surface facing the outer peripheral surface of the article and an exposed outer surface adjacent the inner portion of the mold.

[0046] The apparatus further comprises a fastening device for automatically applying a fastener about a portion of the outer surface of the covered article. The fastening device comprises a fastener retraction assembly for grasping and retracting the fastener for clearing the fastener from the opening to allow clearance for insertion of a pot or article into the opening. In an alternate version, the apparatus may comprise a labeling assembly for automatically applying a label to a portion of the outer surface of the cover of the covered article, preferably after the cover has been fastened to the article.

[0047] The sheet of material used in accordance with the present invention is constructed from a material selected from a group of materials described in greater detail below. The apparatus may further comprise a securing assembly for releasably securing the sheet of material in the cover forming position on the upper support surface for generally immobilizing the sheet prior to the forming step. The apparatus may further comprise a sheet feeder for automatically placing a sheet of material on the support surface and/or a pick and place assembly for picking up the article from an article supply and for placing the article into the opening to form the covered article. Additionally, the apparatus may further comprise a removal assembly for automatically removing the covered article from the opening of the platform.

[0048] The present invention further comprises a method for processing an article, such as a flower pot or potted plant. The first step comprises providing a platform such as described above which has an upper support surface formed thereon and at least one opening extending through the support surface. The opening is sized exactly as described above and has a cover forming mold disposed therein. Each cover forming mold has contacting portions and is sized to receive an article such as a potted plant which has an upper end, a lower end, an opening, and an outer peripheral surface.

[0049] The next step comprises placing a sheet of material in a cover forming position over the opening. The sheet of material, in the cover forming position, is positioned over the cover forming mold in the opening.

[0050] In the next step, a potted plant is covered with the sheet of material by positioning the potted plant in a position over the sheet of material and disposing the lower end of the pot generally above and near the portion of the sheet of material which is above the cover forming mold. The pot is moved in a direction which causes the lower end of the pot to engage a portion of the sheet of material. The sheet of material is thereby caused to contact or nearly contact both the outer peripheral surface of the pot and the contacting portions of the cover forming mold as the pot is moved. The sheet is pressed about the outer peripheral surface of the pot to form a cover about the pot. The cover has an inner surface facing the outer peripheral surface of the pot and an outer surface facing the interior of the mold.

[0051] Following this, a fastener is automatically applied about a portion of the outer surface of the covered pot for fastening the cover about the pot. Then, if a labeling assembly is included as a component of the apparatus a label is automatically applied to a portion of the outer surface of the cover of the covered pot for labeling the covered pot. Finally, the covered pot is removed from the opening. Alternatively, the step of automatically applying a label may occur prior to the step of automatically applying a fastener.

[0052] In an alternative embodiment, the step of placing a sheet of material on the support surface may be performed automatically using an automatic sheet feeding assembly. Also, the step of forming a covered article may be performed automatically by using an automatic pick and place assembly to pick up an article and place it into the opening to form the covered article. Additionally, the step of removing the covered article may further comprise automatically removing the covered article from the opening of the platform.

[0053] The machine may be located on any axis and may be portable or stationary. The machine can use pre-cut sheets fed manually or automatically with a dispenser which feeds a sized sheet from a roll to the proper working position on the machine table. The fastening apparatus may also tie the knot on a radius or on a tangent to the object.

[0054] The Embodiments of FIGS. 1-3

[0055] Shown in FIG. 1 and designated therein by the general reference numeral 10 is a sheet of material. The sheet of material 10 has a first end 12, a second end 14, a first side 16, a second side 18, an upper surface 20 and a lower surface 22.

[0056] A closure bonding material 24 may be disposed on the upper surface 20 of the sheet of material 10, alternatively, the sheet of material 10 may be free of a closure bonding material. As shown in FIG. 1, the closure bonding material 24, if present, may be disposed adjacent the first side 16 of the sheet of material 10 and [extends] extended between the first and the second ends 12 and 14 of the sheet of material 10 or it may be disposed on any other portion of the sheet of material 10. As shown in FIG. 1, the closure bonding material 24 is disposed on the upper surface 20 in a strip of closure bonding material 24, although the closure bonding material 24 also could be applied to the upper surface 20 of the sheet of material 10 in the form of spaced apart spots or the closure bonding material 24 also could be disposed on the upper surface 20 of the sheet of material 10 in any other geometric form and in any pattern including covering the entire upper surface 20 of the sheet of material 10. In this last-mentioned instance, the closure bonding material and the connecting bonding material would be contained within the bonding material covering the sheet of material 10. The term "spot" or "spots" includes any geometric shape of spot including, but not limited to, what is commonly referred to as strips.

[0057] The sheet of material 10 has a thickness in a range from about 0.1 mil to about 30 mils. Preferably, the sheet of material 10 has a thickness in a range from about 0.1 mil to about 5 mils.

[0058] The sheet of material 10 may be any shape and a square or rectangular shape is shown in FIG. 1 only by way of example. The sheet of material 10 for example only may

be square, rectangular, circular or any other geometric shape such as heart shaped, for example only.

[0059] The sheet of material 10 may be constructed of a single layer of material or a plurality of layers of the same or different types of materials. Any thickness of the sheet of material 10 may be utilized in accordance with the present invention as long as the sheet of material 10 is wrappable about an object, such as a plant or flower pot, as described herein. The layers of material comprising the sheet of material 10 may be connected together or laminated or may be separate layers.

[0060] Shown in FIG. 2 is a second sheet of material 26. The second sheet of material 26 has a first end 28, a second end 30, a first side 32, a second side 34, an upper surface 36 and a lower surface 38. The second sheet of material 26, if used is preferably constructed of paper. The term "paper" as used herein means treated or untreated paper, corrugated paper or cardboard or any other form of paper material.

[0061] Referring again to FIG. 1, the first sheet of material 10 has a length 40 extending between the first and the second sides 16 and 18 of the sheet of material 10. The first sheet of material 10 also has a width 42 extending between the first and the second ends 12 and 14 of the first sheet of material 10.

[0062] Referring again to FIG. 2, the second sheet of material 26 has a length 44 extending between the first and the second sides 32 and 34 of the second sheet of material 26. The second sheet of material 26 has a width 46 extending between the first and the second ends 28 and 30 of the second sheet of material 26. In a preferred embodiment, the length 44 of the second sheet of material 26 is less than the length 40 of the first sheet of material 10 as shown in FIG. 3 so that, when the first sheet of material 10 is disposed adjacent the second sheet of material 26, a portion of the first sheet of material 10 adjacent the first side 16 thereof extends a distance beyond the first side 32 of the second sheet of material 26, in a manner and for reason which will be described in greater detail below.

[0063] The first sheet of material 10 has a thickness in a range from about 0.5 mil to about 30 mils and preferably the thickness of the first sheet of material is in a range from about 0.5 mil to about 10 mils. The first sheet of material 10 is constructed of a material which is flexible.

[0064] The second sheet of material 26 has a thickness in a range from about 0.1 mil to about 30 mils and preferably in a range from about 0.1 mil to about 10 mils. The second sheet of material 26 is flexible, but relatively rigid compared to the first sheet of material 10.

[0065] The second sheet of material 26 may be any shape and a square or rectangular shape is shown in FIG. 2 only by way of example. The second sheet of material 26 for example only may be square, rectangular, circular or any other geometric shape.

[0066] The second sheet of material 26 may be constructed of a single layer of materials or a plurality of layers of the same or different types of materials. Any thickness of the second sheet of material 26 may be utilized in accordance with the present invention as long as the second sheet of material 26 is wrappable about an object such as a flower pot, as described herein, and as long as the second sheet of

material **26** provides the rigidity described herein or the absorbency described herein or both. The layers of material comprising the second sheet of material **26** may be connected together or laminated or may be separate layers.

**[0067]** In operation, when a second sheet of material **26** is desired in addition to the first sheet of material **10**, the second sheet of material **26** is placed adjacent the first sheet of material **10** as shown in **FIG. 3**. In this position, the lower surface **38** of the second sheet of material **26** is disposed adjacent the upper surface **20** of the first sheet of material **10**. The width **42** of the first sheet of material **10** is about equal to the width **46** of the second sheet of material **26** so that, when the first and the second sheets of material **10** and **26** are disposed adjacent each other, the first end **28** of the second sheet of material **26** is generally aligned with the first end **12** of the first sheet of material **10**, the second end **30** of the second sheet of material **26** is generally aligned with the second end **14** of the first sheet of material **10**, the second side **18** of the first sheet of material **10** is generally aligned with the second side **34** of the second sheet of material **26** and the first side **16** of the first sheet of material **10** extends a distance beyond the first side **32** of the second sheet of material **26** so that the closure bonding material **24** on the upper surface **20** of the first sheet of material **10** is exposed and not covered by the second sheet of material **26**.

**[0068]** It should be noted that the first and the second sheets of material **10** and **26** each could have virtually identical lengths **40** and **44**. In this case, the second sheet of material **26** is disposed on the first sheet of material **10** in such a manner that the second side **34** of the second sheet of material **26** extends a distance beyond the second side **18** of the first sheet of material **10** whereby the first side **16** of the first sheet of material **10** is spaced a distance from the first side **32** of the second sheet of material **26** thereby leaving the closure bonding material **24** on the first sheet of material **10** exposed and not covered by the second sheet of material **26**. Multiple sheets of material **10** and **26** may be used. Moreover, when multiple sheets of material **10** and **26** are used in combination, the sheets of material **10** and **26** need not be uniform in size or shape. Finally, it will be appreciated that the sheets of material **10** and **26** shown in all embodiments herein are substantially flat.

**[0069]** As noted earlier, the closure bonding material **24** may be disposed on the upper surface of the first sheet of material **10**. The closure bonding material **24** may be applied as a strip or as spots or other shapes. One method for disposing a closure bonding material, in this case an adhesive, is described in U.S. Pat. No. 5,111,637 entitled "Method For Wrapping A Floral Grouping" issued to Weder et al., on May 12, 1992 and which is hereby incorporated herein by reference.

**[0070]** The first sheet of material **10** can be utilized alone or in combination with the second sheet of material **26** to wrap a potted plant or flower pot. The term "flower pot" refers to any type of container used for holding a floral grouping or a potted plant. Examples of flower pots used in accordance with the present invention are clay pots, plastic pots, and the like. "Floral grouping" as used herein means cut fresh flowers, artificial flowers, a single flower other fresh and/or artificial plants or other floral materials and may include other secondary plants and/or ornamentation or artificial or natural materials which add to the aesthetics of

the overall floral arrangement. The floral grouping comprises a bloom or foliage portion and a stem portion. However, it will be appreciated that the floral grouping may consist of only a single bloom or only foliage (not shown). The term "floral grouping" may be used interchangeably herein with the term "floral arrangement".

**[0071]** The first sheet of material **10** or the second sheet of material **26** may be constructed of a single layer of material or a plurality of layers of the same or different types of materials. Any thickness of the sheet of material **10** or **26** may be utilized in accordance with the present invention as long as the sheet of material **10** or **26** may be wrapped or formed about at least a portion of a portion of a flower pot, as described herein. Additionally, an insulating material such as bubble film, preferable as one of two or more layers, can be utilized in order to provide additional protection for the item wrapped therein.

**[0072]** In a preferred embodiment, the first sheet of material **10** is constructed from two polypropylene films (a 20"x15" sheet of Mobil 270 ABW white opaque film laminated to a 20"x15" sheet of Mobil 220 AB clear film) having a thickness in a range of from less than about 1.0 mil to about 2.5 mils. The layers of material comprising the first sheet of material **10** may be connected together or laminated or may be separate layers.

**[0073]** The sheet of material **10** is constructed from any suitable wrapping material that is capable of being wrapped about a flower pot or floral grouping, as the case may be. Preferably, the sheet of material **10** comprises paper (untreated or treated in any manner), cellophane, foil, polymer film, fabric (woven or nonwoven or synthetic or natural), burlap, or combinations thereof.

**[0074]** The term "polymer film" means a man-made polymer such as a polypropylene or a naturally occurring polymer such as cellophane. A polymer film is relatively strong and not as subject to tearing (substantially non-tearable), as might be the case with paper or foil.

**[0075]** The sheet of material **10** or **26** may vary in color. Further, the sheet of material **10** or **26** may consist of designs or decorative patterns which are printed, etched, and/or embossed thereon using inks or other printing materials. An example of an ink which may be applied to the surface of the sheet of material **10** or **26** is described in U.S. Pat. No. 5,147,706 entitled "Water Based Ink On Foil And/Or synthetic organic polymer" issued to Kingman on Sep. 15, 1992 and which is hereby incorporated herein by reference. In addition, the sheet of material **10** or **26** may have various colorings, coatings, flocking and/or metallic finishes, or other decorative surface ornamentation applied separately or simultaneously or may be characterized totally or partially by pearlescent, translucent, transparent, iridescent or the like, qualities. Each of the above-named characteristics may occur alone or in combination and may be applied to the upper and/or lower surface of the sheet of material **10** or **26**. Moreover, each surface of the sheet of material **10** or **26** may vary in the combination of such characteristics. The sheet of material **10** or **26** itself may be opaque, translucent or partially clear or tinted transparent.

**[0076]** Embodiments of **FIGS. 4-8**

**[0077]** Referring now to **FIG. 4**, the bonding material **24** may be applied to either the upper surface of a first sheet of

material **10a** or to the lower surface of a second sheet of material **26a** of material in a plurality of patches **48** for the purpose of bonding the upper surface of the first sheet of material **10a** to the lower surface of the second sheet of material **26a**.

[0078] Shown in FIG. 5 is a modified first sheet of material **10b** connected to a modified second sheet of material **26b**. The first sheet of material **10b** is constructed exactly like the sheet of material **10**. The second sheet of material **26b** is constructed like the sheet of material **26** described in detail before and shown in FIG. 2, except the second sheet of material **26b** includes a bonding material **60** disposed on a lower surface **38b** of the second sheet of material **26b**. The bonding material **60** is in the form of a plurality of spaced apart spots of bonding material **60**, similar to that shown in FIG. 4. The lower surface **38b** of the second sheet of material **26b** is bondingly connected to an upper surface **20b** of the first sheet of material **10b** by way of the bonding material **60**. Since the bonding material **60** is in the form of a plurality of spaced apart spots, a plurality of spaced apart spaces **62** (only one of the spaces **62** being designated by reference numeral in FIG. 5) are formed between the lower surface **38b** of the second sheet of material **26b** and the upper surface **20b** of the first sheet of material **10b**. The spaces **62** provide air gaps which form an insulation when the first and the second sheets of material **10b** and **26b** are wrapped about a flower pot in a manner and for reasons like that described herein.

[0079] Shown in FIG. 6 is a modified first sheet of material **10c** connected to a modified second sheet of material **26c**. The first sheet of material **10c** is constructed exactly like the sheet of material **10** shown in FIG. 1, except the first sheet of material **10c** includes a bonding material **64** disposed on an upper surface **20c** of the first sheet of material **10c**. The bonding material **64** is in the form of a plurality of spaced apart spots of bonding material **64**, similar to that shown in FIG. 5. A lower surface **38c** of the second sheet of material **26c** is bondingly connected to the upper surface **20c** of the first sheet of material **10c** by way of the bonding material **64**. Since the bonding material **64** is in the form of a plurality of spaced apart spots, a plurality of spaces **66** (only one of the spaces **66** being designated by a reference numeral in FIG. 6) are formed between the lower surface **38c** of the second sheet of material **26c** and the upper surface **20c** of the first sheet of material **10c**. The spaces **66** provide air gaps which form an insulation when the first and the second sheets of material **10c** and **26c** are wrapped about a flower pot in a manner and for reasons like that described herein in connection with FIG. 5.

[0080] Shown in FIG. 7 is a modified first sheet of material **10d** connected to a modified second sheet of material **26d**. The first sheet of material **10d** is constructed exactly like the sheet of material **10** shown in FIG. 1, except the first sheet of material **10d** includes a bonding material **68** on an upper surface **20d** thereof. The second sheet of material **26d** is constructed exactly like the second sheet of material **26** shown in FIG. 2, except the second sheet of material **26d** includes a plurality of spaced apart raised portions **70**. The raised portions **70** may be formed by embossing the second sheet of material **26d** or forming corrugations in the second sheet of material **26d** or in any other manner desired in any particular application.

[0081] The upper surface **20d** of the first sheet of material **10d** is disposed generally adjacent a lower surface **38d** of the second sheet of material **26d** or, more particularly, adjacent the raised portions **70** on the second sheet of material **26d**. In this position, the raised portions **70** are bonded to the upper surface **20d** of the first sheet of material **10d** by way of the bonding material **68** to connect the first sheet of material **10d** to the second sheet of material **26d**.

[0082] The spaced apart raised portions **70** on the second sheet of material **26d** form a plurality of spaces **72** between the first sheet of material **10d** and the second sheet of material **26d** in a connected position of the first and the second sheets of material **10d** and **26d** for providing insulation when the first and second sheets of material **10d** and **26d** are connected together and wrapped about a flower pot in a manner like that described herein.

[0083] Shown in FIG. 8 is a modified first sheet of material **10e** connected to a modified second sheet of material **26e**. The first sheet of material **10e** is constructed exactly like the sheet of material **10** shown in FIG. 1, except the first sheet of material **10e** includes a plurality of spaced apart raised portions **74**. The raised portions **74** may be formed in the first sheet of material **10e** by embossing the first sheet of material **10e** or forming corrugations in the first sheet of material **10e** or in any other suitable manner. The second sheet of material **26e** is constructed exactly like the second sheet of material **26** shown in FIG. 2, except the second sheet of material **26e** includes a bonding material **76** disposed on a lower surface **38e** thereof.

[0084] In operation, an upper surface **20e** of the first sheet of material **10e** is disposed generally adjacent the lower surface **38e** of the second sheet of material **26e** or, more particularly, the raised portions **74** on the first sheet of material **10e** are disposed adjacent the lower surface **38e** of the second sheet of material **26e**. In this position, the first sheet of material **10e** is bondingly connected to the second sheet of material **26e** by way of the bonding material **76** on the second sheet of material **26e** or, more particularly, the bonding material **76** on the second sheet of material **26e** bondingly engages and bondingly connects to the raised portions **74** on the first sheet of material **10e** to connect the first sheet of material **10e** to the second sheet of material **26e**. In this connected position of the first sheet of material **10e** and the second sheet of material **26e**, the raised portions **74** cooperate to form a plurality of spaces **78**. Between the first sheet of material **10e** and the second sheet of material **26e**, the spaces **78** cooperate to provide an insulation when the first and the second sheets of material **10e** and **26e** are wrapped about a flower pot in a manner and for reasons like that described herein.

[0085] Embodiments of FIGS. 9-10

[0086] Referring now to FIG. 9, a plurality of individual sheets of material **10f** are connected linearly together to form a roll **80**. Preferably, the plurality of sheets of material **10f** in the roll **80** are connected by perforations **82**, as illustrated in FIG. 9. Such a roll **80** permits one sheet of material **10f** to be withdrawn from the roll **80**, then severed or disconnected from the roll **80**. Alternatively, as shown in FIG. 10, the roll **80** may simply be formed as a continuous roll **80** of wrapping material without perforations, wherein a plurality of sheets of material **10f** may be removed from the roll **80** by unrolling a portion of the roll **80**, and using a separate

cutting element (not shown) to sever the unrolled portion of the roll **80** of material to form the sheet of material **10f**. The roll **80** may also be contained within a dispenser **84**, as illustrated in **FIG. 10**. When the roll **80** is disposed in the dispenser **84**, a portion of the wrapping material is again unrolled, and a serrated cutting edge **86** contained within the dispenser **84**, or a separate cutting element (not shown), severs the unrolled portion of the wrapping material from the roll **80** to form a sheet of material **10f**. Any number of sheets of material **10f** may form the roll **80** as long as it is possible to withdraw at least one sheet of material **10f** from the roll **80** as described herein.

**[0087]** Embodiments of **FIGS. 11-12**

**[0088]** The first and the second sheets of material described herein can be provided in the form of a roll of first and second sheets of material wherein the first and the second sheets of material are unrolled from the roll of first and second sheets of material and the first and the second sheets of material are severed from the roll either by perforations at spaced apart locations in the roll or by cutting the first and the second sheets of material from the roll. It also should be noted that additional sheets of material may be combined with the first and the second sheets of material if so desired in a particular application.

**[0089]** Shown in **FIG. 11** is a roll of material **90** comprising a first material **92** and a second material **94** with the second material **94** being disposed adjacent the first material **92**. The first material **92** is constructed of any of the materials described before with respect to the first sheet of material. The second material **94** is constructed of any of the materials described before with respect to the second sheet of material.

**[0090]** The roll of material **90** is disposed in a dispenser **96** having an opening **98** through which the first and second materials **92** and **94** may be withdrawn from the roll of material **90**. A cutting edge **100** is disposed on the dispenser **96** near the opening **98**. The cutting edge **100** may be a sawtooth type of edge, as shown in **FIG. 11**, or the cutting edge **100** may be any other type of edge or device suitable for cutting a portion of the first and second materials **92** and **94** from the roll of material **90** and the cutting edge **100** may be connected to the dispenser **96** or may be a separate component if desired in particular application.

**[0091]** The roll of material **90** has a leading edge **102**. In operation, the leading edge **102** is gripped or a portion of the first and/or the second materials **92**, **94** are gripped and the first and the second materials **92**, **94** are unrolled and withdrawn from the roll of material **90** in a direction **104**. The first and the second materials **92** and **94** are withdrawn or unrolled from the roll of material **90** until a desired length of the first and the second materials **92** and **94** have been withdrawn from the roll of material **90**. In this position, a portion of the first and the second materials **92** and **94** are disposed adjacent the cutting edge **100**. The first and the second materials **92** and **94** then are maneuvered to pass the first and second materials **92** and **94** over the cutting edge **100** thereby severing a portion of the material extending a distance from the leading edge **102** thereof from the roll of material **90**. The portion of the first and second materials **92** and **94** withdrawn from the roll of material **90** and severed from the roll of material **90** comprise the first and the second sheets of material **92**, **94** as described herein.

**[0092]** The first and second materials **92** and **94** in the roll of material **90** may be connected or unconnected. Further, the roll of material **90** may comprise two rolls of material with one of the rolls of material comprising the first material **92** and the other roll of material comprising the second material **94**. In this last-mentioned embodiment, the first material **92** is withdrawn from the first roll of material and the second material **94** is withdrawn from the second roll of material about simultaneously so that the first and second materials **92** and **94** are provided in a manner as generally shown in **FIG. 11** for severing from the first and second rolls of material to provide the first and second sheets of materials **92**, **94** as described herein. The term "roll of material" as used herein is intended to encompass two or more rolls in the manner generally described.

**[0093]** Shown in **FIG. 12** is a modified roll of material **90a** comprising a first material **92a** and a second material **94a** with a leading edge **102a**. The roll of material **90a** is constructed exactly like the roll of material **90** described before, except the roll of material **90a** is not disposed in a dispenser constructed like the dispenser **96** shown in **FIG. 11**. Rather, the roll of material **90a** is supported on a generally mounted shaft **106**. The first and the second materials **92a** and **94a** are withdrawn from the roll of material **90a** in a manner like that described before in connection with **FIG. 11** until a predetermined length of the first and second materials **92a** and **94a** have been withdrawn from the roll of material **90a**. In this position, a portion of the first and the second materials **92a** and **94a** are disposed under a knife edge **108**. The knife edge **108** is connected to an actuator **110** adapted to move the knife edge **108** in a direction **112** and in a direction **114**. When the predetermined length of first and the second materials **92a** and **94a** have been withdrawn from the roll of material **90a**, the actuator **110** actuates to move the knife edge **108** in the direction **112** to a position wherein the knife edge **108** severingly engages the first and second materials **92a** and **94a** to severingly cut a portion of the first and the second materials **92a** and **94a** from the roll of materials **90a** to provide the first and second sheets of material as described herein. The actuator **110** may comprise a hydraulic or pneumatic cylinder or a motor and gear arrangement or any other form of arrangement suitable for moving the knife edge **108** in the directions **112** and **114**. After the knife edge **108** has cuttingly severed the desired portion of the first and second sheets of material **92a** and **94a** from the roll of material **90a**, the actuator **110** is actuated to move the knife edge **108** in the direction **114** to a storage position disposed a distance above the first and second materials **92a** and **94a** as opposed to the cutting position previously described.

**[0094]** Embodiment of **FIG. 13**

**[0095]** Shown in **FIG. 13** is a pad **116** of first sheets of materials designated by the reference numerals **10f**, **10g**, and **10h** in **FIG. 13** and a plurality of second sheets of material designated in **FIG. 13** by the reference numerals **26f**, **26g** and **26h**. The first sheets of material **10f**, **10g** and **10h** may be constructed like the sheet of material **10** shown in **FIG. 1** and described in detail before and the second sheets of material **26f**, **26g** and **26h** may be constructed like the second sheet of material **26** shown in **FIG. 2** and described in detail before, or like any of the other first and the second sheets of material described herein. The first and second sheets of material **10f**, **10g**, **10h**, **26f**, **26g** and **26h** are

connected in the form of the pad 116 with a closure bonding material 24f, 24g and 24h cooperating to connect the first sheets of material 10f, 10g and 10h in the form of the pad 116. The second sheets of material 26f, 26g and 26h may be connected to the respective first sheets of material 10f, 10g and 10h or may be interleaved between the adjacent first sheets of material 10f, 10g and 10h in the pad 116. In the alternative, the second sheets of material 26f, 26g and 26h may be connected to form the pad 116 with the first sheets of material 10f, 10g and 10h being interleaved in the respective second sheets of material 26f, 26g and 26h and/or connected thereto. In operation, one of the first sheets of material 10f, 10g or 10h along with the adjacent second sheets of material 26f, 26g and 26h may be removed from the pad 116 and then placed in position to be wrapped about the flower pot.

**[0096]** Embodiments of FIGS. 14-18

**[0097]** As noted above, the first sheet of material 10 or the first sheet of material 10 and the second sheet of material 26 may be used to provide a decorative cover for an object such as a flower pot or a potted plant. To cover the object, the sheet or sheets may be manually or automatically placed in a position to be formed about the outer peripheral surface of the pot or potted plant as described in more detail below. Or, the sheet or sheets may be formed into a preformed cover which is then placed in a position to receive the pot or potted plant.

**[0098]** Referring to FIG. 14, to form a sheet of material 10i into a cover about a pot 140, the sheet of material 10i is disposed above an opening in a platform. The pot 140 is then disposed upon an upper surface 20i of the sheet of material 10i, so a lower end 142 of the pot 140 rests upon the portion of the upper surface 20i which is over the opening. The pot 140 has an outer peripheral surface 144 and an upper end 146. In one embodiment of a manual application of the sheet of material 10i about the pot 140, the pot 140 is manually pushed in a direction into the opening covered by the sheet of material 10i. The upper surface 20i of the sheet of material 10i is caused to be pressed about the outer peripheral surface 144 (FIG. 15) thereby engaging the outer peripheral surface 144 to form a cover 148 about the pot 140 as shown in FIG. 16. A lower surface 22i of the sheet of material 10i thereby becomes an outer surface 150 of the cover 148.

**[0099]** Another method for wrapping the sheet of material 10i about the pot 140 for forming such a cover is shown in U.S. Pat. No. 4,733,521 entitled "Cover Forming Apparatus" issued to Weder et al., on Mar. 29, 1988, which is hereby incorporated herein by reference.

**[0100]** The cover 148 formed by wrapping the sheet of material 10i about the flower pot 140 may be secured to the outer peripheral surface 144 of the pot 140 by the use of one or more bonding materials described herein. One particular method of securing the cover 148 to the pot 140 is by applying a band about the pot 140 to hold the covering in place such as is described in U.S. Pat. No. 5,105,599 entitled "Means For Securing A Decorative Cover About A Flower Pot" issued to Weder on Apr. 21, 1992 and which is hereby incorporated herein by reference.

**[0101]** Alternatively, the sheet of material 10i may be preformed into a cover 152 having an opening 154 as shown

in FIG. 17. The cover 152 is self-supporting by virtue of overlapping folds which are bonded to each other, thereby forming a rigid structure. The preformed cover 152 may be deposited into an opening in a table or platform to support the cover 152. A potted plant 156 can then be disposed into the opening 154 of the preformed cover 152, thereby resulting in a covered potted plant 158 as shown in FIG. 18.

**[0102]** One method for forming such a preformed plant cover or pot cover is shown in U.S. Pat. No. 4,773,182 entitled "Article Forming System" issued to Weder et al., on Sep. 27, 1988, which is hereby incorporated herein by reference.

**[0103]** Embodiments of FIGS. 19-22

**[0104]** Referring to FIG. 19, as shown therein and designated by the general reference numeral 10j is another sheet of material constructed in accordance with the present invention. The sheet of material 10j shown in FIG. 19 has an upper surface 12j, a lower surface 14j (FIG. 21), a first end 16j, a second end 18j, a first side 20j and a second side 22j. The ends 16j and 18j cooperate with the sides 20j and 22j to define an outer peripheral surface 24j of the sheet of material 10j. The outer peripheral surface 24j of the sheet of material 10j is defined by perforations 26j as shown in FIGS. 19, 21 and 22.

**[0105]** As shown in FIGS. 19, 21 and 22, a sheet extension 28j is connected to the outer peripheral surface 24j of the sheet of material 10j. As shown in FIGS. 19 and 21, the sheet extension 28j extends a distance outwardly from the outer peripheral surface 24j of the sheet of material 10j. The sheet extension 28j has a first end 30j, a second end 32j, a first side 34j and a second side 36j. A portion of the sheet extension 28j extends a distance outwardly from the first end 16j of the sheet of material 10j terminating with the first end 30j of the sheet extension 28j. Another portion of the sheet extension 28j extends a distance outwardly from the second end 18j of the sheet of material 10j terminating with the second end 32j of the sheet extension 28j. Yet another portion of the sheet extension 28j extends a distance outwardly from the first side 20j of the sheet of material 10j terminating with the first side 34j of the sheet extension 28j. Still another portion of the sheet extension 28j extends a distance outwardly from the second side 22j of the sheet of material 10j terminating with the second side 36j of the sheet extension 28j.

**[0106]** The sheet extension 28j cooperates with the sheet of material 10j to define a generally square or rectangularly shaped sheet with the perforations 26j being disposed in a central portion of the sheet and defining the outer peripheral surface 24j of the sheet of material 10j. Preferably, the sheet of material 10j and the sheet extension 28j are unitary and formed from a single sheet or plies or multiple sheets one on top of the other which may or may not be laminated.

**[0107]** The sheet of material 10j and the sheet extension 28j are constructed from any suitable flexible material that is capable of being wrapped about a floral grouping and formed into the covering, as described herein. Preferably, the sheet of material 10j and the sheet extension 28j are constructed of a material selected from a group of materials consisting of paper, metal foil, cloth (natural or synthetic), denim, burlap or polymer film as defined above or combinations thereof.

[0108] The sheet of material 10j and the sheet extension 28j have a thickness in a range from about 0.1 mil to about 30 mils. Preferably, the sheet of material 10j and the sheet extension 28j have a thickness in a range from about 0.1 mil to about 5 mils.

[0109] The sheet of material 10j and the sheet extension 28j may be any shape and a rectangular shape is shown in FIG. 19 only by way of example. The sheet of material 10j and the sheet extension 28j for example only may be square, rectangular, circular or any other geometric shape such as heart shaped for example only.

[0110] The sheet of material 10j and the sheet extension 28j may be constructed of a single layer of material or a plurality of layers of the same or different types of materials. Any thickness of the sheet of material 10j and the sheet extension 28j may be utilized in accordance with the present invention as long as the sheet of material 10j and the sheet extension 28j is wrappable about a floral grouping and formable into the covering, as described herein. The layers of material comprising the sheet of material 10j and the sheet extension 28j may be connected together or laminated or may be separate layers.

[0111] The covering of the present invention is particularly constructed to be used with a pot 38j (FIG. 20). The pot 38j has a top 40j, a bottom 42j with an opening through the top 40j forming a receiving space 44j within the pot 38j. The pot 38j also has an outer peripheral surface 46j. As shown in FIG. 20, the pot 38j is generally cylindrically shaped. However, the pot 38j may be any shaped as may be desired in a particular application.

[0112] A floral grouping 48j is disposed at least partially within the receiving space 44 of the pot 38j, as shown in FIG. 20. The floral grouping 48j has a stemmed end 50j and a bloom end 52j. In one embodiment as shown in FIG. 20, material such as soil 54j is disposed in the receiving space 44j and a portion of the stem end 50j extends into the soil 54j. The floral grouping 48j extends a distance upwardly from the top 40j of the pot 38j terminating with the bloom end 52j.

[0113] The sheet extension 28j is transparent, although a decorative pattern also may be applied to the sheet extension 28j.

[0114] The sheet of material 10j with the sheet extension 28j connected thereto is placed between a male and a female die or other forming means and formed into a pot cover 56j (FIG. 21). As shown in FIGS. 21 and 22, the pot cover 56j has a top 58j, a closed bottom 60j and a cover opening 62j (FIG. 21) formed through the top 58j and extending through the top 58j a distance toward the bottom 60j of the pot cover 56j providing a pot receiving space 64j (FIG. 21). The pot receiving space 64j is shaped and adapted to receive the pot 38j.

[0115] The pot cover 56j has a plurality of overlapping folds 66j (FIG. 21) with each of the overlapping folds 66j extending at various distances and at various angles over an outer peripheral surface 68j (FIG. 21) of the pot cover 56j extending between the top 58j and the bottom 60j. The overlapping folds 66j extend at various angles and over various distance over the outer peripheral surface 68j.

[0116] The pot cover 56j includes a skirt 70j (FIGS. 21 and 22). The skirt 70j extends from the top 40j of the pot 38j

radially outwardly with an outer peripheral surface of the skirt 70j being formed by the outer peripheral surface 24j of the sheet of material 10j. The perforations 26j extend along the outer peripheral surface of the skirt 70j formed by the outer peripheral surface 24j of the sheet of material 10j.

[0117] The overlapping folds 66j may be connected or at least partially connected. The connection of the overlapping folds 66j may be accomplished by using heat sealing material and heat sealing the overlapping folds or by adhesively or cohesively connecting the overlapping folds.

[0118] The pot 38j is placed in the pot receiving space 64j and positioned in the pot cover 56j such that the bottom 42j of the pot 38j is disposed generally adjacent the bottom 60j of the pot cover 56j. The pot cover 56j substantially encompasses the entire outer peripheral surface 46j of the pot 38j including the bottom 42j. The pot cover 56j extends from the bottom 42j to the top 40j of the pot 38j. The skirt 70j extends radially outwardly from the top 40j of the pot 38j.

[0119] After the pot 38j has been placed in the pot cover 56j, the sheet extension 28j is formed about the floral grouping 48j to a position wherein the sheet extension 28j covers and encompasses a substantial portion of the floral grouping 48j including the bloom end 52j of the floral grouping 48j.

[0120] The sheet extension 28j preferably includes a bonding material 72j (FIG. 19) disposed on the upper surface of the sheet extension 28j and extending about the outer peripheral surface of the sheet extension 28j. After the sheet extension 28j has been formed about the floral grouping 48j, the ends of the sheet of material 10j are bonded together to provide a closed end 74j (FIG. 22). The term "bonding material" as used herein is as defined below.

[0121] The sheet extension 28j remains in a position extending about the floral grouping 48j until it is desired to remove the sheet extension 28j. The sheet extension 28j is removed from the pot cover 56j by tearing along the perforations 26j separating the sheet extension 28j from the pot cover 56j. The sheet extension 28j then is removed from the floral grouping 48j leaving the pot cover 56j providing a decorative cover for the pot 38j.

[0122] In addition to the perforations 26j the sheet extension 28j also may include perforations extending between the perforations 26j and the outer peripheral surface of the sheet extension 28j to further assist in the removal of the sheet extension 28j when it is no longer desired to keep the sheet extension 28j extending about the floral grouping 48j.

[0123] Shown in FIG. 23 and designated by the general reference number 10k is a sheet of material constructed in accordance with the present invention.

[0124] The sheet of material 10k includes a first end 12k, a second end 14k, a first side 16k and a second side 18k. The sheet of material 10k also includes an upper surface 20k (FIG. 23) and a lower surface 22k (FIG. 24).

[0125] A connecting bonding material 24k is disposed on the upper surface 20k of the sheet of material 10k. The sheet of material 10k has an outer peripheral surface 26k. The connecting bonding material 24k is disposed near and spaced a distance 28k from the outer peripheral surface 26k of the sheet of material 10k and extends generally circumferentially about the sheet of material 10k.

[0126] The sheet of material **10k** shown in **FIG. 23** is circularly shaped and the connecting bonding material **24k** extends in a circularly shaped pattern over the upper surface **20k** of the sheet of material **10k**. The sheet of material **10k** may be any geometric shape such as square or rectangular or heart shaped or trapezoidally shaped or any other geometric shape. Further, the connecting bonding material **24k** may extend in any geometric pattern over the upper surface **20k** of the sheet of material **10k**, and the circularly shaped pattern is shown in **FIG. 23** only by way of example.

[0127] A sheet extension **25k** is connected to the sheet of material **10k**. The sheet extension **25k** extends about the outer peripheral surface **26k** of the sheet of material **10k**. The sheet extension **25k** extends outwardly from the sheet of material **10k** terminating with an outer peripheral surface **27k**. The sheet extension **25k** has an upper surface **29k** (**FIG. 23**) and a lower surface **31k** (**FIG. 24**). The upper surface **29k** is disposed in a plane about coplanar with the upper surface **20k** of the sheet of material **10k** and lower surface **31k** is disposed in a plane about coplanar with the lower surface **22k** of the sheet of material **10k**.

[0128] The sheet extension **25k** and the sheet of material **10k** may be integrally constructed of a single sheet of material or the sheet extension **25k** may be laminated to the sheet of material **10k**. A connecting bonding material **33k** is disposed on the upper surface **29k** of the sheet extension **25k**. The connecting bonding material **33k** is disposed near and spaced a distance from the outer peripheral surface **27k** of the sheet extension **25k** and extends generally circumferentially about the sheet extension **25k**.

[0129] The sheet extension **25k** is shown in **FIG. 23** as being circularly shaped. The sheet extension **25k** may be any geometric shape such as a square or rectangular or heart shaped or trapezoidally shaped or any other geometric shape and the geometric shape of the sheet extension **25k** may be the same as the geometric shape of the sheet of material **10k** or the sheet extension **25k** may have a geometric shape different from the geometric shape of the sheet of material **10k**. Further, although the sheet extension **25k** is shown in **FIG. 23** as extending circumferentially about the outer peripheral surface **26k** of the sheet of material **10k**, the sheet extension **25k** may extend only about a portion of the outer peripheral surface **26k** of the sheet of material **10k** or the sheet extension **25k** may comprise segments with each segment extending about a portion of the outer peripheral surface **26k** of the sheet of material **10k**.

[0130] The sheet of material **10k** and the sheet extension **25k** may be constructed of a single layer of material or a plurality of layers of the same or different types of materials as described above. Any thickness of the sheet of material **10k** and the sheet extension **25k** may be utilized in accordance with the present invention as long as the sheet of material **10k** and the sheet extension **25k** are wrappable or formable about a flower pot or a floral grouping in the manners described herein. The layers of material comprising the sheet of material **10k** and the sheet extension **25k** may be connected together or laminated or may be separate layers. A decorative pattern, such as a color and/or an embossed pattern, and/or other decorative surface ornamentation may be applied to the upper surface **20k** and/or the lower surface **22k** of the sheet of material **10k** or portions thereof as described above.

[0131] A decorative pattern, such as a color and/or an embossed pattern, and/or other decorative surface ornamentation may be applied to the upper surface **29k** and/or the lower surface **31k** of the sheet extension **25k** or portions thereof as described above. The sheet extension **25k** also may be totally or partially clear or tinted transparent material as described above.

[0132] The connecting bonding materials **24k** and **33k** are shown in **FIG. 23** as being applied to the upper surface **20k** or the upper surface **29k** in the form of a circularly shaped strip. The connecting bonding materials **24k** or **33k** may be applied in the form of spots or spaced apart strips and the spots may be any geometric pattern or any other type of pattern such as a logo for example. Further, the connecting bonding materials **24k** or **33k** may include a color to obscure the fact that the connecting bonding materials **24k** and **33k** are disposed on the sheet of material **10k** or the sheet extension **25k**.

[0133] Shown in **FIG. 24** is a flower pot **30k** having an upper end **32k**, a lower end **34k** and an outer peripheral surface **36k**. An opening **38k** is formed through the upper end **32k** of the flower pot **30k** providing access to a retaining space **40k**.

[0134] The retaining space **40k** forms an inner peripheral surface **40k** in the flower pot **30k**. A bottom **44k** of the flower pot **30k** is disposed at the lower end **34k** and cooperates to enclose or partially enclose the retaining space **40k**. The flower pot **30k** may be any conventional, commercially available container well known in the art.

[0135] Growing medium **43k** is shown in **FIG. 24** disposed in the retaining space **40k** and a floral grouping **47k** is shown in **FIG. 24** partially disposed in the growing medium **43k**. A portion of the floral grouping **47k** extends a distance upwardly above the upper end **32k** of the flower pot **30k**.

[0136] The flower pot **30k** is placed on the upper surface **20k** of the sheet of material **10k**. More particularly, the bottom **44k** of the flower pot **30k** is disposed on a central portion of the sheet of material **10k**. In this position, the connecting bonding material **24k** extends circumferentially about the flower pot **30k** and the connecting bonding material **24k** is spaced a distance from the flower pot **30k**.

[0137] The sheet of material **10k** then is formed about the flower pot **30k** to a position wherein the sheet of material **10k** extends about and encompasses substantially the entire outer peripheral surface **36k** of the flower pot **30k**, including the bottom **44k**. It should be noted that the sheet of material **10k** does not have to cover the bottom **44k**. In this position, a portion of the sheet of material **10k** is disposed adjacent the bottom **44k** of the flower pot **30k** and portions of the sheet of material **10k** extend upwardly and encompass the entire outer peripheral surface **36k** of the flower pot **30k** between the upper end **32k** and the lower end **34k** of the flower pot **30k**. In one embodiment, the portions of the sheet of material **10k** extending over the outer peripheral surface **36k** are spaced a distance from the outer peripheral surface **36k** of the flower pot **30k** to provide a blossom type affect.

[0138] In this position, the portion of the sheet of material **10k** disposed near and about the connecting bonding material **24k** is crimped by bringing together portions of the sheet of material **10k** near and about the connecting bonding material **24k** so that portions of the sheet of material **10k** near

and about the connecting bonding material **24k** are disposed adjacent each other and the adjacent portions of the sheet of material **10k** are connected by way of the connecting bonding material **24k** thereby forming a plurality of overlapping folds **45k** in the portion of the sheet of material **10k** near and about the connecting bonding material **24k**. The connected overlapping folds **45k** extend at various distances and at various angles. The connected overlapping folds **45k** (FIG. 24) in the area near and about the portion of the sheet of material **10k** containing the connecting bonding material **24k** is designated in FIG. 24 by the reference numeral **46k** and maybe referred to herein as the crimped portion **46k** (FIG. 24).

[0139] A typical section showing a portion of a typical overlapping fold **45k** is shown in FIG. 25. The adjacent portions of the sheet of material **10k** on the upper surface **20k** are shown in FIG. 25 as being connected while the adjacent portions of the sheet of material **10k** on the lower surface **22k** are unconnected since no bonding material is disposed on the lower surface **22k**. It should be noted that connecting bonding material also can be disposed on the lower surface **22k** for connecting adjacent portions of the lower surface **22k** in the crimped portion **46k** if desired and as described in more detail below.

[0140] The crimped portion **46k** extends circumferentially about the upper end **32k** of the flower pot **30k**. The crimped portion **46k** also extends a distance inwardly from the upper end **32k** of the flower pot **30k** toward a central portion of the retaining space **40k** thereby forming a ridge portion **48k** extending circumferentially about the flower pot **30k** generally near the upper end **32k** of the flower pot **30k**. The crimped portion **46k** and the ridge portion **48k** thereof cooperate to engage the upper end **32k** of the flower pot **30k** to assist and cooperate in holding the sheet of material **10k** formed about the flower pot **30k** to provide a decorative cover **50k** (FIG. 24).

[0141] The crimped portion **46k** when formed preferably causes adjacent portions of the upper and lower surfaces **20k** and **22k** of the sheet of material **10k** to be brought together or positioned adjacent each other. The crimped portion **46k** and the other crimped portions shown in the drawings are shown in an expanded form where the portions of the lower surface **22k** are not disposed adjacent each other for the purpose of illustration and because this expanded form may be desired in some applications.

[0142] Either before or after or during the forming of the crimped portion **46k**, the sheet extension **25k** is formed about the floral grouping **47k** to a position wherein the sheet extension **25k** encompasses a substantial portion of the floral grouping **47k**, as shown in FIG. 24. The sheet extension **25k** extends upwardly about the floral grouping **47k** with a portion of the sheet extension **25k** extending upwardly beyond the upper end of the floral grouping **47k** terminating with the outer peripheral surface **27k** of the sheet extension **25k** and forming an open upper end. In this position of the sheet extension **25k**, portions of the sheet extension **25k** near the outer peripheral surface **27k** (the open upper end) thereof are brought into contact thereby bringing the connecting bonding material **33k** into contact and engagement with adjacent portions of the sheet extension **25k** for closing the sheet extension **25k** about or above an upper end of the floral grouping **47k**.

[0143] In a preferred form, a line of perforations **53k** (FIGS. 23 and 24) is formed between the sheet of material **10k** and the sheet extension **25k**. The line of perforations **53k** extends generally about the outer peripheral surface **26k** of the sheet of material **10k**. The sheet extension **25k** encompasses the floral grouping **47k** and provides a protective covering for the floral grouping **47k** to protect the floral grouping **47k** during shipment and/or storage. When it is desired to remove the protective covering provided by the sheet extension **25k**, the operator tears the sheet extension **25k** along the line of perforations **53k** thereby severing or separating the sheet extension **25k** from the sheet of material **10k** so that the sheet extension **25k** can be removed from the sheet of material **10k** or, in other words, the protective covering may be removed from the decorative covering by tearing along the line of perforations **53k**.

[0144] The term "bonding material" when used herein means an adhesive, preferably a pressure sensitive adhesive, or a cohesive. Where the bonding material is a cohesive, a similar cohesive material must be placed on the adjacent surface for bondingly contacting and bondingly engaging with the cohesive material. The term "bonding material" also includes materials which are heat sealable and, in this instance, the adjacent portions of the material must be brought into contact and then heat must be applied to effect the seal. The term "bonding material" also includes materials which are sonic sealable and vibratory sealable. The term "bonding material" when used herein also means a heat sealing lacquer which may be applied to the sheet of material and, in this instance, heat, sound waves, or vibrations, also must be applied to effect the sealing.

[0145] The term "bonding material" when used herein also means any type of material or thing which can be used to effect the bonding or connecting of the two adjacent portions of the material or sheet of material to effect the connection or bonding described herein. The term "bonding material" also includes ties, labels, bands, ribbons, strings, tape, staples or combinations thereof. Some of the bonding materials would secure the ends of the material while other bonding material may bind the circumference of the wrapper. Another way to secure the wrapping is to heat seal the ends of the material to another portion of the material. One way to do this is to contact the ends with an iron of sufficient heat to heat seal the material.

[0146] The term "bonding material" when used herein also means any heat or chemically shrinkable material, and static electrical or other electrical means, magnetic means, mechanical or barb-type fastening means or clamps, curl-type characteristics of the film or materials incorporated in the sheet of material which can cause the material to take on certain shapes, and any type of welding method which may weld portions of the sheet to itself or to the pot, or to both the sheet itself and the pot.

[0147] The term "botanical item" when used herein means a natural or artificial herbaceous or woody plant, taken singly or in combination. The term "botanical item" also means any portion or portions of natural or artificial herbaceous or woody plants including stems, leaves, flowers, blossoms, buds, blooms, cones, or roots, taken singly or in combination, or in groupings of such portions such as bouquet or floral grouping.

[0148] The term "propagule" when used herein means any structure capable of being propagated or acting as an agent

of reproduction including seeds, shoots, stems, runners, tubers, plants, leaves, roots or spores.

**[0149]** The term “growing medium” when used herein means any liquid, solid or gaseous material used for plant growth or for the cultivation of propagules, including organic and inorganic materials such as soil, humus, perlite, vermiculite, sand, water, and including the nutrients, fertilizers or hormones or combinations thereof required by the plants or propagules for growth.

**[0150]** The term “band” when used herein means any material which may be secured about an object such as a flower pot, such bands commonly being referred to as elastic bands, rubber bands or non-elastic bands and also includes any other type of material such as an elastic or non-elastic string or elastic piece of material, non-elastic piece of material, a round piece of material, a flat piece of material, a ribbon, a piece of paper strip, a piece of plastic strip, a piece of wire, a tie wrap or a twist tie or combinations thereof or any other device capable of gathering the sheet of material to removably or substantially permanently form a crimped portion and secure the crimped portion formed in the sheet of material which may be secured about an object such as the flower pot. The band also may include a bow if desired in a particular application.

**[0151]** The sheet of material used herein may further comprise at least one scent (not shown). Examples of scents utilized herein include (but are not limited to) floral scents (flower blossoms, or any portion of a plant), food scents (chocolate, sugar, fruits), herb or spice scents (cinnamon), and the like. Additional examples of scents include flowers (such as roses, daisies, lilacs), plants (such as fruits, vegetables, grasses, trees), foods (for example, candies, cookies, cake), food condiments (such as honey, sugar, salt), herbs, spices, woods, roots, and the like, or any combination of the foregoing. Such scents are known in the art, and are commercially available.

**[0152]** The scent may be disposed upon the sheet of material **10** by spraying the scent thereupon, painting the scent thereupon, brushing the scent thereupon, lacquering the scent thereupon, immersing the sheet of material in a scent-containing liquid, exposing the sheet of material to scent-containing gas, or any combination thereof.

**[0153]** The scent may be contained within a lacquer, or other liquid, before it is disposed upon the sheet of material **10**. The scent may also be contained within a dye, ink, and/or pigment (not shown). Such dyes, inks and pigments are known in the art, and are commercially available, and may be disposed upon or incorporated in the sheet of material **10** by any method described herein or known in the art.

**[0154]** Embodiments of FIGS. 26-28

**[0155]** In one version, the apparatus of the present invention comprises a platform having an upper support surface formed thereon and at least one opening extending through the upper support surface. The upper support surface is adapted to support at least one sheet of material in a cover forming position over the opening. The opening is sized to accommodate a cover forming mold.

**[0156]** The apparatus further comprises a cover forming mold disposed below the opening in the support surface. The cover forming mold has contacting portions for contacting

the sheet of material. The opening and the cover forming mold are adapted for receiving an article such as a flower pot having an upper end, a lower end, an upper opening and an outer peripheral surface such that when the article is moved in a predetermined direction, such as downward, the lower end of the article is caused to engage a portion of the sheet of material disposed over the opening. The article and portions of the sheet of material thus pass into the cover forming mold causing the sheet of material to engage the outer peripheral surface of the article and the contacting portions of the cover forming mold as the article is moved. As this happens, portions of the sheet contactingly engage or nearly engage the outer peripheral surface of the article forming a cover about the article and thereby forming a covered article. The cover of the covered article then has an inner surface facing the outer peripheral surface of the article and an exposed outer surface adjacent the inner portion of the mold.

**[0157]** The apparatus further comprises a fastening device for automatically applying a fastener about a portion of the outer surface of the covered article. In an alternate version, the apparatus may comprise a labeling assembly for automatically applying a label to a portion of the outer surface of the cover of the covered article, preferably after the cover has been fastened to the article.

**[0158]** The sheet of material used in accordance with the present invention is constructed from a material selected from a group of materials described in greater detail below. The apparatus may further comprise a securing assembly for releasably securing the sheet of material in the cover forming position on the upper support surface for generally immobilizing the sheet prior to the forming step. The apparatus may further comprise a sheet feeder for automatically placing a sheet of material on the support surface and/or a pick and place assembly for picking up the article from an article supply and for placing the article into the opening to form the covered article. Additionally, the apparatus may further comprise a removal assembly for automatically removing the covered article from the opening of the platform.

**[0159]** Referring now to FIGS. 26-28, a portion of a covering and fastening assembly designed in accordance with the present invention is generally designated by the reference numeral **170**. The covering and fastening assembly **170** is mounted upon a framework (not shown) which may be mobile or stationary. The covering and fastening assembly **170** comprises an upper platform **172** which has an upper support surface **174** and an opening **176**.

**[0160]** A sheet of material (such as the second sheet of material **26** in FIG. 2) is manually placed upon the upper support surface **174** generally over an opening **176** in the upper support surface **174**. The sheet of material may be obtained from a stack of sheets such as shown in FIG. 13, or may be obtained from a sheet dispenser such as shown in FIGS. 10-12 and discussed above. In one alternate version of the invention, the sheet of material may be automatically fed from a sheet feeding apparatus (not shown). Automatic sheet feeding devices are well known in the art. Examples of such sheet feeding machines are shown in U.S. Pat. No. 4,887,805 issued to Herbert et al., 4,889,331 issued to Sardella, and 5,090,676 issued to Matsumo et al. An automatic sheet feeding machine, if used, is detachably connected to the framework of the apparatus of the present invention.

[0161] In a preferred version of the invention, a cover former (not shown) is detachably mounted in each opening 176. Examples of cover formers contemplated in accordance with the present invention are disclosed in U.S. Pat. No. 4,733,521 as discussed above, and are hereby incorporated herein by reference.

[0162] An article or potted plant or pot such as pot 140 may be delivered to the apparatus manually or automatically. When the operation is manual, the pot 140 or a potted plant such as the potted plant 156 is disposed above the sheet of material and is pushed downward into the opening 176, through the cover former disposed therein, forming the sheet of material into a cover 180 about the potted plant.

[0163] Alternatively, the potted plant 156 may be deposited into the cover forming position by a pick and place machine (not shown) which is an apparatus for grasping an article from a plurality of stored articles, delivering the article to the correct position above a sheet of material and then automatically depositing the article into the opening 176, and disengaging from the article once the article is deposited into the opening 176. Such pick and place machines are familiar to persons of ordinary skill in the art of object pickup and placement.

[0164] Once the pot 140 or potted plant 156 has had the cover 180 applied thereabout, a fastening assembly 182 serves to apply a fastener 184 about the cover 180 which has been applied about the pot 140 or potted plant 156. Examples of fastening machines include tying machines such as those commercially available from Saxmeyer, Bunn, Felins, and Cyclopes.

[0165] The fastening assembly 182 is mounted upon the mobile or stationary framework.

[0166] In the embodiment represented in FIGS. 26-28, the fastening assembly 182 is constructed to apply a fastener or band to the covered article or pot in a plane beneath the upper support surface 174. The fastening assembly 182 comprises a tie arm 186 having a tie end 188 and a pivot end 190, a tie arm shaft 192, a knoter head 194, a rocker plate 196 and a vertical rod 198 mounted to a lower support assembly 200. A string, tie, wire, or other type of band or fastener 184 is drawn through the knoter head 194 and engaged with the tie end 188 of the tie arm 186. The fastener 184 is looped outside of the vertical rod 198 as shown in FIG. 26 which serves as a fastener retraction assembly so that the stress of the fastener 184 upon the cover 180 is relieved so as not to tear the cover 180. The tie arm 186 is rotated by the tie arm shaft 192 in a direction 202 when the tie arm shaft 192 is rotated in a direction 204 by a drive motor (not shown) of the fastening assembly 182.

[0167] An optional labeling apparatus (not shown) is a separate unit which can be mounted and removed from the main framework of the covering and fastening assembly 170. Such labeling devices are known by persons of ordinary skill in the label applying art and are commercially available. The label (not shown) is applied to the side of the cover 180 of the potted plant 156 before or after the fastener 184 is applied about the cover 180. The label may be an adhesive label or may be applied as an ink jet, or even by stamping. As the covered potted plant is recovered from the opening 176 after the fastener 184 has been applied and knotted, the knotted fastener 184 slips off the vertical rod 198 and holds the cover 180 about the pot 140 or potted plant 156.

[0168] Embodiments of FIGS. 29-31

[0169] Referring now to FIGS. 29-31, an alternative covering and fastening assembly is generally designated by the reference numeral 170a. The covering and fastening assembly 170a is exactly the same as the covering and fastening assembly 170 except that it is modified to apply a fastener 184a to a cover 180a in a plane above an upper support surface 174a. A tie arm 186a is supported by a tie arm shaft 192a above the upper support surface 174a. The fastener 184a is looped about a set of studs 206a-d which serve as a fastener retraction assembly and which function to relieve the stress of the fastener 184a as it is applied about the cover 180a. The studs 206a-d are reciprocally mounted in an upper support assembly 172a so that the studs 206a-d can be retracted into the upper support assembly 172a to allow the fastener 184a to grasp the cover 180a. The studs 206a-d can be controlled electrically, pneumatically, hydraulically or by another power source.

[0170] Embodiments of FIGS. 32-33

[0171] Referring now to FIG. 32, a covering and fastening assembly is designated by the reference numeral 170b. The covering and fastening assembly 170b is exactly like the covering and fastening assembly 170a of FIGS. 29-31 except that instead of using a plurality of studs 206a-d to function as a fastener retraction assembly, the covering and fastening assembly 170b uses a fastener retraction assembly 208 comprising a first retraction unit 210 and a second retraction unit 212.

[0172] The first retraction unit 210 comprises a first grasping arm 214 having a grasping end 216 for catching and holding a portion of a fastener 184b. The second retraction unit 212 comprises a second grasping arm 218 having a grasping end 220 for catching and holding a portion of the fastener 184b different from the portion of the fastener 184b held by the first grasping arm 214. The first retraction unit 210 and the second retraction unit 212 may be automatically controlled and may comprise pneumatically or hydraulically controlled pistons.

[0173] In operation, the first grasping arm 214 grasps a portion of the fastener 184b and the second grasping arm 218 grasps another portion of the fastener 184b. The first grasping arm 214 is retracted in a direction 222 and the second grasping arm 218 is retracted in a direction 224 until the fastener 184b is retracted to a position as shown in FIG. 32 in which the fastener 184b is drawn away from an opening 176b in an upper support surface 174b whereby the opening 176b is available for an article or pot to be deposited therein. Once a pot or article has been deposited into the opening 176b to form a cover 180b substantially as described above for the covering and fastening assembly 170a, the first grasping arm 214 and the second grasping arm 218 are caused to release the fastener 184b whereby the fastener 184b engages the circumference of the cover 180b about the pot or article and holds the cover 180b thereabout. The covered pot or article can then be removed from the covering and fastening assembly 170b.

[0174] Embodiment of FIGS. 34-36

[0175] Referring now to FIG. 34, another version of the covering and fastening assembly of the present invention is designated by the general reference numeral 170c. The covering and fastening assembly 170c is exactly like the

covering and fastening assembly **170b** of FIGS. 32-33, except that instead of using a pair of retraction units **210** and **212**, as a fastener retraction assembly, a fastener retraction assembly **230** is alternatively comprised of a U-shaped retraction arm **232** attached to a cylinder **234** (FIG. 36). The retraction arm **232** comprises a first grasping prong **236** having a grasping end **238** and a second grasping prong **240** having a second grasping end **242**. The retraction arm **232** is attached to a rod **244** which is reciprocatingly disposed within the cylinder **234**.

[0176] In operation, the rod **244** is advanced in direction **246** until the grasping ends **238** and **242** catch the fastener **184c**. Once the retraction arm **232** has grasped the fastener **184c**, the rod **244** is reciprocatingly retracted by the cylinder **234** in direction **248** until the fastener **184c** has been retracted a distance sufficient to clear an opening **176c** in the upper support surface of the covering and fastening assembly **170c** as shown in FIG. 35. The covering and fastening assembly **170c** is at that point prepared to proceed in the operation of applying a cover to a pot or article disposed in the opening **176c**. After the pot has been disposed into the opening **176c** and a cover formed thereabout, the fastener **184c** is released from the fastener retraction assembly **230**.

[0177] Embodiment of FIG. 37

[0178] Referring now to FIG. 37, a covering and fastening assembly is designated by the general reference numeral **170d**. The covering and fastening assembly **170d** is exactly any of the covering and fastening assemblies **170**, **170a**, **170b**, or **170c** except that the sheet of material is supplied from a roll of material substantially as described above in the embodiment of FIG. 12.

[0179] Shown in FIG. 37 is a roll of material **250** resting on a shaft **252** supported by a support assembly **254**. A clutch assembly **256** which is driven by a drive assembly (not seen) such as a motor advances a portion of the roll of material **250** under an idler roller **258** until the portion of the roll of material **250** is advanced a predetermined length. A knife edge **260** which is connected to an actuator **262** serves to sever the portion of the sheet from the roll of material **250**. The sheet is then ready to be used to be formed as a cover about a flower pot.

[0180] In Operation

[0181] In operation, the present invention comprises providing a covering and fastening assembly such as the one designated by the reference numeral **170c** in FIGS. 34-36. In the first operational step, a sheet of material **10** is placed on an upper support surface **174c** in a cover forming position over the opening **176c**. There placed, the sheet of material **10** is positioned over the cover former (not shown) mounted within the opening **176c**.

[0182] In the next step, the article, or in the preferred embodiment the pot **140** containing a plant is removed from a storage position. The pot **140** is positioned over the sheet of material **10** and the potted plant is disposed generally above and near the portion of the sheet of material **10** which is above the cover former mounted in the opening **176c**. Then, the pot **140** is moved in a direction through the cover former toward a lower support assembly (not shown, but similar to the lower support assembly **200** shown in FIGS. 27-28) which causes the lower end of the pot **140** to engage a portion of the sheet of material **10**. The pot **140** and

portions of the sheet of material **10** pass through the cover former causing the sheet of material **10** to contact or nearly contact both the outer peripheral surface **144** of the pot **140** and the contacting portions of the inner perimeter of the cover former. The sheet of material **10** is thereby pressed about the outer peripheral surface **144** of the pot **140** thereby forming the cover **180** about the pot **140** and retaining the covered pot **140** in the opening **176c**. The pot **140** is advanced through the cover former opening until the lower end **142** of the pot **140** rests on or nearly rests on the lower support assembly. The band or fastener **184c** is automatically applied about a portion of the outer surface of the cover of the covered potted plant by the fastening apparatus whereby the cover **180** is fasteningly secured about the pot **140**. In the next step, the covered potted plant is removed.

[0183] The method may comprise the optional step of manually arranging portions of the cover **180** and the exposed portions of the plant so that the cover **180** and potted plant are attractively and optimally arranged prior to the fastening step.

[0184] The method may also comprise the additional step of engaging an automatic labeling device (not shown) wherein a label (not shown) is automatically applied to a portion of the outer surface of the cover **180** of the pot **140**. The label may be applied to the outer peripheral surface of the cover **180** or the label may be applied to the bottom (not shown) of the cover **180** through an opening in the lower support assembly **200**.

[0185] Embodiments of FIGS. 38-40

[0186] Referring now to FIGS. 38-40, another version of the covering and fastening assembly is designated by the general reference numeral **170e**. The covering and fastening assembly **170e** is exactly the same as the assembly **170a** in FIGS. 29-31 except in the construction of the mechanism for retracting and releasing the fastener. The covering and fastening assembly **170e** comprises an upper support assembly **172e** having an upper support surface **174e** which has an opening **176e**. A pot **178e** having a cover **180e** is shown in the opening **176e**. A fastener **184e** is looped about a first retraction pin **270** and a second retraction pin **272**. The first retraction pin **270** is stationarily mounted upon the upper support surface **174e**. Similarly, the second retraction pin **272** is stationarily mounted upon the upper support surface **174e**. The pot **178e** is supported by a pot base cup **274** which is supported on a base plate **276**. The base plate **276** is mounted on a reciprocating piston **278** which can be manually or automatically caused to urge the base plate **276** and pot base cup **274** in an upward direction **280** or a downward direction **282**.

[0187] The fastener assembly **170e** further comprises a pin stripping assembly **286**. The function of the pin stripping assembly **286** is to strip the fastener **184e** from the first and second retraction pins **270** and **272** after the fastener **184e** has been tied to allow the tied fastener **184e** to engage and bind the cover **180e** about the pot **178e**. The pin stripping assembly **286** comprises a first stripper **288** and a second stripper **290**. The first stripper **288** strips the fastener **184e** from the first retraction pin **270**. The second stripper **290** strips the fastener **184e** from the second retraction pin **272**. Each stripper **288** and **290** is disposed about the first and second retraction pins **270** and **272**, respectively, in such a manner that the strippers **288**, **290** is able to reciprocatingly

slide up and down the first and second retraction pins. Each first and second retraction pin **270** and **272** has a stop. One such stop is shown in **FIGS. 39 and 40** and is designated by the reference numeral **292**. The stop **292** functions to prevent the stripper **288** from sliding too far down the first retraction pin **270**. The stop **292**, if present, may be adjustable. Each stripper **288** and **290** has an arm **294** and **296**, respectively.

**[0188]** The pin stripping assembly **286** further comprises a support frame **298** which is connected to the base plate **276** via a support arm **300**. Connected to the upper end of the support frame **298** is a first stripper lifting post **304** which has an upper end **306** and a second stripper lifting post **308**, also which has an upper end (not shown).

**[0189]** The pin stripping assembly **286** further comprises a first pot restraint **310** connected to the support frame **298** and a second pot restraint **312** also connected to the support frame **298**. The first and second pot restraints **310** and **312** function to prevent the pot **178e** from leaning in the direction of the first and second retraction pins **270** and **272** when tension is applied by the fastener **184e** to the side of the pot **178e** which is opposite the first and second retraction pins **270** and **272**.

**[0190]** In operation, the pin stripping assembly **286** is activated when the base plate **276** is urged upwardly in direction **280**. The base plate **276** is lifted by the reciprocating piston **278** a predetermined distance **314**. At this point, the upper end of the pot **178e** has been "ejected" or elevated to a position at least partially beyond the opening **176e** in the upper support surface **174e** in order to facilitate removal of the covered pot from the covering and fastening assembly **170e**.

**[0191]** **FIG. 39** shows the pot orientation before the base plate **276** is lifted and **FIG. 40** shows the pot orientation after the base plate **276** is lifted a distance **314** in direction **280**. During the process of lifting the base plate **276** to eject the covered pot **178e**, each stripper lifting post **304** and **306** is elevated and each engages, respectively, the arms **294** and **296** of strippers **288** and **290**. When, for example, first stripper lifting post **304** is elevated, the upper end **306** engages arm **294** of the first stripper **288**, causing the first stripper **288** to be slidingly elevated upwardly along the first retraction pin **270** and causing the fastener **184e** to be released from the first retraction pin **270**. The action is repeated for the portion of the fastener **184e** which is engaged by the second retraction pin **272**. The pin stripping assembly **286** can then be moved downwardly in direction **282** in preparation of repeating the process.

**[0192]** It will be understood by one of ordinary skill in the art that each of the covering and fastening assemblies discussed herein above may be outfitted with means for enabling the apparatus to be mobile, for example, with wheels or casters. It will also be understood that each of the covering and fastening assemblies may be used with a labeling apparatus for applying a label to the covered pot. Each covering and fastening system may also be used in conjunction with an automatic sheet feeding apparatus.

**[0193]** Changes may be made in the construction and the operation of the various components, elements and assemblies described herein or in the steps or the sequence of steps

of the methods described herein without departing from the spirit and scope of the invention as defined in the following claims.

What is claimed is:

1. An apparatus for forming and fastening a decorative cover about a flower pot, the flower pot having an outer peripheral surface and an open upper end, comprising:

a platform having a support surface formed thereon and an opening extending through the support surface, the support surface adapted to support at least portions of a sheet of material in a position generally over the opening, the opening sized to receive the flower pot and at least one sheet of material such that upon movement of the flower pot and the sheet of material into the opening of the platform, the sheet of material is formed into a decorative cover extending about at least a portion of the outer peripheral surface of the flower pot; and

means for automatically applying a fastener about a portion of the outer surface of the decorative cover and for automatically tying the fastener to secure the fastener about the decorative cover and about the outer peripheral surface of the flower pot such that the open upper end of the flower pot remains substantially uncovered.

2. The apparatus of claim 1 wherein the fastener is selected from a group consisting of elastic or non-elastic string, wire, thread, elastic, ribbon, wire and tape.

3. The apparatus of claim 1 further comprising means for automatically removing the covered flower pot from the opening of the platform.

4. The apparatus of claim 1 wherein the means for applying the fastener is positioned above the platform.

5. The apparatus of claim 1 wherein the means for applying the fastener is positioned below the platform.

6. The apparatus of claim 1 further comprising means for automatically elevating the covered flower pot to a position at least partially above the platform for facilitating the removal of the covered flower pot from the platform.

7. An apparatus for forming and fastening a decorative cover about a flower pot, the flower pot having an outer peripheral surface and an open upper end, comprising:

a platform having a support surface formed thereon and an opening extending through the support surface, the support surface adapted to support at least portions of a sheet of material in a position generally over the opening, the opening sized to receive at least a lower portion of the flower pot and at least one sheet of material such that upon movement of the flower pot and the sheet of material into the opening of the platform, the sheet of material is formed into a decorative cover extending about at least a portion of the outer peripheral surface of the flower pot while the open upper end of the flower pot remains substantially uncovered; and

means for automatically applying a fastener about the decorative cover and for automatically tying the fastener to secure the decorative cover about the flower pot.

\* \* \* \* \*