



AU9181104

(12) PATENT ABRIDGMENT (11) Document No. AU-B-81104/91
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 656529

- (54) Title
DEVICE FOR SUPPLYING BOILING WATER
- International Patent Classification(s)
(51)⁵ **F24H 001/20**
- (21) Application No. : **81104/91** (22) Application Date : **17.07.91**
- (30) Priority Data
- (31) Number (32) Date (33) Country
9001631 18.07.90 NL THE NETHERLANDS
- (43) Publication Date : **23.01.92**
- (44) Publication Date of Accepted Application : **09.02.95**
- (71) Applicant(s)
HENRI BERNARD PETERI; NIELS THEODOOR PETERI
- (72) Inventor(s)
HENRI BERNARD PETERI; NIELS THEODOOR PETERI
- (74) Attorney or Agent
CARTER SMITH & BEADLE , Qantas House, 2 Railway Parade, CAMBERWELL VIC 3124
- (56) Prior Art Documents
AU 475895 46378/72 H05B 3/78
- (57) Claim

1. A device suitable for supplying boiling water, comprising a thermally insulated compression resistant water reservoir, an electric heating element of such power that the water present in the reservoir is heated to a temperature above its atmospheric boiling point, a temperature control, with which the temperature of the water in the reservoir is adjusted to a temperature above the boiling temperature under atmospheric pressure, a water inlet which is connected to the water mains and which is suitable for supplying an inlet flow to the reservoir which is at least equal to the delivery flow of the device, a discharge conduit connected to the reservoir for discharge of boiling water therefrom, the discharge conduit having an inlet end and an outlet end, decelerating means arranged adjacent the outlet end of the discharge conduit for decelerating the outflow of water and steam therefrom, wherein a discharge valve is associated with the inlet end of the discharge conduit.

656529

P/00/0011
Regulation 3.2

AUSTRALIA
Patents Act 1990

COMPLETE SPECIFICATION
FOR A STANDARD PATENT

ORIGINAL

Name of Applicants: Henri Bernard PETERI and Niels Theodoor PETERI

Actual Inventor(s): Henri Bernard PETERI and Niels Theodoor PETERI

Address for service in Australia: CARTER SMITH & BEADLE
Qantas House
2 Railway Parade
Camberwell Victoria 3124
Australia
Attorney Code SA

Invention Title: **DEVICE FOR SUPPLYING BOILING WATER**

The following statement is a full description of this invention, including the best method of performing it known to us:

Our Ref: #7253 TNB:WB 07-2pet

The invention relates to a device for supplying boiling water.

The prior art in the field of hot water supplying devices is fairly extensive. The prior art comprises, on the one hand, the devices which dispense hot water and, on the other, the devices which are designed for supplying boiling water.

The first group of devices includes the well known household boilers, which are so constructed that the water present therein can never reach the temperature of the atmospheric boiling point, which is accomplished in particular by means of a thermostat ensuring that a water temperature of, for instance, 85°C, is not exceeded, and in any case, that the boiling temperature of the water is not reached. The water in these boilers is present therein under normal water mains pressure and the boiler, as well as the water outlet conduits connected thereto, are completely filled with water, so that the outflow of the water, too, occurs under water mains pressure and upon withdrawal of water invariably an initial flow of water is obtained whose temperature is lower than that of the water in the boiler. The pressure increase to be expected during the heating of the water in the boiler to a temperature close to its boiling point, the relatively large quantity of water present in household boilers, as well as the substantial scale formation to be expected at temperatures

close to the boiling point, are reasons why achieving temperatures in the neighbourhood of the boiling point of water under atmospheric pressure is carefully avoided in devices as described hereinabove.

5 For many domestic purposes, for instance for making small quantities of coffee or tea, or for preparing small quantities of food, but also in laboratories, etc., it is desirable that small quantities of boiling water can be made available directly. It is noted here that there are important
10 physical differences between boiling water on the one hand and heated, but not boiling, water, on the other, inter alia
15 because boiling or thoroughly boiled water contains practically no carbon dioxide.

 There are known so-called through-flow devices, which
15 operate without pressure, i.e. the pressure on the water to be heated is the atmospheric pressure and the water is not heated to the temperature of the atmospheric boiling point until
20 water is drawn off.

 Known also are boiling-water devices, in which the
20 water is maintained at a superatmospheric temperature in a reservoir and in which a thermostat is set at a value which is
25 above the boiling point of water under atmospheric pressure. In these known boiling-water devices, the proposed, often complicated, construction was dictated by the fear that the pressure in the device would rise too high or that the cold and hot water would mix. The development of the prior art concerned is described in a series of four patent specifications.

Thus, GB patent specification 706,866 discloses a boiling-water device of the type described hereinabove, in which a limited water inlet is provided for, so as to allow the cold incoming water to be heated to the desired

5 temperature before it comes into contact with the rest of the water. In this type of device, the incoming amount of cold water is kept so small that it can be heated to the reservoir temperature while it flows along the heating element and then leaves the reservoir through the outlet arranged adjacent the
 10 bottom. The hot water supply in the reservoir is drawn upon as soon as per unit time more water is being withdrawn than is
 flowing in through the limited inlet. In that case the outflow pressure is determined by the vapour pressure of the water in
 the boiler and this is relatively low and not constant. To
 15 make maximum use of the reservoir contents, it is required that the outlet conduit is connected at the lowest possible point in the reservoir. Further, in devices of this type the water inlet must be limited severely, in view of the high
 specific heat of water and the relatively large amount of
 20 energy which is required for heating a given quantity of water to above its boiling point under atmospheric pressure.

.... In U.S. patent specification 2,786,126 the development as described in GB patent specification 706,866 is carried on, but now a particular control valve is used in the inlet
 25 circuit, so the incoming water cannot cool the water stored below the desired temperature. It is striking, but understandable in view of the object contemplated, that both

the water inlet and the water outlet terminate in the direct vicinity of the heating element.

U.S. patent specification 2,852,656 discloses a device in which there is no limited water inlet and in which means
5 for drawing off boiling water are connected to the top part of the reservoir, i.e. not in the direct vicinity of the heating element. However, it appears from the disclosure in that patent specification, that again all precautions have been taken to pass the incoming water directly along the heating
10 element, so as to adjust it to the temperature of the water already present in the reservoir as fast as possible, so as to prevent cooling of the water already present by the incoming water.

Finally, in U.S. patent specification 2,894,109 again
15 mention is made of the fear that incoming cold water will cool the water present in the reservoir, but this time again recourse is taken to the use of a limited water inlet circuit, accomplished by means of a specially designed control valve,
20 while the water inlet and the water outlet are again so arranged that they terminate in the direct vicinity of the heating element.

The devices described hereinabove have never gained practical application, presumably owing to their complicated construction and the associated problems encountered during
25 use.

The invention as described in Netherlands patent specification 172,589 was based on the finding that the problem of incoming water cooling the reservoir contents does

not arise in practice, and that without particular steps being taken, a good separation of cold and hot water remains present.

The device as described in that patent specification is of the type as described in U.S. patent specification 2,852,656. It comprises a thermally insulated compression resistant water reservoir, an electric heating element of such power that the water present in the reservoir is heated to above its atmospheric boiling point, a temperature control with which the temperature of the water in the reservoir is set above its boiling temperature under atmospheric pressure, a water inlet circuit, which is connected to the water mains and which is suitable for supplying an inlet flow which is at least equal to the delivery flow of the device, as well as means for drawing off boiling water joined directly to the reservoir and connected to the top part thereof.

In that device the water inlet circuit terminates under or at the underside of the heating element, while, preferably, there is arranged in the reservoir adjacent the water inlet a water divider for the incoming water to prevent the mixing of incoming cold water and the hot water present.

As described in that patent specification, in that device the cold/hot separation is maintained so well that more than 80% of the water contents can be withdrawn from the reservoir without the temperature thereof falling below the boiling temperature under atmospheric pressure. In the patent specification it is observed that this is surprising, the more so because the device described is intended for domestic use

in particular, and accordingly is relatively small, having particularly a volume of less than 10 liters, more particularly of approximately 5 liters, so that precisely in such a device a high degree of mixing could be expected.

5 Although the device as described in Netherlands patent specification 172,589 has proved its merits in practice, its use is accompanied by a number of as yet unsolved problems, so that it has not become generally used.

One of these problems is that the discharge conduit for
 10 the boiling water must be kept as short as possible, so as to limit an initial flow of cold, at least not boiling, water as much as possible. In practice, this causes problems, because then the discharge orifice is not disposed sufficiently high above a working surface, for instance a sink or the like,
 15 leaving too little space to place a mug, a pot or the like, under the discharge orifice. Moreover, the necessity of a short discharge conduit requires that the device be arranged directly under the sink top or the like. In practice, this is
 20 not always possible.

In the known device, the discharge valve is arranged at
 the end of the discharge conduit, so as to prevent the
 25 egressing water drops in the discharge conduit from being accelerated too strongly by the expanding, 20-fold volume amount of steam. Moreover, as described, this discharge valve must be of a particular construction to prevent the water spurting from the outlet orifice like a spray.

In practice, this position of the discharge valve leads to two important disadvantages. Because the entire device.

i.e. up to the discharge valve, is filled with water, the use of this device inevitably involves some initial flow of cold water. In view of the fact that the device is used for supplying small quantities of boiling water, for instance for making a single cup of tea or coffee, any initial flow of cold water is altogether unacceptable to the user.

- 5 Moreover, the tap arranged at the end of the discharge conduit will inevitably exhibit a measure of dripping.

It accordance with the present invention there is disclosed a device suitable for supplying boiling water, comprising a thermally insulated compression resistant water reservoir, an electric heating element of such power that the water present in
10 the reservoir is heated to a temperature above its atmospheric boiling point, a temperature control, with which the temperature of the water in the reservoir is adjusted to a temperature above the boiling temperature under atmospheric pressure, a water inlet which is connected to the water mains and which is suitable for supplying an inlet flow to the reservoir which is at least equal to the delivery flow
15 of the device, a discharge conduit connected to the reservoir for discharge of boiling water therefrom, the discharge conduit having an inlet end and an outlet end, decelerating means arranged adjacent the outlet end of the discharge conduit for decelerating the outflow of water and steam therefrom, wherein a discharge valve is associated with the inlet end of the discharge conduit.

- 20 Preferably, the discharge valve is arranged at a point in the conduit, which is lower than the outlet orifice and in particular in an conduit portion ascending from the discharge opening in the reservoir.

Surprisingly, it has been found that by virtue of this construction, after a certain amount of water has been drawn off, virtually no water remains behind in the
25 discharge conduit downstream of the discharge valve, because the rapid temperature drop in that conduit portion causes complete or virtually complete condensation of the water/stream mixture present therein.

The invention thus enables the construction of the device in which the length and the shape of the discharge conduit can



be freely chosen within certain limits, so that the device can not only be used more universally but also installed in such a space of limited accessibility as would not be suitable for installing a device according to the aforementioned

5 Netherlands patent specification in view of the possible length of the discharge conduit.

Another important advantage associated with the device according to the invention is that there is no or virtually no initial flow of cold water. Also the problem of dripping of
...10 the discharge conduit has been obviated, it having been found
... in particular that when the outlet conduit comprises an
... ascending portion that terminates in a descending portion,
... dripping of the tap can be avoided altogether.
...

Further, in the device according to the invention, the
15 pressure in the portion downstream of the discharge valve is atmospheric, at least substantially atmospheric, which allows greater constructional freedom than in the known device.

The inner surface of the discharge conduit in the
device according to the invention is preferably provided with
20 a thermally insulating material, for instance a plastics.

It is noted that in the literature the problem of the
occurrence of an initial flow of cold water in hot water
devices, as well as of dripping from the discharge valve, is known as such, and solutions to these problems have been
25 proposed. Thus, French patent specification 1,482,199 discloses an - atmospheric - device for supplying hot, i.e. non-boiling, water, in which an expansion vessel communicating with the discharge conduit is arranged which is in heat

contact with the reservoir contents. After a certain amount of hot water has been drawn off, the residual water in the discharge conduit is sucked into the expansion vessel.

However, this does not involve the condensation of a

5 water/steam mixture present in the conduit in question.

In U.S. patent specification 3,581,057 an - atmospheric - hot water device is described, in which an expansion chamber is provided and in which the discharge valve is arranged in the cold water pipe to the device. During drawing off, by a
 10 venturi action, from this expansion chamber water is sucked along by the water flowing into the reservoir, while at the
 15 top part of the chamber air enters. After shutting off the valve, by gravity the water returns from the discharge neck into the expansion chamber, so that dripping and cold initial flow are avoided.

In the boiling water reservoir according to the invention, the temperature in the reservoir is maintained above the temperature of the atmospheric boiling point of
 20 water. To that effect, a thermostat that is known per se can be employed, which is set above a temperature of the
 25 atmospheric boiling point and whose control range is such that the temperature in the reservoir cannot fall below the atmospheric boiling point. Thus, non-boiling water is kept in store at a temperature, such that, when drawn off, the discharged water nevertheless has a temperature of at least 100°C. The temperature is preferably set at a temperature between 100 and 120°C.

Because the overheated water will immediately start to boil when flowing out, drawing off water is accompanied by audible and visible steam production. The steam production, which can optionally be adjusted through the thermostat value, gives an indication of the water temperature. Thus, the user can dispose of boiling water at any desired moment, for instance for making a single quick cup of tea or coffee, without being disturbed by the noise that is invariably produced when water is kept boiling continuously. At a water mains pressure above 1.5 atmosphere, the thermostat is preferably set at a temperature of about 110°C.

Although in principle a non-return valve can be used in connecting the device to the water mains, this is not necessary considering the minor dimensions of the reservoir, whose volume is maximally 10 liters, and particularly 5 liters. With such minor dimensions, the boiler can be of robust construction, the price being kept low. Moreover, the advantage is that a minor use of electricity will suffice and that the device occupies little space.

Heretofore, in automatic devices for preparing hot drinks, for which steam of approximately 110°C is required, superheaters have been used in the form the through-flow heaters discussed hereinabove, wherein, using comparatively heavy electric heating elements, water is pumped through a heating zone with a controllable flow. Apart from the fact that this invariably involves an initial flow of cold water, the electricity mains is loaded with heavy electric current

surges, while, moreover, it is impossible to accomplish drip dosaging of hot water.

The device according to the invention may be fitted with known dosing means, for instance for use in vending machines. An alternative dosing possibility is to provide a dosing chamber, in heat contact with the reservoir, which chamber can be connected to the outlet conduit via a shut-off valve and to the reservoir via a second shut-off valve. By operating these two shut-off valves in time-related alternation, for instance electrically, a reliable drip-free dosage can be obtained.

In the device according to the invention, the discharge valve or shut-off can in principle be of any known construction and can be operated directly or, e.g., via a cable or a rod, or electrically. To prevent the water, when it is being drawing off, from spurting from the valve with great force or erratically owing to the steam expansion, preferably a valve design is chosen such that upon discharge steam can separate from the water. The valve may be fitted with a spring-biased valve member, so that in emergencies it serves as a safety means.

~~In general,~~ ^{In} ~~in~~ the device according to the invention, the outflow of water and steam is decelerated, preferably at the end of the discharge conduit. To that effect, there can be provided at the outflow orifice one or more perforated plates, one or more layers of wire mesh, one or more guiding partitions or a combination of these means. These means are so chosen that the total passage resistance is such that a



sufficient delivery flow is ensured when the shut-off valve is fully opened.

To further explain the invention, some embodiments of the boiling-water device will now be described, by way of example only, with reference to the accompanying drawings. Fig. 1 shows a schematic axial section of the device 1, whose volume is smaller than 10 liters and in particular approximately 5 liters, arranged under a sink top 2 or the like and connected directly to the water mains 3, the valve 7, mounted at the top of the reservoir 5, being disposed above the sink top.

From the pipe 3, water is admitted to the reservoir compartment 5, optionally via a non-return valve with safety valve 4, compartment 5 being connected via a shortest possible conduit 6 to a discharge valve 7 and an, optionally pivotal, outlet 8. The reservoir 5 and the discharge means 6,7 are preferably surrounded by an insulation 9, while the inner surface of outlet 8 is preferably likewise provided with an insulating material 10.

Extending in the reservoir 5 is an electric heating element 11 with connections 12. Further, a thermostat 13 with a switch 14 is arranged. Optionally, the switch 14 can be set at a desired temperature from outside.

The water in reservoir 5 is under the same pressure as prevails in pipe 3, for instance 1.5-3 atmosphere, which means that the water will only start to boil at a temperature between about 130°C and 155°C.

If the thermostat 13 is set at a temperature of 110°C with the switch 14, at normal water mains pressures the water will not boil and only upon opening of the valve 7 will it flow out under flash-evaporation, which is both audible and visible. The absence of steam is an immediate indication that the temperature of the water is too low. The rapid release of steam has the advantage that both carbon dioxide and obtrusive flavouring disappear from the water. Because the water, though having a temperature in excess of 100°C, does not boil, harmful deposition of scale will be restricted to a minimum.

According to a preferred embodiment of the device, a water divider 15 is arranged adjacent the bottom of the reservoir, generally adjacent the inlet of fresh water. A non-self-resetting temperature safety 16 can be arranged to prevent the temperature in the reservoir from rising too high if the thermostat fails. By means of threaded wire 17 or, for instance, a bayonet connection, and optionally using adapters, accessories can be connected to the boiling water device ~~instead of, or~~ in combination with, the decelerating means in the outlet orifice 18.

Fig. 2 is a section of the device with the reservoir 5 having the valve 7 mounted thereon, installed in a sink cupboard or a similar space and the outlet 8 being connected to the valve, for instance by means of a hose 19, while the valve is operated via a rod 21 by means of a turning knob 20 arranged above the sink top or the like.



Fig. 3 is a section of the device in which the valve is arranged above the sink top and connected to the reservoir 5 via an insulated conduit 22.

Fig. 4 is a schematic section of a dose-measuring device with a dosing chamber 23 arranged in the top of the reservoir 5 with an inlet valve 24 and an outlet valve 25, respectively connected to the reservoir and the outlet 8. Arranged on top of the dosing chamber 23 is a cover 26 permitting the proper dosage volume to be adjusted by means of filling bodies.

The claims form part of the disclosure of this specification.

The claims defining the invention are as follows:

1. A device suitable for supplying boiling water, comprising a thermally insulated compression resistant water reservoir, an electric heating element of such power that the water present in the reservoir is heated to a temperature above its atmospheric boiling point, a temperature control, with which the temperature of the water in the reservoir is adjusted to a temperature above the boiling temperature under atmospheric pressure, a water inlet which is connected to the water mains and which is suitable for supplying an inlet flow to the reservoir which is at least equal to the delivery flow of the device, a discharge conduit connected to the reservoir for discharge of boiling water therefrom, the discharge conduit having an inlet end and an outlet end, decelerating means arranged adjacent the outlet end of the discharge conduit for decelerating the outflow of water and steam therefrom, wherein a discharge valve is associated with the inlet end of the discharge conduit.
2. A device according to claim 1, characterized in that the discharge valve is arranged in the discharge conduit at a point that is lower than the outlet orifice of the discharge conduit.
3. A device according to either of claims 1-2, characterized in that the discharge conduit is an inverted U-shape, while the discharge valve is arranged in the ascending conduit portion, viewed from the discharge opening in the device.
4. A device according to any one of claims 1-3, characterized in that the internal surface of the discharge conduit is provided with insulating material.
5. A device according to any one of claims 1-4, characterized in that there is arranged in the reservoir adjacent the water inlet a dividing plate or the like for the incoming water.
6. A device according to any one of the preceding claims characterized in that said means for decelerating is formed by one or more perforated plates, one or more layers of wire mesh, one or more guiding partitions or the like or a combination of these means.
7. A device according to any one of the preceding claims wherein the reservoir



volume is less than about 10 litres, and in particular less than about 5 litres.

8. A device according to any one of the preceding claims characterized in that, as a discharge valve, a dose-measuring mechanism is used.

9. A device according to claim 8, characterized in that the dose-measuring
5 device comprises a dosing chamber in heat contact with the reservoir.

10. A device according to claim 9, characterized in that the dosing chamber can be connected to the top of the reservoir via a shut-off valve, while via a second shut-off valve the discharge outlet can be made to communicate with the underside of the dosing chamber.

11. A device for boiling liquids substantially as hereinbefore described with reference to the accompanying drawings.

DATED: 12 July 1994

CARTER SMITH & BEADLE

Patent Attorneys for the Applicants:

HENRI BERNARD PETERI AND NIELS THEODOOR PETERI



ABSTRACT

A device suitable for supplying boiling water, comprising a thermally insulated compression resistant water reservoir (1) and electric heating element (11) of such power that the water present in the reservoir is heated to a temperature above its atmospheric boiling point, a temperature control (13, 14) with which the temperature of the water in the reservoir is adjusted above the boiling temperature under atmospheric pressure, a water inlet circuit (3, 15) which is connected to the water mains and which is suitable for supplying an inlet flow which is at least equal to the delivery flow of the device, as well as a discharge conduit (6) for boiling water joined directly to the reservoir and connected to the top part thereof, the water inlet circuit terminating under or at the underside of the heating element (11), characterized in that a discharge valve (7) is mounted directly on the reservoir (1) or at a point in the discharge conduit (6) as close as possible to the discharge opening in the reservoir.

1/4




FIG.1

2/4




FIG.2

3/4




FIG. 3




FIG.4