



(22) Date de dépôt/Filing Date: 2007/10/04

(41) Mise à la disp. pub./Open to Public Insp.: 2008/04/25

(45) Date de délivrance/Issue Date: 2011/02/15

(30) Priorité/Priority: 2006/10/25 (US11/585,875)

(51) Cl.Int./Int.Cl. *B62B 17/02* (2006.01),
B62D 55/07 (2006.01)


(72) Inventeur/Inventor:
PRYPUTNIEWICZ, NICHOLAS, US

(73) Propriétaire/Owner:
PRYPUTNIEWICZ, NICHOLAS, US

(74) Agent: MCFADDEN, FINCHAM

(54) Titre : SKI DE MOTONEIGE PARABOLIQUE QUAD

(54) Title: QUAD PARABOLIC SNOWMOBILE SKI



(57) **Abrégé/Abstract:**

The quad parabolic snowmobile ski is an elongated body with a pair of symmetrically opposed ski parabolic cutting edges disposed longitudinally along the bottom and keel of the ski. The keel is attached to the bottom of the ski and has a central median ridge, i.e. a keel rail. A substantial portion of the keel rail protrudes below the bottom of the ski to form a central and longitudinal point of contact with the snow. The keel defines symmetrically opposed snow-funneling channels along the opposite sides of the central median ridge. Varying radii of curvature of the channels form parabolically-shaped channel outer sidewalls. Symmetrically opposed keel parabolic cutting edges are formed by contouring a keel body width to follow the contour of the parabolic shaped outer sidewalls at a constant cutting edge width.



ABSTRACT OF THE DISCLOSURE

The quad parabolic snowmobile ski is an elongated body with a pair of symmetrically opposed ski parabolic cutting edges disposed longitudinally along the bottom and keel of the ski. The keel is attached to the bottom of the ski and has a central median ridge, i.e. a keel rail. A substantial portion of the keel rail protrudes below the bottom of the ski to form a central and longitudinal point of contact with the snow. The keel defines symmetrically opposed snow-funneling channels along the opposite sides of the central median ridge. Varying radii of curvature of the channels form parabolically-shaped channel outer sidewalls. Symmetrically opposed keel parabolic cutting edges are formed by contouring a keel body width to follow the contour of the parabolic shaped outer sidewalls at a constant cutting edge width.

QUAD PARABOLIC SNOWMOBILE SKI**TECHNICAL FIELD**

The present invention relates to skis and to snowmobiles, and more particularly to a quad parabolic snowmobile ski for steering a snowmobile.

5

BACKGROUND ART

Skis have been used for transportation for centuries, including skis for attachment directly to the feet and skis for attachment to sleds, sleighs, and various other snow vehicles, including snowmobiles. Only within the last fifty years or so have these skis incorporated or included what have been referred to as wear or steering keel bars, runners, skags, and the like.

10

A typical runner blade may be attached by studs to the bottom surface of a ski, with the front and rear ends of the bar bent to tuck into the bottom of the ski. This method of attachment is still popular today.

15

A wear, steering keel, or runner bar can perform several functions. As one name implies, a wear bar is used to lengthen the life of the under or bottom surface of the ski by focusing the contact or wear on the bar when in contact with the ground or hard surfaces. As a steering keel bar, the bar extends downwards, as in a watercraft, to stabilize and improve the steering responsiveness and capability of the ski. Skis with steering keel bars are now in commonplace usage as steering skis for snowmobiles. However, many present designs incorporating a steering keel still do not provide tight, precision, high performance level steering.

20

International Patent No. WO 83/03554, published October 27, 1983, appears to disclose a wearable mono-ski with improved steering due to rear and front openings in the ski body. The '554 patent does not appear to address a ski appropriate for a snowmobile.

25

Thus, until now the lack of precision in turning capability has remained and often resulted in sloppy high speed turning characteristics that are evidenced by a plowing effect in a current direction of travel, rather than a controlled, turning effect in a steered direction. At high speeds, this effect can be dangerous and result in collision with objects in the path of the snowmobile even though the operator tries to steer around the objects.

30

Keel designers are continuously attempting to deal with this problem by modifying keel lengths and geometries to improve steering characteristics, yet maintain ease of steering

from driver inputs. Nevertheless, the problem of precision, predictable and relatively effortless steering remains to be solved.

Thus, a snowmobile ski solving the aforementioned problems is desired.

5

DISCLOSURE OF INVENTION

The quad parabolic snowmobile ski is an elongated body comprised of a pair of symmetrically opposite, ski parabolic cutting edges longitudinally disposed along the bottom of the ski, and a keel. The keel is attached to the bottom of the ski and has a central median ridge, i.e., a keel rail. A substantial portion of the keel rail protrudes below the bottom of the ski to form a central and longitudinal point of contact with the snow. Moreover, the keel comprises symmetrically opposed snow funneling channels along the left and right sides of the central median ridge.

Varying radii of curvature of the channels form parabolically shaped channel outer sidewalls. Symmetrically opposed keel parabolic cutting edges are formed by contouring a keel body width to follow the contour of the parabolically shaped outer sidewalls at a constant cutting edge width.

In accordance with an embodiment of the present invention, there is provided a snowmobile ski, comprising an elongated body having a top side; a strut attachment block disposed on the top side; a bottom side; a front end forming a tip; a rear end; a pair of symmetrically opposed ski parabolic cutting edges formed on the bottom side; and a keel formed on the bottom side, the keel having a central median ridge extending from the bottom side to form a central and longitudinal point of contact with snow and symmetrically opposed snow-funneling channels defined along opposite sides of the central median ridge, the channels having varying radii of curvature to form outer sidewalls having parabolic shapes, the sidewalls, excluding the tip region, being laterally farthest apart from each other between the tip and a front portion of the strut attachment block, as well as towards the rear end, the keel following the contour of the parabolic shaped outer sidewalls at a constant cutting edge width to form parabolic keel cutting edges, the parabolic cutting edges being disposed longitudinally along the bottom of the ski from a region near the front end tip to a region near the rear end, and having vertices directed laterally towards a longitudinal axis of the ski.

Yet another embodiment provides a snowmobile ski, comprising an elongated body having a top side; a strut attachment block disposed on the top side; a bottom side; a front end forming a tip; and a rear end, the elongated body having a parabolically-shaped lateral curvature extending from a region proximate the rear end to a region located longitudinally between the strut attachment block and the top of the front end; a keel formed on the bottom side, the keel having a central median ridge extending from the bottom side to form a central

35

2a

and longitudinal point of contact with snow and symmetrically opposed snow-funneling channels along opposite sides of the central median ridge, the channels having varying radii of curvature to form outer sidewalls, the outer sidewalls following the lateral contour of the elongated body to form a pair of inner keel parabolic cutting edges and a pair of outer ski parabolic cutting edges.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig 1 is an environmental, perspective view of a quad parabolic snowmobile ski according to the present invention.

Fig. 2 is a top perspective view of the quad parabolic snowmobile ski according to the present invention.

Fig. 3 is a bottom perspective view of the quad parabolic snowmobile ski according to the present invention.

Fig. 4 is an inverted transverse section view of the ski keel of the quad parabolic snowmobile ski according to the present invention.

Fig. 5 is a bottom plan view of the quad parabolic snowmobile ski according to the present invention.

Fig. 6 is a side view of the quad parabolic snowmobile ski according to the present invention.

Similar reference characters denote corresponding features consistently throughout the attached drawings.

BEST MODES FOR CARRYING OUT THE INVENTION

As shown in Fig. 1, the present invention is a quad parabolic snowmobile ski **105**, which is an elongated body having a tip **240** at the front end, a rear end **235**, and a strut attachment block **230** for attaching the ski **105** to a steering strut of snowmobile **S**. As most clearly shown in Figs 2 and 3, the ski **105** is further comprised of a top side **200**, a bottom side **107**, ski parabolic cutting edges **220**, a grab handle **239**, and a keel **202**. Additionally, as shown in Fig. 2, the strut attachment block **230** is molded with, or otherwise fixedly attached to, the ski top **200**.

As most clearly shown in Fig. 2, the grab handle **239** is an arcuate elongate member that extends from a front section of the strut attachment block **230** and wraps around the tip **240** of the ski **105**. The grab handle **239** is provided to help a user grab onto the skis **105** when transporting them, removing them, or preparing them for attachment to the snowmobile **S**.

As illustrated in Figs 3 and 5, the ski parabolic cutting edges **220** are symmetrically opposed, being disposed longitudinally along the bottom **107** from a region near the front end tip **240** to a region near the rear end **235**, and have vertices **VS**, i.e., parabolic curve minima, directed laterally towards a longitudinal axis **500** of the ski. Specific parabolic curve fitting parameters of the cutting edges **220** are preferably predetermined by modeling design template parabolic curves.

Additionally, as shown in Figs 3, 4 and 5, the keel **202** is attached or molded into the bottom **107** of the ski **105** and is disposed longitudinally, extending from a region near the front end tip **240** to a region near the rear end **235**, so that a central median ridge, i.e., a keel rail **205**, protrudes below the bottom **107** of the ski to form a central and longitudinal point of contact with the snow. Moreover, the keel **202** further comprises symmetrically opposed snow funneling channels **210** respectively disposed longitudinally along a first side **204** of the central median ridge **205** and along an opposing second side **206** of the central median ridge **205**. Additionally, the keel rail **205** may have a first gradient **207a** in its depth **D** disposed longitudinally proximate a rear section of the strut attachment block **230**. The first gradient **207a** is provided to lower an overall depth of the central median ridge, i.e., keel rail **205**. A second gradient **207b** may be provided proximate the rear end **235** to form a rear terminus of the keel rail **205**.

As shown in Fig. 4, which depicts an inverted transverse section view of the keel **202**, the channels **210** originate at the peak **T** of the central median ridge **205**, extending laterally

to the first side **204** and the second side **206**, curving down and away from the central median ridge to form a channel depth **D** that extends from the peak **T** to a channel floor **425**. From channel floor **425**, the curvature of the channels **210** then curves up and terminates, forming outer sidewalls **415** having a height less than depth **D** of the central median ridge **205**.

5 The radii of curvature of the symmetrically disposed channels **210**, i.e., the curvature from the outer edges of the ski **105** towards the central ridge or keel rail **205**, vary as a function of sidewall longitudinal displacement from the front end tip **240** to make the outer sidewalls **415** parabolically-shaped as seen in plan view so that, as shown in Figs 2 and 5, excluding the tip **240**, they are laterally closest to each other at a center region **225** of the ski
10 **105** and laterally farthest apart from each other longitudinally between the front end tip **240** and a front portion of the strut attachment block **230**, as well as towards the rear end **235**. Specific parabolic curve fitting parameters of the parabolically-shaped outer sidewalls **415** are preferably predetermined by modeling design template parabolic curves.

 Symmetrically opposite, longitudinally disposed keel parabolic cutting edges **212** are
15 formed by contouring the keel body width **W** to form a constant cutting edge width **EW**. The cutting edge width **EW** is substantially equal to $W - W'$. Since the keel parabolic cutting edges **212** follow the contour of the parabolically-shaped outer sidewalls **415**, excluding the tip **240**, the keel parabolic cutting edges **212** are laterally closest to each other at a center region **225** of the ski **105** and laterally farthest apart from each other between the front end tip
20 **240** and a front portion of the strut attachment block **230**, as well as towards the rear end **235**.

 Advantageously, the channels **210** provide a tunneling action of snow in contact with the keel **202** to reduce straight line travel friction. According to the present invention, the ski parabolic edges **220** work in conjunction with the keel parabolic cutting edges **212** to provide an aggressive cut for turning the snowmobile with ease and in a reliable manner. Before
25 fabrication, tuning of the quad parabolic ski **105** steering characteristics may be achieved by adjusting parameters of the design template parabolic curves according to the equation: $Ax^2 + Bxy + Cy^2 + Dx + Ey + F = 0$ so long as coefficient $B^2 = 4AC$.

 The quad parabolic ski **105** may preferably be fabricated from Ultra High Molecular Weight Polyethylene, i.e., UHMW plastic. Alternatively, the ski **105** may be fabricated from
30 any other material or group of materials having light weight, high tensile strength, shatter resistance, and abrasion resistant properties. A flexible and durable coating **430** that is easily bonded to the ski components and having a low coefficient of surface friction may be applied in order to further reduce turning efforts from steering inputs applied by a snowmobile driver.

As shown in Fig. 6, the front end tip **240** may have an upsweep angle A_t between 0° and 90° . Similarly the rear end **235** may have an upsweep angle A_b between 0° and 90° .

It is to be understood that the present invention is not limited to the embodiment described above, but encompasses any and all embodiments within the scope of the following
5 claims.

6

CLAIMS

1. A snowmobile ski, comprising an elongated body having:

a top side;

a strut attachment block disposed on the top side;

5 a bottom side;

a front end forming a tip;

a rear end;

a pair of symmetrically opposed ski parabolic cutting edges formed on the bottom side; and

10 a keel formed on the bottom side, the keel having a central median ridge extending from the bottom side to form a central and longitudinal point of contact with snow and symmetrically opposed snow-funneling channels defined along opposite sides of the central median ridge, the channels having varying radii of curvature to form outer sidewalls having parabolic shapes, the sidewalls, excluding the tip region, being laterally closest to each other
15 at a center region of the elongated body and laterally farthest apart from each other between the tip and a front portion of the strut attachment block, as well as towards the rear end, the keel following the contour of the parabolic shaped outer sidewalls at a constant cutting edge width to form parabolic keel cutting edges, the parabolic cutting edges being disposed longitudinally along the bottom of the ski from a region near the front end tip to a region near
20 the rear end, and having vertices directed laterally towards a longitudinal axis of the ski.

2. The snowmobile ski according to claim 1, wherein the central median ridge has a first gradient disposed longitudinally proximate a rear section of the strut attachment block, the gradient lowering depth of the central median ridge measured from the elongated body.

3. The snowmobile ski according to claim 2, wherein the central median ridge has a
25 second gradient disposed longitudinally proximate the rear end of the ski, whereby the depth of the central median ridge measured from the elongated body is lowered to form a rear terminus of the central median ridge.

4. The snowmobile ski according to claim 1, wherein the central median ridge extends to a maximum channel depth below the elongated body.

30 5. The snowmobile ski according to claim 4, wherein the outer sidewalls extend downward a distance less than the channel depth from the elongate body.

6. The snowmobile ski according to claim 1, wherein the radii of curvature of the channels vary as a function of sidewall longitudinal displacement from the front end tip so that the outer sidewalls are parabolically-shaped.

5 7. The snowmobile ski according to claim 1, wherein the elongated body is composed of a high tensile strength, shatter resistant material.

8. The snowmobile ski according to claim 7, wherein the elongated body is composed of a lightweight material.

9. The snowmobile ski according to claim 7, wherein the elongated body is composed of an abrasion resistant material.

10 10. The snowmobile ski according to claim 7, further comprising a flexible, durable coating disposed on the elongated body, the coating having a low coefficient of surface friction to provide reduced turning effort from steering inputs during use of the ski.

11. The snowmobile ski according to claim 1, wherein the front end and the rear end of said elongated body are upturned.

15 12. A snowmobile ski, comprising an elongated body having:

a top side;

a strut attachment block disposed on the top side;

a bottom side;

a front end forming a tip; and

20 a rear end, the elongated body having a parabolically-shaped lateral curvature extending from a region proximate the rear end to a region located longitudinally between the strut attachment block and the tip of the front end;

a keel formed on the bottom side, the keel having a central median ridge extending from the bottom side to form a central and longitudinal point of contact with snow and
25 symmetrically opposed snow-funneling channels along opposite sides of the central median ridge, the channels having varying radii of curvature to form outer sidewalls, the outer sidewalls following the lateral contour of the elongated body to form a pair of inner keel parabolic cutting edges and a pair of outer ski parabolic cutting edges.

30 13. The snowmobile ski according to claim 12, wherein the central median ridge has a first gradient disposed longitudinally proximate a rear section of the strut attachment block, the gradient lowering depth of the central median ridge measured from the elongated body.

14. The snowmobile ski according to claim 13, wherein the central median ridge has a second gradient disposed longitudinally proximate the rear end of the ski, whereby the

depth of the central median ridge measured from the elongated body is lowered to form a rear terminus of the central median ridge.

15. The snowmobile ski according to claim 12, wherein the central median ridge extends to a maximum channel depth below the elongated body.

5 16. The snowmobile ski according to claim 15, wherein the outer sidewalls extend downward a distance less than the channel depth from the elongate body.

17. The snowmobile ski according to claim 12, wherein the radii of curvature of the channels vary as a function of sidewall longitudinal displacement from the front end tip so that the outer sidewalls are parabolically-shaped.

10 18. The snowmobile ski according to claim 12, wherein the front end and the rear end of said elongated body are upturned.

19. The snowmobile ski according to claim 12, wherein the elongated body is composed of a high tensile strength, shatter resistant material.

15 20. The snowmobile ski according to claim 12, further comprising a grab handle extending from a front section of the strut attachment block to wrap around the tip of the elongated body, the handle for grabbing onto the ski for transport, and for handling the ski when attaching the ski to, and removing the ski from, a snowmobile.

1/6




Fig. 1

2/6





Fig. 2

3/6

*Fig. 3*




Fig. 4




Fig. 5




Fig. 6

