



(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 10,378,815 B2**
(45) **Date of Patent:** **Aug. 13, 2019**

(54) **REFRIGERATOR**

(71) Applicant: **LG Electronics Inc.**, Seoul (KR)

(72) Inventors: **Ikkyu Lee**, Seoul (KR); **Dongrim Woo**, Seoul (KR)

(73) Assignee: **LG Electronics Inc.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 70 days.

(21) Appl. No.: **15/818,966**

(22) Filed: **Nov. 21, 2017**

(65) **Prior Publication Data**

US 2018/0149420 A1 May 31, 2018

(30) **Foreign Application Priority Data**

Nov. 29, 2016 (KR) 10-2016-0160178
Mar. 4, 2017 (KR) 10-2017-0028004

(51) **Int. Cl.**

F21V 8/00 (2006.01)
H05K 5/00 (2006.01)
H05K 7/14 (2006.01)
F25D 23/02 (2006.01)
F25D 27/00 (2006.01)
F25D 29/00 (2006.01)

(52) **U.S. Cl.**

CPC **F25D 29/005** (2013.01); **F25D 23/028** (2013.01); **F25D 27/005** (2013.01); **G02B 6/009** (2013.01); **G02B 6/0083** (2013.01); **G02B 6/0088** (2013.01); **G02B 6/0091** (2013.01); **H05K 5/0017** (2013.01); **H05K 7/1427** (2013.01); **F25D 2323/023** (2013.01); **F25D 2323/024** (2013.01); **F25D 2400/18** (2013.01); **F25D 2400/36** (2013.01); **F25D 2400/361** (2013.01); **F25D 2400/40** (2013.01)

(58) **Field of Classification Search**

CPC F25D 29/005; F25D 23/02; F25D 23/028; F25D 2400/36; F25D 2700/02; F25D 27/005; F25D 2400/40; F25D 2323/023; F25D 2323/024; G02B 26/026; G02B 6/0088; G02B 6/0091; G02B 6/009; G02B 6/0083; G02F 1/13338; G25D 24/361; H05K 5/0017; H05K 7/1427

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

10,007,385 B2* 6/2018 Kim G06F 3/044
2005/0284159 A1* 12/2005 Kim F25D 23/028
62/126
2006/0196214 A1* 9/2006 Lee F25D 17/065
62/344

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO2016175563 A1 11/2016

OTHER PUBLICATIONS

European Extended Search Report in European Application No. 17202681.7, dated Apr. 25, 2018, 10 pages.

Primary Examiner — Dimary S Lopez Cruz



Assistant Examiner — Ingrid D Wright

(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(57) **ABSTRACT**

Provided is a refrigerator in which a transparent display assembly and electric modules, which are disposed in a door to see through a storage space and output a screen, are easily connected to a control unit provided in a cabinet and guided through a narrow door hinge.

20 Claims, 41 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0063261	A1*	3/2011	Park	G02F 1/13452 345/204
2014/0144083	A1*	5/2014	Artwohl	A47F 3/0434 49/70
2015/0356934	A1*	12/2015	Yamashita	G09G 3/3611 345/205

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 38




FIG. 39




FIG. 40





FIG. 41



REFRIGERATOR**CROSS-REFERENCE TO RELATED APPLICATIONS**

The present application claims priority under 35 U.S.C. 119 and 35 U.S.C. 365 to Korean Patent Application No. 10-2016-0160178 (filed on Nov. 29, 2016) and 10-2017-0028004 (filed on Mar. 4, 2017) which is hereby incorporated by reference in its entirety.

BACKGROUND

The present disclosure relates to a refrigerator.

In general, refrigerators are home appliances for storing foods at a low temperature in a storage space that is covered by a door. For this, refrigerators cool the inside of the storage space by using cool air generated by being heat-exchanged with a refrigerant circulated through a refrigeration cycle to store foods in an optimum state.

In recent years, refrigerators tend to increase in size more and more, and multi-functions are applied to refrigerators as dietary life changes and high-quality is pursued, and accordingly, refrigerators of various structures for user convenience and efficient use of an internal space are being brought to the market.

A storage space of such a refrigerator may be opened and closed by a door. Also, refrigerators may be classified into various types according to an arranged configuration of the storage space and a structure of the door for opening and closing the storage space.

Generally, the refrigerator has a limitation that foods stored therein are not confirmed unless the door is not opened. That is, the door has to be opened to confirm that a desired food is stored in the refrigerator or in a separate storage space provided in the door. In addition, if the stored position of the food is not known precisely, an opened time of the door may increase, or the number of times for opening the door increases. In this case, there is a limitation that unnecessary leakage of cool air occurs.

In recent years, to solve such a limitation, a refrigerator has been developed while allows a portion of a door thereof to be transparent or allows the inside thereof to be seen from the outside.

SUMMARY

Embodiments provide a refrigerator in which at least a portion of a refrigerator door is selectively transparent by user's manipulation to allow the user to see the inside of the refrigerator even though the refrigerator door is closed, and simultaneously, to selectively output a screen.

Embodiments also provide a refrigerator in which a see-through part constituting a portion of a door is capable of being transparent or opaque or outputting a screen according to selective turn-on/off of a door light or a display light.

Embodiments also provide a refrigerator in which a PCB and a cable connected to the PCB are disposed in a door, which is capable of seeing through the inside of the refrigerator by a transparent display assembly, without being exposed through the transparent display.

Embodiments also provide a refrigerator in which is capable of preventing a display and PCBs for driving the display within a door from being damaged and also insulating the inside of the refrigerator.

Embodiments also provide a refrigerator in which a PCB connected to electric modules is easily assembled and mounted in a door.

Embodiments also provide a refrigerator in which a plurality of electric modules in a door are simply connected to a control unit of a main body.

Embodiments also provide a refrigerator in which a door has a compact structure through arrangement and connection of wires connected to electric modules of a transparent display assembly provided in the door.

Embodiments also provide a refrigerator in which a transparent display assembly and electric modules, which are provided in a door, are easily connected to a control unit and guided through a narrow door hinge.

In one embodiment, a refrigerator includes: a cabinet defining a storage space; a control unit disposed on an upper portion of the cabinet; a door connected to the cabinet through a hinge to open and close the storage space and having an opening of which at least a portion is penetrated toward the storage space; and a transparent display assembly mounted to cover the opening and including a plurality of electric modules for see-through of the storage space and an output of an image, wherein the transparent display assembly includes: a PCB disposed inside the door and electrically connected to a portion of the electric modules; and a docking PCB disposed adjacent to the PCB, the docking PCB being connected to the other portion of the electric modules and the PCB through a cable and connected to the control unit through a connection cable to allow the electric modules and the PCB to be indirectly connected to the control unit, wherein, in the docking PCB, the number of connection connectors, to which the connection cable guided to the outside of the door via the hinge is connected, is less than that of connectors to which the cables are connected, and a control signal of the control unit is transmitted to the PCB through the docking PCB to control the electric modules.

At least a portion of the cables may be provided as a flexible flat cable, and the connection cable may be provided as a wire type cable.

The connection cable may be guided to the outside of the door by passing through a wire hole that is opened in an upper cap deco defining a top surface of the door.

The connection cable may be guided to the outside of the door by passing through a hinge shaft of the hinge mounted on an upper end of the door.

The electric modules may include: a display for outputting a screen; a touch sensor for touch manipulation of the display; and a display light for brightening up a light guide plate disposed at a rear side of the display.

A source PCB may be disposed on one end of both ends of the display, and the source PCB may be disposed in a direction perpendicular to the display inside the transparent display assembly.

The refrigerator may further include a flat type display cable connecting the source PCB to the PCB, wherein the display cable may be bent to extend along a circumferential surface of the transparent display assembly.

The refrigerator may further include a flat type touch cable connecting the touch sensor to the PCB, wherein the touch cable may be connected to the PCB by passing through the circumferential surface of the transparent display assembly inside the transparent display assembly.

The refrigerator may further include a flat type display light cable connecting the display light to the PCB, wherein the display light cable may be disposed along a protrusion that protrudes to the outside of a panel defining a front or rear surface of the transparent display assembly.

The electric modules may include a door light disposed on a rear surface of the door to brighten up a rear space of the door.

The PCB may include: a touch PCB electrically connected to the touch sensor; and a T-CON board electrically connected to the display, wherein at least one of the touch PCB and the T-CON board may be connected to the docking PCB.

An opening through which the cable connected to the PCB is exposed and into which the PCB connected to the cable is inserted may be defined in a circumference of the door, and an insulation material may be filled around the door except for a space between the opening and the transparent display assembly.

The opening may be defined in a cap deco defining a top or bottom surface of the door, a deco cover covering the opening may be disposed on the cap deco, and in the deco cover, a PCB mounting part, on which the PCB and the docking PCB are mounted, may extend into the opening.

The connection cable may include: a first connection cable for supplying power; and a second connection cable for processing a signal.

The connection cable may include: a first connection cable connected to the electric module for which supply of a high voltage is required; and a second connection cable connected to the electric module for which supply of a low voltage is required.

The connection cable may include: a first connection cable through which the power is supplied; and a second connection cable through which the power is supplied according an operation signal.

The door may include: a main door opening and closing a first storage space within the cabinet and defining an opened second storage space; a main hinge allowing the main door to be rotatably mounted on the cabinet; a sub door disposed on a front side of the main door to open and close the second storage space and having the opening penetrated at a position corresponding to the second storage space; and a sub hinge allowing the sub door to be rotatably mounted on the main door.

A hinge shaft of the sub hinge may have an inner diameter less than that of a rotation shaft of the main hinge, and the connection cable may be guided to the outside of the door by passing through the hinge shaft of the sub hinge.

The hinge shaft of the sub hinge may communicate with a space, in which the docking PCB is mounted, inside the sub door.

In the connection cable, a plurality of wires may be bound as one bundle by a binding member to pass through the hinge shaft of the sub hinge.

The details of one or more embodiments are set forth in the accompanying drawings and the description below. Other features will be apparent from the description and drawings, and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front view of a refrigerator according to a first embodiment.

FIG. 2 is a perspective view of the refrigerator.

FIG. 3 is a perspective view of the refrigerator with a sub door opened.

FIG. 4 is a perspective view of the refrigerator with a main door opened.

FIG. 5 is a perspective view of the sub door when viewed from a front side.

FIG. 6 is a perspective view of the sub door when viewed from a rear side.

FIG. 7 is an exploded perspective view of the sub door.

FIG. 8 is a partial perspective view illustrating an upper portion of an inner frame when viewed from a front side according to the first embodiment.

FIG. 9 is a partial perspective view of the upper portion of the inner frame when viewed from a rear side.

FIG. 10 is a perspective view of a transparent display assembly according to the first embodiment.

FIG. 11 is an exploded perspective view of the transparent display assembly.

FIG. 12 is a cross-sectional view of the transparent display assembly.

FIG. 13 is an exploded perspective view of a coupling structure between a cap deco and a PCB according to the first embodiment.

FIG. 14 is an exploded perspective view of the coupling structure between the cap deco and the PCB according to the first embodiment.

FIG. 15 is an exploded perspective view illustrating a structure in which the PCB is mounted on the sub door.

FIG. 16 is a cut-away perspective view illustrating an upper end of the sub door.

FIG. 17 is a partial perspective view illustrating a connection structure between cables and PCBs of the transparent display assembly.

FIG. 18 is a plan view illustrating an arrangement of the cable connecting the sub door to a control unit.

FIG. 19 is a block diagram illustrating a flow of a control signal of the refrigerator.

FIGS. 20 and 21 are block diagrams illustrating a different connection state of the connection cable connected to the control unit.

FIG. 22 is a transverse cross-sectional view of the main door and the sub door.

FIG. 23 is a longitudinal cross-sectional view of the main door and the sub door.

FIG. 24 is a view illustrating a state in which the inside of the refrigerator is seen through the transparent display assembly.

FIG. 25 is a view illustrating a state in which a screen is outputted through the transparent display assembly.

FIG. 26 is an exploded perspective view of a door according to a second embodiment.

FIG. 27 is an exploded perspective view of a door according to a third embodiment.

FIG. 28 is an exploded perspective view of a door according to a fourth embodiment.

FIG. 29 is a block diagram illustrating a flow of a control signal in a refrigerator according to the fourth embodiment.

FIG. 30 is a partial perspective view illustrating an arrangement of a wire of a door according to a fifth embodiment.

FIG. 31 is a partial exploded perspective view of a door according to a sixth embodiment.

FIG. 32 is a cross-sectional view of the door according to the sixth embodiment.

FIG. 33 is a plan view of a refrigerator according to a seventh embodiment.

FIG. 34 is a block diagram illustrating a flow of a control signal of the refrigerator.

FIG. 35 is a perspective view illustrating a structure of PCBs disposed in a sub door according to the seventh embodiment.

5

FIG. 36 is an exploded perspective view illustrating a connection structure between the PCBs and a cable inside the sub door.

FIG. 37 is an exploded perspective view illustrating an arrangement of a wire outside the sub door.

FIG. 38 is an exploded perspective view of a door according to an eighth embodiment.

FIG. 39 is an exploded perspective view of a sub door according to the eighth embodiment.

FIG. 40 is an exploded perspective view of a transparent display assembly according to the eighth embodiment.

FIG. 41 is a block diagram illustrating a flow of a control signal in a refrigerator according to the eighth embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

Reference will now be made in detail to the embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. The invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein; rather, that alternate embodiments included in other retrogressive inventions or falling within the spirit and scope of the present disclosure will fully convey the concept of the invention to those skilled in the art.

FIG. 1 is a front view of a refrigerator according to a first embodiment. Also, FIG. 2 is a perspective view of the refrigerator.

Referring to FIGS. 1 and 2, a refrigerator 1 according to a first embodiment includes a cabinet 10 defining a storage space and a door that opens or closes the storage space. Here, an outer appearance of the refrigerator 1 may be defined by the cabinet 10 and the door.

The inside of the cabinet 10 is partitioned into upper and lower portions by a barrier (see FIG. 11). A refrigerating compartment 12 may be defined in the upper portion of the cabinet 10, and a freezing compartment 13 may be defined in the lower portion of the cabinet 10.

Also, a control unit 14 for controlling an overall operation of the refrigerator 1 may be disposed on a top surface of the cabinet 10. The control unit 14 may be configured to control a cooling operation of the refrigerator as well as electric modules for selective see-through and screen output of a see-through part 21.

The door may include a refrigerating compartment door and a freezing compartment door 30. The refrigerating compartment door 20 may be opened and closed by rotating an opened front surface of the refrigerating compartment 12, and the freezing compartment door 30 may be switched by rotating an opened front surface of the freezing compartment 13.

Also, the refrigerating compartment door 20 may be provided in a pair of left and right doors. Thus, the refrigerating compartment 12 is covered by the pair of doors. The freezing compartment door 30 may be provided in a pair of left and right doors. Thus, the freezing compartment 13 may be opened and closed by the pair of doors. Alternatively, the freezing compartment door 30 may be withdrawable in a draw type as necessary and provided as one or more doors.

Although a refrigerator in which, a French type door in which a pair of doors rotate to open and close one space is applied to a bottom freezer type refrigerator in which the freezing compartment 13 is provided at a lower portion, is described as an example in this embodiment, the present

6

disclosure may be applied to all types of refrigerators including door without being limited to shapes of the refrigerators.

Also, recessed handle grooves 201 and 301 may be provided in a lower end of the refrigerating compartment door 20 and an upper end of the freezing compartment door 30. A user may insert a his/her hand into the handle groove 201 or 301 to open and close the refrigerating compartment door 20 or the freezing compartment door 30.

At least one door may be provided so that the inside of the refrigerator is seen through the door. A see-through part 21 that is an area, through which the storage space in the rear surface of the door and/or the inside of the refrigerator are seen, may be provided in the refrigerating compartment door 20. The see-through part 21 may constitute at least a portion of a front surface of the refrigerating compartment door 20. The see-through part 21 may be selectively transparent or opaque according to user's manipulation. Thus, foods accommodated in the refrigerator may be accurately identified through the see-through part 21.

Also, although the structure in which the see-through part 21 is provided in the refrigerating compartment door 20 is described as an example in this embodiment, the see-through part 21 may be provided in different types of refrigerator doors such as the freezing compartment door 30 according to a structure and configuration of the refrigerator.

FIG. 3 is a perspective view of the refrigerator with a sub door opened. Also, FIG. 4 is a perspective view of the refrigerator with a main door opened.

As illustrated in FIGS. 3 and 4, the refrigerating compartment door 20, which is disposed at the right side (when viewed in FIG. 3), of the pair of refrigerating compartment doors 20 may be doubly opened and closed. In detail, the refrigerating compartment door 20, which is disposed at the right side, may include a main door 40 that opening and closing the refrigerating compartment 12 and a sub door 50 rotatably disposed on the main door 40 to open and close an opening defined in the main door 40.

The main door 40 may have the same size as that of the refrigerating compartment door 20, which is disposed at the left side (when viewed in FIG. 1), of the pair of refrigerating compartment doors 20. The main door 40 may be rotatably mounted on the cabinet 10 by an upper hinge 401 and a lower hinge 402 to open at least a portion of the refrigerating compartment door 20.

Also, an opening 41 that is opened with a predetermined size is defined in the main door 40. A door basket 431 may be mounted on the rear surface of the main door 40 as well as the inside of the opening 41. Here, the opening 41 may have a size that occupies most of the front surface of the main door 40 except for a portion of a circumference of the main door 40.

Also, a main gasket 45 may be disposed on a circumference of the rear surface of the main door 40 to prevent cool air within an internal space of the cabinet 10 from leaking when the main door 40 is opened.

The sub door 50 may be rotatably mounted on the front surface of the main door 40 to open and close the opening 41. Thus, the sub door 50 may be opened to expose the opening 41.

The sub door 50 may have the same size as the main door 40 to cover the entire front surface of the main door 40. Also, when the sub door 50 is closed, the main door 40 and the sub door 50 may be coupled to each other to provide the same size and configuration as those of the left refrigerating compartment door 20. Also, a sub gasket 503 may be

disposed on the rear surface of the sub door **50** to seal a gap between the main door **40** and the sub door **50**.

A transparent display assembly **60** that selectively sees the inside and outputs a screen may be disposed at a center of the sub door **50**. Thus, even though the sub door **50** is closed, the inside of the opening **41** may be selectively seen, and also an image inside the opening **41** may be outputted. The see-through part **21** may be a portion of the sub door **50**, through which the inside of the refrigerator **1** is seen. However, the see-through part **21** may not necessarily match the entirety of the transparent display assembly **60**.

The transparent display assembly **60** may be configured to be selectively transparent or opaque according to user's manipulation. Thus, only when the user desires, the transparent display assembly **60** may be transparent so that the inside of the refrigerator **1** is visualized, otherwise, be maintained in the opaque state. Also, the transparent display assembly **60** may output a screen in the transparent or opaque state.

A sub upper hinge **501** and a sub lower hinge **502** may be respectively provided on upper and lower ends of the sub door **50** so that the sub door **50** is rotatably mounted on the front surface of the main door **40**. Also, an opening device **59** may be provided on the sub door **50**. A locking unit **42** may be provided on the main door **40** to correspond to the opening device **59**. Thus, the sub door **50** may be maintained in the closed state by the coupling between the opening device **59** and the locking unit **42**. When the coupling between the opening device **59** and the locking unit **42** is released by manipulation of the opening device **59**, the sub door **50** may be opened with respect to the main door **40**.

Also, a damping device **504** may be provided on a lower end of the sub door **50**. The damping device **504** may be disposed on edges of the lower end and lateral end of the sub door **50**, which are adjacent to the sub lower hinge **502**, so that an impact is damped when the sub door **50** having a relatively heavy weight by the transparent display assembly **60** is closed.

An accommodation case **43** may be provided in the rear surface of the main door **40**. A plurality of door baskets **431** may be disposed on the accommodation case **43**, and a case door **432** may be provided on the accommodation case **43**.

FIG. **5** is a perspective view of the sub door when viewed from a front side. FIG. **6** is a perspective view of the sub door when viewed from a rear side. Also, FIG. **7** is an exploded perspective view of the sub door.

As illustrated in the drawings, the sub door **50** may include an outer plate **51** defining an outer appearance of the sub door **50**, a door linear **56** mounted to be spaced apart from the outer plate **51**, the transparent display assembly **60** mounted on an opening of the outer plate **51** and the door linear **56**, and upper and lower cap decos **54** and **55** defining the top and bottom surfaces of the sub door **50**. The above-described constituents may be coupled to define the whole outer appearance of the sub door **50**.

The outer plate **51** may constitute an outer appearance of the front surface of the sub door **50** and a portion of a circumferential surface of the sub door **50** and be made of a stainless steel material. The outer plate **51** may constitute a portion of the outer appearance of the sub door **50** as well as the front surface of the sub door **50**. Also, the outer plate **51** may be made of the same material of the front surface of each of the refrigerating compartment door **20** and the freezing compartment door **30**. Various surface treatments such as coating or film attachment so as to realize anti-fingerprint coating, hair lines, colors, or patterns may be performed on the front surface of the outer plate **51**.

The outer plate **51** may include a front part **512** defining the outer appearance of the front surface and a side part **513** defining an outer appearance of the side surface that is exposed to the outside. Also, a plate opening **511** may be defined at a center of the front part **512**. Here, the plate opening **511** may be covered by the transparent display assembly **60**. Also, since the inside of the refrigerator **1** is seen through the transparent display assembly **60** covering the plate opening **511**, the inside of the plate opening **511** is called the see-through part **21**.

The front part **512** may have a curvature that gradually decreases outward from a central side of the refrigerator **1** as a whole. The front part **512** may be rounded to correspond to the front surface of the refrigerating compartment door **20**, which is adjacent to the front part **512**. Thus, the outer appearance of the front surface of the refrigerator **1** may be three-dimensionally viewed as a whole.

Also, an opening bent part **514** that is bent backward may be disposed on a circumferential surface of the plate opening **511**. The opening bent part **514** may be disposed along a circumference of the plate opening **511** and extend by a predetermined length so as to be inserted into and fixed to an inner frame **52** that will be described below. Thus, the plate opening **511** may be defined by the opening bent part **514**.

The side part **513** that is bent backward may be disposed on each of both ends of the front part **512**. The side part **513** may define an outer appearance of the side surface of the sub door **50**. Also, an end of the side part **513** may also be bent inward to be coupled to the door linear **56**.

Upper and lower ends of the outer plate **51** may also be bent to be coupled to the upper cap deco **54** and the lower cap deco **55**. Thus, the outer plate **51** may define the outer appearance of the sub door **50** by being coupled to the door linear **56** and the upper and lower cap decos **54** and **55**.

The door linear **56** defines the rear surface of the sub door **50** and has a door linear opening **561** in the area on which the transparent display assembly **60** is disposed. Also, a sub gasket **503** for sealing a gap between the sub door **50** and the main door **40** may be mounted on the rear surface of the door linear **56**.

Also, a door light **57** may be provided on each of both sides of the door linear opening **561**. The door light **57** may illuminate the rear surface of the sub door **50** and a rear side of the transparent display assembly **60**.

Thus, the door light **57** may illuminate an inner space of the accommodation case **43**, and simultaneously, serve as an auxiliary backlight function of the transparent display assembly **60** to more clearly output a screen of the transparent display assembly **60**. When the door light **57** is turned on, the inside of the accommodation case **43** may be brightened up, and thus, the inside of the refrigerator **1** may be more brightened up than the outside of the refrigerator **1** so that the inside of the refrigerator **1** may be visualized through the transparent display assembly **60**.

The door light **57** may be disposed on both sides of the transparent display assembly **60** in directions facing each other. The mounted position of the door light **57** may variously vary as long as the door light **57** has sufficient brightness at the rear side of the sub door.

Also, the opening device **59** may be mounted on the door linear **56**. The opening device **59** may include a manipulation member **591** exposed to the lower end of the sub door **50**, a load **592** extending from the manipulation member **591**, and a locking member **593** protruding from the rear surface of the door linear **56**. The user may manipulate the manipulation member **591** to allow the load **592** to move the locking member **593** so that the sub door **50** is selectively

restricted by the main door **40** and also to manipulate the opening and closing of the sub door **50**.

The upper cap deco **54** may define a top surface of the sub door **50** and be coupled to upper ends of the outer plate **51** and the door linear **56**. Also, a sub upper hinge mounting part **541** may be disposed on one end of the upper cap deco **54**, and a hinge hole **541a** into which a hinge shaft of the upper hinge **401** is inserted may be defined in the sub upper hinge mounting part **541**. A structure of the upper cap deco **54** will be described below in more detail.

The lower cap deco **55** may define a bottom surface of the sub door **50** and be coupled to lower ends of the outer plate **51** and the door linear **56**.

The transparent display assembly **60** may be disposed between the outer plate **51** and the door linear **56**. Also, the transparent display assembly **60** may be configured to cover the plate opening **511** and the door linear opening **561**. Also, the transparent display assembly **60** may be selectively manipulated to one state of transparent, translucent, opaque, and screen output states by the user.

Thus, the user may selectively see through the inner space of the sub door **50** through the transparent display assembly **60** and see the screen outputted through the transparent display assembly **60**.

The inner frame **52** for supporting the transparent display assembly **60** is mounted on a circumference of the plate opening **511** of the outer plate **51**. The transparent display assembly **60** may be fixed and mounted on the outer plate **51** by the inner frame **52**. Particularly, a front surface of the outer plate **51** and the front surface of the transparent display assembly **60** may be disposed on the same extension line so that the front surface of the sub door **50** has a sense of unity.

A frame opening **521** is defined at a center of the inner frame **52**. The frame opening **521** has a size somewhat less than that of the plate opening **511** and has a structure in which the transparent display assembly **60** is seated thereon. Also, the frame opening **521** may have a size less than that of the front panel **61** and greater than that of the rear panel **65**. Thus, when the transparent display assembly **60** is mounted, the rear panel **65** may successively pass through the plate opening **511** and the frame opening **521** and then be seated on the door linear **56**.

Also, the inner frame **52** may have a coupling structure with the outer plate **51**. Here, the outer plate **51** and an end of the transparent display assembly **60** may be mounted on the inner frame **52** in a state in which the outer plate **51** and the end of the transparent display assembly **60** are closely attached to each other.

Also, FIG. **8** is a partial perspective view illustrating an upper portion of the inner frame when viewed from a front side according to the first embodiment. Also, FIG. **9** is a partial perspective view of the upper portion of the inner frame when viewed from a rear side.

As illustrated in the drawings, the inner frame **52** has a rectangular frame shape, and the frame opening **521** is defined in the center of the inner frame **52**. Also, the inner frame **52** has a predetermined width to fix the outer plate **51** and also support the transparent display assembly **60**.

That is, the front surface of the inner frame **52** may have a portion coming into contact with the rear surface of the outer plate **51** and the other portion supporting a rear portion of the front panel **61** defining the front surface of the transparent display assembly **60**.

In detail, the inner frame **52** may include a plate support part **525**, a plate accommodation groove **526**, a front panel support part **528**, and a heater accommodation groove **529** as a whole.

The plate support part **525** may define the outermost portion of the inner frame **52** and have a flat front surface. Also, the plate support part **525** may be closely attached to the rear surface of the outer plate **51**. That is, a circumference of the outermost portion of the inner frame **52** may support the rear surface of the outer plate **51** and adhere to the rear surface of the outer plate **51** by an adhesion member **692** or a member for adhesion such as a double-sided tape.

The plate support part **525** may be disposed on all of an upper frame **522**, a lower frame **523**, and side frames **524**, which constitute the inner frame **52**, and be disposed along the circumference of the inner frame **52** to define an outer appearance of the inner frame **52**.

The plate accommodation groove **526** may be recessed from an end of the plate support part **525** and inserted into the opening bent part **514** that is bent along the opening of the outer plate **51**.

Thus, in a state in which the outer plate **51** adheres to the upper frame **522**, the opening bent part **514** may be in the state of being inserted into the plate accommodation groove **526**. Also, the opening bent part **514** may come into contact with the end of the transparent display assembly **60** in the state of being inserted into the plate accommodation groove **526** and thus be closely attached between the outer plate **51** and the front surface of the transparent display assembly **60** without generating a gap.

The plate accommodation groove **526** may be defined in the side frames **524** and the lower frame **523** except for the upper frame **522**. Also, the opening bent part **514**, which defines the upper end, of the plate opening **511** may be closely attached to an inner end of the upper frame **522** so that the whole of the opening bent part **514** of the outer plate **51** may be supported by the inner frame **52**.

Also, a guide rib **527** may be disposed on an end that connects the plate support part **525** to the bottom of the plate accommodation groove **526**. The guide rib **527** guides the opening bent part **514** so that the opening bent part **514** is maintained in an accurate position in the state in which the opening bent part **514**, which is inserted into the plate accommodation groove **526**, is inserted into the plate accommodation groove **526**.

The guide rib **527** may protrude to come into contact with an inner surface of the opening bent part **514** and extend to a direction that crosses perpendicular to the extension direction of the opening bent part **514**. A plurality of guide ribs **527** may be disposed adjacent to each other. As illustrated in the drawing, three guide ribs **527** may be successively disposed adjacent to each other. In this structure, the guide ribs **527** may be disposed at a predetermined interval to entirely support the opening bent part **514** along the circumference of the opening bent part **514**.

The guide rib **527** may extend from one side of the inner surface of the plate accommodation groove **526** to the bottom surface of the plate accommodation groove **526**. Also, the guide rib **527** may protrude more and more from a position that is close to the plate support part **525** to form an inclined part **527a** having inclination. Thus, when the opening bent part **514** is inserted into the plate accommodation groove **526**, the opening bent part **514** may be inserted along the inclined part **527a**.

Also, a vertical part **527b** may be disposed on an end of the inclined part **527a**. The vertical part **527b** may come into contact with the inner surface of the opening bent part **514** to support the opening bent part **514**. Thus, the opening bent part **514** may be supported by the vertical part **527b** in the state in which the opening bent part **514** is completely inserted into the plate accommodation groove **526**.

A front panel support part **528** may be disposed at an inner side of the plate accommodation groove **526**. The front panel support part **528** may support the rear surface of the front panel **61** that defines the front surface of the transparent display assembly **60**. The front panel support part **528** may be disposed at a rear side of the plate support part **525** and be stepped with respect to the plate support part **525**.

An adhesion member **693** such as a double-sided tape may be attached to a front surface of the front panel support part **528**, or an adhesive may be applied to the front surface of the front panel support part **528** to adhere to the rear surface of the front panel **61**. Here, a height difference between the front panel support part **528** and the plate support part **525** may correspond to a thickness of the front panel **61**. Thus, a stepped portion or a gap may not occur in the front surface of the sub door **50**. Also, an outer end of the transparent display assembly **60** and an end of the plate opening **511** of the outer plate **51** may be disposed on the same plane so that the entire front surface of the sub door **50** has a sense of unity without being stepped. Also, the front panel support part **528** may also be disposed along the side frames **524** and the lower frame **523** except for the upper frame **522**.

A heater accommodation groove **529** may be defined in the front panel support part **528**. The heater accommodation groove **529** may heat the circumference of the transparent display assembly **60** coming into the contact with the front panel support part **528** to prevent dew from being generated on the transparent display assembly **60** and be disposed along the front panel support part **528**.

The heater accommodation groove **529** may have a shape corresponding to that of a heater **532**. The heater accommodation groove **529** may completely accommodate the heater **532** so that the rear surface of the front panel **61** seated on the front panel support part **528** when the front panel **61** is mounted. Here, the heater **632** may come into contact with the rear surface of the front panel **61**.

As illustrated in FIGS. **8** and **9**, a frame barrier **520** may be disposed on an upper end of the upper frame **522**. The frame barrier **520** may partition the inside of the sub door **50**, which is provided above the upper frame **522**, into front and rear sides and extend from the rear surface of the upper frame **522** to the upper cap deco **54**.

In more detail, the frame barrier **520** may include an extension part **520a** extending backward from the rear surface of the upper frame **522** and a barrier part **520b** extending upward from an end of the extension part **520a**.

The extension part **520a** may extend from an inner end of the upper frame **522**, which define the frame opening **521**. The outer plate **51** may be away from the barrier part **520b** according to an extending length of the extension part **520a** to provide a space, in which an insulation material **531** is foamed and filled, between the outer plate **51** and the barrier part **520b**.

The barrier part **520b** may connect the extending end of the extension part **520a** to the bottom surface of the upper cap deco **54** to partition the upper end of the sub door **50** into front and rear portions. Thus, the front space of the barrier part **520b** may be an insulation space in which the insulation material **531** is provided. Also, PCBs for controlling the electric modules within the sub door **50** such as the transparent display assembly **60**, the door light **57**, and the heater **532** may be disposed in the rear space of the barrier part **520b**. The electric modules may include all of electric devices and components, which are provided in the door and further include a touch sensor **612** and a display light **68**.

An insertion rib **520c** that is inserted into a barrier coupling part **541e** disposed on the bottom surface of the upper cap deco **54** may protrude from the upper end of the barrier part **520b**. Thus, the barrier part **520b** may be maintained in the state of being firmly fixed by the coupling with the bottom surface of the upper cap deco **54** and allow the front portion and the rear portion of the upper portion of the sub door **50** to be completely partitioned from each other.

Also, a hinge avoiding part **520d** for avoiding an interference with a sub upper hinge **501** for the rotation of the sub door **50** may be further disposed on one end of the upper end of the barrier part **520b**. The hinge avoiding part **520d** may be disposed on one end of the barrier part **520d** and define a space protruding forward.

The PCB may be disposed in the upper space of the sub door **50**, i.e., disposed in a space between the front barrier **520** and the door linear **56**. As occasion demands, at least a portion of the upper cap deco **54** may be opened so that heat generated from the PCB is released to the outside of the sub door **50**.

FIG. **10** is a perspective view of the transparent display assembly according to the first embodiment. Also, FIG. **11** is an exploded perspective view of the transparent display assembly. Also, FIG. **12** is a cross-sectional view of the transparent display assembly.

As illustrated in the drawings, the transparent display assembly **60** may have a size that is enough to cover the plate opening **511** and the linear opening **561** inside the sub door **50**. Also, the see-through part **21** may be provided in the transparent display assembly **60** so that the inner space of the refrigerator is selectively seen, and a screen is outputted.

In more detail with respect to the transparent display assembly **60**, the transparent display assembly **60** may have an outer appearance that is defined by the front panel **61** and the rear panel **65**, which define the front and rear surfaces of the transparent display assembly **60**, and the module frame **67** connecting the front panel **61** to the rear panel **65**.

Also, a display **62** and a light guide plate **64** may be disposed between the front panel **61** and the rear panel **65**. In addition, a spacing rod **63** for supporting the display **62** and the light guide plate **64** may be further provided, and a display light **68** for emitting light to the light guide plate **64** may be provided.

In more detail, the front panel **61** may be made of a transparent glass material (e.g., blue glass) that defines an outer appearance of the front surface of the transparent display assembly **60**. The front panel **61** may be made of a different material through which the inside of the front panel **61** is seen, and a touch input is enabled.

The front panel **61** may have a size greater than that of the plate opening **511** and be supported by the inner frame **52**. That is, when the transparent display assembly **60** is assembled and mounted from the rear side, a circumferential portion of the front panel **61** may be supported by the rear surface of the inner frame **52**.

In detail, a front protrusion **613** that further protrudes outward than the rear panel may be disposed on the front panel **61**. The front protrusion may have a length greater than that of the rear panel **65** in all directions. Also, the front panel **61** defining the front surface of the transparent display assembly **60** may further extend outward from the plate opening **511** and then be stably fixed and mounted on the inner frame **52** due to characteristics of the transparent display assembly **60** mounted on at the rear side of the outer plate **51**.

Thus, when the transparent display assembly **60** is mounted, each of the extending ends of the front panel **61**,

i.e., the front protrusion **613** may be supported by the inner frame **52**, and thus, the transparent display assembly **60** may be stably maintained in the mounted state without being separated.

A bezel **611** may be disposed on a circumference of the rear surface of the front panel **61**. The bezel **611** may be printed with a black color and have a predetermined width so that the module frame **67** and the spacing rod **63** are covered without being exposed to the outside.

Also, the heater **532** may be disposed along the bezel **611**. Thus, the heater **532** may heat the circumference of the front panel **61** adjacent to the outer plate **51** while being covered by the bezel **611** without being exposed to the outside to prevent dew from being generated on the front surface of the front panel **61**.

A touch sensor **612** may be disposed on an inner area of the bezel **611**. The touch sensor **612** may be formed on the rear surface of the front panel **61** in a printing manner and be configured to detect user's touch manipulation of the front panel **61**. Alternatively, the touch sensor **612** may be formed in various manners such as a film adhesion manner, rather than the printing manner, so that the user touches the front panel **61** to perform the touch input.

A touch cable **601** connected to the touch sensor **612** may be disposed on the upper end of the front panel **61**. The touch cable **601** may be provided as a flexible film type cable such as a flexible flat cable (FFC) or a flexible print cable or flexible print circuit board (FPC). A printed circuit may be printed on the touch cable **601** to constitute at least a portion of a touch PCB **603**. Also, the touch cable **601** may be connected to the touch PCB **603** that will be described below in detail.

The display **62** may be disposed on the rear surface of the front panel **61**. The display **62** may be provided as an LCD module for outputting a screen. Also, the display **62** may be transparent so that the user sees the inside through the display **62** when the screen is not outputted.

A source board **621** may be disposed on one end of both left and right sides of the display **62**. The source board **621** may be configured to output a screen through the display **62** and provided as one assembly with the display **62**. Also, a portion of the source board **621** may include the flexible film type cable structure and extend upward along a side surface of the transparent display assembly **60** in the bent state.

Also, the source board **621** may have a width less than a thickness of the transparent display assembly **60** and be bent while the transparent display assembly **60** is assembled. Here, a position at which the source board **621** is disposed may be defined between the inside of the module frame **67** and the spacing rod **63** and come into contact with an inner surface of the module frame **67** in the bent state.

Also, the source board **621** may be connected to a display cable **605**. The display cable **605** may be connected to a T-CON board **623** at an upper portion of the sub door **50**.

In detail, when the source board **621** is disposed on the rear surface of the display **62**, the source board **621** may be exposed to the outside through the see-through part **21** due to the characteristics of the display **62** that is transparent. Also, when the source board **621** has a structure that protrudes laterally, the sub door **50** may increase in size.

Thus, the source board **621** may be disposed on an end of a circumferential side of the display **62** and bent to come into contact with the inner surface of the module frame **67** inside the module frame **67**. Also, the source board **621** may have a size corresponding to that of the module frame **67** without getting out of a region of the module frame **67** in a state of being closely attached to the module frame **67**.

The source board **621** may be constituted by two upper and lower boards **621** and respectively connected to the pair of display cables **605**. The display cable **605** may have a flexible and flat structure like the touch cable **601** and also have a structure that is freely bendable.

The display cable **605** may extend along the circumferential surface of the transparent display assembly **60** and pass through a sealant **691** defining the side surface of the transparent display assembly **60** to extend to the outside of the transparent display assembly **60**.

Also, the display cable **605** may be bent to extend along the circumferential surface of the transparent display assembly **60**, i.e., be bent so that an end thereof extends upward from the transparent display assembly **60**. Thus, the display cable **605** may be coupled to the T-CON board **602** at the upper side of the sub door **50**.

Both ends of the display **62** may be supported by the spacing rod **63**. The spacing rod **63** may have a rod shape that extending from an upper end to the lower end of the display **62** and be constituted by a first spacing rod **631** and a second spacing rod **632**.

The light guide plate **64** may be disposed at a rear side of the display and disposed to be spaced a predetermined distance from the display **62** by the first spacing rod **631** and the second spacing rod **632**. There may be a difference in depth feeling of the screen outputted from the display **62** according to the position of the light guide plate **64**.

Thus, the light guide plate **64** may be disposed further forward than an intermediate point between the front panel **61** and the rear panel **65** so that the screen outputted by the display **62** is felt closer to the front panel **61**. As a result, a height of each of the first spacing rod **631** and the second spacing rod **632** may be determined.

The light guide plate **64** may diffuse or scatter light emitted from the display light **68** and be made of various materials. For example, the light guide plate **64** may be made of a polymer material or formed by forming a pattern or attaching a film on a surface thereof. The light guide plate **64** may illuminate the display **62** from the rear side of the display **62** when the display light **68** is turned on. For this, the light guide plate **64** may have a plate shape having a size equal to or somewhat greater than that of the display **62**. The display light **68** may be disposed at a position corresponding to each of upper and lower ends of the light guide plate **64**.

The rear panel **65** may be disposed at a rear side of the light guide plate **64**. The rear panel **65** may define the rear surface of the transparent display assembly **60** and have a size greater than that of the light guide plate and less than that of the front panel **61**. Also, the rear panel **65** may have a size greater than that of the linear opening **561** to cover the linear opening **561**.

A circumference of the rear panel **65** may further protrude outward from the module frame **67** to provide a rear panel protrusion **651**. The rear panel protrusion **651** may be seated on the door linear **56** when the transparent display assembly **60** is mounted and provide a space in which a foaming solution is filled when the insulation material **531** is molded in the sub door **50**.

The rear panel **65** may be made of low- ϵ glass to realize thermal insulation. A low radiation coating layer may be formed on a surface of glass for general insulation to form the low- ϵ glass, and thus, the low- ϵ glass may have excellent thermal insulation. As a result, the rear panel **65** may prevent heat of cool air within the refrigerator from being transferred to the outside through the transparent display assembly **60**.

A spacer **66** may be disposed between the rear panel **65** and the light guide plate **64**. The spacer **66** may have a

rectangular frame shape disposed along a circumference of the light guide plate **64** and adhere to the light guide plate **64** and the rear panel **64** to maintain a predetermined distance between the light guide plate **64** and the rear panel **65**.

The distance between the front panel **61** and the light guide plate **64** may be maintained in fixed distance so as to output the screen of the display **62**. Also, the distance between the light guide plate **64** and the rear panel **65** may be determined according to a thickness of the sub door **50** or the total thickness of the transparent display assembly **60**. That is, the spacer **66** may be adjusted in thickness to determine the total thickness of the transparent display assembly **60** so as to be mounted to match a specification of the sub door **50**.

The rear panel **65** may come into contact with the door light **57**. Thus, a distance between the display **62** and the door light **57** may be determined according to the position of the rear panel **65**. The door light **57** may serve as an auxiliary backlight of the display **62** in the turn-on state.

In detail, a distance between the display **62** and the door light **58** may range from about 5 cm to about 15 cm. When the distance between the display **62** and the door light **57** is less than about 5 cm, a shade may occur. When the distance between the display **62** and the door light **57** exceeds about 5 cm, the door light may not serve as the backlight. Thus, to maintain the distance between the display **62** and the door light **57**, the rear panel **65** may also be maintained to be spaced a predetermined distance from the display **62**, and thus, the width of the spacer **66** may be determined.

A gap between the light guide plate **64** and the rear panel **65** may be sealed by the spacer **66**. Thus, a space between the spacer **66** and the light guide plate **64** may become to a vacuum state, or an insulative gas such as argon may be injected for the thermal insulation to more improve the thermal insulation performance.

In the state in which the rear panel **65** adheres to the spacer **66**, an outer end of the rear panel **65** may further extend outward from the spacer **66**. Also, the module frame **67** may be mounted on the outer end of the rear panel **65** so that the rear panel **65** and the front panel **61** are fixed to each other.

The module frame **67** may connect the rear surface of the front panel **61** to the front surface of the rear panel **65** and also define the circumferential surface of the transparent display assembly **60**. Also, a space in which the display light **68** is mounted may be provided in an inner surface of the module frame **67**.

The module frame **67** may have a rectangular frame shape. Also, the module frame **67** may have a size in which the light guide plate **64** and the spacing rod **63** are accommodated. Also, the display light **68** may be mounted on each of the upper and lower ends of the module frame **67**. The light guide plate **64** may be disposed between the display lights **68** disposed on the upper and lower ends of the module frame **67**.

Thus, light emitted through the display light **68** may be directed to an end of the light guide plate **64** and then travel along the light guide plate **64** so that the entire surface of the light guide plate **64** emits light.

The display lights **68** disposed on the inner upper and lower ends of the transparent display assembly **60** may be connected to a display light cable **606**. The display light cable **606** may have a flexible and flat shape like the touch cable **601** and the display cable **605**.

The display light cable **606** may be connected to the display light **68** that is mounted inside the module frame **67** to extend to the outside of the transparent display assembly **60** through the sealant **691**.

Also, the display light cable **606** may extend along the circumference of the transparent display **62** so that the display light cable **606** is not exposed through the transparent display **62**. Also, the display light cable **606** may extend upward in a state of being closely attached to the rear surface of the rear panel **65**. As occasion demands, the display light cable **606** may be bent in the state of adhering to the rear surface of the rear panel **65** and then may be connected to a docking PCB **604** disposed on the upper portion of the sub door **50**.

Here, since the display light cable **606** extends in the state of being closely attached to a rear surface of the rear protrusion **651** of the rear panel **65**, when the sub door **50** is viewed from the outside, the display light cable **606** may not be exposed through the transparent display assembly **60**.

The sealant **691** may be applied to the circumference of the module frame **67**. The sealant **691** may be applied to form the circumferential surface of the transparent display assembly **60**. That is, the sealant **691** may form a circumferential surface between the front panel **61** and the rear panel **65**.

The sealant **691** may seal the transparent display assembly **60** to prevent air from being introduced into the transparent display assembly **60** and be made of a polysulfide (that is called a thiokol) material. As occasion demands, the sealant **691** may be made of a different sealant material such as silicon or urethane so that the sealant **691** comes into direct contact with the foaming solution that is injected to mold the insulation material **531**.

The sealant **691** may maintain the coupling of the module frame **67**, the front panel **61**, and the rear panel **65** and completely seal the connected portions of the components to prevent water or moisture from being introduced. Also, the sealant **691** may be a portion, which comes into directly contact with the foaming solution when the insulation material **531** is molded, and protect the circumference of the transparent display assembly **60**.

Also, the sealant **691** may allow cables **601**, **605**, and **606** connected to the touch sensor **612**, the display panel **62**, and the display light **68** within the transparent display assembly **60** to be accessible therethrough. The sealant **691** may cover outer surfaces of the cables **601**, **605**, and **606** to prevent water or moisture from being introduced through spaces through which the cables **601**, **605**, and **606** are accessible when the cables **601**, **605**, and **606** extent through the circumferential surface of the transparent display assembly **60**.

FIG. 13 is an exploded perspective of a coupling structure between the cap deco and the PCB according to the first embodiment. Also, FIG. 14 is an exploded perspective view of the coupling structure between the cap deco and the PCB according to the first embodiment. Also, FIG. 15 is an exploded perspective view illustrating a structure in which the PCB is mounted on the sub door. Also, FIG. 16 is a cut-away perspective view illustrating an upper end of the sub door.

As illustrated in the drawings, the upper end of the sub door **50** may be defined by the upper cap deco **54**, and the upper cap deco **54** may be coupled to the upper end of the outer plate **51** and the upper end of the door linear **56**.

For this, a plate insertion part **540a** into which the upper end of the outer plate **51** is inserted may be defined in a circumference of a front surface of the upper cap deco **54**.

Also, a plate contact part **540b** coming into contact with the rear surface of the outer plate **51** may be disposed below the plate insertion part **540a**. Also, a closed space in which the insulation material **531** is provided may be defined by the plate contact part **540b** and the upper end of the front surface of the inner frame **52**.

A linear mounting part **540c** coupled to a cap deco insertion part **567** defined in the upper end of the door linear **56** may be disposed on a circumference of a rear surface of the upper cap deco **54**. The linear mounting part **540c** may have a shape that extends downward. A lower end of the linear mounting part **540c** may be inserted into the cap deco insertion part **567** so that the linear mounting part **540c** and the cap deco insertion part **567** are coupled to each other.

Also, the barrier coupling part **541e** may be disposed on the bottom surface of the upper cap deco **54**. The barrier coupling part **541e** may extend from one end to the other end of the upper cap deco **54** and be coupled to the insertion rib **520c** disposed on the upper end of the barrier part **520b**. Thus, the upper cap deco **54** and the barrier part **520b** may be coupled to each other to partition an inner upper space of the sub door **50** into front and rear spaces.

The insulation material **531** may be disposed in the front space partitioned by the barrier part **520b** to thermally insulate the sub door **50**. The PCBs **602**, **603**, and **604** may be disposed in the rear space partitioned by the barrier part **520b** to drive the plurality of electric modules provided in the sub door **50** in addition to the transparent display assembly **60**.

Also, a deco opening **542** may be defined in a top surface of the upper cap deco **54**, and a deco cover **543** may be disposed on the deco opening **542**. The deco opening **542** may communicate with the rear space, which is defined by the barrier part **520b**, of the upper cap deco **54**. Thus, the deco cover **543** may be separated to open the space in which the PCBs **602**, **603**, and **604** are mounted.

The deco cover **543** may be detachably disposed on the upper cap deco **54**, and the PCBs **602**, **603**, and **604** for driving the transparent display assembly **60** may be mounted on the deco cover **543**. Thus, after the sub door **50** is foamed, the PCBs **602**, **603**, and **604** may be mounted on the deco cover **543**, and then the PCBs **602**, **603**, and **604** may be inserted and mounted through the deco opening **542**.

In detail, the deco cover **543** may be constituted by a cover part **544** covering the deco opening **542** and a PCB mounting part **545** on which the PCBs **602**, **603**, and **604** are mounted. The cover part **544** may have a shape corresponding to the deco opening **542**. Also, a screw hole **544a** may be defined in each of both sides of the cover part **544**, and then, a coupling member such as a screw may be coupled in the state in which the upper cap deco **54** is mounted so that the cover part covers the deco opening **542**.

A wire hole **541b** may be defined in one side of the deco cover **543**, i.e., in a wall of one side of the hinge mounting part **541**. The wire hole **541b** may be defined in one side of the PCB mounting part **545** to communicate with the space, in which the PCBs **602**, **603**, and **604** are disposed, of the spaces partitioned by the barrier part **520b**.

The wire hole **541b** may have a size through which the connection cable **607** connected to the control unit **14** is accessible and be introduced into the cabinet **10** along the upper hinge **401** or the cover covering the upper hinge **401**. Thus, even when the sub door **50** is opened or closed, the connection cable **607** may pass through the sub door **50** and the cabinet **10** without interference.

The connection cable **607** may be a wire type cable and have a structure in which the connection cable **607** easily

passes through the wire hole **541b**. Also, the connection cable **607** may be provided in plurality. Here, the plurality of connection cables **607** may be protected by a cable cover **607a** accommodating the plurality of connection cables **607**. The cable cover **608a** may be provided as a shrinkable tube or a tape. Also, the plurality of connection cables **607** may be accessed through the wire hole **541b** in a state in which the plurality of connection cables **607** are bundled as one unit to prevent the bundle of the connection cables **607** from interfering with the cable cover **607a**.

The plurality of PCBs **602**, **603**, and **604** may be connected to the cables **601**, **605**, and **606** exposed within the deco cover **543** before the deco cover **543** is mounted on the deco opening **542**. In detail, in the state in which the plurality of PCBs **602**, **603**, and **604** are mounted on the PCB mounting part **545**, the cables **601**, **605**, and **606** may be respectively connected to the PCBs **602**, **603**, and **604**. The connection cable **607** introduced through the wire hole **541b** may also be connected to the docking PCB **604** and the T-CON board, which will be described below in detail. In the state in which the connection of the cables **601**, **605**, and **606** are completed, the deco cover **543** may be mounted on the upper cap deco **54** to cover the deco opening **542**.

Also, a cover support part **542a** may be further disposed on each of both ends of the deco opening **542** to support both ends of the deco cover **543**. The coupling member such as the screw may be coupled to the cover support part **542a**.

The PCB mounting part **545** may extend downward from a bottom surface of the cover part **544**. A front surface of the PCB mounting part **545**, which faces the barrier part **520b**, may have a flat shape, and the plurality of PCBs may be mounted on a rear surface of the PCB mounting part **545**, which faces the door linear **56**. As occasion demands, the plurality of PCBs **602**, **603**, and **604** may be disposed on both the front and rear surfaces of the PCB mounting part **545** so that all of the plurality of PCBs **602**, **603**, and **604** are disposed in the massed space.

The PCBs mounted on the PCB mounting part **545** may include the T-CON board **602**, the touch PCB **603**, and the docking PCB **604**. The T-CON board **602** may include a display cable **605** for driving the display **62**. The touch PCB **603** may process a touch input signal of the touch sensor **612** and include a touch cable **601** connected to the touch sensor **612**. The docking PCB **604** may connect the cables **601**, **605**, and **606** connected to the PCBs **602**, **603**, and **604** to the connection cable **607** connected to the control unit **14** to guide the connection cable **607** that is a single or a lesser number of wire cables, in which the plurality of flat cables **601**, **605**, and **606** are integrated with each other, to the outside of the sub door **50**.

FIG. **17** is a partial perspective view illustrating a connection structure between the cables and the PCBs of the transparent display assembly. Also, FIG. **18** is a plan view illustrating an arrangement of the cable connecting the sub door to the control unit. Also, FIG. **19** is a block diagram illustrating a flow of a control signal of the refrigerator.

As illustrated in the drawings, the deco cover **543** may be disposed on the upper portion of the sub door **50**, and the plurality of PCBs **602**, **603**, and **604**, i.e., the touch PCB **603**, the T-CON board **602**, and the docking PCB **604** may be mounted on the PCB mounting part **545** of the deco cover **543**. Also, the plurality of PCBs **602**, **603**, and **604** may be connected to the plurality of cables **601**, **605**, and **606** within the sub door **50**.

The cables **601**, **605**, and **606** connecting the plurality of cables **602**, **603**, and **604** to each other may be provided as the flexible film type FFC or FPC. Thus, the touch cable **601**,

the display cable **605**, and the display light cable **606** may occupy a large space within the sub door **50** and be disposed to be closely attached to each other along the outside of the transparent display assembly **60**. Also, the connection structure with the PCBs **602**, **603**, and **604** may also be simply provided and may not be exposed to the outside through the see-through part **21**. In addition, when the insulation material **531** is foamed to be molded in the sub door **50**, the PCBs **602**, **603**, and **604** may not interfere with the insulation material **531**.

In more detail, the touch cable **601** may extend from an upper end of the touch sensor **612** and then be connected to the touch PCB **603**. The touch PCB **603** may be disposed at a position corresponding to the extending end of the touch cable **601**. A touch connector **603a** into which the extending end of the touch cable **601** is inserted may be disposed on the touch PCB **603**. The touch cable **601** may have a flat shape, and the extending end of the touch cable **601** may be bent to be inserted into the touch connector **603a**. Thus, the touch cable **601** may be easily inserted into the touch connector **603a** and have a structure that is connected to the touch PCB **603**.

The display cable **605** may be connected to the source board **621** to extend upward. Then, the display cable **605** may extend along the circumference of the side surface of the transparent display assembly **60** and then be connected to the T-CON board **602**. Also, the display connector **602a** disposed at the position corresponding to the end of the display cable **605** may be disposed on the T-CON board **602**. Thus, the end of the display cable **604** having the flat cable shape may be inserted into the display connector **602a** and connected to the T-CON board **602**.

The display light cable **606** may be connected to the display light **68** disposed on each of the upper and lower portions of the transparent display assembly **60** to extend upward along the outer circumference of the transparent display assembly **60** and then be connected to the docking PCB **604**. The display light cable **606** may also have a flat cable shape and be inserted into a display light connector **604a** disposed on the docking PCB **604** to connect the docking PCB **604** to the display light cable **606**.

The door light connector **604b** may be disposed on the docking PCB **604**. The door light connector **604b** may be connected to an end of the door light cable **609** extending from the door light **57**. The door light **57** may be provided as a separate part with respect to the transparent display assembly **60** and mounted on the door linear **56**. Thus, the door light cable **609** connected to the door light **57** may extend to the docking PCB **604** without passing through the transparent display assembly **60** and be provided as a wire type cable. The door light cable **609** may also be provided as a flat and flexible cable like other cables **601**, **605**, and **606**.

The docking PCB **604** may be connected to the touch PCB **603**. The docking PCB **604** and the touch PCB **603** may be provided as separate parts. Thus, while the docking PCB **604** and the touch PCB **603** are assembled and mounted on the PCB mounting part **545**, the docking PCB **604** and the touch PCB **603** may be connected to each other through a first docking cable **608**. The first docking cable **608** may be connected to a PCB connector **604d** disposed on the docking PCB **604**. Also, as occasion demands, the T-CON board **602** may also be connected to the docking PCB **604**.

Also, in consideration of efficiency of a voltage situation or signal transmission, the T-CON board **602** may not be connected to the docking PCB **604**, but the wire type

connection cable **607** may be directly connected to the control unit **14** through the wire hole **541b**.

Also, a connection connector **604c** connected to the wire type connection cable **607** may be further disposed on the docking PCB **604**. Since the connection connector **604c** is connected to the docking PCB **604**, the flat type cables **601**, **605**, and **606** may be connected to the display PCB **142** within the control unit **14** through the connection cable **607**. Since the connection connector **604c** is connected to the connection cable **607** that is accessed to the outside of the sub door, the connection connector **604c** may be called a lead-in connector. Also, other PCBs **602** and **603** disposed on the docking PCB **604** except for the connection connector **604c** or the connectors **604a**, **604b**, and **604d**, to which the cables **605**, **606**, **608**, and **609** connected to the electric modules are connected, may also be called lead-in connectors.

The connection cable **607** may be accessible through the wire hole **541b** defined in the upper cap deco **54** and pass through the upper hinge **401** or the cover covering the upper hinge **401** to be led to the control unit **14**. Here, the connection cable **607** may not be exposed to the outside and extend to the control unit **14** through the inside of the cabinet **10** and then be connected to the display PCB **142** on the control unit **14**.

As described above, the plurality of electric modules disposed on the sub door **50**, i.e., all of the plurality of flat cables **601**, **605**, and **606** connected to the electric modules constituting the transparent display assembly **60** may be connected to the PCBs **602**, **603**, and **604** in the upper portion of the sub door **50**, and the wire type connection cable **607** extending from the control unit **14** on the cabinet **10** may be simply connected to the docking PCB **604** and the T-CON board **602** to minimize the size of the wire hole **541b** and also minimize the interference when the sub door **50** is opened or closed.

That is, each of the plurality of cables **601**, **605**, and **606** connected to the PCBs **602**, **603**, and **604** may have a very large width, and thus, the wire hole **541b** for guiding the plurality of cables **601**, **605**, and **606** to the outside of the sub door **50** may be vary large to deteriorate the efficiency and the outer appearance. Also, the plurality of cables **601**, **605**, and **606** may be damaged by the interference due to the structural characteristics of the sub door **50** that is opened and closed by the rotation thereof or may be damaged by the exposure to the outside. Thus, the wire type connection cable **607** having a small volume and superior durability may be substantially used as the cable connecting the sub door **50** to the cabinet **10**. Also, the number of connection cables **607** may be minimized to reduce the volume and space for guiding the connection cable **607**.

A main PCB **141**, a display PCB **142**, and an adaptor **143** may be disposed in the control unit **14** connected by the connection cable **607**.

The overall operation of the refrigerator **1** as well as a refrigerating cycle may be controlled by the main PCB **141**. The main PCB **141** may be connected to the display PCB **142** to receive operation information of the transparent display assembly **60**.

Also, a camera **145** for photographing the inside of the refrigerator **1** so as to utilize image information may be connected to the main PCB **141**. Also, a speaker **146** for outputting a voice may be connected to the main PCB **141**. A separate communication module **147** for communication with an external device and a server may be connected to the main PCB **141**. The communication module **147** may be

directly or indirectly connected to the main PCB **141**, the display PCB **142**, the speaker **146**, and the camera **145** to transmit the information.

Also, the adaptor **143** for converting power supplied to the transparent display assembly **60** may be further disposed on the control unit **14**. DC power may be converted into AC power that is suitable for driving the transparent display assembly **60** by the adaptor **143**. Also, since the adaptor **143** has a relatively large size and generate large amount of heat, it may be more efficient when the adaptor **143** is disposed on the control unit **14** on the cabinet **10** rather than the sub door **50**.

FIGS. **20** and **21** are block diagrams illustrating a different connection state of the connection cable connected to the control unit.

As illustrated in the drawings, the connection cable **607** may have various connection structures in addition to the above-described structure. The connection cable **607** may be provided in plurality so that the display PCB **142** on the cabinet **10** and the electric module or the PCBs **602**, **603**, and **604** on the sub door **50** are connected to each other through the wire type connection cables **607**.

In detail, as illustrated in FIG. **20**, the touch PCB **603** may be connected to the docking PCB **604** by the first docking cable **608**, and the T-CON board **602** may be connected to the docking PCB **604** by a second docking cable **602b**. Also, the display light **68** may be connected to the docking PCB **604** by the display light cable **606**.

Also, the connection cable **607** may connect the docking PCB **604** to the display PCB **142**, and the door light **57** on the sub door **50** may be directly connected to the display PCB **142** by the door light cable **609**.

Here, the door light cable **609** may be provided as a wire cable like the connection cable **607**. When a relatively high voltage is required for secure a sufficient light amount, as illustrated in FIG. **20**, the door light cable **609** may be directly connected to the display PCB **142** without via the docking PCB **604**.

Also, as illustrated in FIG. **21**, the touch PCB **603** may be connected by the first docking cable **608**, and the T-CON board **602** may be connected by a second docking cable **602b**. Also, the display light **68** may be connected by the display light cable **606**, and the door light **57** may be connected to the docking PCB **604** by the door light cable **609**.

That is, all of the electric modules within the sub door **50** may be connected to the docking PCB **604** inside the sub door **50** by the plurality of cables **602b**, **606**, **608**, and **609**, and the docking PCB **604** may be connected to the transparent display assembly **60** by the one connection cable **607**. Thus, the number of cables passing through the sub door **50** may be minimized to minimize the number of cables exposed through the sub door **50**.

Hereinafter, turn-on/off states of the display light and the door light will be described in more detail with reference to the accompanying drawings.

FIG. **22** is a transverse cross-sectional view of the main door and the sub door. Also, FIG. **23** is a longitudinal cross-sectional view of the main door and the sub door. Also, FIG. **24** is a view illustrating a state in which the inside of the refrigerator is seen through the transparent display assembly. Also, FIG. **25** is a view illustrating a state in which a screen is outputted through the transparent display assembly.

As illustrated in the drawings, in a state in which a latch **592** of the opening device **59** is inserted into a latch hole **421** of the locking unit **42**, the sub door **50** may be maintained

in a closes state. In this state, the door light **57** may be maintained in a turn-off state. An opened or closed state of the sub door **50** may be detected through a door switch that is separately provided.

In the turn-off state of the door light **57**, as illustrated in FIG. **1**, the rear space of the sub door **50** may be dark, and thus, the inside of the refrigerator **1** may not be seen through the see-through part **21**. Thus, in the closed state of the sub door **50**, if separate manipulation is not performed, the door light **57** may be maintained in the turn-off state, and the inside of the refrigerator **1** may not be seen through the see-through part **21**.

In this state, the user may manipulate the front panel to turn on the door light **57**. When the door light **57** is turned on, light emitted from a lighting module may be emitted to positions of both rear left and right sides of the rear panel **65**, which face each other.

The door light **57** may extend from the upper end to the lower end of the rear panel **65**. That is, the light emitted by the door light **57** may illuminate the entire rear region of the rear panel **65** from both the left and right sides of the rear panel **65**.

Here, when the display light **68** is in the turn-on state together with the door light **57**, light may be emitted upward and downward by the display light **68**, and thus the light may be emitted from left and right sides by the door light **57**. As a result, the light may be emitted to the see-through part **21** in all directions to maximally brighten up an area of the see-through part **21**.

The door light **57** may emit light in directions facing each other in a state of being close to the rear panel **65**. The light emitted by the door light **57** may brighten up an inner case of the accommodation case **43** and also brighten up the front region over the rear panel **65**. Thus, as illustrated in FIG. **22**, the door light **57** may serve as a lighting for brightening up the inner space of the refrigerator **1**, which is seen through the see-through part **21** and also serve as an auxiliary backlight for allow the display **62** to be more clearly displayed.

That is, in a state in which a screen is being outputted through the display **62**, the inner space of the refrigerator **1**, i.e., the rear space of the sub door **50** may be selectively seen through the see-through part **21**. To allow the rear space of the sub door **50** to be seen through the see-through part **21**, the door light **57** may be turned on.

A turn on/off combination of the display light **68** and the door light **57** may be variously realized according to a degree of seeing of the inside of the accommodation case **43** through the see-through part **21**.

Also, when the user manipulates the front panel **61** disposed on the front surface of the refrigerator **1**, the display light **68** may be turned on to turn on the display **62**. Thus, the transparent display assembly **60** may output a screen as illustrated in FIG. **23**. Here, the manipulation of the front panel **61** may be inputted as one of a specific position, the touch number, or a pattern. As occasion demands, a separate physical button or sensor may be used to detect the user's manipulation.

A screen for displaying a state of the refrigerator **1** and manipulating may be outputted on the display **62**. Here, various screens for information with respect to accommodated foods may be outputted by using Internet, image output external input devices, or the like.

In detail, the display light **69** disposed on each of the upper and lower ends of the light guide plate **64** may be turned on together with the display **62** by the user's manipulation. The light guide plate **64** may irregularly reflect and

diffuse light of the display light 68 by the turn-on of the display light 68 to emit light having generally uniform brightness to the front display 62.

Also, light may be emitted to the display 62 from the rear side of the display 62 by the light guide plate 64, and simultaneously, a screen based on inputted image information may be outputted on the display 62. Thus, the user may confirm the clearly outputted screen through the see-through part 21.

In addition to the foregoing embodiment, a refrigerator according to various embodiments may be exemplified.

Since the second embodiment is the same as the first embodiment except for positions of a deco cover and a PCB, the same constituent as that according to the foregoing embodiment may be denoted by the same reference numeral, and its detailed description will be omitted. Also, it is to be noted in advance that the reference numerals which are not shown are also the same as the abovementioned embodiment.

FIG. 26 is an exploded perspective view of a door according to a second embodiment.

A door according to a second embodiment has an outer appearance defined by an outer case 51, and the outer case 51 may have an opened front surface. Also, the opening of the outer case 51 may be covered by a transparent display assembly 60. The transparent display assembly 60 may be selectively transparent to allow a user to selectively see the inside of the refrigerator 1 and also enable a touch input by user's manipulation and output an image through a display 62.

An upper cap deco 54 defining a top surface of the door 50 and a lower cap deco 55 defining a bottom surface of the door 50 may be disposed on upper and lower ends of the door 50, respectively. An insulation material may be disposed on a circumference of the transparent display assembly 60 to fix the transparent display assembly 60 and thermally insulate a circumference of the door 50.

Also, a deco opening 551 that is opened to the inside of the door 50 may be defined in the lower cap deco 55. The deco opening 551 may be covered by a deco cover 552. The lower end of the transparent display assembly 60 may be exposed through the deco opening 551, and cables 601, 605, and 606 connected to electric modules of the transparent display assembly 60 may be exposed downward through the deco opening. The cables 601, 605, and 606 may be closely attached to the circumference of the transparent display assembly 60 to extend downward.

Also, a PCB mounting part 553 extending upward and inserted into the deco opening 551 may be disposed on the deco cover 552, and a plurality of PCBs 602, 603, and 604 may be mounted on the PCB mounting part 553. The PCBs 602, 603, and 604 may include a touch PCB 603 connected to the touch cable 601, a T-CON board 602 connected to the display cable 605, and a docking PCB 604 connected to the display light cable 606.

A wire cable type connection cable 607, which is introduced through a hinge mounting part 541, may be connected to the docking PCB 604 that is directly or indirectly connected to the plurality of flat cable type cables 601, 605, and 606.

Thus, the plurality of cables 601, 605, and 606 connected to the electric modules of the door 50 or the transparent display assembly 60 may be connected to the docking PCB 604 to extend to a main body 10 through one or several connection cables 607 and thus be connected to a control unit 14 of the main body.

Although the sub door 50 according to the first embodiment is described as an example of a door 50 according to the second embodiment for convenience of description and understanding, the door 50 may be equally applied to the door 20 for directly opening and closing the inner space of the refrigerator.

A refrigerator according to various other embodiments in addition to the abovementioned embodiments may be exemplified.

Since a third embodiment is the same as the abovementioned embodiments except for a position at which a PCB is mounted, the same constituent as those according to the foregoing embodiments may be denoted by the same reference numeral, and its detailed description will be omitted. Also, it is to be noted in advance that the reference numerals which are not shown are also the same as the abovementioned embodiments.

FIG. 27 is an exploded perspective view of a door according to a third embodiment.

As illustrated in the drawings, a door 50 according to a third embodiment may have an outer appearance of a front surface, which is defined by an outer case 51, and an outer appearance of a rear surface, which is defined by a door linear 56. Also, an area of a central portion of the outer case 51 and the door linear 56 may be mostly opened, and a transparent display assembly 60 may be disposed between the outer case 51 and the door linear 56.

The transparent display assembly 60 may be selectively transparent to allow a user to selectively see the inside of a refrigerator and also enable a touch input by user's manipulation and output an image through a display 62.

An upper cap deco 54 defining a top surface of the door 50 and a lower cap deco 55 defining a bottom surface of the door 50 may be disposed on upper and lower ends of the door 50, respectively. An insulation material may be disposed on a circumference of the transparent display assembly 60 to fix the transparent display assembly 60 and thermally insulate a circumference of the door 50.

A linear mounting hole 562 may be defined in one side of the rear surface of the door linear 56. In detail, the linear mounting hole 562 may be defined at a position coming into contact with a position corresponding to a hinge mounting part 541 of the upper cap deco 54 and disposed at one side of the transparent display assembly 60.

The linear mounting hole 562 may be configured to expose one side of the transparent display assembly 60 and configured to expose flat type cables 601, 605, and 606 connected to eclectic modules of the transparent display assembly 60. The cables 601, 605, and 606 may be closely attached to a circumference of the transparent display assembly 60 to extend up to the linear mounting hole 562.

Also, a plurality of PCBs 602, 603, and 604 connected to the cables 601, 605, and 606 may be accommodated in the linear mounting hole 562. Also, in the state in which the plurality of PCBs 602, 603, and 604 are mounted inside the linear mounting hole 562, the linear mounting hole 562 may be covered by a linear cover 563.

The PCBs 602, 603, and 604 may include a touch PCB 603 connected to the touch cable 601, a T-CON board 602 connected to the display cable 605, and a docking PCB 604 connected to the display light cable 606.

A wire cable type connection cable 607, which is introduced through a hinge mounting part 541, may be connected to the docking PCB 604 that is directly or indirectly connected to the plurality of flat cable type cables 601, 605, and 606.

Thus, the plurality of cables **601**, **605**, and **606** connected to the electric modules of the door **50** or the transparent display assembly **60** may be connected to the docking PCB **604** to extend to a main body **10** through one or several connection cables **607** and thus be connected to a control unit **14** of the main body.

Although the sub door **50** according to the first embodiment is described as an example of a door **50** according to the third embodiment for convenience of description and understanding, the door **50** may be equally applied to the door **20** for directly opening and closing the inner space of the refrigerator.

A refrigerator according to various other embodiments in addition to the abovementioned embodiments may be exemplified.

Since the fourth embodiment is the same as the abovementioned embodiments except that a PCB connected to a flat cable is provided as a single part and is different in constituent, the same constituent as those according to the foregoing embodiments may be denoted by the same reference numeral, and its detailed description will be omitted. Also, it is to be noted in advance that the reference numerals which are not shown are also the same as the abovementioned embodiments.

FIG. **28** is an exploded perspective view of a door according to a fourth embodiment. Also, FIG. **29** is a block diagram illustrating a flow of a control signal in a refrigerator according to the fourth embodiment.

As illustrated in the drawings, a door **50** according to a fourth embodiment may have an outer appearance of a front surface, which is defined by an outer case **51**, and an outer appearance of a rear surface, which is defined by a door linear **56**. Also, an area of a central portion of the outer case **51** and the door linear **56** may be mostly opened, and a transparent display assembly **60** may be disposed between the outer case **51** and the door linear **56**.

The transparent display assembly **60** may be selectively transparent to allow a user to selectively see the inside of a refrigerator and also enable a touch input by user's manipulation and output an image through a display **62**.

An upper cap deco **54** defining a top surface of the door **50** and a lower cap deco **55** defining a bottom surface of the door **50** may be disposed on upper and lower ends of the door **50**, respectively. An insulation material may be disposed on a circumference of the transparent display assembly **60** to fix the transparent display assembly **60** and thermally insulate a circumference of the door **50**.

A deco opening **542** may be defined in the upper cap deco **54**, and flat cable type cables **601**, **605**, and **606** connected to electric modules of the transparent display assembly **60** may be disposed inside the deco opening **542**. Also, the deco opening **542** may be opened and closed by the deco cover **543**. The cables **601**, **605**, and **606** may be closely attached to the circumference of the transparent display assembly **60** to extend upward.

A PCB mounting part **545** extending downward may be disposed on a bottom surface of the deco cover **543**, and a door PCB **546** may be mounted on the PCB mounting part **545**. The door PCB **546** may be connected to the plurality of cables **601**, **605**, and **606**. In the state in which the door PCB **546** and the cables **601**, **605**, and **606** are connected to each other, the deco cover **543** may cover the deco opening **542**.

The door PCB **546** may control the whole electric modules within the door **50**. Thus, the door light **57** as well as the electric modules of the transparent display assembly **60** may also be connected to the door PCB **546**.

The door PCB **546** may be connected to at least one of the touch cable **601** connected to the touch sensor **612**, the display cable **605** connected to a source board **621** of the display **62**, and the display light cable **606** connected to the display light **68**. That is, all of the plurality of flat cable type cables **601**, **605**, and **606** may be connected to one door PCB **546**.

Also, a connection cable **607** may be connected to the door PCB **546**. The connection cable **607** may have a wire shape and pass through a hinge mounting part **541** of the upper cap deco **54** and thus be guided to the outside. Also, the connection cable **607** may extend to a cabinet **10** via an upper hinge and be connected to a display PCB **142** provided in the cabinet **10**.

A refrigerator according to various other embodiments in addition to the abovementioned embodiments may be exemplified.

A fifth embodiment is characterized by a structure in which a connection cable connected to a PCB within a sub door is guided to the outside of the door through a hinge shaft of a sub upper hinge. In the current embodiment, the same constituent as those of the abovementioned embodiments will be denoted by the same reference numeral, and its detailed description will be omitted. Also, it is to be noted in advance that the reference numerals which are not shown are also the same as the abovementioned embodiments. FIG. **30** is a partial perspective view illustrating an arrangement of a wire of a door according to a fifth embodiment.

As illustrated in the drawing, in a refrigerator **1** according to a fifth embodiment, a main door **40** is mounted to be rotatable by an upper hinge **401** on a front surface of a cabinet **10**. Also, a sub door **50** is mounted to be rotatable by a sub upper hinge **501** on a front surface of the main door **40**.

A deco opening **542** communicating with an upper space of the sub door **50**, in which PCBs **602**, **603**, and **604** are mounted, may be defined in an upper cap deco **54** defining a top surface of the sub door **50**. The deco opening **542** may be covered by a deco cover **543**. Also, the PCBs **602**, **603**, and **604** may be mounted on the deco cover **543** like the abovementioned first embodiment, and electric modules of a transparent display assembly **60** may be connected to the PCBs **602**, **603**, and **604** by flat cable type cables **601**, **605**, and **606**. An arrangement of the PCBs **602**, **603**, and **604** and the cables **601**, **605**, and **606** and a structure of the sub door **50** are the same as those according to the first embodiment, and thus their detailed descriptions will be omitted.

A wire cable type connection cable **607** connected to the docking PCB **604** of the PCBs **602**, **603**, and **604** may be guided to the outside of the hinge mounting part **541** through the hinge shaft **501a** of the sub upper hinge **501**.

That is, the hinge shaft **501a** of the sub upper hinge **501** may have a hollow tube shape or a tube shape that is cut in a "C" shape in cross-section. Thus, the connection cable **607** connected to the docking PCB **604** at a lower side of the upper cap deco **54** may be guided to the outside of the sub door **50** by passing through the hollow of the hinge shaft **501a**.

The sub upper hinge **501** may be covered by a sub hinge cover **505**, and the upper hinge **401** may be covered by a main hinge cover **403**. Also, a sub extension part **505a** and a main extension part **403a** may be disposed on the sub hinge cover **505** and the main hinge cover **403**, respectively.

The main extension part **403a** may extend upward from a rotation axis of the upper hinge **401** at one side of the main hinge cover **403** and have a top surface in which a cover hole **403b**, through which the connection cable **607** passes, is defined. Also, the sub extension part **505a** may extend to an

upper side of the main extension part **403a** to overlap the main extension part **403a**, and a space may be defined in the sub extension part **505a** to accommodate the connection cable **607**. Also, the sub extension part **505a** may cover a top surface of the main extension part **403a**. When the main door **40** rotates, the main door **40** may rotate above the main extension part **403a**.

Thus, the connection cable **607** may pass through the hinge shaft **501a** of the sub upper hinge **501** and then be guided to the hinge mounting part **541**. Then, the connection cable **607** may pass through the sub extension part **505a** of the sub hinge cover **505** to pass through the cover hole **403b** and then be guided to the cabinet **10** through the main extension part **403a** of the main hinge cover **403**. According to the above-described structure, the connection cable **607** may be covered without exposed to the outside from the docking PCB **604** to the cabinet **10**. Also, when the sub door **50** and the main door **40** rotates, the connection cable **607** may not be exposed to the outside or may not interfere.

A refrigerator according to various other embodiments in addition to the abovementioned embodiments may be exemplified.

A sixth embodiment is characterized by a structure in which an upper or lower space of a door is partitioned into a space in which an insulation material is disposed and a space in which a PCB is disposed so that the PCB is mounted on an upper or lower portion of the door after foaming. In the current embodiment, the same constituent as those of the abovementioned embodiments will be denoted by the same reference numeral, and its detailed description will be omitted.

FIG. **31** is a partial exploded perspective view of a door according to a sixth embodiment. Also, FIG. **32** is a cross-sectional view of the door according to the sixth embodiment.

As illustrated in the drawings, a door **50** of a refrigerator **1** according to a sixth embodiment may have an outer appearance of a front surface, which is defined by an outer case **51**, and an outer appearance of a rear surface, which is defined by a door linear **56**. Also, an area of a central portion of the outer case **51** and the door linear **56** may be mostly opened, and a transparent display assembly **60** may be disposed between the outer case **51** and the door linear **56**.

The transparent display assembly **60** may be selectively transparent to allow a user to selectively see the inside of a refrigerator and also enable a touch input by user's manipulation and output an image through a display **62**.

An upper cap deco **54** defining a top surface of the door **50** and a lower cap deco **55** defining a bottom surface of the door **50** may be disposed on upper and lower ends of the door **50**, respectively. An insulation material may be disposed on a circumference of the transparent display assembly **60** to fix the transparent display assembly **60** and thermally insulate a circumference of the door **50**.

A deco opening **542** may be defined in the upper cap deco **54**, and the flat cable type cables **601**, **605**, and **606** connected to electric modules of the transparent display assembly **60** may be disposed inside the deco opening **542**. Also, the deco opening **542** may be opened and closed by the deco cover **543**. The cables **601**, **605**, and **606** may be closely attached to the circumference of the transparent display assembly **60** to extend upward.

A PCB mounting part **545** extending downward may be disposed on a bottom surface of the deco cover **543**, and the PCBs **602**, **603**, and **604** may be mounted on the PCB mounting part **545**. The PCBs **602**, **603**, and **604** may be connected to the plurality of cables **601**, **605**, and **606**. In the

state in which the PCBs **602**, **603**, and **604** and the cables **601**, **605**, and **606** are connected to each other, the deco cover **543** may cover the deco opening **542**.

The PCBs **602**, **603**, and **604** may control the whole electric modules within the door **50**. Thus, the door light **57** as well as the electric modules of the transparent display assembly **60** may also be connected to the PCBs **602**, **603**, and **604**.

The PCBs **602**, **603**, and **604** may be constituted by a touch PCB **603**, a T-CON board **602**, and a docking PCB **604**. The touch PCB **603** may be connected by the touch cable **601** connected to the touch sensor **612**, the T-CON board **602** may be connected by the display cable **605** connected to a source board **621** of the display **62**, and the docking PCB **604** may be connected by the display light cable **606** connected to the display light **68**.

The docking PCB **604** may be connected to at least one of the touch PCB **603** and the T-CON board **602**. Also, the docking PCB **604** may be connected to a connection cable **607**. The connection cable **607** may have a wire shape and pass through a hinge mounting part **541** of the upper cap deco **54** and thus be guided to the outside. Also, the connection cable **607** may extend to a cabinet **10** via an upper hinge and be connected to a display PCB **142** provided in the cabinet **10**.

An inner frame **52** may be disposed on the rear surface of the outer plate **51**. The inner frame **52** may be disposed along a circumference of a plate opening **511** of the outer plate **51**, and a rear surface of the inner frame **52** may support the circumference of the plate opening **511** and a circumference of a front panel **61** of the transparent display assembly **60**.

That is, the inner frame **52** may have a rectangular frame shape and adhere to the circumference of the plate opening **511** and a rear surface of a front protrusion **613**, which protrudes outward, of the front panel **61** by using an adhesion member **693** such as a double-sided tape or an adhesive. Thus, the transparent display assembly **60** may be mounted without being stepped with respect to a front surface of the outer plate **51** by the inner frame **52**.

A barrier **520e** extending upward may be disposed on an upper end of the inner frame **52**. The barrier **520e** may be provided in a pair on both left and right sides and extend from the upper end of the inner frame **52** up to a bottom surface of the upper cap deco **54**. The barrier **520e** may partition an upper portion of the door **50** into both left and right sides, i.e., a space in which a foaming solution is filled to form the insulation material **531** and a space in which the PCBs **602**, **603**, and **604** are accommodated between the pair of barriers **520e**.

Thus, the PCBs **602**, **603**, and **604** may be accommodated into the space defined between the pair of barriers **520e**. Also, in the space defined between the pair of barriers **520e**, the insulation material **531** may not be provided because the space is partitioned by the barrier **520e** so that the foaming solution is not filled. Also, the deco opening **542** may be defined at a position corresponding to the space between the pair of barriers **520e**. The PCBs **602**, **603**, and **604** may be inserted and mounted through the deco opening **542** and then connected to the cables **601**, **605**, and **606** of the transparent display assembly **60**.

A PCB insulation material may be further provided in the space between the pair of barriers **520e**. The PCB insulation material **533** may be disposed at a front side of the PCBs **602**, **603**, and **604** to thermally insulate the rest portion except for a space required for mounting the PCBs **602**, **603**, and **604**.

Thus, the PCB insulation material **533** may be mounted after molding the insulation material **531** that is foamed and formed in the door **50** and have a thickness less than that of the insulation material **531**.

The PCB insulation material **533** may be made of a vacuum insulation material or a Styrofoam (PSP) material, which has relatively superior insulation performance so that the PCB insulation material **533** has a thin thickness and sufficient insulation performance. Also, the PCB insulation material **533** may be formed in a sheet shape and attached to the rear surface of the outer plate **51** or attached to a front surface of the PCB mounting part **545**.

The PCBs **602**, **603**, and **604** may be disposed in a lower space of the door **50**. Here, the deco opening **542** and the deco cover **543** may be mounted on the lower cap deco **55**. This configuration may be the same as that according to the abovementioned embodiments except that the mounted position is changed from the upward direction to the downward direction, and thus, its detailed description will be omitted.

A refrigerator according to various other embodiments in addition to the abovementioned embodiments may be exemplified.

A seventh embodiment is characterized by a structure in which all of connection cables of a docking PCB and a T-CON board within a sub door are guided to a main body through a hinge hole of the sub door. In the current embodiment, the same constituent as those of the abovementioned embodiments will be denoted by the same reference numeral, and its detailed description will be omitted. Also, although not shown, it is to be noted in advance that the reference numerals which are not shown are also the same as the abovementioned embodiments.

FIG. **33** is a plan view of a refrigerator according to a seventh embodiment. FIG. **34** is a block diagram illustrating a flow of a control signal of the refrigerator.

Referring to the drawings, a door **20** for opening and closing a storage space may be disposed on a cabinet **10**. The door **20** may be disposed on each of both left and right sides and rotatably mounted on the cabinet **10** to open and close the storage space.

The door **20** may be provided in a pair on both left and right sides and mounted to be rotatable by a main hinge **401** on the cabinet **10**. A hinge shaft **401a** may be disposed on the main hinge **401**. The hinge shaft **401a** may pass through hinge holes **200a** and **400a** defined in a top surface of the door **20**.

Also, one door (a right door in FIG. **33**) of the pair of both left and right doors **20** may be constituted by a main door **40** and a sub door **50**. Since the main door **40** and the sub door **50** have the same structure as the abovementioned embodiments, their detailed descriptions will be omitted.

The pair of both left and right doors may not be provided according to types of refrigerator. For example, the main door **40** and the sub door **50** may be provided as one door. Here, the main door and the sub door may also have the same structure as the abovementioned embodiments.

The main door **40** may be rotatably connected to the cabinet **10** by the main hinge **401**, and the sub door **50** may be rotatably connected to an upper end of the main door **40** by the sub hinge **501**.

Here, the hinge shaft **401a** of the main hinge **401** is coupled to pass through the hinge hole **400a** defined in an upper end of the main door **40**, and a rotation shaft **501a** of the sub hinge **501** may be mounted to pass through a hinge hole **541a** of the sub door **50**.

Also, each of the hinge shaft of the main hinge **401** and the hinge shaft of the sub hinge **501** may have a hollow tube shape or a tube shape that is bent in a "C" shape" so that a wire is accessible therethrough.

Particularly, a transparent display assembly **60** and a door light **57** may be provided in the sub door **50**. Here, cables connected to the transparent display assembly **60** and the door light **57** may pass through the hinge shaft **501a** and the hinge hole **541a** of the sub hinge **501** and then be connected to a display PCB **142** disposed on a top surface of the cabinet **10**.

As occasion demands, the cables may pass through the hinge supporting a lower end of the sub door **50**.

Each of the hinge shafts **501a** and **501a** and the hinge holes **200a**, **400a**, and **541a** may be limited in size according to a thickness of each of the main door **40** and the sub door **50**.

In detail, each of the right door of the door **20** and the main door **40** may have a relatively thick thickness. Thus, the hinge shaft **401a** and the hinge holes **200a** and **400a** for the rotation of the door **20** and the main door **40** may have predetermined inner diameters D1 and D2. Here, the inner diameter D1 of the hinge hole **400a** of the door **20** and the inner diameter D2 of the hinge hole **400a** of the main door **40** may be the same. Alternatively, since the main door **40** has a thickness less than that of the door **20**, the inner diameter D2 of the hinge hole **400a** of the main door **40** may be somewhat less than that of the D1 of the hinge hole **541a** of the door **20**.

Wires connecting electric modules such as an ice maker, a dispenser, a display device, various sensors, and a heater may be guided through the hinge holes **200a** and **400a** and also be connected to a main PCB **141** on the top surface of the cabinet **10**. Here, the main hinge **401** may include a hinge cover. Thus, the wires may be accommodated without being exposed or to be minimally exposed.

The sub door **50** may have a significantly thin thickness when compared with the main door **40**. The sub door **50** may perform a function of covering an accommodation space defined in the main door **40** without forming a separate accommodation space in a state of being maintained in total thickness of the door **20**. Here, since the sub door **50** has a thickness that is sufficient to accommodate the transparent display assembly **60**, the sub door **50** may have a relatively thin thickness.

Thus, each of the hinge hole **541a** in which the sub hinge **501** for rotatably mounting the sub door **50** is mounted and the hinge shaft **501a** mounted in the hinge hole **541a** may have a relatively small inner diameter.

That is, each of the hinge shaft **501a** of the sub door **50** and the hinge hole **541a** into which the hinge shaft **501a** is inserted may have a diameter D3 necessarily less than that D2 of each of the hinge shaft **401a** of the main door **40** and the hinge hole **541a**.

Also, a display **142** constituting the transparent display assembly **60** and a T-CON board **602** for driving the display **142** may be disposed in the sub door **50**. In addition, a touch sensor **612** and a touch PCB **603** for an operation of the touch sensor **612** may be disposed in the sub door **50**, and a docking PCB **604** connecting the touch PCB **603** to a display light **68** and a door light **57** may be disposed in the sub door **50**.

The plurality of PCBs **602**, **603**, and **604** may be disposed in an upper space of the sub door **50**. Also, the upper space of the sub door **50**, in which the plurality of PCBs **602**, **603**, and **604** are disposed may communicate with the hinge hole **541a**. Thus, cables **607b**, **607c**, and **607d** connected to the

T-CON board **602** and the docking PCB **604** may pass through the hinge hole **541a** and the hinge shaft **501a** and then be guided to the cabinet **10**.

Here, since the inner diameter **D3** of the hinge hole **541a** or the hinge shaft **501a** is limited, all of the cables connected to the plurality of electric modules may not individually pass through the hinge hole **541a**. Particularly, the cables connected to the display **142**, the display light **68**, and the touch sensor **612** may be flat type cables. Thus, each of the cables may have a structure that is not suitable to pass through the hinge hole **541a**.

Thus, the flat type cables may be converted into wire type cables through the docking PCB **604** and rearranged to have an arrangement that is suitable to pass through the hinge hole **541a** so that the cables pass through the hinge hole **541a**.

A display PCB **142** may be disposed on the top surface of the cabinet **10**. The display PCB **142** may control an operation of the transparent display assembly **60**. The display PCB **142** may be constituted by the touch PCB **603**, the T-CON board **602**, and the docking PCB **604**, which are minimum components for driving the transparent display assembly **60** and disposed in the sub door **50**. Also, the rest components may be disposed in the cabinet **10**. That is, the display PCB **142** for the overall control of the components of the sub door **50** and components having relatively large volumes such as an adaptor related to power may be disposed in the cabinet **10** to minimize the size of each of the PCBs **602**, **603**, and **604** within the sub door **50**.

Also, the main PCB **141** and a speaker **146**, a camera **145**, and a communication module **147** connected to the main PCB **141** may be disposed in the cabinet **10**.

FIG. **35** is a perspective view illustrating a structure of PCBs disposed in a sub door according to the seventh embodiment.

Although not shown, a plurality of PCBs **602**, **603**, and **604** may be disposed in a sub door **50**. The PCBs **602**, **603**, and **604** may be divided into a plurality of parts so that the PCBs **602**, **603**, and **604** are efficiently disposed in an upper space of the narrow sub door **50**. Thus, at least portions of at least one of the plurality of PCBs **602**, **603**, and **604** may overall each other and be disposed in a front and rear direction.

That is, the plurality of PCBs **602**, **603**, and **604** may be disposed at an optimum position in the connection to a display **142**, a touch sensor **612**, a door light **57**, and a display light **68**. Also, at least a portion of the PCBs **602**, **603**, and **604** may be disposed in a front and rear directions within the narrow sub door **50**.

The plurality of PCBs **602**, **603**, and **604** may include a T-CON board **602**, a touch PCB **603**, and a docking PCB **604**. The T-CON board **602** and the touch PCB **603** except for the docking PCB **604** may be provided as one PCB. As occasion demands, the T-CON board **602** and the touch PCB **603** may be provided as at least two PCBs separated from each other.

A display connector **602a** may be disposed on the T-CON board **602**, and a flat cable type display cable may be connected to the display connector **602a**. The display connector **602a** may be provided in plurality.

A T-CON output connector **602c** may be disposed on the T-CON board **602**. The T-CON output connector **602c** may be provided as a wire type T-CON connection cable **607b**. The T-CON output connector **602c** may have a minimum volume when the T-CON output connector **602c** is provided as a plurality of strands of cables, each of which has a thin thickness, are bound to each other and thus may easily pass through the hinge hole **541a** and the hinge shaft **501a**.

The touch connector **603a** may be disposed on the touch PCB **603**, and a flat cable type touch cable **601** may be connected to the touch connector **603a**. Also, a PCB connector **604d** may be disposed on the touch PCB **603** and the docking PCB **604**. A PCB cable **608** may be connected to the PCB connector **604d**, and the touch PCB **603** may be connected to the docking PCB **604** by the PCB cable **608**.

A door light connector **604b** and a display light connector **604d** may be disposed on the docking PCB **604**. A door light cable **609** connected to the door light **57** may be connected to the door light connector **604b**, and a display light cable **606** may be connected to the display light connector **604a**. Since two display lights and two door lights **57** are provided, two door light cables **606** and two door light cables **609** may also be provided. Thus, the connector provided in the docking PCB **604** may include total five connectors, i.e., the PCB connector **604d**, the two display light connectors **604a**, and the two door light connectors **604b**, which connected to each other. Alternatively, as occasion demands, the number of cables or connector may increase or decrease. Also, the cables and the connectors may be provided in a terminal structure in which the cables and the connectors are simply coupled to each other so that assembly and connection are easy. Also, a first connection connector **604e** and a second connection connector **604f** may be disposed on the docking PCB **604**. A first connection cable **607c** and a second connection cable **607d**, which are provided as wire type cables, may be connected to the first connection connector **604e** and the second connection connector **604f**, respectively.

The first connection cable **607c** and the second connection cable **607d** may be provided for transmitting a signal or power of the PCB cable **608** and pass through the hinge hole **541a** and the hinge shaft **501a** to connect the docking PCB **604** to the display PCB **142**.

That is, the PCB cable **608**, the two display light cables **606**, and the two door light cables **609** may be connected and led to the docking PCB **604**. In the docking PCB **604**, the PCB cable **608**, the two display light cables **606**, and the two door light cables **609** may be rearranged to be outputted to the first connection cable **607c** and the second connection cable **607d** and then be connected to the display PCB **142** disposed in the cabinet **10**.

That is, in the docking PCB **604**, the number of outputted cables to the number of cables physically inputted in the form of 5 input-2 output may be reduced, and also, the flat type cables may be converted into the wire type cables.

The first connection cable **607c** and the second connection cable **607d** may be rearranged in various manners.

For example, the first connection cable **607c** and the second connection cable **607d** may be configured to redistribute and output the plurality of input cables **605**, **606**, **608**, and **609** according to a kind of cables.

For example, the first connection cable **607c** may be a cable related to power and constituted by cables for supplying power to the touch PCB **603**, the display light **68**, and the door light **57**. Also, the second connection cable **607d** may be a cable related to a signal or processing and constituted by cables for transmitting and processing a signal to the touch PCB **603**, the display light **68**, and the door light **57**.

That is, in the docking PCB **604**, the plurality of cables connected to the docking PCB **604** may be rearranged into the power and signal-related cables and then outputted to two type cables of a first connection cable **607c** having a high voltage and a second connection cable **607d** having a low voltage to significantly reduce the number of cables.

For another example, the first connection cable **607c** and the second connection cable **607d** may be configured to redistribute and output the plurality of input cables according to voltages.

For example, the first connection cable **607c** may be a cable for transmitting a high voltage and be constituted by cables that are connected to a component that requires a high voltage to transmit the high voltage. Also, the second connection cable **607d** may be a cable for transmitting a low voltage and be constituted by cables that are connected to a component that requires a low voltage to transmit the low voltage.

That is, in the docking PCB **604**, the cables of the plurality of components connected to the docking PCB **604** may be rearranged according to a difference in voltage and then outputted to two type cables of a first connection cable **607c** having a high voltage and a second connection cable **607d** having a low voltage to significantly reduce the number of cables.

For another example, the first connection cable **607c** and the second connection cable **607d** may be configured to redistribute and output the plurality of input cables according to functions.

For example, the first connection cable **607c** may be constituted by cables connected to the touch PCB **603** to which the power is being supplied. Also, the second connection cable **607d** may be constituted by cables connected to the display light **68** and the door light **57** to which the power is supplied according to an operation signal.

That is, in the docking PCB **604**, the cables of the plurality of components connected to the docking PCB **604** may be rearranged into a component that requires normal power and a component that does not require the normal power and then outputted to the first connection cable **607c** to which the normal power is supplied and the second connection cable **607d** to which power is supplied during the operation to significantly reduce the number of cables.

Each of the first connection cable **607c** and the second connection cable **607d** may be provided as a wire type cable. Each of the first and second connection cables **607c** and **607d** may have a minimum volume when each of the first and second connection cables **607c** and **607d** is bound as a plurality of strands of cables, each of which has a thin thickness, are bound to each other and thus may easily pass through the hinge hole **541a** and the hinge shaft **501a**.

As described above, all of the T-CON connection cable **607b** connected to the T-CON output connector **602c** and the first and second connection cables **607c** and **607d** connected to the first and second connection connectors **604e** and **604f** may pass through the hinge hole **541a** of the sub door **50** and the hinge shaft **501a** of the sub hinge **501** and then be guided to the cabinet **10**.

FIG. **36** is an exploded perspective view illustrating a connection structure between the PCBs and the cable inside the sub door. Also, FIG. **37** is an exploded perspective view illustrating an arrangement of a wire outside the sub door.

As illustrated in the drawings, a deco opening **542** may be defined in an upper cap deco **54** defining a top surface of the sub door **50**, and the touch PCB **603**, the T-CON board **602**, and the docking PCB **604** may be mounted on the deco cover **543** that covers the deco opening **542** and then accommodated into the deco opening **542**.

A hinge hole **541a** in which the sub hinge **501** is mounted may be defined in one side of the upper cap deco **54**. The hinge hole **541a** may communication with an inner space of the deco opening **542**. Thus, the T-CON connection cable **607b** connected to the T-CON board **602** and the first and

second connection cables **607c** and **607d** of the docking PCB **604** may be accessible through the hinge hole **541a**.

Here, the T-CON connection cable **607b** and the first and second connection cables **607c** and **607d** may be provided as one wire form by a binding member **607a** such as a shrinkable tube, a separate binding film, or a tape to pass through the hinge hole **541a** and the hinge shaft **501a**.

The binding member **607a** may be disposed in a section passing through at least the hinge hole **541a** and the hinge shaft **501a**. Thus, the binding member **607a** may easily pass through the hinge hole **541a** and the hinge shaft **501a** and also prevent the cables **607b**, **607c**, and **607d** from being damaged even when the sub door is repeatedly opened and closed.

The cables **607b**, **607c**, and **607d** passing through the hinge hole **541a** and the hinge shaft **501a** may be exposed to an upper side of the sub door **50** through the hinge shaft **501a** as illustrated in FIG. **37** and pass through the sub hinge cover **505** covering the sub hinge **501** and then be introduced into the main hinge cover **403**.

Here, the cables **607b**, **607c**, and **607d** may be rotatably coupled to each other and pass through a sub extension part **505a** and a main extension part **403a**, which communicate with each other, and then be guided to the cabinet **10**. Thus, the cables **607b**, **607c**, and **607d** may be prevented from interfering or being damaged even when the sub door rotates and be guided to the cabinet **10** and then be connected to the display PCB **142**.

A refrigerator according to various other embodiments in addition to the abovementioned embodiments may be exemplified.

An eighth embodiment is characterized by a door structure in which an entire surface of a door is defined by a transparent display assembly. Although not shown, the same constitution as that of the foregoing embodiment will be denoted as the same reference numeral, and its detailed description will be omitted.

FIG. **38** is an exploded perspective view of a door according to an eighth embodiment.

As illustrated in the drawing, a door **20** of a refrigerator **1** according to an eighth embodiment may include a main door **70** that opens and closes at least a portion of an opened front surface of a cabinet **10** and a sub door **80** that opens and closes an opening **703** of the main door **70**.

The opening **703** that is opened with a predetermined size is defined in the main door **70**. A separate accommodation space may be defined in the opening **703**, and an access to the accommodation space may be enabled through opening and closing of the sub door.

Also, an outer appearance of the main door **70** may be defined by an outer plate **71** made of a metal material, a door linear **72** coupled to the outer plate **71**, and a door cap deco disposed on each of upper and lower ends of the door linear **72**.

Also, a door lighting unit **74** for brightening up the inside of the opening **703** may be disposed on an inner surface of the door linear **72**. The door lighting unit **74** may be disposed on both left and right surfaces or a top surface of the opening **703**. The door lighting unit **74** may allow the sub door **80** to be transparent or perform a backlight function of a transparent display assembly **90** mounted on the sub door **80** to visualize a screen outputted through the transparent display assembly **90**.

A door frame **73** may be further disposed between the outer plate **71** and the door linear **72**. The door frame **73** may be coupled between the outer plate **71** and the door linear **72** to form a circumference of the opening **703**.

Also, a hinge hole **733** in which sub hinges **81** and **82** for mounting the sub door **80** are mounted may be defined to be opened in one side of the door frame **73**. The hinge hole **733** may be opened at a position facing a side surface of the sub door **80**, and the sub hinges **81** and **82** may be inserted into the hinge hole **733**. Also, a connection cable **884** connected to a door PCB **88** may be accessible through the hinge hole **733**.

Upper and lower ends of the sub door **80** may be recessed so that the sub hinges **81** and **82** are mounted, respectively. Also, the sub hinges **81** and **82** may extend laterally to the hinge hole **733** and be coupled inside the main door **70**. Thus, the sub hinges **81** and **82** may prevent an interference with the main door **70** from occurring when the sub door **80** rotates while maintaining a very narrow space between the sub hinges **81** and **82** and the main door **70**. Also, the sub hinges **81** and **82** may further include a hinge cover **811** disposed above the sub hinge **81** to cover the sub hinge **81** and guide an access of the connection cable **884**.

FIG. **39** is an exploded perspective view of the sub door according to the eighth embodiment.

As illustrated in the drawing, the sub door **80** may have a shape corresponding to that of the opening **703**. The sub door **80** may include a transparent display assembly **90** through which the inside of the refrigerator **1** is seen, and a screen is outputted, side frames **83** and **84** defining both side surfaces of the sub door **80**, a sub door linear defining a circumference of a rear surface of the sub door **80**, a sub door gasket **851** mounted on the sub door linear **85** to seal a gap between the main door **70** and the sub door **80**, and upper and lower cap decos **86** and **87** defining top and bottom surfaces of the sub door **80**.

An outer appearance of front and rear surfaces of the transparent display assembly **90** may be defined by a front panel **91** and a rear panel **97**, which are made of a glass material and define the front and rear surfaces of the sub door **80**. Also, a display **94** for outputting a screen and a touch sensor **92** for touch input may be disposed between the front panel **91** and the rear panel **97**.

Also, flat cable type cables **921** and **942** and **961** connected to electric modules of the transparent display assembly **90** may be disposed along the circumference of the transparent display assembly **90** to extend upward and then be coupled to a door PCB **88**.

The door PCB **88** may be configured to control the electric modules within the transparent display assembly **90** and be disposed at a position that is capable of being connected to the cables **921**, **942**, and **961**. Also, the door PCB **88** may be connected to a wire cable type connection cable **884** that is introduced to the sub hinge **81**. Thus, the door PCB **88** may convert a signal, which is received or transmitted through the plurality of flat cable type cables **921**, **942**, and **961**, through the wire cable type connection cable **884** to guide the signal to the outside of the sub door **80**.

The door PCB **88** may be disposed to be divided into a plurality of parts according to a size of an inner space of the sub door **80** or may be disposed to be integrated in one PCB shape. When the door PCB **88** is provided in plurality, the plurality of door PCBs **88** may be disposed horizontally and vertically and be stacked with each other.

For this, a deco opening **861** may be defined in the upper cap deco **86** that is disposed at a position corresponding to that of the cables **921**, **942**, and **961**, and the door PCB **88** may be mounted inside the deco opening **861**. Also, the deco opening **861** may be covered by a deco cover **862** in the state in which the door PCB **88** is mounted.

FIG. **40** is an exploded perspective view of the transparent display assembly according to the eighth embodiment.

As illustrated in the drawings, the transparent display assembly **90** may provide a see-through part of the sub door **80** and define an outer appearance of each of the front and rear surfaces of the sub door **80**. Thus, an accommodation space inside the opening **703** may be seen, or the screen may be outputted through the transparent display assembly **90**.

The transparent display assembly **90** may include a front panel **91** defining an outer appearance of a front surface, a display **94** disposed at a rear side of the front panel **91**, a rear panel **97** which is disposed at a rear side of the display **94** and on which a PDLC film for illuminating the display **94** is attached, and a display frame **98** for fixing the front panel **91**, the display **94**, and the rear panel **97**.

In more detail, the front panel **91** may be disposed at the frontmost position of the transparent display assembly **90** to define the front surface of the sub door **80**. The front panel **91** may be made of blue glass, and a bezel **911** may be printed on a circumference of a rear surface of the front panel **91**. Spacing rods **93** and **95** disposed at the rear side of the front panel **91** or the door PCB **88** may not be exposed to the outside by the bezel **911**. The bezel **911** may have a width that is adjustable according to the mounted position of the door PCB **88**. The bezel **88** disposed at an end of a side at which the door PCB **911** is disposed may have a thicker thickness to completely cover the door PCB **911**.

A printing or film type touch sensor **92** may be attached to the rear surface of the front panel **91**. Thus, when a user touches the front panel **91**, the touch sensor **92** may recognize the user's touch. Also, a flexible flat cable type touch cable **921** may be connected to one side of the touch sensor **92**.

The display **94** may be mounted on the rear side of the front panel **91** to which the touch sensor **92** is attached. Also, the first spacing rod **93** may be disposed between the display **94** and the front panel **91**. The first spacing rod **93** may have a rectangular frame shape disposed along a circumference of the display **94**. Also, the first spacing rod **93** may adhere between the display **94** and the front panel **91** to maintain a predetermined distance between the front panel **91** and the display **94** and support the display **94**.

The display **94** may be provided as a transparent LCD display. Thus, although the display **94** does not output a screen, the inside of the refrigerator **1** may be seen through the display **94** as if glass. Also, a source board **941** for controlling the display **94** may be mounted on one end of the display **94**, and a flexible flat cable type display cable **942** may be connected to the source board **941**.

The rear panel **97** may define an outer appearance of a rear surface of the transparent display assembly **90** and be exposed to the door linear **72**. The rear panel **97** may be made of low- ϵ glass to realize thermal insulation.

The PDLC film **96** may be attached to the front surface of the rear panel **97**. The PDLC film **96** may be selectively transparent or opaque according to applying of power. Thus, the user may selectively see the inside of the refrigerator according to the state of the PDLC film **96**. Also, a flexible flat cable type PDLC cable **961** may be connected to one side of the PDLC film **96**.

Also, the second spacing rod **95** having the same structure as the first spacing rod **93** may be disposed between the rear panel **97** and the display **94** to maintain a space between the display **94** and the rear panel **97**.

The display frame **98** may define a circumferential surface of the transparent display assembly **90**. Also, the display frame **98** may fix the front panel **91** and the rear panel **97** to

maintain the preset space between the front panel **91** and the rear panel **97**. Also, the transparent display assembly **90** may be fixed and mounted on the sub door **80** when the transparent display assembly **90** is completely assembled. Also, the flat type cables **921**, **942**, and **961** may be guided to the outside between the display frame **98** and an adhesion surface of the front panel **91** or the rear panel **97**, and a sealant may be applied to an outer surface of the display frame **98** to seal a gap so that the gap does not occur.

In the state in which the display **94** does not output the screen, and the PDLC film **96** is transparent, the transparent display assembly **90** may be transparent. In this state, when the door lighting unit **74** is turned on, the space inside the opening **703** may be seen from the outside.

Also, in the state in which the PDLC film **96** is opaque, the transparent display assembly **90** may be opaque. In this state, when the door lighting unit **74** is turned off, the inside of the refrigerator may be darker, and thus, the space inside the opening **703** may not be seen.

The display **94** may be driven to output the screen. In this case, in the state in which the door lighting unit **74** is turned on, and the PDLC film **96** is transparent, the door lighting unit **74** may serve as a backlight that brightens up the display **94** so that the display **94** is more clearly displayed.

FIG. **41** is a block diagram illustrating a flow of a control signal in the refrigerator according to the eighth embodiment.

As illustrated in the drawing, the flat type touch cable **921**, the display cable **942**, and the PDLC cable **961** may be connected to one side of the door PCB **88** disposed on the sub door **80**. Also, in the other side of the door PCB **88**, the wire type connection cable **884** may be guided to the main door **70** through the upper hinge **81** and the hinge hole **733** to pass through main door **70** and then be connected to the transparent display assembly **90** on the cabinet **10**.

Since the connection cable **884** has a small volume and superior durability, the connection cable **884** may be disposed to easily pass through the sub door **80** and the main door **70** and prevent the main door **70** and the sub door **80** from being damaged even though the main door **70** and the sub door **80** are repeatedly opened and closed. Also, the door lighting unit **74** mounted on the main door **70** may also be connected to the display PCB **142** on the cabinet **10** by passing through the main door **70**.

The display PCB **142** may receive a signal inputted from the touch sensor **92** and control the turn-on/off of the door lighting unit **74** and the image output of the display **94**.

Although the door PCB **88** is disposed on the upper end in the eighth embodiment, the door PCB **88** may be disposed on the lower end of the sub door **80**, or both side ends of the sub door **80** so that the door PCB **88** is capable of being accommodated and also be disposed outside the transparent display assembly **90** so that the door PCB **88** is not exposed through the transparent display assembly **90**.

The following effects may be expected in the refrigerator according to the proposed embodiments.

In the refrigerator according to the embodiments, the see-through part that sees the accommodation space may be provided in the door. The see-through part may include the transparent display and be selectively transparent or opaque according to the turn-on/off of the door light and the display light. Thus, the user may confirm the accommodation space through the see-through part by the user's manipulation without opening the door to improve the user's convenience and reduce the power consumption.

Also, in the see-through part, the display may operate according to the user's manipulation to display various

screens and thereby to provide various pieces of information for the user's convenience and allow the user to input the manipulation thereof, thereby improving the user's convenience.

Also, the cables connected to the electric modules of the transparent display assembly may have the flexible structure as the flat type cable. Thus, the cables may easily access between the transparent display assembly having the structure in which the plurality of panels are laminated, and the airtight state may be maintained.

Also, the cables may be bent and thus closely attached to the circumference of the transparent display assembly. Thus, the door may have the compact structure, and the interface with the insulation material may be minimized.

Also, the PCB for controlling the electric modules of the transparent display assembly may be disposed at the upper, lower, or left/right sides of the transparent display assembly. In addition, since the cables connected to the PCB are also disposed along the circumference of the transparent display assembly, the PCB or the cables may not be exposed to the outside through the transparent display assembly. That is, the inside of the refrigerator may be seen through the transparent display assembly that is capable of outputting the screen. Here, the interference with the PCB or the cables may be prevented.

Also, the PCBs may be connected to the cables that are exposed through the opening of the door. Thus, the PCBs may be mounted after the foaming for molding the insulation material in the door is performed to prevent the PCBs from being damaged by the foaming heat or static electricity.

Also, the PCB may have one side connected to the plurality of flat type cables and the other side connected to the wire type cable. Thus, the wire type cable may be guided outward from the inside of the door and then connected to the control unit disposed in the cabinet. Thus, the flat type cables connected to the plurality of electric modules may not pass through the door. As a result, the lead-out structure of the cable to the outside of the door may be simplified, and even though the door is repeatedly opened and closed, the cable may be prevented from being short-circuited or damaged.

In addition, the number of cables, which are connected to the electric modules and other PCBs within the door, in the docking PCB may be less than that of connection cables, which pass through the door hinge through the control unit, in the docking PCB. Also, the control signal transmitted from the control unit in the cabinet may be transmitted to the electric modules and other PCBs through the docking PCB.

Thus, the control signal and the power may be supplied to the inside of the door, in which the plurality of electric modules are provided, through the narrow door hinge. Particularly, in the refrigerator having the sub door structure, the hinge shaft of the sub door may be very narrow. Thus, the arrangement structure of the wire for driving the display and the electric module may be realized through the narrow hinge shaft.

Also, the connector may be provided in the PCB to allow the flat type cable exposed through the opening of the door to be easily inserted into and mounted on the connector, thereby improving the workability in assembly of the PCB.

In addition, the PCB for controlling the operation of the door and/or the transparent display assembly may be provided in the door, and the additional display assembly connected to the PCB may be provided in the cabinet. Thus, the constituents of the PCB provided in the door may be minimized, and also, the number of wires connected to the PCB may be minimized to maximally expand the space in

which the transparent display assembly is disposed. Therefore, the visible area of the accommodation space may be more expanded.

Also, the plurality of PCBs for driving the transparent display assembly and the door light may be provided and then connected to each other in the same space so as to be modularized, thereby improving the assemblability of the door and the transparent display assembly.

Although embodiments have been described with reference to a number of illustrative embodiments thereof, it should be understood that numerous other modifications and embodiments can be devised by those skilled in the art that will fall within the spirit and scope of the principles of this disclosure. More particularly, various variations and modifications are possible in the component parts and/or arrangements of the subject combination arrangement within the scope of the disclosure, the drawings and the appended claims. In addition to variations and modifications in the component parts and/or arrangements, alternative uses will also be apparent to those skilled in the art.

What is claimed is:

1. A refrigerator comprising:
 - a cabinet defining a storage space;
 - a control unit disposed on an upper portion of the cabinet;
 - a door rotatably coupled to the cabinet by a hinge and configured to open and close at least a portion of the storage space, the door defining an opening and at least a portion of the opening facing toward the storage space; and
 - a transparent display assembly covering the opening and being configured to provide at least one of a see-through view of the storage space or an output of an image,
 wherein the transparent display assembly comprises:
 - a plurality of electric modules,
 - a printed circuit board (PCB) disposed inside the door and electrically connected to a first portion of the plurality of electric modules, and
 - a docking PCB disposed adjacent to the PCB, the docking PCB being connected to a second portion of the plurality of electric modules and to the PCB, wherein the docking PCB comprises:
 - first connectors connected to the PCB through cables, and
 - second connectors connected to the control unit through a connection cable that is guided to an outside of the door,
 wherein a number of the second connectors is less than a number of the first connectors,
 wherein the plurality of electric modules and the PCB are connected to the control unit through the docking PCB and the connection cable, and
 - wherein the control unit is configured to transmit a control signal to the PCB through the docking PCB to control the plurality of electric modules.
2. The refrigerator according to claim 1, wherein at least one of the cables comprises a flexible flat cable, and wherein the connection cable comprises a wire type cable.
3. The refrigerator according to claim 1, wherein the door comprises a cap decoration that defines a top surface of the door and that defines a wire hole through which the connection cable is guided to the outside of the door.
4. The refrigerator according to claim 1, wherein the door comprises a hinge shaft disposed at an upper end of the door, and
 - wherein the connection cable is guided to the outside of the door by passing through the hinge shaft.

5. The refrigerator according to claim 1, wherein the plurality of electric modules comprises:

- a display configured to output a screen;
- a touch sensor configured to receive a touch input on the display; and
- a display light configured to illuminate a light guide plate disposed at a rear side of the display.

6. The refrigerator according to claim 5, wherein the display comprises a source PCB disposed on one end of a pair of ends of the display, and

- wherein the source PCB is disposed inside the transparent display assembly and oriented in a direction in which a surface of the source PCB is perpendicular to a surface of the display.

7. The refrigerator according to claim 6, further comprising a flat type display cable connecting the source PCB to the PCB,

- wherein the flat type display cable is bent and arranged along a circumferential surface of the transparent display assembly.

8. The refrigerator according to claim 7, further comprising a flat type touch cable connecting the touch sensor to the PCB,

- wherein the flat type touch cable is arranged inside the transparent display assembly, and a portion of the flat type touch cable penetrates the circumferential surface of the transparent display assembly to connect to the PCB.

9. The refrigerator according to claim 5, further comprising a flat type display light cable connecting the display light to the PCB,

- wherein the flat type display light cable is arranged along a protrusion that protrudes from a front surface of the transparent display assembly or from a rear surface of the transparent display assembly.

10. The refrigerator according to claim 5, wherein the plurality of electric modules comprises a door light disposed on a rear surface of the door and configured to illuminate a rear space of the door.

11. The refrigerator according to claim 5, wherein the PCB comprises:

- a touch PCB electrically connected to the touch sensor; and
 - a timing controller (T-CON) board electrically connected to the display, and
- wherein at least one of the touch PCB and the T-CON board is connected to the docking PCB.

12. The refrigerator according to claim 1, wherein the door defines a cap opening at a circumference of the door, wherein the PCB inserts into the cap opening, and the cables connected to the PCB are exposed to the cap opening, and

- wherein an insulation material is filled around the door except for a space between the cap opening and the transparent display assembly.

13. The refrigerator according to claim 12, wherein the door comprises:

- a cap decoration defining a top or bottom surface of the door, the cap decoration defining the cap opening;
- a decoration cover being disposed on the cap decoration and covering the cap opening; and
- a PCB mounting part extending from the decoration cover toward the cap opening and being configured to seat the PCB and the docking PCB.

14. The refrigerator according to claim 1, wherein the connection cable comprises:

- a first connection cable configured to transmit power; and

41

a second connection cable configured to transmit the control signal.

15. The refrigerator according to claim 1, wherein the connection cable comprises:

a first connection cable connected to a first electric module and configured to supply a high voltage to the first electric module; and

a second connection cable connected to a second electric module and configured to supply a low voltage to the second electric module, the high voltage exceeding the low voltage.

16. The refrigerator according to claim 1, wherein the connection cable comprises:

a first connection cable configured to supply power; and a second connection cable configured to supply power based on an operation signal.

17. The refrigerator according to claim 1, wherein the door comprises:

a main door rotatably coupled to the cabinet and configured to open and close a first storage space within the cabinet, the main door defining a second storage space;

a main hinge about which the main door is configured to rotate with respect to the cabinet;

a sub door rotatably coupled to the main door and disposed on a front side of the main door, the sub door being configured to open and close the second storage space; and

42

a sub hinge about which the sub door is configured to rotate with respect to the main door, and

wherein the opening of the door is defined at a position corresponding to the second storage space.

18. The refrigerator according to claim 17, wherein the sub hinge includes a hinge shaft, and the main hinge includes a rotation shaft,

wherein an inner diameter of the hinge shaft of the sub hinge is less than an inner diameter of the rotation shaft of the main hinge, and

wherein the connection cable is guided to the outside of the door by passing through the hinge shaft of the sub hinge.

19. The refrigerator according to claim 18, wherein the hinge shaft of the sub hinge communicates with a space defined in the sub door, the docking PCB being mounted in the space.

20. The refrigerator according to claim 18, wherein the connection cable comprises a plurality of wires and a binding member that bundles the plurality of wires, and

wherein the plurality of wires bundled by the binding member pass through the hinge shaft of the sub hinge.

* * * * *