



(22) Date de dépôt/Filing Date: 1999/04/26

(41) Mise à la disp. pub./Open to Public Insp.: 1999/10/27

(45) Date de délivrance/Issue Date: 2008/01/08

(30) Priorité/Priority: 1998/04/27 (ITMI98U 000296)

(51) Cl.Int./Int.Cl. *B65G 21/20* (2006.01)


(72) Inventeur/Inventor:
MARSETTI, SERGIO, IT

(73) Propriétaire/Owner:
SYSTEM PLAST S.P.A., IT

(74) Agent: ROBIC

(54) Titre : PIECE DE FIXATION POUR AU MOINS UNE GOUPILLE DE SOUTIEN POUR COMPOSANTS D'UN
TRANSPORTEUR A COURROIE

(54) Title: CLAMPING MEMBER FOR AT LEAST ONE SUPPORT PIN FOR BELT CONVEYOR COMPONENTS



(57) Abrégé/Abstract:

A clamping member (4) for at least one support pin (7, 7A) for components of belt conveyors (1), for example guide elements (2), comprising means (10-13) for removably-securing said pin (7, 7A) to a head (8, 8D, 8E); the means are formed in such a manner as to secure the pin (7, 7A) to the head (8) by the action of an elastic element (10) arranged to urge that portion of the pin (7, 7A) inserted into a seat (16, 17) provided in the head, against the walls of said seat to hence maintain the pin secured to the head, said means also being formed in such a manner as to enable the pin (7, 7A) to be released from the head (8) by exerting on said portion of the pin (7, 7A) an opposite action to that of the elastic element (10).



Abstract:

A clamping member (4) for at least one support pin (7, 7A) for components of belt conveyors (1), for example guide elements (2), comprising means (10-13) for removably securing said pin (7, 7A) to a head (8, 8D, 8E); the means are formed in such a manner as to secure the pin (7, 7A) to the head (8) by the action of an elastic element (10) arranged to urge that portion of the pin (7, 7A) inserted into a seat (16, 17) provided in the head, against the walls of said seat to hence maintain the pin secured to the head, said means also being formed in such a manner as to enable the pin (7, 7A) to be released from the head (8) by exerting on said portion of the pin (7, 7A) an opposite action to that of the elastic element (10).

CLAMPING MEMBER FOR AT LEAST ONE SUPPORT PIN FOR BELT CONVEYOR COMPONENTS

This invention relates to a clamping member for at least one support pin for belt conveyor components, for example guide elements.

Known belt conveyors comprise lateral guide elements for the conveyed products, these guide elements generally being connected to the support structure of the belt conveyor or conveyors by a plurality of parts comprising a pin and a clamping head for said pin.

It should be noted that the lateral guide elements can take various forms and that the pins may also support other usual conveyor components, for example rollers or photoelectric cells.

In known clamping members a portion of the pin is inserted into a through hole provided in the clamping head and is rigidly secured thereto by a screw. This latter engages in a threaded hole perpendicular to and communicating with that into which the pin is inserted, such that the end of the screw can make contact with that pin portion housed in the head, and which on tightening the screw becomes rigidly secured to the head. To facilitate tightening of the screw, it generally carries an associated handwheel or handle.

The operations involved in tightening the screw to position the guide elements and more generally the conveyor components in the desired manner are relatively burdensome in terms both of time and

of the effort required.

It should also be noted that in known systems the pin is secured to the relative head only if the screw is sufficiently tightened. However it often happens that the screw slackens with the passage of time or, because of lack of attention, is not tightened with the necessary force.

10 An object of this invention is to provide a clamping member which by making the operations faster and less fatiguing simplifies the operations involved in securing the pins to the relative heads, while at the same time providing a perfect connection between the pin and the head which remains reliable with time.

A further object is to provide a clamping member which comprises a small number of pieces and is therefore of simple low-cost construction.

20 These and further objects are attained by a clamping member comprising at least one support pin for mounting components of belt conveyors, the clamping member further comprises a head, having a seat and a hole provided in a lateral wall of said head for the passage of said pin and securing means for removably securing said pin to said head, characterised in that said securing means comprises an element movable in said seat and having a hole for the passage of said pin, an elastic element housed in said head and arranged to urge said movable element in a direction to secure that portion of said pin which has been inserted through said aligned holes against walls of said holes, and a knob connected to said movable element and projecting from said head to enable said movable element to be pushed against the action of said elastic element allowing said pin to be withdrawn from said holes, the pin comprises at least one annular groove and said movable element comprises a single locking element projecting from the wall defining said hole to cooperate with said at least one
30 annular groove of said pin to lock and facilitate the positioning of said pin relative to said head.


2a

The invention will be more apparent from the accompanying drawings, which are provided by way of non-limiting example and on which:

Figure 1 is a schematic cross-section through a conventional conveyor, comprising two different clamping members according to the invention.

10 Figures 2A, 2B, 2C, 3A, 3B, 3C, 4A, 4B, 4C are respectively a schematic perspective, exploded and longitudinal sectional view of a first, a second and a third embodiment of a clamping member of the invention:

Figure 5 is a partial view of a support pin according to the invention.



3

Referring to Figure 1, this shows a belt conveyor of conventional type, indicated overall by 1, comprising lateral guide elements 2 (also conventional) for the conveyed products 3. The guide elements 2 are connected to a support structure, indicated overall by 4, comprising a pin 7, and a member 5 according to the invention for clamping the pin 4.

In a first embodiment (indicated by A in Figure 1 and also shown in Figures 2A-C) the clamping member 5 is removably connected to an arm 6 of conventional type.

The clamping member 5 comprises a main body or head 8, a screw 9 for fixing the member 5 to the arm 6, a spring 10, an inner movable element 11, a circlip 12 and a knob 13.

The head 8, which is cylindrical in the example, has a coaxial hole defining a seat 15 for the movable element 11 and comprising projecting guide ribs 14 which, by cooperating with grooves 14A provided in the movable element 11, enable this latter to move only coaxially to the head 8. The seat 15 is closed lowerly by a base wall 8A comprising a central hole for passage of the threaded shank of the screw 9, the head of which rests on the inner face of said base wall 8A.

A hole 16 for passage of the pin 7 is provided in the lateral wall of the head 8.

The movable element 11, which is cylindrical in the example, has a hole 17 for passage of the pin 7, this hole preferably having a greater diameter than the hole 16 provided in the head 8.

Lowerly, the movable element 11 comprises an annular groove 18 for housing one end of the spring 10; upperly, the element comprises a projection 19 for its snap-connection to the knob 13. The movable element 11 is shaped such that when inserted into the head 8 and the spring 10 exerts an upward thrust, it can still be pushed downwards against the spring so that the two holes 16 and 17 become coaxial and the pin 7 can be inserted through them. From a

lower portion of the wall 17A defining the hole 17 there projects into the hole a locking element 17B (Figure 2C). This latter cooperates with annular grooves 7B, C, D provided in the pin 7 in order both to lock the pin and to allow it to be rapidly and precisely positioned.

The knob 13 advantageously comprises an annular groove 19A for the upper edge 8B of the head 8, and a seat for snap-housing the projection 19 on the movable element.

10

The clamping member is very easily and quickly assembled. The screw 9 is firstly inserted into the head 8, followed by the spring 10 and the movable element 11. While then pressing the movable element 11 downwards against the spring 10, the pin 7 is inserted through the holes 16, 17. The circlip 12 is then inserted to snap into an annular groove 8C in the inner wall of the seat 15 for the head 8. The circlip 12 prevents the element 11 escaping from the head 8. Finally the knob 13 is snap-fitted onto the movable element 11. When the clamping member has been mounted, to insert the pin 7 through the head 8 and secure it thereto it is necessary merely to push the knob 13 downwards against the spring 10, so that the hole 16 in the movable element 11 and the hole 17 in the head 8 become aligned to allow passage of the pin 7. Then on releasing the knob 13 the pin remains reliably secured to the head 8 by the action of the spring 10. To improve the locking of the pin and facilitate its positioning, the pin comprises the plurality of annular grooves 7B-D. On snapping into one of the grooves 7B-D the locking element 17B on the one hand effectively locks the pin while on the other hand "advising" that the pin has been positioned at a precise distance. In this respect, each groove 7B-D corresponds to a precise distance of the end 7E of the pin from the clamping member. In this manner, pin positioning is extremely simple compared with known clamping members and pins.

20

30

It should be noted that the principle of operation is quite different from that of clamping members of the prior art. In this respect the pin 7 is always stably secured to the head 8. The

5

knob 13 is used only to enable the pin to be connected to the head, and not to clamp the pin to the head as in known members. In this manner it is no longer possible for the connection between the pin and head to slacken either with the passage of time or by error.

Figures 3A-C show a clamping member incorporating both "elastic" clamping means of type similar to those described heretofore (parts in common with the preceding embodiment are indicated by the same numbers), and clamping means of traditional type, comprising a screw 20 rigidly fixed to a handwheel 21. The screw 20 is arranged to penetrate into a threaded hole 22 provided in the lower end of the head 8D and communicating with a hole 23 for the insertion of a second pin 7A. The pin 7A is locked to the head 8 by tightening the screw 20. In a preferred embodiment, the passage holes for the two pins 7, 7A lie at an angle to each other.

Figures 4A-C show a clamping member comprising at both ends of the head 8E elastic clamping means of identical type to those described heretofore (those parts already described are indicated in Figures 4A-C by the previously used numbers).

Using the clamping members shown in Figures 3A-C and 4A-C, cross-shaped support structures can be constructed for the guide elements or other components of the conveyor.

Advantageously, the heads 8, 8D, 8E, the movable elements 11 and the knobs 13 are formed from a conventional plastic suitable for the purpose, such as polyamide.

The head 8 could also be formed in one piece with the arm 6 (Figures 1 and 2A) as shown schematically in Figure 1 and indicated by the arrow B.

Finally it should be noted that the aforescribed embodiments are provided by way of example only, and that numerous modifications are possible all falling within the same inventive concept. For example the movable element 11 or the heads 8, 8D, 8E could be

6

shaped differently and/or the spring 10 could be replaced by another conventional elastic element.

WHAT IS CLAIMED IS:

1. A clamping member (5) comprising at least one support pin (7) for mounting components of belt conveyors (1), the clamping member (5) further comprises a head (8, 8D, 8E), having a seat (15) and a hole (16) provided in a lateral wall of said head (8, 8D, 8E) for the passage of said pin (7) and securing means (10-13) for removably securing said pin (7) to said head (8, 8D, 8E), characterised in that said securing means (10-13) comprises an element (11) movable in said seat (15) and having a hole (17) for the passage of said pin (7),
10 an elastic element (10) housed in said head (8, 8D, 8E) and arranged to urge said movable element (11) in a direction to secure that portion of said pin (7) which has been inserted through said aligned holes (16, 17) against walls of said holes (16, 17), and a knob (13) connected to said movable element (11) and projecting from said head (8, 8D, 8E) to enable said movable element (11) to be pushed against the action of said elastic element (10) allowing said pin (7) to be withdrawn from said holes (16, 17), the pin (7) comprises at least one annular groove (7B-D) and said movable element (11) comprises a single locking element (17B) projecting from the wall (17A) defining said hole (17) to cooperate with said at least one annular groove (7B-D) of said pin (7) to lock
20 and facilitate the positioning of said pin (7) relative to said head (8, 8D, 8E).
2. The clamping member as claimed in claim 1, characterised in that the securing means comprise an element (12) for limiting the movement of the movable element (11) within the head (8, 8E, 8D).
3. The clamping member as claimed in claim 1, characterised in that the head (8, 8D, 8E) and the movable element (11) comprise guide elements (14, 14A) allowing the movable element (11) to move only coaxially to the head (8, 8D, 8E).

4. The clamping member as claimed in any one of claims 1 to 3, characterised in that the head (8) is formed in one piece with a support arm (6).
5. The clamping member as claimed in any one of claims 1 to 2, characterised by comprising means (1) for its fixing to a support arm (6).
6. The clamping member as claimed in claim 1, characterised by comprising further means (22, 23, 20, 21) for securing a further pin (7A), said further means being of a screw type.
7. The clamping member as claimed in claim 1, characterised by comprising two means (10, 11, 12, 13) for securing two pins (7, 7A), said means being
10 provided at opposite ends of the head (8E).
8. The clamping member as claimed in any one of claims 6 to 7, characterised in that the passage holes for the two pins (7, 7A) lie at an angle to each other.




Fig. 1




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 3A




Fig. 3B




Fig. 3C





Fig. 4A




Fig. 4B




Fig. 4C




Fig. 5

