



(22) **Date de dépôt/Filing Date:** 2013/02/27

(41) **Mise à la disp. pub./Open to Public Insp.:** 2013/09/08

(45) **Date de délivrance/Issue Date:** 2020/06/30

(30) **Priorité/Priority:** 2012/03/08 (US61/608,584)

(51) **Cl.Int./Int.Cl.** **A47G 1/02** (2006.01),
A45D 42/10 (2006.01), **A45D 42/12** (2006.01),
A47G 1/24 (2006.01), **F21V 33/00** (2006.01)


(72) **Inventeurs/Inventors:**
YANG, FRANK, US;
WOLBERT, DAVID, US;
SANDOR, JOSEPH, US;
CARDENAS, ORLANDO, US;
BUSHROE, FREDERICK, US

(73) **Propriétaire/Owner:**
SIMPLEHUMAN, LLC, US

(74) **Agent:** SMART & BIGGAR LLP

(54) **Titre : MIROIR DE MEUBLE-COIFFEUSE**

(54) **Title: VANITY MIRROR**



(57) **Abrégé/Abstract:**

A mirror assembly can include a housing, a mirror, and a light source. In certain embodiments, the mirror includes a light pipe configured to emit a substantially constant amount of light along a periphery of the mirror. In some embodiments, the mirror assembly includes a sensor assembly. The sensor assembly can be configured to adjust the amount of emitted light based on the position of a user in relation to the mirror. Certain embodiments of the mirror include an algorithm to adjust light based on the position of a user relative to the mirror, the level of ambient light, and/or the activation of different light modes.

VANITY MIRROR**ABSTRACT OF THE DISCLOSURE**

5 A mirror assembly can include a housing, a mirror, and a light source. In certain
embodiments, the mirror includes a light pipe configured to emit a substantially constant
amount of light along a periphery of the mirror. In some embodiments, the mirror assembly
includes a sensor assembly. The sensor assembly can be configured to adjust the amount of
emitted light based on the position of a user in relation to the mirror. Certain embodiments
of the mirror include an algorithm to adjust light based on the position of a user relative to the
10 mirror, the level of ambient light, and/or the activation of different light modes.

VANITY MIRROR

BACKGROUND

Field

5 The present disclosure relates to reflective devices, such as mirrors.

Description of the Related Art

 Vanity mirrors are mirrors that are typically used for reflecting an image of a user during personal grooming, primping, cosmetic care, or the like. Vanity mirrors are available in different configurations, such as free-standing mirrors, hand-held mirrors, mirrors
10 connected to vanity tables, bathroom wall mirrors, car mirrors, and/or mirrors attached to or produced by electronic screens or devices.

 Many vanity mirrors distort the reflected image because of, for example, poor quality reflective surfaces, harsh light sources, and/or uneven distribution of light. Additionally, the light sources of conventional vanity mirrors are typically energy inefficient. Further, the light
15 sources of conventional vanity mirrors are not adjustable or are difficult to effectively adjust.

SUMMARY

 In some embodiments, a mirror assembly comprises a base, a reflective face connected with the base, a sensor (e.g., a proximity sensor or a reflective type sensor), an
20 electronic processor, and a light source. In some implementations, the sensor is configured to detect, and generate a signal indicative of, the distance between an object and the sensor. The electronic processor can be configured to receive the signal from the sensor and can control the light source, for example, by varying the quantity or quality of light emitted by the light source depending on the detected distance between the object and the sensor.

25 In some embodiments, a mirror assembly comprises a base, a reflection face, one or more light sources, and a light-conveying pathway such as a light pipe. In combination, the light sources and light pipe reflect substantially constant light along a length of the light pipe. For example, in certain embodiments, the light conveying pathway is generally disposed around some, substantially all, or all of a periphery of the reflection face.

Certain aspects of this disclosure are directed toward a mirror assembly. The mirror assembly can include a mirror coupled with the housing portion, and a light source disposed at a periphery of the mirror. The mirror assembly can include a light path, such as a light pipe, having a length and positioned around at least a portion of the periphery of the mirror.

5 The mirror assembly can include a light scattering region, such as a plurality of light scattering elements disposed along the length of the light pipe. The light scattering elements can have a pattern density that varies depending, at least in part, on the distance along the light path from the light source. The light scattering elements can be configured to encourage a portion of the light impacting the light scattering elements to be emitted out of the light path along a desired portion of the length of the light path. The amount of light scattering
10 elements on the light path can vary depending, at least in part, on the distance along the light path from the light source. In certain embodiments, the pattern density can be less dense in a region generally adjacent the light source and more dense in a region spaced away from, or generally opposite from, the light source along the periphery of the mirror, thereby scattering
15 the light to a greater degree as the intensity of the light diminishes further from the light source, and facilitating a substantially constant amount of light emitted along the length of the light pipe.

Any of the vanity mirror features, structures, steps, or processes disclosed in this specification can be included in any embodiment. The light scattering elements in the region
20 generally adjacent the light source can be smaller compared to the light scattering elements in the region spaced from, or generally opposite from, or generally furthest from, the light source. The light source can be positioned near an upper portion of the mirror. The light pipe can be disposed along substantially all of the periphery of the mirror. The light source can emit light in a direction generally orthogonal to a standard viewing direction of the mirror. The light pipe can be generally circular and can include a first end and a second end.
25 The light source can emit light into the first end, and another light source can emit light into the second end. In some embodiments, the light scattering elements can be generally uniformly distributed along at least a portion of the light pipe.

Certain aspects of this disclosure are directed toward a mirror assembly including a mirror coupled with a housing portion and one or more light sources disposed at a periphery of the mirror. The one or more light sources can be configured to emit light in a direction generally orthogonal to a primary viewing direction of the mirror. The light pipe can have a length and can be disposed along substantially all of the periphery of the mirror. The light pipe can be configured to receive light from the one or more light sources and distribute the light generally consistently along the length, thereby providing a generally constant level of illumination to the periphery of the mirror.

Any of the vanity mirror features, structures, steps, or processes disclosed in this specification can be included in any embodiment. The one or more light sources can include a first light source configured to project light in a first direction around the periphery of the mirror and a second light source configured to project light in a second direction around the periphery of the mirror. The one or more light sources can be two light sources. Each of the light sources can use less than or equal to about three watts of power. The one or more light sources can have a color rendering index of at least about **90**. The one or more light sources can include light emitting diodes. The light pipe can be configured to transmit at least about **95%** of the light emitted from the one or more light sources.

Certain aspects of this disclosure are directed toward methods of manufacturing a mirror assembly, such as any of the mirror assemblies disclosed in this specification. The methods can include coupling a mirror and a housing portion. The method can include disposing a light source at a periphery of the mirror. The method can include positioning a light pipe around at least a portion of the periphery of the mirror. The method can include disposing a plurality of light scattering elements along the length of a light pipe. In certain embodiments, the plurality of light scattering elements can have a pattern density. The light scattering elements can be configured to encourage a portion of the light impacting the light scattering elements to be emitted out of the light pipe. The pattern density can be less dense in a region generally adjacent the light source, and the pattern density can be more dense in a region generally opposite from, spaced from, or furthest from, the light source along the periphery of the mirror, thereby facilitating a substantially constant amount of light emitted

along the length of the light pipe. In certain embodiments, the method can include positioning the light source near an upper portion of the mirror. In certain embodiments, the method can include disposing the light pipe around substantially all of the periphery of the mirror. In certain embodiments, the method can include positioning the light source to emit
5 light in a direction generally orthogonal to a main viewing direction of the mirror. In certain embodiments, the method can include positioning the light source to emit light into a first end of the light pipe and positioning another light source to emit light into a second end of the light pipe. In certain embodiments, the method can include disposing the light scattering elements in a generally uniform pattern along at least a portion of the light pipe.

10 In one embodiment, there is provided a mirror assembly including: a housing portion; a mirror coupled with the housing portion; one or more light sources; a proximity sensor configured to detect an object within a sensing region, the proximity sensor configured to generate a signal indicative of a distance between the object and the proximity sensor; and an electronic processor configured to generate an electronic signal to the one or more light
15 sources for emitting a level of light that varies depending on the distance between the object and the sensor.

In another embodiment, there is provided a method of manufacturing a mirror assembly. The method involves: coupling a mirror with a housing portion; disposing one or more light sources at a periphery of the mirror; configuring a proximity sensor to generate a
20 signal indicative of a distance between an object and the proximity sensor; and configuring an electronic processor to generate an electronic signal to the one or more light sources for emitting a level of light that varies depending on the distance between the object and the sensor.

25 In another embodiment, there is provided a mirror assembly including: a housing portion; a mirror coupled with the housing portion; one or more light sources disposed at a periphery of the mirror; a proximity sensor configured to detect an object within a sensing region, the proximity sensor configured to generate a signal indicating that the object is within a predetermined distance from the proximity sensor; and an electronic processor

configured to generate an electronic signal to the one or more light sources for emitting light when the object is within the predetermined distance from the proximity sensor.

5 In another embodiment, there is provided a mirror assembly configured to provide an illuminated reflection of a user. The mirror assembly includes: a mirror; at least one light source disposed at a periphery of the mirror; a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity; a reflective surface positioned along the light-conveying pathway; a sensor configured to detect the presence of a user in front of the mirror assembly; and a controller in electrical communication with the sensor. The controller is configured to actuate the light source to illuminate the user when the sensor detects the presence of the user in front of the mirror assembly and to deactivate the light source upon a predetermined delay after the sensor no longer detects the presence of a user in front of the mirror assembly.

15 In another embodiment, there is provided a mirror assembly configured to provide an illuminated reflection of a user. The mirror assembly includes: a mirror; at least one light source disposed at a periphery of the mirror; a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity; a reflective surface positioned along the light-conveying pathway; a sensor configured to detect the presence of a user in front of the mirror assembly; and a controller in electrical communication with the sensor. The controller is configured to actuate the light source to illuminate the user when the sensor detects the presence of the user in front of the mirror assembly and to deactivate the light source after the sensor no longer detects the presence of a user in front of the mirror assembly. The controller is configured to communicate wirelessly with a computer outside of the mirror assembly to adjust a color of light emitted by the at least one light source.

20 In another embodiment, there is provided a combination of the mirror assembly described above and the computer outside of the mirror assembly.

In another embodiment, there is provided a mirror assembly. The mirror assembly comprises: a housing portion; a mirror; one or more light sources disposed at a periphery of

the mirror; a proximity sensor configured to detect an object within a sensing region, the proximity sensor configured to generate a signal indicating that the object is within a predetermined distance from the proximity sensor; and an electronic processor configured to generate an electronic signal to the one or more light sources for emitting light when the processor receives the signal from the proximity sensor indicating that the object is within the predetermined distance from the proximity sensor. When the proximity sensor detects the object, the size or width of a sensitivity zone is temporarily increased in order for the proximity sensor and the electronic processor to trigger or to maintain the light source in an active state.

In another embodiment, there is provided a mirror assembly. The mirror assembly comprises: a mirror; at least one light source disposed at a periphery of the mirror that emits light; a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity; a sensor configured to detect the presence of a user in front of the mirror assembly; a reflective surface positioned along the light-conveying pathway; and a controller in electrical communication with the sensor. Upon the sensor detecting the presence of the user in front of the mirror assembly, the controller activates the at least one light source to illuminate the user. Upon activation of the at least one light source, the controller gradually increases a level of light emitted from the at least one light source.

In another embodiment, there is provided a mirror assembly. The mirror assembly comprises: a mirror; at least one light source disposed at a periphery of the mirror that emits light; a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity; a sensor configured to detect ambient light; a reflective surface positioned along the light-conveying pathway; and a controller configured to activate the at least one light source and to deactivate the at least one light source. A brightness of the emitted light is affected by a level of the detected ambient light. When ambient light is at a first ambient brightness level, the controller causes the light emitted from the at least one light source to be emitted at a first emitted brightness level, and when ambient light is at a second ambient

brightness level, the controller causes the light emitted from the at least one light source to be emitted at a second emitted brightness level that is brighter than the first emitted brightness level.

5 In another embodiment, there is provided a mirror assembly configured to provide an illuminated reflection of a user. The mirror assembly comprises: a mirror; at least one light source disposed at a periphery of the mirror; a light-conveying pathway configured to receive light from the at least one light source and to convey substantially constant light along a periphery of the mirror; a sensor configured to detect the presence of a user in front of the mirror assembly; and a controller in electrical communication with the sensor, the controller
10 being configured to activate the at least one light source to illuminate the user when the sensor detects the presence of the user in front of the mirror assembly. After the sensor detects the presence of the user, the sensor is configured to have increased sensitivity.

15 For purposes of summarizing the disclosure, certain aspects, advantages and features of the inventions have been described herein. It is to be understood that not necessarily any or all such advantages are achieved in accordance with any particular embodiment of the inventions disclosed herein. No aspects of this disclosure are essential or indispensable.

BRIEF DESCRIPTION OF THE DRAWINGS

The above-mentioned and other features of the mirror assembly disclosed herein are described below with reference to the drawings of certain embodiments. The illustrated
5 embodiments are intended to illustrate, but not to limit the present disclosure. The drawings contain the following Figures:

Figure 1 illustrates a perspective view of an embodiment of a mirror assembly.

Figure 2 illustrates a front view of the embodiment of Figure 1.

Figures 3 and 4 illustrate side views of the embodiment of Figure 1.

10 Figure 5 illustrates a top view of the embodiment of Figure 1.

Figure 6 illustrates a bottom view of the embodiment of Figure 1.

Figure 7 illustrates a rear view of the embodiment of Figure 1.

Figure 8A illustrates an exploded view of an embodiment of the mirror assembly.

15 Figure 8B illustrates an exploded view of another embodiment of the mirror assembly.

Figure 9 illustrates an enlarged view of the embodiment of Figure 8A showing a sensor assembly.

Figure 10 illustrates an enlarged view of the embodiment of Figure 8B showing a rear side of a sensor assembly.

20 Figure 11 illustrates a light conveying pathway of the embodiment shown in Figure 1.

Figures **11A-11B** illustrate enlarged views of portions of the light conveying pathway shown in Figure **11**.

Figure **12** illustrates an enlarged view of the embodiment of Figure **1** showing a partially exploded view of a base portion.

5 Figure **13** illustrates a block diagram of an embodiment of an algorithm that can be carried-out by components of the mirror assembly of Figure **1**.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

10 Certain embodiments of a mirror assembly are disclosed in the context of a portable, free-standing vanity mirror, as it has particular utility in this context. However, the various aspects of the present disclosure can be used in many other contexts as well, such as wall-mounted mirrors, mirrors mounted on articles of furniture, automobile vanity mirrors (e.g., mirrors located in sun-visors), and otherwise. None of the features described herein are essentially or indispensable. Any feature, structure, or step disclosed herein can be replaced with or combined with any other feature, structure, or step disclosed herein, or omitted.

15 As shown in Figures **1-7**, the mirror assembly **2** can include a housing portion **8** and a visual image reflective surface, such as a mirror **4**. The housing portion **8** can include a support portion **20**, a shaft portion **12**, and/or a base portion **14**. The housing portion **8** can also include a pivot portion **16** connecting the support portion **20** and the shaft portion **12**. Certain components of the housing portion **8** can be integrally formed or separately formed and connected together to form the housing portion **8**. The housing **8** can include plastic, stainless steel, aluminum, or other suitable materials.

20 The mirror assembly **2** can include one or more of the components described in connection with Figures **8A** and **8B**. Figure **8B** illustrates a mirror assembly **102** including many components similar to the mirror assembly **2** components. The similar components include similar reference numbers in the **100s** (e.g., mirror **4** can be similar to mirror **104**).

25 The mirror **4** can include a generally flat or generally spherical surface, which can be convex or concave. The radius of curvature can depend on the desired optical power. In some embodiments, the radius of curvature can be at least about **15** inches and/or less than or equal to about **30** inches. The focal length can be half of the radius of curvature. For

example, the focal length can be at least about **7.5** inches and/or less than or equal to about **15** inches. In some embodiments, the radius of curvature can be at least about **18** inches and/or less than or equal to about **24** inches. In some embodiments, the mirror **4** can include a radius of curvature of about **20** inches and a focal length of about **10** inches. In some
5 embodiments, the mirror **4** is aspherical, which can facilitate customization of the focal points.

In some embodiments, the radius of curvature of the mirror **4** is controlled such that the magnification (optical power) of the object is at least about **2** times larger and/or less than or equal to about **7** times larger. In certain embodiments, the magnification of the object is
10 about **5** times larger. In some embodiments, the mirror can have a radius of curvature of about **19** inches and/or about **7** times magnification. In some embodiments, the mirror can have a radius of curvature of about **24** inches and/or about **5** times magnification.

As shown in Figure **8A**, the mirror **4** can have a generally circular shape. In other embodiments, the mirror **4** can have an overall shape that is generally elliptical, generally
15 square, generally rectangular, or any other shape. In some embodiments, the mirror **4** can have a diameter of at least about **8** inches and/or less than or equal to about **12** inches. In some embodiments, the mirror **4** can have a diameter of about **8** inches. In certain embodiments, the mirror **4** can have a diameter of at least about **12** inches and/or less than or equal to about **16** inches. In some embodiments, the mirror **4** can include a thickness of at
20 least about **2** mm and/or less than or equal to about **3** mm. In some embodiments, the thickness is less than or equal to about two millimeters and/or greater than or equal to about three millimeters, depending on the desired properties of the mirror **4** (e.g., reduced weight or greater strength). In some embodiments, the surface area of the mirror **4** is substantially greater than the surface area of the base **14**. In other embodiments, the surface area of the
25 image-reflecting surface of the mirror **4** is greater than the surface area of the base **14**.

The mirror **4** can be highly reflective (e.g., has at least about **90%** reflectivity). In some embodiments, the mirror **4** has greater than about **70%** reflectivity and/or less than or equal to about **90%** reflectivity. In other embodiments, the mirror **4** has at least about **80%** reflectivity and/or less than or equal to about **100%** reflectivity. In certain embodiments, the

mirror has about **87%** reflectivity. The mirror **4** can be cut out or ground off from a larger mirror blank so that mirror edge distortions are diminished or eliminated. One or more filters can be provided on the mirror to adjust one or more parameters of the reflected light. In some embodiments, the filter comprises a film and/or a coating that absorbs or enhances the reflection of certain bandwidths of electromagnetic energy. In some embodiments, one or more color adjusting filters, such as a Makrolon filter, can be applied to the mirror to attenuate desired wavelengths of light in the visible spectrum.

The mirror **4** can be highly transmissive (e.g., nearly **100%** transmission). In some embodiments, transmission can be at least about **90%**. In some embodiments, transmission can be at least about **95%**. In some embodiments, transmission can be at least about **99%**. The mirror **4** can be optical grade and/or comprise glass. For example, the mirror **4** can include ultra clear glass. Alternatively, the mirror **4** can include other translucent materials, such as plastic, nylon, acrylic, or other suitable materials. The mirror **4** can also include a backing including aluminum or silver. In some embodiments, the backing can impart a slightly colored tone, such as a slightly bluish tone to the mirror. In some embodiments, an aluminum backing can prevent rust formation and provide an even color tone. The mirror **4** can be manufactured using molding, machining, grinding, polishing, or other techniques.

The mirror assembly **2** can include one or more light sources **30** configured to transmit light. For example, as shown in Figure **9**, the mirror assembly can include a plurality (e.g., two) of light sources **30**. Various light sources **30** can be used. For example, the light sources **30** can include light emitting diodes (LEDs), fluorescent light sources, incandescent light sources, halogen light sources, or otherwise. In some embodiments, each light source **30** consumes at least about **2** watts of power and/or less than or equal to about **3** watts of power. In certain embodiments, each light source **30** consumes about **2** watts of power.

In certain embodiments, the width of each light source can be less than or equal to about **10.0** mm. In certain embodiments, the width of each light source can be less than or equal to about **6.5** mm. In certain embodiments, the width of each light source can be less

than or equal to about **5.0** mm. In certain embodiments, the width of each light source can be about **4.0** mm.

The light sources **30** can be configured to mimic or closely approximate natural light with a substantially full spectrum of light in the visible range. In some embodiments, the light sources **30** have a color temperature of greater than or equal to about **4500** K and/or less than or equal to about **6500** K. In some embodiments, the color temperature of the light sources **30** is at least about **5500** K and/or less than or equal to about **6000** K. In certain embodiments, the color temperature of the light sources **30** is about **5700** K.

In some embodiments, the light sources **30** have a color rendering index of at least about **70** and/or less than or equal to about **90**. Certain embodiments of the one or more light sources **30** have a color rendering index (CRI) of at least about **80** and/or less than or equal to about **100**. In some embodiments, the color rendering index is high, at least about **87** and/or less than or equal to about **92**. In some embodiments, the color rendering index is at least about **90**. In some embodiments, the color rendering index can be about **85**.

In some embodiments, the luminous flux can be at least about **80** lm and/or less than or equal to about **110** lm. In some embodiments, the luminous flux can be at least about **90** lm and/or less than or equal to about **100** lm. In some embodiments, the luminous flux can be about **95** lm.

In some embodiments, the forward voltage of each light source can be at least about **2.4** V and/or less than or equal to about **3.6** V. In some embodiments, the forward voltage can be at least about **2.8** V and/or less than or equal to about **3.2** V. In some embodiments, the forward voltage is about **3.0** V.

In some embodiments, the illuminance at an outer periphery of the sensing region is at least about **500** lux and/or less than or equal to about **1000** lux. The illuminance level can be higher at a distance closer to the face of the mirror. In some embodiments, the illuminance at an outer periphery of the sensing region is about **700** lux. In some embodiments, the illuminance at an outer periphery of the sensing region is about **600** lux. In some embodiments, the sensing region extends about **8** inches away from the face of the mirror. Many other sensing regions can also be utilized, some of which are described below. In

certain variants, the mirror assembly **2** can include a dimmer to adjust the intensity of the light.

In some embodiments, the light sources **30** are configured to provide multiple colors of light and/or to provide varying colors of light. For example, the light sources **30** can provide two or more discernable colors of light, such as red light and yellow light, or provide an array of colors (e.g., red, green, blue, violet, orange, yellow, and otherwise). In certain embodiments, the light sources **30** are configured to change the color or presence of the light when a condition is met or is about to be met. For example, certain embodiments momentarily change the color of the emitted light to advise the user that the light is about to be deactivated.

As shown in Figure **9**, the light sources can be positioned near the uppermost region of the mirror assembly **2**. In other embodiments, the light sources **30** are positioned at other portions of the mirror assembly **2**, such as, within the light pipe **10** or directly mounted to the mirror **4** at spaced-apart intervals around the periphery of the mirror **4**. For example, the light sources **30** can be positioned around some, substantially all, or all of the periphery of the mirror **4**. In certain embodiments, the light sources **30** is separate from and does not connect with the mirror assembly **2**.

The light sources **30** can be positioned in various orientations in relation to each other, such as side-by-side, back-to-back, or otherwise. In certain embodiments, the light sources **30** can be positioned to emit light in opposing directions. For example, as shown in Figure **9**, a first light source **30a** projects light in a first direction (e.g., clockwise) around the periphery of the mirror **4**, and a second light source **30b** projects light in a second direction (e.g., counter-clockwise) around the periphery of the mirror **4**. In certain embodiments, the light sources **30** can be positioned to emit light generally orthogonally to the viewing surface of the mirror assembly **2**. In certain embodiments, the light sources **30** can be positioned to emit light tangentially in relation to the periphery of the mirror **4**.

The mirror assembly **2** can include a mechanism to actively or passively dissipate, transfer, or radiate heat energy away from the light sources **30**, such as a fan, vent, and/or one or more passive heat dissipating or radiating structures **34**. The support portion **20** can

include a receiving portion **22** near an upper region of the mirror assembly **2** for receiving a heat dissipating structures **34**. The heat dissipating structures **34** can formed of materials with a high rate of heat conduction, such as aluminum or steel, to help remove heat from the mirror assembly that is generated by the light sources **30**. Many other heat dissipating materials, such as copper or brass, can be used.

The heat dissipating structures **34** can dissipate heat created by the light sources **30** and/or conduct electricity to the light sources. The heat dissipating structures **34** that both dissipate heat and conduct electricity to the light sources **30** reduce the total number of necessary components. In some embodiments, as illustrated, the heat dissipating structure **34** can include one or more components that are generally comparatively long in one dimension, generally comparatively wide in another dimension, and generally comparatively narrow in another dimension, to provide a large surface area over a thin surface to conduct heat efficiently through the heat dissipating structure **34** and then readily transfer such heat into the surrounding air and away from heat-sensitive electronic components in the mirror assembly. For example, the length of the heat dissipating structure **34** can be substantially greater than the width of the heat dissipating structure **34**, and the width of the heat dissipating structure **34** can be substantially greater than the thickness.

The heat dissipating structures **34** can be electrically connected circuit boards and/or provides electric power and signals to the light sources **30** attached directly or indirectly thereto. In some embodiments, the temperature of the light sources **30** with the heat dissipating structures **34** is less than or equal to about 70° F. In some embodiments, the temperature of the light sources **30** with the heat dissipating structures **34** is between about 50° F and 60° F.

As shown in Figure **8A**, the heat dissipating structure **34** can be a single structure including a support panel **34c** positioned substantially parallel to the mirror **4**. In some embodiments, the support panel **34c** is a circuit board. The heat dissipating structure **34** can also include one or more fins mounted to the support panel **34c**. As shown in Figure **8A**, the heat dissipating structure **34** can include two fins **34a**, **34b**. The fins **34a**, **34b** can be positioned between the support panel **34c** and the mirror **4**. The fins **34a**, **34b** can also be

positioned such that the first ends of each of the fins **34a'**, **34b'** are closer together than the second ends of the fins **34a''**, **34b''** (e.g., V-shaped). The fins **34a**, **34b** can be directly or indirectly connected to the light sources **30**. For example, each fin **34a**, **34b** can receive a light source **30**.

5 As shown in Figure **8B**, the heat dissipating structures **134a**, **134b** can be separate components. Similar to Figure **8A**, the heat dissipating structures **134a**, **134b** can be positioned such that the first ends of each of the structures **134a'**, **134b'** are closer together than the second ends of the fins **134a''**, **134b''** (e.g., generally V-shaped). The structures **134a**, **134b** can be directly or indirectly connected to the light sources **130**. For example,
10 each of the structures **134a**, **134b** can receive a light source **130**.

Figure **10** shows a rear side of the mirror assembly **102** without a rear cover portion **118**. The second end of each of the heat dissipating structures **134a''**, **134b''** can be positioned between the first end **140a** and the second end **140b** of the light pipe and on either side of the sensor assembly **128**. The heat dissipating structures **134a**, **134b** can be positioned
15 behind the support structure **120**. For example, the heat dissipating structures **134a**, **134** can be positioned between a circuit board **170** and the rear cover portion (not shown). The support portion **120** can also include one or more clasps **172** or other structures for engaging the circuit board **170**.

The support portion **20** can support the mirror **4** and a light conveying structure, such
20 as a light pipe **10**, positioned around at least a portion of a periphery of the mirror **4**. In some embodiments, the light pipe **10** is positioned only along an upper portion of mirror **4** or a side portion of the mirror **4**. In other embodiments, the light pipe **10** extends around at least majority of the periphery of the mirror **4**, substantially the entire periphery of the mirror **4**, or around the entire periphery of the mirror **4**. As shown in Figure **8A**, the support portion **20**
25 can include a structure, such as a ridge **21**, which can support the light pipe **10** (e.g., a portion of the light pipe **10** can be disposed along the ridge **21**).

Some or all of the light from the light sources **30** can be transmitted generally toward, or into, the light pipe **10**. For example, as shown in Figure **8A**, the light pipe **10** can include ends **40a**, **40b**, and the light sources **30** can emit light into one or both of the ends **40a**, **40b** of

the light pipe **10**. The light sources **30** can be positioned such that the light is emitted generally toward a user facing the viewing surface of the mirror assembly **2**. For example, some or all of the light from the light sources **30** and/or the light pipe **10** can be emitted toward, and reflected off of, another component before contacting the user. In some
5 embodiments, the light sources **30** are positioned behind the mirror **4** (e.g., creating a backlighting effect of the mirror **4**). In some embodiments, the light sources **30** are positioned (e.g., by tilting) such that light emitted from the light sources **30** contacts the viewing surface of the mirror assembly **2** at an angle, such as an acute angle. In some
10 embodiments, the light sources **30** are positioned such that light emitted from the light sources **30** contacts the viewing surface of the mirror assembly **2** at an obtuse angle.

When installed on the support member **20**, the light pipe **10** has a radial width and an axial depth. Some variants have a radial width that is greater than or equal to the axial depth. In certain implementations, the light pipe **10** is configured to provide adequate area for the reflecting surface of the mirror **4** and to provide sufficient area for light to be emitted
15 from the light pipe **10**, as will be discussed in more detail below. For example, the ratio of the radial width of the light pipe **10** to the radius of the mirror **4** can be less than or equal to about: $1/5$, $1/15$, $1/30$, $1/50$, values in between, or otherwise.

As shown in Figure **8A**, the light pipe **10** can be substantially circularly shaped. The light pipe **10** can include a gap **44**, and the sensor assembly **28** and/or the light sources **30** can
20 be positioned in the gap **44**. In some embodiments, the light pipe **10** can be substantially linearly shaped, or the light pipe **10** has a non-linear and non-circular shape. The light pipe **10** can include acrylic, polycarbonate, or any other clear or highly transmissive material. The light pipe **10** can be at least slightly opaque.

The light can pass along and through a portion of the light pipe **10** and/or emit from
25 the light pipe **10** via an outer face **42** of the light pipe **10**. In some embodiments, the light pipe **10** is configured to transmit at least about 95% of the light emitted from the light sources **30**. The light sources **30** can be configured, in combination with light pipe **10**, to emit light generally around the periphery of the mirror **4**. The light pipe **10** can be configured to disperse light from the light sources **30** through the light pipe **10**. The light sources **30** and

the light pipe **10** can be configured such that the amount of light emitted from the outer face **42** is substantially constant along the length of the light pipe **10**. Many different ways of achieving a substantially constant intensity of conveyed light around the light pipe **10** can be used.

5 The support portion **20** and/or the light pipe **10** can include features to facilitate generally even or uniform diffusion, scattering, and/or reflection of the light emitted by the light sources **30** around the periphery of the mirror. For example, the support portion **20** and/or light pipe **10** can include an irregular anterior and/or posterior surface that is molded in a non-flat and/or non-planar way, etched, roughened, painted, and/or otherwise surface
10 modified. The light scattering elements can be configured to disperse a substantially constant amount of light along the periphery of the mirror **4**. These features can help achieve high energy-efficiency, reducing the total number of light sources necessary to light substantially the entire periphery of the mirror and reducing the temperature of the mirror assembly **2**.

 The light pipe **10** can comprise a generally translucent material with varying degrees
15 of scattering, such that the minimum amount of scattering occurs in a region near the light source(s) and the maximum scattering occurs in a region of the light pipe **10** that is located furthest from the light source(s). The light pipe **10** can comprise a region configured to scatter light in a varying manner. In some embodiments, the light conveying pathway or light
20 pipe **10** can comprise a varying, non-constant, non-smooth anterior, posterior, and/or interior surface formed from any suitable process, such as molding, etching, roughening painting, coating, and/or other methods. In some embodiments, one or more surface irregularities can be very small bumps, protrusions, and/or indentations.

 In some embodiments, light passing through the light pipe **10** can be scattered at a plurality of different intensity levels, depending on the location of the light within the light
25 pipe **10**. For example, light at a first location on the light pipe **10** can be scattered at a first intensity level, light at a second location on the light pipe **10** can be scattered at a second intensity level, and light at a third location on the light pipe **10** can be scattered at a third intensity level, with the third intensity level being more than the second intensity level, and the second intensity level being more than the first intensity level., etc. Many other levels of

scattering and many ways of spatially increasing or decreasing scattering can be used instead of or in addition to providing macro scattering elements, such as spatially varying a level of die or a frosting effect within the material of the light pipe **10**, or by spatially varying scattering particles embedded within the material, or by spatially varying a surface pattern on one or more outside surfaces of the material.

The light pipe **10** can include a surface pattern, such as light scattering elements **74** (e.g., a dot pattern) as shown in Figure **11**. The light scattering elements **74** can be configured to encourage a portion of the light passing through the light pipe **10** to exit the outer face **42** of the light pipe **10**, thereby generally illuminating the user in a generally even or generally uniform manner. The light scattering elements can be configured such that the light intensity emitted from the outer face **42** of the light pipe **10** is substantially constant along a substantial portion of, or virtually the entirety of, the length of the light pipe **10**. Accordingly, the user can receive generally constant light volume or intensity around the periphery of the mirror **4**. For example, the light scattering elements can include one or more of varied density, irregular patterns, or varied sizes.

As shown in Figure **11**, the light scattering elements **74** can be less dense near the light sources **30** (Figure **11B**), and become increasingly dense as a function of increased distance from the light sources **30** (Figure **11A**). Such a configuration can, for example, reduce the amount of light that is scattered or reflected (and thus exits the outer face **42**) in areas having generally increased light volume or light intensity, such as portions of the light pipe **10** that are near the light sources **30**. Further, such a configuration can encourage additional scattering or reflection (and thus increase the amount that exits the outer face **42**) in areas having generally decreased light volume or intensity, such as portions of the light pipe **10** that are spaced away from the light sources **30**. Accordingly, the mirror assembly **2** can avoid bright areas at some portions of the periphery of the mirror **4** and dark areas at other portions. The mirror assembly **2** can have a substantially constant amount of light emitted along some, substantially all, or all of the periphery of the mirror **4**.

The light scattering elements can be dispersed in an irregular pattern, such that the light scattering pattern in a first region is different than a light scattering pattern in a second

region. A distance between a first light scattering element and a second light scattering element can be different than a distance between a first light scattering element and a third light scattering element.

The sizes (e.g., the diameter) of the light scattering elements can be varied. In some variants, the light scattering elements near the light sources **30** can have a smaller size when compared to light scattering elements that are farther from the light sources **30**. For example, the light scattering elements can include a smaller diameter near the light sources **30** and become increasingly larger as a function of distance from the light sources **30**. Such a configuration allows substantially even reflection of light to the outer surface **42**. In certain embodiments, each light scattering element has a diameter of less than or equal to about one millimeter. In some embodiments, the light scattering elements each have a diameter greater than or equal to about one millimeter.

In some embodiments, the light scattering elements can be generally circular. In some embodiments, the light scattering elements have other shapes, such as generally square, generally rectangular, generally pentagonal, generally hexagonal, generally octagonal, generally oval, and otherwise. In certain embodiments, the pattern in the light pipe **10** is a series of lines, curves, spirals, or any other pattern. In certain embodiments, the light scattering elements are white. The light scattering elements can be dispersed such that the light pipe **10** appears frosted. In some embodiments, the light scattering elements are not easily visible to the user. For example, the light pipe **10** can be slightly opaque to conceal the appearance of the surface pattern. In some embodiments, the light scattering elements are visible to the user, the light pipe **10** can be clear to show the general color and pattern of the surface elements.

The light pipe **10** can include a reflective material to achieve high reflectivity. For example, the light pipe **10** can include a reflective backing material along the rear side of the light pipe. In some embodiments, the reflective material can reflect at least about **95%** of light. In some embodiments, the reflective material reflects about **98%** of light. The reflective material can be optically reflective paper.

As shown in Figure 8B, the mirror assembly **102** can also include a diffuser **156**. The diffuser **156** can be positioned on the surface of the light pipe **110** and/or around the periphery of the mirror **104**. For example, the diffuser **156** can be positioned between the light pipe **10** and the user to provide a diffuse, scattered light source, not a focused, sharp light source, which would be less comfortable on the user's eyes. In some embodiments, the transmissivity of the diffuser is substantially constant around its perimeter or circumference. In some embodiments, the diffuser **156** can surround a majority of the periphery of the mirror **104**, substantially the entire periphery of the mirror, or the entire periphery of the mirror. As shown in Figure 8B, the diffuser **156** can surround generally the same portion of the periphery of the mirror **104** as the light pipe **110**. The diffuser **156** can also include an opening **160** for the sensor assembly **128** and/or a receiving portion **157** for receiving the mirror **104**. The diffuser **156** can include an at least partially opaque material. For example, the diffuser **156** can include optical grade acrylic.

The diffuser **156** can include an irregular anterior and/or posterior surface formed from etching, roughening, painting, and/or other methods of surface modification. For example, the diffuser **156** can include a pattern of light scattering elements (not shown) created using any of the methods discussed herein. The light scattering elements can be modified to include any of the shapes and/or sizes discussed in connection with the light pipe **10**.

The light scattering elements can be configured to create soft light by further scattering the light. For example, the light scattering elements can include a plurality of dots having the same diameter or different diameters. In some embodiments, the light scattering elements can be evenly dispersed across the diffuser **156**. In other embodiments, the light scattering elements can be randomly dispersed across the diffuser **156**.

Returning to Figure 8A, a cover member **6** can cover the sensor assembly **28** and the light sources **30**. The cover member **6** can be clear and polished acrylic, polycarbonate, or any other suitable material. On the rear side, the housing **8** can include a rear cover portion **18**, which can be configured to at least partially enclose one or more components of the mirror assembly **2**. The rear cover portion **18** can include an aperture **32** through which the

pivot portion **16** can extend to engage with the support portion **20**. The rear cover portion **18** can also include one or more vents to further reduce the temperature. As shown in Figure 8B, the mirror assembly **102** can include a gasket **164** positioned between the support portion **120** and rear cover portion **118**.

5 As previously noted, the pivot portion **16** can connect the support portion **20** and the shaft portion **12**. The pivot portion **16** allows the mirror **4** to be pivoted in one or more directions (e.g., up, down, right, left, and/or in any other direction). For example, the pivot **16** can include a ball joint, one or more hinges, or otherwise.

10 The support portion **20** and the mirror **4** can be adjustable (e.g., slidably movable and/or rotatable) along an axis generally parallel to the surface of the mirror **4** and to the ground and/or along an axis generally parallel to the surface of the mirror **4** and perpendicular to the ground. For example, the shaft portion **12** can be adjustable (e.g., slidably movable and/or rotatable) along an axis generally parallel to the surface of the mirror **4** and perpendicular to the ground. The support portion **20** and the mirror **4** can also be rotatable
15 along an axis generally perpendicular from the surface of the mirror **4** (e.g., rotatable about the center of the mirror **4**). The housing portion **8** can also include additional pivot portions, such as along the shaft portion **12**.

20 To adjust the height of the mirror assembly **2**, the shaft portion **12** can be configured to translate generally perpendicular to the ground when the mirror assembly **2** is positioned on the base **14**. In some embodiments, the height of the shaft portion **12** can be adjusted within a range of at least about three inches and/or within a range less than four inches. In some embodiments, the height of the shaft portion **12** can be adjusted within about a four inch range. In some embodiments, the height of the shaft portion **12** can be adjusted within about a three inch range.

25 The shaft portion **12** can include a first shaft portion **12a** and a second shaft portion **12b**. The shaft portions **12a**, **12b** can be configured to adjustably engage each other, thereby allowing the user to select and maintain the mirror assembly **2** at a desired height. For example, the first shaft portion **12a** can include one or more biased adjustment structures, such as spring-loaded retractable pegs (not shown), and the second shaft portion **12b** can

include one or more corresponding adjustment structures, such as notches (not shown). The pegs of the first shaft portion **12a** can engage (e.g., snap into) with the notches of the second shaft portion **12b** to control provide articulating adjustment of the height of the mirror assembly **2**.

5 In some embodiments, the first shaft portion **12a** and the second shaft portion **12b** can form an interference fit. This applied pressure allows the first shaft portion **12a** and the second shaft portion **12b** to be stationary relative to each other (e.g. hold the support portion **20** in desired height) without external force being applied. However, the applied pressure between the shaft portions **12a** and **12b** can be controlled so that when the user wants to
10 adjust the height of the support portion **20**, the pressure can be overcome and shaft portions **12a** and **12b** can move relative to each other. For example, the amount of force required to downwardly or upwardly adjust the height or effective length of the shaft portion **12** can be greater than the downward force of gravity induced by the mass of the mirror assembly and upper shaft portion but generally less than or equal to a natural human adjustment force for an
15 appliance, such as less than or equal to about **3** or about **4** pounds. The sliding or adjustment of the height or effective length of the shaft components can be configured to stop virtually immediately when the user's adjustment force stops, without requiring further adjustments or securing structure to stop the sliding or to secure the components of the shaft portion against further unintended movement or change in height or length. The applied pressure can also
20 simulate a dampening effect during movement of the shaft portions **12a** and **12b**.

 The shaft portion **12** can also include a constraining member, such as ring member, that dampens or prevents the first shaft portion **12a** from moving relative to the second shaft portion **12b**. For example, certain variants of the ring member threadably engage with the second shaft portion **12b**, thereby radially compressing the second shaft portion **12b** against
25 the first shaft portion **12a**, which in turn inhibits the first shaft portion **12a** from translating relative to the second shaft portion **12b**. In certain implementations, loosening the ring member allows the user to adjust the height of the shaft portion **12**, while tightening the ring member secures the first shaft portion **12a** to the second shaft portion **12b**.

In some embodiments, the shaft portion **12** includes a connector, such as a set-screw (not shown), which can be positioned generally perpendicular to the first shaft portion **12a**. The second shaft portion **12b** can include an opening (not shown) through which the screw member can extend. In certain implementations, when the set-screw is loosened, the first shaft portion **12a** can be adjusted relative to the second shaft portion **12b**. Tightening the screw member until it contacts the first shaft portion **12a** can inhibit or prevent the first shaft portion **12a** from moving relative to the second shaft portion **12b**.

As shown in Figure **8B**, the shaft portion **112** can include one or more biasing members **154**, such as springs (e.g., spiral coil springs, wave springs, conical springs, or otherwise). In certain variants, the one or more biasing members **154** are configured to facilitate adjustment of the height of the shaft portion **112**. For example, the one or more biasing members **154** can reduce the amount of vertical force a user must exert to raise the height of the mirror **104** relative to the base **114**. The biasing members can be positioned in a lumen of the shaft portion **112**.

The shaft portion **12** can include plastic, stainless steel, aluminum, or other suitable materials. The first shaft portion **12a** can also include compressible materials, such as rubber, nylon, and plastics, on at least a portion of its outer surface that press against the inner surface of the second shaft portion **12b** when the first shaft portion **12a** is inserted into the second shaft portion **12b**.

A portion of the support portion **20** can be cantilevered outward from the longitudinal axis of the shaft portion **12**. Such a configuration can impart a moment of force on the mirror assembly **2**, which, if uncompensated for, could lead to tipping. The base portion **14** can also be configured to counteract such a moment. For example, the base portion **14** can include a weight that is sufficient to reduce substantially the likelihood of tipping of the mirror assembly **2**.

The base **14** and/or other portions of the mirror assembly **2** can be generally balanced in mass distribution such that the center of mass of the mirror assembly **2** is generally positioned near the shaft **12** and/or near the base **14**. The base portion **14** can weigh at least about **2 lbs.**, **4 lbs.**, **6 lbs.**, **8 lbs.**, **10 lbs.**, values in between, or otherwise. The base

portion **14** can also include one or more supporting feet or be configured to be semi-permanently mountable (e.g., to be mounted to a countertop with one or more fasteners).

In some embodiments, as illustrated, the base portion **14** can have a generally curved outer surface. For example, a horizontal cross-section of the base at a plurality of points along its height can be generally circular or generally elliptical. In the illustrated embodiment, the base portion **14** is generally conical, such as generally frusto-conical. The outer surface of the base can be generally smooth, generally tapered and/or generally sloping, as illustrated, and/or present a virtually entirely continuous surface generally circumscribing the periphery of the base **14**. The horizontal cross-sectional area or diameter of the top of the base **14** generally can be about the same as the horizontal cross-sectional area or diameter of the bottom of the shaft portion **12**. The horizontal cross-sectional area of the base **14** can generally continuously increase from the top region of the base **14** to the bottom region of the base **14**. For example, a horizontal cross-sectional area or diameter at the bottom region of the base **14** can be substantially larger than a horizontal cross-sectional area or diameter at the top region of the base **14** (e.g., at least about two or at least about three times larger), which is an example of a base **14** that can help resist tipping of the mirror. In some embodiments, as illustrated, the distance along the shaft portion **12** from the bottom of the mirror portion to the top of the base portion can be generally about the same as the height of the base portion **14**.

As discussed in further detail below, the base portion **14** can include a battery (e.g., a rechargeable battery). The weight and positioning of the battery can also reduce the chances of tipping of the mirror assembly **2**. In some embodiments, the battery can deliver power to the light sources for at least about ten minutes per day for about thirty days. The battery **26** can be recharged via a port **24** (e.g., a universal serial bus (USB) port or otherwise), as shown in Figure **12**. The port **24** can be configured to permanently or removably receive a connector coupled with a wire or cable (not shown). The port **24** can also be configured to allow electrical potential to pass between the batteries **26** with a power source via the connector. The port **24** may be used to program or calibrate different operations of the mirror

illumination or object sensing when connect to a computer. Other charging methods can be used, such as via conventional electric adapter to be plugged in to an electric outlet.

The mirror assembly **2** can include an indicator device configured to issue a visual, audible, or other type of indication to a user of the mirror assembly **2** regarding a characteristic of the mirror assembly **2**, the user, and/or the relationship between the mirror assembly **2** and the user. For example, the indicator can indicate on/off status, battery levels, imminent deactivation, and/or certain mode of operation. The indicator can be used for other purposes as well.

The color of the indicator light can vary depending on the indication. For example, the indicator can emit a green light when the mirror assembly is turned on and/or a red light when the battery is running low.

As shown in Figure **1**, the indicator **58** can ring-shaped and positioned around an upper portion of the base portion **14**. The indicator **58** can take on any other shape and be positioned around the support portion **20**, along the base portion **14**, or on any other location on the mirror assembly **2**.

The controller **50** controls the operation of a light sources **30**. The controller **50** can be disposed in the base **14** and can include one or a plurality of circuit boards (PCBs), which can provide hard wired feedback control circuits, a processor and memory devices for storing and performing control routines, or any other type of controller.

The mirror assembly **2** can include a sensor assembly **28**, as shown in Figures **2A** and **9**. The sensor assembly **28** can be positioned near an upper region of the mirror assembly **2** (e.g., the top of the mirror). For example, the sensor assembly **28** can be positioned in the gap **44** in the light pipe **10**. The sensor assembly **28** can also be recessed from the front surface of the mirror assembly **2**. Alternatively, the sensor assembly **28** can disposed along any other portion of the mirror assembly **2** or not positioned on the mirror assembly **2**. For example, the sensor assembly **28** can be positioned in any location in a room in which the mirror assembly **2** sits. The sensor assembly **28** can include a proximity sensor or a reflective-type sensor. For example, the sensor **28** can be triggered when an object (e.g., a body part) is moved into, and/or produces movement within, a sensing region.

The sensor assembly **28** can include a transmitter and a receiver. The transmitter **36** can be an emitting portion (e.g., electromagnetic energy such as infrared light), and the receiver **38** can be a receiving portion (e.g., electromagnetic energy such as infrared light). The beam of light emitting from the light emitting portion **36** can define a sensing region. In certain variants, the transmitter can emit other types of energy, such as sound waves, radio waves, or any other signals. The transmitter and receiver can be integrated into the same sensor or configured as separate components.

In some embodiments, the light emitting portion **36** can emit light in a generally perpendicular direction from the front face of the mirror assembly. In some embodiments, the light emitting portion **36** emits light at a downward angle from a perpendicular to the front face of the mirror assembly by at least about **5** degrees and/or less than or equal to about **45** degrees. In some embodiments, the light emitting portion **36** emits light at a downward angle from a perpendicular to the front face of the mirror assembly by at least about **15** degrees and/or less than or equal to about **60** degrees. In certain embodiments, the light emitting portion **36** emits light at a downward angle of about **15** degrees.

In some embodiments, the sensor assembly **28** can detect an object within a sensing region. In certain embodiments, the sensing region can have a range from at least about **0** degrees to less than or equal to about **45** degrees downward relative to an axis extending from the sensor assembly **28**, and/or relative to a line extending generally perpendicular to a front surface of the sensor assembly, and/or relative to a line extending generally perpendicular to the front face of the mirror and generally outwardly toward the user from the top of the mirror assembly. In certain embodiments, the sensing region can have a range from at least about **0** degrees to less than or equal to about **25** degrees downward relative to any of these axes or lines. In certain embodiments, the sensing region can have a range from at least about **0** degrees to less than or equal to about **15** degrees downward relative to any of these axes or lines..

In some embodiments, the sensing region can be adjusted by mounting the sensor assembly **28** at an angle. In certain embodiments, the sensor assembly **28** can be mounted such that the front surface of the sensing assembly **28** can be generally parallel or coplanar

with a front surface of mirror **4**. In certain embodiments, the sensor assembly **28** can be mounted such that the front surface of the sensing assembly **28** can be at an angle relative to the front surface of the mirror.

5 In some embodiments, the sensing region can be adjusted by modifying one or more features of the cover member **6**. In certain embodiments, the cover member **6** can include a lens material. In certain embodiments, the cover member **6** can include a generally rectangular cross-section. In certain embodiments, the cover member **6** can include a generally triangular cross-section. In certain embodiments, the cover member **6** can include a front surface generally parallel or coplanar with a front surface of the mirror **4**. In certain
10 embodiments, the cover member **6** can include a front surface at an angle relative to the front surface of the mirror **4**. In certain embodiments, the front surface of the cover member **6** can be positioned at an angle relative to the sensor assembly **28**.

In some embodiments, the sensing area generally widens as the front surface of the cover member **6** moves from the configuration generally parallel or coplanar with the front
15 surface of the mirror **4** to the configuration at an angle relative to the front surface of the mirror **4**. In certain embodiments, when the front surface of the cover member **6** is generally parallel or coplanar with the front surface of the mirror, the sensing region can have a range from about **0** degrees to about **15** degrees downward relative to the axis extending generally from the sensor assembly **28** and/or generally perpendicular to the front surface of the sensor
20 assembly. In certain embodiments, when the front surface of the cover member **6** is at an angle relative to the front surface of the mirror **4**, the sensing region can have a range from about **0** degrees to about **25** degrees downward relative to the axis extending generally from the sensor assembly **28** and/or generally perpendicular to the front surface of the sensor assembly.

25 The sensor assembly **28** may only require enough power to generate a low power beam of light, which may or may not be visible to the human eye. Additionally, the sensor assembly **28** can operate in a pulsating mode. For example, the light emitting portion **36** can be powered on and off in a cycle such as, for example, for short bursts lasting for any desired period of time (e.g., less than or equal to about **0.01** second, less than or equal to about **0.1**

second, or less than or equal to about 1 second) at any desired frequency (e.g., once per half second, once per second, once per ten seconds). Cycling can greatly reduce the power demand for powering the sensor assembly 28. In operation, cycling does not degrade performance in some embodiments because the user generally remains in the path of the light beam long enough for a detection signal to be generated.

If the receiving portion 38 detects reflections (e.g., above a threshold level) from an object within the beam of light emitted from the light emitting portion 36, the sensor assembly 28 sends a signal to the controller to activate a light source.

The sensor assembly 28 can send different signals to the controller 50 based on the amount of light reflected back toward the receiver 38. For example, the sensor assembly 28 is configured such that the amount of light emitted by the light sources 30 is proportional to the amount of reflected light, which can indicate the distance between the mirror 4 and the user. In certain variants, if the user is in a first sensing region, then the controller causes the one or more light sources 30 to activate from an off state or to emit a first amount of light. If the user is in a second sensing region (e.g., further away from the sensor assembly 28 than the first sensing region), then the controller causes the one or more light sources 30 to emit a second amount of light (e.g., less than the first amount of light).

The controller 50 can trigger at least two different levels of brightness from the light sources 30, such as brighter light or dimmer light. For example, if the user is anywhere in a first sensing region, then the controller 50 signals for bright light to be emitted; if the user is anywhere in a second sensing region, then the controller 50 signals for dim light to be emitted.

The controller 50 can also trigger more than two brightness levels. In certain implementations, the level of emitted light is related (e.g., linearly, exponentially, or otherwise) to the distance from the sensor to the user. For example, as the user gets closer to the sensor assembly 28, the one or more light sources 30 emit more light. Alternatively, the mirror assembly 2 can be configured to emit more light when the user is further away from the sensor assembly 28, and less light as the user moves closer to the sensor assembly 28.

The sensor assembly **28** can include two light emitting portions **36a** and **36b**. Each transmitter **36a**, **36b** emits a cone of light with proper shielding or guiding on the transmitters **36a** and **36b**, which defines the detection zones of the sensors (subject to the nominal range of the sensors **28**). The area in which the two cones overlap creates a primary sensing region, and areas in which the two cones emit light but do not overlap create a secondary sensing region. If a user is detected in the primary sensing region, then the sensor assembly **28** sends an appropriate signal to the controller **50**, which triggers a first level of light from the light sources **30**. If a user is detected in the secondary sensing region, then the sensor assembly **28** sends an appropriate signal to the controller **50**, which activates a second level of light from the light sources **30**. In some embodiments, the first level of light is brighter than the second level of light. In other embodiments, the second level of light is brighter than the first level of light. In some embodiments, the sensor assembly **28** defines more than two sensing regions and triggers more than two levels of light.

As shown in Figure **9**, the light emitting portions **38** can be positioned generally along the same horizontal plane (e.g., relative to the ground). The sensor assembly **28** can issue an appropriate signal to the controller **50**, which can trigger brighter light when the user is within a first sensing region, directly in front of the sensor assembly **28**. The sensor assembly can trigger dimmer light when the user is within a second sensing region, in the periphery of the mirror assembly **2**.

The sensor assembly **28** can include two or more light emitting portions **36** that do not create overlapping detection cones within the nominal range of the sensors **28**. A first cone of light defines a first sensing region and a second cone of light defines a second sensing region. If a user is detected in the first sensing region alone or the second sensing region alone, then the sensor assembly **28** signals the controller **50**, which activates a first level of light from the light sources **30**. In certain variants, if a user is concurrently detected in the first and second sensing regions, then the sensor assembly **28** signals the controller **50** to activate a second level of light from the light sources **30**. In some embodiments, the first level of light is brighter than the second level of light. In other embodiments, the second level of light is brighter than the first level of light.

Activation of the light sources **30** or adjusting the amount of light emitted from the light sources **30** can be based on factors other than the presence of a user within a sensing region. For example, the amount of light emitted from the light sources **30** can adjust based on motion within the detection zone and nominal range of the sensor **28**. Certain
5 implementations are configured such that, if a user lifts his/her hand in an upward motion, then the controller signals for the amount of light to increase, and if a user lowers his/her hand in a downward motion, then the controller signals for the amount of light to decrease.

Once a light source **30** activates, the light source **30** can remain activated so long as the sensor assembly **28** detects an object in a sensing region. Alternatively, the light source
10 **30** remains activated for a pre-determined period of time. For example, activating the light source **30** can initialize a timer. If the sensor assembly **28** does not detect an object before the timer runs out, then the light source **30** is deactivated. If the sensor assembly **28** detects an object before the timer runs out, then the controller **50** reinitializes the timer, either immediately or after the time runs out.

The one or more sensing regions can be used in any type of configuration that allows
15 the user to control an aspect of the operation of the mirror assembly **2**. For example, the one or more sensing regions can be used to trigger the mirror assembly **2** to emit different levels of light, operate for varying durations of time, pivot the mirror, or any other appropriate parameter.

In several embodiments, the mirror assembly **2** has one or more modes of operation,
20 for example, an on mode and an off mode. A controller **50** can activate different modes based on signals received from different sensing regions, motions, or any other parameter. Any of the modes described below can be used separately or in combination with each other.

The mirror assembly **2** can include a task mode. When the task mode is activated, the
25 mirror assembly **2** can trigger a light source **30** to remain activated or cause the sensor to enter a hyper mode (e.g., during which the sensor is configured to have increased sensitivity to movement within a zone, or to have a larger or wider sensitivity zone, or to have some other increased sensitivity signal detection) for a pre-determined period of time. For example, in some embodiments, the task mode can be especially useful when the user plans

to use the mirror assembly **2** for an extended period of time, especially if the user's body position is substantially still for an extended period, to avoid intermittent loss of lighting while the user is still looking into the mirror. The task mode can trigger a light source **30** to remain activated for a predetermined amount of time, even if the user is not detected within a sensing region. The pre-determined amount of time can be less than or equal to about: 3 minutes, 5 minutes, 10 minutes, or any other suitable period of time. If the sensor assembly **28** does not detect a user before the timer runs out, then the mirror assembly **2** deactivates task mode. In certain embodiments, the mirror assembly **2** remains in task mode until the user signals a light source **30** to deactivate.

The mirror assembly **2** can include a power saver mode. When the power saver mode is activated, the light source **30** emits less light than the mirror assembly **2** when not in power saver mode. The power saver mode can be user-activated and can be used when a user plans to use the mirror for a relatively long period of time. Alternatively, the mirror assembly **2** enters power saver mode automatically as a transition between on mode and off mode. For example, a controller **50** can initialize a timer when a light source **30** activates. If the sensor assembly **28** does not detect a user before the timer runs out, then the controller **50** enters power saver mode and initializes a second timer. If the sensor assembly **28** does not detect a user before the second timer runs out, then the controller **50** deactivates the light source **30**.

The mirror assembly **2** can include a hyper mode. As described above, in some embodiments, the mirror assembly **2** has two light emitting portions **36**, each emitting a cone of light. In certain implementations, the controller **50** only triggers the light sources **30** to activate when the sensor assembly **28** detects an object in the region where the two cones of light intersect (e.g., the primary sensing region). In some embodiments, after the light source **30** has been activated, the mirror assembly **2** enters hyper mode. The controller **50** can keep the light sources **30** activated as long as the sensor assembly **2** detects the user in either one or both of the cones of light (the secondary or the primary sensing regions). The secondary sensing region can be different from the primary sensing region. For example, the secondary sensing region can be larger than the primary sensing region. In some embodiments, this allows the user to move around and still keep the light source **30** activated.

Hyper mode can also help save power by preventing unintentional activation when the user is near a periphery of the mirror assembly 2.

The mirror assembly 2 can also include ambient light sensing capabilities. For example, when the ambient light is relatively low, the light emitting from the light source 30 will be brighter than if the ambient light is relatively bright. The light receiving portion 38 can detect both ambient light and light emitted from the transmitter 36, or the mirror assembly 2 can include a second sensor assembly for detecting ambient light.

The controller 50 can adjust the amount of signal necessary to trigger a light source 30 based on the amount of detected ambient light. For example, the amount of detected light required to activate the light sources 30 can be proportional to the ambient light. Such a configuration can allow the light source 30 to be activated even when the level of ambient light is modest (e.g., in dimmed bathroom lighting). When the ambient light is less than or equal to a first level, the controller 50 activates light source 30 when a first level of the reflected signal is detected. When the ambient light is greater than the first level, the controller 50 activates light source 30 when a second level (e.g., greater than the first level) of the reflected signal is detected.

The controller 50 can also adjust the amount of light emitted by the light sources 30 based on the ambient light. Such a configuration can, for example, avoid emitting a starting burst of very bright light that would be uncomfortable to a user's eyes, especially when the user's eyes were previously adjusted to a lower light level, such as when the surrounding environment is dim. For example, the amount of light emitted by the light sources 30 can be proportional to the amount of ambient detected light.

The controller 50 can also gradually increase the level of emitted light from the light sources 30 when the light sources 30 are activated and/or gradually decrease the amount of light emitted from the light sources 30 when the light sources 30 are deactivated. Such a configuration can inhibit discomfort to a user's eyes when the light sources 30 turn on.

The mirror assembly 2 can also include a calibration mode. For example, the calibration mode can calibrate the different sensing regions with different output characteristics as desired by the user. An algorithm can be configured to utilize multiple

sensing regions to perform different functions. For example, a user can configure a first sensing region to correspond with a first level of light (e.g., lower intensity light) and configure a second sensing region to correspond with a second level of light (e.g., higher intensity light). In another example, the user can adjust the size (e.g., width or height) of the sensing region. The user can designate a first sensing region to correspond with a first level of light and designate a second sensing region to correspond with a second level of light. This calibration mode can be triggered by a user indicator, such as pressing a button, activating a sensor, or any other appropriate mechanism.

In some embodiments, an ideal sensing region is designed so that the center of a user's face is generally positioned at about the center of the mirror portion, at a suitable perpendicular distance away from the mirror to permit the user to generally closely fit the user's face within the outer periphery of the mirror. A proximity sensor, generally positioned at the top region of the mirror, can be tilted downwardly at an angle below horizontal (e.g., at least about 10 degrees downward, such as about 15 degrees downward), and an algorithm can trigger a power change to the mirror when a user's face (or any other object) is detected within a predetermined range of distances in a perpendicular forward direction from the front face of the mirror. For example, in some embodiments, the first region can be within a range of at least about 10 inches and/or less than or equal to about 12 inches (e.g., about 11 inches) from the front face of the mirror, and the second region can be in a range of at least about 7 inches and/or less than or equal to about 9 inches (e.g., about 8 inches) from the front face of the mirror.

An algorithm can be configured to send a command to activate the light sources based on the detected signal. The algorithm can also be configured to emit different levels of light or vary durations of time. The algorithm can also be configured to send a command to trigger one or more modes, including any of the modes discussed above. The command can vary based on the signal received. For example, the signal can depend on the distance between an object and the sensor assembly 28, and/or other parameters such as duration or path of motion.

The algorithm can initialize a timer when a light source is activated. The timer can run for at least **30** seconds and/or less than or equal to **60** seconds, or any other quantity of time. In some embodiments, the timer can run for less than **30** seconds. In some embodiments, the timer can run for about five seconds. In some embodiments, the light source will immediately turn off when the time runs out. In some embodiments, the light will remain activated so long as the sensor assembly **28** detects an object before time runs out. If the sensor assembly **28** detects the object, the timer can immediately restart, or restart when the time runs out. If the sensor assembly **28** does not detect an object before the time runs out, then the light source will turn off.

The algorithm can incorporate a delay that deactivates the sensor or otherwise prevents a light source **30** from emitting light immediately after the light source **30** deactivates. The delay can be for **1** second, **5** seconds, or any other amount of time. The delay helps prevent the user from unintentionally triggering the light source **30**. During the delay period, the light source **30** will not emit light even if an object is in a sensing region during the delay period. If the sensor assembly **28** detects an object after the delay period, the light sources **30** can emit light again.

The level of light emitted from the light sources **30** does not depend solely or at all on the length of time that the user remains in the sensing region. The level of light emitted from the light sources **30** can differ depending on the location of the user in a different sensing region, even if certain other parameters are the same (such as the length of time that the user is sensed in a region).

The mirror assembly **2** can also include an algorithm configured to send a command to trigger the light sources **30** to activate based on the detected signal. For example, the algorithm **200** can resemble the flow chart depicted in Figure **13**. Beginning at start block **202**, the controller initializes mirror assembly hardware and variables in operation block **204**. Moving on to decision block **206**, if the signal is detected in a first sensing region, then the controller activates first level of light in operation block **208**. If a signal is not detected in a first sensing region, then the algorithm moves on to decision block **210**.

If a signal is detected in a second region, then the controller activates a second level of light in operation block **212**. If a signal is not detected in a second sensing region, then the algorithm moves on to decision block **214**. If a signal is detected for a task mode then the controller activates a third level of light in operation block **216**.

5 The third level of light can be a power saving level of light, such as if the user plans to keep the light source **30** activated for a relatively long period of time (e.g., **30** minutes or longer). After the third level of light is activated, a timer is initialized (block **218**). The timer can be for **30** seconds or any other period of time. If a user is not detected within the sensing region during the **30** second timer, then the light source **30** turns off and the algorithm returns
10 to just after the hardware and variables initialization in operation block **104**. If a user is detected in a sensing region within the **30** second timer, then the **30** second timer repeats itself.

 In some embodiments, the mirror assembly **2** can include an algorithm configured to maintain the light source (e.g., LED) brightness at a generally constant level even as the
15 battery capacity is nearing the end of its life (necessitating a recharge) by adjusting the electrical characteristics of the power source supplied to the light source depending on the stage of battery life (e.g., increasing the voltage as the current decreases or increasing the current as the voltage decreases).

 Algorithm **200** may not include all of the blocks described above, or it may include
20 more decision blocks to account for additional sensing regions, other modes, or other parameters as described throughout this disclosure.

 In some embodiments, the mirror assembly **2** can include an algorithm configured to detect whether the mirror was inadvertently activated, such as with a false trigger or by the presence of an inanimate object. For example, when the sensor detects an object, the
25 controller can initialize a timer. If the mirror assembly **2** does not detect any movement before the timer runs out, then the light sources will turn off. If the mirror assembly **2** does detect movement, then the timer can re-initialize.

 As noted above, the mirror assembly **2** can include a processor, which can control, by various scheme and algorithms, input and output characteristics and functions of the mirror

assembly 2. The mirror assembly 2 can also include memory, such as firmware, to store the various control schemes and algorithms, as well certain instructions and/or settings related to various characteristics of the mirror assembly 2. For example, the memory can include instructions and/or settings regarding the size of the sensing regions, the sensitivity of the sensors, the level of output light, the length of various timers, and otherwise.

The mirror assembly 2 can be configured such that a user can modify (e.g., update, program, or otherwise) the memory, such as by connecting the mirror assembly 2 to a computer. For example, the mirror 2 can be communicatively connected with a computer via the port 24 (e.g., using a USB, cable). Data can be transferred between the computer and the mirror assembly 2 via the port 24. The mirror assembly 2 can alternatively be configured to communicate with a computer wirelessly, such as by a cellular, Wi-Fi, or Bluetooth® network, infrared, or otherwise.

When the mirror assembly 2 is in communication with the computer, a control panel may be displayed on the computer. The control panel may allow the user adjust various input and output characteristics for the mirror assembly 2. For example, a user can use the control panel to adjust the output of the emitting portions 36a and 36b and/or the sensitivity of the transmitter 36a, 36b. The user can also configure the light levels associated with the first and second sensing regions. In another example, the user can adjust the size (e.g., depth, width, and/or height) of one or more of the sensing regions. In some implementations, the user can use the control panel to modify the operation and output (e.g., intensity and/or color of the light) of the light source 30 based on certain conditions, such as the time of day, level of ambient light, amount of battery power remaining, and otherwise. In certain variants, the ability to modify the operational parameters of the mirror assembly 2 with the control panel can reduce or obviate the need for one or more adjustment devices (e.g., buttons, knobs, switches, or the like) on the mirror assembly 2, thereby providing a generally uniform exterior surface of the mirror assembly 2 (which can facilitate cleaning) and reducing the chance of unintentional adjustment of the operational parameters (such as when transporting the mirror assembly 2).

When the mirror assembly 2 is in communication with the computer, data can be transferred from the mirror assembly 2 to the computer. For example, the mirror assembly 2 can transfer data, such as power consumption, estimated remaining battery power, the number of activations and/or deactivations of the light source 30, the length of use (e.g., of individual instances and/or in total) of the light source 30, and otherwise. Software can be used to analyze the transferred data, such as to calculate averages, review usage statistics (e.g., during specific periods), recognize and/or draw attention to unusual activity, and display usage statistics on a graph. Transferring usage statistics from the mirror assembly 2 to the computer allows the user to monitor usage and enables the user to calibrate different characteristics of the mirror assembly 2 (e.g., based on previous usage and parameters). Transferring data from the mirror assembly 2 to the computer can also reduce or avoid the need for one or more adjustment or display devices on the mirror assembly itself.

When the mirror assembly 2 is in communication with the computer, the mirror the computer can also transfer data to the mirror assembly 2. Furthermore, when the mirror assembly 2 is in communication with the computer, electrical potential can be provided to the battery 26 before, during, or after such two-way data transfer.

Although the vanity mirror has been disclosed in the context of certain embodiments and examples, it will be understood by those skilled in the art that the present disclosure extends beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the subject matter and obvious modifications and equivalents thereof. In addition, while several variations of the vanity mirror have been described in detail, other modifications, which are within the scope of the present disclosure, will be readily apparent to those of skill in the art based upon this disclosure. It is also contemplated that various combinations or sub-combinations of the specific features and aspects of the embodiments can be made and still fall within the scope of the present disclosure. It should be understood that various features and aspects of the disclosed embodiments can be combined with or substituted for one another in order to form varying modes of the vanity mirror. Thus, it is intended that the scope of the subject matter herein disclosed should not be limited by the particular disclosed embodiments described above.

EMBODIMENTS IN WHICH AN EXCLUSIVE PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS FOLLOWS:

1. A mirror assembly comprising:
 - a housing portion;
 - 5 a mirror coupled with the housing portion;
 - one or more light sources;
 - a proximity sensor configured to detect an object within a sensing region, the proximity sensor configured to generate a signal indicative of a distance between the object and the proximity sensor; and
 - 10 an electronic processor configured to generate an electronic signal to the one or more light sources for emitting a level of light that varies depending on the distance between the object and the sensor.
2. The mirror assembly of Claim 1, wherein the proximity sensor is positioned generally near a top region of the mirror.
- 15 3. The mirror assembly of Claim 1, wherein the electronic processor is configured to generate an electronic signal to the one or more light sources to deactivate if the proximity sensor does not detect the object for a period of time.
4. The mirror assembly of Claim 1, wherein the proximity sensor is configured to have increased sensitivity after the proximity sensor detects the object.
- 20 5. The mirror assembly of Claim 1, further comprising an ambient light sensor configured to detect a level of ambient light.
6. The mirror assembly of Claim 1, wherein the sensing region extends from about 0 degrees to about 45 degrees downward relative to an axis extending from the proximity sensor.
7. The mirror assembly of Claim 1, wherein the proximity sensor is mounted at an angle
25 relative to a viewing surface of the mirror.

8. The mirror assembly of Claim 1, further comprising a lens cover positioned near the proximity sensor.
9. The mirror assembly of Claim 8, wherein a front surface of the lens cover is positioned at an angle relative to the proximity sensor.
- 5 10. The mirror assembly of Claim 1, further comprising a light pipe having a length and being disposed along substantially all of the periphery of the mirror, the light pipe configured to receive light from the one or more light sources and distribute the light generally consistently along the length, thereby providing a substantially constant level of illumination to the periphery of the mirror.
- 10 11. A method of manufacturing a mirror assembly, the method comprising:
- coupling a mirror with a housing portion;
- disposing one or more light sources at a periphery of the mirror;
- configuring a proximity sensor to generate a signal indicative of a distance between an object and the proximity sensor; and
- 15 configuring an electronic processor to generate an electronic signal to the one or more light sources for emitting a level of light that varies depending on the distance between the object and the sensor.
12. The method of Claim 11, further comprising positioning the proximity sensor generally near a top region of the mirror.
- 20 13. The method of Claim 11, further comprising configuring the electronic processor to generate an electronic signal to the one or more light sources to deactivate if the proximity sensor does not detect the object for a period of time.
14. The method of Claim 11, further comprising configuring the proximity sensor to have increased sensitivity after the proximity sensor detects the object.

15. The method of Claim 11, further comprising configuring an ambient light sensor to detect a level of ambient light.
16. The method of Claim 11, further comprising configuring the proximity sensor to detect an object within a sensing region extending from about 0 degrees to about 45 degrees downward relative to an axis extending from the proximity sensor.
17. The method of Claim 11, further comprising mounting the proximity sensor at an angle relative to a viewing surface of the mirror.
18. The method of Claim 11, further comprising positioning a lens cover near the proximity sensor.
19. The method of Claim 18, further comprising positioning a front surface of the lens cover at an angle relative to the proximity sensor.
20. The method of Claim 11, further comprising disposing a light pipe along substantially all of the periphery of the mirror, the light pipe configured to receive light from the one or more light sources and distribute the light generally consistently along the length, thereby providing a substantially constant level of illumination to the periphery of the mirror.
21. A mirror assembly comprising:
- a housing portion;
 - a mirror coupled with the housing portion;
 - one or more light sources disposed at a periphery of the mirror;
 - a proximity sensor configured to detect an object within a sensing region, the proximity sensor configured to generate a signal indicating that the object is within a predetermined distance from the proximity sensor; and
 - an electronic processor configured to generate an electronic signal to the one or more light sources for emitting light when the object is within the predetermined distance from the proximity sensor.

22. The mirror assembly of Claim 21, wherein the level of light generated is proportional to the distance between the object and the proximity sensor.

23. The mirror assembly of Claim 21, further comprising an ambient light sensor.

24. The mirror assembly of Claim 21, further comprising an algorithm for resisting false triggers.

25. The mirror assembly of Claim 21, further comprising a rechargeable mobile power source.

26. A mirror assembly configured to provide an illuminated reflection of a user, the mirror assembly comprising:

a mirror;

at least one light source disposed at a periphery of the mirror;

a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity;

a reflective surface positioned along the light-conveying pathway;

a sensor configured to detect the presence of a user in front of the mirror assembly; and

a controller in electrical communication with the sensor, the controller being configured to actuate the light source to illuminate the user when the sensor detects the presence of the user in front of the mirror assembly and to deactivate the light source upon a predetermined delay after the sensor no longer detects the presence of a user in front of the mirror assembly.

27. The mirror assembly of Claim 26, further comprising a support attached to the mirror, a shaft coupled to the support behind the mirror, and a base coupled to the shaft.

28. The mirror assembly of Claim 26, wherein the intensity of light emitted by the at least one light source is adjustable.

29. The mirror assembly of Claim 26, further comprising a rechargeable battery.
30. The mirror assembly of Claim 29, wherein the rechargeable battery is located in the base.
31. The mirror assembly of Claim 26, wherein the intensity of light emitted by the light source is configured to be adjustable by a user's hand.
- 5 32. The mirror assembly of Claim 26, wherein one or more functions of the mirror assembly are configured to be modified by a computer outside of the mirror assembly.
33. The mirror assembly of Claim 32, wherein one of the one or more functions modifiable by the computer is a color of the light.
34. The mirror assembly of Claim 33, wherein the mirror assembly is configured to
10 communicate with the computer wirelessly.
35. The mirror assembly of Claim 26, wherein the light-conveying pathway is generally circular.
36. A mirror assembly configured to provide an illuminated reflection of a user, the mirror assembly comprising:

a mirror;

15 at least one light source disposed at a periphery of the mirror;

a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity;

a reflective surface positioned along the light-conveying pathway;

20 a sensor configured to detect the presence of a user in front of the mirror assembly;
and

a controller in electrical communication with the sensor, the controller being configured to actuate the light source to illuminate the user when the sensor detects the presence of the user in front of the mirror assembly and to deactivate the light

source after the sensor no longer detects the presence of a user in front of the mirror assembly;

wherein the controller is configured to communicate wirelessly with a computer outside of the mirror assembly to adjust a color of light emitted by the at least one light source.

- 5
37. A combination of the mirror assembly of Claim 36 and the computer outside of the mirror assembly.
38. The mirror assembly of Claim 36, wherein the intensity of the light is configured to be adjustable by a user's hand.
- 10 39. The mirror assembly of Claim 36, wherein the mirror assembly comprises a rechargeable power supply.
40. The mirror assembly of Claim 36, wherein the mirror assembly is portable.
41. The mirror assembly of Claim 36, wherein the light-conveying pathway is configured to transmit at least about 95% of the light emitted from the at least one light source.
- 15 42. The mirror assembly of Claim 36, further comprising a support attached to the mirror, a shaft coupled to the support by way of a pivot located behind the mirror, and a base coupled to the shaft.
43. The mirror assembly of Claim 42, wherein a rechargeable power supply is located in the base.
- 20 44. The mirror assembly of Claim 42, wherein the support does not attach to the shaft on a periphery of the support.
45. The mirror assembly of Claim 36, wherein the light-conveying pathway is generally circular.
46. The mirror assembly of Claim 36, wherein the controller does not deactivate the at least one light source immediately upon no longer detecting the presence of a user in front of the mirror assembly.
- 25

47. A mirror assembly comprising:

a housing portion;

a mirror;

one or more light sources disposed at a periphery of the mirror;

5 a proximity sensor configured to detect an object within a sensing region, the proximity sensor configured to generate a signal indicating that the object is within a predetermined distance from the proximity sensor; and

10 an electronic processor configured to generate an electronic signal to the one or more light sources for emitting light when the processor receives the signal from the proximity sensor indicating that the object is within the predetermined distance from the proximity sensor,

wherein when the proximity sensor detects the object, the size or width of a sensitivity zone is temporarily increased in order for the proximity sensor and the electronic processor to trigger or to maintain the light source in an active state.

15 **48.** The mirror assembly of Claim **47**, wherein the level of light generated is proportional to the distance between the object and the proximity sensor.

49. The mirror assembly of Claim **47**, further comprising an ambient light sensor.

50. The mirror assembly of Claim **47**, wherein the processor is configured to resist false triggers using an algorithm.

20 **51.** The mirror assembly of Claim **47**, further comprising a rechargeable mobile power source.

52. The mirror assembly of **51**, wherein the rechargeable mobile power source is configured to be recharged via a port.

53. The mirror assembly of Claim **52**, wherein the port is a USB port.

54. The mirror assembly of Claim 47, wherein an illuminance at an outer periphery of the sensing region is at least about 500 lux and less than or equal to about 1000 lux.
55. The mirror assembly of Claim 54, wherein the illuminance is about 600 lux.
56. The mirror assembly of Claim 47, wherein the one or more light sources have a color rendering index of at least about 80.
57. The mirror assembly of Claim 56, wherein the color rendering index is about 90.
58. The mirror assembly of Claim 47, wherein each of the one or more light sources has a color temperature of less than or equal to about 6500K.
59. The mirror assembly of Claim 47, wherein after the processor generates the signal to the one or more light sources for emitting light, the processor is configured to deactivate the one or more light sources if the object is not detected within the sensing region before a timer elapses.
60. The mirror assembly of Claim 47, wherein the one or more light sources comprises at least two different colored light sources.
61. The mirror assembly of Claim 47, wherein the one or more light sources comprises a plurality of light sources.
62. The mirror assembly of Claim 61, wherein the plurality of light sources are configured to change the color of the emitted light.
63. The mirror assembly of Claim 47, wherein the color of the light emitted from the one or more light sources is adjustable by a user.
64. The mirror assembly of Claim 47, wherein the intensity of the light emitted from the one or more light sources is adjustable by a user.
65. The mirror assembly of Claim 47, wherein the electronic processor is configured to activate a task mode, the task mode being configured to activate a state of increased sensitivity of the proximity sensor.

66. A mirror assembly comprising:

a mirror;

at least one light source disposed at a periphery of the mirror that emits light;

a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity;

a sensor configured to detect the presence of a user in front of the mirror assembly;

a reflective surface positioned along the light-conveying pathway; and

a controller in electrical communication with the sensor,

wherein upon the sensor detecting the presence of the user in front of the mirror assembly, the controller activates the at least one light source to illuminate the user;

wherein upon activation of the at least one light source, the controller gradually increases a level of light emitted from the at least one light source.

67. The mirror assembly of Claim **66**, wherein upon deactivation of the at least one light source, the controller gradually decreases the level of light emitted from the at least one light source.

68. The mirror assembly of Claim **66**, wherein upon no longer detecting the presence of the user in front of the mirror assembly, the controller decreases an amount of emitted light from the at least one light source for a predetermined amount of time, and wherein after the predetermined amount of time, the controller deactivates the at least one light source.

69. A mirror assembly comprising:

a mirror;

at least one light source disposed at a periphery of the mirror that emits light;

a light-conveying pathway configured to receive light from the at least one light source and to convey the light along a periphery of the mirror at a generally even or a generally uniform intensity;

a sensor configured to detect ambient light;

5 a reflective surface positioned along the light-conveying pathway; and

a controller configured to activate the at least one light source and to deactivate the at least one light source,

wherein a brightness of the emitted light is affected by a level of the detected ambient light, and

10 wherein when ambient light is at a first ambient brightness level, the controller causes the light emitted from the at least one light source to be emitted at a first emitted brightness level, and when ambient light is at a second ambient brightness level, the controller causes the light emitted from the at least one light source to be emitted at a second emitted brightness level that is brighter than the first emitted
15 brightness level.

70. The mirror assembly of Claim **69**, wherein before the at least one light source is deactivated, the controller decreases an amount of emitted light from the at least one light source for a predetermined amount of time.

71. A mirror assembly configured to provide an illuminated reflection of a user, the mirror
20 assembly comprising:

a mirror;

at least one light source disposed at a periphery of the mirror;

a light-conveying pathway configured to receive light from the at least one light source and to convey substantially constant light along a periphery of the mirror;

a sensor configured to detect the presence of a user in front of the mirror assembly;
and

a controller in electrical communication with the sensor, the controller being
configured to activate the at least one light source to illuminate the user when the
5 sensor detects the presence of the user in front of the mirror assembly,

wherein after the sensor detects the presence of the user, the sensor is configured to
have increased sensitivity.

72. The mirror assembly of Claim 71, further comprising a support attached to the mirror, a shaft
coupled to the support behind the mirror, and a base coupled to the shaft.

10 73. The mirror assembly of Claim 72, further comprising a rechargeable battery located in the
base.

74. The mirror assembly of Claim 71, wherein the intensity of light emitted by the at least one
light source is adjustable.

15 75. The mirror assembly of Claim 74, wherein the intensity of light emitted by the at least one
light source is configured to be adjustable by a user's hand.

76. The mirror assembly of Claim 71, wherein the light-conveying pathway is generally circular.

77. The mirror assembly of Claim 71, wherein the controller is configured to activate a task
mode, the task mode being configured to activate a state of increased sensitivity of the
sensor.

20 78. The mirror assembly of Claim 71, wherein the at least one light source comprises at least two
different colored light sources.

79. The mirror assembly of Claim 71, wherein the at least one light source is configured to
change a color of the emitted light.

80. The mirror assembly of Claim **71**, wherein the controller is configured to gradually increase a level of light emitted from the at least one light source when the at least one light source is activated.

81. The mirror assembly of Claim **80**, wherein the controller is configured to gradually decrease the level of light emitted from the at least one light source when the at least one light source is deactivated.

82. The mirror assembly of Claim **80**, wherein upon no longer detecting the presence of a user in front of the mirror assembly, the controller is configured to decrease an amount of emitted light from the at least one light source for a predetermined amount of time, and wherein after the predetermined amount of time, the controller is configured to deactivate the light source.

83. The mirror assembly of Claim **71**, wherein a brightness of the emitted light is affected by a level of detected ambient light.

84. The mirror assembly of Claim **71**, wherein the controller is configured to communicate wirelessly with a computer outside of the mirror assembly to adjust a color of light emitted by the at least one light source.

85. A combination of the mirror assembly of Claim **71** and the computer outside of the mirror assembly.

1/13




FIG. 1




FIG. 2

3/13




FIG. 3

4/13






FIG. 4

5/13

*FIG. 5**FIG. 6*

6/13






FIG. 7








FIG. 9

10/13




FIG. 10




FIG. 11




FIG. 11B




FIG. 11A

12/13





FIG. 12

13/13

*FIG. 13*

