



(51) International Patent Classification:

G02B 5/02 (2006.0 1) F21 V 8/00 (2006.0 1)  
G02B 5/04 (2006.0 1) G02B 3/00 (2006.0 1)

(21) International Application Number:

PCT/US2014/031655

(22) International Filing Date:

25 March 2014 (25.03.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/850,277 25 March 2013 (25.03.2013) US

(71) Applicant: **3M INNOVATIVE PROPERTIES COMPANY** [US/US]; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55 133-3427 (US).

(72) Inventors: **JOHNSON, Nicholas A.**; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55 133-3427 (US). **SYKORA, Michael J.**; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55 133-3427 (US). **LAUTERS, Michael E.**; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US). **WHEATLEY, John A.**; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55 133-3427 (US).

(74) Agents: **D3EN, Daniel J.** et al; 3M Center, Office of Intellectual Property Counsel Post Office Box 33427, Saint Paul, Minnesota 55 133-3427 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on nextpage]

(54) Title: DUAL-SIDED FILM WITH SPLIT LIGHT SPREADING STRUCTURES




FIG. 1A

(57) Abstract: Dual-sided optical films have extended split spreading structures formed on one major surface, and extended prisms formed on an opposite major surface. One portion of each split spreading structure has a low light spreading characteristic, and another portion has a high light spreading characteristic. For each split spreading structure, the low light spreading portion may be disposed alongside the high light spreading portion. The split spreading structures may be arranged in a one-to-one correspondence with the prisms. Light that enters a given prism from one inclined surface thereof can be associated primarily with light transmitted through the low light spreading portion of the split spreading structure, and light that enters the given prism from the other inclined surface thereof can be associated primarily with light transmitted through the high light spreading portion.



**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(H))*
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(Hi))*

**Published:**

- *with international search report (Art. 21(3))*

**DUAL-SIDED FILM WITH SPLIT LIGHT SPREADING STRUCTURES****FIELD OF THE INVENTION**

5           This invention relates generally to microstructured optical films, particularly to such films in which the opposed major surfaces are both structured, as well as articles and systems that incorporate such films, and methods pertaining to such films.

**BACKGROUND**

10           Optical films that have structured surfaces on opposed major surfaces thereof, referred to herein as dual-sided optical films, are known. In some such films, one structured surface has lenticular features formed therein and the other structured surface has prismatic features formed therein. There is a one-to-one correspondence of prismatic features to lenticular features, and individual prismatic features are elongated and extend parallel to each other and to individual lenticular features, which are also elongated.

15           Such films have been disclosed for use as optical light redirecting films in autostereoscopic 3D display systems. See for example U.S. Patents 8,035,771 (Brott et al.) and 8,068,187 (Huizinga et al.), and patent application publications US 2005/0052750 (King et al.), US 201 1/0149391 (Brott et al.), and US 2012/0236403 (Sykora et al.).

**BRIEF SUMMARY**

20           We have developed a new family of dual-sided optical films in which structures formed on one side of the optical film are split into one portion that has a low light spreading characteristic, disposed alongside another portion that has a high light spreading characteristic. One low light spreading portion in combination with an adjacent high light spreading portion may be referred to as a split spreading

25           structure. The high light spreading characteristic may be associated with a surface that is roughened and/or curved (e.g. a lenslet or portion thereof), and the low light spreading characteristic may be associated with a surface that is smooth, and in some cases the surface may also be flat while in other cases the surface may be curved. The split spreading structures may be extended or elongated, and combined with extended or elongated (e.g. linear) prismatic features in the structured surface on the

30           opposite side of the optical film, e.g. in a one-to-one correspondence of prismatic features to split spreading structures. Light that enters a given prismatic feature from one inclined surface thereof can be associated primarily with light transmitted through the low light spreading portion of its associated split spreading structure, and light that enters the given prismatic feature from the other inclined surface thereof can be associated primarily with light transmitted through the high light spreading portion of the

35           structure. When combined with a suitable light guide and light sources, such an optical film can be used to provide unique optical systems, including a display system having a selective privacy capability that is electronically switchable, and a luminaire system having a selective spotlight capability that is electronically switchable.

The present application further discloses, *inter alia*, dual-sided optical films having opposed first and second structured surfaces, with a plurality of extended prisms formed on the first structured surface, and a plurality of extended split spreading structures formed on the second structured surface, each split spreading structure having a high spreading portion disposed alongside a low spreading portion, and the prisms and the split spreading structures being arranged in a one-to-one correspondence of prisms to split spreading structures.

Each prism may have on one side thereof a first inclined surface and on another side thereof a second inclined surface, and the high spreading portion of a given split spreading structure may be associated primarily with light transmitted through the first inclined surface of its associated prism. The low spreading portion of the given split spreading structure may be associated primarily with light transmitted through the second inclined surface of the associated prism.

For each of the split spreading structures, the low spreading portion may have a smooth surface characteristic and the high spreading portion may have a roughened surface characteristic. Each of the split spreading structures may comprise a curved segment of the second structured surface, and the low and high spreading portions of each split spreading structure may comprise smooth and roughened portions respectively of the curved segment.

For each split spreading structure, the high spreading portion may be a roughened portion and the low spreading portion may be a lenslet. For each split spreading structure, the high spreading portion may be a lenslet and the low spreading portion may be a flat. The lenslet of each split spreading structure may be a diverging lenslet. The lenslet of each split spreading structure may alternately be a converging lenslet.

The split spreading structures may extend along respective elongation axes that are parallel to each other, and, for each of the split spreading structures, the low and high spreading portions may meet along a boundary that is parallel to the elongation axis in plan view. The prisms may extend along respective first elongation axes that are parallel to each other, and the split spreading structures may extend along respective second elongation axes that are parallel to each other, and the first elongation axes may be parallel to the second elongation axes.

The optical film may define a reference plane, the prisms may have respective prism optical axes, and each prism optical axis may be perpendicular to the reference plane. Alternatively, a plurality of the prism optical axes may be tilted with respect to a normal axis perpendicular to the reference plane. Furthermore, each split spreading structure may have a spreading structure optical axis, and each spreading structure optical axis may be perpendicular to the reference plane, or a plurality of the spreading structure optical axes may be tilted with respect to a normal axis perpendicular to the reference plane.

An optical system may comprise any such dual-sided optical film, and a light guide having a major surface adapted to emit light preferentially at oblique angles, where the optical film is disposed proximate the light guide and oriented so that light emitted from the major surface of the light guide enters the optical film through the first structured surface.

We also disclose optical systems that include a light guide having a major surface adapted to emit light, a first and second light source configured to inject light into the light guide along different first and second respective directions, and a dual-sided optical film. The optical film has opposed first and second structured surfaces, and is disposed proximate the light guide and oriented so that light emitted from the major surface of the light guide is deviated by and passes through the optical film to provide an output beam as a function of which of the first and second light sources are energized. The output beam is a wide output beam when the first light source is energized and the second light source is not energized, and the output beam is a narrow output beam when the second light source is energized and the first light source is not energized.

The wide output beam may have a beam width (FWHM) of at least 40 degrees in a given plane of observation, and the narrow output beam may have a beam width (FWHM) of no more than 30 degrees in the given plane of observation. The narrow output beam may be subsumed by, i.e., entirely contained within, the wide output beam in the plane of observation. The optical film may have a first structured surface facing the light guide and a second structured surface opposed to the first structured surface. A plurality of extended prisms may be formed on the first structured surface, and a plurality of extended split spreading structures may be formed on the second structured surface, each split spreading structure having a high spreading portion disposed alongside a low spreading portion, and the prisms and the split spreading structures may be arranged in a one-to-one correspondence of prisms to split spreading structures.

The system may also include a switch coupled to the first and second light sources. The system may comprise a display, and the switch may provide the display with a switchable privacy/sharing function. The system may comprise a luminaire, task light, or similar lighting device, and the switch may provide the device with a switchable spotlight function.

We also disclose display systems that include a display panel, a backlight disposed behind the display panel, the backlight including one or more first light sources and one or more second light sources, and a switch coupled to the one or more first light sources and to the one or more second light sources to selectively energize such light sources. The backlight may be configured to provide a first output light beam when the one or more first light sources are ON and the one or more second light sources are OFF, and may further be configured to provide a second output light beam when the one or more first light sources are OFF and the one or more second light sources are ON. The first output light beam may have a wider angular spread than the second output light beam, such that the switch provides the display system with a switchable privacy/sharing function.

The backlight may include a dual-sided optical film having opposed first and second structured surfaces, the optical film comprising: a plurality of extended prisms formed on the first structured surface; and a plurality of extended split spreading structures formed on the second structured surface, each split spreading structure having a high spreading portion disposed alongside a low spreading portion. The prisms and the split spreading structures may be arranged in a one-to-one correspondence of prisms to split spreading structures. The backlight may include a light guide.

Related methods, systems, and articles are also discussed.

These and other aspects of the present application will be apparent from the detailed description below. In no event, however, should the above summaries be construed as limitations on the claimed subject matter, which subject matter is defined solely by the attached claims, as may be amended during prosecution.

### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1A is a schematic side view of an illustrative display system that includes a dual-sided optical film;

10 FIG. 1B is a schematic perspective view of a lighting system that may serve as the backlight in the display system of FIG. 1A, or that may be used in other applications;

FIG. 2 is a schematic perspective view of a light guide, which shows in exaggerated fashion exemplary surface structure on the two major surfaces of the light guide;

15 FIG. 2A is a view of the light guide of FIG. 2 in combination with collimated light sources, illustrating how a light guide can be effectively subdivided or partitioned as a function of which light sources on a given side of the light guide are turned ON;

FIG. 3 is a schematic side view of a lighting system such as that of FIG. 1B, with one light source energized, this light source producing a wide output beam emerging from the dual-sided optical film;

20 FIG. 4A is a schematic side view of the lighting system of FIG. 3 but with the opposite light source energized, this light source producing a narrow output beam emerging from the dual-sided optical film;

FIG. 4B is a schematic side view of a lighting system similar to FIG. 4A but where the dual-sided optical film is modified to produce a modified narrow output beam, which has a beam waist;

FIG. 5 is a schematic perspective view of a portion of an exemplary dual-sided optical film;

25 FIG. 6 is a schematic side view of a portion of a dual-sided optical film having the same or similar design as that of FIG. 5, this view showing one prism/split spreading structure pair;

FIG. 6A is a schematic side view of the film portion of FIG. 6, with light rays added to show how oblique light entering a first inclined surface of the prism are primarily directed to a high spreading portion of the split spreading structure;

30 FIG. 6B is a schematic side view of the film portion of FIG. 6, with light rays added to show how oblique light entering a second inclined surface of the prism are primarily directed to a low spreading portion of the split spreading structure;

FIG. 7 is a schematic perspective view of a portion of another exemplary dual-sided optical film;

35 FIG. 8 is a schematic side view of a portion of a dual-sided optical film having the same or similar design as that of FIG. 7, this view showing one prism/split spreading structure pair;

FIG. 8A is a schematic side view of the film portion of FIG. 8, with light rays added to show how oblique light entering a first inclined surface of the prism are primarily directed to a high spreading portion of the split spreading structure;

FIG. 8B is a schematic side view of the film portion of FIG. 8, with light rays added to show how oblique light entering a second inclined surface of the prism are primarily directed to a low spreading portion of the split spreading structure;

FIG. 9 is a schematic perspective view of a portion of another exemplary dual-sided optical film;

5 FIG. 10 is a schematic side view of a portion of a dual-sided optical film having the same or similar design as that of FIG. 9, this view showing one prism/split spreading structure pair;

FIG. 10A is a schematic side view of the film portion of FIG. 10, with light rays added to show how oblique light entering a first inclined surface of the prism are primarily directed to a high spreading portion of the split spreading structure;

10 FIG. 10B is a schematic side view of the film portion of FIG. 10, with light rays added to show how oblique light entering a second inclined surface of the prism are primarily directed to a low spreading portion of the split spreading structure;

FIG. 11 is a schematic perspective view of a portion of another exemplary dual-sided optical film;

15 FIG. 12 is a schematic side view of a portion of a dual-sided optical film having the same or similar design as that of FIG. 11, this view showing one prism/split spreading structure pair;

FIG. 12A is a schematic side view of the film portion of FIG. 12, with light rays added to show how oblique light entering a first inclined surface of the prism are primarily directed to a high spreading portion of the split spreading structure;

20 FIG. 12B is a schematic side view of the film portion of FIG. 12, with light rays added to show how oblique light entering a second inclined surface of the prism are primarily directed to a low spreading portion of the split spreading structure;

FIG. 13 is a schematic perspective view of a portion of another exemplary dual-sided optical film;

25 FIG. 14 is a schematic side view of a portion of a dual-sided optical film having the same or similar design as that of FIG. 13, this view showing one prism/split spreading structure pair;

FIG. 14A is a schematic side view of the film portion of FIG. 14, with light rays added to show how oblique light entering a first inclined surface of the prism are primarily directed to a high spreading portion of the split spreading structure;

30 FIG. 14B is a schematic side view of the film portion of FIG. 14, with light rays added to show how oblique light entering a second inclined surface of the prism are primarily directed to a low spreading portion of the split spreading structure;

FIG. 15 is a schematic side view of an exemplary dual-sided optical film or portion thereof in which the split spreading structures are aligned with their respective prisms, and a pitch of the split spreading structures is the same as the pitch of the prisms;

35 FIG. 16 is a schematic side view of an exemplary dual-sided optical film or portion thereof in which the pitch of the split spreading structures is different from the prism pitch;

FIG. 17 is a schematic side view of an exemplary dual-sided optical film or portion thereof in which the split spreading structure pitch is different from the prism pitch and the prisms have optical axes that are tilted as a function of position on the film;

5 FIG. 18 is a schematic side view of a prism/split spreading structure pair, in which the elements are translationally and rotationally aligned with each other;

FIG. 19 is a schematic side view of a prism/split spreading structure pair in which the elements are translationally and rotationally misaligned with each other, and are tilted by different amounts;

10 FIG. 20A is a simplified representation of possible angular distributions of an input beam of oblique light incident on a given dual-sided optical film and a wide angle output light beam produced by the film;

FIG. 20B is a simplified representation of possible angular distributions of a different input beam of oblique light incident on a the dual-sided optical film of FIG. 20A and a narrow angle output light beam produced by the film;

15 FIG. 21 is a schematic top or side view of a display system utilizing an exemplary dual-sided optical film;

FIG. 22 is a schematic top or side view of another display system utilizing another exemplary dual-sided optical film;

FIG. 23 is a schematic side view of a luminaire utilizing an exemplary dual-sided optical film;

20 FIG. 24 is a schematic side view of another luminaire utilizing another exemplary dual-sided optical film;

FIGS. 25A through 25E are schematic perspective views of optical systems which demonstrate some planar and non-planar shapes that the dual-sided optical film and/or the light guide may have;

25 FIG. 26 is a graph of the modeled brightness as a function of polar angle for output beams produced by a dual-sided optical film similar to that of FIGS. 5 and 6, the graph showing a wide angle output beam and a narrow angle output beam;

FIG. 27 is a graph of the modeled brightness as a function of polar angle for output beams produced by a dual-sided optical film similar to that of FIGS. 7 and 8, the graph showing a wide angle output beam and a narrow angle output beam; and

30 FIGS. 28A and 28B are polar iso-candela graphs of the modeled wide and narrow angle output beams of FIG. 27, respectively.

In the figures, like reference numerals designate like elements.

## DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

35 An optical system **100** capable of utilizing the unique properties of the disclosed dual-sided optical films is shown in FIG. 1A. In this case, the optical system **100** is a display system, but other devices and applications, including ambient lighting devices such as luminaires or task lights, are also contemplated. The system **100** is shown in relation to a Cartesian x-y-z coordinate system so that directions and orientations of selected features can be more easily discussed. The system **100** includes a

display panel **120**, e.g., a liquid crystal display (LCD) panel, and a backlight **130** positioned to provide light to the display panel **120**. The backlight **130** includes one or more light guides **150**, one or more first light sources **134**, and one or more second light sources **132**. The backlight **130** also includes a dual-sided optical film **140**, details of which are discussed further below. The x-y plane of the coordinate system is assumed to lie parallel to the plane of the film **140**, which is also typically parallel to the plane of the light guide **150** and display panel **120**.

The light sources **132**, **134** are disposed on opposite ends of the light guide, and inject light into the light guide from opposite directions. Each of the light sources may emit light that is nominally white and of a desired hue or color temperature. Alternatively, each light source may emit colored light, e.g., light perceived to be red, green, blue, or another known non-white color, and/or may emit ultraviolet and/or infrared (including near infrared) light. The light sources may also be or comprise clusters of individual light emitting devices, some or all of which may emit non-white colored light, but the combination of light from the individual devices may produce nominally white light, e.g. from the summation of red, green, and blue light. Light sources on opposite ends of the light guide may emit light of different white or non-white colors, or they emit light of the same colors. The light sources **132**, **134** can be of any known design or type, e.g., one or both may be or comprise cold cathode fluorescent lamps (CCFLs), and one or both may be or comprise one or more inorganic solid state light sources such as light emitting diodes (LEDs) or laser diodes, and one or both may be or comprise one or more organic solid state light sources such as organic light emitting diodes (OLEDs). The round shapes used to represent the light sources in the drawings are merely schematic, and should not be construed to exclude LED(s), or any other suitable type of light source. The light sources **132**, **134** are preferably electronically controllable such that either one can be energized to an ON state (producing maximum or otherwise significant light output) while keeping the other one in an OFF state (producing little or no light output), or both can be in the ON state at the same time if desired, and both may be turned OFF during non-use. In many cases, the light sources **132**, **134** do not need to satisfy any particular requirement with regard to switching speed. For example, although either or both light sources **132**, **134** may be capable of repetitively transitioning between the OFF state and the ON state at a rate that is imperceptible to the human eye (e.g., at least 30 or 60 Hz), such a capability is not necessary in many embodiments. (For flicker-free operation, transition rates may be in a range from 50 to 70 Hz, or more; for two-sided operation, transition rates may be in a range from 100 to 140 Hz (or more) for the display panel (if any) and the light sources.) Thus, light sources that have much slower characteristic transition times between the ON and OFF states can also be used.

The light guide **150** includes a first light input side **150c** adjacent to the first light source **134** and an opposing second light input side **150d** adjacent to the second light source **132**. A first light guide major surface **150b** extends between the first side **150c** and second side **150d**. A second light guide major surface **150a**, opposite the first major surface **150b**, extends between the first side **150c** and the second side **150d**. The major surfaces **150b**, **150a** of the light guide **150** may be substantially parallel to each other, or they may be non-parallel such that the light guide **150** is wedge-shaped. Light may be

reflected or emitted from either surface **150b**, **150a** of the light guide **150**, but in general light is emitted from surface **150a** and is reflected from surface **150b**. In some cases, a highly reflective surface may be provided on or adjacent to the first surface **150b** to assist in re-directing light out through the second surface **150a**. Light extraction features **153**, e.g., shallow prisms, lenticular features, white dots, haze coatings, and/or other features, may be disposed on one or both major surfaces **150b**, **150a** of the light guide **150**. Exemplary light extraction features for the light guide are discussed below in connection with FIG. 2. The light extraction features **153** are typically selected so that light emitted from the major surface **150a** propagates preferentially at highly oblique angles in air as measured in the x-z plane, rather than propagating at normal or near-normal propagation directions that are parallel to, or deviate only slightly from, the z-axis (again as measured in the x-z plane). For example, the light emitted from the surface **150a** into air may have a peak intensity direction that makes an angle relative to the surface normal (z-axis) of 60 degrees or more, or 70 degrees or more, or 80 degrees or more, where the peak intensity direction refers to the direction along which the intensity distribution of the output beam in the x-z plane is a maximum.

The light guide **150** may have a solid form, i.e., it may have an entirely solid interior between the first and second major surfaces **150a**, **150b**. The solid material may be or comprise any suitable light-transmissive material, such as glass, acrylic, polyester, or other suitable polymer or non-polymer materials. Alternatively, the light guide **150** may be hollow, i.e., its interior may be air or another gas, or vacuum. If hollow, the light guide **150** is provided with optical films or similar components on opposite sides thereof to provide the first and second major surfaces **150a**, **150b**. Hollow light guides may also be partitioned or subdivided into multiple light guides. Whether solid or hollow, the light guide **150** may be substantially planar, or it may be non-planar, e.g., undulating or curved, and the curvature may be slight (close to planar) or great, including cases where the light guide curves in on itself to form a complete or partial tube. Such tubes may have any desired cross-sectional shape, including curved shapes such as a circle or ellipse, or polygonal shapes such as a square, rectangle, or triangle, or combinations of any such shapes. A hollow tubular light guide may in this regard be made from a single piece of optical film or similar component(s) that turns in on itself to form a hollow tube, in which case the first and second major surfaces of the light guide may both be construed to be provided by such optical film or component(s). The curvature may be only in the x-z plane, or only in the y-z plane, or in both planes. Although the light guide and dual-sided film may be non-planar, for simplicity they are shown in the figures as being planar; in the former case one may interpret the figures as showing a small enough portion of the light guide and/or optical film such that it appears to be planar. Whether solid or hollow, depending on the material(s) of construction and their respective thicknesses, the light guide may be physically rigid, or it may be flexible. A flexible light guide or optical film may be flexed or otherwise manipulated to change its shape from planar to curved or vice versa, or from curved in one plane to curved in an orthogonal plane.

The dual-sided optical film **140** is disposed between the display panel **120** and the light guide **150**. The film **140** has opposed structured surfaces. On the structured surface that is oriented away from

the light guide **150**, split spreading structures **142** are formed. The split spreading structures **142** are depicted in FIGS. 1A and 1B as contiguous extended lenslets, finer details of which are omitted from the drawing for simplicity but described further below. Split spreading structures of alternative design are also described below.

5 Prisms **141** are formed on the opposite structured surface of the film **140**, which is oriented towards the light guide **150**. In this orientation, light emitted from the major surface **150a** of the light guide **150** is incident on the prisms **141**, which help to deviate the incident light. The incident light is deviated by and passes through the film **140** to provide an output light beam that emerges from the film **140**. As described further below, the properties of the output beam are strongly influenced by which of  
10 the light sources **132**, **134** is in an ON state. When one light source is ON, the output beam may be a wide angle beam. When the opposite light source is ON, the output beam may be a narrow angle beam.

Both the prisms **141** and the split spreading structures **142** are typically linear, or, in cases where one or both are not precisely linear (e.g. not straight), they are otherwise extended or elongated along a particular in-plane axis. Thus, the split spreading structures **142** may extend along respective spreading  
15 structure axes that are parallel to each other. One such axis is shown in FIG. 1B as axis **144**, which is assumed to be parallel to the y-axis. The prisms **141** may extend along respective prism axes that are parallel to each other. The spreading structure axes of elongation are typically parallel to the prism axes of elongation. Perfect parallelism is not required, and axes that deviate slightly from perfect parallelism may also be considered to be parallel; however, misalignment results in different amounts of registration  
20 between a given prism/split spreading structure pair at different places along their length on the working surface of the dual-sided film - and such differences in the degree of registration (regardless of whether the degree of registration is tailored to have precise alignment, or intentional misalignment, of the relevant vertices or other reference points, as discussed below) are desirably about 1 micron or less. In some cases, extraction features **153** on the major surface **150b** of the light guide may be linear or  
25 elongated along axes that are parallel to the elongation axes of the split spreading structures and prisms of the film **140**; alternatively, such elongated extraction features **153** may be oriented at other angles.

In the film **140** or pertinent portion thereof, there is a one-to-one correspondence of prisms **141** to split spreading structures **142**. Thus, for each prism **141** there is a unique split spreading structure **142** with which the given prism primarily interacts, and vice versa. One, some, or all of the split spreading  
30 structures **142** may be in substantial registration with their respective prisms **141**. Alternatively, the film **140** may be designed to incorporate a deliberate misalignment or misregistration of some or all of the split spreading structure(s) relative to their respective prism(s). Related to alignment or misalignment of the prisms and split spreading structures is the center-to-center spacings or pitches of these elements. In the case of a display system, the pitch of the split spreading structures **142** and the pitch of the prisms **141**  
35 may be selected to reduce or eliminate Moire patterns with respect to periodic features in the display panel **120**. The pitch of the split spreading structures **142** and the pitch of the prisms **141** can also be determined based upon manufacturability. As LCD panels are manufactured with different pixel pitches, it can be desirable to change the pitch of the optical film to accommodate the different pixel pitches of the

LCD panel. Useful pitch ranges for the respective elements on the structured surface of the optical film **140** is about 10 microns to about 140 microns, for example, but this should not be interpreted in an unduly limiting way.

5 The system **100** can have any useful shape or configuration. In many embodiments, the display panel **120**, the light guide **150**, and/or the dual-sided optical film **140** can have a square or rectangular shape. In some embodiments, however, any or all of these elements may have more than four sides and/or a curved shape.

10 A switchable driving element **160** is electrically connected to the first and second light sources **132**, **134**. This element may contain a suitable electrical power supply, e.g. one or more voltage sources and/or current sources, capable of energizing one or both of the light sources **132**, **134**. The power supply may be a single power supply module or element, or a group or network of power supply elements, e.g., one power supply element for each light source. The driving element **160** may also contain a switch that is coupled to the power supply and to the electrical supply lines that connect to the light sources. The switch may be a single transistor or other switching element, or a group or network of switching modules  
15 or elements. The switch and power supply within the driving element **160** may be configured to have several operational modes. These modes may include two, three, or all of: a mode in which only the first light source **134** is ON; a mode in which only the second light source **132** is ON; a mode in which both the first and second light sources are ON; and a mode in which neither of the first and second light sources are ON (i.e., both are OFF).

20 A controller **170** couples to the switchable driving element **160** and to the display panel **120**. The controller **170** may control or direct the driving element into one of its operational modes so as to selectively energize the light sources. Coupling between the controller **170** and the driving element **160** may be wired, or wireless, or some combination of wired and wireless. For example, a user may employ a mobile phone or other mobile wireless device to activate the driving element **160**, and the mobile phone  
25 or other wireless device may be considered to be part of the controller **170**. The controller **170** may also control the display panel **120** so that it displays a desired image or series of images. Image information may be provided from the controller **170** to the display panel **120** in any known manner. The image may be a still image, sequence of images, video stream, and/or rendered computer graphics, for example.

30 We describe in more detail below how the dual-sided optical film **140** can provide the backlight with the capability to produce a wide angle output beam or a narrow angle output beam, depending on which light sources the driving element **160** energizes. The wide angle output beam allows for viewing of the image by observers that may be widely dispersed in angle or position relative to the backlight **130**. This may be considered to be a "public viewing mode" or "sharing mode" of operation of the optical system **100**, since the display may be viewable by not only a single user but by a group of individuals  
35 substantially angularly separated from each other. The narrow angle output beam only allows viewing of the image by observers that are more narrowly dispersed in angle or position (compared to the wide angle output beam) relative to the backlight **130**. This may be considered to be a "private viewing mode" or "non-sharing mode" of operation of the optical system, since the display may not be easily or readily

viewable by individuals other than a single primary user. The display of system 100 can thus be said to have a selective privacy or selective sharing capability that is electronically switchable. By removing the display panel 120 and making any other suitable adaptations, the system 100 can be readily converted to a luminaire system having a selective spotlight capability that is electronically switchable.

5 Figure 1B is a schematic perspective view of the back light 130 showing the light guide 150, the optical film 140, and the second light sources 132. Like elements between FIGS. 1A and 1B have like reference numerals, and need not be further discussed. The optical film 140 includes split spreading structures 142 oriented away from the light guide 150 and prisms 141 with prism peaks oriented toward the light guide 150. The axis of elongation 144 of the split spreading structures, which may also  
10 correspond to the axis of elongation of the prisms 141, is shown to be parallel to the y-axis. In the case of the prisms 141, the elongation axis runs parallel to the vertex of the prism. The film 140 is shown to be adjacent the light guide 150 but spaced slightly apart. The film 140 may also be mounted or held so that it is in contact with the light guide 150, e.g. the film 140 may rest upon the light guide 150, while still substantially maintaining an air/polymer interface at the facets or inclined side surfaces of the prisms 141  
15 (with a physically thin but optically thick layer of air) so that their refractive characteristics can be preserved. Alternatively, a low refractive index bonding material may be used between the prisms 141 and the light guide 150 to bond the film 140 to the light guide. In this regard, nanovoiced materials having an ultra low index (ULI) of refraction are known that can come somewhat close in refractive index to air, and that can be used for this purpose. See e.g. patent application publications WO 2010/120864  
20 (Hao et al.) and WO 2011/088161 (Wolk et al.), which discuss ULI materials whose refractive index (n) is in a range from about  $n \approx 1.15$  to  $n \gg 1.35$ . See also patent application publications WO 2010/120422 (Kolb et al.), WO 2010/120468 (Kolb et al.), WO 2012/054320 (Coggio et al.), and US 2010/0208349 (Beer et al.). Air gap spacing techniques, e.g. wherein an array of microreplicated posts is used to bond the two components together while substantially maintaining an air gap between them, may also be used.  
25 See e.g. patent application publication US 2013/0039077 (Edmonds et al.).

The disclosed dual-sided optical films and associated components may be provided in a variety of forms and configurations. In some cases, the dual-sided optical film may be packaged, sold, or used by itself, e.g. in piece, sheet, or roll form. In other cases, the dual-sided optical film may be packaged, sold, or used with a light guide whose output beam characteristics are tailored for use with the dual-sided film.  
30 In such cases, the dual-sided film may be bonded to the light guide as discussed above, or they may not be bonded to each other. In some cases, the dual-sided optical film may be packaged, sold, or used with both a light guide that is tailored for use with the dual-sided film, and one or more LED(s) or other light source(s) that are adapted to inject light into the light guide, e.g., from opposite ends thereof as shown generally in FIG. 1A. The dual-sided film, the light guide, and the light source(s) may be bonded,  
35 attached, or otherwise held in proximity to each other to form a lighting module, which may be large or small, rigid or flexible, and substantially flat/planar or non-flat/non-planar, and which may be used by itself or in combination with other components. A lighting system that includes a dual-sided optical film,

a light guide, and one or more light source(s) may be adapted for any desired end use, e.g., a display, a backlight, a luminaire, a task light, or a general-purpose lighting module.

Figure 2 shows a schematic perspective view of an exemplary light guide **250** that may be suitable for use with some or all of the disclosed dual-sided optical films. The light guide **250** may be substituted for the light guide **150** in FIG. 1A, and the properties, options, and alternatives discussed in connection with the light guide **150** will be understood to apply equally to the light guide **250**. Cartesian x-y-z coordinates are provided in FIG. 2 in a manner consistent with the coordinates of FIGS. 1A and 1B. Figure 2 shows in exaggerated fashion exemplary surface structure on the two major surfaces of the light guide **250**, but other orientations of the structured surface(s) relative to the edges or boundaries of the light guide can be used. The light guide **250** includes a first major surface **250a** from which light is extracted towards a dual-sided optical film, a second major surface **250b** opposite the first major surface, and side surfaces **250d**, **250c** which may serve as light injection surfaces for the first and second light sources as discussed elsewhere herein. For example, one light source may be positioned along the side surface **250c** to provide a first oblique light beam emitted from the light guide **250**, and a similar light source can be positioned along the side surface **250d** to provide a second oblique light beam emitted from the light guide **250**. An oblique light beam in this regard refers to a light beam whose intensity distribution in the x-z plane has a peak intensity direction of 60 degrees or more, or 70 degrees or more, or 80 degrees or more relative to the surface normal (z-axis), as discussed above.

The rear major surface **250b** of the light guide is preferably machined, molded, or otherwise formed to provide a linear array of shallow prism structures **252**. These prism structures are elongated along axes parallel to the y-axis, and are designed to reflect an appropriate portion of the light propagating along the length of the light guide (along the x-axis) so that the reflected light can refract out of the front major surface **250a** into air (or a tangible material of suitably low refractive index) at a suitably oblique angle, and onward to the dual-sided optical film. In many cases, it is desirable for the reflected light to be extracted from the front major surface **250a** relatively uniformly along the length of the light guide **250**. The surface **250b** may be coated with a reflective film such as aluminum, or it may have no such reflective coating. In the absence of any such reflective coating, a separate back reflector may be provided proximate the surface **250b** to reflect any downward-propagating light that passes through the light guide so that such light is reflected back into and through the light guide. The prism structures **252** typically have a depth that is shallow relative to the overall thickness of the light guide, and a width or pitch that is small relative to the length of the light guide. The prism structures **252** have apex angles that are typically much greater than the apex angles of prisms used in the disclosed dual-sided optical films. The light guide may be made of any transparent optical material, typically with low scattering such as polycarbonate, or an acrylic polymer such as Sparteck Polycast material. In one exemplary embodiment, the light guide may be made of acrylic material, such as cell-cast acrylic, and may have an overall thickness of 1.4 mm and a length of 140 mm along the x-axis, and the prisms may have a depth of 2.9 micrometers and a width of 81.6 micrometers, corresponding to a prism apex angle of

about 172 degrees. The reader will understand that these values are merely exemplary, and should not be construed as unduly limiting.

The front major surface **250a** of the light guide may be machined, molded, or otherwise formed to provide a linear array of lenticular structures or features **254** that are parallel to each other and to a lenticular elongation axis. In contrast to the elongation axis of the prism structures **252**, the lenticular elongation axis is typically parallel to the x-axis. The lenticular structures **254** may be shaped and oriented to enhance angular spreading in the y-z plane for light that passes out of the light guide through the front major surface, and, if desired, to limit spatial spreading along the y-axis for light that remains in the light guide by reflection from the front major surface. In some cases, the lenticular structures **254** may have a depth that is shallow relative to the overall thickness of the light guide, and a width or pitch that is small relative to the width of the light guide. In some cases, the lenticular structures may be relatively strongly curved, while in other cases they may be more weakly curved. In one embodiment, the light guide may be made of cell-cast acrylic and may have an overall thickness of 0.76 mm, a length of 141 mm along the x-axis, and a width of 66 mm along the y-axis, and the lenticular structures **254** may each have a radius of 35.6 micrometers, a depth of 32.8 micrometers, and a width of 72.6 mm, for example. In this embodiment, the prism structures **252** may have a depth of 2.9 micrometers, a width of 81.6 micrometers, and a prism apex angle of about 172 degrees. Again, the reader will understand that these embodiments are merely exemplary, and should not be construed as unduly limiting; for example, structures other than lenticular structures may be used on the front major surface of the light guide.

As mentioned above, the lenticular structures **254** may be shaped and oriented to limit spatial spreading along the y-axis for light that remains in the light guide by reflection from the front major surface. Limited spatial spreading along the y-axis can also be achieved, or enhanced, with light sources that are collimated (including substantially collimated) in the plane of the light guide, i.e., the x-y plane. Such a light source may be a relatively small area LED die or dies in combination with one or more collimating lenses, mirrors, or the like. FIG. 2A shows the light guide **250** of FIG. 2 in combination with light sources **232a**, **232b**, **232c** arranged along side surface **250d**, and light sources **234a**, **234b**, **234c** arranged along side surface **250c**. These light sources may be substantially collimated, or the lenticular structures **254** may be shaped to limit spatial spreading of light along the y-axis, or both. In the figure, the light sources **232a**, **232b**, **232c** are shown as being ON, and the other light sources are OFF. Due to the collimation of the light sources, the shape of the lenticular structures **254**, or both, the light sources **232a**, **232b**, **232c** illuminate respective stripes or bands **250-1**, **250-2**, **250-3** of the light guide **250**. The bands may be distinct, with little or no overlap as shown in the figure, or they may overlap to some extent. Each of the light sources may be independently addressable, such that the light guide can be effectively subdivided or partitioned as a function of which light sources on each side of the light guide are turned ON. For example, only one of the bands **250-1**, **250-2**, **250-3** may be illuminated, or only two may be illuminated, or all of the bands may be illuminated. Light sources **234a**, **234b**, **234c**, which are located on the opposite side of the light guide, may be aligned with their counterpart light sources at side surface **250d** such that they illuminate the same respective bands **250-1**, **250-2**, **250-3**; alternately, the

light sources **234a**, **234b**, **234c** may be shifted or staggered along the y-direction relative to the light sources at side surface **250d**, such that they illuminate other bands which may or may not overlap with each other in similar fashion to bands **250-1**, **250-2**, **250-3**. The light sources **232a**, **232b**, **232c**, **234a**, **234b**, **234c** may all emit white light, or light of a non-white color or wavelength, or the light sources may  
5 emit different colors. A given portion of the light guide **250**, such as any of the bands **250-1**, **250-2**, **250-3**, may thus function as an independent light guide, and may emit three different output beams as a function of whether only its associated light source(s) at one side surface (e.g. surface **250d**) is ON, or whether only its associated light source(s) at the opposite side surface (e.g. surface **250c**) is ON, or whether both such light sources are ON. When a dual-sided optical film is used with such a light guide,  
10 the spatially banded or striped output capability of the light guide is substantially transferred to the dual-sided optical film, such that, by energizing the appropriate light source(s), a wide angle output beam can emerge from the dual-sided optical film over all (all stripes or bands), or only a portion (at least one but less than all stripes or bands), or none (no stripes or bands) of its output surface, and a narrow angle output beam can also emerge at the same time from the dual-sided optical film over all, or only a portion,  
15 or none of its output surface.

Turning now to FIG. 3, we see there a schematic side view of a lighting system **300** in the context of a coordinate system that is consistent with that of FIGS. 1A, 1B, and 2. System **300** may be the same as or similar to the backlight **130** of FIGS. 1A and 1B, except that the controller **170** in FIG. 3 is not coupled to any display panel, and the light guide **150** of FIG. 3 may have a design substantially as  
20 described in connection with light guide **250** of FIG. 2. Other than this, like elements are labeled with like reference numbers, and need not be discussed further. Furthermore, in FIG. 3, only the light source **134** is energized (ON), and the light source **132** is not energized (OFF). Due to the characteristics of the light guide **150**, the characteristics of the optical film **140**, and the interaction between the light guide and the optical film, light from the light source **134** produces a first output beam **310** emerging from the dual-  
25 sided optical film, the first output beam **310** having a relatively wide angular spread in the x-z plane.

Light from the energized light source **134** enters the light guide **150** through the first side **150c**. This light travels along the light guide **150** generally in the positive x-direction, the light reflecting from the major surfaces **150a**, **150b** to provide a first guided light beam **134-1**. As the beam **134-1** propagates, some of the light is refracted or otherwise extracted from the major surface **150a** to provide an oblique  
30 light beam **134-2**, represented by obliquely oriented arrows representing a direction of maximum light intensity in the x-z plane. The oblique light beam **134-2** is typically emitted over substantially the entire surface area of the major surface **150a**, i.e., not only in the geometric center of the major surface **150a** but also at or near its edges and at intermediate positions in between, as indicated by the multiple oblique arrows. The oblique light beam **134-2** has a direction of maximum light intensity that is most closely  
35 aligned with the positive x-direction. The direction of maximum light intensity of the beam **134-2** may deviate from the positive x-direction by, for example, 30 degrees or less, or 20 degrees or less, or 15 degrees or less, or 10 degrees or less.

Because of the directionality of the oblique light beam **134-2**, light from the light source **134** enters the dual-sided optical film **140** predominantly through only one facet or inclined side surface of each of the prisms **141** on the lower structured surface of the film **140**. The upper structured surface of the film **140** is then designed so that such light is directed primarily to the high spreading portions of the associated split spreading structures **142**, as described in more detail below. As a result, light emerges from the film **140** as the wide/first output beam **310**. The wide output beam **310** arises from the summation of individual output beams or "beamlets" emitted from each split spreading structure **142** across the film **140**. Three such representative beamlets are illustrated in FIG. 3: a beamlet **310-0** emitted at or near the geometric center of the film **140**, a beamlet **310-1** emitted at or near a first end or edge of the film **140**, and a beamlet **310-2** emitted at or near a second end or edge of the film **140**. In the illustrated embodiment, the angular spreads of the individual beams or beamlets are nominally the same as the angular spread of the overall output beam **310**, i.e., the beamlets each have a wide angular spread. The wide angular spread is "wide" relative to the (narrower) angular spread of the output beam produced by the opposite light source; in many cases, the wide angular spread may have a full angular width at half maximum of the intensity distribution in the x-z plane of at least 50 degrees. In other embodiments, the angular spread of the individual beams or beamlets may differ somewhat from that of the overall output beam **310**.

If the first light source **134** is turned OFF and the second light source **132** is turned ON, the system **300** produces a second, narrower output beam. We show two possible different cases of such a narrower output beam in FIGS. 4A and 4B. These two different cases assume different designs or embodiments of the dual-sided optical film **140**, as explained further below, but in each case the optical film **140** produces the relatively wider output beam **310** when only the first light source **134** is turned ON, as shown in FIG. 3.

In one case, the film **140** may be designed to produce a second output beam as shown in FIG. 4A, the second output beam being narrower than the first output beam of FIG. 3. In FIG. 4A, a lighting system **400a** is shown in the context of a coordinate system consistent with that of FIG. 3. The system **400a** may be the same as or similar to the lighting system **300**, except that the light source **134** is not energized (OFF), and the light source **132** is energized (ON). Due to the characteristics of the light guide **150**, the characteristics of the optical film **140**, and the interaction between the light guide and the optical film, light from the light source **132** produces a second output beam **410a** emerging from the dual-sided optical film, the second output beam **410a** having a relatively narrow angular spread in the x-z plane.

Light from the energized light source **132** enters the light guide **150** through the second side **150d**. This light travels along the light guide **150** generally in the negative x-direction, the light reflecting from the major surfaces **150a**, **150b** to provide a first guided light beam **132-1**. As the beam **132-1** propagates, some of the light is refracted or otherwise extracted from the major surface **150a** to provide an oblique light beam **132-2**, represented by obliquely oriented arrows representing a direction of maximum light intensity in the x-z plane. The oblique light beam **132-2** is typically emitted over substantially the entire surface area of the major surface **150a**, i.e., not only in the geometric center of the

major surface **150a** but also at or near its edges and at intermediate positions in between, as indicated by the multiple oblique arrows. The oblique light beam **132-2** has a direction of maximum light intensity that is most closely aligned with the negative x-direction. The direction of maximum light intensity of the beam **132-2** may deviate from the negative x-direction by, for example, 30 degrees or less, or 20 degrees or less, or 15 degrees or less, or 10 degrees or less.

Because of the directionality of the oblique light beam **132-2**, light from the light source **132** enters the dual-sided optical film **140** predominantly through only one facet or inclined side surface of each of the prisms **141** on the lower structured surface of the film **140**, this facet or inclined surface being the opposite of the facet/surface used in connection with FIG. 3. The upper structured surface of the film **140** is then designed so that such light is directed primarily to the low spreading portions of the associated split spreading structures **142**, as described in more detail below. As a result, light emerges from the film **140** as the narrow/second output beam **410a**. The narrow output beam **410a** arises from the summation of individual output beams or "beamlets" emitted from each split spreading structure **142** across the film **140**. Three such representative beamlets are illustrated in FIG. 4A: a beamlet **410-0a** emitted at or near the geometric center of the film **140**, a beamlet **410-1a** emitted at or near a first end or edge of the film **140**, and a beamlet **410-2a** emitted at or near a second end or edge of the film **140**. In the illustrated embodiment, the angular spreads of the individual beams or beamlets are nominally the same as the angular spread of the overall output beam **410a**, i.e., the beamlets each have a narrow angular spread. Such angular spreads are said to be "narrow" because they are narrower than the respective angular spreads of the respective output beams produced when the opposite light source is solely energized; in many cases, the narrow angular spread may have a full angular width at half maximum (FWHM) that is at least 25 degrees less than that of the wide output beam. The beamlets **410-0a**, **410-1a**, **410-2a** are all oriented in substantially the same direction. This results in the second output beam **410a** being diverging as it emerges from the film **140**. An alternative arrangement is shown in FIG. 4B.

As mentioned above, FIG. 4B depicts an alternative embodiment to that of FIG. 4A, but that is also compatible with FIG. 3. In other words, one embodiment of the dual-sided optical film **140** may produce the wide angle output beam of FIG. 3 when only the first light source **134** is ON and the narrow angle output beam of FIG. 4A when only the second light source **132** is ON, while a different embodiment of the dual-sided optical film **140** may produce the wide angle output beam of FIG. 3 when only the first light source **134** is ON and the narrow angle output beam of FIG. 4B when only the second light source **132** is ON.

Thus, in this alternative case, the film **140** is designed to produce a second output beam as shown in FIG. 4B, the second output beam being narrower than the first output beam of FIG. 3. In FIG. 4B, a lighting system **400b** is shown in the context of a coordinate system consistent with that of FIG. 3. The system **400b** may be the same as or similar to the lighting system **300**, except that the light source **134** is not energized (OFF), and the light source **132** is energized (ON). Due to the characteristics of the light guide **150**, the characteristics of the optical film **140**, and the interaction between the light guide and the optical film, light from the light source **132** produces a second output beam **410b** emerging from the dual-

sided optical film, the second output beam **410b** having a relatively narrow angular spread in the x-z plane.

Just as in FIG. 4A, light from the energized light source **132** enters the light guide **150** through the second side **150d**. This light travels along the light guide **150** generally in the negative x-direction, the light reflecting from the major surfaces **150a**, **150b** to provide a first guided light beam **132-1**. As the beam **132-1** propagates, some of the light is refracted or otherwise extracted from the major surface **150a** to provide an oblique light beam **132-2**, represented by obliquely oriented arrows representing a direction of maximum light intensity in the x-z plane. The oblique light beam **132-2** is typically emitted over substantially the entire surface area of the major surface **150a**, i.e., not only in the geometric center of the major surface **150a** but also at or near its edges and at intermediate positions in between, as indicated by the multiple oblique arrows. The oblique light beam **132-2** has a direction of maximum light intensity that is most closely aligned with the negative x-direction. The direction of maximum light intensity of the beam **132-2** may deviate from the negative x-direction by, for example, 30 degrees or less, or 20 degrees or less, or 15 degrees or less, or 10 degrees or less.

Because of the directionality of the oblique light beam **132-2**, light from the light source **132** enters the dual-sided optical film **140** predominantly through only one facet or inclined side surface of each of the prisms **141** on the lower structured surface of the film **140**, this facet or inclined surface being the opposite of the facet/surface used in connection with FIG. 3. The upper structured surface of the film **140** is then designed so that such light is directed primarily to the low spreading portions of the associated split spreading structures **142**, as described in more detail below. As a result, light emerges from the film **140** as the narrow/second output beam **410b**. The narrow output beam **410b** arises from the summation of individual output beams or "beamlets" emitted from each split spreading structure **142** across the film **140**. Three such representative beamlets are illustrated in FIG. 4B: a beamlet **410-0b** emitted at or near the geometric center of the film **140**, a beamlet **410-1b** emitted at or near a first end or edge of the film **140**, and a beamlet **410-2b** emitted at or near a second end or edge of the film **140**. In the illustrated embodiment, the angular spreads of the individual beams or beamlets (in the x-z plane) are each smaller than the angular spread of the overall output beam **410b**, e.g., the difference between the angular spread of an individual beamlet and that of the overall output beam may be 2 or 3 degrees or more. Each individual beamlet may have an angular spread in the x-z plane of 30 degrees or less. The beamlets **410-0b**, **410-1b**, **410-2b** are oriented in different directions as shown, which results in the second output beam **410b** being converging as it emerges from the film **140**. The second beam **410b** achieves a minimum beam width (for the light distribution in the x-z plane) at a beam waist **410b'**, beyond which the beam **410b** diverges. The beam waist **410b'** can be compared to the focal point of a lens, and we may define a distance **f** as the axial distance from the film **140** to the beam waist **410b'**. We can tailor the distance **f** by controlling the spread angles and the tilt angles of the beamlets produced by the low spreading portions of the split spreading structures. Such beam control is discussed further below.

We will now discuss several exemplary dual-sided optical film designs that can be used in any of the optical systems discussed herein. In general, such films have opposed first and second structured

surfaces, the first structured surface having a plurality of extended prisms formed therein, and the second structured surface having a plurality of extended split spreading structures formed therein. Each split spreading structure has a high spreading portion disposed alongside a low spreading portion. The prisms and the split spreading structures are arranged in a one-to-one correspondence of prisms to split spreading structures.

The structured surfaces of the films can be made using any known microreplication techniques, e.g. by embossing or thermoforming a polymer film, or using continuous cast-and-cure methods. In the latter case, a curable polymer material or polymer precursor material may be applied between a transparent carrier film and a suitably configured structured surface tool. The material is then cured and separated from the tool to provide a layer that is bonded to the carrier film and has the desired microstructured topography. One such layer can be applied on one side of the carrier film to form the prisms (see e.g. prisms **141** in FIG. 3), and another such layer can be applied on the opposite side of the carrier film to form the split spreading structures (see e.g. split spreading structures **142** in FIG. 3). In some cases, increased surface roughness is used to distinguish the high spreading portion from the low spreading portion of each split spreading structure, and in such cases, known surface roughening techniques can be used to selectively roughen portions of the structured surface to define the high spreading portions. The roughening technique(s) may be applied to portions of a tool, such that portions having increased surface roughness are produced immediately after separation of the film from the tool. Alternatively or in addition, the selective roughening technique(s) may be applied to a surface before or after microreplication, or in some cases instead of microreplication. To the extent microreplication techniques and/or roughening techniques are used in the fabrication of the film, they are desirably employed in such a manner that the relative positions of elements on opposite structured surfaces of the film, e.g. a given split spreading structure and a given prism, may be controlled, and so that the axial distance between them can also be controlled e.g. by appropriate selection of film thicknesses and coating thicknesses. Reference is made to patent application publication US 2005/0052750 (King et al.), which describes among other things how microrephcated structures can be made in alignment on opposite sides of an article.

The structured surfaces of the disclosed dual-sided optical films, as well as the structured surfaces of the disclosed light guides, can alternatively or in addition be made using known additive manufacturing techniques, sometimes referred to as three-dimensional printing or 3D printing.

Figure 5 is a schematic view of a portion of one exemplary dual-sided optical film **540**. This film has opposed first and second structured surfaces **543**, **544**. The film **540** is shown in relation to a Cartesian x-y-z coordinate system which is consistent with the coordinates in the previous figures. The first structured surface **543** has a plurality of prisms **541** formed therein. The prisms **541** each extend along an elongation axis parallel to the y-axis. The second structured surface **544** has a plurality of split spreading structures **542** formed therein. These too extend along elongation axes that are parallel to the y-axis. The film **540** is shown to include three constituent layers or elements **545**, **546**, **547**, although more or fewer layers are also contemplated. The layer **547** may be a carrier film, and layers **545**, **547** may

be layers that are bonded to the carrier film e.g. using a casting-and-curing procedure or other suitable procedure. The film **540** and its constituent layers are assumed to comprise substantially transparent materials of high optical transmission and low absorption throughout the visible spectrum, although in some cases the film **540**, or one or more of its constituent layers, may include dye(s), pigment(s), and/or other absorptive agent(s) to provide colored and/or grayscale tint(s) to the film **540**. Exemplary materials for use in the film are light-transmissive polymer materials, however, other suitable light-transmissive materials may also be used. The film and/or some or all of its constituent components may have a refractive index for visible wavelengths in a range from 1.4 to 1.7, or from 1.5 to 1.7 (e.g. a refractive index of 1.67 for the carrier film and 1.51 for resin that forms layers **546** and/or **545**), but these ranges should be considered exemplary and not unduly limiting.

Each prism **541** on the structured surface **543** generally has two inclined side surfaces or facets **541a**, **541b**. Some adjacent pairs of these inclined surfaces intersect to form prism vertices, while others intersect to form edges or boundaries for each prism **541**. Both the vertices and the edges/boundaries are shown in FIG. 5 as being pointed or v-shaped; however, non-pointed and non-v-shaped profiles, e.g., truncated profiles, can also be used. The inclined surfaces **541a**, **541b** are typically flat, but surfaces that are somewhat curved or otherwise non-flat can also be used. Each prism **541** can be characterized by a vertex angle, even if the vertex is not sharp. Typical vertex angles are in a range from 50 to 90 degrees, e.g., 63.5 degrees, but this should not be construed as unduly limiting. Regardless of the vertex angle, the vertex is often fairly sharp, e.g., having a radius of curvature of no more than 5, or 3, or 2, or 1. The prisms **541** may collectively be characterized by a pitch **pi**. The pitch may be measured center-to-center, as shown, or from edge-to-edge of adjacent prisms. The pitch is typically uniform over the extent of the structured surface **543**, but in some cases it may not be uniform.

Each split spreading structure **542** on the structured surface **544** has a high spreading portion **542a** and a low spreading portion **542b** disposed alongside each other. In the figure, the high spreading portions are shown shaded to indicate a roughened surface in comparison to the smoother surface of the low spreading portion **542b**. Each split spreading structure **542** is shown as a curved segment or lenslet of the structured surface **544**. However, due to the selective roughening associated with the high spreading portions **542a**, each curved segment as a whole responds to light in a more complex fashion than a conventional lenslet. For each split spreading structure, the high spreading portion **542a** and the low spreading portion **542b** meet along a boundary that is parallel to the axis of elongation of the split spreading structure. One such boundary **542c** is labeled in FIG. 5, the boundary **542c** being parallel to the y-axis. In some embodiments the boundary may undulate in the y-z plane; thus, more generally, the boundary between the high spreading portion and the low spreading portion may be said to be parallel to the elongation axis in plan view. The boundary **542c** may be characterized by a transition between the high and low spreading portions that is sharp and abrupt, or, alternatively, slow and gradual. The split spreading structures **542** may collectively be characterized by a pitch **p2**. The pitch may be measured center-to-center, as shown, or from edge-to-edge of adjacent split spreading structures. The pitch is typically uniform over the extent of the structured surface **543**, but in some cases it may not be uniform.

The pitch  $p_2$  may equal  $p_1$ , whereupon the degree of registration of the split spreading structures **542** to the prisms **541** remains constant or substantially constant over the relevant area of the film **540** along the x-axis. Alternatively,  $p_2$  may be slightly greater than or less than  $p_1$ , whereupon the degree of registration of the structures **542** to the prisms **541** changes over the relevant area of the film **540** along the x-axis.

In FIG. 6 we show a schematic view of a portion of a dual-sided optical film **640** which may be the same as, or similar to, the film **540** of FIG. 5. The view of FIG. 6 is enlarged compared to that of FIG. 5 to allow closer inspection of a single prism/split spreading structure pair, labeled **648**, which is assumed to be immersed in air. The Cartesian coordinate system of FIG. 6 is consistent with the coordinates in FIG. 5 and the previous figures. The film **640** is shown to be unitary, but it may alternatively have the layered construction of FIG. 5, or a different layered construction. The film **640** has a first structured surface **643** with a plurality of prisms **641** formed therein. The surface **643** and prism **641** may be the same as the respective structured surface **543** and prism **541** discussed above. In that regard, the prism **641** has two inclined side surfaces or facets **641a**, **641b**, which may be the same as respective inclined surfaces **541a**, **541b** discussed above. The surfaces **641a**, **641b** intersect to form a prism vertex **Vprism**, which vertex may be a line or ridge extending parallel to the y-axis.

The film **640** also has a second structured surface **644** with a plurality of split spreading structures **642** formed therein. The surface **644** and split spreading structure **642** may be the same as the respective structured surface **544** and split spreading structure **542** discussed above. The split spreading structure **642** thus has a high spreading portion **642a**, which may be the same as portion **542a** discussed above, disposed alongside a low spreading portion **642b**, which may be the same as portion **542b** discussed above. The figure indicates that the high spreading portion **642a** has a roughened surface characteristic relative to low spreading portion **642b**. Taken together, the portions **642a**, **642b** can be considered to form a single curved segment or lenslet. The outer edges of the curved segment (which also correspond to the edges of the split spreading structure **642**) and the outer edges of the prism **641** are shown connected by dashed vertical line segments, which may be considered to mark the boundaries of the prism/split spreading structure pair **648**. A geometrical center of the curved segment (also corresponding to its vertex) is labeled **GC**, and a center of curvature of the curved segment is labeled **C**. The geometric center for each split spreading structure refers to a point on the structured surface half way between the opposed edges or boundaries of the split spreading structure as a whole; in FIG. 6 such edges or boundaries are the terminal ends of the curved segment. In FIG. 6, the geometric center is disposed at the boundary between the high spreading portion **642a** and the low spreading portion **642b**, but in alternative embodiments the high spreading portion may be enlarged and the low spreading portion reduced, or vice versa, such that the geometric center of the split spreading structure lies within the high spreading portion, or within the low spreading portion. The geometrical center **GC** and the prism vertex **Vprism** may be used as reference points with which to characterize the degree of alignment (or misalignment) of the prism **641** relative to the split spreading structure **642**. If the curved segment has a uniform curvature, the center of curvature **C** (typically a line parallel to the y-axis) is the center of curvature for the entire curved

segment, including both the vertex and the outer edges. The curved segment may alternatively have a nonuniform curvature, in which case the center of curvature **C** is applicable to only the vertex, and other portions of the curved segment would have different centers of curvature.

Figures 6A and 6B reproduce the prism/split spreading structure pair **648** of FIG. 6, but  
5 superimpose on it light rays that are indicative of its operation in a mode that produces a wide angle output beam (see e.g. FIG. 3) and a mode that produces a narrow angle output beam (see e.g. FIGS. 4A or 4B). Items having the same reference number as in FIG. 6 refer to the same respective elements, and need no further discussion.

In FIG. 6A, incident light rays **634-2** impinge on the structured surface **643** of the film **640** along  
10 a direction aligned most closely with the positive x-direction. This is analogous to FIG. 3. The incident light rays **634-2** are fairly representative of the oblique light beam **134-2** (see FIG. 3). The light rays **634-2** may for example represent light rays propagating in the x-z plane and making an angle of about  $20 \pm 10$  degrees relative to the x-axis. The light rays **634-2** enter the first inclined side surface **641a** of the prism **641**. The light rays thereafter propagate through the film as generally depicted in the figure. In an  
15 exemplary embodiment, the refractive index of the film **640** may be 1.67 (for a central carrier film portion) and 1.51 (for the prism and split spreading structure portions); the prism apex angle maybe about 60 degrees; the radius of curvature of the curved segment may be uniform or non-uniform, and may be about 40 microns; and the distance between the geometrical center **GC** of the split spreading structure and the prism vertex **Vprism** may be about 110 microns. The foregoing values are merely representative  
20 of a particular embodiment and should not be interpreted in an unduly limiting way. Using these assumptions, the oblique light rays **634-2** will tend to propagate through the film **640** as depicted generally in the figure, and emerge from the film **640** as an output beam represented by the light rays **610A**. The light rays **610A** provide a wide output beam similar to the wide output beam **310** (FIG. 3), or any of its individual beamlets. The film **640** directs the obliquely incident light rays **634-2** primarily to  
25 the high spreading portion **642a** of the split spreading structure **642**. This is so even though some of the incident rays may be directed to the low spreading portion **642b**, and even though some of the incident light rays may be directed to portions of the structured surface **644** that lie outside the bounds of the particular prism/split spreading structure pair **648**.

Figure 6B is for the opposite case, i.e., for the mode that produces a narrow angle output beam.  
30 Thus, incident light rays **632-2** impinge on the structured surface **643** of the film **640** along a direction aligned most closely with the negative x-direction. This is analogous to FIGS. 4A or 4B. The incident light rays **632-2** are fairly representative of the oblique light beam **132-2** (see FIGS. 4A, 4B). The light rays **632-2** may for example represent light rays propagating in the x-z plane and making an angle of about  $20 \pm 10$  degrees relative to the (negative) x-axis. The light rays **632-2** enter the second inclined side  
35 surface **641b** of the prism **641**. The light rays thereafter propagate through the film as generally depicted in FIG. 6B, assuming the same design features as in FIG. 6A. The light rays **632-2** thus emerge from the film **640** as an output beam represented by the light rays **610B**. The light rays **610B** provide a narrow output beam similar to the narrow output beam **410a** (FIG. 4A) or **410b** (FIG. 4B), or any of their

individual beamlets. The film **640** directs the obliquely incident light rays **632-2** primarily to the low spreading portion **642b** of the split spreading structure **642**. This is so even though some of the incident rays may be directed to the high spreading portion **642a**, and even though some of the incident light rays may be directed to portions of the structured surface **644** that lie outside the bounds of the particular prism/split spreading structure pair **648**.

An exemplary dual-sided optical film of an alternative design is shown in FIGS. 7, 8, 8A, and 8B. This film may be composed of the same or similar materials as those discussed above, and can be made with manufacturing techniques and design features that are the same as or similar to those discussed above.

Figure 7 shows a dual-sided optical film **740**. This film has opposed first and second structured surfaces **743**, **744**, and is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures. The first structured surface **743** has a plurality of prisms **741** formed therein. The prisms **741** each extend along an elongation axis parallel to the y-axis. The second structured surface **744** has a plurality of split spreading structures **742** formed therein. These too extend along elongation axes that are parallel to the y-axis. The film **740** has three constituent layers or elements **745**, **746**, **747**, but more or fewer layers are contemplated.

Each prism **741** on the structured surface **743** generally has two inclined side surfaces or facets **741a**, **741b**. Some adjacent pairs of these inclined surfaces intersect to form prism vertices, while others intersect to form edges or boundaries for each prism **741**. Both the vertices and the edges/boundaries are shown in FIG. 7 as being pointed or v-shaped; however, non-pointed and non-v-shaped profiles, e.g., truncated profiles, can also be used. First inclined surfaces **741a** are substantially flat, while second inclined surfaces **741b** have a gentle curvature in the x-z plane. In alternative embodiments, both surfaces may be flat, or both may be curved. The prisms **741** are characterized by a pitch  $p_1$ , which may be the same as or different from the pitch  $p_1$  from previously described embodiments.

Each split spreading structure **742** on the structured surface **744** has a high spreading portion **742a** and a low spreading portion **742b** disposed alongside each other. In the embodiment of FIG. 7, both the high spreading portion **742a** and the low spreading portion **742b** may be characterized by smooth surfaces. However, the high spreading portion **742a** is highly curved in the x-z plane relative to the low spreading portion **742b**, which may be substantially flat as shown. For each split spreading structure, the high spreading portion **742a** and the low spreading portion **742b** meet along a boundary that is parallel to the axis of elongation of the split spreading structure, i.e., parallel to the y-axis. The boundary may be abrupt or gradual. The split spreading structures **742** are characterized by a pitch  $p_2$ , which may be the same as or different from the pitch  $p_2$  from previously described embodiments.

In FIG. 8 we show a schematic view of a portion of a dual-sided optical film **840** which may be the same as, or similar to, the film **740** of FIG. 7. The view of FIG. 8 is enlarged compared to that of FIG. 7 to allow closer inspection of a single prism/split spreading structure pair, labeled **848**, which is assumed to be immersed in air. The Cartesian coordinate system of FIG. 8 is consistent with the coordinates in FIG. 7 and the previous figures. The film **840** is shown to be unitary, but it may

alternatively have the layered construction of FIG. 7, or a different layered construction. The film **840** has a first structured surface **843** with a plurality of prisms **841** formed therein. The surface **843** and prism **841** may be the same as the respective structured surface **743** and prism **741** discussed above. In that regard, the prism **841** has two inclined side surfaces or facets **841a**, **841b**, which may be the same as  
5 respective inclined surfaces **741a**, **741b** discussed above. The surfaces **841a**, **841b** intersect to form a prism vertex **Vprism**, which vertex may be a line or ridge extending parallel to the y-axis.

The film **840** also has a second structured surface **844** with a plurality of split spreading structures **842** formed therein. The surface **844** and split spreading structure **842** may be the same as the respective structured surface **744** and split spreading structure **742** discussed above. The split spreading structure  
10 **842** thus has a high spreading portion **842a**, which may be the same as portion **742a** discussed above, disposed alongside a low spreading portion **842b**, which may be the same as portion **742b** discussed above. The high spreading portion **842a** has a highly curved surface in the x-z plane relative to low spreading portion **842b**. The high spreading portion **842a** is a lenslet which is diverging or concave. The outer edges of the split spreading structure **842** and the outer edges of the prism **841** are shown connected  
15 by dashed vertical line segments, which may be considered to mark the boundaries of the prism/split spreading structure pair **848**. A geometrical center (from the standpoint of the x-z plane) of the split spreading structure **842** is labeled **GC**. The geometrical center **GC** and the prism vertex **Vprism** may be used as reference points with which to characterize the degree of alignment (or misalignment) of the prism **841** relative to the split spreading structure **842**.

20 Figures 8A and 8B reproduce the prism/split spreading structure pair **848** of FIG. 8, but superimpose on it light rays that are indicative of its operation in a mode that produces a wide angle output beam (see e.g. FIG. 3) and a mode that produces a narrow angle output beam (see e.g. FIGS. 4A or 4B). Items having the same reference number as in FIG. 8 refer to the same respective elements, and need no further discussion.

25 In FIG. 8A, incident light rays **834-2** impinge on the structured surface **843** of the film **840** along a direction aligned most closely with the positive x-direction. This is analogous to FIG. 3. The incident light rays **834-2** are fairly representative of the oblique light beam **134-2** (see FIG. 3). The light rays **834-2** were modeled as light rays propagating in the x-z plane and making an angle of  $18 \pm 10$  degrees relative to the x-axis. The light rays **834-2** enter the first inclined side surface **841a** of the prism **841**. Optical  
30 modeling was used to determine how the light rays would thereafter propagate through the film. The modeling assumed: the refractive index of the film **840** was 1.67 (for a central carrier film portion) and 1.51 (for the prism and split spreading structure portions); the prism apex angle was about 63.5 degrees; the radius of curvature of the prism surface **841b** was 160 microns; the radius of curvature of the high spreading portion **842a** was 30 microns; and the distance between the geometrical center **GC** and the  
35 prism vertex **Vprism** was 113 microns. Using these assumptions, the optical modeling computed the trajectories of the light rays **834-2** through the film **840**, and the results are shown as the light rays **810A**. Inspection of FIG. 8A reveals that the light rays **810A** provide a wide output beam similar to the wide output beam **310** (FIG. 3), or any of its individual beamlets. The output beam of rays **810A** is made wider

by the fact that the second inclined surfaces **841b** are curved; this curvature works in concert with the curvature of the high spreading portions **842a** to provide more light spreading than if the inclined surfaces **841b** were flat, in similar fashion to the operation of a compound lens. Inspection of FIG. 8A further reveals that the film **840** directs the obliquely incident light rays **834-2** primarily to the high spreading portion **842a** of the split spreading structure **842**. This is so even though some of the incident rays are directed to the low spreading portion **842b**, and even though some of the incident light rays are directed to portions of the structured surface **844** that lie outside the bounds of the particular prism/split spreading structure pair **848**.

Figure 8B is for the opposite case, i.e., for the mode that produces a narrow angle output beam. Thus, incident light rays **832-2** impinge on the structured surface **843** of the film **840** along a direction aligned most closely with the negative x-direction. This is analogous to FIGS. 4A or 4B. The incident light rays **832-2** are fairly representative of the oblique light beam **132-2** (see FIGS. 4A, 4B). The light rays **832-2** were modeled as light rays propagating in the x-z plane that make an angle of  $18 \pm 10$  degrees relative to the (negative) x-axis. The light rays **832-2** enter the second inclined side surface **841b** of the prism **841**. Optical modeling was used to determine how the light rays would thereafter propagate through the film. The modeling assumed the same design features as in FIG. 8A. Using these assumptions, the optical modeling computed the trajectories of the light rays **832-2** through the film **840**, and the results are shown as the light rays **810B**. Inspection of FIG. 8B reveals that the light rays **810B** provide a narrow output beam similar to the narrow output beam **410a** (FIG. 4A) or **410b** (FIG. 4B), or any of their individual beamlets. Inspection of FIG. 8B further reveals that the film **840** directs the obliquely incident light rays **832-2** primarily to the low spreading portion **842b** of the split spreading structure **842**. This is so even though some of the incident rays are directed to the high spreading portion **842a**, and even though some of the incident light rays are directed to portions of the structured surface **844** that lie outside the bounds of the particular prism/split spreading structure pair **848**.

An exemplary dual-sided optical film of an alternative design is shown in FIGS. 9, 10, 10A, and 10B. This film may be composed of the same or similar materials as those discussed above, and can be made with manufacturing techniques and design features that are the same as or similar to those discussed above.

Figure 9 shows a dual-sided optical film **940**. This film has opposed first and second structured surfaces **943**, **944**, and is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures. The first structured surface **943** has a plurality of prisms **941** formed therein. The prisms **941** each extend along an elongation axis parallel to the y-axis. The second structured surface **944** has a plurality of split spreading structures **942** formed therein. These too extend along elongation axes that are parallel to the y-axis. The film **940** has three constituent layers or elements **945**, **946**, **947**, but more or fewer layers are contemplated.

Each prism **941** on the structured surface **943** generally has two inclined side surfaces or facets **941a**, **941b**. Some adjacent pairs of these inclined surfaces intersect to form prism vertices, while others intersect to form edges or boundaries for each prism **941**. Both the vertices and the edges/boundaries are

shown in FIG. 9 as being pointed or v-shaped; however, non-pointed and non-v-shaped profiles, e.g., truncated profiles, can also be used. Both the first inclined surfaces **941a** and the second inclined surfaces **942b** are substantially flat. In alternative embodiments, one or both surfaces may be gently curved in the x-z plane. The prisms **941** are characterized by a pitch **pi**, which may be the same as or different from the pitch **pi** from previously described embodiments.

Each split spreading structure **942** on the structured surface **944** has a high spreading portion **942a** and a low spreading portion **942b** disposed alongside each other. In the figure, the high spreading portions **942a** are shown shaded to indicate a roughened surface in comparison to the smoother surface of the low spreading portion **942b**. In the embodiment of FIG. 9, both the high spreading portion **942a** and the low spreading portion **942b** may be substantially flat and parallel to the x-y plane, but the low spreading portion **942b** is characterized by a smooth surface (which provides little or no light scattering) in comparison to the high spreading portion **942a**, which is characterized by a roughened surface to provide significant light scattering. For each split spreading structure, the high spreading portion **942a** and the low spreading portion **942b** meet along a boundary that is parallel to the axis of elongation of the split spreading structure, i.e., parallel to the y-axis. The boundary may be abrupt or gradual. The split spreading structures **942** are characterized by a pitch **p2**, which may be the same as or different from the pitch **p2** from previously described embodiments.

In FIG. 10 we show a schematic view of a portion of a dual-sided optical film **1040** which may be the same as, or similar to, the film **940** of FIG. 9. The view of FIG. 10 is enlarged compared to that of FIG. 9 to allow closer inspection of a single prism/split spreading structure pair, labeled **1048**, which is assumed to be immersed in air. The Cartesian coordinate system of FIG. 10 is consistent with the coordinates in FIG. 9 and the previous figures. The film **1040** is shown to be unitary, but it may alternatively have the layered construction of FIG. 9, or a different layered construction. The film **1040** has a first structured surface **1043** with a plurality of prisms **1041** formed therein. The surface **1043** and prism **1041** may be the same as the respective structured surface **943** and prism **941** discussed above. In that regard, the prism **1041** has two inclined side surfaces or facets **1041a**, **1041b**, which may be the same as respective inclined surfaces **941a**, **941b** discussed above. The surfaces **1041a**, **1041b** intersect to form a prism vertex **Vprism**, which vertex may be a line or ridge extending parallel to the y-axis.

The film **1040** also has a second structured surface **1044** with a plurality of split spreading structures **1042** formed therein. The surface **1044** and split spreading structure **1042** may be the same as the respective structured surface **944** and split spreading structure **942** discussed above. The split spreading structure **1042** thus has a high spreading portion **1042a**, which may be the same as portion **942a** discussed above, disposed alongside a low spreading portion **1042b**, which may be the same as portion **942b** discussed above. The high spreading portion **1042a** has a roughened surface characteristic in the x-z plane relative to low spreading portion **1042b**, which is smooth in comparison. The outer edges of the split spreading structure **1042** and the outer edges of the prism **1041** are shown connected by dashed vertical line segments, which may be considered to mark the boundaries of the prism/split spreading structure pair **1048**. A geometrical center (from the standpoint of the x-z plane) of the split spreading

structure **1042** is labeled **GC**. The geometrical center **GC** and the prism vertex **Vprism** may be used as reference points with which to characterize the degree of alignment (or misalignment) of the prism **1041** relative to the split spreading structure **1042**.

5 Figures 10A and 10B reproduce the prism/split spreading structure pair **1048** of FIG. 10, but superimpose on it light rays that are indicative of its operation in a mode that produces a wide angle output beam (see e.g. FIG. 3) and a mode that produces a narrow angle output beam (see e.g. FIGS. 4A or 4B). Items having the same reference number as in FIG. 10 refer to the same respective elements, and need no further discussion.

10 In FIG. 10A, incident light rays **1034-2** impinge on the structured surface **1043** of the film **1040** along a direction aligned most closely with the positive x-direction. This is analogous to FIG. 3. The incident light rays **1034-2** are fairly representative of the oblique light beam **134-2** (see FIG. 3). The light rays **1034-2** may for example represent light rays propagating in the x-z plane and making an angle of about  $20 \pm 10$  degrees relative to the x-axis. The light rays **1034-2** enter the first inclined side surface **1041a** of the prism **1041**. The light rays thereafter propagate through the film as generally depicted in the  
15 figure. In an exemplary embodiment, the refractive index of the film **1040** may be 1.67 (for a central carrier film portion) and 1.51 (for the prism and split spreading structure portions); the prism apex angle may be about 60 degrees; the roughness (Ra) of the high spreading portion **1042a** may be a value substantially greater than that of the low spreading portion **1042b**; and the distance between the geometrical center **GC** and the prism vertex **Vprism** may be 113 microns. The foregoing values are  
20 merely representative of a particular embodiment and should not be interpreted in an unduly limiting way. Using these assumptions, the oblique light rays **1034-2** will tend to propagate through the film **1040** as depicted generally in the figure, and emerge from the film **1040** as an output beam represented by the light rays **1010A**. The light rays **1010A** provide a wide output beam similar to the wide output beam **310** (FIG. 3), or any of its individual beamlets. The film **1040** directs the obliquely incident light rays **1034-2**  
25 primarily to the high spreading portion **1042a** of the split spreading structure **1042**. This is so even though some of the incident rays may be directed to the low spreading portion **1042b**, and even though some of the incident light rays may be directed to portions of the structured surface **1044** that lie outside the bounds of the particular prism/split spreading structure pair **1048**.

30 Figure 10B is for the opposite case, i.e., for the mode that produces a narrow angle output beam. Thus, incident light rays **1032-2** impinge on the structured surface **1043** of the film **1040** along a direction aligned most closely with the negative x-direction. This is analogous to FIGS. 4A or 4B. The incident light rays **1032-2** are fairly representative of the oblique light beam **132-2** (see FIGS. 4A, 4B). The light rays **1032-2** may for example represent light rays propagating in the x-z plane that make an angle of about  $20 \pm 10$  degrees relative to the (negative) x-axis. The light rays **1032-2** enter the second inclined side  
35 surface **1041b** of the prism **1041**. The light rays thereafter propagate through the film as generally depicted in FIG. 10B, assuming the same design features as in FIG. 10A. The light rays **1032-2** thus emerge from the film **1040** as an output beam represented by the light rays **1010B**. The light rays **1010B** provide a narrow output beam similar to the narrow output beam **410a** (FIG. 4A) or **410b** (FIG. 4B), or

any of their individual beamlets. The film **1040** directs the obliquely incident light rays **1032-2** primarily to the low spreading portion **1042b** of the split spreading structure **1042**. This is so even though some of the incident rays may be directed to the high spreading portion **1042a**, and even though some of the incident light rays may be directed to portions of the structured surface **1044** that lie outside the bounds of the particular prism/split spreading structure pair **1048**.

An exemplary dual-sided optical film of an alternative design is shown in FIGS. 11, 12, 12A, and 12B. This film may be composed of the same or similar materials as those discussed above, and can be made with manufacturing techniques and design features that are the same as or similar to those discussed above.

Figure 11 shows a dual-sided optical film **1140**. This film has opposed first and second structured surfaces **1143**, **1144**, and is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures. The first structured surface **1143** has a plurality of prisms **1141** formed therein. The prisms **1141** each extend along an elongation axis parallel to the y-axis. The second structured surface **1144** has a plurality of split spreading structures **1142** formed therein. These too extend along elongation axes that are parallel to the y-axis. The film **1140** has three constituent layers or elements **1145**, **1146**, **1147**, but more or fewer layers are contemplated.

Each prism **1141** on the structured surface **1143** generally has two inclined side surfaces or facets **1141a**, **1141b**. Some adjacent pairs of these inclined surfaces intersect to form prism vertices, while others intersect to form edges or boundaries for each prism **1141**. Both the vertices and the edges/boundaries are shown in FIG. 11 as being pointed or v-shaped; however, non-pointed and non-v-shaped profiles, e.g., truncated profiles, can also be used. Both the first inclined surfaces **1141a** and the second inclined surfaces **1142b** are substantially flat. In alternative embodiments, one or both surfaces may be gently curved in the x-z plane. The prisms **1141** are characterized by a pitch **pi**, which may be the same as or different from the pitch **pi** from previously described embodiments.

Each split spreading structure **1142** on the structured surface **1144** has a high spreading portion **1142a** and a low spreading portion **1142b** disposed alongside each other. In the figure, the high spreading portions **1142a** are shown shaded to indicate a roughened surface in comparison to the smoother surface of the low spreading portion **1142b**. In the embodiment of FIG. 11, both the high spreading portion **1142a** and the low spreading portion **1142b** may be substantially flat and parallel to the x-y plane, but the low spreading portion **1142b** is characterized by a smooth surface (which provides little or no light scattering) in comparison to the high spreading portion **1142a**, which is characterized by a roughened surface to provide significant light scattering. Furthermore, the high spreading portions **1142a** are raised relative to the low spreading portions **1142b**, which may be used to facilitate the selective roughening. For example, the structured surface **1144** may initially be formed such that the portions **1142a** are raised but smooth, and then a roughening operation may be performed on the structured surface, but, due to the recessed nature of the portions **1142b**, only the portions **1142a** are roughened, while the portions **1142b** remain smooth. (In an alternative embodiment in which the roles of the portions **1142a**, **1142b** are reversed, the raised portions may remain smooth, and a diffusive or scattering material may be printed or

otherwise deposited in the recesses but not on the raised portions. In such a case, the portions **1142a** would then be low spreading portions, and the portions **1142b** would be high spreading portions.) For each split spreading structure, the high spreading portion **1142a** and the low spreading portion **1142b** meet along a boundary that is parallel to the axis of elongation of the split spreading structure, i.e.,  
5 parallel to the y-axis. The boundary may be abrupt or gradual. The split spreading structures **1142** are characterized by a pitch **p2**, which may be the same as or different from the pitch **p2** from previously described embodiments.

In FIG. 12 we show a schematic view of a portion of a dual-sided optical film **1240** which may be the same as, or similar to, the film **1140** of FIG. 11. The view of FIG. 12 is enlarged compared to that of  
10 FIG. 11 to allow closer inspection of a single prism/split spreading structure pair, labeled **1248**, which is assumed to be immersed in air. The Cartesian coordinate system of FIG. 12 is consistent with the coordinates in FIG. 11 and the previous figures. The film **1240** is shown to be unitary, but it may alternatively have the layered construction of FIG. 11, or a different layered construction. The film **1240** has a first structured surface **1243** with a plurality of prisms **1241** formed therein. The surface **1243** and  
15 prism **1241** may be the same as the respective structured surface **1143** and prism **1141** discussed above. In that regard, the prism **1241** has two inclined side surfaces or facets **1241a**, **1241b**, which may be the same as respective inclined surfaces **1141a**, **1141b** discussed above. The surfaces **1241a**, **1241b** intersect to form a prism vertex **Vprism**, which vertex may be a line or ridge extending parallel to the y-axis.

The film **1240** also has a second structured surface **1244** with a plurality of split spreading  
20 structures **1242** formed therein. The surface **1244** and split spreading structure **1242** may be the same as the respective structured surface **1144** and split spreading structure **1142** discussed above. The split spreading structure **1242** thus has a high spreading portion **1242a**, which may be the same as portion **1142a** discussed above, disposed alongside a low spreading portion **1242b**, which may be the same as portion **1142b** discussed above. The high spreading portion **1242a** has a roughened surface characteristic  
25 in the x-z plane relative to low spreading portion **1242b**, which is smooth in comparison, and the portion **1242a** is raised relative to the portion **1242b**. The outer edges of the split spreading structure **1242** and the outer edges of the prism **1241** are shown connected by dashed vertical line segments, which may be considered to mark the boundaries of the prism/split spreading structure pair **1248**. A geometrical center (from the standpoint of the x-z plane) of the split spreading structure **1242** is labeled **GC**. The  
30 geometrical center **GC** and the prism vertex **Vprism** may be used as reference points with which to characterize the degree of alignment (or misalignment) of the prism **1241** relative to the split spreading structure **1242**.

Figures 12A and 12B reproduce the prism/split spreading structure pair **1248** of FIG. 12, but superimpose on it light rays that are indicative of its operation in a mode that produces a wide angle  
35 output beam (see e.g. FIG. 3) and a mode that produces a narrow angle output beam (see e.g. FIGS. 4A or 4B). Items having the same reference number as in FIG. 12 refer to the same respective elements, and need no further discussion.

In FIG. 12A, incident light rays **1234-2** impinge on the structured surface **1243** of the film **1240** along a direction aligned most closely with the positive x-direction. This is analogous to FIG. 3. The incident light rays **1234-2** are fairly representative of the oblique light beam **134-2** (see FIG. 3). The light rays **1234-2** may for example represent light rays propagating in the x-z plane and making an angle of about  $20 \pm 10$  degrees relative to the x-axis. The light rays **1234-2** enter the first inclined side surface **1241a** of the prism **1241**. The light rays thereafter propagate through the film as generally depicted in the figure. In an exemplary embodiment, the refractive index of the film **1240** may be 1.67 (for a central carrier film portion) and 1.51 (for the prism and split spreading structure portions); the prism apex angle may be about 60 degrees; the roughness (Ra) of the high spreading portion **1242a** may be a value substantially greater than that of the low spreading portion **1242b**; the vertical separation between the high spreading portion **1242a** and the low spreading portion **1242b** may be 25 microns; and the distance between the geometrical center **GC** and the prism vertex **Vprism** may be 113 microns. The foregoing values are merely representative of a particular embodiment and should not be interpreted in an unduly limiting way. Using these assumptions, the oblique light rays **1234-2** will tend to propagate through the film **1240** as generally depicted in the figure, and emerge from the film **1240** as an output beam represented by the light rays **1210A**. The light rays **1210A** provide a wide output beam similar to the wide output beam **310** (FIG. 3), or any of its individual beamlets. The film **1240** directs the obliquely incident light rays **1234-2** primarily to the high spreading portion **1242a** of the split spreading structure **1242**. This is so even though some of the incident rays may be directed to the low spreading portion **1242b**, and even though some of the incident light rays may be directed to portions of the structured surface **1244** that lie outside the bounds of the particular prism/split spreading structure pair **1248**.

Figure 12B is for the opposite case, i.e., for the mode that produces a narrow angle output beam. Thus, incident light rays **1232-2** impinge on the structured surface **1243** of the film **1240** along a direction aligned most closely with the negative x-direction. This is analogous to FIGS. 4A or 4B. The incident light rays **1232-2** are fairly representative of the oblique light beam **132-2** (see FIGS. 4A, 4B). The light rays **1232-2** may for example represent light rays propagating in the x-z plane that make an angle of about  $20 \pm 10$  degrees relative to the (negative) x-axis. The light rays **1232-2** enter the second inclined side surface **1241b** of the prism **1241**. The light rays thereafter propagate through the film as generally depicted in FIG. 12B, assuming the same design features as in FIG. 12A. The light rays **1232-2** thus emerge from the film **1240** as an output beam represented by the light rays **1210B**. The light rays **1210B** provide a narrow output beam similar to the narrow output beam **410a** (FIG. 4A) or **410b** (FIG. 4B), or any of their individual beamlets. The film **1240** directs the obliquely incident light rays **1232-2** primarily to the low spreading portion **1242b** of the split spreading structure **1242**. This is so even though some of the incident rays may be directed to the high spreading portion **1242a**, and even though some of the incident light rays may be directed to portions of the structured surface **1244** that lie outside the bounds of the particular prism/split spreading structure pair **1248**.

An exemplary dual-sided optical film of an alternative design is shown in FIGS. 13, 14, 14A, and 14B. This film may be composed of the same or similar materials as those discussed above, and can be

made with manufacturing techniques and design features that are the same as or similar to those discussed above.

Figure 13 shows a dual-sided optical film **1340**. This film has opposed first and second structured surfaces **1343**, **1344**, and is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures. The first structured surface **1343** has a plurality of prisms **1341** formed therein. The prisms **1341** each extend along an elongation axis parallel to the y-axis. The second structured surface **1344** has a plurality of split spreading structures **1342** formed therein. These too extend along elongation axes that are parallel to the y-axis. The film **1340** has three constituent layers or elements **1345**, **1346**, **1347**, but more or fewer layers are contemplated.

Each prism **1341** on the structured surface **1343** generally has two inclined side surfaces or facets **1341a**, **1341b**. Some adjacent pairs of these inclined surfaces intersect to form prism vertices, while others intersect to form edges or boundaries for each prism **1341**. Both the vertices and the edges/boundaries are shown in FIG. 13 as being pointed or v-shaped; however, non-pointed and non-v-shaped profiles, e.g., truncated profiles, can also be used. Both the first inclined surfaces **1341a** and the second inclined surfaces **1342b** are substantially flat. In alternative embodiments, one or both surfaces may be gently curved in the x-z plane. The prisms **1341** are characterized by a pitch **pi**, which may be the same as or different from the pitch **pi** from previously described embodiments.

Each split spreading structure **1342** on the structured surface **1344** has a high spreading portion **1342a** and a low spreading portion **1342b** disposed alongside each other. In the figure, both the high spreading portion **1342a** and the low spreading portion **1342b** may be characterized by smooth surfaces. However, the high spreading portion **1342a** is highly curved in the x-z plane relative to the low spreading portion **1342b**, which may be substantially flat and parallel to the x-y plane as shown. (Note that the curvature of the high spreading portions **1342a** is opposite that of the high spreading portions **742a** in FIG. 7 - the spreading portions **1342a** being positive or focusing lenslets and the spreading portions **742a** being negative or defocusing lenslets.) The high spreading portion **1342a** is a lenslet which is converging or convex. For each split spreading structure, the high spreading portion **1342a** and the low spreading portion **1342b** meet along a boundary that is parallel to the axis of elongation of the split spreading structure, i.e., parallel to the y-axis. The boundary may be abrupt or gradual. The split spreading structures **1342** are characterized by a pitch **p2**, which may be the same as or different from the pitch **p2** from previously described embodiments.

In FIG. 14 we show a schematic view of a portion of a dual-sided optical film **1440** which may be the same as, or similar to, the film **1340** of FIG. 13. The view of FIG. 14 is enlarged compared to that of FIG. 13 to allow closer inspection of a single prism/split spreading structure pair, labeled **1448**, which is assumed to be immersed in air. The Cartesian coordinate system of FIG. 14 is consistent with the coordinates in FIG. 13 and the previous figures. The film **1440** is shown to be unitary, but it may alternatively have the layered construction of FIG. 13, or a different layered construction. The film **1440** has a first structured surface **1443** with a plurality of prisms **1441** formed therein. The surface **1443** and prism **1441** may be the same as the respective structured surface **1343** and prism **1341** discussed above.

In that regard, the prism **1441** has two inclined side surfaces or facets **1441a**, **1441b**, which may be the same as respective inclined surfaces **1341a**, **1341b** discussed above. The surfaces **1441a**, **1441b** intersect to form a prism vertex **Vprism**, which vertex may be a line or ridge extending parallel to the y-axis.

The film **1440** also has a second structured surface **1444** with a plurality of split spreading structures **1442** formed therein. The surface **1444** and split spreading structure **1442** may be the same as the respective structured surface **1344** and split spreading structure **1342** discussed above. The split spreading structure **1442** thus has a high spreading portion **1442a**, which may be the same as portion **1342a** discussed above, disposed alongside a low spreading portion **1442b**, which may be the same as portion **1342b** discussed above. The high spreading portion **1442a** has a highly curved surface in the x-z plane relative to low spreading portion **1442b**. The outer edges of the split spreading structure **1442** and the outer edges of the prism **1441** are shown connected by dashed vertical line segments, which may be considered to mark the boundaries of the prism/split spreading structure pair **1448**. A geometrical center (from the standpoint of the x-z plane) of the split spreading structure **1442** is labeled **GC**. The geometrical center **GC** and the prism vertex **Vprism** may be used as reference points with which to characterize the degree of alignment (or misalignment) of the prism **1441** relative to the split spreading structure **1442**.

Figures 14A and 14B reproduce the prism/split spreading structure pair **1448** of FIG. 14, but superimpose on it light rays that are indicative of its operation in a mode that produces a wide angle output beam (see e.g. FIG. 3) and a mode that produces a narrow angle output beam (see e.g. FIGS. 4A or 4B). Items having the same reference number as in FIG. 14 refer to the same respective elements, and need no further discussion.

In FIG. 14A, incident light rays **1434-2** impinge on the structured surface **1443** of the film **1440** along a direction aligned most closely with the positive x-direction. This is analogous to FIG. 3. The incident light rays **1434-2** are fairly representative of the oblique light beam **134-2** (see FIG. 3). The light rays **1434-2** were modeled as light rays propagating in the x-z plane and making an angle of 18 degrees relative to the x-axis. The light rays **1434-2** enter the first inclined side surface **1441a** of the prism **1441**. Optical modeling was used to determine how the light rays would thereafter propagate through the film. The modeling assumed: the refractive index of the film **1440** was 1.67 (for a central carrier film portion) and 1.51 (for the prism and split spreading structure portions); the prism apex angle was 60 degrees; the radius of curvature of the high spreading portion **1442a** was 22.3 microns; and the distance between the geometrical center **GC** and the prism vertex **Vprism** was 113 microns. Using these assumptions, the optical modeling computed the trajectories of the light rays **1434-2** through the film **1440**, and the results are shown as the light rays **1410A**. Inspection of FIG. 14A reveals that the light rays **1410A** provide a wide output beam similar to the wide output beam **310** (FIG. 3), or any of its individual beamlets. Inspection of FIG. 14A further reveals that the film **1440** directs the obliquely incident light rays **1434-2** primarily to the high spreading portion **1442a** of the split spreading structure **1442**. This is so even though some of the incident rays are directed to the low spreading portion **1442b**, and even though some

of the incident light rays are directed to portions of the structured surface **1444** that lie outside the bounds of the particular prism/split spreading structure pair **1448**.

Figure 14B is for the opposite case, i.e., for the mode that produces a narrow angle output beam. Thus, incident light rays **1432-2** impinge on the structured surface **1443** of the film **1440** along a direction aligned most closely with the negative x-direction. This is analogous to FIGS. 4A or 4B. The incident light rays **1432-2** are fairly representative of the oblique light beam **132-2** (see FIGS. 4A, 4B). The light rays **1432-2** were modeled as light rays propagating in the x-z plane that make an angle of  $18 \pm 5$  degrees relative to the (negative) x-axis. The light rays **1432-2** enter the second inclined side surface **1441b** of the prism **1441**. Optical modeling was used to determine how the light rays would thereafter propagate through the film. The modeling assumed the same design features as in FIG. 14A. Using these assumptions, the optical modeling computed the trajectories of the light rays **1432-2** through the film **1440**, and the results are shown as the light rays **1410B**. Inspection of FIG. 14B reveals that the light rays **1410B** provide a narrow output beam similar to the narrow output beam **410a** (FIG. 4A) or **410b** (FIG. 4B), or any of their individual beamlets. Inspection of FIG. 14B further reveals that the film **1440** directs the obliquely incident light rays **1432-2** primarily to the low spreading portion **1442b** of the split spreading structure **1442**. This is so even though some of the incident rays are directed to the high spreading portion **1442a**, and even though some of the incident light rays are directed to portions of the structured surface **1444** that lie outside the bounds of the particular prism/split spreading structure pair **1448**.

Having now described several dual-sided optical films that incorporate split spreading structures and prisms, we now discuss in more detail various ways in which these elements can be combined in a film to produce a desired output beam in a lighting system. Particular attention is given to the mode of operation in which a narrow angle output beam is produced, but the wide angle output beam is also affected. Design details of each prism/split spreading structure pair in the film, including the vertical separation of the prism and split spreading structure, the relative transverse position of these elements (whether they are in transverse alignment or not), the amount of tilt (if any) of the prism, and the amount of tilt (if any) of the split spreading structure, determine the shape and other properties of the output beam or beamlet produced by the given prism/split spreading structure pair, for a given input light beam. In some cases, a design parameter such as relative transverse position and/or amount of tilt changes over the face of the film, having one value in the center of the film and monotonically increasing or decreasing towards the outer edges or extremities of the film. Such spatial variation can be used to produce output beams such as output beam **410b** of FIG. 4B. In other cases, the relevant design parameters may all be substantially the same over the face of the film, such that the beams or beamlets produced by all of the prism/split spreading structure pairs are substantially the same. Such spatial uniformity can be used to produce output beams such as output beam **410a** in FIG. 4A.

A dual-sided optical film **1540** is shown schematically in FIG. 15. The film **1540** has a first structured surface **1543** and a second structured surface **1544**, the first structured surface **1543** having formed therein a plurality of prisms **1541**, and the second structured surface **1544** having formed therein a

plurality of split spreading structures **1542**. For generality, the split spreading structures **1542** are shown very schematically as thin boxes or rectangles, which together form a structured surface. The reader will understand that these thin boxes may represent any of the split spreading structured disclosed herein. The film **1540** is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures.

5 Each prism **1541** includes two inclined side surfaces or facets that intersect at a vertex **Vprism**. Each prism **1541** also has a prism optical axis **1549-1**. The prism optical axis **1549-1** lies in the x-z plane, passes through the prism vertex, and bisects the prism vertex angle such that it is equidistant from both inclined side surfaces. The prisms **1541** are characterized by a prism pitch  $p_i$  from center-to-center (e.g. prism vertex to prism vertex) along the x-axis, the pitch  $p_l$  not labeled in FIG. 15 for reduced clutter.

10 Each split spreading structure **1542** has a high spreading portion and a low spreading portion, not shown in FIG. 15. Each split spreading structure **1542** is characterized by a geometrical center GC as discussed above, and a spreading structure optical axis **1549-2**. The spreading structure optical axis **1549-2** passes through the geometrical center GC, and: if the split spreading structure is substantially symmetrical (see e.g. split spreading structures **642** and **1042** in FIGS. 6 and 10, respectively), then the  
15 spreading structure optical axis **1549-2** is the axis of symmetry of the split spreading structure **1542**;  
otherwise, if no substantial symmetry is present in the split spreading structure, but if one or both of the high spreading portion or the low spreading portion is flat (see e.g. split spreading structures **842**, **1242**,  
**1442** in FIGS. 8, 12, and 14 respectively) then the spreading structure optical axis **1549-2** is  
perpendicular to such flat surface(s); otherwise, if no substantial symmetry is present in the split  
20 spreading structure and neither the high spreading portion nor the low spreading portion is flat, then the  
spreading structure optical axis **1549-2** is perpendicular to a plane that is a best fit to the topography of  
the split spreading structure **1542**. The split spreading structures **1542** are characterized by a spreading  
structure pitch  $p_2$  from center-to-center (e.g. GC to GC) along the x-axis, the pitch  $p_2$  not labeled in FIG.  
15 for reduced clutter.

25 In the film **1540**, the structured surfaces **1543**, **1544** are configured such that  $p_i = p_2$ , and each of  
the prism vertices **Vprism** is vertically aligned with the GC of its respective split spreading structure, and  
the prism optical axes **1549-1** are parallel to each other and to the z-axis, and the spreading structure  
optical axes **1549-2** are also parallel to each other and to the z-axis. All of the prism optical axes **1549-1**  
and all of the spreading structure optical axes **1549-2** in the film **1540** thus have zero tilt. In alternative  
30 embodiments,  $p_i$  may again equal  $p_2$ , but the prism vertices **Vprism** may be misaligned from their  
respective split spreading structure GC points by a desired amount in order to steer the output beam in a  
particular direction.

Another dual-sided optical film **1640** is shown in FIG. 16, in the same schematic fashion as the  
film of FIG. 15. The film **1640** has a first structured surface **1644** and a second structured surface **1644**,  
35 the first structured surface **1643** having formed therein a plurality of prisms **1641**, and the second  
structured surface **1644** having formed therein a plurality of split spreading structures **1642**. The film  
**1640** is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures.

Each prism **1641** includes two inclined side surfaces or facets that intersect at a vertex **Vprism**, and a prism optical axis **1649-1** as discussed above. The prisms **1641** are characterized by a prism pitch  $p_1$ , which is not labeled in FIG. 16 for reduced clutter.

Each split spreading structure **1642** has a high spreading portion and a low spreading portion, not shown in FIG. 16. Each split spreading structure **1642** is characterized by a geometrical center GC and a spreading structure optical axis **1649-2** as discussed above. The split spreading structures **1642** are characterized by a spreading structure pitch  $p_2$ , which is not labeled in FIG. 16 for reduced clutter.

In the film **1640**, the structured surfaces **1643**, **1644** are configured such that  $p_1 > p_2$ , and the prism optical axes **1649-1** are parallel to each other and to the z-axis, and the spreading structure optical axes **1649-2** are also parallel to each other and to the z-axis. All of the prism optical axes **1649-1** and all of the spreading structure optical axes **1649-2** in the film **1640** thus have zero tilt. For the prism/split spreading structure pair located in the center of the film (fifth vertex from the left extremity of the film and fifth vertex from the right extremity of the film), the prism vertex **Vprism** is vertically aligned with the GC of its respective split spreading structure. However, for the remaining prism/split spreading structure pairs on the film, no such vertical alignment occurs, and the amount of misalignment increases monotonically with increasing distance from the center of the film **1640**. Films made using the technique shown in FIG. 16, or more generally where  $p_1 \neq p_2$ , can produce an effect where the central distribution of the output light can be pointed or aimed inward to produce a converging effect e.g. as shown in FIG. 4B. Greater degrees of misalignment produce greater levels of crosstalk, and the maximum acceptable degree of misalignment may be limited by the maximum acceptable crosstalk level for a particular application. Crosstalk is brought on when nominally aligned feature pairs (prism/split spreading structure pairs) begin to overlap with their nearest neighbors. In some cases, this approach of aiming light may be limited to an angle between the normal direction of the film (z-axis) and the central output angle of the various prism/split spreading structure pairs of about 10 degrees or less. Limits on this angle of deviation may depend on geometrical aspects of the film, such as thickness (see  $D_z$  in FIG. 18), pitch, substrate, included angle of the prism, etc., and is affected by the output distribution of the light guide.

Still another dual-sided optical film **1740** is shown in FIG. 17, in the same schematic fashion as the films of FIGS. 15 and 16. The film **1740** has a first structured surface **1744** and a second structured surface **1744**, the first structured surface **1743** having formed therein a plurality of prisms **1741**, and the second structured surface **1744** having formed therein a plurality of split spreading structures **1742**. The film **1740** is shown in relation to a Cartesian x-y-z coordinate system consistent with the previous figures.

Each prism **1741** includes two inclined side surfaces or facets that intersect at a vertex **Vprism**, and a prism optical axis **1749-1** as discussed above. The prisms **1741** are characterized by a prism pitch  $p_1$ , which is not labeled in FIG. 17 for reduced clutter.

Each split spreading structure **1742** has a high spreading portion and a low spreading portion, not shown in FIG. 17. Each split spreading structure **1742** is characterized by a geometrical center GC and a spreading structure optical axis **1749-2** as discussed above. The split spreading structures **1742** are characterized by a spreading structure pitch  $p_2$ , which is not labeled in FIG. 17 for reduced clutter.

In the film **1740**, the structured surfaces **1743**, **1744** are configured such that  $p_1 > p_2$ , and the spreading structure optical axes **1749-2** are parallel to each other and to the z-axis. All of the spreading structure optical axes **1749-2** in the film **1740** thus have zero tilt (but in alternative embodiments they may have nonzero tilts, see e.g. FIG. 19). However, the prism optical axes **1749-1** are tilted as a function of position on the film, with the center prism (fifth vertex from the left or right extremity of the film) having zero tilt (parallel to the z-axis), prisms to the left of the center prism having positive tilts which monotonically increase with increasing distance from the center prism, and prisms to the right of the center prism having negative tilts which also monotonically increase (in magnitude) with increasing distance from the center prism. In this regard, positive tilts refer to clockwise tilts, and negative tilts refer to counterclockwise tilts. The prism vertex **V<sub>prism</sub>** for the center prism is vertically aligned with the CG of its respective split spreading structure, but for the remaining prism/split spreading structure pairs on the film, no such vertical alignment occurs, and the amount of misalignment increases monotonically with increasing distance from the center of the film **1740**. Film made using the technique shown in FIG. 17, or more generally where the prisms and/or split spreading structures are tilted) can produce an effect where the central distribution of the output light can be pointed or aimed inward to produce a converging effect e.g. as shown in FIG. 4B. Greater degrees of misalignment produce greater levels of crosstalk, and the maximum acceptable degree of misalignment may be limited by the maximum acceptable crosstalk level for a particular application, as discussed above. In some cases, this approach of aiming light may be limited to an angle between the normal direction of the film (z-axis) and the central output angle of the various prism/split spreading structure pairs of about 35 degrees or less. Limits on this angle of deviation may depend on geometrical aspects of the film, such as thickness (see Dz in FIG. 18), pitch, substrate, included angle of the prism, etc., and is affected by the output distribution of the light guide. Reference is also made to patent application publication US 2012/0236403 (Sykora et al.) for further details of this alignment technique.

In still other alternative designs, the split spreading structures in any of FIGS. 15, 16, and 17 may be tilted in any desired fashion, for example, in a manner that changes as a function of position on the film, e.g., having zero tilt in the center of the film, increasingly positive tilts from the center to the left edge of the film, and increasingly negative tilts from the center to the right edge of the film.

Figures 18 and 19 show enlarged depictions of different prism/split spreading structure pairs that may be present in a dual-sided optical film. In FIG. 18, the elements of the pair are translationally and rotationally aligned with each other. In FIG. 19, the elements are translationally and rotationally misaligned with each other, and tilted by different amounts. In both of these figures, for generality, the split spreading structures are represented schematically by a thin box or rectangle, just as in FIGS. 15 through 17.

In FIG. 18, a prism/split spreading structure pair **1848** has one prism **1841** and one split spreading structure **1842**. The prism **1841** has inclined side surfaces or facets **1841a**, **1841b** which meet at a vertex **V<sub>prism</sub>**. The prism **1841** also has a prism optical axis **1849-1**, as discussed above. The split spreading structure **1842** has a geometrical center GC and a spreading structure optical axis **1849-2**, as discussed

above. By appropriate selection of film thicknesses and/or coating thicknesses, the vertical distance  $Dz$  between the prism vertex and the GC of the structure **1842** can be controlled to provide desired optical performance of the output beams. Determining an optimal value for  $Dz$  also typically takes into consideration the refractive index of the optical film. The optical axes **1849-1**, **1849-2** are parallel to each other and to the z-axis, and in alignment with each other.

In FIG. 19, a prism/split spreading structure pair **1948** has one prism **1941** and one split spreading structure **1942**. The prism **1941** has inclined side surfaces or facets **1941a**, **1941b** which meet at a vertex **Vprism**. The prism **1941** also has a prism optical axis **1949-1**, as discussed above. The split spreading structure **1942** has a geometrical center GC and a spreading structure optical axis **1949-2**, as discussed above. By appropriate selection of film thicknesses and/or coating thicknesses, the vertical distance  $Dz$  between the prism vertex and the GC of the structure **1942** can be controlled to provide desired optical performance of the output beams, also taking into consideration the refractive index of the optical film. The split spreading structure **1942** is translationally misaligned with the prism **1941** by a displacement amount  $Dx$  along the x-axis. The split spreading structure **1942** is also rotationally misaligned with the prism **1941**: the spreading structure optical axis **1949-2** is tilted in the x-z plane with respect to the prism optical axis **1949-1**, and furthermore, both the spreading structure optical axis **1949-2** and the prism optical axis **1949-1** are tilted with respect to the z-axis. The angles  $\alpha$  and  $\beta$  can be used to refer to the tilt angles of the spreading structure optical axis and the prism optical axis, as shown in the figure. The dual-sided optical films disclosed herein can make appropriate use of the design parameters  $Dz$ ,  $Dx$ ,  $\alpha$ , and  $\beta$ , which may be uniform over the area of the film (for all prism/split spreading structure pairs) or which may be non-uniform over such area, to provide a wide angle output beam when one light source is ON, and to provide a narrow angle output beam when a different light source is ON.

Figures 20A and 20B are graphs that show idealized angular distributions associated with the disclosed dual-sided optical films. The curves in these figures are not real data, but rather illustrate in an idealized fashion the possible operation of an optical system containing a suitably tailored dual-sided optical film. These figures graph relative light intensity in the x-z plane as a function of polar angle  $\Theta$  where  $\Theta$  is the angle between the propagation direction of light in air and the z-axis. In FIG. 20A, one light source of the optical system, such as light source **134** in FIG. 3, is ON, and the other light source is OFF. Light from the light source is provided to the optical film as an input beam **2034-2** of highly oblique light. See e.g. oblique light beam **134-2** of FIG. 3. This input beam enters the dual-sided optical film through first inclined surfaces of the prisms, which first inclined surfaces are associated primarily with the high spreading portions of the split spreading structures. Consequently, the beam emerges from the film as a wide angle output beam **2010A**. The curve **2010A** represents the light output over the entire area of the dual-sided optical film, but may also represent each of the individual beams or beamlets that emerge from each prism/split spreading structure pair of the film.

In FIG. 20B, the opposite light source, such as light source **132** in FIG. 4A or 4B, is ON. Light from this light source is provided to the optical film as an input beam **2032-2** of highly oblique light. See e.g. oblique light beam **132-2** of FIG. 4A or 4B. This input beam enters the dual-sided optical film

through second inclined surfaces of the prisms, which second inclined surfaces are associated primarily with the low spreading portions of the split spreading structures. Consequently, the beam emerges from the film as a narrow angle output beam **2010B**. The curve **2010B** represents the light output over the entire area of the dual-sided optical film, but may also represent each of the individual beams or beamlets that emerge from each prism/split spreading structure pair of the film. By tilting the optical axes of the prisms and/or the split spreading structures, and/or by misaligning the prisms with their associated split spreading structures, the narrow output beam can be tailored to emerge from the film along a primary direction that is not orthogonal to the film, see e.g. alternative narrow angle output beams **2010B'** and **2010B''**.

Figure 21 is a schematic view of a display system **2100** that utilizes an exemplary dual-sided optical film. The system includes one or more first light sources **2134**, one or more second light sources **2132**, a backlight package **2130**, and a display panel (not shown). The light sources **2134**, **2132** may be the same as or similar to light sources **134**, **132** discussed above. The backlight package **2130** contains at least a light guide and a dual-sided optical film, in an arrangement such as that of FIGS. 1A and 1B. The dual-sided optical film may have any of the design characteristics discussed herein, suitably tailored for this application. In accordance with the foregoing discussion of those design characteristics, the dual-sided optical film is designed to provide, in a first mode of operation, a wide angle output beam **2110A** when the first light source **2134** is ON and the second light source **2132** is OFF, and to provide in a second mode of operation a narrow angle output beam **2110B** when the second light source **2132** is ON and the first light source **2134** is OFF. The system **2100** desirably includes a switch that the user can activate to change from the first mode of operation to the second, or vice versa. In the first mode of operation, the wide angle output beam **2110A** is provided, which allows not only a centrally located observer **2102** to view the display but also peripherally located observers **2103**, **2104**. This may be considered to be a public viewing mode of operation of the system **2130**. In the second mode of operation, the narrow angle output beam **2110B** is provided, which allows only the centrally located observer **2102**, not the peripherally located observers **2103**, **2104**, to view the display. This may be considered to be a private viewing mode of operation of the system **2130**. The system **2100** can thus have an electronically switchable privacy capability.

The display system **2200** of FIG. 22 is similar to that of FIG. 21, but the dual-sided optical film is tailored so that the narrow angle output beam converges as it emerges from the optical film. The system **2200** thus utilizes an exemplary dual-sided optical film, and includes one or more first light sources **2234**, one or more second light sources **2232**, a backlight package **2230**, and a display panel (not shown). The light sources **2234**, **2232** may be the same as or similar to light sources **2134**, **2132** of FIG. 21. The backlight package **2230** may be similar to the backlight package 2130 of FIG. 21, except that the dual-sided optical film is configured so that individual prism/split spreading structure pairs produce beams or beamlets oriented in different directions across the output area of the optical film, see e.g. FIG. 4B. In a first mode of operation, the dual-sided optical film provides a wide angle output beam **2210A** when the first light source **2234** is ON and the second light source **2232** is OFF. In a second mode of operation, the

dual-sided optical film provides a narrow angle output beam **2210B** when the second light source **2232** is ON and the first light source **2234** is OFF. As shown, the narrow angle output beam initially converges as it exits the optical film, achieving a minimum beam width at a beam waist **2210B'**, beyond which the beam **2210B** diverges. Similar to system **2100**, the system **2200** desirably includes a switch that the user can activate to change from the first mode of operation to the second, or vice versa. The wide angle output beam **2210A** of the first mode of operation allows not only a centrally located observer **2202** to view the display, but also peripherally located observers **2203**, **2204**. The narrow angle output beam **2210B** of the second mode of operation allows only the centrally located observer **2202**, not the peripherally located observers **2203**, **2204**, to view the display. The system **2200** can thus also have an electronically switchable privacy capability. Note that the centrally located observer **2202** may continue to view the display at other viewing locations (see e.g. observer **2202'**), so long as such observer does not deviate too much from a central viewing axis of the system **2200**, which can be defined by the output beam **2210B**.

The features and principles of FIGS. 21 and 22 can also be applied to lighting systems other than display systems. In FIGS. 23 and 24, these principles are applied to lighting systems whose function is to illuminate a room, office, or other living space. The luminaire system **2300** of FIG. 23 may be similar to the display system **2100** of FIG. 21, except that the display panel is removed. Thus, the system **2300** includes one or more first light sources, one or more second light sources, a light guide, and a dual-sided optical film. The light sources may be the same as or similar to other light sources discussed above. The dual-sided optical film may have any of the design characteristics discussed herein, suitably tailored for this application. The dual-sided optical film is designed to provide, in a first mode of operation, a wide angle output beam **2310A** when the first light source is ON and the second light source is OFF, and to provide in a second mode of operation a narrow angle output beam **2310B** when the second light source is ON and the first light source is OFF. The system **2300** desirably includes a switch that the user can activate to change from the first mode of operation to the second, or vice versa. In the first mode of operation, the wide angle output beam **2310A** is provided, which broadly illuminates wide areas of the room or living space. The system **2300** is shown to be ceiling-mounted in a room having a floor **2305** and an occupant **2302**. In the second mode of operation, the narrow angle output beam **2310B** is provided, which illuminates a substantially smaller portion of the room. In comparison to the broader illumination of the first mode, the narrower illumination can be considered to provide a spotlight output. The system **2300** can thus have an electronically switchable spotlight capability.

The luminaire system **2400** of FIG. 24 is similar to that of FIG. 23, but the dual-sided optical film is tailored so that the narrow angle output beam converges as it emerges from the optical film. This can provide even more of a spotlight effect for the second mode of operation. The system **2400** thus utilizes one or more first light sources, one or more second light sources, a light guide, and a dual-sided optical film. These items may be the same as or similar to corresponding items in the system **2300**, except that the dual-sided optical film is configured so that individual prism/split spreading structure pairs produce beams or beamlets oriented in different directions across the output area of the optical film, see e.g. FIG.

4B. In a first mode of operation, the dual-sided optical film provides a wide angle output beam **2410A** when the first light source is ON and the second light source is OFF. In a second mode of operation, the dual-sided optical film provides a narrow angle output beam **2410B** when the second light source is ON and the first light source is OFF. As shown, the narrow angle output beam initially converges as it exits  
5 the optical film, achieving a minimum beam width at a beam waist **2410B'**, beyond which the beam **2410B** diverges. Similar to system **2300**, the system **2400** desirably includes a switch that the user can activate to change from the first mode of operation to the second, or vice versa. In the first mode of operation, the wide angle output beam **2310A** broadly illuminates wide areas of the room or living space. The system **2400** is shown to be ceiling-mounted in a room having a floor **2405**, a table or other elevated  
10 surface **2406**, and an occupant **2402**. In the second mode of operation, the narrow angle output beam **2410B** illuminates a substantially smaller portion of the room. In comparison to the broader illumination of the first mode, the narrower illumination can be considered to provide a spotlight output. The beam waist **2410B'** is located an axial distance  $f$  from the system **2400**, and the dual-sided optical film can be tailored so that the beam waist **2410B'** is positioned at a desired axial location, e.g. on the floor **2405**, or  
15 at the level of the table **2406**. The system **2400** can thus have an electronically switchable spotlight capability.

Numerous modifications can be made to, and numerous features incorporated into, the disclosed dual-sided optical films, light guides, and related components. For example, any given structured surface of the dual-sided optical film or of the light guide may be spatially uniform, i.e., the individual elements  
20 or structures of the structured surface may form a repeating pattern that occupies the entire major surface of the component. See e.g. FIGS. 1B and 2. Alternatively, any such structured surface may be patterned in such a way that portion(s) of the structured surface do not contain such individual elements or structures, or that the portion(s) contain such individual elements or structures, but such elements or structures have been rendered completely or partially inoperative. The absence of such individual  
25 elements or structures over portion(s) of the structured surface may be achieved by forming the elements or structures over the entire major surface, and then destroying or otherwise removing them by any suitable technique, e.g., applying sufficient heat and/or pressure to flatten the elements or structures, but selectively (pattern-wise) in the desired portion(s). Alternatively, the absence of the individual elements or structures may be achieved by not forming them in the desired portion(s) of the structured surface at  
30 the time when elements or structures are being formed in other regions of the structured surface, e.g. using a suitably patterned tool. In cases where individual elements or structures are rendered completely or partially inoperative in desired portion(s) of the structured surface, the structured surface may initially be spatially uniform, but individual elements or structures may then be coated or otherwise covered in a pattern-wise fashion with an adhesive, printing medium, or other suitable material whose refractive index  
35 matches (including substantially matches) the refractive index of the elements or structures, or that at least has a refractive index different from than air or vacuum. Such a pattern-wise applied material, which may be cured or crosslinked after application to the structured surface, may planarize the desired portion(s) of the structured surface. Whether the individual elements or structures are omitted or rendered

inoperative, the optical system may be designed such that only one structured surface (e.g. a structured surface of the light guide, or a structured surface of the dual-sided film) is patterned, or only two structured surfaces are patterned, or only three structured surfaces are patterned, or four structured surfaces are patterned. If more than two structured surfaces are patterned, the same pattern may be used for any two patterned surfaces, or different patterns may be used.

In other alternatives, with a suitably designed light guide, two dual-sided optical films can be used on opposite sides of the light guide. The light guide may be configured to provide oblique light beams from each of its two opposed major surfaces, and one dual-sided film can be provided at each major surface of the light guide to convert the oblique light beam to a wide angle output beam or a narrow angle output beam as discussed above, depending on which light source(s) are ON. For example, in FIG. IB, a dual-sided film which is a mirror image (relative to the x-y plane) of the film **140** may be placed on the opposite side of the light guide **150** such that the light guide is disposed between the two mirror-image dual-sided optical films.

In other alternatives, the optical system may also include secondary structures to limit or reduce the degree of light spreading of the output beam(s) produced by the dual-sided optical film. For example, a conventional lowered privacy film and/or a shroud (e.g. including one or more light blocking members) may be provided at the output of the dual-sided film. These secondary structures may operate by occluding a portion of a given initial output beam in the x-z plane and/or in the y-z plane (refer e.g. to the x-y-z coordinate orientation of FIGS. 3, 4A, 4B) to produce a modified output beam, the modified output beam being narrower than the initial output beam in the plane(s) of occlusion.

The light guide and the dual-sided optical film may both be substantially planar in overall shape, or one or both may be non-planar. Exemplary lighting system embodiments are schematically depicted in FIGS. 25A through 25E. In each of these figures, first light sources **2534** and second light sources **2532** are provided along opposed edges of an extended body. The light sources **2534**, **2532** may be the same as or similar to light sources **134**, **132** discussed above. The extended body, which is labeled **EBa** in FIG. 25A, **EBb** in FIG. 25B, **EBc** in FIG. 25C, **EBd** in FIG. 25D, and **EBe** in FIG. 25E, may represent the light guide, the dual-sided optical film, or both. The extended bodies of these figures are shown in relation to Cartesian x-y-z coordinate systems consistent with the previous figures. Deviations from planarity may be indicative of a flexible extended body, or a physically rigid extended body that was formed in a non-planar fashion. The extended body **EBa** is substantially planar, extending parallel to the x-y plane. The extended body **EBb** is non-planar, with curvature in the y-z plane but not in the x-z plane. The extended body **EBc** is also non-planar, but with curvature in the x-z plane and not in the y-z plane. Alternative embodiments may have curvature in both the x-z plane and the y-z plane. The extended body **EBd** is non-planar, with curvature in the y-z plane but not in the x-z plane, and the curvature in the y-z plane is such that the body closes in upon itself to form a tubular structure. The tubular structure may include a lengthwise slot or gap as shown. The tubular structure may have a substantially circular shape in transverse cross section (e.g., a cross section in the y-z plane), or alternatively an elliptical or other non-circular shape. The extended body **EBd** is non-planar, but with curvature in the x-z plane and not in

the y-z plane, and the curvature in the x-z plane is such that the body closes in upon itself to form a tubular structure. The tubular structure may include a lengthwise slot or gap as shown. The tubular structure may have a substantially circular shape in transverse cross section (e.g., a cross section in the x-z plane), or alternatively an elliptical or other non-circular shape. Lighting systems having any of the shapes of FIGS. 25A through 25E may be constructed in any desired form factor, including a form factor similar to a conventional light bulb, and may be used in place of conventional light bulbs, with the added capability of switchable wide/narrow output beam distributions.

#### EXAMPLES

10 A dual-sided optical film similar to that shown in FIGS. 5 and 6 was modeled with optical design software. The film was assumed to have the design characteristics described above in connection with FIGS. 6A and 6B, that is: the refractive index of the film was 1.67 for a central carrier film portion, and 1.51 for the prism and split spreading structure portions; the prism apex angle was about 60 degrees; the nominal radius of curvature of the curved segment (half of which was roughened) was about 41 microns; 15 the distance between the geometrical center **GC** of the split spreading structure and the prism vertex **Vprism** was 111 microns; and the surface roughness (Ra) of the high spreading portion was 0.588 microns. A light guide adjacent this dual-sided film was modeled as a first input beam associated with energizing only a first light source and a second input beam associated with energizing only a second light source, these input beams impinging upon the prism side of the dual-sided film. One of these input 20 beams was modeled as light rays propagating in the x-z plane (see FIGS. 5 and 6 for coordinate system orientation) and making an angle of  $20 \pm 10$  degrees relative to the (positive) x-axis, and the other input beam was modeled as light rays propagating in the x-z plane and making an angle of  $20 \pm 10$  degrees relative to the (negative) x-axis. With the first light source turned ON and the second light source turned OFF, the system produced an output beam whose distribution in the x-z plane, as a function of polar angle 25 (i.e. the angle relative to the z-axis), is shown as curve **2601** in FIG. 26. With the first light source turned OFF and the second light source turned ON, the system produced an output beam whose distribution in the x-z plane is shown as curve **2602**. The output beam of curve **2601** is wider than that of curve **2602**. We expect that the shape of curve **2601** can be further modified to provide a distribution having a single wide bell-shaped profile by appropriate optimization of the design details of the dual-sided film.

30 Another dual-sided optical film was modeled with the optical design software. The film was similar in design to that shown in FIGS. 7 and 8. The film was assumed to have the design characteristics described above in connection with FIGS. 8A and 8B, that is: the refractive index of the film was 1.67 for a central carrier film portion, and 1.51 for the prism and split spreading structure portions; the prism apex angle was about 63.5 degrees; the radius of curvature of the prism surface was 160 microns; the 35 radius of curvature of the high spreading portion was 30 microns; and the distance between the geometrical center **GC** and the prism vertex **Vprism** was 113 microns. A first oblique input light beam (analogous to a first light source ON and a second light source OFF) was simulated by injecting light rays into one of the inclined side surfaces of the prism. The injected rays were spread over a range of angles

as follows: the projections of the rays in the x-z plane (see FIGS. 7 and 8 for coordinate orientation) had positive x-components and made angles with respect to the z-axis of 62 to 82 degrees ( $72 \pm 10$  degrees); the projections of the rays in the y-z plane had positive z-components and made angles with respect to the z-axis of -40 to +40 degrees ( $0 \pm 40$  degrees). The dual-sided optical film converted this first oblique input beam to a first output beam whose distribution in the x-z plane, as a function of polar angle, is shown as curve **2701** in the relative intensity plot of FIG. 27. A second oblique input light beam (analogous to the first light source OFF and the second light source ON) was then simulated by injecting light rays into the other inclined surface of the prism. The injected rays were spread over a range of angles as follows: the projections of the rays in the x-z plane had negative x-components and made angles with respect to the z-axis of 62 to 82 degrees ( $72 \pm 10$  degrees); the projections of the rays in the y-z plane again had positive z-components and again made angles with respect to the z-axis of -40 to +40 degrees ( $0 \pm 40$  degrees). The dual-sided optical film converted this second oblique input beam to a second output beam whose distribution in the x-z plane as a function of polar angle is shown as curve **2702** in FIG. 27. Note the wider spreading of light for the first output beam (curve **2701**) in comparison to the second output beam (curve **2702**). The first output beam has an angular spread, measured as the full-width-at-half-maximum (FWHM) in the x-z plane, of 55 degrees, and the second output beam has an angular spread (measured in the same way) of 11 degrees.

Conoscopic plots are convenient for showing how light is emitted by the dual-sided film both as a function of polar angle and as a function of azimuthal angle. Closely related to conoscopic plots are polar iso-candela plots, which provide similar convenient angular information, except that the intensity values are not cosine corrected in a polar iso-candela plot; however, by dividing the intensity values by the cosine of the polar angle, relative luminance data can be obtained. A polar iso-candela plot of the first output beam of this modeled dual-sided optical film is provided in FIG. 28A, and a polar iso-candela plot of the second output beam is provided in 28B. In these plots, the z-axis corresponds to a point at the center of the circular scale, polar angle (relative to the z-axis) corresponds to the radial distance from the center, and azimuthal angle (relative to the y-axis) is indicated by the numbers 0, 15, 30, 45, ... 345 at the periphery of the circular scale. The calculated relative light intensity is shown at each point by shading in grayscale, with darker points on the graph indicating brighter light, as provided by the linear scale at the left side representing relative intensity. Note the wider light spreading in the x-z plane (azimuthal angles of 90 and 270 degrees) provided by the first output beam (FIG. 28A) in comparison to the second output beam (FIG. 28B).

Unless otherwise indicated, all numbers expressing quantities, measurement of properties, and so forth used in the specification and claims are to be understood as being modified by the term "about". Accordingly, unless indicated to the contrary, the numerical parameters set forth in the specification and claims are approximations that can vary depending on the desired properties sought to be obtained by those skilled in the art utilizing the teachings of the present application. Not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at

least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques. Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, to the extent any numerical values are set forth in specific examples described herein, they are reported as precisely as reasonably possible. Any numerical value, however, 5 may well contain errors associated with testing or measurement limitations.

Various modifications and alterations of this invention will be apparent to those skilled in the art without departing from the spirit and scope of this invention, and it should be understood that this invention is not limited to the illustrative embodiments set forth herein. The reader should assume that features of one disclosed embodiment can also be applied to all other disclosed embodiments unless 10 otherwise indicated. It should also be understood that all U.S. patents, patent application publications, and other patent and non-patent documents referred to herein are incorporated by reference, to the extent they do not contradict the foregoing disclosure.

This document discloses numerous embodiments, including but not limited to the following:

15 Item 1 is an optical film having opposed first and second structured surfaces, the optical film comprising:

a plurality of extended prisms formed on the first structured surface; and

a plurality of extended split spreading structures formed on the second structured surface, each split spreading structure having a high spreading portion disposed alongside a low spreading portion;

20 wherein the prisms and the split spreading structures are arranged in a one-to-one correspondence of prisms to split spreading structures.

Item 2 is the film of item 1, wherein each prism has on one side thereof a first inclined surface and on another side thereof a second inclined surface, and wherein the low spreading portion of a given split spreading structure is associated primarily with light transmitted through the first inclined surface of its 25 associated prism.

Item 3 is the film of item 2, wherein the low spreading portion of the given split spreading structure is associated primarily with light transmitted through the second inclined surface of the associated prism.

Item 4 is the film of item 1, wherein, for each of the split spreading structures, the low spreading portion has a smooth surface characteristic and the high spreading portion has a roughened surface 30 characteristic.

Item 5 is the film of item 1, wherein each of the split spreading structures comprises a curved segment of the second structured surface, and wherein the low and high spreading portions of each split spreading structure comprise smooth and roughened portions respectively of the curved segment.

Item 6 is the film of item 1, wherein for each split spreading structure, the high spreading portion is a 35 roughened portion and the low spreading portion is a lenslet.

Item 7 is the film of item 1, wherein for each split spreading structure, the high spreading portion is a lenslet and the low spreading portion is a flat.

Item 8 is the film of item 7, wherein the lenslet of each split spreading structure is a diverging lenslet.

Item 9 is the film of item 7, wherein the lenslet of each split spreading structure is a converging lenslet.

Item 10 is the film of item 1, wherein the split spreading structures extend along respective elongation axes that are parallel to each other, and wherein, for each of the split spreading structures, the low and high spreading portions meet along a boundary that is parallel to the elongation axis in plan view.

Item 11 is the film of item 1, wherein the prisms extend along respective first elongation axes that are parallel to each other, and the split spreading structures extend along respective second elongation axes that are parallel to each other.

Item 12 is the film of item 11, wherein the first elongation axes are parallel to the second elongation axes.

Item 13 is the film of item 1, wherein the optical film defines a reference plane, wherein the prisms have respective prism optical axes, and wherein each prism optical axis is perpendicular to the reference plane.

Item 14 is the film of item 1, wherein the optical film defines a reference plane, wherein the prisms have respective prism optical axes, and wherein a plurality of the prism optical axes are tilted with respect to a normal axis perpendicular to the reference plane.

Item 15 is the film of item 1, wherein the optical film defines a reference plane, wherein each split spreading structure has a spreading structure optical axis, and wherein each spreading structure optical axis is perpendicular to the reference plane.

Item 16 is the film of item 1, wherein the optical film defines a reference plane, wherein each split spreading structure has a spreading structure optical axis, and wherein a plurality of the spreading structure optical axes are tilted with respect to a normal axis perpendicular to the reference plane.

Item 17 is an optical system, comprising:

the optical film of item 1; and  
a light guide having a major surface adapted to emit light preferentially at oblique angles;  
wherein the optical film is disposed proximate the light guide and oriented so that light emitted from the major surface of the light guide enters the optical film through the first structured surface.

Item 18 is an optical system, comprising:

a light guide having a major surface adapted to emit light;  
a first and second light source configured to inject light into the light guide along different first and second respective directions; and  
an optical film having opposed first and second structured surfaces, the optical film being disposed proximate the light guide and oriented so that light emitted from the major surface of the light guide is deviated by and passes through the optical film to provide an output beam as a function of which of the first and second light sources are energized;  
wherein the output beam is a wide output beam when the first light source is energized and the second light source is not energized, and wherein the output beam is a narrow output beam when the second light source is energized and the first light source is not energized.

Item 19 is the system of item 18, wherein the wide output beam has a beam width (FWHM) of at least 40 degrees in a given plane of observation, and the narrow output beam has a beam width (FWHM) of no more than 30 degrees in the given plane of observation.

5 Item 20 is the system of item 18, wherein the narrow output beam is subsumed by the wide output beam in the given plane of observation.

Item 21 is the system of item 18, wherein the optical film has a first structured surface facing the light guide and a second structured surface opposed to the first structured surface.

10 Item 22 is the system of item 21, wherein a plurality of extended prisms are formed on the first structured surface, and a plurality of extended split spreading structures are formed on the second structured surface, each split spreading structure having a high spreading portion disposed alongside a low spreading portion, and wherein the prisms and the split spreading structures are arranged in a one-to-one correspondence of prisms to split spreading structures.

Item 23 is the system of item 18, further comprising:

a switch coupled to the first and second light sources.

15 Item 24 is the system of item 23, wherein the system comprises a display, and the switch provides the display with a switchable privacy/sharing function.

Item 25 is the system of item 23, wherein the system comprises a luminaire, and the switch provides the luminaire with a switchable spotlight function.

Item 26 is a display system, comprising:

20 a display panel;

a backlight disposed behind the display panel, the backlight including one or more first light sources and one or more second light sources; and

a switch coupled to the one or more first light sources and to the one or more second light sources to selectively energize such light sources;

25 wherein the backlight is configured to provide a first output light beam when the one or more first light sources are ON and the one or more second light sources are OFF, and is further configured to provide a second output light beam when the one or more first light sources are OFF and the one or more second light sources are ON; and

30 wherein the first output light beam has a wider angular spread than the second output light beam, such that the switch provides the display system with a switchable privacy/sharing function.

Item 27 is the system of item 26, wherein the backlight includes a dual-sided optical film having opposed first and second structured surfaces, the optical film comprising:

a plurality of extended prisms formed on the first structured surface; and

35 a plurality of extended split spreading structures formed on the second structured surface, each split spreading structure having a high spreading portion disposed alongside a low spreading portion;

wherein the prisms and the split spreading structures are arranged in a one-to-one correspondence of prisms to split spreading structures.

Item 28 is the system of item 26, wherein the backlight includes a light guide.

## CLAIMS

1. An optical film having opposed first and second structured surfaces, the optical film comprising:  
5 a plurality of extended prisms formed on the first structured surface; and  
a plurality of extended split spreading structures formed on the second structured surface, each split  
spreading structure having a high spreading portion disposed alongside a low spreading portion;  
wherein the prisms and the split spreading structures are arranged in a one-to-one correspondence of  
prisms to split spreading structures.
- 10
2. The film of claim 1, wherein, for each of the split spreading structures, the low spreading portion has a  
smooth surface characteristic and the high spreading portion has a roughened surface characteristic.
3. The film of claim 1, wherein each of the split spreading structures comprises a curved segment of the  
15 second structured surface, and wherein the low and high spreading portions of each split spreading  
structure comprise smooth and roughened portions respectively of the curved segment.
4. The film of claim 1, wherein for each split spreading structure, the high spreading portion is a  
roughened portion and the low spreading portion is a lenslet.
- 20
5. The film of claim 1, wherein for each split spreading structure, the high spreading portion is a lenslet  
and the low spreading portion is a flat.
6. The film of claim 5, wherein the lenslet of each split spreading structure is a diverging lenslet.
- 25
7. The film of claim 5, wherein the lenslet of each split spreading structure is a converging lenslet.
8. An optical system, comprising:  
a light guide having a major surface adapted to emit light;  
30 a first and second light source configured to inject light into the light guide along different first and  
second respective directions; and  
an optical film having opposed first and second structured surfaces, the optical film being disposed  
proximate the light guide and oriented so that light emitted from the major surface of the light guide  
is deviated by and passes through the optical film to provide an output beam as a function of which  
35 of the first and second light sources are energized;  
wherein the output beam is a wide output beam when the first light source is energized and the second  
light source is not energized, and wherein the output beam is a narrow output beam when the  
second light source is energized and the first light source is not energized.

9. A display system, comprising:  
a display panel;  
a backlight disposed behind the display panel, the backlight including one or more first light sources  
5 and one or more second light sources; and  
a switch coupled to the one or more first light sources and to the one or more second light sources to  
selectively energize such light sources;  
wherein the backlight is configured to provide a first output light beam when the one or more first  
light sources are ON and the one or more second light sources are OFF, and is further configured to  
10 provide a second output light beam when the one or more first light sources are OFF and the one or  
more second light sources are ON; and  
wherein the first output light beam has a wider angular spread than the second output light beam, such  
that the switch provides the display system with a switchable privacy/sharing function.
- 15 10. The system of claim 9, wherein the backlight includes a dual-sided optical film having opposed first  
and second structured surfaces, the optical film comprising:  
a plurality of extended prisms formed on the first structured surface; and  
a plurality of extended split spreading structures formed on the second structured surface, each split  
spreading structure having a high spreading portion disposed alongside a low spreading portion;  
20 wherein the prisms and the split spreading structures are arranged in a one-to-one correspondence of  
prisms to split spreading structures.




FIG. 1A




FIG. 1B




FIG. 2




FIG. 2A




FIG. 3






FIG. 4B





FIG. 5



*FIG. 6*




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12

17/30




FIG. 12A




FIG. 12B




FIG. 13




FIG. 14




FIG. 14A







FIG. 14B






FIG. 18




FIG. 19




FIG. 20A




FIG. 20B

24/30




FIG. 21




FIG. 22




FIG. 23









FIG. 24






FIG. 26





FIG. 27



*FIG. 28A*




FIG. 28B

**INTERNATIONAL SEARCH REPORT**

International application No PCT/US2014/031655
---

A. CLASSIFICATION OF SUBJECT MATTER  
 INV. G02B5/02      G02B5/04      F21V8/00      G02B3/00  
 ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
 EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2008/259634 AI (MI XIANG-DONG [US] ET AL) 23 October 2008 (2008-10-23) paragraphs [0003], [0103], [0118], [0120]; figures 4A,6-8 -----	1-4
X	US 2009/067156 AI (BONNETT PAUL [GB] ET AL) 12 March 2009 (2009-03-12) paragraphs [0001], [0156], [0157]; figures 10A, 10B, 14A -----	8,9
A	US 2012/236403 AI (SYKORA MICHAEL J [US] ET AL) 20 September 2012 (2012-09-20) paragraphs [0039], [0040]; figures 1a, 1b, 2, 4a -----	1,8,9
A	US 2012/299985 AI (ICHIHASHI KOUKI [JP] ET AL) 29 November 2012 (2012-11-29) paragraphs [0033], [0046]; figures 1,8 ----- -/--	1,8,9

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search  12 June 2014	Date of mailing of the international search report  23/06/2014
---	--

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer  Verdrager, Veronique
--	--

## INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2014/031655

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 2011/085108 A1 (PARK JEONG-HO [KR] ET AL) 14 April 2011 (2011-04-14) paragraphs [0060], [0063], [0090], [0095], [0100], [0109], [0114]; figures 3, 4, 12, 13, 17(a), 18</p> <p>-----</p>	1, 8, 9
A	<p>US 2007/211493 A1 (FANG CHONG-YANG [TW] ET AL) 13 September 2007 (2007-09-13) paragraph [0041]; figure 8</p> <p>-----</p>	1
A	<p>US 5 600 455 A (ISHIKAWA TSUYOSHI [JP] ET AL) 4 February 1997 (1997-02-04) column 4, lines 29-56; figure 7</p> <p>-----</p>	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No <b>PCT/US2014/031655</b>
--

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2008259634	AI	23-10-2008	CN 101324726 A 17-12-2008
			JP 2009037205 A 19-02-2009
			KR 20080093931 A 22-10-2008
			TW 200907497 A 16-02-2009
			US 2008259634 AI 23-10-2008
-----			
US 2009067156	AI	12-03 -2009	NONE
-----			
US 2012236403	AI	20-09 -2012	EP 2686726 A2 22-01 -2014
			KR 20140012718 A 03-02 -2014
			TW 201248201 A 01-12 -2012
			US 2012236403 AI 20-09 -2012
			Wo 2012125323 A2 20-09 -2012
-----			
US 2012299985	AI	29-11 -2012	JP 2013008010 A 10-01 -2013
			US 2012299985 AI 29-11 -2012
-----			
US 2011085108	AI	14-04 -2011	KR 20090127496 A 14-12 -2009
			US 2011085108 AI 14-04 -2011
-----			
US 2007211493	AI	13-09 -2007	NONE
-----			
US 5600455	A	04-02 -1997	NONE
-----			