



US011926989B2

(12) **United States Patent**
Parzynski, Jr. et al.

(10) **Patent No.:** **US 11,926,989 B2**

(45) **Date of Patent:** **Mar. 12, 2024**

(54) **ADAPTER BOARD WITH SPLINED BUSHING**

(56) **References Cited**

(71) Applicant: **Caterpillar Inc.**, Peoria, IL (US)
(72) Inventors: **David Bruno Parzynski, Jr.**, Peoria, IL (US); **Thomas Marshall Congdon**, Dunlap, IL (US); **Tobias James Toennies**, Metamora, IL (US)
(73) Assignee: **Caterpillar Inc.**, Peoria, IL (US)
(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 407 days.

U.S. PATENT DOCUMENTS

1,633,057 A	6/1927	Wold
3,652,130 A	3/1972	Elders
4,002,209 A	1/1977	van der Lely
4,368,789 A	1/1983	Orr et al.
4,454,921 A	6/1984	Schlicker, Jr.
4,753,299 A	6/1988	Meyers
4,883,129 A	11/1989	Lonn et al.
5,261,170 A	11/1993	Ward
5,400,861 A	3/1995	Sheirer
5,533,283 A	7/1996	Roth
5,549,431 A	8/1996	Royle
5,833,017 A	11/1998	Woods et al.
6,202,327 B1	3/2001	Fuller
8,714,659 B2	5/2014	Klabisch et al.
9,222,353 B2	12/2015	Morris et al.

(21) Appl. No.: **17/110,442**

(22) Filed: **Dec. 3, 2020**

(65) **Prior Publication Data**
US 2021/0087780 A1 Mar. 25, 2021

FOREIGN PATENT DOCUMENTS

CN	206794946	12/2017
CN	108350676	7/2018

(Continued)

(Continued)

Related U.S. Application Data

(62) Division of application No. 16/182,736, filed on Nov. 7, 2018, now Pat. No. 10,914,050.

(51) **Int. Cl.**
E02F 3/815 (2006.01)
E02F 9/28 (2006.01)

(52) **U.S. Cl.**
CPC **E02F 3/8152** (2013.01); **E02F 9/2808** (2013.01); **E02F 9/2825** (2013.01); **E02F 9/2833** (2013.01)

(58) **Field of Classification Search**
CPC E02F 3/8152; E02F 9/2808; E02F 9/2825; E02F 9/2833

See application file for complete search history.


“Square Bits Replace Grader Cutting Edge”, Machine Design, Penton Media, Cleveland, OH, US, vol. 62 No. 5 Mar. 8, 1990. p. 86. XP000123468. ISSN:0024-9114, the whole document.

Primary Examiner — Tara Mayo

(57) **ABSTRACT**

A blade assembly includes an adapter board including a lower tool bit attachment portion, terminating in a lower adapter board free end, the lower adapter board free end defining a bottom surface defining a plurality of shank receiving bores. A plurality of bushings are disposed in a corresponding one of the plurality of shank receiving bores.

20 Claims, 45 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

9,387,723	B2	7/2016	Beatty	
2008/0139061	A1	6/2008	Chen	
2013/0248215	A1*	9/2013	Tutschek et al.	E02F 9/2833 172/762
2017/0136612	A1	5/2017	Moore	
2018/0195255	A1	7/2018	Congdon et al.	

FOREIGN PATENT DOCUMENTS

EP	3045591	A1	7/2016
FR	2332381	A1	6/1977
WO	0068512	A1	11/2000
WO	2013101501	A1	7/2013

* cited by examiner




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 18




FIG. 19




FIG. 23




FIG. 24




FIG. 25




FIG. 26 **FIG. 27** **FIG. 28**




FIG. 29




FIG. 30




FIG. 31




FIG. 34

FIG. 33

FIG. 32




FIG. 35




FIG. 36




FIG. 37




FIG. 41




FIG. 42




FIG. 43




FIG. 46

FIG. 45

FIG. 44




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 63




FIG. 62




FIG. 64




FIG. 65




FIG. 66




FIG. 67

1

**ADAPTER BOARD WITH SPLINED
BUSHING****CROSS-REFERENCE TO RELATED
APPLICATION**

The present application is a divisional application of application Ser. No. 16/182,736, filed on Nov. 7, 2018, entitled "Adapter Board with Splined Bushing", claiming priority thereto, and incorporating its contents by reference in its entirety herein.

TECHNICAL FIELD

The present disclosure relates to blade assemblies with an adapter board having removable tool bits attached thereto. More specifically, the present disclosure relates to a blade assembly with pry point that help allow the tool bits to be removed.

BACKGROUND

Machines such as motor graders employ a long blade that is used to level work surfaces during the grading phase of a construction project or the like. These blades often encounter abrasive material such as rocks, dirt, etc. that can degrade the working edge, making such blades ineffective for their intended purpose. Some blades have a serrated cutting edge meaning that the edge is not continuously flat but undulates up and down, forming teeth. A drawback to such blades is that the teeth may be more easily worn than is desired. In harsh environments, such blades may be rendered dull, with the teeth having been essentially removed, after 100-200 hours of operation. Necessitating their replacement. Serrated cutting edges are sometimes provided to improve penetration via the use of detachable tool bits, etc.

Often, the tool bits that are attached to the adapter board of a blade assembly experience significant loads that may alter the shape of the tool bit and/or the adapter board to which the tool bit has been attached. Consequently, removing the tool bits may be difficult as a press fit or catch point is created by the deformation of the adapter board and/or the tool bit. This may necessitate pressing the tool bit out of the adapter board. This may be time consuming and/or may cause damage to the tool bit or adapter board.

In other situations, the bit shank hole will experience packing of material scraped by the blade assembly and this will result in the bit getting seized within the bit shank hole. Some customers will try to strike the bits with a hammer but this results in the bits mushrooming within the bit shank hole and making it harder to remove them.

In either case, the adapter board or the tool bit may need to be replaced, increasing the cost of using such blade assemblies.

Accordingly, there exists a need for providing a blade assembly that allows for easier removal of tool bits, especially after the tool bits have been used in a blade assembly and have been subjected to significant loads.

SUMMARY OF THE DISCLOSURE

A blade assembly according to an embodiment of the present disclosure may comprise an adapter board including a lower tool bit attachment portion, terminating in a lower adapter board free end, the lower adapter board free end defining a bottom surface defining a plurality of shank

2

receiving bores. A plurality of bushings may be disposed in a corresponding one of the plurality of shank receiving bores.

5 A splined tool bit according to an embodiment of the present disclosure may comprise a working portion; and a splined shank portion extending from the working portion to a splined shank portion free end.

10 A splined bushing according to an embodiment of the present disclosure may comprise an annular cylindrical body defining a longitudinal axis, a radial direction, and a circumferential direction, the annular cylindrical body including an inner cylindrical surface defining a thru-hole that extends axially through the annular cylindrical body, the body further including a plurality of bushing splines. Each 15 one of the plurality of bushing splines may extend axially and radially from the inner cylindrical surface and may be spaced circumferentially away from an adjacent one of the plurality of bushing splines.

BRIEF DESCRIPTION OF THE DRAWINGS

20 FIG. 1 is a side view of a motor grader that may employ a blade assembly and/or a tool bit according to an embodiment of the present disclosure.

25 FIG. 2 is a front oriented perspective view of a blade assembly according to an embodiment of the present disclosure utilizing a tool bit with arcuate bit surfaces shown in isolation from the machine of FIG. 1.

30 FIG. 3 is a perspective view of a first embodiment of the present disclosure showing a tool bit utilizing an arcuate bit surface that may be used in conjunction with the blade assembly of FIG. 2.

35 FIG. 4 is a perspective view of a second embodiment of the present disclosure showing a tool bit utilizing a longer arcuate bit surface than the first embodiment of FIG. 3 that may be used in conjunction with the blade assembly of FIG. 2.

40 FIG. 5 is a perspective view of a third embodiment of the present disclosure showing a tool bit utilizing an arcuate bit face with more draft than the first embodiment of FIG. 3 that may be used in conjunction with the blade assembly of FIG. 2.

45 FIG. 6 is a perspective view of a fourth embodiment of the present disclosure showing a tool bit utilizing an arcuate bit face with more draft than the third embodiment of FIG. 5.

FIG. 7 is a top view of the blade assembly of FIG. 2 showing the tool bits arranged at a zero degree incline with respect to the centerline of the blade assembly.

50 FIG. 8 is a top view of the blade assembly of FIG. 2 showing the tool bits arranged at a ten degree incline with respect to the centerline of the blade assembly.

55 FIG. 9 is a top view of the blade assembly of FIG. 2 showing the tool bits arranged at a twenty degree incline with respect to the centerline of the blade assembly.

FIG. 10 is a top view of the blade assembly of FIG. 2 showing the tool bits arranged at a thirty degree incline with respect to the centerline of the blade assembly.

60 FIG. 11 is a perspective view of a wide grader tool bit that is drafted for reduced drag as the tool bit passes through the ground or other work surface, lacking arcuate surfaces.

FIG. 12 is a front view of the wide grader tool bit of FIG. 11.

65 FIG. 13 is a side view of the wide grader tool bit of FIG. 11.

FIG. 14 is a cross-section of the wide grader tool bit of FIG. 12 taken along lines 14-14 thereof.

FIG. 15 is a cross-section of the wide grader tool bit of FIG. 12 taken along lines 15-15 thereof.

FIG. 16 is a cross-section of the wide grader tool bit of FIG. 12 taken along lines 16-16 thereof.

FIG. 17 is a perspective view of a standard grader tool bit that is more heavily drafted than the tool bit of FIG. 11, helping to penetrate the ground or other work surface, and also lacking arcuate surfaces.

FIG. 18 is a front view of the standard grader tool bit of FIG. 17.

FIG. 19 is a side view of the standard grader tool bit of FIG. 17.

FIG. 20 is a cross-section of the standard grader tool bit of FIG. 18 taken along lines 20-20 thereof.

FIG. 21 is a cross-section of the standard grader tool bit of FIG. 18 taken along lines 21-21 thereof.

FIG. 22 is a cross-section of the standard grader tool bit of FIG. 18 taken along lines 22-22 thereof.

FIG. 23 is a perspective view of a sharp grader tool bit that is more heavily drafted than the tool bit of FIG. 17, helping to penetrate the ground or other work surface, and also lacking arcuate surfaces.

FIG. 24 is a front view of the sharp grader tool bit of FIG. 23.

FIG. 25 is a side view of the sharp grader tool bit of FIG. 23.

FIG. 26 is a cross-section of the sharp grader tool bit of FIG. 24 taken along lines 26-26 thereof.

FIG. 27 is a cross-section of the sharp grader tool bit of FIG. 24 taken along lines 27-27 thereof.

FIG. 28 is a cross-section of the sharp grader tool bit of FIG. 24 taken along lines 28-28 thereof.

FIG. 29 is a perspective view of a penetration grader tool bit that is more heavily drafted than the tool bit of FIG. 23, helping to penetrate the ground or other work surface, and also lacking arcuate surfaces.

FIG. 30 is a front view of the penetration grader tool bit of FIG. 29.

FIG. 31 is a side view of the penetration grader tool bit of FIG. 29.

FIG. 32 is a cross-section of the penetration grader tool bit of FIG. 30 taken along lines 32-32 thereof.

FIG. 33 is a cross-section of the penetration grader tool bit of FIG. 30 taken along lines 33-33 thereof.

FIG. 34 is a cross-section of the penetration grader tool bit of FIG. 30 taken along lines 34-34 thereof.

FIG. 35 is a perspective view of a wide mining tool bit with an additional insert, helping to prolong the useful life of the tool bit, and also lacking arcuate surfaces.

FIG. 36 is a front view of the wide mining tool bit of FIG. 35.

FIG. 37 is a side view of the wide mining tool bit of FIG. 35.

FIG. 38 is a cross-section of the wide mining tool bit of FIG. 36 taken along lines 38-38 thereof.

FIG. 39 is a cross-section of the wide mining tool bit of FIG. 36 taken along lines 39-39 thereof.

FIG. 40 is a cross-section of the wide mining tool bit of FIG. 36 taken along lines 40-40 thereof.

FIG. 41 is a perspective view of a standard mining tool bit with an additional insert, helping to prolong the useful life of the tool bit, and also lacking arcuate surfaces.

FIG. 42 is a front view of the standard mining tool bit of FIG. 41.

FIG. 43 is a side view of the standard mining tool bit of FIG. 41.

FIG. 44 is a cross-section of the standard mining tool bit of FIG. 42 taken along lines 44-44 thereof.

FIG. 45 is a cross-section of the standard mining tool bit of FIG. 42 taken along lines 45-45 thereof.

FIG. 46 is a cross-section of the standard mining tool bit of FIG. 42 taken along lines 46-46 thereof.

FIG. 47 is a perspective view of an insert according to a first embodiment of the present disclosure.

FIG. 48 is a perspective view of an insert according to a second embodiment of the present disclosure.

FIG. 49 is a rear oriented perspective view of a blade assembly showing tool bits angled at a ten degree angle with the centerline of the adapter board, configured to move material to the right of the adapter board in use.

FIG. 50 is a front oriented perspective view of a blade assembly showing tool bits angled at a ten degree angle with the centerline of the adapter board, configured to move material to the left of the adapter board in use.

FIG. 51 is a rear oriented partially exploded assembly view of the blade assembly of FIG. 50 showing the flipping of an orientation plate onto the top surface of the lower tool bit attachment portion of the adapter board.

FIG. 52 illustrates the blade assembly of FIG. 51 with the orientation plate flipped, allowing the left set of tool bits to be oriented at an opposite ten degree angle with the centerline as compared to the right set of tool bits.

FIG. 53 depicts the blade assembly of FIG. 52 fully assembled.

FIG. 54 is a front oriented perspective view of the blade assembly of FIG. 53.

FIG. 55 is a front view of a serrated blade assembly according to an embodiment of the present disclosure using differently configured components such as tool bits and wear members.

FIG. 56 is a perspective view of a wear member according to an embodiment of the present disclosure that may be used in the serrated blade assembly of FIG. 55.

FIG. 57 is a perspective view of a wear member according to another embodiment of the present disclosure.

FIG. 58 is a rear oriented perspective view of a blade assembly employing an adapter board with pry points according to an embodiment of the present disclosure.

FIG. 59 is an enlarged view of a tool bit and pry point disposed at the end of the adapter board of the blade assembly of FIG. 58.

FIG. 60 is an enlarged bottom view of one of the pry points of the adapter board of FIG. 58 with the tool bit removed for enhanced clarity.

FIG. 61 is a rear oriented perspective view of a blade assembly employing an adapter board utilizing a splined bushing and a tool bit having a splined shank portion mating with the splined bushing according to an embodiment of the present disclosure.

FIG. 62 is a perspective view of the tool bit having a splined shank portion according to an embodiment of the present disclosure that may be used in the blade assembly of FIG. 61.

FIG. 63 is a perspective view of the splined bushing according to an embodiment of the present disclosure that may be used in the blade assembly of FIG. 61.

FIG. 64 is an exploded assembly view of the blade assembly of FIG. 61 illustrating the tool bit being inserted into the bushing.

FIG. 65 is an enlarged detail view of the blade assembly of FIG. 61, showing the mating of the splines of the shank portion of the tool bit with the splines of the bushing, and

5

also showing the positioning of the snap ring groove near the end of the shank portion of the tool bit above the adapter board.

FIG. 66 is a sectional perspective view of another blade assembly employing another embodiment of splined tool bit, a bushing lacking splines, and an adapter board having splines that mate with those of the tool bit.

FIG. 67 is an enlarged detail view of FIG. 66 illustrating the splined shank portion of the tool bit and its top ledge holding a snap ring in place more clearly.

DETAILED DESCRIPTION

Reference will now be made in detail to embodiments of the disclosure, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts. In some cases, a reference number will be indicated in this specification and the drawings will show the reference number followed by a letter for example, 100a, 100b or a prime indicator such as 100', 100" etc. It is to be understood that the use of letters or primes immediately after a reference number indicates that these features are similarly shaped and have similar function as is often the case when geometry is mirrored about a plane of symmetry. For ease of explanation in this specification, letters or primes will often not be included herein but may be shown in the drawings to indicate duplications of features discussed within this written specification.

A blade assembly using tool bits with arcuate surfaces according to an embodiment of the present disclosure will be described. Then, a tool bit with an arcuate surface will be discussed.

First, a machine will now be described to give the reader the proper context for understanding how various embodiments of the present disclosure are used to level or grade a work surface. It is to be understood that this description is given as exemplary and not in any limiting sense. Any embodiment of an apparatus or method described herein may be used in conjunction with any suitable machine.

FIG. 1 is a side view of a motor grader in accordance with one embodiment of the present disclosure. The motor grader 10 includes a front frame 12, rear frame 14, and a work implement 16, e.g., a blade assembly 18, also referred to as a drawbar-circle-moldboard assembly (DCM). The rear frame 14 includes a power source (not shown), contained within a rear compartment 20, that is operatively coupled through a transmission (not shown) to rear traction devices or wheels 22 for primary machine propulsion.

As shown, the rear wheels 22 are operatively supported on tandems 24 which are pivotally connected to the machine between the rear wheels 22 on each side of the motor grader 10. The power source may be, for example, a diesel engine, a gasoline engine, a natural gas engine, or any other engine known in the art. The power source may also be an electric motor linked to a fuel cell, capacitive storage device, battery, or another source of power known in the art. The transmission may be a mechanical transmission, hydraulic transmission, or any other transmission type known in the art. The transmission may be operable to produce multiple output speed ratios (or a continuously variable speed ratio) between the power source and driven traction devices.

The front frame 12 supports an operator station 26 that contains operator controls 82, along with a variety of displays or indicators used to convey information to the operator, for primary operation of the motor grader 10. The front frame 12 also includes a beam 28 that supports the blade

6

assembly 18 and which is employed to move the blade assembly 100 to a wide range of positions relative to the motor grader 10. The blade assembly 18 includes a drawbar 32 pivotally mounted to a first end 34 of the beam 28 via a ball joint (not shown). The position of the drawbar 32 is controlled by three hydraulic cylinders: a right lift cylinder 36 and left lift cylinder (not shown) that control vertical movement, and a center shift cylinder 40 that controls horizontal movement. The right and left lift cylinders are connected to a coupling 70 that includes lift arms 72 pivotally connected to the beam 28 for rotation about axis C. A bottom portion of the coupling 70 has an adjustable length horizontal member 74 that is connected to the center shift cylinder 40.

The drawbar 32 includes a large, flat plate, commonly referred to as a yoke plate 42. Beneath the yoke plate 42 is a circular gear arrangement and mount, commonly referred to as the circle 44. The circle 44 is rotated by, for example, a hydraulic motor referred to as the circle drive 46. Rotation of the circle 44 by the circle drive 46 rotates the attached blade assembly 100 about an axis A perpendicular to a plane of the drawbar yoke plate 42. The blade cutting angle is defined as the angle of the blade assembly 100 relative to a longitudinal axis of the front frame 12. For example, at a zero degree blade cutting angle, the blade assembly 100 is aligned at a right angle to the longitudinal axis of the front frame 12 and beam 28.

The blade assembly 100 is also mounted to the circle 44 via a pivot assembly 50 that allows for tilting of the blade assembly 100 relative to the circle 44. A blade tip cylinder 52 is used to tilt the blade assembly 100 forward or rearward. In other words, the blade tip cylinder 52 is used to tip or tilt a top edge 54 relative to the bottom cutting edge 56 of the blade 30, which is commonly referred to as blade tip. The blade assembly 100 is also mounted to a sliding joint associated with the circle 44 that allows the blade assembly 100 to be slid or shifted from side-to-side relative to the circle 44. The side-to-side shift is commonly referred to as blade side shift. A side shift cylinder (not shown) is used to control the blade side shift. The placement of the blade assembly 100 allows a work surface 86 such as soil, dirt, rocks, etc. to be leveled or graded as desired. The motor grader 10 includes an articulation joint 62 that pivotally connects front frame 12 and rear frame 14, allowing for complex movement of the motor grader, and the blade.

U.S. Pat. No. 8,490,711 to Polumati illustrates another motor grader with fewer axes of movement than that just described with respect to FIG. 1. It is contemplated that such a motor grader could also employ a blade according to various embodiments of the present disclosure, etc. Other machines than graders may use various embodiments of the present disclosure.

Turning now to FIG. 2, a blade assembly 100 for use with a grading machine 10 according to an embodiment of the present disclosure will be described. The blade assembly 100 comprises an adapter board 102 defining an upper adapter board attachment portion 104, terminating in an upper adapter board free end 106. This portion 104 is used to attach to a moldboard (not shown). The adapter board 100 further comprising a lower tool bit attachment portion 108, terminating in a lower adapter board free end 110. The lower tool bit attachment portion 108 defines a length along the lateral direction. A plurality of tool bits 200 are provided that are configured to be attached to the adapter board 102. While FIG. 2 shows the tool bits 200 already attached to the adapter board 102 via mounting hardware (not shown), it is to be understood that the tool bits 200 may be supplied with the

adapter board **102** or separately from the adapter board **102**, without being attached to the adapter board **102**.

Looking now at FIGS. **2** and **3**, each tool bit **200** may include a shank portion **202** defining a longitudinal axis L, and a working portion **204**. The working portion **204** may include at least a first arcuate surface **206** disposed longitudinally adjacent the shank portion **202**, and the at least first arcuate surface **206** may define a radius of curvature ROC (measured in a plane perpendicular to the longitudinal axis L) that is equal to or greater than half of the width W of the lower tool bit attachment portion **108** of the adapter board **102**. Examples of arcuate surfaces include radial, elliptical, polynomial surfaces, etc.

As best seen in FIGS. **2**, and **7** thru **10**, the lower tool bit attachment portion **108** of the adapter board **102** may define a plurality of cylindrical thru-bores **112**. As shown in FIG. **3**, the shank portion **202** of the tool bit **200** may include a cylindrical configuration defining a circumferential direction C and a radial direction R. The shank portion **202** may be configured to fit snugly within one of the plurality of cylindrical thru-bores **112**.

Focusing on FIG. **3**, the working portion **204** of the tool bit **200** includes a second arcuate surface **208** disposed adjacent the first arcuate surface **206** circumferentially on one side of the first arcuate surface **206** and a third arcuate surface **210** disposed adjacent the first arcuate surface **206** on the other side of the first arcuate surface **206**. The shank portion **202** defines two flat surfaces **212** circumferentially aligned with the first arcuate surface **206**, the two flat surfaces **212** partially defining a cross-hole **214** extending radially thru the shank portion **202**. Mounting hardware (not shown) may be used in conjunction with the cross-hole **214** of the shank portion **202** for retaining the tool bit **200** to the adapter board **102**. As best seen in FIGS. **7** thru **10**, the flat surfaces **212** may be used with an orientation plate **114** that sits on top of the lower tool bit attachment portion **108** to control the angle of inclination α of the tool bits **200** relative to the centerline CL of the blade assembly **100**.

Returning to FIG. **3**, the first arcuate surface **206**, second arcuate surface **208** and/or third arcuate surface **210** may define a radius of curvature ROC ranging from 50 mm to 65 mm. As alluded to earlier herein, the radius of curvature ROC may be adjusted based on the width W of the lower tool bit attachment portion **108** of the adapter board **102** and is measured in a plane perpendicular to the longitudinal axis L. As used herein, the width W is often the minimum dimension of the lower tool bit attachment portion **108** measured along a direction perpendicular to the longitudinal axis L of the shank portion **202** (parallel to CL in FIG. **7**). The tool bit **200** may further comprising a rear face **216**, a first side region **218** extending from the second arcuate surface **208** to the rear face **216**, and a second side region **220** extending from the third arcuate surface **210** to the rear face **216**. The first side region **218** may be divided into a first set of multiple side surfaces **222** and the second side region **220** may be divided into a second set of multiple side surfaces (not shown). The working portion **204** defines a free axial end **224** and a notch **226** disposed proximate the free axial end **224**. An insert **228** or tile may be disposed in the notch **226**. The insert **228** may be made from a carbide material such as Tungsten Carbide with a binding agent (such as Cobalt). The tool bit **200** itself or the adapter board **102** may be forged or cast using iron, grey cast-iron, steel or any other suitable material.

Various surfaces of the working portion **204** of the tool bit **200** may be drafted relative to the longitudinal axis L of the shank portion **202**, allowing the tool bit **200** to enter and exit

the ground or other work surface more easily. The draft angle would be the angle formed between the longitudinal axis L and the surface in a cross-section defined by a plane containing the radial direction R and the longitudinal axis L. The draft angle may be negative, resulting in the width of the cross-section of the working portion, in a plane perpendicular to the longitudinal axis L, decreasing as one progresses upwardly along the longitudinal axis L toward the shank portion (this may be the case in FIG. **4**). Alternatively, the draft angle may be positive, resulting in the width of the cross-section of the working portion increasing as one progresses upwardly along the longitudinal axis L toward the shank portion (this may be the case in FIGS. **3**, **5** and **6**).

As seen in FIG. **3**, the rear face **216** may define a first draft angle β_1 with the longitudinal axis L ranging from 0 to 30 degrees. Similarly, the first side region **218** may define a second draft angle β_2 with the longitudinal axis ranging from 0 to 30 degrees. Likewise, the second side region **220** may define a third draft angle β_3 (same as β_2 since the tool bit is usually symmetrical) with the longitudinal axis L ranging from 0 to 30 degrees. Also, the first arcuate surface **206**, second arcuate surface **208** and/or third arcuate surface **210** define a fourth draft angle β_4 with the longitudinal axis L ranging from 0 to 30 degrees. Other draft angles or no draft angle may be provided for any of these surfaces in other embodiments.

For the embodiment shown in FIG. **3**, a Cartesian coordinate system X, Y, Z may be placed with its origin O at the longitudinal axis L of the shank portion **202** and its X-axis oriented parallel to the cross-hole **214** of the shank portion **202**. The tool bit **200** may be symmetrical about the X-Z plane. This may not be the case in other embodiments.

Other configurations of the tool bit are possible and considered to be within the scope of the present disclosure. For example, FIG. **4** discloses another embodiment for a tool bit **300** of the present disclosure similarly configured to that of FIG. **3** except for the following differences. This tool bit **300** includes a first arcuate surface **306**, a second arcuate surface **308** and a third arcuate surface **310**. The tool bit **300** further comprises a fourth arcuate surface **330** extending circumferentially from the third arcuate surface **310**, a fifth arcuate surface **332** extending circumferentially from the fourth arcuate surface **330**, and a sixth arcuate surface **334** extending circumferentially from the fifth arcuate surface **332**. The angle of extension γ of the tool bit **300** formed in a plane perpendicular to the longitudinal axis L is greater than the angle of extension γ of the tool bit **300** in FIG. **3**.

The fourth draft angle β_4 of the first, second, third, fourth, fifth, and sixth arcuate surfaces **306**, **308**, **310**, **330**, **332**, **334** varies more than the fourth draft angle β_4 of first, second, and third arcuate surfaces **206**, **208**, **210** of the embodiments shown in FIG. **3**. This forms a depression **336** at the X-Z plane as the arcuate surfaces **306**, **308**, **310**, **330**, **332**, **334** extend downwardly along the longitudinal axis L. The first draft angle β_1 of the rear face **316** may range from 0 to 30 degrees. Similarly, the second draft angle β_2 of the first side region **318** and the third draft angle β_3 of the second side region **320** may range from 0 to 30 degrees. The radius of curvature ROC of the first, second, third, fourth, fifth and sixth arcuate surfaces **306**, **308**, **310**, **330**, **332**, **334** may range from 50 mm to 65 mm for the embodiment shown in FIG. **4**. Again, the tool bit **300** is symmetrical about the X-Z plane. This may not be the case in other embodiments of the present disclosure.

A tool bit **200**, **300**, **400**, **500** for use with a blade assembly **100** of a grading machine **10** will now be described with reference to FIGS. **3** thru **6** that may be provided

separately from the blade assembly **100**. The tool bit **200**, **300**, **400**, **500** may comprise a shank portion **202**, **302**, **402**, **502** defining a longitudinal axis L, and a working portion **204**, **304**, **404**, **504**. The working portion **204**, **304**, **404**, **504** includes at least a first arcuate surface **206**, **306**, **406**, **506** disposed longitudinally adjacent the shank portion **202**, **302**, **402**, **502**. The shank portion **202**, **302**, **402**, **502** includes a cylindrical configuration defining a circumferential direction C and a radial direction R.

The working portion **204**, **304**, **404**, **504** may include a second arcuate surface **208**, **308**, **408**, **508** disposed adjacent the first arcuate surface **206**, **306**, **406**, **506** circumferentially on one side of the first arcuate surface **206**, **306**, **406**, **506** and a third arcuate surface **210**, **310**, **410**, **510** disposed adjacent the first arcuate surface **206**, **306**, **406**, **506** on the other side of the first arcuate surface **206**, **306**, **406**, **506**.

The shank portion **202**, **302**, **402**, **502** may define two flat surfaces **212**, **312**, **412**, **512** circumferentially aligned with the first arcuate surface **206**, **306**, **406**, **506**. The two flat surfaces **212**, **312**, **412**, **512** partially defining a cross-hole **214**, **314**, **414**, **514** extending radially thru the shank portion **202**, **302**, **402**, **502**. The shank portions **202**, **302**, **402**, **502** may be similarly configured so that they will work with the same adapter board **102** of the blade assembly **100**.

The working portion **204**, **304**, **404**, **504** may include a first arcuate surface **206**, **306**, **406**, **506**, a second arcuate surface **208**, **308**, **408**, **508** or a third arcuate surface **210**, **310**, **410**, **510** that defines a radius of curvature ROC ranging from 50 mm to 65 mm.

The tool bit **200**, **300**, **400**, **500** further comprising a rear face **216**, **316**, **416**, **516**, a first side region **218**, **318**, **418**, **518** extending from the second arcuate surface **208**, **308**, **408**, **508** to the rear face **216**, **316**, **416**, **516**, and a second side region **220**, **320**, **420**, **520** extending from the third arcuate surface **210**, **310**, **410**, **510** to the rear face **216**, **316**, **416**, **516**. As shown in FIG. 4, the tool bit **300** may further comprising a fourth arcuate surface **330** extending circumferentially from the third arcuate surface **310**, a fifth arcuate surface **332** extending circumferentially from the fourth arcuate surface **330**, and a sixth arcuate surface **334** extending circumferentially from the fifth arcuate surface **332**.

Referring again to FIGS. 3 thru 6, the working portion **204**, **304**, **404**, **504** may define a free axial end **224**, **324**, **424**, **524** and a notch **226**, **326**, **426**, **526** disposed proximate the free axial end **224**, **324**, **424**, **524**. An insert **228**, **328**, **428**, **528** disposed in the notch **226**, **326**, **426**, **526**.

The rear face **216**, **316**, **416**, **516** defines a first draft angle β_1 with the longitudinal axis L ranging from 0 to 40 degrees, the first side region **218**, **318**, **418**, **518** defines a second draft angle β_2 with the longitudinal axis L ranging from 0 to 40 degrees, the second side region **220**, **320**, **420**, **520** defines a third draft angle β_3 with the longitudinal axis L ranging from 0 to 40 degrees, and the first arcuate surface **206**, **306**, **406**, **506**, second arcuate surface **208**, **308**, **408**, **508** and third arcuate surface **210**, **310**, **410**, **510** define a fourth draft angle β_4 with the longitudinal axis L ranging from 0 to 30 degrees. Each of the tool bits **200**, **300**, **400**, **500** are symmetrical about the X-Z plane. Tool bit **400** has greater draft angles β_1 , β_2 , β_3 , β_4 than tool bit **300**. Tool bit **500** has greater drafter angles β_1 , β_2 , β_3 , β_4 than tool bit **400**.

The differences between the various tool bits **200**, **300**, **400**, **500** of FIGS. 3 thru 6 will now be discussed. As mentioned previously the tool bit **300** of FIG. 4 has a greater angle of extension γ as compared to the tool bit **200** of FIG. 3. Also, the side regions **218**, **220** of the tool bit **200** of FIG. 3 are slightly different configured than those of FIG. 4. The tool bit of FIG. 3 includes a top side transitional surface **230**

connecting the second arcuate surface **208** to the top rear side surface **232**. Both these surfaces **230**, **232** transition downwardly along the negative Z axis to a bottom side surface **234**. The tool bit **300** of FIG. 4 omits the bottom side surface but includes a top side transitional surface **338** and a top rear side surface **340**. The differences may be at least partially attributed to providing suitable back support for the inserts **228**, **328**, which have predominantly angled flat surfaces **236**, **342**. The insert **328** in FIG. 4 has a depression **344**, matching the depression **336** of the tool bit **300**. Thus, the tool bit **200**, **300** helps provide proper support to the insert **228**, **328**, thereby helping to prolong its useful life.

The tool bit **400** of FIG. 5 and the tool bit **500** of FIG. 6 have heavier draft angles β_1 , β_2 , β_3 , β_4 than those of the tool bit **200** of FIG. 3, allowing the these tool bits **400**, **500** to penetrate the ground or other work surface more easily than the tool bit **200** of FIG. 3. The tool bit **500** of FIG. 6 has a heavier draft angle β_1 , β_2 , β_3 , β_4 than the tool bit **400** of FIG. 5 for similar reasons. The side regions **418**, **420**, **518**, **520** of these tool bits **400**, **500** also have a top side transitional surface **430**, **530** a top rear side surface **432**, **532** and a bottom side surface **434**, **534** for the same reasons just discussed. Also, the inserts **428**, **528** comprise predominately angled flat surfaces **436**, **536**. This may not be the case for other embodiments of the present disclosure. The inserts for any embodiment may be symmetrical about the X-Z plane.

Additional drafted tool bits will now be described with reference to FIGS. 11 thru 46. It is to be understood that various features of the tool bits of FIGS. 11 thru 16 may have arcuate surfaces such as disclosed in FIGS. 3 thru 6. Likewise, the tool bits of FIGS. 3 thru 6, may have the features such as the drafted surfaces, dimensions, angles, etc. as will now be described with reference to FIGS. 11 thru 46.

Specifically, in FIGS. 3 and 17, surface **230** may be similarly constructed as surface **730**, surface **232** may be similarly constructed as surface **732**, and surface **234** may be similarly constructed as surface **734**. In FIGS. 4 and 11, surface **338** may be similarly constructed as surface **630**, and surface **340** may be similarly constructed as surface **632**, etc. In FIGS. 5 and 23, surface **430** and surface **830** may be similarly constructed. Surface **432** and surface **832** may be similarly constructed and surface **434** and surface **734** may be similarly constructed, etc. In FIGS. 6 and 29, surface **530** and surface **930**, surface **532** and surface **932**, and surface **534** and surface **934** may be similarly constructed, etc.

Looking at FIGS. 11 thru 16, a tool bit **600** (e.g. a wide grading tool bit) for use with a blade assembly **100** of a grading machine **10** is illustrated. The tool bit **600** comprises a shank portion **602** defining a longitudinal axis L, and a working portion **604**. The working portion **604** includes a rear region **616**, a front working region **605**, a first side region **618** and a second side region **620**, and the first side region **618** and the second side region **620** may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L, forming a wider front working region **605** than the rear region **616** in a plane perpendicular to the longitudinal axis L. The angle of extension γ may range from 0 to 20 degrees. The front working region **605** is so called since this region that predominantly performs the work when contacting or penetrating the ground or other work surface.

The shank portion **602** may include a cylindrical configuration defining a circumferential direction C and a radial direction R. The rear region **616** may at least partially form

a right angle RA with the radial direction R in a plane perpendicular to the longitudinal axis L (best seen in FIGS. 14 thru 16).

The front working region 605 may include a first angled surface 606 and a second angled surface 608 forming a first included angle $\ominus 1$ with the first angled surface 606 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 150 to 180 degrees. Similarly, the front working region 605 may further comprise a third angled surface 610 forming a first external angle $\alpha 1$ with the second angled surface 608 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 150 to 180 degrees. Likewise, the front working region 605 further comprises a fourth angled surface 611 forming a second included angle $\theta 2$ with the third angled surface 610 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 150 to 180 degrees.

The first side region 618 or second side region 620 may include a first drafted side surface 632 configured to reduce drag of the tool bit 600 along the longitudinal axis L in use. For the embodiment shown in FIGS. 11 and 16, this surface may have little to no draft (e.g. 0 to 5 degrees). In many embodiments such as that shown in FIGS. 11 thru 16, the tool bit 600 is symmetrical about an X-Z plane of a Cartesian coordinate system with its origin O on the longitudinal axis L and its X-axis aligned with the cross-hole 614 passing through the flat surfaces 612 of the shank portion 602.

Referring to FIGS. 11 and 13, the rear region 616 may form a first draft angle $\beta 1$ with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L , the first draft angle $\beta 1$ ranging from 0 to 20 degrees. The first side region 618 may form a second draft angle $\beta 2$ with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L , ranging from 0 to 30 degrees. The second side region 620 may form a third draft angle $\beta 3$ with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L , ranging from 0 to 30 degrees. The front working region 605 may form a fourth draft angle $\beta 4$ with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L , ranging from 0 to 30 degrees. $\beta 2$ and $\beta 3$ are negative draft angles as seen in FIGS. 14 thru 15 since the width of the cross-section of the working portion 604 is decreasing as one progresses upwardly along the longitudinal axis L .

This tool bit 600 may be further describe as follows with reference to FIGS. 11 thru 16. A tool bit 600 for use with a blade assembly 100 of a grading machine 10 may comprise a shank portion 602 defining a longitudinal axis L , and a working portion 604. The working portion 604 includes a rear region 616, a front working region 605, a first side region 618 and a second side region 620, and the first side region 618 or the second side region 620 include a first vertical surface 630 disposed longitudinally adjacent the shank portion 602, and a first drafted side surface 632 configured to reduce drag of the tool bit 600 through the ground or other work surface extending from the first vertical surface 630.

The first drafted side surface 632 may extend downwardly longitudinally from or past the first vertical surface 630 and the working portion 605 and terminate at the free axial end 624 of the tool bit 600. The first drafted surface 632 forms at least partially a first obtuse included angle $\varphi 1$ with the rear region 616 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L , ranging from 90 to 120 degrees. The first drafted side surface 632 and the

first vertical surface 630 may at least partially border a notch 626 configured to receive an insert 628.

FIGS. 14 thru 16 show how the cross-section of the tool bit 600 changes over time as the tool bit wears. FIG. 16 shows a first state of initial wear. FIG. 15 shows an intermediate state of wear while FIG. 14 shows an advanced state of wear. Polygonal cross-sections, such as nearly trapezoidal cross-sections, are formed.

FIGS. 17 thru 22 depict a standard grading tool bit. This tool bit is similarly configured as the tool bit of FIGS. 11 thru 16. The tool bit 700 comprises a shank portion 702 defining a longitudinal axis L , and a working portion 704 extending downwardly axially from the shank portion 702. The working portion 704 includes a rear region 716, a front working region 705, a first side region 718 and a second side region 720, and the first side region 718 and the second side region 720 may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L , forming a wider front working region 705 than the rear region 716 in a plane perpendicular to the longitudinal axis. The angle of extension γ may range from 0 to 40 degrees.

The shank portion 702 may include a cylindrical configuration defining a circumferential direction C and a radial direction R and the rear region 716 may at least partially form a right angle RA with the radial direction R in a plane perpendicular to the longitudinal axis L (best seen in FIGS. 20 thru 22).

The front working region 705 may include a first angled surface 706 and a second angled surface 708 forming a first included angle $\ominus 1$ with the first angled surface 706 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis, ranging from 130 to 180 degrees. The first side region 718 or second side region 720 may include a first drafted side surface 732 configured to improve penetration of the tool bit 700 in use. In many embodiments such as that shown in FIGS. 17 thru 22, the tool bit 700 is symmetrical about an X-Z plane about a Cartesian coordinate system with its origin O on the longitudinal axis L and its X-axis aligned with the cross-hole 714 passing through the flat surfaces 712.

As shown in FIG. 19, the rear region 716 may form a first draft angle $\beta 1$ with the longitudinal axis L measured in a plane containing the radial direction R and longitudinal axis L , the first draft angle $\beta 1$ ranging from 0 to 35 degrees. Similarly, as shown in FIG. 18, the first side region may form a second draft angle $\beta 1$ with the longitudinal axis L measured in a plane containing the radial direction R and longitudinal axis L , forming a second draft angle $\beta 2$, ranging from 0 to 40 degrees. The second side region 720 may form a third draft angle $\beta 3$ with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L , ranging from 0 to 40 degrees. Returning to FIG. 19, the front working region 705 may form a fourth draft angle $\beta 4$ with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L , ranging from 0 to 30 degrees. $\beta 2$ and $\beta 3$ are positive draft angles as seen in FIGS. 20 thru 15 since the width of the cross-section of the working portion 704 is increasing as one progresses upwardly along the longitudinal axis L .

This tool bit 700 may be further describe as follows with reference to FIGS. 17 thru 22. A tool bit 700 for use with a blade assembly 100 of a grading machine 10 may comprise a shank portion 702 defining a longitudinal axis L , and a working portion 704. The working portion 704 includes a rear region 716, a front working region 705, a first side region 718 and a second side region 720, and the first side region 718 or the second side region 720 includes a first

vertical surface **730** disposed longitudinally adjacent the shank portion **702**, and a first drafted side surface **732** configured to improve penetration of the tool bit **700** extending from the first vertical surface **730**.

The first drafted side surface **732** may extend downwardly longitudinally from the first vertical surface **730** and the working portion **705** may include a second vertical surface **734** extending downwardly longitudinally from the first drafted side surface **732**. The first drafted side surface **732** forms at least partially a first included obtuse angle ϕ_1 with the rear region **716** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L. The first drafted side surface **732** and the second vertical surface **734** may at least partially border a notch **726** configured to receive an insert **728**.

FIGS. **20** thru **22** show how the cross-section of the tool bit **700** changes over time as the tool bit **700** wears. FIG. **22** shows a first state of initial wear. FIG. **21** shows an intermediate state of wear while FIG. **20** shows an advanced state of wear. Polygonal cross-sections, such as nearly trapezoidal cross-sections, are formed.

FIGS. **23** thru **28** depict a sharp grader tool bit. This tool bit is similarly configured as the tool bit of FIGS. **17** thru **22**, but with more draft, etc. The tool bit **800** comprises a shank portion **802** defining a longitudinal axis L, and a working portion **804** extending downwardly axially from the shank portion **802**. The working portion **804** includes a rear region **816**, a front working region **805**, a first side region **818** and a second side region **820**, and the first side region **818** and the second side region **820** may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L, forming a wider front working region **805** than the rear region **816** in a plane perpendicular to the longitudinal axis. The angle of extension γ may range from 0 to 50 degrees.

The shank portion **802** may include a cylindrical configuration defining a circumferential direction C and a radial direction R and the rear region **816** may at least partially form a right angle RA with the radial direction R in a plane perpendicular to the longitudinal axis L (best seen in FIG. **20**).

The front working region **805** may include a first angled surface **806** and a second angled surface **808** forming a first included angle Θ_1 with the first angled surface **806** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis, ranging from 140 to 180 degrees. The first side region **818** or second side region **820** may include a first drafted side surface **832** configured to improve penetration of the tool bit **800** in use. In many embodiments such as that shown in FIGS. **23** thru **28**, the tool bit **800** is symmetrical about an X-Z plane about a Cartesian coordinate system with its origin O on the longitudinal axis L and its X-axis aligned with the cross-hole **814** passing through the flat surfaces **812**.

As shown in FIG. **25**, the rear region **816** may form a first draft angle β_1 with the longitudinal axis L measured in a plane containing the radial direction R and longitudinal axis L, the first draft angle β_1 ranging from 0 to 30 degrees. Similarly, as shown in FIG. **24**, the first side region **818** may form a second draft angle β_2 with the longitudinal axis L measured in a plane containing the radial direction R and longitudinal axis L, ranging from 0 to 40 degrees. The second side region **820** may form a third draft angle β_3 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 40 degrees. Returning to FIG. **25**, the front working region **805** may form a fourth draft angle β_4 with the longitudinal axis L measured in a plane containing the radial

direction R and the longitudinal axis L, ranging from 0 to 30 degrees. β_2 and β_3 are positive draft angles as seen in FIGS. **26** thru **28** since the width of the cross-section of the working portion **804** is increasing as one progresses upwardly along the longitudinal axis L.

This tool bit **800** may be further describe as follows with reference to FIGS. **23** thru **28**. A tool bit **800** for use with a blade assembly **100** of a grading machine **10** may comprise a shank portion **802** defining a longitudinal axis L, and a working portion **804**. The working portion **804** includes a rear region **816**, a front working region **805**, a first side region **818** and a second side region **820**, and the first side region **818** or the second side region **820** includes a first vertical surface **830** disposed longitudinally adjacent the shank portion **802**, and a first drafted side surface **832** configured to improve penetration of the tool bit **800** extending from the first vertical surface **830**.

The first drafted side surface **832** may extend downwardly longitudinally from the first vertical surface **830**. The working portion **805** may include a second vertical surface **834** extending downwardly longitudinally from the first drafted side surface **832**. The first drafted side surface **832** forms at least partially a first included obtuse angle ϕ_1 with the rear region **816** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L. The first drafted side surface **832** and the second vertical surface **834** may at least partially border a notch **826** configured to receive an insert **828**.

FIGS. **26** thru **28** show how the cross-section of the tool bit **800** changes over time as the tool bit **800** wears. FIG. **28** shows a first state of initial wear. FIG. **27** shows an intermediate state of wear while FIG. **26** shows an advanced state of wear. Polygonal cross-sections, such as nearly trapezoidal cross-sections, are formed.

FIGS. **29** thru **34** depict a penetration grader tool bit. This tool bit is similarly configured as the tool bit of FIGS. **17** thru **22**, but with more draft, etc. The tool bit **900** comprises a shank portion **902** defining a longitudinal axis L, and a working portion **904** extending downwardly axially from the shank portion **902**. The working portion **904** includes a rear region **916**, a front working region **905**, a first side region **918** and a second side region **920**, and the first side region **918** and the second side region **920** may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L, forming a wider front working region **905** than the rear region **916** in a plane perpendicular to the longitudinal axis L. The angle of extension γ may range from 0 to 40 degrees.

The shank portion **902** may include a cylindrical configuration defining a circumferential direction C and a radial direction R and the rear region **916** may at least partially form a right angle RA with the radial direction R in a plane perpendicular to the longitudinal axis L (best seen in FIG. **32**).

The front working region **905** may include a first angled surface **906** and a second angled surface **908** forming a first included angle Θ_1 with the first angled surface **906** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L, ranging from 130 to 180 degrees. The first side region **918** or second side region **920** may include a first drafted side surface **932** configured to improve penetration of the tool bit **900** in use. In many embodiments such as that shown in FIGS. **29** thru **34**, the tool bit **900** is symmetrical about an X-Z plane about a Cartesian coordinate system with its origin O on the longitudinal axis L and its X-axis aligned with the cross-hole **914** passing through the flat surfaces **912**.

As shown in FIG. 31, the rear region 916 may form a first draft angle β_1 with the longitudinal axis L measured in a plane containing the radial direction R and longitudinal axis L, the first draft angle β_1 ranging from 0 to 30 degrees. Similarly, as shown in FIG. 30, the first side region 918 may form a second draft angle β_2 with the longitudinal axis L measured in a plane containing the radial direction R and longitudinal axis L, ranging from 0 to 45 degrees. The second side region 920 may form a third draft angle β_3 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 45 degrees. Returning to FIG. 31, the front working region 905 may form a fourth draft angle β_4 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 30 degrees. β_2 and β_3 are positive draft angles as seen in FIGS. 32 thru 34 since the width of the cross-section of the working portion 904 is increasing as one progresses upwardly along the longitudinal axis L.

This tool bit 900 may be further describe as follows with reference to FIGS. 29 thru 34. A tool bit 900 for use with a blade assembly 100 of a grading machine 10 may comprise a shank portion 902 defining a longitudinal axis L, and a working portion 904. The working portion 904 includes a rear region 916, a front working region 905, a first side region 918 and a second side region 920, and the first side region 918 or the second side region 920 includes a first vertical surface 930 disposed longitudinally adjacent the shank portion 902, and a first drafted side surface 932 configured to improve penetration of the tool bit 900 extending from the first vertical surface 930.

The first drafted side surface 932 may extend downwardly longitudinally from the first vertical surface 930. The working portion 905 may include a second vertical surface 934 extending downwardly longitudinally from the first drafted side surface 932. The first drafted side surface 932 forms at least partially a first included obtuse angle φ_1 with the rear region 916 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L (best seen in FIG. 32). The first drafted side surface 932 and the second vertical surface 934 may at least partially border a notch 926 configured to receive an insert 928.

FIGS. 32 thru 34 show how the cross-section of the tool bit 900 changes over time as the tool bit 900 wears. FIG. 34 shows a first state of initial wear. FIG. 33 shows an intermediate state of wear while FIG. 32 shows an advanced state of wear. Polygonal cross-sections, such as nearly trapezoidal cross-sections, are formed.

Looking at FIGS. 35 thru 40, a tool bit 1000 (e.g. a wide mining tool bit, similarly configured as the wide grading bit except that the working portion is longer axially and includes an extra insert, etc.) for use with a blade assembly 100 of a grading machine 10 is illustrated. The tool bit 1000 comprises a shank portion 1002 defining a longitudinal axis L, and a working portion 1004. The working portion 1004 includes a rear region 1016, a front working region 1005, a first side region 1018 and a second side region 1020, and the first side region 1018 and the second side region 1020 may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L, forming a wider front working region 1005 than the rear region 1016 in a plane perpendicular to the longitudinal axis L. The angle of extension γ may range from 0 to 40 degrees. The front working region 1005 is so called since this region that predominantly performs the work when contacting or penetrating the ground or other work surface.

The shank portion 1002 may include a cylindrical configuration defining a circumferential direction C and a radial direction R. The rear region 1016 may at least partially form a right angle RA with the radial direction R in a plane perpendicular to the longitudinal axis L (best seen in FIGS. 38 thru 40).

The front working region 1005 may include a first angled surface 1006 and a second angled surface 1008 forming a first included angle $\ominus 1$ with the first angled surface 1006 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 150 to 180 degrees. Similarly, the front working region 1005 may further comprise a third angled surface 1010 forming a first external angle $\alpha 1$ with the second angled surface 1008 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 150 to 180 degrees. Likewise, the front working region 1005 further comprises a fourth angled surface 1011 forming a second included angle $\theta 2$ with the third angled surface 1010 projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 150 to 180 degrees.

The first side region 1018 or second side region 1020 may include a first drafted side surface 1032 configured to reduce drag of the tool bit 1000 along the longitudinal axis L in use. For the embodiment shown in FIGS. 35 and 40, this surface may have little to no draft (e.g. 0 to 5 degrees). In many embodiments such as that shown in FIGS. 36 thru 40, the tool bit 1000 is symmetrical about an X-Z plane of a Cartesian coordinate system with its origin O on the longitudinal axis L and its X-axis aligned with the cross-hole 1014 passing through the flat surfaces 1012 of the shank portion 1002.

Referring to FIGS. 35 and 37, the rear region 1016 may form a first draft angle β_1 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, the first draft angle β_1 ranging from 0 to 30 degrees. The first side region 1018 may form a second draft angle β_2 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 30 degrees. The second side region 1020 may form a third draft angle β_3 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 30 degrees. The front working region 1005 may form a fourth draft angle β_4 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 30 degrees. β_2 and β_3 are negative draft angles as seen in FIGS. 38 thru 40 since the width of the cross-section of the working portion 1004 is decreasing as one progresses upwardly along the longitudinal axis L.

This tool bit 1000 may be further describe as follows with reference to FIGS. 35 thru 40. A tool bit 1000 for use with a blade assembly 100 of a grading machine 10 may comprise a shank portion 1002 defining a longitudinal axis L, and a working portion 1004. The working portion 1004 includes a rear region 1016, a front working region 1005, a first side region 1018 and a second side region 1020, and the first side region 1018 or the second side region 1020 include a first vertical surface 1030 disposed longitudinally adjacent the shank portion 1002, and a first drafted side surface 1032 configured to reduce draft of the tool bit 1000 through the ground or other work surface extending from the first vertical surface 1030.

The first drafted side surface 1032 may extend downwardly longitudinally from or past the first vertical surface 1030 and the working portion 1005 and terminate at the free

axial end **1024** of the tool bit **1000**. The first drafted surface **1032** forms at least partially a first obtuse included angle φ_1 with the rear region **1016** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L, ranging from 90 to 120 degrees. The first drafted side surface **1032** and the first vertical surface **1030** may at least partially border a notch **1026** configured to receive an insert **1028**.

FIGS. **38** thru **40** show how the cross-section of the tool bit **1000** changes over time as the tool bit wears. FIG. **40** shows a first state of initial wear. FIG. **39** shows an intermediate state of wear while FIG. **38** shows an advanced state of wear. Polygonal cross-sections, such as nearly trapezoidal cross-sections, are formed.

The working portion **1004** of this tool bit **1000** further defines a slot **1034** extending along a direction parallel to the Y-axis, from one drafted side surface **1032** of the first side region **1018** to the other drafted side surface **1032** of second side region **1020**. An extra reinforcement insert **1036** may be disposed therein made of a similar material and/or having similar properties as the other insert **1028**.

Looking at FIGS. **41** thru **46**, a tool bit **2000** (e.g. a standard mining tool bit, similarly configured as the wide mining bit except that the working portion is more narrow, etc.) for use with a blade assembly **100** of a grading machine **10** is illustrated. The tool bit **2000** comprises a shank portion **2002** defining a longitudinal axis L, and a working portion **2004**. The working portion **2004** includes a rear region **2016**, a front working region **2005**, a first side region **2018** and a second side region **2020**, and the first side region **2018** and the second side region **2020** may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L, forming a wider front working region **2005** than the rear region **2016** in a plane perpendicular to the longitudinal axis L. The angle of extension γ may range from 0 to 40 degrees. The front working region **2005** is so called since this region that predominantly performs the work when contacting or penetrating the ground or other work surface.

The shank portion **2002** may include a cylindrical configuration defining a circumferential direction C and a radial direction R. The rear region **2016** may at least partially form a right angle RA with the radial direction R in a plane perpendicular to the longitudinal axis L (best seen in FIG. **44**).

The front working region **2005** may include a first angled surface **2006** and a second angled surface **2008** forming a first included angle θ_1 with the first angled surface **2006** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 140 to 180 degrees. The first side region **2018** or second side region **2020** may include a first drafted side surface **2032** configured to improve penetration of the tool bit **2000** along the longitudinal axis L in use. In many embodiments such as that shown in FIGS. **41** thru **46**, the tool bit **2000** is symmetrical about an X-Z plane of a Cartesian coordinate system with its origin O on the longitudinal axis L and its X-axis aligned with the cross-hole **2014** passing through the flat surfaces **2012** of the shank portion **2002**.

Referring to FIGS. **42** and **43**, the rear region **2016** may form a first draft angle β_1 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, the first draft angle β_1 ranging from 0 to 30 degrees. The first side region **2018** may form a second draft angle β_2 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 40 degrees. The second side region **2020** may form a third draft angle β_3 with the longitudinal axis L measured in a plane containing the radial direction R

and the longitudinal axis L, ranging from 0 to 40 degrees. The front working region **2005** may form a fourth draft angle β_4 with the longitudinal axis L measured in a plane containing the radial direction R and the longitudinal axis L, ranging from 0 to 30 degrees. β_2 and β_3 are positive draft angles as seen in FIGS. **38** thru **40** since the width of the cross-section of the working portion **2004** is increasing as one progresses upwardly along the longitudinal axis L.

This tool bit **2000** may be further describe as follows with reference to FIGS. **41** thru **46**. A tool bit **2000** for use with a blade assembly **100** of a grading machine **10** may comprise a shank portion **2002** defining a longitudinal axis L, and a working portion **2004**. The working portion **2004** includes a rear region **2016**, a front working region **2005**, a first side region **2018** and a second side region **2020**, and the first side region **2018** or the second side region **2020** include a first vertical surface **2030** disposed longitudinally adjacent the shank portion **2002**, and a first drafted side surface **2032** configured to improve penetration of the tool bit **2000** into the ground or other work surface extending from the first vertical surface **2030**.

The first drafted side surface **2032** may extend downwardly longitudinally from or past the first vertical surface **2030** and the working portion **2005** and terminate at the free axial end **2024** of the tool bit **2000**. The first drafted surface **2032** forms at least partially a first obtuse included angle φ_1 with the rear region **2016** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L, ranging from 90 to 120 degrees. A second vertical surface **2033** may extend downwardly from the first drafted side surface **2032**, both of which may at least partially border a notch **2026** configured to receive an insert **2028**.

FIGS. **44** thru **46** show how the cross-section of the tool bit **2000** changes over time as the tool bit wears. FIG. **46** shows a first state of initial wear. FIG. **45** shows an intermediate state of wear while FIG. **44** shows an advanced state of wear. Polygonal cross-sections, such as nearly trapezoidal cross-sections, are formed.

The working portion **2004** of this tool bit **2000** further defines a slot **2034** extending along a direction parallel to the Y-axis, from one drafted side surface **2032** of the first side region **2018** to the other drafted side surface **2032** of second side region **2020**. An extra reinforcement insert **2036** may be disposed therein made of a similar material and/or having similar properties as the other insert **1028**.

FIG. **47** illustrates an insert (may also be referred to as a tile) that may be similarly or identically configured as the insert used in FIGS. **3**, **4**, **11**, **17**, **35**, and **42**. It should be noted that the geometry of the insert may be doubled in a single insert or two similar inserts may be used side by side such as shown in FIG. **11**, etc. Accordingly, the insert **3000** is configured to be attached to the notch of a tool bit for use with a grading machine as previously described. The insert **3000** may comprise a first side face **3002**, a second side face **3004**, a top face **3006**, a bottom face **3008**, a rear face **3010**, and a front region **3012** including a first flat face **3014**, and a second flat face **3016** forming an obtuse included angle **3018** with the first flat face **3014** on the top face **3006** ranging from 130 to 180 degrees.

The first side face **3002** may be perpendicular to the rear face **3010** and to the top face **3006** and may be parallel to the second side face **3004**. The insert **300** may further comprise a blend **3020** transitioning from the first flat surface **3014** to the second flat surface **3016** and a bottom face **3008** that forms right angles with the rear face **3010**, the first side face **3002**, and the second side face **3004**. The insert **3000** further comprises a chamfered surface **3022** connecting the first flat

face **3014**, second flat face **3016**, blend **3020** and the bottom face **3008**. The chamfered surface **3022** may form a chamfer angle **3024** with bottom face ranging from 120 to 180 degrees. It should be noted that the first side face **3002** and second side face **3004**, and the associated obtuse included angle **3018** may be designed to match to the corresponding surfaces of a tool bit and vice versa. Any of the angles may be varied as needed or desired in any embodiment.

FIG. **48** illustrates an insert (may also be referred to as a tile) that may be similarly or identically configured as the insert used in FIGS. **5**, **6**, **23** and **29**. The insert **4000** is configured to be attached to the notch of a tool bit for use with a grading machine as previously described. The insert **4000** may comprise a first side face **4002**, a second side face **4004**, a top face **4006**, a bottom face **4008**, a rear face **4010**, and a front region **4012** including a first flat face **4014**, and a second flat face **4016** forming an obtuse included angle **4018** with the first flat face **4014** on the top face **4006** ranging from 120 to 180 degrees.

The first side face **4002** may be perpendicular to the rear face **4010** and to the top face **4006** and may be parallel to the second side face **4004**. The insert **4000** may further comprise a blend **4020** transitioning from the first flat surface **4014** to the second flat surface **4016** and a bottom face **4008** that forms right angles with the rear face **4010**, the first side face **4002**, and the second side face **4004**. The insert **4000** may further comprise a bottom region **4022**, similarly configured to the front region **4012**, allowing the geometry to wrap around the bottom of the insert **4000**. The bottom region **4022** may form a bottom obtuse angle **4024** with the rear face **4010** ranging from 90 to 140 degrees (see FIGS. **30** and **31**). The bottom region **4022** includes a third flat face **4026** and a fourth flat face **4028** that form a bottom included angle **4030** with each other that may match the obtuse included angle **4018**.

The bottom and rear regions of a tool bit using such inserts **3000**, **4000** may have faceted features that allow the included angle of the front region to extend from the top of the front region about the bottom of the tool bit up to the top portion of the rear region of the tool bit. For examples, see FIGS. **13** and **31**.

Various embodiments of a tool bit that allows greater versatility of its orientation with respect to the centerline of an adapter board will now be discussed. For brevity, only specific embodiments of the tool bits shown in FIGS. **4**, **11** and **17** will be described in detail. It is to be understood that the same features are present and the same description applies to the embodiments shown in the tool bits of FIGS. **3**, **5**, **6**, **23**, **29**, **35**, and **41**, etc.

Looking at FIGS. **4**, and **11** thru **22**, a tool bit **5000**, **6000**, **7000** for use with a blade assembly **100** of a grading machine **10** as just mentioned is shown. The tool bit **5000**, **6000**, **7000** may comprise a shank portion **5002**, **6002**, **7002** defining a longitudinal axis **L** and a perimeter **5003**, **6003**, **7003**. A pair of parallel flat surfaces **5012**, **6012**, **7012** may be disposed on the perimeter **5003**, **6003**, **7003** and the shank portion **5002**, **6002**, **7002** may define a cross-hole **5014**, **6014**, **7014** defining a cross-hole axis **A5014**, **A6014**, **A7014** along which the cross-hole **5014**, **6014**, **7014** extends through the flat surfaces **5012**, **6012**, **7012** perpendicularly. The tool bit **5000**, **6000**, **7000** may also include a working portion **5004**, **6004**, **7004** extending downwardly axially from the shank portion **5002**, **6002**, **7002**. The working portion **5004**, **6004**, **7004** may include a rear region **5016**, **6016**, **7016**, a front working region **5005**, **6005**, **7005** defining a width **W5005**, **W6005**, **W7005** with a midpoint **MW5005**, **MW6005**, **MW7005**, a first side region **5018**,

6018, **7018** and a second side region **5020**, **6020**, **7020**. The first side region **5018**, **6018**, **7018** and the second side region **5020**, **6020**, **7020** define an angle of extension γ measured in a plane perpendicular to the longitudinal axis **L**. The cross-hole axis **A5014**, **A6014**, **A7014** may pass through the width **W5005**, **W6005**, **W7005** of the front working region **5005**, **6005**, **7005** when projected onto a plane perpendicular to the longitudinal axis **L**.

In the embodiments shown in FIGS. **4**, and **11** thru **22**, the angle of extension γ forms a wider front working region **5005**, **6005**, **7005** than the rear region **5016**, **6016**, **7016** in a plane perpendicular to the longitudinal axis **L**. The angle of extension γ may range from 0 to 30 degrees. The shank portion **5002**, **6002**, **7002** includes a cylindrical configuration defining a circumferential direction **C** and a radial direction **R**, and the rear region **5016**, **6016**, **7016** at least partially forms a right angle **RA** with the radial direction in a plane perpendicular to the longitudinal axis **L**. The cross-hole **5014**, **6014**, **7014** having a cylindrical configuration defining a cylindrical axis **L5014**, **L6014**, **L7014** passing perpendicularly through the longitudinal axis **L** of the shank portion **5002**, **6002**, **7002**, and the cross-hole axis **A5014**, **A6014**, **A7014** passes through the midpoint **MW5005**, **MW6005**, **MW7005** of the width **W5005**, **W6005**, **W7005** of the front working region **5005**, **6005**, **7005** when projected onto a plane perpendicular to the longitudinal axis **L**. These features may be differently configured or omitted in other embodiments.

For the tool bits **6000**, **7000** in FIGS. **11** thru **22**, the front working region **6005**, **7005** includes a first angled surface **6006**, **7006** and a second angled surface **6008**, **7008** forming a first included angle θ_1 with the first angled surface **6006**, **7006** projected along the longitudinal axis **L** onto a plane perpendicular to the longitudinal axis **L** ranging from 140 to 180 degrees. For the tool bit **6000** shown in FIGS. **11** thru **16**, the tool bit **6000** further comprises a third angled surface **6010** forming a first external angle α_1 with the second angled surface **6008** projected along the longitudinal axis **L** onto a plane perpendicular to the longitudinal axis **L** ranging from 140 to 180 degrees. The front working region **6005** further comprises a fourth angled surface **6011** forming a second included angle θ_2 with the third angled surface **6010** projected along the longitudinal axis **L** onto a plane perpendicular to the longitudinal axis ranging from 140 to 180 degrees.

For the tool bits **5000**, **6000**, **7000** shown in FIGS. **4**, and **11** thru **22**, the first side region **5018**, **6018**, **7018** or second side region **5020**, **6020**, **7020** may include a first drafted side surface **5032**, **6032**, **7032** configured to improve penetration of the tool bit **5000**, **6000**, **7000** or reduce drag in use. Also, the rear region **5016**, **6016**, **7016** may form a first draft angle β_1 with the longitudinal axis measured **L** in a plane containing the radial direction **R** and the longitudinal axis **L**, ranging from 0 to 40 degrees, the first side region **5018**, **6018**, **7018** may form a second draft angle β_2 with the longitudinal axis **L** measured in a plane containing the radial direction **R** and the longitudinal axis **L**, ranging from 0 to 40 degrees, the second side region **5020**, **6020**, **7020** may form a third draft angle β_3 with the longitudinal axis **L** measured in a plane containing the radial direction **R** and the longitudinal axis **L**, ranging from 0 to 40 degrees, and the front working region **5005**, **6005**, **7005** may form a fourth draft angle β_4 with the longitudinal axis **L** measured in a plane containing the radial direction **R** and the longitudinal axis **L**, ranging from 0 to 30 degrees.

For the tool bit **5000** shown in FIG. **4**, the working portion **5004** includes at least a first arcuate surface **5006** disposed

21

longitudinally adjacent the shank portion **5002**, the at least first arcuate surface **5006** defining a radius of curvature ROC that is equal to or greater than the half of the width W of the lower tool bit attachment portion **108** of the adapter board **102**. Returning to FIG. **49** and FIG. **17**, and the lower tool bit attachment portion **108** of the adapter board **102** may define a plurality of cylindrical thru-bores **112** and the shank portion **7002** of the tool bit **7000** includes a cylindrical configuration defining a circumferential direction C and a radial direction R. The shank portion **7002** is configured to fit within one of the plurality of cylindrical thru-bores **112** and the cross-hole **7014** may have a cylindrical configuration defining a cylindrical axis L**7014** passing perpendicularly through the longitudinal axis L of the shank portion **7002**. The cross-hole axis A**7014** passes through the midpoint MW**7005** of the width W**7005** of the front working region **7005** when projected onto a plane perpendicular to the longitudinal axis L.

Still Referring to FIG. **4**, the working portion **5004** includes a second arcuate surface **5008** disposed adjacent the first arcuate surface **5006** circumferentially on one side of the first arcuate surface **5006** and a third arcuate surface **5010** disposed adjacent the first arcuate surface **5006** on the other side of the first arcuate surface **5006**. Referring now to FIG. **17**, the front working region **7005** includes a first angled surface **7006** and a second angled surface **7008** forming a first included angle $\Theta 1$ with the first angled surface **7006** projected along the longitudinal axis L onto a plane perpendicular to the longitudinal axis L ranging from 140 to 180 degrees.

The first arcuate surface **5006**, the second arcuate surface **5008** or third arcuate surface **5010** may define a radius of curvature ROC as previously described herein. The tool bit **5000** may further comprise a rear face **5016**, a first side region **5018** extending from the second arcuate surface **5008** to the rear region **5016**, and a second side region **5020** extending from the third arcuate surface **5006** to the rear region **5016**. The tool bit **5000** may further comprise a fourth arcuate surface **5011** extending circumferentially from the third arcuate surface **5010**.

For the tool bits **5000**, **6000**, **7000** shown in FIGS. **4**, and **11** thru **22**, each tool bit **5000**, **6000**, **7000** defines a first draft angle ($\beta 1$ with the longitudinal axis L ranging from 0 to 40 degrees, the first side region **5018**, **6018**, **7018** defines a second draft angle $\beta 2$ with the longitudinal axis L ranging from 0 to 40 degrees, the second side region **5020**, **6020**, **7020** defines a third draft angle ($\beta 3$ with the longitudinal axis L ranging from 0 to 40 degrees, and (see FIG. **4**) the first arcuate surface **5006**, the second arcuate surface **5008** and third arcuate surface **5010** define a fourth draft angle $\beta 4$ with the longitudinal axis L ranging from 0 to 30 degrees.

Now, an embodiment of a blade assembly **8000** that may use tool bits **5000**, **6000**, **7000** having a greater versatility of orientations relative the centerline CL of the adapter board will be discussed with reference to FIGS. **49** thru **54**. A blade assembly **8000** for use with a grading machine **10** may comprise an adapter board **102** defining an upper adapter board attachment portion **104**, terminating in an upper adapter board free end **106**, and a lower tool bit attachment portion **108**, terminating in a lower adapter board free end **110**, the lower tool bit attachment portion **108** defining a width W.

A plurality of tool bits **5000**, **6000**, **7000** (e.g. see FIGS. **4** and **11** thru **22**) may be configured to be attached to the adapter board **102**, each tool bit **5000**, **6000**, **7000** may include a shank portion **5002**, **6002**, **7002** defining a longitudinal axis L and a perimeter **5003**, **6003**, **7003**, a pair of

22

parallel flat surfaces **5012**, **6012**, **7012** on the perimeter **5003**, **6003**, **7003** and a cross-hole **5014**, **6014**, **7014** defining a cross-hole axis A**5014**, A**6014**, A**7014** (best seen in FIGS. **4**, and **11** thru **22**), extending through the flat surfaces **5012**, **6012**, **7012** perpendicularly. The working portion **5004**, **6004**, **7004** may include a rear region **5016**, **6016**, **7016**, a front working region **5005**, **6005**, **7005** defining a width W**5005**, W**6005**, W**7005** with a midpoint MW**5005**, MW**6005**, MW**7005**, a first side region **5018**, **6018**, **7018** and a second side region **5020**, **6020**, **7020**. The first side region **5018**, **6018**, **7018** and the second side region **5020**, **6020**, **7020** may define an angle of extension γ measured in a plane perpendicular to the longitudinal axis L. The cross-hole axis A**5014**, A**6014**, A**7014** may pass through the width W**5005**, W**6005**, W**7005** of the front working region **5005**, **6005**, **7005** when projected onto a plane perpendicular to the longitudinal axis L.

For the tool bit **500** shown in FIG. **4**, the tool bit **5000** may comprise a first arcuate surface **5006** defining a radius of curvature ROC in a plane perpendicular to the longitudinal axis L ranging from 50 to 65 mm. Additional arcuate surfaces may be provided. This radius of curvature ROC may allow the tool bit **5000** to be better supported in a plurality of orientations relative to the CL of the adapter board **102** (see FIGS. **7** thru **10**).

Focusing on FIGS. **49** thru **54**, an orientation plate **9000** may also be provided that defines a plurality of apertures **9002**, each aperture **9002** having an orientation flat **9004** configured to contact a flat surface **7012** of the shank portion **7002** of tool bit **7000**. It is to be understood that any of the tool bits discussed herein may be used with the blade assembly **8000** or blade assembly **100**.

More specifically, with reference to FIGS. **7** and **51**, an orientation plate **9000** configured to orient a tool bit **200**, **5000**, **6000**, **7000** relative to the centerline CL of an adapter board **102** may be described as follows. The orientation plate **9000** may comprise a rectangular body **9001** defining a top surface **9006**, a bottom surface **9008**, a front surface **9010**, a back surface **9012**, a first end surface **9014**, a second end surface **9016**, and a thickness **9018** that is the minimum dimension of the body **9001**.

A plurality of apertures **9002** may extend through the thickness **9018** of the body **9001**, each aperture **9002** defining a perimeter **9020** having at least one orientation flat **9004**. In the embodiments shown in FIGS. **7** and **51**, the plurality of apertures **9002** are similarly configured, having two orientation flats **9004** parallel to each other and two circular portions **9022** connecting the two orientation flats **9004**. The two orientation flats **9004** of each perimeter **9020** of each aperture **9002** may be similarly configured such that all the orientation flats **9004** are parallel to each other. In many embodiments, the plurality of apertures **9002** are identically configured. The thickness **9018** of the plate **900** may define a midplane MP and the plate **9000** may be symmetrical about the midplane MP.

As shown in FIGS. **7**, **49** and **51**, mounting hardware **10000** may be used to hold the tool bits **200**, **5000**, **6000**, **7000** in place. The mounting hardware **10000** may include the orientation plate **9000** and a lynch pin **10002** with a pull ring **10004**. The user simply needs to install the lynch pin **10002** into the cross-hole **314** of the shaft portion **302** of the tool bit **300** to hold the tool bit **300** in place (e.g. see FIG. **4**). Pulling on the pull ring **10004** removes the lynch pin **10002** from the cross-hole **314**, allowing removal of the tool bit **300**.

The relative dimensions of the shaft portion may enable any tool bit discussed herein to mate as desired with the

mounting hardware **1000** in order to attach the tool bit to the adapter board, allowing interchangeability. For example, as shown in FIG. 17, the axial length AL**7002** (measured along the longitudinal axis L) of the shank portion **7002** may range from 40 to 80 mm. The axial length AL**7012** (measured along the longitudinal axis L) of the flats **7012** of the shank portion **7002** may range from 10 to 30 mm. The axial positioning (AD**7012**) of the flats **7012** to the working portion **7004** may range from 30 to 70 mm. The diameter D**7002** of the shaft portion **7002** may range from 20 to 45 mm. The shaft portion of any tool bit discussed herein may be similarly or identically configured as other shaft portions to facilitate the interchangeability of the tool bits with the adapter board.

Various embodiments of a serrated blade assembly using differently configured components to form the serrated configuration as well as a wear member that may be used in such a serrated assembly will now be discussed. For brevity, only specific embodiments of the tool bit shown in FIG. 4, and FIGS. 11 thru 16 will be described in detail. It is to be understood that the embodiments shown of the tool bits of FIGS. 3, 5, 6, 23, 29, 35, and 41, etc. may be used instead in other embodiments of the serrated blade assembly.

A blade assembly (such as a serrated blade assembly) for use with a grading machine is shown in FIG. 55. The blade assembly **11000** may comprise an adapter board **11002** defining an upper adapter board attachment portion **11004**, terminating in an upper adapter board free end **11006**, and a lower tool bit attachment portion **11008**, terminating in a lower adapter board free end **11010**, the adapter board **11002** defining a lateral direction LD and a width W**11002** measured along the lateral direction LD, and vertical direction VD perpendicular to the lateral direction LD, a plurality of tool bits **300**, **600** configured to be attached to the adapter board **11002**, each tool bit **300**, **600** including a working portion **304**, **604** defining a working length L**304**, L**604** measured along the vertical direction VD (parallel to the shaft longitudinal axis) and a working width W**304**, W**604** measured along the lateral direction LD, and a plurality of wear members **11012**, **11012'** configured to be attached to the adapter board **11002**.

Each wear member **11012**, **11012'** may include a wear portion **11014**, **11014'** defining a wear length L**11014**, L**11014'** measured along the vertical direction VD and a wear width W**11014**, W**11014'** measured along the lateral direction LD. The wear length may be less than the working length. In some embodiments, the wear length L**11014**, L**11014'** is at least 20% less than the working length L**304**, L**604** and may be as much as 50% less than the working length L**304**, L**604** or more. The wear portion and the working portion may be differently configured from each other in other ways. For example, the perimeter of the working portion may have more intricate features as compared to the wear portion.

Looking now at FIGS. 56 and 57, the features of the wear member **11012**, **11012'** may be seen more clearly. The wear portion **11014**, **11014'** may include a rectangular configuration. In other embodiments, the wear portion **11014**, **11014'** includes a square configuration. Looking at FIGS. 56 and 57 along with FIG. 55, the wear width W**11014**, W**11014'** may be the same as the working width W**304**, W**604**. This may be useful when the distance from tool bit **300**, **300'** to the wear member **11012**, **11012'** is consistent as one progresses along the lateral direction LD of the blade assembly **11000**. Looking at FIG. 57, the wear member **11012**, **11012'** may

include an insert **11016** (e.g. made from a ceramic material, white iron, wear button) that forms part of the wear portion **11014**, **11014'**.

Focusing now on FIG. 55, the working portion **304**, **604** of the tool bit **300**, **600** includes angled surfaces **606**, **608** or arcuate surfaces **306**, **308** (see FIG. 4 for an example). In some embodiments, the working portion **304** may include both angled surfaces **342** and arcuate surfaces **306**, **308** (see FIG. 4).

Referring back to FIG. 55, once the plurality of tool bits **300**, **600** are attached to the adapter board **11002** and the plurality of wear members **11012**, **11012'** are attached to the adapter board **11002**, the tool bits **300**, **600** and the wear members **11012**, **11012'** may form an alternating pattern along the lateral direction LD switching from tool bit to wear member. In some embodiments, the tool bit **300**, **600** may include an insert **328**, **628** that forms part of the working portion **304**, **604** and the plurality of tool bits **300**, **600** are identically configured to each other. Similarly, the plurality of wear members **11012**, **11012'** may be identically configured to each other. Also, the plurality of tool bits **300**, **600** and the plurality of wear members **11012**, **11012'** may include identical shank portions **302**, **602**, allowing the tool bits **300**, **600** and the wear members **11012**, **11012'** to be attached to the adapter board.

Focusing now on FIGS. 56 and 57, various embodiments of the wear member **11012**, **11012'** may be characterized as follows. The wear member **11012**, **11012'** may comprise a shank portion **11018**, **11018'** defining a longitudinal axis L**11018**, L**11018'** and a perimeter **11020**, **11020'** a pair of parallel flat surfaces **11022**, **11022'** on the perimeter **11020**, **11020'** and a cross-hole **11024**, **11024'** defining a cross-hole axis A**11024**, A**11024'** along which the cross-hole **11024**, **11024'** extends through the flat surfaces **11022**, **11022'** perpendicularly, and a wear portion **11014**, **11014'** extending downwardly axially from the shank portion **11018**, **11018'**.

The wear portion **11014**, **11014'** may include a rectangular configuration and the shank portion **11018**, **11018'** may include a cylindrical configuration.

In other embodiments, the wear portion **11014**, **11014'** includes a polygonal configuration other than a rectangular or square configuration. In some embodiments, the wear portion **11014**, **11014'** may not have a polygonal configuration, etc. (e.g. circular, polynomial, elliptical).

The wear portion **11014**, **11014'** may define a bottom portion **11026** and may include an insert **11016** attached to the bottom portion **11026**.

In embodiments where a polygonal configuration is provided for the wear portion **11014**, **11014'** of the wear member **11012**, the polygonal configuration may include a straight surface **11028**, **11028'** that is parallel to the flat surfaces **11022**, **11022'** of the shank portion **11018**, **11018'**.

A wear member **11012**, **11012'** according to another embodiment of the present disclosure may be described as follows. The wear member **11012**, **11012'** may comprise a shank portion **11018**, **11018'** defining a longitudinal axis L**11018**, L**11018'** and a perimeter **11020**, **11020'**, at least one flat surface **11022**, **11022'** on the perimeter **11020**, **11020'** and a cross-hole **11024**, **11024'** defining a cross-hole axis A**11024**, A**11024'** along which the cross-hole **11024**, **11024'** extends through the at least one flat surface **11022**, **11022'** perpendicularly, and a wear portion **11014**, **11014'** extending downwardly axially from the shank portion **11018**, **11018'**, the wear portion **11014**, **11014'** including a polygonal configuration.

The wear portion **11014**, **11014'** may include a bottom portion **11026** and a plurality of inserts **11016** may be

25

attached to the bottom portion **11026**. The shank portion **11018**, **11018'** may define a shank longitudinal length **11030**, **11030'** and the wear portion **11014**, **11014'** may define a wear portion longitudinal length **L11014**, **L11014'** that is less than the shank longitudinal length **11030**, **11030'**.

FIGS. **58** thru **60** depict a blade assembly and an adapter board with pry points. These pry points may allow tool bits or wear members to be removed from the adapter board after being used.

More specifically, an adapter board **12000** for use with a blade assembly **13000** according to an embodiment of the present disclosure may be described as follows. The adapter board **12000** may comprise a lower tool bit attachment portion **12002**, terminating in a lower adapter board free end **12004**. The lower adapter board free end **12004** may define a bottom surface **12006** defining a plurality of shank receiving bores **12008** and a plurality of pry slots **12010**. Each one of the plurality of pry slots **12010** may be disposed adjacent at least one of the plurality of shank receiving bores **12008**.

In some embodiments, the adapter board **12000** may further comprise an upper adapter board attachment portion **12012**, terminating in an upper adapter board free end **12014**. The upper adapter board attachment portion **12014** may be separate from or unitary with the lower tool bit attachment portion **12002**. The lower tool bit attachment portion **12002** of the adapter board **12000** defines a rear surface **12016** disposed adjacent the bottom surface **12006** and the rear surface **12016** defines a plurality of openings **12018** of the plurality of pry slots **12010**. This may allow a pry bar or other tool to enter the pry slot **12010** between the adapter board **12000** and the tool bit **13002** or wear member (e.g. see **11012**, **11012'** in FIG. **55**).

Looking at FIGS. **59** and **60**, a rear abutment surface **12018** may be provided such that none of the plurality of pry slots **12010** are in communication with the plurality of shank receiving bores **12008**. More particularly, each one of the plurality of pry slots **12010** is spaced away from the adjacent one of the plurality of shank receiving bores **12008** a predetermined distance **12028** ranging from 0 to 25 mm. This may not be the case in other embodiments such as when the pry slot **12010** extends completely through the lower tool bit attachment portion **12002**. The predetermined distance **12028** is the minimum distance **12028** between the pry slot **12010** and the shank receiving bore **12008** excluding blends (e.g. fillets, chamfers) or other transitional geometry.

In some embodiments, each one of the plurality of pry slots **12010** includes a rectangular configuration having a top pry surface **12018**, a rear abutment surface **12020**, a first side guide surface **12022**, and a second side guide surface **12024**. The first and the second guide surfaces **12022**, **12024** may aid in guiding a pry bar or other tool to reach the rear abutment surface **12020** or to otherwise stay within the pry slot **12010**, focusing the leverage of the pry bar or other tool onto the tool bit **13002** or wear member (e.g. see **11012**, **11012'** in FIG. **55**) to force the tool bit or wear member out of the shank receiving bore **12008**.

In still further embodiments, as shown in FIGS. **58** thru **60**, the adapter board **12000** may comprise an upper adapter board attachment portion **12012**, terminating in an upper adapter board free end **12014**, and a lower tool bit attachment portion **12002**, terminating in a lower adapter board free end **12004**. For example, the adapter board may be manufactured as a unitary component. The lower adapter board free end **12004** may define a bottom surface **12006** defining at least one shank receiving bore **12008** and at least one pry slot **12010** disposed adjacent the at least one shank receiving bore **12008**.

26

The shape of the pry slot **12010** may take various configurations. In some embodiments, the lower tool bit attachment portion **12002** of the adapter board **12000** defines a rear surface **12016** disposed adjacent the bottom surface **12006** and the rear surface **12016** defines an opening **12026** of the pry slot **12010**. This may not be the case for other embodiments. In some embodiments, the pry slot **12010** is a blind pocket, meaning that the pry slot **12010** is spaced away from the adjacent one of the plurality of shank receiving bores **12008** a predetermined distance **12028** ranging from 0 to 25 mm.

The pry slot **12010** may include a rectangular configuration having a top pry surface **12018**, a rear abutment surface **12020**, a first side guide surface **12022**, and a second side guide surface **12024**, and the rear abutment surface **12020** is positioned closest to the shank receiving bore **12008**. This may not be the case in other embodiments.

A blade assembly **13000** for use with a grading machine according to another embodiment of the present disclosure having pry points will now be discussed with reference to FIGS. **58** thru **60**. The blade assembly **13000** may comprise an adapter board **12000** defining an upper adapter board attachment portion **12012**, terminating in an upper adapter board free end **12014**, and a lower tool bit attachment portion **12002**, terminating in a lower adapter board free end **12004**. The lower adapter board free end **12004** may define a bottom surface **12006** defining a plurality of shank receiving bores **12008** and a plurality of pry slots **12010**. Each one of the plurality of pry slots **12010** is disposed adjacent at least one of the plurality of shank receiving bores **12008**. A plurality of tool bits **13002** including shank portions **13004** configured to fit within the plurality of shank receiving bores **12008** may be provided. In addition to or in lieu of the plurality of tool bits, a plurality of wear members including shank portions (e.g. see FIGS. **56** and **57**) configured to fit within the plurality of shank receiving bores **12008** may be provided. It is to be understood that any tool bit or wear member discussed herein may be used with a blade assembly having pry points.

The lower tool bit attachment portion **12002** of the adapter board **12000** defines a rear surface **12016** disposed adjacent the bottom surface **12006** and the rear surface **12016** defines a plurality of openings **12026** of the plurality of pry slots **12010**. As best seen in FIG. **60**, none of the plurality of pry slots **12010** are in communication with the plurality of shank receiving bores **12008**. Instead, each one of the plurality of pry slots **12010** is spaced away from the adjacent one of the plurality of shank receiving bores **12008** a predetermined distance **12028** ranging from 0 to 25 mm. Again, this distance is the minimum distance from the rear abutment surface **12020** to the shank receiving bore **12008**, ignoring any transitional geometry.

Various configurations of the pry slot are possible. For the embodiment shown in FIGS. **58** thru **60**, each one of the plurality of pry slots **12010** includes a rectangular configuration having a top pry surface **12018**, a rear abutment surface **12020**, a first side guide surface **12020**, and a second side guide surface **12024**.

Focusing on FIGS. **59** and **60**, the lower tool bit attachment portion **12002** defines a first plurality of blends **12030** between the rear surface **12016** and each one of the plurality of pry slots **12010** and a second plurality of blends **12032** between the bottom surface **12006** and each one of the plurality of pry slots **12010**. Each one of the plurality of pry slots **12010** defines a depth **12034** measured from the rear surface **12016** of the lower tool bit attachment portion **12002** of the adapter board **12000** to the rear

abutment surface **12020** (minimum distance excluding transitional geometry) ranging from 5 mm to 30 mm. Similarly, each one of the plurality of pry slots **12010** defines a height **12036** measured from the bottom surface **12006** of the lower tool bit attachment portion **12002** of the adapter board **12000** to the top pry surface **12018** (minimum distance excluding transitional geometry) ranging from 5 mm to 20 mm. Likewise, each one of the plurality of pry slots **12010** defines a width **12038** measured from the first side guide surface **12022** to the second side guide surface **12024** (minimum distance excluding transitional geometry) ranging from 5 mm to 50 mm. Any of these dimensions may be varied as needed or desired in other embodiments to have values other than those specifically mentioned herein.

As best seen in FIG. **60**, each one of the plurality of shank receiving bores **12008** defines a diameter **12040** and the width **12038** of each one of the plurality of pry slots **12010** is less than the diameter **12040** of the plurality of shank receiving bores **12008**. This may not be the case for other embodiments. Also, the lower tool bit attachment portion **12002** defines at least one blend **12042** between the first side guide surface **12022** and the top pry surface **12018**, at least one blend **12044** between the second side guide surface **12024** and the top pry surface **12018**, and at least one blend **12046** between the rear abutment surface **12020** and the top pry surface **12018**. These features may be omitted in other embodiments or may be differently configured.

As best seen in FIGS. **59** and **60**, each one of the plurality of pry slots **12010** defines a width **12038** measured from the first side guide surface **12022** to the second side guide surface **12024**, and the plurality of tool bits **13002** includes a working portion **13006** or the plurality of wear members includes a wear portion (see FIGS. **55** thru **57**), and the shank portions **13006** of either the plurality of tool bits **13000** or the shank portions of the plurality of wear members are installed into the shank receiving bores **13008**. That is to say, the blade assembly of FIG. **55** may have pry slots like that disclosed in FIGS. **58** thru **60**. It is to be understood that pry slots may be used with any blade assembly, tool bit, and wear member or adapter board discussed herein.

In some embodiments, such as shown in FIGS. **59** and **60**, the width **13008** of the working portion **13006** of each one of the plurality of tool bits **13000** or the width of the wear portion of each one of the plurality of wear members (as understood with reference to FIGS. **55** thru **57**) is greater than the width **12038** of each one of the plurality of pry slots **12010**. This may not be the case for other embodiments.

FIGS. **61** thru **65** disclose a blade assembly **14000** according to an embodiment of the present disclosure may include a bushing and a tool bit with spline features. More particularly, a blade assembly **14000** may comprise an adapter board **14002** including a lower tool bit attachment portion **14004**, terminating in a lower adapter board free end **14006**. The lower adapter board free end **14006** defining a bottom surface **14008** defining a plurality of shank receiving bores **14010**. The blade assembly **14000** may also include a plurality of splined bushings **14012**. Each one of the plurality of splined bushings **14012** may be disposed in a corresponding one of the plurality of shank receiving bores **14010**.

Each one of the plurality of splined bushings **14012** may be retained in each one of the plurality of shank receiving bores **14010**, such as being press fit into each corresponding one of the plurality of shank receiving bores **14010**, welded, etc.

As best seen looking at FIGS. **63** and **64**, each one of the plurality of splined bushings **14012** may include a cylindrical

cal annular configuration defining a bushing cylindrical axis **14014**, a bushing radial direction **14016**, a bushing circumferential direction **14018**, and a central hole **14020**. The central hole **14020** may define an inside circumferential surface **14022** including a plurality of axially extending splines **14024** forming a circumferential array about the bushing cylindrical axis **14014**.

In some embodiments, the central thru-hole **14020** may be a blind hole or as shown in FIGS. **63** and **64**, the central hole **14020** may be a thru-hole **14026** extending completely through the splined bushing **14012**. When the hole is blind, a central or interior snap ring for the tool bit or wear member may be provided for retaining a tool bit or a wear member to the adapter board. On the other hand, when the hole is a thru-hole, an external snap ring may be provided for retaining a tool bit or a wear member to the adapter board as will be shown and described herein momentarily.

Referring to FIGS. **61**, **62**, **64** and **65**, the blade assembly **14000** may further comprise a plurality of splined tool bits **14028** or wear members including those shown in FIGS. **61**, **64** and **65** or otherwise shown or described herein. Each one of the plurality of splined tool bits **14028** may include a splined shank portion **14030** configured to mate with a corresponding one of the plurality of splined bushings **14012**.

The splined shank portion **14030** may include a splined cylindrical configuration defining a circumferential direction **14032** and a longitudinal axis **14034**. The splined shank portion **14030** may further include a circumferential surface **14036** further comprising a series of longitudinally extending splines **14038**.

In some embodiments, the splined shank portion **14030** may include a free end **14040** and the series of longitudinally extending splines **14038** may extend to the free end **14040**. This may not be the case in other embodiments.

Focusing on FIG. **65**, the splined shank portion **14030** may define a circumferential snap ring slot **14042** disposed proximate the free end **14040** of the splined shank portion **14030**. More specifically, the lower tool bit attachment portion **14004** of the adapter board **14002** includes a top surface **14044** of the lower tool bit attachment portion **14004** and each of the plurality of shank receiving bores **14010** may extend through the top surface **14044** with each of the plurality of splined bushings **14012** being flush to recessed to the top surface **14044**. This may not be the case for other embodiments.

Looking at FIG. **62**, the series of longitudinally extending splines **14038** may include 18 identically configured shank portion splines **14046**. Likewise, in FIG. **63** it can be seen that the plurality of axially extending splines **14024** may include 18 identically configured bushing splines **14048**. In other embodiments, the splines may be differently configured from each other and/or a different number of splines may be provided that are spaced the same distance or a different distance from each other, etc.

Looking at FIG. **62**, a splined tool bit **15000** may comprise a working portion **15002**, and a splined shank portion **15004** extending from the working portion **15002** to a splined shank portion free end **15006**. The splined shank portion **15004** may include a cylindrical configuration defining a circumferential direction **14032**, a radial direction **15008**, and a shank portion cylindrical axis **15010**. The splined shank portion **15004** may further include one or a plurality of shank splines **15012** wherein each one of the plurality of shank splines **15012** may extend axially and radially from the splined shank portion **15004** (e.g. in a

radially outer direction) and may be spaced circumferentially away from an adjacent one of the plurality of shank splines **15012**.

In some embodiments, each of the plurality of shank splines **15012** extends axially to the splined shank portion free end **15006**. Each of the plurality of shank splines **15012** extends axially to the working portion **15002**. As alluded to earlier, the splined shank portion **15004** may define a circumferential snap ring groove **15014** disposed axially adjacent to the splined shank portion free end **15006**.

Each one of the plurality of shank splines **15012** may be spaced circumferentially away from an adjacent one of the plurality of shank splines **15012** by an angle **15016** having a value of 20 degrees. This angle **15016** may be varied between each pair of splines in other embodiments and/or may have other values in other embodiments.

Turning now to FIG. **63**, a splined bushing **16000** may comprise an annular cylindrical body **16002** defining a longitudinal axis **16004**, a radial direction **16006**, and a circumferential direction **16008**. The annular cylindrical body **16002** may include an inner cylindrical surface **16010** defining a thru-hole **16012** that extends axially through the annular cylindrical body **16002**. The body **16002** may further include a plurality of bushing splines **16014** wherein each one of the plurality of bushing splines **16014** extends axially and radially from the inner cylindrical surface **16010** and is spaced circumferentially away from an adjacent one of the plurality of bushing splines **16014**. Other configurations for the splines such as helical are possible in other embodiments.

More particularly, each one of the plurality of bushing splines **16014** may be spaced circumferentially away from the adjacent one of the plurality of bushing splines **16014** by a predetermined angle **16016**. The predetermined angle **16016** may have a value of 20 degrees. Other values for the predetermined angle **16016** are possible in other embodiments, etc. Also, each one of the plurality of bushing splines **16014** may extend axially the entire extent of the splined bushing **16000**. This may not be the case for other embodiments.

Referring now to FIGS. **66** and **67**, another embodiment of a blade assembly **14000'** that is similarly configured to that of FIGS. **61** thru **65** except for the following differences may be seen.

As shown in FIGS. **66** and **67**, the blade assembly **14000'**, instead of a splined bushing, a bushing **14012'** lacking splines may be employed. Moreover, each of the shank receiving bores **14010'** may define a longitudinal axis **14014'**, a radial direction **14016'** and may include a counterbore portion **14050** defining a shelf surface **14052**. Each of the plurality of bushings **14012'** may be disposed in one of the counterbore portions **14050** such that the bushings **14012'** contact or nearly contact the shelf surface **14052**. The bushings **14012'** may be pressed into the shank receiving bores **14010'** or may be welded to the adapter board **14002'**, etc. Each of the counterbore portions **14050** may define a counterbore diameter **D14050**, while each of the shank receiving bores **14040'** may further include a reduced diameter portion **14054** defining a reduced diameter **D14054** that is less than the counterbore diameter **D14050**. The reduced diameter portion **14054** may also extend axially from the counterbore portion **14050** and include a plurality of axially extending splines **14024'**. Each of the bushings **14012'** may define an inner diameter **ID14012'** and the reduced diameter **D14054** may be greater than the inner diameter **ID14012'** of the bushing **14012'**.

For this particular embodiment, the counterbore portion **14050** extends from the bottom surface **14008'** of the lower tool bit attachment portion **14004'** of the adapter board **14002'**. In other embodiments, the counterbore portion **14050** may extend from the top surface **14044'** of the lower tool bit attachment portion **14004'** of the adapter board **14002'**. Again, for this embodiment, the reduced diameter portion **14054** is a thru-hole extending from the top surface **14044'** to the counterbore portion **14050**. In other embodiments, the reduced diameter portion may extend from the bottom surface, etc.

Focusing now on the splined tool bit **15000'**, the series of longitudinally extending splines **14038'** are flush with the circumferential surface **14036'** of the splined shank portion **14030'**, extending radially inwardly from the circumferential surface **14036'** and axially to the free end **14040'** while stopping short of the working portion **15002'**.

Assembly of the embodiments shown in FIGS. **66** and **67** may be performed in the following manner. The bushings **14012'** are attached to the adapter board **14002'** after being inserted in the counterbore portion **14050** of the shank receiving bores **14010'**. Then, the splined shank portions **14030'** are inserted into the bushings **14012'** and the shank receiving bores **14010'** and rotated such that the splines **14038'** of the shank portions are aligned appropriately relative to the corresponding splines **14024'** of the adapter board. Insertion continues as the circumferential surface **14036'** of the splined shank portion makes a slip fit with the inner diameter **ID14012** of the bushing **14012'** and the splines **14038'** of the splined shank portion **14030** make a clearance fit radially with the reduced diameter portion **14054** of the shank received bore **14010'**. Then, a snap ring **14056** may be used to hold the tool bit **15000'** in place.

More particularly, the snap ring **14056** is sandwiched between the ledge **14058** of the splined shank portion **14030'** of the tool bit **15000'** and the lower tool bit attachment portion of the adapter board. At least one ledge **14058** extends radially from one of the plurality of longitudinally extending splines **14038'** that is configured to contact a snap ring **14056**. A plurality of ledges **14058** may be provided that each extends from each one of the longitudinally extending splines **14038'**.

For the embodiment shown in FIGS. **66** and **67**, at least one of the splines **14038"** of the splined shank portion **14030'** is facing toward the front or the rear of the adapter board **14002'**, establishing a zero degree orientation of the tool bit **15000'** (such as shown in FIG. **7**). Once installed, the shank portion of the tool bit conveys any loads to the bushing while the splines of the adapter board contact the splines of the tool bit to help maintain the desired orientation.

Again, it should be noted that any of the dimensions, angles, surface areas and/or configurations of various features may be varied as desired or needed including those not specifically mentioned herein. Although not specifically discussed, blends such as fillets are shown in FIGS. **3** thru **67** to connect the various surfaces. These may be omitted in other embodiments and it is to be understood that their presence may be ignored sometimes when reading the present specification.

INDUSTRIAL APPLICABILITY

In practice, a machine, a blade assembly, a tool bit, a bushing, a wear member, and/or an adapter board may be manufactured, bought, or sold to retrofit a machine, a tool bit, a wear member or blade assembly in the field in an

aftermarket context, or alternatively, may be manufactured, bought, sold or otherwise obtained in an OEM (original equipment manufacturer) context.

Referring to FIGS. 61 thru 67, with a bushing within the adapter board, if a bit (or a wear member) were to get seized within the bit shank hole, then both the bit and the bushing can be pressed out and a new bushing can be pressed back in. The bushing may also help with the adapter board's end of life. Instead of scrapping the adapter board, bushings can be replaced to rebuild the adapter board. The bit or wear member can held in place in any suitable manner including using an internal snap ring, an external snap ring, or a lynch pin attached at the top of the shank of the wear member or tool bit. The bushing may be made of any suitable material including steel, etc.

The splined features may be added to any tool bit or wear member discussed or shown herein. Using the splined features, the tool bit or wear member may be angled at a desired angle instead of using an orientation plate or in addition to an orientation plate. The tool bits or wear members may be angled at the same or different angles relative to each other as needed or desired.

It will be appreciated that the foregoing description provides examples of the disclosed assembly and technique. However, it is contemplated that other implementations of the disclosure may differ in detail from the foregoing examples. All references to the disclosure or examples thereof are intended to reference the particular example being discussed at that point and are not intended to imply any limitation as to the scope of the disclosure more generally. All language of distinction and disparagement with respect to certain features is intended to indicate a lack of preference for those features, but not to exclude such from the scope of the disclosure entirely unless otherwise indicated.

Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein, and each separate value is incorporated into the specification as if it were individually recited herein.

It will be apparent to those skilled in the art that various modifications and variations can be made to the embodiments of the apparatus and methods of assembly as discussed herein without departing from the scope or spirit of the invention(s). Other embodiments of this disclosure will be apparent to those skilled in the art from consideration of the specification and practice of the various embodiments disclosed herein. For example, some of the equipment may be constructed and function differently than what has been described herein and certain steps of any method may be omitted, performed in an order that is different than what has been specifically mentioned or in some cases performed simultaneously or in sub-steps. Furthermore, variations or modifications to certain aspects or features of various embodiments may be made to create further embodiments and features and aspects of various embodiments may be added to or substituted for other features or aspects of other embodiments in order to provide still further embodiments.

Accordingly, this disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

What is claimed is:

1. A blade assembly comprising:

an adapter board including a lower tool bit attachment portion, terminating in a lower adapter board free end, the lower adapter board free end defining a bottom surface defining a plurality of shank receiving bores; and

a plurality of bushings,

wherein each one of the plurality of bushings is disposed in a corresponding one of the plurality of shank receiving bores,

wherein the plurality of shank receiving bores includes counterbore portions, and

wherein each of the plurality of bushings is disposed in one of the counterbore portions,

each of the counterbore portions defining a counterbore diameter,

each of the plurality of shank receiving bores further including a reduced diameter portion defining a reduced diameter that is less than the counterbore diameter, and

the reduced diameter portion extending from the counterbore portion and including a plurality of axially extending splines.

2. The blade assembly of claim 1,

wherein each one of the plurality of bushings includes a cylindrical annular configuration defining a bushing cylindrical axis, a bushing radial direction, a bushing circumferential direction, and a central hole defining an inside circumferential surface including another plurality of axially extending splines forming a circumferential array about the bushing cylindrical axis, and

wherein each one of the plurality of bushings is press fit into each corresponding one of the plurality of shank receiving bores.

3. The blade assembly of claim 1, wherein the reduced diameter portion is a thru-hole and includes a series of axially extending splines,

the plurality of axially extending splines extending radially from the reduced diameter portion.

4. The blade assembly of claim 1, further comprising:

a plurality of splined tool bits,

wherein each one of the plurality of splined tool bits includes a working portion and a splined shank portion configured to mate with a corresponding one of the plurality of bushings.

5. The blade assembly of claim 4, wherein the splined shank portion includes a circumferential surface comprising a series of longitudinally extending splines that are flush with the circumferential surface.

6. The blade assembly of claim 5,

wherein the splined shank portion includes a free end, and wherein the series of longitudinally extending splines extend to the free end and stop short of the working portion.

7. The blade assembly of claim 6, wherein the splined shank portion includes at least one ledge extending from one of the series of longitudinally extending splines.

8. The blade assembly of claim 6,

wherein the series of longitudinally extending splines includes 18 identically configured shank portion splines, and

wherein the plurality of axially extending splines includes 18 identically configured bushing splines.

33

9. The blade assembly of claim 1,
 wherein each of the plurality of bushings define an inner
 diameter, and
 wherein the reduced diameter is greater than the inner
 diameter.
10. A blade assembly comprising:
 a plurality of shank receiving bores;
 a plurality of bushings,
 wherein a bushing, of the plurality of bushings, is
 pressed into a shank receiving bore of the plurality of
 shank receiving bores,
 wherein the plurality of shank receiving bores includes
 counterbore portions,
 wherein each of the plurality of bushings is disposed in
 one of the counterbore portions,
 each of the counterbore portions defining a counter-
 bore diameter,
 each of the plurality of shank receiving further
 including a reduced diameter portion defining a
 reduced diameter that is less than the counterbore
 diameter, and
 the reduced diameter portion extending from the
 counterbore portion and
 including a plurality of axially extending splines; and
 a plurality of tool bits,
 wherein a tool bit, of the plurality of tool bits, is
 configured to mate with the bushing.
11. The blade assembly of claim 10, wherein the tool bit
 includes:
 a working portion, and
 a splined shank portion configured to mate with the
 bushing.
12. The blade assembly of claim 11,
 wherein the splined shank portion includes a series of
 longitudinally extending splines and a free end, and

34

- wherein the series of longitudinally extending splines
 extend to the free end and stops short of the working
 portion.
13. The blade assembly of claim 10, wherein the bushing
 includes a cylindrical annular configuration defining a bush-
 ing cylindrical axis, a bushing radial direction, a bushing
 circumferential direction, and a central hole defining an
 inside circumferential surface including another plurality of
 axially extending splines forming a circumferential array
 about the bushing cylindrical axis.
14. The blade assembly of claim 10, wherein the reduced
 diameter portion is a thru-hole and includes a series of
 axially extending splines.
15. The blade assembly of claim 14, wherein the plurality
 of axially extending splines extend radially from the reduced
 diameter portion.
16. The blade assembly of claim 10, wherein the tool bit
 includes a splined shank portion configured to mate with the
 bushing.
17. The blade assembly of claim 16, wherein the splined
 shank portion includes a circumferential surface comprising
 a series of longitudinally extending splines that are flush
 with the circumferential surface.
18. The blade assembly of claim 16, wherein the splined
 shank portion includes:
 a series of longitudinally extending splines, and
 at least one ledge extending from one of the series of
 longitudinally extending splines.
19. The blade assembly of claim 10,
 wherein each of the plurality of bushings define an inner
 diameter, and
 wherein the reduced diameter is greater than the inner
 diameter.
20. The blade assembly of claim 10, wherein the tool bit
 includes 18 shank portion splines.

* * * * *