

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau

(43) International Publication Date

28 March 2019 (28.03.2019)



(10) International Publication Number

WO 2019/058225 A1

(51) International Patent Classification:

A24F 47/00 (2006.01) *A61M 11/04* (2006.01)
A61M 15/06 (2006.01) *A61M 15/00* (2006.01)
A61M 16/00 (2006.01)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:

PCT/IB2018/057015

(22) International Filing Date:

13 September 2018 (13.09.2018)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15/708,898 19 September 2017 (19.09.2017) US


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(71) Applicant: **RAI STRATEGIC HOLDINGS, INC.**
 [US/US]; 401 North Main Street, Winston-Salem, North Carolina 27101 (US).

(72) Inventor: **SUR, Rajesh**; 1774 Queen Catherine Lane, Winston-Salem, North Carolina 27106 (US).

(74) Agent: **LI, Zheng** et al.; Womble Bond Dickinson (US) LLP, Attn: Patent Docketing, P.O. Box 7037, Atlanta, Georgia 30357-0037 (US).

(54) Title: DIFFERENTIAL PRESSURE SENSOR FOR AN AEROSOL DELIVERY DEVICE



Declarations under Rule 4.17:

- *as to the identity of the inventor (Rule 4.17(i))*
- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

Published:

- *with international search report (Art. 21(3))*
- *in black and white; the international application as filed contained color or greyscale and is available for download from PATENTSCOPE*

DIFFERENTIAL PRESSURE SENSOR FOR AN AEROSOL DELIVERY DEVICE

TECHNOLOGICAL FIELD

[0001] The present disclosure relates to aerosol delivery devices such as smoking articles, and more particularly to aerosol delivery devices that may utilize electrically generated heat for the production of aerosol (e.g., smoking articles commonly referred to as electronic cigarettes). The smoking articles may be configured to heat an aerosol precursor, which may incorporate materials that may be made or derived from, or otherwise incorporate tobacco, the precursor being capable of forming an inhalable substance for human consumption.

10

BACKGROUND

[0002] Many devices have been proposed through the years as improvements upon, or alternatives to, smoking products that require combusting tobacco for use. Many of those devices purportedly have been designed to provide the sensations associated with cigarette, cigar, or pipe smoking, but without delivering considerable quantities of incomplete combustion and pyrolysis products that result from the burning of tobacco. To this end, there have been proposed numerous alternative smoking products, flavor generators, and medicinal inhalers that utilize electrical energy to vaporize or heat a volatile material, or attempt to provide the sensations of cigarette, cigar, or pipe smoking without burning tobacco to a significant degree. See, for example, the various alternative smoking articles, aerosol delivery devices and heat generating sources set forth in the background art described in U.S. Pat. No. 8,881,737 to Collett et al., U.S. Pat. App. Pub. No. 2013/0255702 to Griffith Jr. et al., U.S. Pat. App. Pub. No. 2014/0000638 to Sebastian et al., U.S. Pat. App. Pub. No. 2014/0096781 to Sears et al., U.S. Pat. App. Pub. No. 2014/0096782 to Ampolini et al., U.S. Pat. App. Pub. No. 2015/0059780 to Davis et al., and U.S. Pat. App. Ser. No. 15/222,615 to Watson et al., filed July 28, 2016, all of which are incorporated herein by reference. See also, for example, the various implementations of products and heating configurations described in the background sections of U.S. Pat. Nos. 5,388,594 to Counts et al. and 8,079,371 to Robinson et al., which are incorporated by reference.

[0003] However, it may be desirable to provide aerosol delivery devices with improved electronics such as may extend usability of the devices.

BRIEF SUMMARY

5 **[0004]** The present disclosure relates to aerosol delivery devices, methods of forming such devices, and elements of such devices. The present disclosure includes, without limitation, the following example implementations.

10 **[0005] Example Implementation 1:** An aerosol delivery device comprising at least one housing enclosing a reservoir configured to retain an aerosol precursor composition; a heating element; a sensor configured to produce measurements of differential pressure between an ambient atmospheric pressure and a pressure caused by airflow through at least a portion of the aerosol delivery device, the sensor being configured to convert the measurements of differential pressure to corresponding electrical signals; and a microprocessor coupled to the heating element and the sensor, 15 the microprocessor being configured to receive the corresponding electrical signals and operate in an active mode only in an instance in which the differential pressure is at least a threshold differential pressure, the microprocessor in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition.

20 **[0006] Example Implementation 2:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor is a microelectromechanical systems-based (MEMS-based) sensor.

25 **[0007] Example Implementation 3:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor is a multidirectional electromechanical pressure sensor configured to produce measurements of differential pressure based on pressure on the sensor in different directions.

30 **[0008] Example Implementation 4:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor and the microprocessor are potted in a waterproof material to thereby make the sensor and the microprocessor waterproof or resistant to water, aerosol precursor composition or vaporize components of the aerosol precursor composition.

[0009] **Example Implementation 5:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the microprocessor is responsive to electrical signals having only at a predetermined frequency of the corresponding electrical signals from the sensor to prevent electrical signals having other frequencies from devices external to the aerosol delivery device from causing the microprocessor to operate in the active mode.

[0010] **Example Implementation 6:** The aerosol delivery device of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor is operable in a frequency mode selectable from a plurality of frequency modes, and the microprocessor is configured to select and thereby control the frequency mode of the sensor, and wherein the plurality of frequency modes includes a first frequency mode and a second frequency mode, the first frequency mode being at a higher frequency with lesser power consumption by the sensor and lower resolution of the measurements relative to the second frequency mode at a lower frequency with greater power consumption by the sensor and higher resolution of the measurements.

[0011] **Example Implementation 7:** A control body coupled or coupleable with a cartridge to form an aerosol delivery device, the cartridge including a reservoir configured to retain an aerosol precursor composition, and equipped with a heating element controllable to activate and vaporize components of the aerosol precursor composition, the control body comprising a housing; and within the housing, a sensor configured to produce measurements of differential pressure between an ambient atmospheric pressure and a pressure caused by airflow through at least a portion of the control body, the sensor being configured to convert the measurements of differential pressure to corresponding electrical signals; and a microprocessor coupled to the heating element and the sensor when the control body is coupled with the cartridge, the microprocessor being configured to receive the corresponding electrical signals and operate in an active mode only in an instance in which the differential pressure is at least a threshold differential pressure, the microprocessor in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition.

[0012] **Example Implementation 8:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor is a microelectromechanical systems-based (MEMS-based) sensor.

5 [0013] **Example Implementation 9:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor is a multidirectional electromechanical pressure sensor configured to produce measurements of differential pressure based on pressure on the sensor in different directions.

10 [0014] **Example Implementation 10:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor and the microprocessor are potted in a waterproof material to thereby make the sensor and the microprocessor waterproof or resistant to water, aerosol precursor composition or vaporize components of the aerosol precursor composition.

15 [0015] **Example Implementation 11:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the microprocessor is responsive to electrical signals having only at a predetermined frequency of the corresponding electrical signals from the sensor to prevent electrical signals having other frequencies from devices external 20 to the control body from causing the microprocessor to operate in the active mode.

25 [0016] **Example Implementation 12:** The control body of any preceding example implementation, or any combination of any preceding example implementations, wherein the sensor is operable in a frequency mode selectable from a plurality of frequency modes, and the microprocessor is configured to select and thereby control the frequency mode of the sensor, and wherein the plurality of frequency modes includes a first frequency mode and a second frequency mode, the first frequency mode being at a higher frequency with lesser power consumption by the sensor and lower resolution of the measurements relative to the second frequency mode at a lower frequency with greater power consumption by the sensor and higher 30 resolution of the measurements.

[0017] These and other features, aspects, and advantages of the present disclosure will be apparent from a reading of the following detailed description together with the accompanying drawings, which are briefly described below. The present disclosure includes any combination of two, three, four or more features or elements set forth in

this disclosure, regardless of whether such features or elements are expressly combined or otherwise recited in a specific example implementation described herein. This disclosure is intended to be read holistically such that any separable features or elements of the disclosure, in any of its aspects and example implementations, should 5 be viewed as combinable, unless the context of the disclosure clearly dictates otherwise.

[0018] It will therefore be appreciated that this Brief Summary is provided merely for purposes of summarizing some example implementations so as to provide a basic understanding of some aspects of the disclosure. Accordingly, it will be appreciated 10 that the above described example implementations are merely examples and should not be construed to narrow the scope or spirit of the disclosure in any way. Other example implementations, aspects and advantages will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of some described example 15 implementations.

BRIEF DESCRIPTION OF THE DRAWING(S)

[0019] Having thus described the disclosure in the foregoing general terms, reference will now be made to the accompanying drawings, which are not necessarily 20 drawn to scale, and wherein:

[0020] FIG. 1 illustrates a side view of an aerosol delivery device including a cartridge coupled to a control body, according to an example implementation of the present disclosure; and

[0021] FIG. 2 is a partially cut-away view of the aerosol delivery device according 25 to various example implementations.

DETAILED DESCRIPTION

[0022] The present disclosure will now be described more fully hereinafter with reference to example implementations thereof. These example implementations are 30 described so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Indeed, the disclosure may be embodied in many different forms and should not be construed as limited to the implementations set forth herein; rather, these implementations are provided so that this disclosure will satisfy applicable legal requirements. As used in the specification

and the appended claims, the singular forms “a,” “an,” “the” and the like include plural referents unless the context clearly dictates otherwise.

[0023] As described hereinafter, example implementations of the present disclosure relate to aerosol delivery devices. Aerosol delivery devices according to the present disclosure use electrical energy to heat a material (preferably without combusting the material to any significant degree) to form an inhalable substance; and components of such systems have the form of articles most preferably are sufficiently compact to be considered hand-held devices. That is, use of components of preferred aerosol delivery devices does not result in the production of smoke in the sense that aerosol results principally from by-products of combustion or pyrolysis of tobacco, but rather, use of those preferred systems results in the production of vapors resulting from volatilization or vaporization of certain components incorporated therein. In some example implementations, components of aerosol delivery devices may be characterized as electronic cigarettes, and those electronic cigarettes most preferably incorporate tobacco and/or components derived from tobacco, and hence deliver tobacco derived components in aerosol form.

[0024] Aerosol generating pieces of certain preferred aerosol delivery devices may provide many of the sensations (e.g., inhalation and exhalation rituals, types of tastes or flavors, organoleptic effects, physical feel, use rituals, visual cues such as those provided by visible aerosol, and the like) of smoking a cigarette, cigar or pipe that is employed by lighting and burning tobacco (and hence inhaling tobacco smoke), without any substantial degree of combustion of any component thereof. For example, the user of an aerosol generating piece of the present disclosure can hold and use that piece much like a smoker employs a traditional type of smoking article, draw on one end of that piece for inhalation of aerosol produced by that piece, take or draw puffs at selected intervals of time, and the like.

[0025] While the systems are generally described herein in terms of implementations associated with aerosol delivery devices such as so-called “e-cigarettes,” it should be understood that the mechanisms, components, features, and methods may be embodied in many different forms and associated with a variety of articles. For example, the description provided herein may be employed in conjunction with implementations of traditional smoking articles (e.g., cigarettes, cigars, pipes, etc.), heat-not-burn cigarettes, and related packaging for any of the products disclosed herein. Accordingly, it should be understood that the description

of the mechanisms, components, features, and methods disclosed herein are discussed in terms of implementations relating to aerosol delivery devices by way of example only, and may be embodied and used in various other products and methods.

[0026] Aerosol delivery devices of the present disclosure also can be

5 characterized as being vapor-producing articles or medicament delivery articles.

Thus, such articles or devices can be adapted so as to provide one or more substances (e.g., flavors and/or pharmaceutical active ingredients) in an inhalable form or state.

For example, inhalable substances can be substantially in the form of a vapor (i.e., a substance that is in the gas phase at a temperature lower than its critical point).

10 Alternatively, inhalable substances can be in the form of an aerosol (i.e., a suspension of fine solid particles or liquid droplets in a gas). For purposes of simplicity, the term “aerosol” as used herein is meant to include vapors, gases and aerosols of a form or type suitable for human inhalation, whether or not visible, and whether or not of a form that might be considered to be smoke-like.

15 **[0027]** In use, aerosol delivery devices of the present disclosure may be subjected to many of the physical actions employed by an individual in using a traditional type of smoking article (e.g., a cigarette, cigar or pipe that is employed by lighting and inhaling tobacco). For example, the user of an aerosol delivery device of the present disclosure can hold that article much like a traditional type of smoking article, draw 20 on one end of that article for inhalation of aerosol produced by that article, take puffs at selected intervals of time, etc.

[0028] Aerosol delivery devices of the present disclosure generally include a number of components provided within an outer body or shell, which may be referred to as a housing. The overall design of the outer body or shell can vary, and the format

25 or configuration of the outer body that can define the overall size and shape of the aerosol delivery device can vary. Typically, an elongated body resembling the shape of a cigarette or cigar can be a formed from a single, unitary housing or the elongated housing can be formed of two or more separable bodies. For example, an aerosol delivery device can comprise an elongated shell or body that can be substantially tubular in shape and, as such, resemble the shape of a conventional cigarette or cigar.

30 In one example, all of the components of the aerosol delivery device are contained within one housing. Alternatively, an aerosol delivery device can comprise two or more housings that are joined and are separable. For example, an aerosol delivery device can possess at one end a control body comprising a housing containing one or

more reusable components (e.g., an accumulator such as a rechargeable battery and/or rechargeable supercapacitor, and various electronics for controlling the operation of that article), and at the other end and removably coupleable thereto, an outer body or shell containing a disposable portion (e.g., a disposable flavor-containing cartridge).

5 More specific formats, configurations and arrangements of components within the single housing type of unit or within a multi-piece separable housing type of unit will be evident in light of the further disclosure provided herein. Additionally, various aerosol delivery device designs and component arrangements can be appreciated upon consideration of the commercially available electronic aerosol delivery devices.

10 **[0029]** Aerosol delivery devices of the present disclosure most preferably comprise some combination of a power source (i.e., an electrical power source), at least one control component (e.g., means for actuating, controlling, regulating and ceasing power for heat generation, such as by controlling electrical current flow the power source to other components of the article – e.g., a microprocessor, individually or as part of a microcontroller), a heater or heat generation member (e.g., an electrical resistance heating element or other component) or vibrating piezoelectric mesh, which alone or in combination with one or more further elements may be commonly referred to as an “atomizer”, an aerosol precursor composition (e.g., commonly a liquid capable of yielding an aerosol upon application of sufficient heat, such as ingredients 15 commonly referred to as “smoke juice,” “e-liquid” and “e-juice”), and a mouthend region or tip for allowing draw upon the aerosol delivery device for aerosol inhalation (e.g., a defined airflow path through the article such that aerosol generated can be withdrawn therefrom upon draw).

[0030] Alignment of the components within the aerosol delivery device of the 25 present disclosure can vary. In specific implementations, the aerosol precursor composition can be located near an end of the aerosol delivery device which may be configured to be positioned proximal to the mouth of a user so as to maximize aerosol delivery to the user. Other configurations, however, are not excluded. Generally, the heating element can be positioned sufficiently near the aerosol precursor composition 30 so that heat from the heating element can volatilize the aerosol precursor (as well as one or more flavorants, medicaments, or the like that may likewise be provided for delivery to a user) and form an aerosol for delivery to the user. When the heating element heats the aerosol precursor composition, an aerosol is formed, released, or generated in a physical form suitable for inhalation by a consumer. It should be noted

that the foregoing terms are meant to be interchangeable such that reference to release, releasing, releases, or released includes form or generate, forming or generating, forms or generates, and formed or generated. Specifically, an inhalable substance is released in the form of a vapor or aerosol or mixture thereof, wherein 5 such terms are also interchangeably used herein except where otherwise specified.

[0031] As noted above, the aerosol delivery device may incorporate a battery or other electrical power source to provide current flow sufficient to provide various functionalities to the aerosol delivery device, such as powering of a heater, powering of control systems, powering of indicators, and the like. The power source can take 10 on various implementations. Preferably, the power source is able to deliver sufficient power to rapidly heat the heating element to provide for aerosol formation and power the aerosol delivery device through use for a desired duration of time. The power source preferably is sized to fit conveniently within the aerosol delivery device so that the aerosol delivery device can be easily handled. Additionally, a preferred power 15 source is of a sufficiently light weight to not detract from a desirable smoking experience.

[0032] More specific formats, configurations and arrangements of components within the aerosol delivery devices of the present disclosure will be evident in light of the further disclosure provided hereinafter. Additionally, the selection and 20 arrangement of various aerosol delivery device components can be appreciated upon consideration of commercially-available electronic aerosol delivery devices. Further information regarding formats, configurations and arrangements of components within the aerosol delivery devices of the present disclosure, as well as commercially-available electronic aerosol delivery devices, may be found in U.S. Pat. App. Ser. No. 25 15/291,771 to Sur et al., filed October 12, 2016, which is incorporated herein by reference.

[0033] FIG. 1 illustrates a side view of an aerosol delivery device **100** including a control body **102** and a cartridge **104**, according to various example implementations of the present disclosure. In particular, FIG. 1 illustrates the control body and the 30 cartridge coupled to one another. The control body and the cartridge may be detachably aligned in a functioning relationship. Various mechanisms may connect the cartridge to the control body to result in a threaded engagement, a press-fit engagement, an interference fit, a magnetic engagement or the like. The aerosol delivery device may be substantially rod-like, substantially tubular shaped, or

substantially cylindrically shaped in some example implementations when the cartridge and the control body are in an assembled configuration. The aerosol delivery device may also be substantially rectangular, rhomboidal or triangular in cross-section, multifaceted shapes, or the like, some of which may lend itself to greater compatibility with a substantially flat or thin-film power source, such as a power source including a flat battery.

5 [0034] The control body **102** and cartridge **104** may include separate, respective housings or outer bodies, which may be formed of any of a number of different materials. The housing may be formed of any suitable, structurally-sound material. 10 In some examples, the housing may be formed of a metal or alloy, such as stainless steel, aluminum or the like. Other suitable materials include various plastics (e.g., polycarbonate), metal-plating over plastic, ceramics and the like.

15 [0035] In some example implementations, one or both of the control body **102** or the cartridge **104** of the aerosol delivery device **100** may be referred to as being disposable or as being reusable. For example, the control body may have a replaceable battery, rechargeable battery (e.g., rechargeable thin-film solid state battery) or rechargeable supercapacitor, or some combination thereof. Thus, the control body may be combined with any type of recharging technology, including connection to a typical wall outlet, connection to a car charger (i.e., a cigarette lighter receptacle), connection to a computer, such as through a universal serial bus (USB) cable or connector, connection to a photovoltaic cell (sometimes referred to as a solar cell) or solar panel of solar cells, wireless connection to a Radio Frequency (RF), wireless connection to induction-based charging pads, or connection to a RF-to-DC converter. Further, in some example implementations, the cartridge may comprise a 20 single-use cartridge, as disclosed in U.S. Pat. No. 8,910,639 to Chang et al., which is incorporated herein by reference.

25 [0036] FIG. 2 more particularly illustrates the aerosol delivery device **100**, in accordance with some example implementations. As seen in the cut-away view illustrated therein, again, the aerosol delivery device can comprise a control body **102** and a cartridge **104** each of which include a number of respective components. The 30 components illustrated in FIG. 2 are representative of the components that may be present in a control body and cartridge and are not intended to limit the scope of components that are encompassed by the present disclosure. As shown, for example, the control body can be formed of a control body shell **206** that can include a control

component **208** (e.g., a microprocessor, individually or as part of a microcontroller), a flow sensor **210**, a power source **212** and one or more light-emitting diodes (LEDs) **214**, quantum dot enabled LEDs or the like, and such components can be variably aligned. The power source may include, for example, a battery (single-use or 5 rechargeable), rechargeable supercapacitor, rechargeable solid-state battery (SSB), rechargeable lithium-ion battery (LiB) or the like, or some combination thereof. Some examples of a suitable power source are provided in U.S. Pat. App. Ser. No. 14/918,926 to Sur et al., filed October 21, 2015, which is incorporated herein by reference. Other examples of a suitable power source are provided in U.S. Pat. App. 10 Pub. No. 2014/0283855 to Hawes et al., U.S. Pat. App. Pub. No. 2014/0014125 to Fernando et al., U.S. Pat. App. Pub. No. 2013/0243410 to Nichols et al., U.S. Pat. App. Pub. No. 2010/0313901 to Fernando et al., and U.S. Pat. App. Pub. No. 2009/0230117 to Fernando et al., all of which are incorporated herein by reference.

[0037] The LED **214** may be one example of a suitable visual indicator with 15 which the aerosol delivery device **100** may be equipped. Other indicators such as audio indicators (e.g., speakers), haptic indicators (e.g., vibration motors) or the like can be included in addition to or as an alternative to visual indicators such as the LED, quantum dot enabled LEDs.

[0038] The cartridge **104** can be formed of a cartridge shell **216** enclosing a 20 reservoir **218** configured to retain the aerosol precursor composition, and including a heater **222** (sometimes referred to as a heating element). In various configurations, this structure may be referred to as a tank; and accordingly, the terms “cartridge,” “tank” and the like may be used interchangeably to refer to a shell or other housing enclosing a reservoir for aerosol precursor composition, and including a heater.

[0039] As shown, in some examples, the reservoir **218** may be in fluid 25 communication with a liquid transport element **220** adapted to wick or otherwise transport an aerosol precursor composition stored in the reservoir housing to the heater **222**. In some examples, a valve may be positioned between the reservoir and heater, and configured to control an amount of aerosol precursor composition passed or delivered from the reservoir to the heater.

[0040] Various examples of materials configured to produce heat when electrical current is applied therethrough may be employed to form the heater **222**. The heater in these examples may be a resistive heating element such as a wire coil, micro heater or the like. Example materials from which the heating element may be formed

include Kanthal (FeCrAl), Nichrome, stainless steel, Molybdenum disilicide (MoSi₂), molybdenum silicide (MoSi), Molybdenum disilicide doped with Aluminum (Mo(Si,Al)₂), graphite and graphite-based materials (e.g., carbon-based foams and yarns) and ceramics (e.g., positive or negative temperature coefficient ceramics).

5 Example implementations of heaters or heating members useful in aerosol delivery devices according to the present disclosure are further described below, and can be incorporated into devices such as those described herein.

[0041] An opening **224** may be present in the cartridge shell **216** (e.g., at the mouthend) to allow for egress of formed aerosol from the cartridge **104**.

10 **[0042]** The cartridge **104** also may include one or more electronic components **226**, which may include an integrated circuit, a memory component (e.g., EEPROM, flash memory), a sensor, or the like. The electronic components may be adapted to communicate with the control component **208** and/or with an external device by wired or wireless means. The electronic components may be positioned anywhere within 15 the cartridge or a base **228** thereof.

[0043] Although the control component **208** and the flow sensor **210** are illustrated separately, it is understood that various electronic components including the control component and the flow sensor may be combined on an electronic printed circuit board (PCB) that supports and electrically connects the electronic components.

20 Further, the PCB may be positioned horizontally relative the illustration of FIG. 1 in that the PCB can be lengthwise parallel to the central axis of the control body. In some examples, the air flow sensor may comprise its own PCB or other base element to which it can be attached. In some examples, a flexible PCB may be utilized. A flexible PCB may be configured into a variety of shapes, include substantially tubular 25 shapes. In some examples, a flexible PCB may be combined with, layered onto, or form part or all of a heater substrate.

[0044] The control body **102** and the cartridge **104** may include components adapted to facilitate a fluid engagement therebetween. As illustrated in FIG. 2, the control body can include a coupler **230** having a cavity **232** therein. The base **228** of the cartridge can be adapted to engage the coupler and can include a projection **234** 30 adapted to fit within the cavity. Such engagement can facilitate a stable connection between the control body and the cartridge as well as establish an electrical connection between the power source **212** and control component **208** in the control body and the heater **222** in the cartridge. Further, the control body shell **206** can

include an air intake **236**, which may be a notch in the shell where it connects to the coupler that allows for passage of ambient air around the coupler and into the shell where it then passes through the cavity **232** of the coupler and into the cartridge through the projection **234**.

5 [0045] A coupler and a base useful according to the present disclosure are described in U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., which is incorporated herein by reference. For example, the coupler **230** as seen in FIG. 2 may define an outer periphery **238** configured to mate with an inner periphery **240** of the base **228**. In one example the inner periphery of the base may define a radius that is 10 substantially equal to, or slightly greater than, a radius of the outer periphery of the coupler. Further, the coupler may define one or more protrusions **242** at the outer periphery configured to engage one or more recesses **244** defined at the inner periphery of the base. However, various other examples of structures, shapes and components may be employed to couple the base to the coupler. In some examples 15 the connection between the base of the cartridge **104** and the coupler of the control body **102** may be substantially permanent, whereas in other examples the connection therebetween may be releasable such that, for example, the control body may be reused with one or more additional cartridges that may be disposable and/or refillable.

20 [0046] The reservoir **218** illustrated in FIG. 2 can be a container or can be a fibrous reservoir, as presently described. For example, the reservoir can comprise one or more layers of nonwoven fibers substantially formed into the shape of a tube encircling the interior of the cartridge shell **216**, in this example. An aerosol precursor composition can be retained in the reservoir. Liquid components, for example, can be sorptively retained by the reservoir. The reservoir can be in fluid connection with the 25 liquid transport element **220**. The liquid transport element can transport the aerosol precursor composition stored in the reservoir via capillary action to the heater **222** that is in the form of a metal wire coil in this example. As such, the heater is in a heating arrangement with the liquid transport element.

30 [0047] In some examples, a microfluidic chip may be embedded in the reservoir **218**, and the amount and/or mass of aerosol precursor composition delivered from the reservoir may be controlled by a micro pump, such as one based on microelectromechanical systems (MEMS) technology. The heater **222** may be configured to implement radio-frequency inductive based heating of the aerosol precursor composition without a wick or physical contact with the aerosol precursor

composition, such as in a manner described in U.S. Pat. App. Ser. No. 14/934,763 to Davis et al., filed November 6, 2015, which is incorporated by reference. Other example implementations of reservoirs and transport elements useful in aerosol delivery devices according to the present disclosure are further described below, and 5 such reservoirs and/or transport elements can be incorporated into devices such as those described herein. In particular, specific combinations of heating members and transport elements as further described below may be incorporated into devices such as those described herein.

[0048] In use, when a user draws on the aerosol delivery device **100**, airflow is 10 detected by the flow sensor **210**, and the heater **222** is activated to vaporize components of the aerosol precursor composition. Drawing upon the mouthend of the aerosol delivery device causes ambient air to enter the air intake **236** and pass through the cavity **232** in the coupler **230** and the central opening in the projection **234** of the base **228**. In the cartridge **104**, the drawn air combines with the formed vapor to form 15 an aerosol. The aerosol is whisked, aspirated or otherwise drawn away from the heater and out the opening **224** in the mouthend of the aerosol delivery device.

[0049] In some examples, the aerosol delivery device **100** may include a number 20 of additional software-controlled functions. For example, the aerosol delivery device may include a power-source protection circuit configured to detect power-source input, loads on the power-source terminals, and charging input. The power-source protection circuit may include short-circuit protection, under-voltage lock out and/or over-voltage charge protection, battery temperature compensation. The aerosol delivery device may also include components for ambient temperature measurement, and its control component **208** may be configured to control at least one functional 25 element to inhibit power-source charging – particularly of any battery – if the ambient temperature is below a certain temperature (e.g., 0 °C) or above a certain temperature (e.g., 45 °C) prior to start of charging or during charging.

[0050] Additionally or alternatively, in some examples, the control component 30 **208** may include a microprocessor with an embedded analog-to-digital converter (ADC) useful for measurement of the temperature of the heater **222**. More particularly, for example, the microprocessor may be programmed to cause a fixed current to the heater, and measure the voltage across the heater. The microprocessor may then be configured to calculate the resistance of the heater that varies with temperature from the current and voltage ($R = V / I$). The resistance may then be used

to determine the temperature of the heater from a known relationship between resistance and temperature for the heater material. This relationship may be expressed in a number of different manners, such as by a lookup table.

[0051] Power delivery from the power source **212** may vary over the course of each puff on the device **100** according to a power control mechanism. The device may include a “long puff” safety timer such that in the event that a user or component failure (e.g., flow sensor **210**) causes the device to attempt to puff continuously, the control component **208** may control at least one functional element to terminate the puff automatically after some period of time (e.g., four seconds). Further, the time between puffs on the device may be restricted to less than a period of time (e.g., 100 seconds). A watchdog safety timer may automatically reset the aerosol delivery device if its control component or software running on it becomes unstable and does not service the timer within an appropriate time interval (e.g., eight seconds). Further safety protection may be provided in the event of a defective or otherwise failed flow sensor **210**, such as by permanently disabling the aerosol delivery device in order to prevent inadvertent heating. A puffing limit switch may deactivate the device in the event of a pressure sensor fail causing the device to continuously activate without stopping after the four second maximum puff time.

[0052] The aerosol delivery device **100** may include a puff tracking algorithm configured for heater lockout once a defined number of puffs has been achieved for an attached cartridge (based on the number of available puffs calculated in light of the e-liquid charge in the cartridge). The aerosol delivery device may include a sleep, standby or low-power mode function whereby power delivery may be automatically cut off after a defined period of non-use. Further safety protection may be provided in that all charge/discharge cycles of the power source **212** may be monitored by the control component **208** over its lifetime. After the power source has attained the equivalent of a predetermined number (e.g., 200) of full discharge and full recharge cycles, it may be declared depleted, and the control component may control at least one functional element to prevent further charging of the power source.

[0053] The various components of an aerosol delivery device according to the present disclosure can be chosen from components described in the art and commercially available. Examples of batteries that can be used according to the disclosure are described in U.S. Pat. No. 9,484,155 to Peckerar et al., which is incorporated herein by reference.

[0054] The aerosol delivery device **100** can incorporate the sensor **210** or another sensor or detector for control of supply of electric power to the heater **222** when aerosol generation is desired (e.g., upon draw during use). As such, for example, there is provided a manner or method of turning off power to the heater when the aerosol delivery device is not be drawn upon during use, and for turning on power to actuate or trigger the generation of heat by the heater during draw. Additional representative types of sensing or detection mechanisms, structure and configuration thereof, components thereof, and general methods of operation thereof, are described in U.S. Pat. No. 5,261,424 to Sprinkel, Jr., U.S. Pat. No. 5,372,148 to McCafferty et al., and PCT Pat. App. Pub. No. WO 2010/003480 to Flick, all of which are incorporated herein by reference.

[0055] The aerosol delivery device **100** most preferably incorporates the control component **208** or another control mechanism for controlling the amount of electric power to the heater **222** during draw. Representative types of electronic components, structure and configuration thereof, features thereof, and general methods of operation thereof, are described in U.S. Pat. No. 4,735,217 to Gerth et al., U.S. Pat. No. 4,947,874 to Brooks et al., U.S. Pat. No. 5,372,148 to McCafferty et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 7,040,314 to Nguyen et al., U.S. Pat. No. 8,205,622 to Pan, U.S. Pat. App. Pub. No. 8,881,737 to Collet et al., U.S. Pat. No. 9,423,152 to Ampolini et al., U.S. Pat. No. 9,439,454 to Fernando et al., and U.S. Pat. App. Pub. No. 2015/0257445 to Henry et al., all of which are incorporated herein by reference.

[0056] Representative types of substrates, reservoirs or other components for supporting the aerosol precursor are described in U.S. Pat. No. 8,528,569 to Newton, U.S. Pat. App. Pub. No. 2014/0261487 to Chapman et al., U.S. Pat. App. Pub. No. 2015/0059780 to Davis et al., and U.S. Pat. App. Pub. No. 2015/0216232 to Bless et al., all of which are incorporated herein by reference. Additionally, various wicking materials, and the configuration and operation of those wicking materials within certain types of electronic cigarettes, are set forth in U.S. Pat. No. 8,910,640 to Sears et al., which is incorporated herein by reference.

[0057] The aerosol precursor composition, also referred to as a vapor precursor composition, may comprise a variety of components including, by way of example, a polyhydric alcohol (e.g., glycerin, propylene glycol or a mixture thereof), nicotine, tobacco, tobacco extract and/or flavorants. Representative types of aerosol precursor

components and formulations also are set forth and characterized in U.S. Pat. No. 7,217,320 to Robinson et al., U.S. Pat. No. 9,254,002 to Chong et al., U.S. Pat. No. 8,881,737 to Collett et al., U.S. Pat. Pub. No. 2013/0008457 to Zheng et al., U.S. Pat. Pub. No. 2015/0020823 to Lipowicz et al., and U.S. Pat. Pub. No. 2015/0020830 to 5 Koller, as well as PCT Pat. App. Pub. No. WO 2014/182736 to Bowen et al., and U.S. Pat. App. Ser. No. 15/222,615 to Watson et al., filed July 28, 2016, the disclosures of which are incorporated herein by reference. Other aerosol precursors that may be employed include the aerosol precursors that have been incorporated in the VUSE® product by R. J. Reynolds Vapor Company, the BLU™ product by Imperial Tobacco 10 Group PLC, the MISTIC MENTHOL product by Mistic Ecigs, and the VYPE product by CN Creative Ltd. Also desirable are the so-called “smoke juices” for electronic cigarettes that have been available from Johnson Creek Enterprises LLC.

[0058] Implementations of effervescent materials can be used with the aerosol precursor, and are described, by way of example, in U.S. Pat. App. Pub. No.

15 2012/0055494 to Hunt et al., which is incorporated herein by reference. Further, the use of effervescent materials is described, for example, in U.S. Pat. No. 4,639,368 to Niazi et al., U.S. Pat. No. 5,178,878 to Wehling et al., U.S. Pat. No. 5,223,264 to Wehling et al., U.S. Pat. No. 6,974,590 to Pather et al., U.S. Pat. No. 7,381,667 to Bergquist et al., U.S. Pat. No. 8,424,541 to Crawford et al., and U.S. Pat. No.

20 8,627,828 to Strickland et al., as well as U.S. Pat. No. 9,307,787 to Sun et al., U.S. Pat. App. Pub. No. 2010/0018539 to Brinkley et al., and PCT Pat. App. Pub. No. WO 97/06786 to Johnson et al., all of which are incorporated by reference herein.

Additional description with respect to implementations of aerosol precursor compositions, including description of tobacco or components derived from tobacco included therein, is provided in U.S. Pat. App. Ser. Nos. 15/216,582 and 15/216,590, 25 each filed July 21, 2016 and each to Davis et al., which are incorporated herein by reference.

[0059] Additional representative types of components that yield visual cues or indicators may be employed in the aerosol delivery device **100**, such as visual

30 indicators and related components, audio indicators, haptic indicators and the like.

Examples of suitable LED components, and the configurations and uses thereof, are described in U.S. Pat. No. 5,154,192 to Sprinkel et al., U.S. Pat. No. 8,499,766 to Newton, U.S. Pat. No. 8,539,959 to Scatterday, and U.S. Pat. No. 9,451,791 to Sears et al., all of which are incorporated herein by reference.

[0060] Yet other features, controls or components that can be incorporated into aerosol delivery devices of the present disclosure are described in U.S. Pat. No. 5,967,148 to Harris et al., U.S. Pat. No. 5,934,289 to Watkins et al., U.S. Pat. No. 5,954,979 to Counts et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 8,365,742 to Hon, U.S. Pat. No. 8,402,976 to Fernando et al., U.S. Pat. App. Pub. No. 2005/0016550 to Katase, U.S. Pat. No. 8,689,804 to Fernando et al., U.S. Pat. App. Pub. No. 2013/0192623 to Tucker et al., U.S. Pat. No. 9,427,022 to Leven et al., U.S. Pat. App. Pub. No. 2013/0180553 to Kim et al., U.S. Pat. App. Pub. No. 2014/0000638 to Sebastian et al., U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., and U.S. Pat. No. 9,220,302 to DePiano et al., all of which are incorporated herein by reference.

[0061] As indicated above, the control component **208** includes a number of electronic components, and in some examples may be formed of a PCB. The electronic components may include a microprocessor or processor core, and a memory. In some examples, the control component may include a microcontroller with integrated processor core and memory, and may further include one or more integrated input/output peripherals. In some examples, the control component may be coupled to a communication interface **246** to enable wireless communication with one or more networks, computing devices or other appropriately-enabled devices.

20 Examples of suitable communication interfaces are disclosed in U.S. Pat. App. Pub. No. 2016/0261020 to Marion et al., the content of which is incorporated herein by reference. Another example of a suitable communication interface is the CC3200 single chip wireless microcontroller unit (MCU) from Texas Instruments. And examples of suitable manners according to which the aerosol delivery device may be 25 configured to wirelessly communicate are disclosed in U.S. Pat. App. Pub. No. 2016/0007651 to Ampolini et al., and U.S. Pat. App. Pub. No. 2016/0219933 to Henry, Jr. et al., each of which is incorporated herein by reference.

[0062] In accordance with some example implementations, the flow sensor **210** is 30 configured to produce measurements of differential pressure between an ambient atmospheric pressure and a pressure caused by airflow through at least a portion of the aerosol delivery device **100**. The sensor is configured to convert the measurements of differential pressure to corresponding electrical signals, and the control component **208** (e.g., a microprocessor) is configured to receive the corresponding electrical signals. In some examples, the control component is responsive to electrical signals

having only at a predetermined frequency of the corresponding electrical signals from the sensor to prevent electrical signals having other frequencies from devices external to the aerosol delivery device from causing the microprocessor to operate in the active mode. And in some examples, the sensor and at least the microprocessor of the 5 control component are potted in a waterproof material to thereby make the sensor and the microprocessor waterproof or resistant to water, aerosol precursor composition or vaporize components of the aerosol precursor composition.

[0063] In some examples, the flow sensor **210** is operable in a frequency mode selectable from a plurality of frequency modes, and the control component **208** (e.g., a 10 microprocessor) is configured to select and thereby control the frequency mode of the sensor. In these examples, the plurality of frequency modes includes a first frequency mode and a second frequency mode. The first frequency mode is at a higher frequency with lesser power consumption by the sensor and lower resolution of the measurements relative to the second frequency mode. And the second frequency mode is at a lower frequency with greater power consumption by the sensor and higher resolution of the measurements.

[0064] In examples including the above-described differential pressure sensor, the control component **208** is configured to operate in an active mode only in an instance in which the differential pressure is at least a threshold differential pressure. In the 20 active mode, the control component is configured to control the heater **222** (heating element) to activate and vaporize components of the aerosol precursor composition. In some examples, the control component is configured to control the heater to vaporize components of the aerosol precursor composition proportional to the differential pressure, with more components being vaporized with a greater 25 differential pressure, and fewer components being vaporized with a lesser differential pressure (above the threshold differential pressure).

[0065] In some examples, the sensor **210** is a microelectromechanical systems-based (MEMS-based) sensor. In some examples, the sensor is a multidirectional electromechanical pressure sensor configured to produce measurements of differential 30 pressure based on pressure on the sensor in different directions. Examples of suitable MEMS-based sensors include the ZPA series MEMS barometric pressure sensors from Murata Manufacturing.

[0066] The foregoing description of use of the article(s) can be applied to the various example implementations described herein through minor modifications,

which can be apparent to the person of skill in the art in light of the further disclosure provided herein. The above description of use, however, is not intended to limit the use of the article but is provided to comply with all necessary requirements of disclosure of the present disclosure. Any of the elements shown in the article(s) 5 illustrated in FIGS. 1 and 2 or as otherwise described above may be included in an aerosol delivery device according to the present disclosure.

[0067] Many modifications and other implementations of the disclosure set forth herein will come to mind to one skilled in the art to which this disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the 10 associated drawings. Therefore, it is to be understood that the disclosure is not to be limited to the specific implementations disclosed, and that modifications and other implementations are intended to be included within the scope of the appended claims. Moreover, although the foregoing descriptions and the associated drawings describe example implementations in the context of certain example combinations of elements 15 and/or functions, it should be appreciated that different combinations of elements and/or functions may be provided by alternative implementations without departing from the scope of the appended claims. In this regard, for example, different combinations of elements and/or functions than those explicitly described above are also contemplated as may be set forth in some of the appended claims. Although 20 specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

WHAT IS CLAIMED IS:

1. An aerosol delivery device comprising:
 - at least one housing enclosing a reservoir configured to retain an aerosol precursor composition;
 - a heating element;
 - 5 a sensor configured to produce measurements of differential pressure between an ambient atmospheric pressure and a pressure caused by airflow through at least a portion of the aerosol delivery device, the sensor being configured to convert the measurements of differential pressure to corresponding electrical signals; and
 - a microprocessor coupled to the heating element and the sensor, the
 - 10 microprocessor being configured to receive the corresponding electrical signals and operate in an active mode only in an instance in which the differential pressure is at least a threshold differential pressure, the microprocessor in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition.
- 15 2. The aerosol delivery device of claim 1, wherein the sensor is a microelectromechanical systems-based (MEMS-based) sensor.
3. The aerosol delivery device of claim 1, wherein the sensor is a
20 multidirectional electromechanical pressure sensor configured to produce measurements of differential pressure based on pressure on the sensor in different directions.
4. The aerosol delivery device of claim 1, wherein the sensor and the
25 microprocessor are potted in a waterproof material to thereby make the sensor and the microprocessor waterproof or resistant to water, aerosol precursor composition or vaporize components of the aerosol precursor composition.
5. The aerosol delivery device of claim 1, wherein the microprocessor is
30 responsive to electrical signals having only at a predetermined frequency of the corresponding electrical signals from the sensor to prevent electrical signals having other frequencies from devices external to the aerosol delivery device from causing the microprocessor to operate in the active mode.

6. The aerosol delivery device of claim 1, wherein the sensor is operable in a frequency mode selectable from a plurality of frequency modes, and the microprocessor is configured to select and thereby control the frequency mode of the
5 sensor, and

wherein the plurality of frequency modes includes a first frequency mode and a second frequency mode, the first frequency mode being at a higher frequency with lesser power consumption by the sensor and lower resolution of the measurements relative to the second frequency mode at a lower frequency with greater power
10 consumption by the sensor and higher resolution of the measurements.

7. A control body coupled or coupleable with a cartridge to form an aerosol delivery device, the cartridge including a reservoir configured to retain an aerosol precursor composition, and equipped with a heating element controllable to
15 activate and vaporize components of the aerosol precursor composition, the control body comprising:

a housing; and within the housing,
a sensor configured to produce measurements of differential pressure between an ambient atmospheric pressure and a pressure caused by airflow through at least a
20 portion of the control body, the sensor being configured to convert the measurements of differential pressure to corresponding electrical signals; and

a microprocessor coupled to the heating element and the sensor when the control body is coupled with the cartridge, the microprocessor being configured to receive the corresponding electrical signals and operate in an active mode only in an
25 instance in which the differential pressure is at least a threshold differential pressure, the microprocessor in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition.

8. The control body of claim 7, wherein the sensor is a
30 microelectromechanical systems-based (MEMS-based) sensor.

9. The control body of claim 7, wherein the sensor is a multidirectional electromechanical pressure sensor configured to produce measurements of differential pressure based on pressure on the sensor in different directions.

10. The control body of claim 7, wherein the sensor and the
microprocessor are potted in a waterproof material to thereby make the sensor and the
microprocessor waterproof or resistant to water, aerosol precursor composition or
5 vaporize components of the aerosol precursor composition.

11. The control body of claim 7, wherein the microprocessor is responsive
to electrical signals having only at a predetermined frequency of the corresponding
electrical signals from the sensor to prevent electrical signals having other frequencies
10 from devices external to the control body from causing the microprocessor to operate
in the active mode.

12. The control body of claim 7, wherein the sensor is operable in a
frequency mode selectable from a plurality of frequency modes, and the
15 microprocessor is configured to select and thereby control the frequency mode of the
sensor, and

wherein the plurality of frequency modes includes a first frequency mode and
a second frequency mode, the first frequency mode being at a higher frequency with
lesser power consumption by the sensor and lower resolution of the measurements
20 relative to the second frequency mode at a lower frequency with greater power
consumption by the sensor and higher resolution of the measurements.




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2018/057015

A. CLASSIFICATION OF SUBJECT MATTER

INV. A24F47/00 A61M15/06
ADD. A61M16/00 A61M11/04 A61M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A24F A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2017/245547 A1 (LIPOWICZ PETER J [US]) 31 August 2017 (2017-08-31) paragraphs [0043] - [0065], [0069] - [0074], [0081], [0084], [0085], [0088], [0091]; figures 1-5 -----	1-3,6-9, 12 4,5,10, 11
Y	US 2016/366939 A1 (ALARCON RAMON [US] ET AL) 22 December 2016 (2016-12-22) paragraphs [0027] - [0039], [0052] - [0053]; figures 1-3, 6A-6B, 12 -----	1,5,7,11 5,11
X	US 2015/245658 A1 (WORM STEVEN L [US] ET AL) 3 September 2015 (2015-09-03) paragraphs [0032] - [0037], [0044], [0059] - [0065], [0077], [0080]; figures 1-5 ----- -/-	1,7

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

22 November 2018

30/11/2018

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Fischer, Olivier

INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2018/057015

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2014/270727 A1 (AMPOLINI FREDERIC PHILIPPE [US] ET AL) 18 September 2014 (2014-09-18) paragraphs [0063] - [0066], [0087] - [0090], [0096] - [0105], [0116]; figures 1-3, 11-12 -----	1,7
Y	US 2014/270729 A1 (DEPIANO JOHN [US] ET AL) 18 September 2014 (2014-09-18) paragraphs [0114], [0116]; figures 1, 23 -----	4,10
A	US 2016/128389 A1 (LAMB WILSON CHRISTOPHER [US] ET AL) 12 May 2016 (2016-05-12) paragraphs [0004] - [0006], [0024] - [0035], [0043] - [0046], [0049] - [0050], [0053] - [0057]; figures 1-5 -----	1-12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2018/057015

Patent document cited in search report	Publication date	Patent family member(s)			Publication date
US 2017245547	A1 31-08-2017	CN 108697167 A KR 20180116249 A US 2017245547 A1 WO 2017144703 A1			23-10-2018 24-10-2018 31-08-2017 31-08-2017
US 2016366939	A1 22-12-2016	AU 2014281351 A1 BR 112015032001 A2 CA 2916242 A1 CN 105452977 A EP 3011405 A1 JP 2016525345 A KR 20160033112 A MX 356938 B RU 2016101273 A RU 2018118600 A US 2016366939 A1 WO 2014205263 A1 ZA 201600046 B			28-01-2016 25-07-2017 24-12-2014 30-03-2016 27-04-2016 25-08-2016 25-03-2016 20-06-2018 25-07-2017 08-11-2018 22-12-2016 24-12-2014 26-04-2017
US 2015245658	A1 03-09-2015	CN 106231933 A EP 3110271 A2 JP 2017506901 A KR 20160127086 A RU 2016134930 A US 2015245658 A1 US 2018077970 A1 WO 2015130598 A2			14-12-2016 04-01-2017 16-03-2017 02-11-2016 02-04-2018 03-09-2015 22-03-2018 03-09-2015
US 2014270727	A1 18-09-2014	CN 105208884 A EP 2967140 A1 ES 2636950 T3 HK 1220094 A1 JP 6410193 B2 JP 2016517270 A KR 20150130458 A RU 2015139369 A US 2014270727 A1 WO 2014150247 A1			30-12-2015 20-01-2016 10-10-2017 28-04-2017 24-10-2018 16-06-2016 23-11-2015 24-04-2017 18-09-2014 25-09-2014
US 2014270729	A1 18-09-2014	US 2014270729 A1 US 2016345633 A1 US 2018303164 A1			18-09-2014 01-12-2016 25-10-2018
US 2016128389	A1 12-05-2016	CN 107205481 A EP 3217816 A1 JP 2017535265 A US 2016128389 A1 WO 2016077428 A1			26-09-2017 20-09-2017 30-11-2017 12-05-2016 19-05-2016