




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G02B 6/38, 6/44</b>	<b>A1</b>	(11) International Publication Number: <b>WO 95/07480</b> (43) International Publication Date: 16 March 1995 (16.03.95)
<p>(21) International Application Number: PCT/GB94/01913</p> <p>(22) International Filing Date: 2 September 1994 (02.09.94)</p> <p>(30) Priority Data: 9318633.6 8 September 1993 (08.09.93) GB</p> <p>(71) Applicant (for all designated States except MG US): N.V. RAYCHEM S.A. [BE/BE]; Diestsesteenweg 692, B-3010 Kessel-Lo (BE).</p> <p>(71) Applicant (for MG only): RAYCHEM LIMITED [GB/GB]; Faraday Road, Dorcan, Swindon, Wiltshire SN3 5HH (GB).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): MACKEN, Luk, Jozef [BE/BE]; Van Schoonbekestraat 77, B-2018 Antwerpen (BE). DAEMS, Daniel [BE/BE]; Vosstraat 328, B-2600 Berchem (BE). DE COSTER, Pieter [BE/BE]; Wolvendreef 52, B-3210 Linden (BE). VAN NOTEN, Lodewijk, Cordula, Michael [BE/BE]; Oude Rondelaan 96, B-3000 Leuven (BE).</p> <p>(74) Agents: BENSON, John, Everett et al.; Raychem Limited, Faraday Road, Dorcan, Swindon, Wiltshire SN3 5HH (GB).</p>		<p>(81) Designated States: AM, AU, BG, BR, BY, CA, CN, CZ, FI, GE, HU, JP, KE, KG, KR, KZ, LT, LV, MD, MG, MN, NO, NZ, PL, RO, RU, SI, SK, TJ, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> With international search report.</p>

(54) Title: ORGANIZATION OF OPTICAL FIBRES

## (57) Abstract

A base for an optical fibre organizer, which comprises: a first passage along one longitudinal edge portion for incoming fibres; a second passage along an opposite longitudinal edge portion for outgoing fibres; a plurality of first fibre guides separated from one another along the length of the base and extending from the first passage across the base towards the second passage where fibres in said guides are directed away from the plane of the base; a plurality of second fibre guides separated from one another along the length of the base and extending from the second passage across the base towards the first passage where fibres in said guides are directed away from the plane of the base.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

ORGANIZATION OF OPTICAL FIBRES

The present invention relates to various components for use in an optical fibre network, in particular to components for fibre routing and to modules to be installed with optical fibres.

Optical fibre networks can have a complex architecture involving precise fibre routing and storage between fibre splices and fibre splitters etc. Since splicing and splitting of optical fibres is a complex and lengthy process requiring clean conditions, carrying it out in the field can add considerably to the cost and time for installation of an optical fibre network.

A further problem is that many optical fibre networks have many different points at which fibre organization is required. For example, fibres must be terminated at an exchange, terminated at subscribers, spliced between lengths of optical fibre cable, spliced at spur points from ring networks etc., and splitting must be carried out since each fibre from an exchange carries information for many subscribers.

If organizers and other components were to be tailor-made for each of these points of use their cost would be high. We have therefore designed an essentially modular system, particularly allowing pre-installation of fibres thereby reducing installation work that must be carried out in the field.

We have designed a base which can route fibres from incoming and outgoing cables, and an organizer module which can be removably attached to it.

Thus, the present invention provides a base for an optical fibre organizer, which comprises:

a first passage along one longitudinal edge portion for incoming fibres;

- 2 -

a second passage along an opposite longitudinal edge portion for outgoing fibres;

a plurality of first fibre guides separated from one another along the length of the base and extending from the first passage across the base towards the second passage where fibres in said guides are directed away from the plane of the base; and

a plurality of second fibre guides separated from one another along the length of the base and extending from the second passage across the base towards the first passage where fibres in said guides are directed away from the plane of the base.

The invention also provides an optical fibre organizer module which comprises:

- (1) a plate;
- (2) means overlying the plate for location of a plurality of optical fibre organizer trays separated from one another along the length of the plate;
- (3) a plurality of organizer trays located by means (2); and
- (4) guides running between plate (1) and the means (2) that can direct fibres from one side portion of the plate at one longitudinal position corresponding to one organizer tray to any of a plurality of longitudinal positions corresponding to those of other organizer trays at an opposite side portion of the base.

The invention further provides a module pre-installed with optical fibres capable of connection between an incoming fibre and a plurality of outgoing fibres, which comprises:

- (1) an input organizer tray;
- (2) a splitter organizer tray;
- (3) a splitter located in the splitter tray;
- (4) a plurality of output organizer trays;
- (5) a fibre pre-installed between the input tray and the input to the splitter; and
- (6) fibres pre-installed between the output of the splitter and the output trays.

- 3 -

Each guide of the base preferably terminates in a ramp having a minimum bend radius at least equal to the critical bend radius of the fibre, and those guides are preferably mutually interdigitated and preferably defined by walls that separate the first guides from the second guides.

The fibres directed by the first and second guides away from the plane of the base will in general be received by optical fibre organizer trays that are positioned above the base. Since it may be desirable that any given tray be able to receive a fibre from either side of the base and since each tray will not in general be individually moveable to achieve this, we prefer that pairs of first and second guides terminate at substantially equal distances along the length of the base. This can be achieved if the first guides curve along the base towards one end thereof, or if the first guides curve along the base towards one end and the second guides curve along the base towards the opposite end, such that pairs of first and second guides direct fibres away from the plane of the base at substantially equal distances along the length of the base.

In order that incoming fibres initially extending parallel to the length of the base are not excessively bent, we prefer that the first and second guides curve into the first and second passages respectively at a minimum bend radius at least equal to the critical bend radius of the fibre. The fibres will usually be provided within fibre tubes which preferably terminate at an end or other portion of the first and second passages, optionally at those curved portions. The first and second guides may have means for retaining such fibre tubes, which means preferably comprise protrusions in the guides or other means for ensuring an interference fit.

The base preferably additionally comprises a plate (which will generally be substantially in sheet form, but may comprise a grid) that can overlie the guides thereby preventing lateral displacement

- 4 -

of fibres from the guides but allowing longitudinal movement of fibres into or out of the guides. In this way, the plate can be installed and fibres subsequently inserted into the guides. If the plate does not overlie the extreme ends of the guides fibre tube can be inserted into those extreme ends by internal press fit, rather than by longitudinal sliding. The plate can preferably be removably attached to the base for example by a snap-fitting achieved for example by a series of detents protruding from the base engaging with holes in the plate.

The plate preferably has passages therein, preferably holes therethrough, through which can pass fibres that are directed away from the plane of the base by the first and second guides. These passages or holes preferably have a minimum radius of curvature at least equal to the critical bend radius of the fibres and preferably curved upwardly from the plane of the plate.

The plate, or other part of the base, preferably has means for location of one or more optical fibre organizer trays. Such means for location preferably allows a plurality of trays to be pivotally secured adjacent one another on top of the plate. The means for location is preferably bonded or otherwise semi-permanently or permanently secured to the top of the plate. It is envisaged that the plate together with the means for location and the trays will be pre-assembled in the factory, together with optical fibres connecting a splitter on one plate to a series of other plates, thus forming an organizer module. This module can then be snap-fitted onto the base in the field thereby saving field installation time.

Fibre routing between the various trays may be provided in any suitable way, but we prefer that the base have third guides that can direct fibres at one side portion of the base at one longitudinal position to any of a plurality of longitudinal positions at an opposite side portion of the base. These third guides are preferably provided by the plate and/or by a means for location of the trays.

- 5 -

The invention is further illustrated with respect to the accompanying drawings, in which:

Figures 1 and 2 show prior art optical fibre organizers;

Figures 3A to C show a base for an optical fibre organizer;

Figure 4 shows a plate, means for location of trays, and a series of trays;

Figure 5 shows the plate;

Figures 6 to 8 show the means for location;

Figures 9A to C show organizer trays; and

Figure 10 shows an enclosure within which the components of the invention may be used.

Figure 1 shows a prior art optical fibre organizer as disclosed in EP 0159857 (Raychem). It comprises a base 1 and dome-shaped cover 2, the base carrying various inlets 3 for optical fibre cables on one side thereof and organizer trays 4 attached to a support 5 at the other side thereof. The design as illustrated allows little possibility for choice of fibre routing and little possibility for pre-installation of fibres.

The design of figure 2, disclosed in US 4373776 (Northern Telecom Limited), has similar disadvantages. This design has a series of optical fibre organizer trays 4 mounted on a base 5 within a box. An inlet port 3 is provided at one end of the box that can lead to longitudinal passages 6 along which fibres can run to the trays 4. Splices between incoming and outgoing fibres are secured to the trays. There appears to be no specific provision for bend radius control nor any provision for passage of fibres across the width of the organizer.

Figures 3A, 3B and 3C show a base 7 of the invention. The base 7 has a first passage 8 along one longitudinal edge portion for incoming fibres, and a second passage 9 along an opposite longitudinal edge portion for outgoing fibres. The designations

- 6 -

incoming and outgoing are arbitrary and are not intended to indicate direction of light.

Several of first fibre guides 10 are shown separated from one another along the length of the base and extending from the first passage 8 across the base toward the second passage 9. Similarly several second fibre guides 11 can be seen separated from one another along the length of the base and extending from the second passage 9 across the base towards the first passage 8. Only a few of these guides are shown in figure 3A, and they can be seen in greater detail in figure 3C. Figure 3B is a cross-section taken line AA of figure 3A so the transverse guides can only be partially seen in that figure.

The first and second guides 10, 11 direct fibres they contain away from the plane of the base, and this may be achieved by the provision of small ramps 12 of the correct minimum bend radius.

The first and second guides 10, 11, can be seen to be mutually interdigitated and defined by walls 13 that separate the first guides 10 from the second guides 11. Each guide curves along the base, approximately at positions 14, 15, towards opposite ends of the base (taking into account the direction in which fibres are inserted into the guides from the passages 8, 9). As a result, pairs of ramps 12 are positioned such that the first and second guides 10, 11 direct fibres away from the plane of the base at substantially equal distances along the length of the base.

In order that fibres leaving the passages 8,9 and entering the guides 10,11 do not bend excessively, the guides curve into the passages as shown at 16. These curved portions 16 can be seen to have protrusions 17 that aid interference fit of fibre tubes within the guides. The guides can be seen to become thinner at a position approximately half-way along their length and fibre tubes may terminate anywhere along this thicker portion allowing the fibres



- 7 -

they contain to continue along the guides, up the ramps and into organizer trays mounted above the base.

A plate, shown in figures 4 and 5 may overlies the base and be retained by catches 18 which may snap through holes in the plate. The plate serves to maintain fibres in the guides whilst allowing their longitudinal movement, and also serves to secure the organizer trays into which the fibres will pass.

Figure 4 shows the base 19 together with means 22 for locating optical fibre trays, and a series of such trays 23. Holes 20 can be seen in the plate 19 for receiving the snap fastenings 18 of the base shown in figure 3. These holes 20 may also serve as passages through which pass fibres leaving the base 7. We prefer, in fact, that the ramps 12 protrude slightly through these holes 20.

Fibres entering the base 7 along one of the passages 8, 9 therefore enter guides 10, 11, cross the base, pass up the ramps 12 through the holes 20 in the plate 19, and then enter the organizer trays 23.

Fibre entering an input tray 23A in this way is spliced to a further fibre which leaves that tray and passes to a splitter tray 23B where it may be spliced to a splitter, the outgoing fibres from the splitter then being directed to a series of further output trays 23C. A fibre entering one of these further trays is then spliced to an outgoing fibre which leaves that further tray through the hole 20 in the plate, down the ramp, across a guide in the base and then leaves the base along the other of the passages 8, 9.

A preferred way in which fibres are routed between the various trays will be described below in connection with figures 6 to 8. Nonetheless, it can be seen that organization of incoming and outgoing fibres (done by the base 7) has been separated from the fibre organization associated with splitters, splices and stored loops

- 8 -

(done above the plate 19) thus the complicated and time consuming installation of splitters etc. can be done in the factory. All that needs to be done in the field is insertion of fibres along passages 8,9 through the guides 10,11 and into an input or output organizer tray 23A, 23C where it is spliced to pre-installed fibres that are already connected to a splitter tray.

Figures 5A, 5B and 5C are respectively a plan view, an end elevation and a perspective view of the plate 19.

Figures 6 to 8 show means for locating organizers on such a plate. The means 22 has means 24 such as holes for receiving pivot pins of an optical fibre organizer tray. Such pivot pins may be carried by projections from the base of the tray, which projections snap behind catches 25 to prevent accidental removal of the trays. The means 22 may conveniently be manufactured by moulding in two parts, a top part being visible in figure 6, and a bottom part being shown in figures 7A and 7B. The part shown in figure 7A carries supports 27 which protrude through holes in the base of the top part and which provide support for pivot pins of the organizer tray. The underside of the means 22 is shown in figure 7B, which illustrates the guides by means of which optical fibres pass from one tray to another. Means 22 may be bonded to the upper surface of the plate 19 (figures 4 and 5). The top of the lands shown in figure 7B will contact and be bonded to the surface of the plate without damage to fibres lying in the guides 28 and 29. Preferably the fibres will be positioned in these guides before the bonding operation takes place. Fibres running from one organizer tray to another will pass across means 22 by entering a guide 28 on one side (lower left or top right sides as shown in figure 7B) and then leave through an opposite guide 28 after passing along the trunk guide 29 the requisite distance.

Several means 22 may be positioned on the plate end to end as shown in figure 8 where it can be seen that the pattern of guides

- 9 -

repeats itself to allow interconnection between any two trays positioned along the plate.

In order to aid correct location of the means 22 on the plate and to confine adhesive to where it is required matching ridges and protuberances 30 may be provided on the means 22 and on the plate.

Figures 9A, 9B and 9C show various designs of optical fibre organizer trays. Pivot pins 31 carried by protrusions from the base of the organizer trays can be seen. Each tray has various curved walls 32 and catches 33 to retain fibre within the trays. Recesses or protrusions 34 may also be provided to locate fibre splices or fibre splitters.

Figure 10 is a cut away drawing of a splice closure 36 which may accommodate and seal the various components of the invention. The closure comprises a base 37 and a dome-shaped cover 38. The base 37 carries various circular ports 39 and an oval port 40. Attached to a base is a frame or other support 41 to which a routing organizer 42 is attached. A second support or frame 43 is provided separated from frame or support 41 by a gap 44. This gap 44 may contain loops of fibre from incoming and outgoing cables that are not spliced within the enclosure and therefore by-pass the routing organizer 42.

The base 7 of the invention may be positioned in space 35 and its passages 8, 9 supplied by fibres leaving the routing organizer 42. A module of the invention, preferably pre-installed with fibres, may then be snap-fitted onto the base 7 and connections made to the fibres in the passages 8, 9 that have left the routing organizer 42.

A second routing organizer 42, and base and module of the invention, may be provided on the back of the frame or support 43, and therefore out of view. The two routing organizers 42 may then

- 10 -

be in communication via through holes 45 so that fibres entering through any of the ports on the base 3 of the closure may pass to any of the organizer trays.

Cable is preferably supplied to the closure as follows. A loop of cable of approximately two metres length is inserted into the oval port 40. Some of the fibres constituting that loop will simply be stored in space 44, and others will be cut and fed to the routing organizer 42. That loop of cable may form part of a ring or spur in a fibre optic network. Fibres leaving the circular ports 39 after being spliced to or split from cut fibres of the loop may pass to subscribers or may be used to form a further spur. In a ring architecture a cable leaves main transmitting/receiving equipment at an exchange follows a ring and returns to back-up transmitting/receiving equipment at the exchange. The two ends resulting from cutting looped fibres in the enclosure therefore both go to the exchange and might both be needed to form a new spur or to go to subscribers. One end could be dealt with on frame 41 and the other on frame 43. Alternatively, send fibres could be dealt with on one frame and receive fibres on the other. The components of the invention allow for this flexibility.

For the avoidance of doubt it is noted that the invention provides various components, assemblies, systems and methods for organizing, storing and protecting optical fibres. Any of the various components disclosed may be used with any one or more other such components.

CLAIMS

1. A base for an optical fibre organizer, which comprises:
  - a first passage along one longitudinal edge portion for incoming fibres;
  - a second passage along an opposite longitudinal edge portion for outgoing fibres;
  - a plurality of first fibre guides separated from one another along the length of the base and extending from the first passage across the base towards the second passage where fibres in said guides are directed away from the plane of the base;
  - a plurality of second fibre guides separated from one another along the length of the base and extending from the second passage across the base towards the first passage where fibres in said guides are directed away from the plane of the base.
2. A base according to claim 1, in which each guide terminates in a ramp having a minimum bend radius at least equal to the critical bend radius of the fibre.
3. A base according to claim 1 or 2, in which the first and second guides are mutually interdigitated.
4. A base according to claim 3, in which the first and second guides are defined by a wall that separates first guides from second guides.
5. A base according to claim 3 or 4, in which the first guides curve along the base towards one end thereof, or the first guides

- 12 -

curve along the base towards one end and the second guides curve along the base towards the opposite end, such that pairs of first and second guides direct fibres away from the plane of the base at substantially equal distances along the length of the base.

6. A base according to any preceding claim in which the first and second guides curve into the first and second passages respectively at a minimum bend radius at least equal to the critical bend radius of the fibres.
7. A base according to any preceding claim, in which the first and second guides have means for retaining fibre tubes therein.
8. A base according to any preceding claim, which additionally comprises:  
a plate that can overlie the guides thereby preventing lateral displacement of fibres from the guides but allowing longitudinal movement of fibres into or out of the guides.
9. A base according to claim 8, in which the plate has passages therein through which can pass fibres directed away from the plane of the base by the first or second guide.
10. A base according to any preceding claim, having means for location of one or more optical fibre organizer trays.
11. A base according to claim 10, in which the plate carries the means for location of the organizer trays.
12. A base according to claim 10 or 11, in which the means for location allows a plurality of trays to be pivotally secured adjacent one another.

- 13 -

13. A base according to any preceding claim having third guides that can direct fibres at one side portion of the base at one longitudinal position to any of a plurality of longitudinal positions at an opposite side portion of the base.
14. A base according to any preceding claim in which the third guides are provided by the plate and/or by the means for location of the trays.
15. An optical fibre organizer which comprises:
  - (1) a base according to any of claims 1-4;
  - (2) means for location of a plurality of optical fibre organizer trays separated from one another along the length of the base;
  - (3) a plurality of optical fibre organizer trays located by means (2);
  - (4) third guides that can direct fibres on one side portion of the base at a longitudinal position corresponding to that of one organizer tray to any of a plurality of longitudinal positions corresponding to that of other organizer trays at an opposite side portion of the base.
16. An organizer according to claim 15, which additionally comprises:
  - (5) a plate that can overlie the first and second guides thereby preventing lateral displacement of fibres from those guides, and on top of which the means (2) is located such that the third guides run between plate (5) and means (2).
17. An organizer according to claim 15 or 16, pre-installed with optical fibres running from a first tray via a third guide to a second tray where it is spliced to an optical fibre that runs from the second tray via a third guide to a third tray.

- 14 -

18. An organizer according to claim 17, having a plurality of third trays, the splice comprising an optical splitter attached to fibres running to each of said third trays via third guides.
19. An optical fibre organizer module which comprises:
  - (1) a plate;
  - (2) means overlying the plate for location of a plurality of optical fibre organizer trays separated from one another along the length of the plate;
  - (3) a plurality of organizer trays located by means (2); and
  - (4) guides running between plate (1) and the means (2) that can direct fibres from one side portion of the plate at one longitudinal position corresponding to one organizer tray to any of a plurality of longitudinal positions corresponding to those of other organizer trays at an opposite side portion of the base.
20. A module according to claim 19, in which the plate (1) has means for removably securing it over a base according to any of claims 1-14 such as to allow longitudinal movement of fibres into the first and second guides.
21. A module according to claim 19 or 20, in which the base (1) has passages therein through which fibres passing underneath it and across its width can pass to the organizer trays located by the means (2) overlying it.
22. A module according to claim 21, in which the passages are curved at a minimum bend radius equal to at least the critical bend radius of the fibre.
23. A module according to any of claims 19-22, that is pre-installed with optical fibres running from a first tray via a




- 15 -

guide (4) to a second tray where it is spliced to an optical fibre that runs from the second tray via a guide (4) to a third tray.

24. A module pre-installed with optical fibres capable of connection between an incoming fibre and a plurality of outgoing fibres, which comprises:
- (1) an input organizer tray;
  - (2) a splitter organizer tray;
  - (3) a splitter located in the splitter tray;
  - (4) a plurality of organizer output trays;
  - (5) a fibre pre-installed between the input tray and the input to the splitter; and
  - (6) fibres pre-installed between the output of the splitter and the output trays.

Fig.1. Prior Art



2 / 10

Fig.2. Prior Art




Fig.3A.




Fig.3B.



Fig.3C.




Fig.4.




Fig.5A.




Fig.5B.




Fig.5C.




Fig.6.




Fig.7 A.




Fig.7B.







Fig.8.



9 / 10

Fig.9A.




Fig.9B.






Fig.9C.



10 / 10

Fig.10.



## INTERNATIONAL SEARCH REPORT

Inter: al Application No

PCT/GB 94/01913

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 G02B6/38 G02B6/44

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 G02B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	WO,A,91 18311 (MMM) 28 November 1991 see claims; figures ---	1,6,7 10-12, 15,16,24
Y	DE,A,28 46 951 (SIEMENS) 30 April 1980 see claims; figures ---	1,6,7
A	US,A,4 489 830 (L.J.CHARLEBOIS) 25 December 1984 see claims; figures ---	1
A	US,A,4 148 559 (F.GAUTHIER) 10 April 1979 see claims; figures ---	1
A	US,A,4 496 215 (J.M.SHAHEEN) 29 January 1985 see claims; figures ---	1
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

30 November 1994

Date of mailing of the international search report

14.12.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Pfahler, R

## INTERNATIONAL SEARCH REPORT

Intern al Application No

PCT/GB 94/01913

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 116 481 (SILEC) 22 August 1984 see claims; figures ---	1
A	DE,A,40 07 405 (SIEMENS) 12 September 1991 see claims; figures -----	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 94/01913

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9118311	28-11-91	EP-A- 0530325	10-03-93
DE-A-2846951	30-04-80	NONE	
US-A-4489830	25-12-84	NONE	
US-A-4148559	10-04-79	FR-A- 2367295	05-05-78
		CA-A- 1087008	07-10-80
		CH-A- 622106	13-03-81
		DE-A, C 2744101	06-04-78
		GB-A- 1588346	23-04-81
		JP-C- 1263875	16-05-85
		JP-A- 53045540	24-04-78
		JP-B- 59042847	18-10-84
		NL-A- 7710946	07-04-78
US-A-4496215	29-01-85	NONE	
EP-A-0116481	22-08-84	FR-A- 2538919	06-07-84
		US-A- 4634216	06-01-87
DE-A-4007405	12-09-91	NONE	