



- (51) **International Patent Classification:**
B65D 65/46 (2006.01) *C11D 17/04* (2006.01)
C11D 17/00 (2006.01)
- (21) **International Application Number:**
PCT/EP2014/061858
- (22) **International Filing Date:**
6 June 2014 (06.06.2014)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
13172900.6 19 June 2013 (19.06.2013) EP
- (71) **Applicant** (for AE, AG, AU, BB, BH, BN, BW, BZ, CA, CY, EG, GB, GD, GH, GM, IE, IL, IN, KE, KN, LC, LK, LS, MT, MW, MY, NA, NG, NZ, OM, PG, QA, RW, SA, SC, SD, SG, SL, SZ, TT, TZ, UG, VC, ZA, ZM, ZW only): **UNILEVER PLC** [GB/GB]; Unilever House, 100 Victoria Embankment, London, Greater London EC4Y 0DY (GB).
- (71) **Applicant** (for all designated States except AE, AG, AU, BB, BH, BN, BW, BZ, CA, CY, EG, GB, GD, GH, GM, IE, IL, IN, KE, KN, LC, LK, LS, MT, MW, MY, NA, NG, NZ, OM, PG, QA, RW, SA, SC, SD, SG, SL, SZ, TT, TZ, UG, US, VC, ZA, ZM, ZW): **UNILEVER N.V.** [NL/NL]; Weena 455, NL-3013 AL Rotterdam (NL).
- (71) **Applicant** (for US only): **CONOPCO, INC., D/B/A UNILEVER** [US/US]; 800 Sylvan Avenue, AG West, S. Wing, Englewood Cliffs, New Jersey 07632 (US).
- (72) **Inventors:** **COOLEY, Stuart Stephen**; Unilever R&D Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside CH63 3JW (GB). **NAYLOR, Paul**; Unilever R&D Port Sunlight, Quarry Road East, Bebington, Wirral, Merseyside CH63 3JW (GB).
- (74) **Agents:** **NEWBOULD, Frazer, Anthony** et al.; Unilever PLC, Unilever Patent Group, Colworth House, Sharnbrook, Bedford, Bedfordshire MK44 1LQ (GB).
- (81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).
- Declarations under Rule 4.17:**
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
 - as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))
 - of inventorship (Rule 4.17(iv))
- Published:**
- with international search report (Art. 21(3))

(54) **Title:** MULTI-COMPARTMENT WATER-SOLUBLE CAPSULES

(57) **Abstract:** A multi-compartment water-soluble capsule thermoformed from two sheets of water-soluble film, the capsule comprising a least two compartments with a different part of a detergent composition in each compartment, the two sheets of film being sealed together to form seal areas around each compartment, all the seal areas lying substantially in a first plane; - the capsule having at least one larger volume outer compartment and at least one smaller volume inner compartment generally enclosed in the first plane by the outer compartment(s), the outer compartment(s) being separated from the inner compartment(s) by a continuous partition seal area which is substantially rectangular and lies in the first plane, - the outer compartment(s) having a generally rectangular outer perimeter with rounded corners and a substantially uniform cross-section taken along a plane perpendicular to the first plane and perpendicular to the inner seal separating the inner and outer compartments.



- 1 -

MULTI-COMPARTMENT WATER-SOLUBLE CAPSULES**TECHNICAL FIELD**

- 5 This invention relates to multi-compartment water-soluble capsules comprising at least two compartments made from water-soluble film, each compartment containing a part of a detergent composition.

BACKGROUND

10

Multi-compartment water-soluble detergent capsules made with water-soluble film are known. The water soluble-film is typically polyvinyl alcohol. The preferred capsule manufacturing process involves thermoforming the film. By thermoforming is meant a process in which a first sheet of film is subjected to a moulding process to form recesses in the film. The process involves heating the film to soften it and also the application of vacuum to hold the film in the moulds. The recesses are then filled, typically with a detergent liquid. The capsules are completed by overlaying a second sheet over the filled recesses and sealing it to the first sheet of film around the edges of the recesses to form a flat seal area.

15

20

Relaxation of the first film typically then causes the applied second sheet to bulge out when the vacuum is released from the first sheet of film in the mould. The capsules are cut apart to leave part of the flat seal area as a peripheral "skirt" around each capsule when it is removed from the mould. Although the seal is flat when in the mould it may deform a little when removed from the mould. Likewise a rectangular profile capsule usually relaxes slightly away from having a perfect rectangular profile after it is released from the mould. Throughout this specification flat seals are ones that are moulded flat and rectangular capsules are ones formed in rectangular moulds, usually with their corners rounded off.

25

- 2 -

Multi-compartment capsules are suited for delivery of main wash laundry compositions to automatic washing machines and even for hand wash applications. Although a multi-compartment configuration is more difficult to manufacture than a single compartment it may be chosen because components of the detergent composition need to be mixed at point of use and/or have reduced stability when stored together. It may also give the capsule aesthetic appeal because the different compartments can be filled with different coloured contents. In general the formulator would like to keep the number of compartments to a minimum in order to avoid complexity and added cost.

Multi-compartment water-soluble detergent capsules comprising from 2 to 5 compartments obtained by thermoforming a water-soluble film are disclosed in EP 1375637 and EP 1394065 (Unilever). Each compartment of the package contains a different part of a cleaning composition and the compartments are connected to each other and separated from one another by at least one flat seal area. One compartment may contain a liquid part of the detergent composition and another compartment a granular part of the composition, such as bleach or builder. A problem with capsules having their compartments separated by a flat seal area that extends across the capsule as described in most of the embodiments disclosed is that they are floppy because they will fold up along the flat seal. This folding has been found to cause handling problems and a floppy capsule is not liked by consumers. Figure 1 shows plan and side elevations of a foldable two-compartment water-soluble capsule as described in these documents. Figure 2 shows the one embodiment (Figure 1d) from EP 1375 637A1 that does not suffer from this undisclosed folding problem. A generally rectangular compartment surrounds a small circular compartment. From paragraph 0079 we are told that the larger compartment contained 50 ml of the liquid formulation and the small compartment 7 g of the semi-solid formulation. According the preceding paragraph 0078 the liquid composition comprised:

- 3 -

	<i>Ingredient</i>	<i>Parts by weight</i>
	LAS, monoethanolamine salt	24.0
	Nonionic 7EO	20.3
	Soap	22.4
5	Monopropyleneglycol	23.7
	Moisture, salts, NDOM	6.9
	Minors (enzymes, polymers, perfume)	2.7

From paragraph 0077 it is disclosed that the semi solid composition comprised:

10

	<i>Ingredient</i>	<i>Parts by weight</i>
	Na-LAS	39.1
	Nonionic 7EO	33.5
	C12 soap	7.3
15	Monopropyleneglycol	to 100

In WO2010 0088112 a two compartment "stacked" capsule is made having a smaller liquid compartment and a larger powder compartment. The two compartments are separated only by a thin layer of polyvinylalcohol film. The disclosure is mainly focused on dishwashing compositions and the exemplary two compartment capsule has the following liquid and granular compositions in its compartments:

- 4 -

Ingredient	% in compartment	% in capsule
Percarbonate bleach	74.9	64.369
Acrylic acid / maleic acid copolymer	7.5	6.446
Polyacrylate or polycarboxylate polymer	13	11.172
Proteases and amylase enzyme mix	3	2.578
HEDP granular	1.5	1.289
Perfume	0.1	0.086
<i>Total in powder compartment</i>	<i>100</i>	<i>85.94</i>
Dipropylene glycol	57.29	5.970
Glycerine	2.99	0.312
Colour	0.9	0.094
Surfactant LF244	29.47	3.071
Nonionic surfactant	2.63	0.274
Water	6.72	0.700
<i>Total in liquid compartment</i>	<i>100.00</i>	<i>10.42</i>

It was also known, from the product sold as “Tide Pods” or “Ariel Pods”, to assemble two thermoformed “capsules” to form a multi-compartment capsule whereby a first “capsule” having at least two smaller liquid compartments joined together with foldable flat seals is then used to seal a larger compartment. This configuration prevents the seals from folding. However, this approach suffers from the disadvantages of a complex manufacturing process and having a seal area with triple layers of film. To avoid dissolution problems resulting from such triple layer seals it is necessary to use thinner than normal film, which leads to issues with leakage due to pin-holing of the thinner film elsewhere in the capsules during manufacture.

- 5 -

Polyvinylalcohol film cannot completely prevent migration of the contents of one liquid compartment into another. In any capsule where there is a liquid compartment separated from other ingredients only by a single thin layer of polyvinylalcohol film the ability to effectively segregate ingredients that need to be kept apart until use is inevitably compromised. For example in the three compartment capsule, only the contents of the two smaller liquid compartments can be considered to be effectively segregated, so it takes a minimum of three compartments to achieve significant segregation benefits when using this approach. The need to include sensitive ingredients in the smaller compartments then drives complexity as more and more of the smaller compartments are needed to keep these sensitive ingredients segregated from one another.

An alternative to thermoforming of capsules is a vertical form fill seal process (VFFS). US 2001/0033883 (Body) discloses multi-compartment capsules having separate compartments for granular and liquid materials, preferably popcorn kernels and oil, the contents being packed so that they can move within their respective compartments on the application of an external force thereby inhibiting the rupture of the compartments. A two compartment capsule has three layers of film. The extra third layer being used to form an internal partition between the fluid material in one compartment and the granular materials in a second compartment. If applied to a detergent composition this construction suffers from possible contamination of the granular compartment by transfer of liquid through the film. Such preformed packs are also more expensive to produce than thermoformed packs.

A known issue with water-soluble detergent capsules, including those used in automatic laundry washing machines, is that consumers do not read the instructions for their use carefully and therefore may use them incorrectly. They are known to put the capsule into the washing machine dispensing drawer when it should be added directly to the drum and they are also known to use capsules in

- 6 -

overloaded water conserving washing machines where the capsule may then not be exposed to much water.

There is a need for an improved multi-compartment water-soluble thermoformed capsule design, particularly one that uses only two layers of water-soluble film and is capable of withstanding the expected abuses by consumers.

SUMMARY OF THE INVENTION

According to the present invention there is provided a multi-compartment water-soluble capsule thermoformed from two sheets of water-soluble film, the capsule comprising a least two compartments with a different part of a detergent composition in each compartment, the two sheets of film being sealed together to form seal areas around each compartment, all the seal areas lying substantially in a first plane;

- the capsule having at least one larger volume outer compartment and at least one smaller volume inner compartment generally enclosed in the first plane by the outer compartment(s), the outer compartment(s) being separated from the inner compartment(s) by a continuous partition seal area which is substantially rectangular and lies in the first plane,
- the outer compartment(s) having a generally rectangular outer perimeter with rounded corners and a substantially uniform cross-section taken along a plane perpendicular to the first plane and perpendicular (radial) to the inner seal separating the inner and outer compartments.

If there is more than one inner compartment then each inner compartment is separated by a partition seal also lying in the first plane and formed from the two sheets of film. If there are also multiple outer compartments then the partition

- 7 -

seals for those outer compartments are also in the first plane and there are two such outer partition seals for each additional outer compartment.

When present, preferably the outer partition seals do not align with any inner
5 partition seals present. By arranging that the multiple inner and multiple outer compartment seals do not align this ensures that the capsule is not able to fold on itself.

Preferably there is only one inner compartment. More preferably it contains a
10 powdered or granular part of the detergent composition, most preferably granular. By granular is meant particles generally larger than 200 micron in diameter, even larger than 350 micron diameter.

The compartments are thermoformed, a first lower film being heated and then
15 held by vacuum in a mould while the inner and outer compartments are filled. Powdered or granular parts of the composition are preferably filled into their compartment(s) before any liquid parts of the composition are filled into their compartment(s). This has the advantage that any spilt solid material can be removed from the liquid compartment(s) and seal areas before the liquid is filled
20 into them.

Preferably the (uniform) cross-section of the at least one outer compartment is substantially circular. This is achieved by use of a semi-circular mould cross-section for the compartment. The relaxation of the formed capsule once it has
25 been removed from the mould makes the semi-circular cross-section change to be nearer to a fully circular cross-section. In any event the cross-section remains substantially uniform because the relaxation is substantially uniform. The uniform cross-section is preferably formed by having a uniform width the mould cavity, i.e. the distance between the inner and outer edges of the outer compartment is
30 constant in plan view.

- 8 -

Preferably there is a single, generally rectangular in plan, inner compartment located about the centre of the capsule and there is also a single outer compartment extending circumferentially and continuously around the inner compartment and defining a continuous partition seal of generally uniform width and an outer compartment of generally uniform width extending outwardly away from the inner compartment. In that case the capsule has two compartments.

Preferably the multi-compartment capsule has the at least one outer compartment(s) filled with liquid parts of the detergent composition and the at least one inner compartment (s) filled with free flowing granular or powdered parts of the detergent composition, the contents of all the compartments when combined forming a full detergent composition which is released on dissolution or rupture of the water-soluble films encasing the compartments. Most preferably there is a single liquid part of the composition in a single outer compartment and a single granular part of the composition in a single rectangular inner compartment. By a single granular part is meant a substantially homogeneous mixture of granules and/or powder that may individually have different compositions. For example: a mixture of granules comprising enzyme and granules comprising sequestrant. The term granule includes agglomerated particles.

The film is preferably polyvinyl alcohol film and it is more preferably less than 100 micron thick in the finished capsule.

An advantage of this capsule shape is that during the thermoforming process the constant cross-section of the outer compartment means that the water-soluble film is drawn simultaneously into all parts of the mould cavity and to the same extent around the outer mould cavity to form the outer compartment. This means that it is drawn at an equal rate and this reduces problems of ridge formation and pinholing which leads to damaged film, leakage and distortion of the outer compartment. Whilst, a single circular outer compartment would also solve the

- 9 -

problem of uneven film draw, it would also provide inefficient use of the films due to the moulds typically being arranged in a rectangular pattern in thermoforming processes which will generate large and unnecessary outer seal areas.

- 5 Furthermore, since a circular outer compartment would make the projected shape of the inner compartment circular too and that would increase problems with the filling of the inner compartment, especially if granular materials were used. The symmetrical recess of a circular thermoformed inner compartment can cause granules to bounce out during high speed filling. Such a high speed is needed to
10 have a commercially viable process. Making the inner compartment rectangular avoids this bouncing out problem and also provides for a longer travel time past the filling head compared to an equivalent volume circular inner compartment.

- It will be appreciated that the projection of the generally rectangular outer
15 compartment(s) always results in a rectangular central area to form the rectangular inner compartment(s) when the cross-section of the outer compartment is uniform and constant and the continuous seal between the inner and outer compartment s is as narrow as possible to avoid wastage of film.

- 20 The flat profile of the capsule, together with the cavity formed by the seal between the inner and outer compartments when there is a single continuous outer compartment has been found to give the capsule unexpected consumer related advantages. It has been found that it dispenses well from a washing machine drawer. Furthermore it has been found that it will deliver its contents well even if
25 only a very small quantity of water falls onto it, when placed in the drum of the washing machine, on top of the load.

- A yet further unexpected advantage of this capsule shape has been the way that it seems to automatically take up less volume in a pack due to the shape helping it
30 to form stacks of capsules with minimal wasted space in between. It would even

- 10 -

be possible to dispense the capsules from a tube like pack containing a highly efficiently packed single stack of capsules.

DETAILED DESCRIPTION OF THE INVENTION

5

Thermoforming Process.

The multi-compartment capsule is produced by a process of thermoforming. Such a process may advantageously comprise the following steps to form the preferred
10 two compartment capsule:

- (a) placing a first sheet of water-soluble polyvinyl alcohol film over a mould having sets of cavities, each set comprising an inner cavity surrounded by an outer cavity;
- 15 (b) heating and applying vacuum to the film to mould the film into the cavities and hold it in place to form two recesses in the film; an inner recess and an outer recess connected to the inner recess by the film;
- (c) filling two different parts of a detergent composition into the inner and outer recesses, the parts together forming a full detergent composition;
- 20 (d) sealing a second sheet of film to the first sheet of film across the formed recesses to produce a two compartment capsule having an inner compartment and a surrounding outer compartment, wherein the two compartments are connected to each other and separated by a continuous flat seal area.
- (e) cutting between the outer compartments so that a series of multi-compartment
25 capsules are formed, each capsule containing a part of a detergent composition in two compartments (one inner and one outer compartment).

Sealing can be done by any suitable method for example heat-sealing, solvent sealing or UV sealing. Particularly preferred is water-sealing. Water sealing may

- 11 -

be carried out by applying moisture to the second sheet of film before it is sealed to the first sheet of film to form the seal areas.

5 The seal area between the inner and outer compartments preferably has a width of from 1 to 10 mm, most preferably from 1.5 to 4 mm.

Typically the outer compartment(s) will have an area in the first plane of from 100 to 5000 mm², more preferred from 400 to 4000 mm², most preferred from 800 to 3500 mm² and the inner compartments will have an area in the first plane of from
10 50 to 1200 mm², more preferred from 100 to 800 mm², most preferred from 150 to 550 mm².

The shape of the outer compartment or compartments taken together in the first plane comprises curved and generally straight lines. The preferred shape for the
15 outer compartment is generally rectangular. By generally rectangular is meant that the plan view of the shape has rounded corners. Furthermore, the sides of the rectangle may be slightly curved due to relaxation of the capsule on removal from the mould. For example the outer sides of the outer compartment may be slightly concave so the capsule is wider near to the corners than it is in the centres
20 of the sides. Capsule shapes with the outer compartment based on a rectangle with rounded corners are preferred because the polyvinyl alcohol film seals around the outer compartment may then easily be slit or cut to separate capsules from one another. The substantially constant cross section of the outer compartment then projects this shape inwardly to make the inner compartment
25 also generally rectangular.

Preferably each compartment has a maximum depth of from 5 to 40 mm, more preferred from 8 to 35 mm, most preferred from 9 to 15 mm. When the outer compartment contains liquid and the inner compartment contains granular solid
30 material the depth of the outer compartment may be greater than the depth of the

- 12 -

inner compartment. The result of such smaller depth inner compartment(s) is that the outer compartment(s) protect the inner compartment(s), not only by surrounding them in the first plane, but also by reducing the chance that the inner compartments come into contact with outer compartments of other capsules when the capsules are stored. This is a particular benefit when the inner compartments contain a dry powder and/or granular part of the detergent composition which needs to be kept as separated as possible from the liquid compartments. The ratio of the deepest compartment to the least deep compartment may be from 5:1 to 1:1, more preferred 3:1 to 1.1:1, most preferred from 2:1 to 1:1. The depth may be considered in this context to be either the maximum draw depth into the mould or the total depth perpendicular to the first plane after the first film and second films have relaxed to form the finished capsule: the two ratios are substantially the same.

In one embodiment the depths of the mould cavities for the inner and outer compartments are approximately the same. In another embodiment the inner compartment is deeper than the outer compartment; this can be advantageous especially when powders are to be filled into the inner compartment.

If desired the release time of the parts of the detergent composition in each compartment can be adjusted by altering aspects of the capsule shape and manufacturing process. For example, by changing the draw depth relative to the compartment width a compartment has the thickness of its film adjusted, which in turn affects the time for rupture and also dissolution in use.

The ratio of areas in the first plane of the outer compartment(s) to the inner compartment(s) may be from 20:1 to 1:1, more preferably from 10:1 to 1.2:1, most preferably from 8:1 to 2:1.

- 13 -

The compartments may be shaped in such manner that the average film-thickness of the inner and outer compartments differ. If this is the case it is preferred for the inner compartment(s) to be thinner than the outer compartment(s). Preferably at least four measuring points are taken per compartment to calculate the average.

5

Suitable methods to reduce the average film thickness of a compartment are known in the art.

Preferably the first film thickness (pre thermoforming) is from 50 to 150

10 micrometer, more preferably from 60 to 120 micrometer, most preferably from 80 to 100 micrometer. After capsule manufacture generally the average thickness of the first film will be from 30 to 90 micrometer, more preferably from 40 to 80 micrometer.

15 The second film is typically of a similar type to that used for the first film, but slightly thinner, preferably from 50 to 75 micron. In an advantageous embodiment of the invention the ratio of thickness of the first film to the thickness of the second film is from 1:1 to 2:1. Advantageously the initial thickness for the second film may be from 20 to 100 micrometer, more preferably from 25 to 80 micrometer,
20 most preferably from 30 to 60 micrometer.

A preferred thermoforming process uses a rotary drum on which the forming cavities are mounted. A vacuum thermoforming machine that uses such a drum is available from Cloud LLC. The capsules according to the invention could also be
25 made by thermoforming on a linear array of cavity sections. Machines suitable for that type of process are available from Höfliger. The following example description is focussed onto the rotary process. A skilled person will appreciate how this would be adapted without inventive effort to use a linear array process.

30

- 14 -

Detergent composition

The detergent composition may be any type of cleaning composition for which it is desirable to provide a dose thereof in a water-soluble capsule. The multi-

5 compartment capsules comprise at least two different parts of the detergent composition. Preferably one part of the detergent composition is particulate; and another is a liquid.

10 Suitable detergent compositions that may be split into different components for use in the present invention include those intended for laundry (fabric cleaning, softening and/or treatment) or machine dishwashing. Preferred are laundry compositions, particularly laundry cleaning compositions.

15 The multi-compartment capsules comprise in at least two compartments at least two different parts of a detergent composition which, when combined, make up the full detergent composition. By that is meant that the formulation of each of the parts of the detergent composition is different either in its physical form, its composition or its colour. Sometimes it will be sufficient to only have minor differences between the parts of the detergent composition e.g. colour, perfume
20 etc. Often, however, it will be advantageous to have visible differences, for example a clearly different physical form of the detergent composition. In this context suitably one part of the composition in one compartment may, for example, be a solid (e.g. a particulate or powdered formulation) while another part of the composition in another compartment may be a liquid or a semi-solid.

25 The smaller central compartment may comprise sequestrants, enzymes, bleach catalysts, perfume, builders etc, most preferably in granular form.

Advantageously the outer compartment(s) of the multi-compartment capsule will be filled with liquids. By filled it is meant that the compartment contains liquid and
30 a gas bubble. The presence of the gas bubble provides some protection from

- 15 -

compression of the compartment due to its compressibility. The gas is preferably air trapped in the compartment during manufacture. Also advantageously the inner compartments of the multi-compartment capsule will contain granular material. To maintain the granular material in a free flowing and easily dispersible state it is preferable that the inner compartments are not completely filled. I.e. they, like the liquid compartments, have a visible amount of air trapped inside them during manufacturing and subsequently retained in the finished capsule. We have found that such partially filled powder cavities provide a number of advantages including better dispersal of the contents on dissolution and a sensory result when the loose powder is shaken and makes an engaging noise audible to a consumer. The liquid compartment and the granular compartment are separated by the flat seal area as described above. Preferred liquids have a viscosity in the range 100 to 1000 cP.

- 15 A liquid part of the composition in a compartment preferably has a low water content of less than 10 wt%, more preferably from 0.5 to 9 wt% water, most preferably from 1 to 7 wt%.

- 20 A particulate part of the composition in a compartment preferably has some moisture in the granules to avoid the film drying out and becoming brittle. 1 to 5 wt% moisture is preferred. The particles may be prepared by granulation and may contain a mixture of ingredients. It is preferred that they do not contain any organic detergent surfactant as it may cause the granules to stick together such that they disperse poorly on dissolution of the capsule. Suitable granulation methods are well known in the art. The granulated particles may be optionally mixed with other materials to form the particulate composition. The granules may be partially dyed to make a speckled material, or fully dyed to render the compartment full of coloured material.

- 16 -

Preferably the particulate composition has a bulk density measured by a tap down method as known in the art of at least 400 g/litre, preferably at least 500 g/litre, and most preferably at least 600 g/litre.

5 Surfactants

The detergent composition may comprise one or more organic surfactants. Many suitable detergent-active compounds are available and are fully described in the literature, for example, in "Surface-Active Agents and Detergents", Volumes I and
10 II, by Schwartz, Perry and Berch.

The organic surfactant may be anionic (soap or non-soap), cationic, zwitterionic, amphoteric, nonionic or mixture of two or more of these. The preferred organic surfactants are mixtures of soap, synthetic non-soap anionic and nonionic
15 compounds optionally with amphoteric surfactant.

Anionic surfactant may be present in an amount from 0.5 to 50 wt%, preferably from 2 wt% or 4 wt% up to 30 wt% or 40 wt% of the detergent composition. Suitable examples include alkyl benzene sulphonates, particularly sodium linear
20 alkyl benzene sulphonates having an alkyl chain length of C₈-C₁₅; olefin sulphonates; alkane sulphonates; dialkyl sulphosuccinates; and fatty acid ester sulphonates.

Suitable nonionic surfactant compounds include in particular the reaction products
25 of compounds having a hydrophobic group and a reactive hydrogen atom, for example, aliphatic alcohols, acids, amides or alkyl phenols with alkylene oxides, especially ethylene oxide.

Specific nonionic surfactant compounds are alkyl (C₈₋₂₂) phenol-ethylene oxide
30 condensates, the condensation products of linear or branched aliphatic C₈₋₂₀

- 17 -

primary or secondary alcohols with ethylene oxide, and products made by condensation of ethylene oxide with the reaction products of propylene oxide and ethylene-diamine.

- 5 In a fabric washing detergent composition, these organic surfactants preferably comprise 5 to 50 wt% of the detergent composition. In a machine dishwashing composition, organic surfactant is likely to constitute from 0.5 to 8 wt% of the detergent composition and preferably consists of nonionic surfactant, either alone or in a mixture with anionic surfactant.

10

Builders and sequestrants

The detergent compositions may contain a so-called detergency builder which serves to remove or sequester calcium and/or magnesium ions in the water.

15

Soluble builder may be added to a liquid part of the composition. For example sodium citrate or a soluble sequestrant, for example, Dequest 2066, which may also assist with stabilising the liquid.

- 20 A water soluble builder may alternatively or additionally form part of the granular or solid part of the composition. A material beneficially provided as a solid is HEDP which is difficult to dissolve in the type of non aqueous liquid typically utilised in the liquid part of the composition.

- 25 The builder or sequestrant material is preferably fully soluble so as to eliminate the possibility of unwanted and unsightly residues on fabrics. For that reason Alkali metal aluminosilicates are not favoured .

Non-phosphorus water-soluble detergency builders may be organic or inorganic.


- 30 Inorganic builders that may be present include alkali metal (generally sodium)

- 18 -

carbonate; while organic builders include polycarboxylate polymers, such as polyacrylates, acrylic/maleic copolymers, and acrylic phosphonates, monomeric polycarboxylates such as citrates, gluconates, oxydisuccinates, glycerol mono- di- and trisuccinates, carboxymethyloxysuccinates, carboxymethyloxymalonates, dipicolinates and hydroxyethyliminodiacetates. Electrolytes such as sodium carbonate are not preferred due to the way they suppress the solubility of polyvinylalcohol.

Bleach System

The detergent compositions may contain a bleach system. This preferably consists of an air bleaching catalyst. For example the catalyst being a ligand of the formula (I) complexed with a transition metal, selected from Fe(II) and Fe(III),



Where R1 and R2 are independently selected from:

C1-C4-alkyl,

C6-C10-aryl, and,

a group containing a heteroatom capable of coordinating to a transition metal, wherein at least one of R1 and R2 is the group containing the heteroatom; preferably at least one of R1 or R2 is pyridin-2-ylmethyl. More preferably the catalyst is one in which R1 is pyridin-2-ylmethyl. Most preferably R1 is pyridin-2-ylmethyl and R2 is methyl;

- 19 -

R3 and R4 are independently selected from hydrogen, C1-C8 alkyl, C1-C8-alkylene-O-C1-C8-alkyl, C1-C8-alkylene-O-C6-C10-aryl, C6-C10-aryl, C1-C8-hydroxyalkyl, and $-(CH_2)_nC(O)OR_5$;


- 5 wherein R5 is independently selected from: hydrogen, C1-C4-alkyl, n is from 0 to 4, and mixtures thereof; preferably $R_3=R_4=-C(O)OMe$ and,

- each R is independently selected from: hydrogen, F, Cl, Br, hydroxyl, C1-C4-alkylo-, $-NH-CO-H$, $-NH-CO-C1-C4-alkyl$, $-NH_2$, $-NH-C1-C4-alkyl$, and C1-C4-alkyl; preferably each R is hydrogen,
- 10

X is selected from $C=O$, $-[C(R_6)_2]_y-$ wherein Y is from 0 to 3, preferably 1, each R6 is independently selected from hydrogen, hydroxyl, C1-C4-alkoxy and C1-C4-alkyl preferably X is $C=O$.

15

Most preferably the catalyst is $[(Fe(N_2py_3o)Cl)Cl]$ with structure (II):



- Also known as Iron(1+), chloro[rel-1,5-dimethyl (1R,2S,4R,5S)-9,9-dihydroxy-3-methyl-2,4-di(2-pyridinyl-κN)-7-[(2-pyridinyl-κN)methyl]-3,7-
- 20

- 20 -

diazabicyclo[3.3.1]nonane-1,5-dicarboxylate- κ N3, κ N7]-, chloride (1:1), (OC-6-63)-
[CAS Registry Number 478945-46-9].

To avoid possible gassing of ingredients it is preferred to avoid the use of persalt
5 or peracid bleaching species in the capsules.

Further optional ingredients

Detergency enzymes may be employed in the compositions. If included in
10 particulate form as granules, then they optionally have a protective coating.

The compositions may also contain a fluorescer (optical brightener), for example,
Tinopal (Trade Mark) DMS or Tinopal CBS available from Ciba-Geigy AG, Basel,
Switzerland. Tinopal DMS is disodium 4,4'-bis-(2-morpholino-4-anilino-s-triazin-6-
15 ylamino) stilbene disulphonate; and Tinopal CBS is disodium 2,2'-bis-(phenyl-
styryl) disulphonate.

An antifoam material is advantageously included when organic surfactant is
present; especially if the detergent composition is primarily intended for use in
20 front-loading drum-type automatic washing machines. Soap is a suitable anti-
foam.

It may also be desirable that the composition comprises an amount of an alkali
metal silicate. A detergent composition for machine dishwashing advantageously
25 comprises at least 20 wt% silicate.

Further ingredients which can optionally be employed in laundry detergent
compositions of the invention include antiredeposition agents such as sodium
carboxymethylcellulose, straight-chain polyvinyl pyrrolidone and the cellulose

- 21 -

ethers such as methyl cellulose and ethyl hydroxyethyl cellulose, fabric-softening agents; perfumes; and colorants or coloured speckles.

Capsule material

5

The capsule is produced from a water-soluble film comprising polyvinyl alcohol or a polyvinyl alcohol derivative, i.e. a substantially uniform material. Such film materials can for example be produced by a process of blowing or casting.

- 10 The water-soluble film can also contain plasticizers, antifoams, anti-oxidants, surfactants, perfumes and the like.

Suitable films include Monosol M4045 and Monosol M8045 (75, 82, 88 & 90 micron) & Aicello PT films (PT 75 & 90).

15

The multi-compartment capsules are particularly suitable for use in (fabric) washing machines and in dishwashing machines amongst other applications. They can also be used in manual laundry and dishwashing operations.

- 20 In use the capsules according to the invention are preferably, and conveniently, placed directly into the liquid which will form the wash liquor or into the area where this liquid will be introduced. The capsule dissolves on contact with the liquid, thereby releasing the detergent composition from the separate compartments and allowing them to form the desired wash liquor.

- 25 It is a particular advantage of the inventive capsules that they may alternatively be placed into a dispensing drawer of the type found in automatic laundry washing machines where water flows through the drawer. Surprisingly the capsules have been found to dispense effectively from such drawers.

- 22 -

A further unexpected advantage of the rectangular central compartment shape and the two compartment variant of the capsule is that the capsule is able to dissolve and disperse even if only minimal amounts of water fall onto it in the washing process. It seems that the volume of the recess combined with the
5 thickness and type of the film is critical for this effect to be seen.

EXAMPLES

The invention will now be further described with reference to the following non-
10 limiting examples and with reference to the drawings, of which:

Figure 1 is a plan and side view of a prior art two-compartment capsule,
Figure 2 is a plan and side view of a further prior art two-compartment capsule,
Figure 3 is a pictorial view of a cavity section used for thermoforming the base film
15 to obtain a two-compartment rectangular capsule according to the invention,
Figure 4 is a view of the drum of a rotary thermoforming machine showing the cutting blades,
Figure 5 is a side elevation of the drum area of a rotary thermoforming machine,
Figure 6 is a plan view of a rectangular two-compartment capsule with inner
20 granule containing compartment, and
Figure 7 is a three dimensional view of a rectangular two-compartment capsule with the compartment filled with granules.

Figure 1 shows a prior art type of multi-compartment thermoformed detergent
25 capsule. The larger compartment 1 and the smaller compartment 2 may be partially filled with, for example, a liquid and a powder part of a detergent composition. After the second film 3 is sealed over the surface, the capsule is released from its mould and the second film will tend to bulge upwards as the first film relaxes. A known problem with this capsule is that it can fold along the flat

- 23 -

seal area. This makes it difficult to handle by a consumer and also creates handling difficulties during manufacture and packing of the capsules.

Figure 2 shows a different type of prior art two-compartment soluble capsule. The large rectangular compartment 5 completely surrounds a much smaller circular plan compartment 6. The problems with this capsule are that the small compartment is not easily filled with granular material and that the variable cross section of the larger compartment imparts stresses to the capsule which cause it to distort after it is removed from the mould. Besides being unsightly, this distortion causes these capsules to fit less efficiently into a pack.

Figure 3 shows a cavity section used to thermoform a first film to manufacture a capsule having an inner and an outer compartment. Each cavity section has an inner rectangular cavity 10 and an outer rectangular ring cavity 11. Each cavity is provided with a number of ducts 12, 13 to which may be applied a vacuum.

Figure 4 shows a plurality of such cavity sections arranged in a rectangular array 30 on the outside of a rotary cylindrical drum with a horizontal axis 31.

Figure 5 shows the rotary cylindrical drum 40 from the side. The first film 41 is fed from a supply roll (not shown) over a heating roller (not shown) which has a nominal surface temperature of between 90 and 150°C. When the first film used is Aicello PT90 the heating roller temperature is maintained between 120 and 140°C). Immediately after passing over the heating roller, the hot base film is fed onto the cavity section which is part of an array of such sections around a rotary drum. As shown in Figure 4 the rectangular cavity sections are aligned with the longer of their sides in the direction of rotation of the drum.

Rotation of the cylinder so the cavities reach point 42 ensures that the heated first film fully covers the cavities in the cavity section. At point 42 a vacuum is then

- 24 -

applied to the cavity section through its ducts. The vacuum is applied simultaneously to all the ducts. The vacuum pulls the first film into the cavities 10 and 11 (as shown in figure 3) and holds it there. A uniform thermoformed base film outer cavity shape is achieved due to the uniform cross-section of outer cavity 11.

We have found that it is important for the film to retain some elasticity at this stage. This leads to a tighter capsule which is preferred for ongoing line handling and robustness as well as consumer perception.

Once the cavities are thermoformed and held in place with the vacuum, the inner powder compartment 10 is filled first. This is conveniently done using a micro powder auger (not shown) located at a point 44, just before the cylinder reaches its higher position 45. For an inner compartment capacity of approx 5.5 ml the fill volume is aimed at approx 3.5 to 4ml (64-73%). The auger delivers the powder to the cavity along the centre line and the advantage of a rectangular cavity is that the distance that the powder falls into the base of the cavity remains roughly constant for the entire fill time as the cavity 10 moves past the auger. Because the powder is filled on a slight incline and due to the way powder forms an inverted V shape in the cavity the maximum level of fill is less than 100%.

The outer liquid compartment 11 is filled second. This is done by a single filling pump with a split nozzle. The liquid is designed to fill down the two long sections of the cavity ring and that is why they are arranged to be aligned with the direction of rotation of the drum. Fill volume vs. brimful volume is aimed at a minimum of 80%. I.e. for a 28 ml liquid fill the cavity volume is thus at most 35 ml. Filling is done at the apex of the cylinder 45.

Immediately after filling of the liquid compartment the second film 46 is brought into position over the filled cavities. Immediately before this the second film has

- 25 -

been passed through a water bath (not shown). This makes the lower surface of the second film 46 wet which acts as the mechanism for sealing the second film to the first film where it contacts it; thus forming the seal areas. The second film is a similar type to that used for the first film but is the slightly thinner 60 micron

5 Aicello. The seal area is made secure by pressure application of a sealing roller at position 47.

Post sealing, the filled capsule is cut from the sheet at position 48. This is achieved by horizontal cuts from cylindrical cutter 32 and vertical cuts from static
10 knife blades 33 as shown in Figure 3.

Figure 6 is a plan view of a finished capsule 50. The outer compartment 51 and inner compartment 52 are separated by the continuous flat seal area 53. The rounded corners of the outer compartment 54 and the longer sides 55 and shorter
15 sides 56 of the outer compartment are projected to create the rectangular inner compartment 52. The cut seals around the outer compartment 57 are rectangular but are shown to have some distortion where the material has become corrugated. This is more clearly visible as 60 in Figure 7. Also in Figure 7 the way that the inner granule filled compartment 61 does not protrude above the
20 outer liquid filled compartment 62 and the air bubble in the liquid compartment 63 is visible.

The advantage of a rectangular capsule over a square or other shaped capsule is twofold. First the choice of a rectangle leads to advantages filling the central
25 compartment, especially if it is of comparatively low volume (say 20% of the size of the outer compartment) and most especially if it is filled with a powder component. Second the total seal area can be reduced. There is less waste film due to the selection of a shape with rectangular or square plan - compared say to a circular plan view – because the film must be cut in a square or rectangular
30 shape. This either leaving large areas of outer seal or else requiring a separate

- 26 -

and costly trimming operation, and resulting waste or recycle of the trimmings. Also, due to the fact that the cutting accuracy is greater for the seals running in the direction of movement of the capsule during manufacture a rectangular shape reduces the area of seals on each capsule and may at the same time increase

5 film utilisation

Experiments to show the advantages of the capsules

Example 1 - Dissolution tests

10

In dissolution tests, the liquid compartment of the capsule ruptures quicker than a conventional single compartment thermoformed capsule containing a laundry liquid, thus releasing the liquid contents more quickly.

15 Example 2 – Drawer dispensing

A capsule as shown in Figure 6 made from polyvinyl alcohol films and with a liquid filled outer compartment according to the invention was put into the drawer of a Zanussi machine on a 40°C cotton program. This program allows water through
20 the drawer at ambient temp. After the first inlet (30+ seconds) the capsule was still complete with no signs of dissolving. After the second water inlet (40+ seconds) the capsule was completely gone with no film, liquid or powder residues left. It was further observed that the load in the machine was producing a good foam, confirming that the capsule had gone into the drum and started dissolving.

25

The same procedure was done using a commercially available single compartment Ariel liquitab capsule. The whole capsule was still in the drawer after the first and second inlet of water and was still there 30 mins later. Although it had started to deform none of the liquid had come out of the film.

30

- 27 -

Example 3 - Capsule water ingress

This study looked at benefit of the capsule design according to the invention compared to prior art capsules, in terms of rate of water ingress and liquid release
5 when wet from above.

The capsule according to the invention was compared with commercially available Rectangular (Persil from Unilever), Square (Ariel from P&G) , Multi-compartment Stacked Tide Pods 3 in 1 from P&G and Side-by-side two compartment capsules
10 Persil Duo from Henkel.

First it was determined that 8g of water could be held in the “well” between the inner and outer compartments of a capsule according to the invention. Then to observe the effect of exposure to this amount of water sprinkled from above onto
15 each capsule the capsule to be tested was placed on top of an upturned beaker, allowing excess water to flow away as if the capsule was on top of a load of washing. Water was then poured over the capsule, and observations made.

In order to ensure this was a stress test 16g of water was also used when testing
20 the prior art commercially available capsule designs. The same sample placement and method of assessment was used throughout, with capsules arranged to maximise water retention.

Capsule according to the Invention (8g) results

25 Water ingress (8g): Almost immediate
Liquid flow: 15 seconds

Persil Duo (16g) results

Water ingress (16g): 25 seconds
30 Liquid flow: Minimal after 1 minute

- 28 -

Persil Duo (8g) results

Water ingress (16g): None
Liquid flow: None at 1 minute
Observation after 2 mins: No water ingress or liquid flow

5

Persil (rectangle) (16g) results

Water ingress (16g): None
Liquid flow: None at 1 minute
Observation after 2 mins: No water ingress or liquid flow

10

Ariel Excel Tabs (square) (16g) results

Water ingress (16g): None
Liquid flow: None at 1 minute
Observation after 2 mins: No water ingress or liquid flow

15

Tide Pods (16g) results

Water ingress (16g): None
Liquid flow: None at 1 minute
Observation after 2 mins: No water ingress or liquid flow

20

Observation summary

8g is enough water to induce considerable ingress and product flow after just 25 seconds with the rectangular well two-compartment capsule design.

25

Commercial liquid two-compartment Persil Duo capsules (from Henkel) are similar to the prior art two-compartment capsules of Figure 1, they showed only minimal water ingress and liquid flow after 60 seconds. Using an 8g water dose with Persil Duo produces no water ingress and liquid flow, even after 2 minutes.

30

- 29 -

From this test it can be seen that only the capsule design according to the present invention, with a well created by the inner and outer compartments and the continuous seal that joins them together, captures enough water and has a large enough surface area of film exposed to that captured water to give the required level of dispensing under sparse water conditions. The generally rectangular shape of the compartments increases the volume of the well and the surface area of the film exposed to the captured water. The well of the capsule design can therefore increase the speed of product dispersion. The prior art commercially available capsule designs provided less water ingress and liquid flow, even with double water delivery and double time of exposure.

CLAIMS

1. A multi-compartment water-soluble capsule thermoformed from two sheets of water-soluble film, the capsule comprising a least two compartments with a different part of a detergent composition in each compartment, the two sheets of film being sealed together to form seal areas around each compartment, all the seal areas lying substantially in a first plane;
- the capsule having at least one larger volume outer compartment and at least one smaller volume inner compartment generally enclosed in the first plane by the outer compartment(s), the outer compartment(s) being separated from the inner compartment(s) by a continuous partition seal area which is substantially rectangular and lies in the first plane,
- the outer compartment(s) having a generally rectangular outer perimeter with rounded corners and a substantially uniform cross-section taken along a plane perpendicular to the first plane and perpendicular to the inner seal separating the inner and outer compartments.
2. A capsule according to claim 1 where if there is more than one inner compartment then each inner compartment is separated by a partition seal also lying in the first plane and formed from the two sheets of film.
3. A capsule according to any preceding claim wherein if there are also multiple outer compartments then the partition seals for those outer compartments are also in the first plane and there are two such outer partition seals for each additional outer compartment.

- 31 -

4. A capsule according to any preceding claim wherein when present the outer partition seals do not align with any inner partition seals present.
- 5 5. A capsule according to any preceding claim in which there is only one inner compartment.
6. A capsule according to any preceding claim in which the inner compartment(s) contain a particulate part of the detergent composition, preferably granular.
- 10 7. A capsule according to claim 6 in which the inner compartment(s) are shallower than the outer compartment(s) on at least one side of the capsule.
- 15 8. A capsule according to any preceding claim in which the substantially uniform cross-section of the outer compartment(s) is substantially circular.
9. A capsule according to any preceding claim in which the outer compartment(s) have a constant distance between their inner and outer boundaries in plan view.
- 20 10. A capsule according to any preceding claim which has a single, substantially rectangular in plan, inner compartment located at the centre of the capsule and a single outer compartment extending circumferentially and continuously around the inner compartment and defining a uniform width separating seal and a uniform width of the outer compartment extending from the inner compartment.
- 25

- 32 -

11. A capsule according to any preceding claim in which the multi-compartment capsule has its outer compartment(s) filled with liquid parts of the detergent composition and its inner compartment(s) filled with free flowing particulate parts of the detergent composition.

5

12. A capsule according to any preceding claim in which there is a single liquid part of the detergent composition in a single outer compartment and a single particulate part of the detergent composition in a single substantially rectangular inner compartment.

10

13. A capsule according to any preceding claim comprising at least one compartment partially filled with free flowing particles and the movement of the particles against the film of the compartment makes an audible noise when the capsule is shaken.

15

14. A capsule according to any preceding claim in which the water-soluble film is polyvinyl alcohol.

20

15. A capsule according to any preceding claim in which the water-soluble film has a thickness of from 50 to 100 micron.

16. A laundry washing process whereby a capsule according to any preceding claim is dispensed from a washing machine drawer.

25

17. A laundry washing process whereby a capsule according to any preceding claim is placed on the washing inside a washing machine.

18. A process according to claim 17 in which the washing machine has a spray system.

30

1/4

Fig. 1






Fig. 2



2/4

Fig. 3



3/4

Fig. 4





Fig. 5



4/4

Fig. 6





Fig. 7



INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/061858

A. CLASSIFICATION OF SUBJECT MATTER
INV. B65D65/46 C11D17/00 C11D17/04
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B65D C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 374 580 A (RECKITT BENCKISER [GB]) 23 October 2002 (2002-10-23) figure 4	1-18
A	----- WO 2009/056861 A1 (RECKITT BENCKISER NV [NL]; RECKITT BENCKISER UK LTD [GB]; AICH SAUMITR) 7 May 2009 (2009-05-07) figure 1 page 3, line 6 - line 14 page 5, line 21 - page 6, line 2 page 15, line 16 - line 20 page 16, line 5 - line 9 claims	1-18
A	----- US 2011/250241 A1 (DUFFIELD PAUL JOHN [GB] ET AL) 13 October 2011 (2011-10-13) claims figure 2 -----	1-18



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 September 2014

Date of mailing of the international search report

29/09/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Culmann, J

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/061858

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2374580	A	23-10-2002	AT 425099 T 15-03-2009
		CA 2444737 A1 31-10-2002	
		EP 1381544 A1 21-01-2004	
		ES 2322695 T3 25-06-2009	
		GB 2374580 A 23-10-2002	
		US 2004115375 A1 17-06-2004	
		US 2005263428 A1 01-12-2005	
		WO 02085736 A1 31-10-2002	
WO 2009056861	A1	07-05-2009	EP 2214886 A1 11-08-2010
			US 2013181382 A1 18-07-2013
			WO 2009056861 A1 07-05-2009
US 2011250241	A1	13-10-2011	AR 029772 A1 16-07-2003
			AT 273868 T 15-09-2004
			AT 356045 T 15-03-2007
			AU 780424 B2 17-03-2005
			AU 1647001 A 30-05-2001
			BR 0015617 A 10-09-2002
			CA 2391613 A1 25-05-2001
			CN 1409682 A 09-04-2003
			CN 1473742 A 11-02-2004
			DE 20022487 U1 13-12-2001
			DE 60013165 D1 23-09-2004
			DE 60013165 T2 11-08-2005
			DE 60033864 T2 22-11-2007
			EP 1232100 A1 21-08-2002
			EP 1447343 A2 18-08-2004
			EP 1457431 A2 15-09-2004
			EP 1647494 A2 19-04-2006
			EP 2266889 A2 29-12-2010
			ES 2222253 T3 01-02-2005
			ES 2279233 T3 16-08-2007
			GB 2358382 A 25-07-2001
			GB 2370552 A 03-07-2002
			GB 2370553 A 03-07-2002
			GB 2370554 A 03-07-2002
			JP 4989835 B2 01-08-2012
			JP 2003327270 A 19-11-2003
			JP 2004500285 A 08-01-2004
			MX PA02004981 A 12-11-2004
			PL 355840 A1 17-05-2004
			US 2003108705 A1 12-06-2003
			US 2004151855 A1 05-08-2004
			US 2008073239 A1 27-03-2008
			US 2008296196 A1 04-12-2008
			US 2009008820 A1 08-01-2009
			US 2010021534 A1 28-01-2010
			US 2011250241 A1 13-10-2011
			WO 0136290 A1 25-05-2001