





May 10, 1932.

E. E. GLOMSTEAD

1,857,854

SANITARY NAPKIN

Filed Feb. 16, 1932



Inventor
Edwin E. Glomstead
By Fisher, Clapp, Soans & Sand Atty's.

UNITED STATES PATENT OFFICE

EDWIN E. GLOMSTEAD, OF MENASHA, WISCONSIN, ASSIGNOR TO INTERNATIONAL CELLUCOTTON PRODUCTS COMPANY, OF CHICAGO, ILLINOIS, A CORPORATION OF DELAWARE

SANITARY NAPKIN

REISSUED

Application filed February 16, 1932. Serial No. 593,360.

This invention relates to an improvement in the construction of a sanitary napkin and this application is in part a continuation of my copending application, Serial No. 573,772, filed November 9, 1931.

The principal object of this invention is to provide a sanitary napkin of superior form fitting characteristics, that is to say, to provide a sanitary napkin in which the pad element is so formed that its end portions will have a decided tendency to maintain a normal flat condition and to fit snugly against the body without protruding sufficiently to cause any anxiety to the wearer that the presence of the napkin will be detectable by reason of any bulge or the like in the dress of the person. The improved construction is of particular advantage when tight fitting dresses are worn but the increased comfort of a smooth and close fitting sanitary napkin renders the improvement advantageous and desirable without regard to the style of clothing worn.

Other objects and advantages of the invention will be understood by reference to the following specification and accompanying drawings in which is illustrated a sanitary napkin embodying a selected form of the improved construction.

In the drawings, Fig. 1 is a perspective, a portion of the wrapper being unfolded to disclose the interior construction.

Fig. 2 is a section on the line 2—2 of Fig. 1.

Fig. 3 is a section on the line 3—3 of Fig. 1.

Fig. 4 is a perspective of the pad element alone bent to substantially the shape which it takes when worn.

Fig. 5 is an end elevation of the pad element when in the condition illustrated in Fig. 4, and

Fig. 6 is a side elevation of one end portion of the pad element.

Referring now to the drawings, the improved sanitary napkin therein illustrated includes a pad element 8 which is surrounded by a gauze or like textile material wrapper 9. The pad element 8 is elongated and has rounded ends as indicated at 10 and the gauze wrapper is also elongated and folded longitudinally around the pad element so that its

side marginal portions 11 and 12 overlap the top side of the pad. The gauze wrapper extends considerably beyond the ends of the pad element 8 to form attachment flaps such as indicated at 9^a.

The pad element 8 is preferably formed of a plurality of relatively superposed layers or sheets of cellulose wadding, i. e. crepe paper. Such a pad has a very high capacity for absorption and it has been found to be very soft and flexible so that it is well-adapted for sanitary napkin purposes.

According to the present invention, the end portions of the pad element are treated so as to stiffen the end portions transversely and preferably to taper the normal thickness of the pad to a comparatively thin end. This result may be effected by compressing or compacting the ends of the pad in areas spaced slightly inwardly from the end edge of the napkin as indicated at 13. As clearly shown in Fig. 3, a marginal edge portion 14 is not directly compressed but is nevertheless reduced in thickness to a marked extent as an incident to the compacting of the area 13. Hence, the edge of the pad retains a certain degree of fluffiness or softness.

By compressing the end portions of the pad in the manner just described, the sheets or layers of paper which form the pad are united, in effect welded, together so that they will resist separation and relative slippage both longitudinally and transversely. In this way the area 13 is also stiffened so that it tends to retain its normal flat condition.

When a napkin embodying the described pad construction is applied, the body portion of the pad element intermediate its ends is folded longitudinally and downwardly so as to present a smooth, convex top surface and the opposite ends of the pad are turned upwardly to lie flat against the body. The compressed and stiffened area 13 serves to maintain the end portions substantially flat so as to avoid any bulging effect at the ends of the pad. As evident from an inspection of Fig. 3, the compacting of the ends of the pad element is preferably effected in such a manner as to maintain the top 16 of the pad substantially flat throughout its length and

so as to effect the tapering of the thickness of the pad at its ends principally on the bottom or outside of the pad element. Hence, when the pad assumes the condition illustrated in Figs. 4, 5 and 6, the tapered portion 17 of the pad assumes a position in which it does not project materially beyond the plane of the extreme end portion of the pad. Hence, bulging does not occur at a point spaced below the extreme end of the pad. The thinness of the extreme ends of the pad also serves to avoid any bulging effect at such extremities.

When a napkin is applied, it is ordinarily suspended from a belt or undergarment to which it is secured at each end either by means of a single buckle, safety pin or other fastening means, thus concentrating the upward draft or pull mainly along the centerline of the gauze wrapper. This centerline pull has a tendency to crease or wrinkle the end portions of the pad, more or less in continuation of the fold of the intermediate portion of the pad. This tendency is effectively resisted by the stiffened area 13 so that the body hugging characteristic of the pad ends is insured.

Changes may be made in the described construction without departing from the spirit of the invention, the scope of which should be determined by reference to the following claim, the same being construed as broadly as possible consistent with the state of the art.

I claim as my invention:—

A sanitary napkin comprising a pad element and a wrapper of textile material, the pad element being formed of a plurality of relatively superposed layers of crepe paper, an area at an end portion of the pad being compacted sufficiently to permanently reduce the thickness of such end portion and to stiffen the same sufficiently to maintain such end portion in substantially flat condition when the napkin is applied.

EDWIN E. GLOMSTEAD.

50

55

60