



(12) **DEMANDE DE BREVET CANADIEN**
CANADIAN PATENT APPLICATION

(13) **A1**

(86) Date de dépôt PCT/PCT Filing Date: 2017/03/29
(87) Date publication PCT/PCT Publication Date: 2017/10/05
(85) Entrée phase nationale/National Entry: 2018/09/07
(86) N° demande PCT/PCT Application No.: US 2017/024716
(87) N° publication PCT/PCT Publication No.: 2017/172892
(30) Priorité/Priority: 2016/04/01 (US62/317,120)

(51) Cl.Int./Int.Cl. *H01G 11/34* (2013.01),
H01G 11/36 (2013.01), *H01G 11/86* (2013.01)
(71) Demandeur/Applicant:
THE REGENTS OF THE UNIVERSITY OF CALIFORNIA,
US
(72) Inventeurs/Inventors:
KANER, RICHARD B., US;
EL-KADY, MAHER F., US;
MOUSAVI, MIR FAZLOLLAH, IR;
HASHEMI, MASUMEH, IR;
RAHMANIFAR, MOHAMMAD S., IR
(74) Agent: AIRD & MCBURNEY LP

(54) Titre : CROISSANCE DIRECTE DE NANOTUBES DE POLYANILINE SUR UN TISSU DE CARBONE POUR DES
SUPERCONDENSATEURS FLEXIBLES ET A HAUTES PERFORMANCES
(54) Title: DIRECT GROWTH OF POLYANILINE NANOTUBES ON CARBON CLOTH FOR FLEXIBLE AND HIGH-
PERFORMANCE SUPERCAPACITORS




FIG. 2

(57) **Abrégé/Abstract:**

The present disclosure further provides an exemplary energy storage device fabricated from rectangular-tube polyaniline (PANI) that is chemically synthesized by a simple and convenient method. The rectangular-tube PANI, as an active material, is synthesized on a functionalized carbon cloth (FCC) as a substrate, and the obtained composite is immobilized on a stainless steel mesh as a current collector. The present disclosure additionally presents a facile technique for the direct synthesis of PANI nanotubes, with rectangular pores, on chemically activated CC.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(10) International Publication Number
WO 2017/172892 A1(43) International Publication Date
5 October 2017 (05.10.2017)

(51) International Patent Classification:

H01G 11/34 (2013.01) *H01G 11/86* (2013.01)
H01G 11/36 (2013.01)

(21) International Application Number:

PCT/US2017/024716

(22) International Filing Date:

29 March 2017 (29.03.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/317,120 1 April 2016 (01.04.2016) US

(71) Applicant: **THE REGENTS OF THE UNIVERSITY OF CALIFORNIA** [US/US]; 1111 Franklin Street, Twelfth Floor, Oakland, California 94607-5200 (US).(72) Inventors: **KANER, Richard, B.**; 481 Almar Avenue, Pacific Palisades, California 90272 (US). **EL-KADY, Maher, F.**; 741 Gayley Avenue Apt. #421, Los Angeles, California 90024 (US). **MOUSAVI, Mir, Fazlollah**; No.12, Alvand 11, Shahrack Jandarmery, P.O. Box: 14637-36144, Tehran (IR). **HASHEMI, Masumeh**; No. 142, Imam Musa Street, Alvand City, P.O. Box: 34314-13876, Qazvin (IR). **RAHMANIFAR, Mohammad, S.**; No. 26, East Shaghae-

gh 24, Shagheiegh Bul. Ferdous Bul., P.O. Box: 14849-13656, Tehran (IR).

(74) Agent: **WITHROW, Benjamin, S.**; Withrow & Terranova, P.L.L.C., 106 Pinedale Springs Way, Cary, North Carolina 27511 (US).(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

[Continued on next page]

(54) Title: DIRECT GROWTH OF POLYANILINE NANOTUBES ON CARBON CLOTH FOR FLEXIBLE AND HIGH-PERFORMANCE SUPERCAPACITORS




FIG. 2

(57) Abstract: The present disclosure further provides an exemplary energy storage device fabricated from rectangular-tube polyaniline (PANI) that is chemically synthesized by a simple and convenient method. The rectangular-tube PANI, as an active material, is synthesized on a functionalized carbon cloth (FCC) as a substrate, and the obtained composite is immobilized on a stainless steel mesh as a current collector. The present disclosure additionally presents a facile technique for the direct synthesis of PANI nanotubes, with rectangular pores, on chemically activated CC.

WO 2017/172892 A1



SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG). **Published:**

— *with international search report (Art. 21(3))*

DIRECT GROWTH OF POLYANILINE NANOTUBES ON CARBON CLOTH FOR FLEXIBLE AND HIGH-PERFORMANCE SUPERCAPACITORS

CROSS-REFERENCE

[0001] This application claims the benefit of U.S. Provisional Application No. 62/317,120, filed
5 April 1, 2016, which application is incorporated herein by reference.

BACKGROUND

[0002] The development of high-performance energy storage devices has gained significant attention in a broad range of applications. While normal electronic devices progress rapidly, according to Moore's law, batteries have advanced only slightly, mainly due to the limitations of
10 current materials' energy densities and capacities. As such, batteries with a reduced charge time and an increased charge density may have a profound effect on the design and use of portable electronics and renewable energy devices.

SUMMARY

[0003] Provided herein are methods, devices, and systems for growing nanotubes on
15 functionalized carbon cloth. The growing may include the manufacture (or synthesis) of functionalized carbon cloth, the manufacture (or synthesis) of nanotubes and nanostructures, and/or the manufacture (or synthesis) of an electrolyte. Some embodiments provide methods, devices, and systems for the manufacture (or synthesis) of functionalized carbon cloth and/or for the manufacture (or synthesis) of nanotubes and nanostructures and/or for the manufacture (or synthesis) of
20 electrolytes and/or for the manufacture (or synthesis) of supercapacitors.

[0004] A first aspect disclosed herein is a device comprising a functionalized carbon electrode comprising a carbon substrate and a conducting polymer disposed on the carbon substrate.

[0005] In some embodiments, the functionalized carbon electrode comprises a polyaniline functionalized carbon electrode.

25 [0006] In some embodiments, the carbon substrate comprises carbon cloth, carbon fiber, amorphous carbon, glassy carbon, carbon nanofoam, carbon aerogel or any combination thereof.

[0007] In some embodiments, the conducting polymer is a semi-flexible rod polymer. In some embodiments, the semi-flexible rod polymer comprises polyaniline, poly(p-phenylene oxide), poly(p-phenylene sulfide), poly(3,4-ethylenedioxythiophene), polypyrrole, polythiophene, poly(3-

alkythiophene), poly(3-methylthiophene), poly(3-hexylthiophene), or any combination thereof. In some embodiments, the conducting polymer has a nanotube morphology, wherein the nanotube has a cross-sectional shape comprising a rectangle, a square, a circle, or a polygon.

[0008] In some embodiments, the nanotube has a length of about 100 nanometers to about 10,000 nanometers. In some embodiments, the nanotube has a length of at least about 100 nanometers. In some embodiments, the nanotube has a length of at most about 10,000 nanometers. In some embodiments, the nanotube has a length of about 100 nanometers to about 500 nanometers, about 100 nanometers to about 1,000 nanometers, about 100 nanometers to about 2,000 nanometers, about 100 nanometers to about 3,000 nanometers, about 100 nanometers to about 4,000 nanometers, about 100 nanometers to about 5,000 nanometers, about 100 nanometers to about 6,000 nanometers, about 100 nanometers to about 7,000 nanometers, about 100 nanometers to about 8,000 nanometers, about 100 nanometers to about 9,000 nanometers, about 100 nanometers to about 10,000 nanometers, about 500 nanometers to about 1,000 nanometers, about 500 nanometers to about 2,000 nanometers, about 500 nanometers to about 3,000 nanometers, about 500 nanometers to about 4,000 nanometers, about 500 nanometers to about 5,000 nanometers, about 500 nanometers to about 6,000 nanometers, about 500 nanometers to about 7,000 nanometers, about 500 nanometers to about 8,000 nanometers, about 500 nanometers to about 9,000 nanometers, about 500 nanometers to about 10,000 nanometers, about 1,000 nanometers to about 2,000 nanometers, about 1,000 nanometers to about 3,000 nanometers, about 1,000 nanometers to about 4,000 nanometers, about 1,000 nanometers to about 5,000 nanometers, about 1,000 nanometers to about 6,000 nanometers, about 1,000 nanometers to about 7,000 nanometers, about 1,000 nanometers to about 8,000 nanometers, about 1,000 nanometers to about 9,000 nanometers, about 1,000 nanometers to about 10,000 nanometers, about 2,000 nanometers to about 3,000 nanometers, about 2,000 nanometers to about 4,000 nanometers, about 2,000 nanometers to about 5,000 nanometers, about 2,000 nanometers to about 6,000 nanometers, about 2,000 nanometers to about 7,000 nanometers, about 2,000 nanometers to about 8,000 nanometers, about 2,000 nanometers to about 9,000 nanometers, about 2,000 nanometers to about 10,000 nanometers, about 3,000 nanometers to about 4,000 nanometers, about 3,000 nanometers to about 5,000 nanometers, about 3,000 nanometers to about 6,000 nanometers, about 3,000 nanometers to about 7,000 nanometers, about 3,000 nanometers to about 8,000 nanometers, about 3,000 nanometers to about 9,000 nanometers, about 3,000 nanometers to about 10,000 nanometers, about 4,000 nanometers to about 5,000 nanometers, about 4,000 nanometers to about 6,000 nanometers, about 4,000 nanometers to about 7,000 nanometers, about 4,000

nanometers to about 8,000 nanometers, about 4,000 nanometers to about 9,000 nanometers, about 4,000 nanometers to about 10,000 nanometers, about 5,000 nanometers to about 6,000 nanometers, about 5,000 nanometers to about 7,000 nanometers, about 5,000 nanometers to about 8,000 nanometers, about 5,000 nanometers to about 9,000 nanometers, about 5,000 nanometers to about 10,000 nanometers, about 6,000 nanometers to about 7,000 nanometers, about 6,000 nanometers to about 8,000 nanometers, about 6,000 nanometers to about 9,000 nanometers, about 6,000 nanometers to about 10,000 nanometers, about 7,000 nanometers to about 8,000 nanometers, about 7,000 nanometers to about 9,000 nanometers, about 7,000 nanometers to about 10,000 nanometers, about 8,000 nanometers to about 9,000 nanometers, about 8,000 nanometers to about 10,000 In some embodiments, the nanotube has an outer width of about 10 nanometers to about 1,000 nanometers. In some embodiments, the nanotube has an outer width of at least about 10 nanometers. In some embodiments, the nanotube has an outer width of at most about 1,000 nanometers. In some embodiments, the nanotube has an outer width of about 10 nanometers to about 50 nanometers, about 10 nanometers to about 100 nanometers, about 10 nanometers to about 200 nanometers, about 10 nanometers to about 300 nanometers, about 10 nanometers to about 400 nanometers, about 10 nanometers to about 500 nanometers, about 10 nanometers to about 600 nanometers, about 10 nanometers to about 700 nanometers, about 10 nanometers to about 800 nanometers, about 10 nanometers to about 900 nanometers, about 10 nanometers to about 1,000 nanometers, about 50 nanometers to about 100 nanometers, about 50 nanometers to about 200 nanometers, about 50 nanometers to about 300 nanometers, about 50 nanometers to about 400 nanometers, about 50 nanometers to about 500 nanometers, about 50 nanometers to about 600 nanometers, about 50 nanometers to about 700 nanometers, about 50 nanometers to about 800 nanometers, about 50 nanometers to about 900 nanometers, about 50 nanometers to about 1,000 nanometers, about 100 nanometers to about 200 nanometers, about 100 nanometers to about 300 nanometers, about 100 nanometers to about 400 nanometers, about 100 nanometers to about 500 nanometers, about 100 nanometers to about 600 nanometers, about 100 nanometers to about 700 nanometers, about 100 nanometers to about 800 nanometers, about 100 nanometers to about 900 nanometers, about 100 nanometers to about 1,000 nanometers, about 200 nanometers to about 300 nanometers, about 200 nanometers to about 400 nanometers, about 200 nanometers to about 500 nanometers, about 200 nanometers to about 600 nanometers, about 200 nanometers to about 700 nanometers, about 200 nanometers to about 800 nanometers, about 200 nanometers to about 900 nanometers, about 200 nanometers to about 1,000 nanometers, about 300 nanometers to about 400 nanometers, about 300

nanometers to about 500 nanometers, about 300 nanometers to about 600 nanometers, about 300 nanometers to about 700 nanometers, about 300 nanometers to about 800 nanometers, about 300 nanometers to about 900 nanometers, about 300 nanometers to about 1,000 nanometers, about 400 nanometers to about 500 nanometers, about 400 nanometers to about 600 nanometers, about 400 nanometers to about 700 nanometers, about 400 nanometers to about 800 nanometers, about 400 nanometers to about 900 nanometers, about 400 nanometers to about 1,000 nanometers, about 500 nanometers to about 600 nanometers, about 500 nanometers to about 700 nanometers, about 500 nanometers to about 800 nanometers, about 500 nanometers to about 900 nanometers, about 500 nanometers to about 1,000 nanometers, about 600 nanometers to about 700 nanometers, about 600 nanometers to about 800 nanometers, about 600 nanometers to about 900 nanometers, about 600 nanometers to about 1,000 nanometers, about 700 nanometers to about 800 nanometers, about 700 nanometers to about 900 nanometers, about 700 nanometers to about 1,000 nanometers, about 800 nanometers to about 900 nanometers, about 800 nanometers to about 1,000 nanometers, or about 900 nanometers to about 1,000 nanometers.

[0009] In some embodiments, the nanotube has an inner width of about 50 nanometers to about 800 nanometers. In some embodiments, the nanotube has an inner width of at least about 50 nanometers. In some embodiments, the nanotube has an inner width of at most about 800 nanometers. In some embodiments, the nanotube has an inner width of about 50 nanometers to about 100 nanometers, about 50 nanometers to about 300 nanometers, about 50 nanometers to about 400 nanometers, about 50 nanometers to about 500 nanometers, about 50 nanometers to about 600 nanometers, about 50 nanometers to about 700 nanometers, about 50 nanometers to about 800 nanometers, about 100 nanometers to about 300 nanometers, about 100 nanometers to about 400 nanometers, about 100 nanometers to about 500 nanometers, about 100 nanometers to about 600 nanometers, about 100 nanometers to about 700 nanometers, about 100 nanometers to about 800 nanometers, about 300 nanometers to about 400 nanometers, about 300 nanometers to about 500 nanometers, about 300 nanometers to about 600 nanometers, about 300 nanometers to about 700 nanometers, about 300 nanometers to about 800 nanometers, about 400 nanometers to about 500 nanometers, about 400 nanometers to about 600 nanometers, about 400 nanometers to about 700 nanometers, about 400 nanometers to about 800 nanometers, about 500 nanometers to about 600 nanometers, about 500 nanometers to about 700 nanometers, about 500 nanometers to about 800 nanometers, about 600 nanometers to about 700 nanometers, about 600 nanometers to about 800 nanometers, or about 700 nanometers to about 800 nanometers.

[0010] In some embodiments, the surface of the nanotube includes one or more nanostructures. In some embodiments, the one or more nanostructure comprise(s) a nanorod, nanochain, nanofiber, nanoflake, nanoflower, nanoparticle, nanoplatelet, nanoribbon, nanoring, nanosheet, or a combination thereof.

5 **[0011]** In some embodiments, the nanostructure has a length of about 4 nanometers to about 400 nanometers. In some embodiments, the nanostructure has a length of at least about 4 nanometers. In some embodiments, the nanostructure has a length of at most about 400 nanometers. In some
 10 embodiments, the nanostructure has a length of about 4 nanometers to about 10 nanometers, about 4 nanometers to about 25 nanometers, about 4 nanometers to about 50 nanometers, about 4 nanometers to about 75 nanometers, about 4 nanometers to about 100 nanometers, about 4 nanometers to about 200 nanometers, about 4 nanometers to about 300 nanometers, about 4 nanometers to about 400
 15 nanometers, about 10 nanometers to about 25 nanometers, about 10 nanometers to about 50 nanometers, about 10 nanometers to about 75 nanometers, about 10 nanometers to about 100 nanometers, about 10 nanometers to about 200 nanometers, about 10 nanometers to about 300
 20 nanometers, about 10 nanometers to about 400 nanometers, about 25 nanometers to about 50 nanometers, about 25 nanometers to about 75 nanometers, about 25 nanometers to about 100 nanometers, about 25 nanometers to about 200 nanometers, about 25 nanometers to about 300
 25 nanometers, about 25 nanometers to about 400 nanometers, about 50 nanometers to about 75 nanometers, about 50 nanometers to about 100 nanometers, about 50 nanometers to about 200
 30 nanometers, about 50 nanometers to about 300 nanometers, about 50 nanometers to about 400 nanometers, about 75 nanometers to about 100 nanometers, about 75 nanometers to about 200 nanometers, about 75 nanometers to about 300 nanometers, about 75 nanometers to about 400
 nanometers, about 100 nanometers to about 200 nanometers, about 100 nanometers to about 300 nanometers, about 100 nanometers to about 400 nanometers, about 200 nanometers to about 300
 nanometers, about 200 nanometers to about 400 nanometers, or about 300 nanometers to about 400 nanometers.

[0012] In some embodiments, the nanostructure has a width of about 4 nanometers to about 400 nanometers. In some embodiments, the nanostructure has a width of at least about 4 nanometers. In some
 30 embodiments, the nanostructure has a width of at most about 400 nanometers. In some
 embodiments, the nanostructure has a width of about 4 nanometers to about 10 nanometers, about 4 nanometers to about 25 nanometers, about 4 nanometers to about 50 nanometers, about 4 nanometers to about 75 nanometers, about 4 nanometers to about 100 nanometers, about 4 nanometers to about

200 nanometers, about 4 nanometers to about 300 nanometers, about 4 nanometers to about 400 nanometers, about 10 nanometers to about 25 nanometers, about 10 nanometers to about 50 nanometers, about 10 nanometers to about 75 nanometers, about 10 nanometers to about 100 nanometers, about 10 nanometers to about 200 nanometers, about 10 nanometers to about 300 nanometers, about 10 nanometers to about 400 nanometers, about 25 nanometers to about 50 nanometers, about 25 nanometers to about 75 nanometers, about 25 nanometers to about 100 nanometers, about 25 nanometers to about 200 nanometers, about 25 nanometers to about 300 nanometers, about 25 nanometers to about 400 nanometers, about 50 nanometers to about 75 nanometers, about 50 nanometers to about 100 nanometers, about 50 nanometers to about 200 nanometers, about 50 nanometers to about 300 nanometers, about 50 nanometers to about 400 nanometers, about 75 nanometers to about 100 nanometers, about 75 nanometers to about 200 nanometers, about 75 nanometers to about 300 nanometers, about 75 nanometers to about 400 nanometers, about 100 nanometers to about 200 nanometers, about 100 nanometers to about 300 nanometers, about 100 nanometers to about 400 nanometers, about 200 nanometers to about 300 nanometers, about 200 nanometers to about 400 nanometers, or about 300 nanometers to about 400 nanometers.

[0013] In some embodiments, the electrode has an areal capacitance of about 150 millifarads per square centimeters (mF/cm²) to about 750 mF/cm². In some embodiments, the electrode has an areal capacitance of at least about 150 mF/cm². In some embodiments, the electrode has an areal capacitance of at least about 750 mF/cm². In some embodiments, the electrode has an areal capacitance of about 150 mF/cm² to about 250 mF/cm², about 150 mF/cm² to about 350 mF/cm², about 150 mF/cm² to about 450 mF/cm², about 150 mF/cm² to about 550 mF/cm², about 150 mF/cm² to about 650 mF/cm², about 150 mF/cm² to about 750 mF/cm², about 250 mF/cm² to about 350 mF/cm², about 250 mF/cm² to about 450 mF/cm², about 250 mF/cm² to about 550 mF/cm², about 250 mF/cm² to about 650 mF/cm², about 250 mF/cm² to about 750 mF/cm², about 350 mF/cm² to about 450 mF/cm², about 350 mF/cm² to about 550 mF/cm², about 350 mF/cm² to about 650 mF/cm², about 350 mF/cm² to about 750 mF/cm², about 450 mF/cm² to about 550 mF/cm², about 450 mF/cm² to about 650 mF/cm², about 450 mF/cm² to about 750 mF/cm², about 550 mF/cm² to about 650 mF/cm², about 550 mF/cm² to about 750 mF/cm², or about 650 mF/cm² to about 750 mF/cm².

[0014] In some embodiments, the resistance of the electrode decreases after 1,000 folding cycles by about 1% to about 8%. In some embodiments, the resistance of the electrode decreases after

1,000 folding cycles by at most about 8%. In some embodiments the resistance of the electrode decreases after 1,000 folding cycles by about 1% to about 2%, about 1% to about 3%, about 1% to about 4%, about 1% to about 5%, about 1% to about 6%, about 1% to about 7%, about 1% to about 8%, about 2% to about 3%, about 2% to about 4%, about 2% to about 5%, about 2% to about 6%,
5 about 2% to about 7%, about 2% to about 8%, about 3% to about 4%, about 3% to about 5%, about 3% to about 6%, about 3% to about 7%, about 3% to about 8%, about 4% to about 5%, about 4% to about 6%, about 4% to about 7%, about 4% to about 8%, about 5% to about 6%, about 5% to about 7%, about 5% to about 8%, about 6% to about 7%, about 6% to about 8%, or about 7% to about 8%.

[0015] A second aspect disclosed herein is a supercapacitor comprising two or more electrodes,
10 wherein each electrode comprises a functionalized carbon electrode, a current collector, and an electrolyte.

[0016] In some embodiments the functionalized carbon electrode comprises: a carbon substrate comprising carbon cloth, carbon fiber, amorphous carbon, glassy carbon, carbon nanofoam, carbon aerogel, graphene foam or any combination thereof; and a conducting polymer disposed on the
15 carbon substrate, wherein the conducting polymer comprises polyaniline, poly(p-phenylene oxide), poly(p-phenylene sulfide), poly(3,4-ethylenedioxythiophene), polypyrrole, polythiophene, poly(3-alkylthiophene), poly(3-methylthiophene), poly(3-hexylthiophene), or any combination thereof.

[0017] In some embodiments, the functionalized carbon electrode is a polyaniline functionalized carbon electrode.

20 [0018] In some embodiments, the current collector is metallic. In some embodiments, the current collector is ferritic. In some embodiments, the current collector comprises stainless steel, crucible steel, carbon steel, spring steel, alloy steel, maraging steel, weathering steel, tool steel, or any combination thereof.

[0019] In some embodiments, an electrolyte is disposed between the first functionalized carbon
25 electrode and the second functionalized carbon electrode. In some embodiments, the electrolyte is a redox electrolyte. In some embodiments, the electrolyte comprises an acid. In some embodiments, the electrolyte comprises a solvent. In some embodiments, the electrolyte comprises an acid and a solvent. In some embodiments, the acid is a strong acid. In some embodiments, the strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid,
30 p-toluenesulfonic acid, methanesulfonic acid, or any combination thereof.

[0020] In some embodiments, the solvent comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide, nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof.

[0021] In some embodiments, the concentration of the acid is about 0.5 molar (M) to about 2 M. In some embodiments, the concentration of the acid is at least about 0.5 M. In some embodiments, the concentration of the acid is at most about 2 M. In some embodiments, the concentration of the acid is about 0.5 M to about 0.75 M, about 0.5 M to about 1 M, about 0.5 M to about 1.25 M, about 0.5 M to about 1.5 M, about 0.5 M to about 1.75 M, about 0.5 M to about 2 M, about 0.75 M to about 1 M, about 0.75 M to about 1.25 M, about 0.75 M to about 1.5 M, about 0.75 M to about 1.75 M, about 0.75 M to about 2 M, about 1 M to about 1.25 M, about 1 M to about 1.5 M, about 1 M to about 1.75 M, about 1 M to about 2 M, about 1.25 M to about 1.5 M, about 1.25 M to about 1.75 M, about 1.25 M to about 2 M, about 1.5 M to about 1.75 M, about 1.5 M to about 2 M, or about 1.75 M to about 2 M.

[0022] In some embodiments, the electrolyte is aqueous.

[0023] In those embodiments, the supercapacitor has a working potential of about 0.3 volts (V) to about 1 V. In those embodiments, the supercapacitor has a working potential of at least about 0.3 V. In those embodiments, the supercapacitor has a working potential of at most about 1 V. In those embodiments, the supercapacitor has a working potential of about 0.3 V to about 0.4 V, about 0.3 V to about 0.5 V, about 0.3 V to about 0.6 V, about 0.3 V to about 0.7 V, about 0.3 V to about 0.8 V, about 0.3 V to about 0.9 V, about 0.3 V to about 1 V, about 0.4 V to about 0.5 V, about 0.4 V to about 0.6 V, about 0.4 V to about 0.7 V, about 0.4 V to about 0.8 V, about 0.4 V to about 0.9 V, about 0.4 V to about 1 V, about 0.5 V to about 0.6 V, about 0.5 V to about 0.7 V, about 0.5 V to about 0.8 V, about 0.5 V to about 0.9 V, about 0.5 V to about 1 V, about 0.6 V to about 0.7 V, about 0.6 V to about 0.8 V, about 0.6 V to about 0.9 V, about 0.6 V to about 1 V, about 0.7 V to about 0.8 V, about 0.7 V to about 0.9 V, about 0.7 V to about 1 V, about 0.8 V to about 0.9 V, about 0.8 V to about 1 V, or about 0.9 V to about 1 V.

[0024] In those embodiments, after about 1,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by about 4% to about 18%. In those embodiments, after about 1,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by at most about 18%. In those embodiments, after about 1,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by about 4% to about 8%, about 4% to about 10%, about 4% to about 12%, about 4% to about 14%, about 4% to about 16%, about 4% to about 18%, about 8% to about 10%,

about 8% to about 12%, about 8% to about 14%, about 8% to about 16%, about 8% to about 18%, about 10% to about 12%, about 10% to about 14%, about 10% to about 16%, about 10% to about 18%, about 12% to about 14%, about 12% to about 16%, about 12% to about 18%, about 14% to about 16%, about 14% to about 18%, or about 16% to about 18%.

5 [0025] In those embodiments, after about 5,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by about 6% to about 26%. In those embodiments, after about 5,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by at least about 6%. In those embodiments, after about 5,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by at most about 26%. In those embodiments, after about 5,000 cycles of charging, the gravimetric capacitance of the supercapacitor reduces by about 6% to about 10%,
10 about 6% to about 14%, about 6% to about 18%, about 6% to about 22%, about 6% to about 26%, about 10% to about 14%, about 10% to about 18%, about 10% to about 22%, about 10% to about 26%, about 14% to about 18%, about 14% to about 22%, about 14% to about 26%, about 18% to about 22%, about 18% to about 26%, or about 22% to about 26%.

15 [0026] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 1 amps/grams (A/g), of about 300 farads/grams (F/g) to about 1,400 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 1 A/g, of at least about 300 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 1 A/g, of at most about 1,400 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 1 A/g, of about 300 F/g to about 500 F/g, about 300 F/g to about 700 F/g, about 300 F/g to about 900 F/g, about 300 F/g to about 1,100 F/g, about 300 F/g to about 1,400 F/g, about 500 F/g to about 700 F/g, about 500 F/g to about 900 F/g, about 500 F/g to about 1,100 F/g, about 500 F/g to about 1,400 F/g, about 700 F/g to about 900 F/g, about 700 F/g to about 1,100 F/g, about 700 F/g to about 1,400 F/g, about 900 F/g to about 1,100 F/g, about 900 F/g to about 1,400 F/g, or about 1,100 F/g to about 1,400 F/g.
20
25

[0027] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 250 F/g to about 1,200 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at least about 250 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at most about 1,20 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 250 F/g to about 500 F/g, about 250 F/g to about 750 F/g, about 250 F/g to about 1,000 F/g, about 250 F/g to about 1,200 F/g, about
30

500 F/g to about 750 F/g, about 500 F/g to about 1,000 F/g, about 500 F/g to about 1,200 F/g, about 750 F/g to about 1,000 F/g, about 750 F/g to about 1,200 F/g, or about 1,000 F/g to about 1,200 F/g.

[0028] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of about 200 F/g to about 900 F/g. In those embodiments, the

5 supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of at least about 200 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of at most about 900 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of about 200 F/g to about 300 F/g, about 200 F/g to about 400 F/g, about 200 F/g to about 500 F/g, about 200 F/g to about 600 F/g, 10 about 200 F/g to about 700 F/g, about 200 F/g to about 800 F/g, about 200 F/g to about 900 F/g, about 300 F/g to about 400 F/g, about 300 F/g to about 500 F/g, about 300 F/g to about 600 F/g, about 300 F/g to about 700 F/g, about 300 F/g to about 800 F/g, about 300 F/g to about 900 F/g, about 400 F/g to about 500 F/g, about 400 F/g to about 600 F/g, about 400 F/g to about 700 F/g, about 400 F/g to about 800 F/g, about 400 F/g to about 900 F/g, about 500 F/g to about 600 F/g, 15 about 500 F/g to about 700 F/g, about 500 F/g to about 800 F/g, about 500 F/g to about 900 F/g, about 600 F/g to about 700 F/g, about 600 F/g to about 800 F/g, about 600 F/g to about 900 F/g, about 700 F/g to about 800 F/g, about 700 F/g to about 900 F/g, or about 800 F/g to about 900 F/g.

[0029] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 20 A/g, of about 150 F/g to about 700 F/g. In those embodiments, the

20 supercapacitor has a gravimetric capacitance, in a current density of about 20 A/g, of at least about 150 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 20 A/g, of at most about 700 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 20 A/g, of about 150 F/g to about 250 F/g, about 150 F/g to about 350 F/g, about 150 F/g to about 450 F/g, about 150 F/g to about 550 F/g, 25 about 150 F/g to about 650 F/g, about 150 F/g to about 700 F/g, about 250 F/g to about 350 F/g, about 250 F/g to about 450 F/g, about 250 F/g to about 550 F/g, about 250 F/g to about 650 F/g, about 250 F/g to about 700 F/g, about 350 F/g to about 450 F/g, about 350 F/g to about 550 F/g, about 350 F/g to about 650 F/g, about 350 F/g to about 700 F/g, about 450 F/g to about 550 F/g, about 450 F/g to about 650 F/g, about 450 F/g to about 700 F/g, about 550 F/g to about 650 F/g, 30 about 550 F/g to about 700 F/g, or about 650 F/g to about 700 F/g.

[0030] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 50 A/g, of about 125 F/g to about 600 F/g. In those embodiments, the

supercapacitor has a gravimetric capacitance, in a current density of about 50 A/g, of at least about 125 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 50 A/g, of at least about 600 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 50 A/g, of about 125 F/g to about 150 F/g, about 125 F/g to about 200 F/g, about 125 F/g to about 300 F/g, about 125 F/g to about 400 F/g, about 125 F/g to about 500 F/g, about 125 F/g to about 600 F/g, about 150 F/g to about 200 F/g, about 150 F/g to about 300 F/g, about 150 F/g to about 400 F/g, about 150 F/g to about 500 F/g, about 150 F/g to about 600 F/g, about 200 F/g to about 300 F/g, about 200 F/g to about 400 F/g, about 200 F/g to about 500 F/g, about 200 F/g to about 600 F/g, about 300 F/g to about 400 F/g, about 300 F/g to about 500 F/g, about 300 F/g to about 600 F/g, about 400 F/g to about 500 F/g, about 400 F/g to about 600 F/g, or about 500 F/g to about 600 F/g.

[0031] In those embodiments, the supercapacitor has a gravimetric energy density of about 30 watt hours per kilogram (Wh/kg) to about 120 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at least about 30 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at most about 120 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of about 30 Wh/kg to about 40 Wh/kg, about 30 Wh/kg to about 50 Wh/kg, about 30 Wh/kg to about 60 Wh/kg, about 30 Wh/kg to about 70 Wh/kg, about 30 Wh/kg to about 80 Wh/kg, about 30 Wh/kg to about 100 Wh/kg, about 30 Wh/kg to about 120 Wh/kg, about 40 Wh/kg to about 50 Wh/kg, about 40 Wh/kg to about 60 Wh/kg, about 40 Wh/kg to about 70 Wh/kg, about 40 Wh/kg to about 80 Wh/kg, about 40 Wh/kg to about 100 Wh/kg, about 40 Wh/kg to about 120 Wh/kg, about 50 Wh/kg to about 60 Wh/kg, about 50 Wh/kg to about 70 Wh/kg, about 50 Wh/kg to about 80 Wh/kg, about 50 Wh/kg to about 100 Wh/kg, about 50 Wh/kg to about 120 Wh/kg, about 60 Wh/kg to about 70 Wh/kg, about 60 Wh/kg to about 80 Wh/kg, about 60 Wh/kg to about 100 Wh/kg, about 60 Wh/kg to about 120 Wh/kg, about 70 Wh/kg to about 80 Wh/kg, about 70 Wh/kg to about 100 Wh/kg, about 70 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, or about 100 Wh/kg to about 120 Wh/kg.

[0032] In some embodiments, the electrolyte is aqueous and further comprises a quinone wherein the quinone comprises 1,2-Benzoquinone; 1,4-Benzoquinone; 1,4-Naphthoquinone; 9,10-Anthraquinone; or any combination thereof.

[0033] In those embodiments, the quinone has a concentration of about 0.25 M to about 1 M. In those embodiments, the quinone has a concentration of at least about 0.25 M. In those embodiments,

the quinone has a concentration of at most about 1 M. In those embodiments, the quinone has a concentration of about 0.25 M to about 0.375 M, about 0.25 M to about 0.5 M, about 0.25 M to about 0.625 M, about 0.25 M to about 1 M, about 0.375 M to about 0.5 M, about 0.375 M to about 0.625 M, about 0.375 M to about 1 M, about 0.5 M to about 0.625 M, about 0.5 M to about 1 M, or about 0.625 M to about 1 M.

[0034] In those embodiments, the supercapacitor has a working potential of about 0.4 V to about 1.2 V. In those embodiments, the supercapacitor has a working potential of at least about 0.4 V. In those embodiments, the supercapacitor has a working potential of at most about 1.2 V. In those embodiments, the supercapacitor has a working potential of about 0.4 V to about 0.5 V, about 0.4 V to about 0.6 V, about 0.4 V to about 0.7 V, about 0.4 V to about 0.8 V, about 0.4 V to about 0.9 V, about 0.4 V to about 1 V, about 0.4 V to about 1.1 V, about 0.4 V to about 1.2 V, about 0.5 V to about 0.6 V, about 0.5 V to about 0.7 V, about 0.5 V to about 0.8 V, about 0.5 V to about 0.9 V, about 0.5 V to about 1 V, about 0.5 V to about 1.1 V, about 0.5 V to about 1.2 V, about 0.6 V to about 0.7 V, about 0.6 V to about 0.8 V, about 0.6 V to about 0.9 V, about 0.6 V to about 1 V, about 0.6 V to about 1.1 V, about 0.6 V to about 1.2 V, about 0.7 V to about 0.8 V, about 0.7 V to about 0.9 V, about 0.7 V to about 1 V, about 0.7 V to about 1.1 V, about 0.7 V to about 1.2 V, about 0.8 V to about 0.9 V, about 0.8 V to about 1 V, about 0.8 V to about 1.1 V, about 0.8 V to about 1.2 V, about 0.9 V to about 1 V, about 0.9 V to about 1.1 V, about 0.9 V to about 1.2 V, about 1 V to about 1.1 V, about 1 V to about 1.2 V, or about 1.1 V to about 1.2 V.

[0035] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 0.2 A/g, of about 300 F/g to about 1,400 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 0.2 A/g, of at least about 300 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 0.2 A/g, of at most about 11,400 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 0.2 A/g, of about 300 F/g to about 500 F/g, about 300 F/g to about 700 F/g, about 300 F/g to about 900 F/g, about 300 F/g to about 1,100 F/g, about 300 F/g to about 1,400 F/g, about 500 F/g to about 700 F/g, about 500 F/g to about 900 F/g, about 500 F/g to about 1,100 F/g, about 500 F/g to about 1,400 F/g, about 700 F/g to about 900 F/g, about 700 F/g to about 1,100 F/g, about 700 F/g to about 1,400 F/g, about 900 F/g to about 1,100 F/g, about 900 F/g to about 1,400 F/g, or about 1,100 F/g to about 1,400 F/g.

[0036] In those embodiments, the supercapacitor has a gravimetric energy density of about 12 Wh/kg to about 120 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy

density of at least about 12 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at most about 120 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of about 12 Wh/kg to about 20 Wh/kg, about 12 Wh/kg to about 40 Wh/kg, about 12 Wh/kg to about 60 Wh/kg, about 12 Wh/kg to about 80 Wh/kg, about 12 Wh/kg to about 100 Wh/kg, about 12 Wh/kg to about 120 Wh/kg, about 20 Wh/kg to about 40 Wh/kg, about 20 Wh/kg to about 60 Wh/kg, about 20 Wh/kg to about 80 Wh/kg, about 20 Wh/kg to about 100 Wh/kg, about 20 Wh/kg to about 120 Wh/kg, about 40 Wh/kg to about 60 Wh/kg, about 40 Wh/kg to about 80 Wh/kg, about 40 Wh/kg to about 100 Wh/kg, about 40 Wh/kg to about 120 Wh/kg, about 60 Wh/kg to about 80 Wh/kg, about 60 Wh/kg to about 100 Wh/kg, about 60 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, or about 100 Wh/kg to about 120 Wh/kg.

[0037] In some embodiments, the electrolyte is a gel and further comprises a quinone comprising 1,2-Benzoquinone, 1,4-Benzoquinone, 1,4-Naphthoquinone, 9,10-Anthraquinone or any combination thereof.

[0038] In those embodiments, the concentration of the quinone is about 5 millimolar (mM) to about 20 millimolar. In those embodiments, the concentration of the quinone is at least about 5 millimolar. In those embodiments, the concentration of the quinone is at most about 20 millimolar. In those embodiments, the concentration of the quinone is about 5 millimolar to about 7 millimolar, about 5 millimolar to about 9 millimolar, about 5 millimolar to about 11 millimolar, about 5 millimolar to about 13 millimolar, about 5 millimolar to about 15 millimolar, about 5 millimolar to about 20 millimolar, about 7 millimolar to about 9 millimolar, about 7 millimolar to about 11 millimolar, about 7 millimolar to about 13 millimolar, about 7 millimolar to about 15 millimolar, about 7 millimolar to about 20 millimolar, about 9 millimolar to about 11 millimolar, about 9 millimolar to about 13 millimolar, about 9 millimolar to about 15 millimolar, about 9 millimolar to about 20 millimolar, about 11 millimolar to about 13 millimolar, about 11 millimolar to about 15 millimolar, about 11 millimolar to about 20 millimolar, about 13 millimolar to about 15 millimolar, about 13 millimolar to about 20 millimolar, or about 15 millimolar to about 20 millimolar.

[0039] In those embodiments, the supercapacitor has a working potential of about 0.4 V to about 1.6 V. In those embodiments, the supercapacitor has a working potential of at least about 0.4 V. In those embodiments, the supercapacitor has a working potential of at most about 0.4 V. In those embodiments, the supercapacitor has a working potential of about 0.4 V to about 0.5 V, about 0.4 V

to about 0.6 V, about 0.4 V to about 0.7 V, about 0.4 V to about 0.8 V, about 0.4 V to about 0.9 V, about 0.4 V to about 1 V, about 0.4 V to about 1.2 V, about 0.4 V to about 1.4 V, about 0.4 V to about 1.6 V, about 0.5 V to about 0.6 V, about 0.5 V to about 0.7 V, about 0.5 V to about 0.8 V, about 0.5 V to about 0.9 V, about 0.5 V to about 1 V, about 0.5 V to about 1.2 V, about 0.5 V to about 1.4 V, about 0.5 V to about 1.6 V, about 0.6 V to about 0.7 V, about 0.6 V to about 0.8 V, about 0.6 V to about 0.9 V, about 0.6 V to about 1 V, about 0.6 V to about 1.2 V, about 0.6 V to about 1.4 V, about 0.6 V to about 1.6 V, about 0.7 V to about 0.8 V, about 0.7 V to about 0.9 V, about 0.7 V to about 1 V, about 0.7 V to about 1.2 V, about 0.7 V to about 1.4 V, about 0.7 V to about 1.6 V, about 0.8 V to about 0.9 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, about 0.8 V to about 1.4 V, about 0.8 V to about 1.6 V, about 0.9 V to about 1 V, about 0.9 V to about 1.2 V, about 0.9 V to about 1.4 V, about 0.9 V to about 1.6 V, about 1 V to about 1.2 V, about 1 V to about 1.4 V, about 1 V to about 1.6 V, about 1.2 V to about 1.4 V, about 1.2 V to about 1.6 V, or about 1.4 V to about 1.6 V.

[0040] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 350 F/g to about 1,400 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at least about 350 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at most about 1,400 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 350 F/g to about 450 F/g, about 350 F/g to about 550 F/g, about 350 F/g to about 650 F/g, about 350 F/g to about 750 F/g, about 350 F/g to about 850 F/g, about 350 F/g to about 1,000 F/g, about 350 F/g to about 1,200 F/g, about 350 F/g to about 1,400 F/g, about 450 F/g to about 550 F/g, about 450 F/g to about 650 F/g, about 450 F/g to about 750 F/g, about 450 F/g to about 850 F/g, about 450 F/g to about 1,000 F/g, about 450 F/g to about 1,200 F/g, about 450 F/g to about 1,400 F/g, about 550 F/g to about 650 F/g, about 550 F/g to about 750 F/g, about 550 F/g to about 850 F/g, about 550 F/g to about 1,000 F/g, about 550 F/g to about 1,200 F/g, about 550 F/g to about 1,400 F/g, about 650 F/g to about 750 F/g, about 650 F/g to about 850 F/g, about 650 F/g to about 1,000 F/g, about 650 F/g to about 1,200 F/g, about 650 F/g to about 1,400 F/g, about 750 F/g to about 850 F/g, about 750 F/g to about 1,000 F/g, about 750 F/g to about 1,200 F/g, about 750 F/g to about 1,400 F/g, about 850 F/g to about 1,000 F/g, about 850 F/g to about 1,200 F/g, about 850 F/g to about 1,400 F/g, about 1,000 F/g to about 1,200 F/g, about 1,000 F/g to about 1,400 F/g, or about 1,200 F/g to about 1,400 F/g.

[0041] In those embodiments, the supercapacitor has a gravimetric energy density of about 30 Wh/kg to about 130 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at least about 30 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at most about 130 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of about 30 Wh/kg to about 40 Wh/kg, about 30 Wh/kg to about 50 Wh/kg, about 30 Wh/kg to about 60 Wh/kg, about 30 Wh/kg to about 70 Wh/kg, about 30 Wh/kg to about 80 Wh/kg, about 30 Wh/kg to about 100 Wh/kg, about 30 Wh/kg to about 120 Wh/kg, about 30 Wh/kg to about 130 Wh/kg, about 40 Wh/kg to about 50 Wh/kg, about 40 Wh/kg to about 60 Wh/kg, about 40 Wh/kg to about 70 Wh/kg, about 40 Wh/kg to about 80 Wh/kg, about 40 Wh/kg to about 100 Wh/kg, about 40 Wh/kg to about 120 Wh/kg, about 40 Wh/kg to about 130 Wh/kg, about 50 Wh/kg to about 60 Wh/kg, about 50 Wh/kg to about 70 Wh/kg, about 50 Wh/kg to about 80 Wh/kg, about 50 Wh/kg to about 100 Wh/kg, about 50 Wh/kg to about 120 Wh/kg, about 50 Wh/kg to about 130 Wh/kg, about 60 Wh/kg to about 70 Wh/kg, about 60 Wh/kg to about 80 Wh/kg, about 60 Wh/kg to about 100 Wh/kg, about 60 Wh/kg to about 120 Wh/kg, about 60 Wh/kg to about 130 Wh/kg, about 70 Wh/kg to about 80 Wh/kg, about 70 Wh/kg to about 100 Wh/kg, about 70 Wh/kg to about 120 Wh/kg, about 70 Wh/kg to about 130 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 130 Wh/kg, about 100 Wh/kg to about 120 Wh/kg, about 100 Wh/kg to about 130 Wh/kg, or about 120 Wh/kg to about 130 Wh/kg.

[0042] In some embodiments, the supercapacitor further comprises a third functionalized carbon electrode. In some embodiments the third functionalized carbon electrode is a polyaniline functionalized carbon electrode.

[0043] In some embodiments, the electrolyte is disposed between the electrodes. In some embodiments, the electrolyte comprises an acid. In some embodiments, the electrolyte comprises a solvent. In some embodiments, the electrolyte comprises an acid and a solvent. In some embodiments, the acid is a strong acid. In some embodiments, the strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid, p-toluenesulfonic acid, methanesulfonic acid, or any combination thereof. In some embodiments, the solvent comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide, nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof. In some embodiments the concentration of the acid has a great influence on the structure and properties of polyaniline (PANI).

[0044] In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 1 millimolar. In those embodiments, the concentration of the quinone is at least about 0.25 millimolar. In those embodiments, the concentration of the quinone is at most about 1 millimolar. In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 0.375 millimolar, about 0.25 millimolar to about 0.5 millimolar, about 0.25 millimolar to about 0.625 millimolar, about 0.25 millimolar to about 0.75 millimolar, about 0.25 millimolar to about 1 millimolar, about 0.375 millimolar to about 0.5 millimolar, about 0.375 millimolar to about 0.625 millimolar, about 0.375 millimolar to about 0.75 millimolar, about 0.375 millimolar to about 1 millimolar, about 0.5 millimolar to about 0.625 millimolar, about 0.5 millimolar to about 0.75 millimolar, about 0.5 millimolar to about 1 millimolar, about 0.625 millimolar to about 0.75 millimolar, about 0.625 millimolar to about 1 millimolar, or about 0.75 millimolar to about 1 millimolar.

[0045] In those embodiments, the supercapacitor has a working potential of about 0.1 V to about 1.6 V. In those embodiments, the supercapacitor has a working potential of at least about 0.1 V. In those embodiments, the supercapacitor has a working potential of at most about 1.6 V. In those embodiments, the supercapacitor has a working potential of about 0.1 V to about 0.2 V, about 0.1 V to about 0.3 V, about 0.1 V to about 0.4 V, about 0.1 V to about 0.6 V, about 0.1 V to about 0.8 V, about 0.1 V to about 1 V, about 0.1 V to about 1.2 V, about 0.1 V to about 1.4 V, about 0.1 V to about 1.6 V, about 0.2 V to about 0.3 V, about 0.2 V to about 0.4 V, about 0.2 V to about 0.6 V, about 0.2 V to about 0.8 V, about 0.2 V to about 1 V, about 0.2 V to about 1.2 V, about 0.2 V to about 1.4 V, about 0.2 V to about 1.6 V, about 0.3 V to about 0.4 V, about 0.3 V to about 0.6 V, about 0.3 V to about 0.8 V, about 0.3 V to about 1 V, about 0.3 V to about 1.2 V, about 0.3 V to about 1.4 V, about 0.3 V to about 1.6 V, about 0.4 V to about 0.6 V, about 0.4 V to about 0.8 V, about 0.4 V to about 1 V, about 0.4 V to about 1.2 V, about 0.4 V to about 1.4 V, about 0.4 V to about 1.6 V, about 0.6 V to about 0.8 V, about 0.6 V to about 1 V, about 0.6 V to about 1.2 V, about 0.6 V to about 1.4 V, about 0.6 V to about 1.6 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, about 0.8 V to about 1.4 V, about 0.8 V to about 1.6 V, about 1 V to about 1.2 V, about 1 V to about 1.4 V, about 1 V to about 1.6 V, about 1.2 V to about 1.4 V, about 1.2 V to about 1.6 V, or about 1.4 V to about 1.6 V.

[0046] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of about 5,000 F/g to about 20,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of at least about 5,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current

density of about 10 A/g, of at most about 20,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of about 5,000 F/g to about 6,000 F/g, about 5,000 F/g to about 7,000 F/g, about 5,000 F/g to about 8,000 F/g, about 5,000 F/g to about 9,000 F/g, about 5,000 F/g to about 10,000 F/g, about 5,000 F/g to about 12,500 F/g, about 5,000 F/g to about 15,000 F/g, about 5,000 F/g to about 17,500 F/g, about 5,000 F/g to about 20,000 F/g, about 6,000 F/g to about 7,000 F/g, about 6,000 F/g to about 8,000 F/g, about 6,000 F/g to about 9,000 F/g, about 6,000 F/g to about 10,000 F/g, about 6,000 F/g to about 12,500 F/g, about 6,000 F/g to about 15,000 F/g, about 6,000 F/g to about 17,500 F/g, about 6,000 F/g to about 20,000 F/g, about 7,000 F/g to about 8,000 F/g, about 7,000 F/g to about 9,000 F/g, about 7,000 F/g to about 10,000 F/g, about 7,000 F/g to about 12,500 F/g, about 7,000 F/g to about 15,000 F/g, about 7,000 F/g to about 17,500 F/g, about 7,000 F/g to about 20,000 F/g, about 8,000 F/g to about 9,000 F/g, about 8,000 F/g to about 10,000 F/g, about 8,000 F/g to about 12,500 F/g, about 8,000 F/g to about 15,000 F/g, about 8,000 F/g to about 17,500 F/g, about 8,000 F/g to about 20,000 F/g, about 9,000 F/g to about 10,000 F/g, about 9,000 F/g to about 12,500 F/g, about 9,000 F/g to about 15,000 F/g, about 9,000 F/g to about 17,500 F/g, about 9,000 F/g to about 20,000 F/g, about 10,000 F/g to about 12,500 F/g, about 10,000 F/g to about 15,000 F/g, about 10,000 F/g to about 17,500 F/g, about 10,000 F/g to about 20,000 F/g, about 12,500 F/g to about 15,000 F/g, about 12,500 F/g to about 17,500 F/g, about 12,500 F/g to about 20,000 F/g, about 15,000 F/g to about 17,500 F/g, about 15,000 F/g to about 20,000 F/g, or about 17,500 F/g to about 20,000 F/g.

[0047] A third aspect disclosed herein is a supercapacitor comprising two or more electrodes, wherein the first electrode comprises a functionalized carbon electrode and the second electrode comprises an activated carbon electrode; a current collector; and an electrolyte. In some embodiments, the current collector is metallic. In some embodiments, the functionalized carbon electrode is a polyaniline functionalized carbon electrode. In some embodiments, the current collector is ferritic. In some embodiments, the current collector comprises stainless steel, crucible steel, carbon steel, spring steel, alloy steel, maraging steel, weathering steel, tool steel, or any combination thereof.

[0048] In some embodiments, the electrolyte is disposed between the first functionalized carbon electrode and the second functionalized carbon electrode. In some embodiments, the electrolyte comprises an acid. In some embodiments, the electrolyte comprises a solvent. In some embodiments, the electrolyte comprises an acid and a solvent. In some embodiments, the acid is a strong acid. In some embodiments, the strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid,

hydrochloric acid, sulfuric acid, p-toluenesulfonic acid methanesulfonic acid, or any combination thereof. In some embodiments, the solvent comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide, nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof.

5 [0049] In some embodiments the electrolyte is an aqueous electrolyte.

[0050] In those embodiments, the supercapacitor has a working potential of about 0.6 V to about 2.6 V. In those embodiments, the supercapacitor has a working potential of at least about 0.6 V. In those embodiments, the supercapacitor has a working potential of at most about 2.6 V. In those
 10 embodiments, the supercapacitor has a working potential of about 0.6 V to about 0.8 V, about 0.6 V to about 1 V, about 0.6 V to about 1.2 V, about 0.6 V to about 1.4 V, about 0.6 V to about 1.6 V, about 0.6 V to about 1.8 V, about 0.6 V to about 2 V, about 0.6 V to about 2.2 V, about 0.6 V to about 2.4 V, about 0.6 V to about 2.6 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, about 0.8 V to about 1.4 V, about 0.8 V to about 1.6 V, about 0.8 V to about 1.8 V, about 0.8 V to about 2 V, about 0.8 V to about 2.2 V, about 0.8 V to about 2.4 V, about 0.8 V to about 2.6 V, about 1 V to
 15 about 1.2 V, about 1 V to about 1.4 V, about 1 V to about 1.6 V, about 1 V to about 1.8 V, about 1 V to about 2 V, about 1 V to about 2.2 V, about 1 V to about 2.4 V, about 1 V to about 2.6 V, about 1.2 V to about 1.4 V, about 1.2 V to about 1.6 V, about 1.2 V to about 1.8 V, about 1.2 V to about 2 V, about 1.2 V to about 2.2 V, about 1.2 V to about 2.4 V, about 1.2 V to about 2.6 V, about 1.4 V to about 1.6 V, about 1.4 V to about 1.8 V, about 1.4 V to about 2 V, about 1.4 V to about 2.2 V, about 1.4 V to about 2.4 V, about 1.4 V to about 2.6 V, about 1.6 V to about 1.8 V, about 1.6 V to about 2 V, about 1.6 V to about 2.2 V, about 1.6 V to about 2.4 V, about 1.6 V to about 2.6 V, about 1.8 V to about 2 V, about 1.8 V to about 2.2 V, about 1.8 V to about 2.4 V, about 1.8 V to about 2.6 V, about 2 V to about 2.2 V, about 2 V to about 2.4 V, about 2 V to about 2.6 V, about 2.2 V to about 2.4 V, about 2.2 V to about 2.6 V, or about 2.4 V to about 2.6 V.

25 [0051] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 150 F/g to about 600 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at least about 150 F/g. In those
 30 embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at most about 600 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 150 F/g to about 200 F/g, about 150 F/g to about 250 F/g, about 150 F/g to about 300 F/g, about 150 F/g to about 350 F/g, about 150 F/g to about 400 F/g, about 150 F/g to about 450 F/g, about 150 F/g to about 500 F/g, about 150 F/g to about 550 F/g,

about 150 F/g to about 600 F/g, about 200 F/g to about 250 F/g, about 200 F/g to about 300 F/g, about 200 F/g to about 350 F/g, about 200 F/g to about 400 F/g, about 200 F/g to about 450 F/g, about 200 F/g to about 500 F/g, about 200 F/g to about 550 F/g, about 200 F/g to about 600 F/g, about 250 F/g to about 300 F/g, about 250 F/g to about 350 F/g, about 250 F/g to about 400 F/g, about 250 F/g to about 450 F/g, about 250 F/g to about 500 F/g, about 250 F/g to about 550 F/g, about 250 F/g to about 600 F/g, about 300 F/g to about 350 F/g, about 300 F/g to about 400 F/g, about 300 F/g to about 450 F/g, about 300 F/g to about 500 F/g, about 300 F/g to about 550 F/g, about 300 F/g to about 600 F/g, about 350 F/g to about 400 F/g, about 350 F/g to about 450 F/g, about 350 F/g to about 500 F/g, about 350 F/g to about 550 F/g, about 350 F/g to about 600 F/g, about 400 F/g to about 450 F/g, about 400 F/g to about 500 F/g, about 400 F/g to about 550 F/g, about 400 F/g to about 600 F/g, about 450 F/g to about 500 F/g, about 450 F/g to about 550 F/g, about 450 F/g to about 600 F/g, about 500 F/g to about 550 F/g, about 500 F/g to about 600 F/g, or about 550 F/g to about 600 F/g.

[0052] In those embodiments, the supercapacitor has a gravimetric energy density of about 45 Wh/kg to about 180 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at least about 45 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at most about 180 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of about 45 Wh/kg to about 60 Wh/kg, about 45 Wh/kg to about 80 Wh/kg, about 45 Wh/kg to about 100 Wh/kg, about 45 Wh/kg to about 120 Wh/kg, about 45 Wh/kg to about 140 Wh/kg, about 45 Wh/kg to about 160 Wh/kg, about 45 Wh/kg to about 180 Wh/kg, about 60 Wh/kg to about 80 Wh/kg, about 60 Wh/kg to about 100 Wh/kg, about 60 Wh/kg to about 120 Wh/kg, about 60 Wh/kg to about 140 Wh/kg, about 60 Wh/kg to about 160 Wh/kg, about 60 Wh/kg to about 180 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 140 Wh/kg, about 80 Wh/kg to about 160 Wh/kg, about 80 Wh/kg to about 180 Wh/kg, about 100 Wh/kg to about 120 Wh/kg, about 100 Wh/kg to about 140 Wh/kg, about 100 Wh/kg to about 160 Wh/kg, about 100 Wh/kg to about 180 Wh/kg, about 120 Wh/kg to about 140 Wh/kg, about 120 Wh/kg to about 160 Wh/kg, about 120 Wh/kg to about 180 Wh/kg, about 140 Wh/kg to about 160 Wh/kg, about 140 Wh/kg to about 180 Wh/kg, or about 160 Wh/kg to about 180 Wh/kg.

[0053] In some embodiments, the aqueous electrolyte comprises a quinone.

[0054] In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 1 millimolar. In those embodiments, the concentration of the quinone is at least about 0.25 millimolar.

In those embodiments, the concentration of the quinone is at most about 1 millimolar. In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 0.375 millimolar, about 0.25 millimolar to about 0.5 millimolar, about 0.25 millimolar to about 0.625 millimolar, about 0.25 millimolar to about 0.75 millimolar, about 0.25 millimolar to about 1 millimolar, about 0.375 millimolar to about 0.5 millimolar, about 0.375 millimolar to about 0.625 millimolar, about 0.375 millimolar to about 0.75 millimolar, about 0.375 millimolar to about 1 millimolar, about 0.5 millimolar to about 0.625 millimolar, about 0.5 millimolar to about 0.75 millimolar, about 0.5 millimolar to about 1 millimolar, about 0.625 millimolar to about 0.75 millimolar, about 0.625 millimolar to about 1 millimolar, or about 0.75 millimolar to about 1 millimolar.

[0055] In those embodiments, the supercapacitor has a working potential of about 0.6 V to about 3.5 V. In those embodiments, the supercapacitor has a working potential of at least about 0.6 V. In those embodiments, the supercapacitor has a working potential of at most about 3.5 V. In those embodiments, the supercapacitor has a working potential of about 0.6 V to about 0.8 V, about 0.6 V to about 1 V, about 0.6 V to about 1.2 V, about 0.6 V to about 1.4 V, about 0.6 V to about 1.6 V, about 0.6 V to about 1.8 V, about 0.6 V to about 2 V, about 0.6 V to about 2.5 V, about 0.6 V to about 3 V, about 0.6 V to about 3.5 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, about 0.8 V to about 1.4 V, about 0.8 V to about 1.6 V, about 0.8 V to about 1.8 V, about 0.8 V to about 2 V, about 0.8 V to about 2.5 V, about 0.8 V to about 3 V, about 0.8 V to about 3.5 V, about 1 V to about 1.2 V, about 1 V to about 1.4 V, about 1 V to about 1.6 V, about 1 V to about 1.8 V, about 1 V to about 2 V, about 1 V to about 2.5 V, about 1 V to about 3 V, about 1 V to about 3.5 V, about 1.2 V to about 1.4 V, about 1.2 V to about 1.6 V, about 1.2 V to about 1.8 V, about 1.2 V to about 2 V, about 1.2 V to about 2.5 V, about 1.2 V to about 3 V, about 1.2 V to about 3.5 V, about 1.4 V to about 1.6 V, about 1.4 V to about 1.8 V, about 1.4 V to about 2 V, about 1.4 V to about 2.5 V, about 1.4 V to about 3 V, about 1.4 V to about 3.5 V, about 1.6 V to about 1.8 V, about 1.6 V to about 2 V, about 1.6 V to about 2.5 V, about 1.6 V to about 3 V, about 1.6 V to about 3.5 V, about 1.8 V to about 2 V, about 1.8 V to about 2.5 V, about 1.8 V to about 3 V, about 1.8 V to about 3.5 V, about 2 V to about 2.5 V, about 2 V to about 3 V, about 2 V to about 3.5 V, about 2.5 V to about 3 V, about 2.5 V to about 3.5 V, or about 3 V to about 3.5 V.

[0056] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 150 F/g to about 700 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at least about 150 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g,

of at most about 700 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 150 F/g to about 200 F/g, about 150 F/g to about 250 F/g, about 150 F/g to about 300 F/g, about 150 F/g to about 350 F/g, about 150 F/g to about 400 F/g, about 150 F/g to about 450 F/g, about 150 F/g to about 500 F/g, about 150 F/g to about 600 F/g, about 150 F/g to about 700 F/g, about 200 F/g to about 250 F/g, about 200 F/g to about 300 F/g, about 200 F/g to about 350 F/g, about 200 F/g to about 400 F/g, about 200 F/g to about 450 F/g, about 200 F/g to about 500 F/g, about 200 F/g to about 600 F/g, about 200 F/g to about 700 F/g, about 250 F/g to about 300 F/g, about 250 F/g to about 350 F/g, about 250 F/g to about 400 F/g, about 250 F/g to about 450 F/g, about 250 F/g to about 500 F/g, about 250 F/g to about 600 F/g, about 250 F/g to about 700 F/g, about 300 F/g to about 350 F/g, about 300 F/g to about 400 F/g, about 300 F/g to about 450 F/g, about 300 F/g to about 500 F/g, about 300 F/g to about 600 F/g, about 300 F/g to about 700 F/g, about 350 F/g to about 400 F/g, about 350 F/g to about 450 F/g, about 350 F/g to about 500 F/g, about 350 F/g to about 600 F/g, about 350 F/g to about 700 F/g, about 400 F/g to about 450 F/g, about 400 F/g to about 500 F/g, about 400 F/g to about 600 F/g, about 400 F/g to about 700 F/g, about 450 F/g to about 500 F/g, about 450 F/g to about 600 F/g, about 450 F/g to about 700 F/g, about 500 F/g to about 600 F/g, about 500 F/g to about 700 F/g, or about 600 F/g to about 700 F/g.

[0057] In those embodiments, the supercapacitor has a gravimetric energy density of about 40 Wh/kg to about 1,600 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at least about 40 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at most about 1,600 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of about 40 Wh/kg to about 50 Wh/kg, about 40 Wh/kg to about 100 Wh/kg, about 40 Wh/kg to about 250 Wh/kg, about 40 Wh/kg to about 500 Wh/kg, about 40 Wh/kg to about 750 Wh/kg, about 40 Wh/kg to about 1,000 Wh/kg, about 40 Wh/kg to about 1,250 Wh/kg, about 40 Wh/kg to about 1,600 Wh/kg, about 50 Wh/kg to about 100 Wh/kg, about 50 Wh/kg to about 250 Wh/kg, about 50 Wh/kg to about 500 Wh/kg, about 50 Wh/kg to about 750 Wh/kg, about 50 Wh/kg to about 1,000 Wh/kg, about 50 Wh/kg to about 1,250 Wh/kg, about 50 Wh/kg to about 1,600 Wh/kg, about 100 Wh/kg to about 250 Wh/kg, about 100 Wh/kg to about 500 Wh/kg, about 100 Wh/kg to about 750 Wh/kg, about 100 Wh/kg to about 1,000 Wh/kg, about 100 Wh/kg to about 1,250 Wh/kg, about 100 Wh/kg to about 1,600 Wh/kg, about 250 Wh/kg to about 500 Wh/kg, about 250 Wh/kg to about 750 Wh/kg, about 250 Wh/kg to about 1,000 Wh/kg, about 250 Wh/kg to about 1,250 Wh/kg, about 250 Wh/kg to about 1,600 Wh/kg, about 500 Wh/kg

to about 750 Wh/kg, about 500 Wh/kg to about 1,000 Wh/kg, about 500 Wh/kg to about 1,250 Wh/kg, about 500 Wh/kg to about 1,600 Wh/kg, about 750 Wh/kg to about 1,000 Wh/kg, about 750 Wh/kg to about 1,250 Wh/kg, about 750 Wh/kg to about 1,600 Wh/kg, about 1,000 Wh/kg to about 1,250 Wh/kg, about 1,000 Wh/kg to about 1,600 Wh/kg, or about 1,250 Wh/kg to about 1,600 Wh/kg.

[0058] In some embodiments, the electrolyte is a gel electrolyte.

[0059] In those embodiments, the supercapacitor has a working potential of about 0.6 V to about 2.4 V. In those embodiments, the supercapacitor has a working potential of at least about 0.6 V. In those embodiments, the supercapacitor has a working potential of at most about 2.4 V. In those

embodiments, the supercapacitor has a working potential of about 0.6 V to about 0.8 V, about 0.6 V to about 1 V, about 0.6 V to about 1.2 V, about 0.6 V to about 1.4 V, about 0.6 V to about 1.6 V, about 0.6 V to about 1.8 V, about 0.6 V to about 2 V, about 0.6 V to about 2.2 V, about 0.6 V to about 2.4 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, about 0.8 V to about 1.4 V, about 0.8 V to about 1.6 V, about 0.8 V to about 1.8 V, about 0.8 V to about 2 V, about 0.8 V to about 2.2 V, about 0.8 V to about 2.4 V, about 1 V to about 1.2 V, about 1 V to about 1.4 V, about 1 V to about 1.6 V, about 1 V to about 1.8 V, about 1 V to about 2 V, about 1 V to about 2.2 V, about 1 V to about 2.4 V, about 1.2 V to about 1.4 V, about 1.2 V to about 1.6 V, about 1.2 V to about 1.8 V, about 1.2 V to about 2 V, about 1.2 V to about 2.2 V, about 1.2 V to about 2.4 V, about 1.4 V to about 1.6 V, about 1.4 V to about 1.8 V, about 1.4 V to about 2 V, about 1.4 V to about 2.2 V, about 1.4 V to about 2.4 V, about 1.6 V to about 1.8 V, about 1.6 V to about 2 V, about 1.6 V to about 2.2 V, about 1.6 V to about 2.4 V, about 1.8 V to about 2 V, about 1.8 V to about 2.2 V, about 1.8 V to about 2.4 V, about 2 V to about 2.2 V, about 2 V to about 2.4 V, or about 2.2 V to about 2.4 V.

[0060] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 150 F/g to about 650 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at least about 150 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at most about 650 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 150 F/g to about 200 F/g, about 150 F/g to about 250 F/g, about 150 F/g to about 300 F/g, about 150 F/g to about 350 F/g, about 150 F/g to about 400 F/g, about 150 F/g to about 450 F/g, about 150 F/g to about 500 F/g, about 150 F/g to about 550 F/g, about 150 F/g to about 600 F/g, about 150 F/g to about 650 F/g, about 200 F/g to about 250 F/g, about 200 F/g to about 300 F/g, about 200 F/g to about 350 F/g, about 200 F/g to about 400 F/g,

about 200 F/g to about 450 F/g, about 200 F/g to about 500 F/g, about 200 F/g to about 550 F/g, about 200 F/g to about 600 F/g, about 200 F/g to about 650 F/g, about 250 F/g to about 300 F/g, about 250 F/g to about 350 F/g, about 250 F/g to about 400 F/g, about 250 F/g to about 450 F/g, about 250 F/g to about 500 F/g, about 250 F/g to about 550 F/g, about 250 F/g to about 600 F/g, about 250 F/g to about 650 F/g, about 300 F/g to about 350 F/g, about 300 F/g to about 400 F/g, about 300 F/g to about 450 F/g, about 300 F/g to about 500 F/g, about 300 F/g to about 550 F/g, about 300 F/g to about 600 F/g, about 300 F/g to about 650 F/g, about 350 F/g to about 400 F/g, about 350 F/g to about 450 F/g, about 350 F/g to about 500 F/g, about 350 F/g to about 550 F/g, about 350 F/g to about 600 F/g, about 350 F/g to about 650 F/g, about 400 F/g to about 450 F/g, about 400 F/g to about 500 F/g, about 400 F/g to about 550 F/g, about 400 F/g to about 600 F/g, about 400 F/g to about 650 F/g, about 450 F/g to about 500 F/g, about 450 F/g to about 550 F/g, about 450 F/g to about 600 F/g, about 450 F/g to about 650 F/g, about 500 F/g to about 550 F/g, about 500 F/g to about 600 F/g, about 500 F/g to about 650 F/g, about 550 F/g to about 600 F/g, about 550 F/g to about 650 F/g, or about 600 F/g to about 650 F/g.

[0061] In those embodiments, the supercapacitor has a gravimetric energy density of about 30 Wh/kg to about 130 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at least about 30 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of at most about 130 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density of about 30 Wh/kg to about 40 Wh/kg, about 30 Wh/kg to about 50 Wh/kg, about 30 Wh/kg to about 60 Wh/kg, about 30 Wh/kg to about 70 Wh/kg, about 30 Wh/kg to about 80 Wh/kg, about 30 Wh/kg to about 90 Wh/kg, about 30 Wh/kg to about 100 Wh/kg, about 30 Wh/kg to about 110 Wh/kg, about 30 Wh/kg to about 120 Wh/kg, about 30 Wh/kg to about 130 Wh/kg, about 40 Wh/kg to about 50 Wh/kg, about 40 Wh/kg to about 60 Wh/kg, about 40 Wh/kg to about 70 Wh/kg, about 40 Wh/kg to about 80 Wh/kg, about 40 Wh/kg to about 90 Wh/kg, about 40 Wh/kg to about 100 Wh/kg, about 40 Wh/kg to about 110 Wh/kg, about 40 Wh/kg to about 120 Wh/kg, about 40 Wh/kg to about 130 Wh/kg, about 50 Wh/kg to about 60 Wh/kg, about 50 Wh/kg to about 70 Wh/kg, about 50 Wh/kg to about 80 Wh/kg, about 50 Wh/kg to about 90 Wh/kg, about 50 Wh/kg to about 100 Wh/kg, about 50 Wh/kg to about 110 Wh/kg, about 50 Wh/kg to about 120 Wh/kg, about 50 Wh/kg to about 130 Wh/kg, about 60 Wh/kg to about 70 Wh/kg, about 60 Wh/kg to about 80 Wh/kg, about 60 Wh/kg to about 90 Wh/kg, about 60 Wh/kg to about 100 Wh/kg, about 60 Wh/kg to about 110 Wh/kg, about 60 Wh/kg to about 120 Wh/kg, about 60 Wh/kg to about 130 Wh/kg, about 70 Wh/kg to about 80 Wh/kg, about 70 Wh/kg to about 90 Wh/kg, about 70 Wh/kg to about 100 Wh/kg, about 70 Wh/kg to about 110 Wh/kg, about 70 Wh/kg to about 120 Wh/kg, about 70 Wh/kg to about 130 Wh/kg, about 80 Wh/kg to about 90 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 110 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 130 Wh/kg, about 90 Wh/kg to about 100 Wh/kg, about 90 Wh/kg to about 110 Wh/kg, about 90 Wh/kg to about 120 Wh/kg, about 90 Wh/kg to about 130 Wh/kg, about 100 Wh/kg to about 110 Wh/kg, about 100 Wh/kg to about 120 Wh/kg, about 100 Wh/kg to about 130 Wh/kg, about 110 Wh/kg to about 120 Wh/kg, about 110 Wh/kg to about 130 Wh/kg, about 120 Wh/kg to about 130 Wh/kg, or about 130 Wh/kg.

90 Wh/kg, about 70 Wh/kg to about 100 Wh/kg, about 70 Wh/kg to about 110 Wh/kg, about 70 Wh/kg to about 120 Wh/kg, about 70 Wh/kg to about 130 Wh/kg, about 80 Wh/kg to about 90 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 110 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 130 Wh/kg, about 90 Wh/kg to about 100 Wh/kg, about 90 Wh/kg to about 110 Wh/kg, about 90 Wh/kg to about 120 Wh/kg, about 90 Wh/kg to about 130 Wh/kg, about 100 Wh/kg to about 110 Wh/kg, about 100 Wh/kg to about 120 Wh/kg, about 100 Wh/kg to about 130 Wh/kg, about 110 Wh/kg to about 120 Wh/kg, about 110 Wh/kg to about 130 Wh/kg, or about 120 Wh/kg to about 130 Wh/kg.

[0062] In some embodiments the gel electrolyte comprises a quinone.

[0063] In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 1 millimolar. In those embodiments, the concentration of the quinone is at least about 0.25 millimolar. In those embodiments, the concentration of the quinone is at most about 1 millimolar. In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 0.375 millimolar, about 0.25 millimolar to about 0.5 millimolar, about 0.25 millimolar to about 0.625 millimolar, about 0.25 millimolar to about 0.75 millimolar, about 0.25 millimolar to about 1 millimolar, about 0.375 millimolar to about 0.5 millimolar, about 0.375 millimolar to about 0.625 millimolar, about 0.375 millimolar to about 0.75 millimolar, about 0.375 millimolar to about 1 millimolar, about 0.5 millimolar to about 0.625 millimolar, about 0.5 millimolar to about 0.75 millimolar, about 0.5 millimolar to about 1 millimolar, about 0.625 millimolar to about 0.75 millimolar, about 0.625 millimolar to about 1 millimolar, or about 0.75 millimolar to about 1 millimolar.

[0064] In those embodiments, the supercapacitor has a working potential of about 0.7 V to about 2.8 V. In those embodiments, the supercapacitor has a working potential of at least about 0.7 V. In those embodiments, the supercapacitor has a working potential of at most about 2.8 V. In those embodiments, the supercapacitor has a working potential of about 0.7 V to about 0.8 V, about 0.7 V to about 1 V, about 0.7 V to about 1.2 V, about 0.7 V to about 1.4 V, about 0.7 V to about 1.6 V, about 0.7 V to about 1.8 V, about 0.7 V to about 2 V, about 0.7 V to about 2.2 V, about 0.7 V to about 2.4 V, about 0.7 V to about 2.6 V, about 0.7 V to about 2.8 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, about 0.8 V to about 1.4 V, about 0.8 V to about 1.6 V, about 0.8 V to about 1.8 V, about 0.8 V to about 2 V, about 0.8 V to about 2.2 V, about 0.8 V to about 2.4 V, about 0.8 V to about 2.6 V, about 0.8 V to about 2.8 V, about 1 V to about 1.2 V, about 1 V to about 1.4 V, about 1 V to about 1.6 V, about 1 V to about 1.8 V, about 1 V to about 2 V, about 1 V to about 2.2 V, about 1 V to about 2.4 V, about 1 V to about 2.6 V, about 1 V to about 2.8 V, about 1.2 V to about

1.4 V, about 1.2 V to about 1.6 V, about 1.2 V to about 1.8 V, about 1.2 V to about 2 V, about 1.2 V to about 2.2 V, about 1.2 V to about 2.4 V, about 1.2 V to about 2.6 V, about 1.2 V to about 2.8 V, about 1.4 V to about 1.6 V, about 1.4 V to about 1.8 V, about 1.4 V to about 2 V, about 1.4 V to about 2.2 V, about 1.4 V to about 2.4 V, about 1.4 V to about 2.6 V, about 1.4 V to about 2.8 V, about 1.6 V to about 1.8 V, about 1.6 V to about 2 V, about 1.6 V to about 2.2 V, about 1.6 V to about 2.4 V, about 1.6 V to about 2.6 V, about 1.6 V to about 2.8 V, about 1.8 V to about 2 V, about 1.8 V to about 2.2 V, about 1.8 V to about 2.4 V, about 1.8 V to about 2.6 V, about 1.8 V to about 2.8 V, about 2 V to about 2.2 V, about 2 V to about 2.4 V, about 2 V to about 2.6 V, about 2 V to about 2.8 V, about 2.2 V to about 2.4 V, about 2.2 V to about 2.6 V, about 2.2 V to about 2.8 V, about 2.4 V to about 2.6 V, about 2.4 V to about 2.8 V, or about 2.6 V to about 2.8 V.

[0065] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 2,500 F/g to about 10,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at least about 2,500 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of at most about 10,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 2 A/g, of about 2,500 F/g to about 3,000 F/g, about 2,500 F/g to about 4,000 F/g, about 2,500 F/g to about 5,000 F/g, about 2,500 F/g to about 6,000 F/g, about 2,500 F/g to about 7,000 F/g, about 2,500 F/g to about 8,000 F/g, about 2,500 F/g to about 9,000 F/g, about 2,500 F/g to about 10,000 F/g, about 3,000 F/g to about 4,000 F/g, about 3,000 F/g to about 5,000 F/g, about 3,000 F/g to about 6,000 F/g, about 3,000 F/g to about 7,000 F/g, about 3,000 F/g to about 8,000 F/g, about 3,000 F/g to about 9,000 F/g, about 3,000 F/g to about 10,000 F/g, about 4,000 F/g to about 5,000 F/g, about 4,000 F/g to about 6,000 F/g, about 4,000 F/g to about 7,000 F/g, about 4,000 F/g to about 8,000 F/g, about 4,000 F/g to about 9,000 F/g, about 4,000 F/g to about 10,000 F/g, about 5,000 F/g to about 6,000 F/g, about 5,000 F/g to about 7,000 F/g, about 5,000 F/g to about 8,000 F/g, about 5,000 F/g to about 9,000 F/g, about 5,000 F/g to about 10,000 F/g, about 6,000 F/g to about 7,000 F/g, about 6,000 F/g to about 8,000 F/g, about 6,000 F/g to about 9,000 F/g, about 6,000 F/g to about 10,000 F/g, about 7,000 F/g to about 8,000 F/g, about 7,000 F/g to about 9,000 F/g, about 7,000 F/g to about 10,000 F/g, about 8,000 F/g to about 9,000 F/g, about 8,000 F/g to about 10,000 F/g, or about 9,000 F/g to about 10,000 F/g.

[0066] In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the weight of the electrodes, of about 700 Wh/kg to about 3,000 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the weight of the electrodes,

of at least about 700 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the weight of the electrodes, of at most about 3,00 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the weight of the electrodes, of about 700 Wh/kg to about 1,000 Wh/kg, about 700 Wh/kg to about 1,250 Wh/kg, about 700 Wh/kg to about 1,500 Wh/kg, about 700 Wh/kg to about 1,750 Wh/kg, about 700 Wh/kg to about 2,000 Wh/kg, about 700 Wh/kg to about 2,250 Wh/kg, about 700 Wh/kg to about 2,500 Wh/kg, about 700 Wh/kg to about 2,750 Wh/kg, about 700 Wh/kg to about 3,000 Wh/kg, about 1,000 Wh/kg to about 1,250 Wh/kg, about 1,000 Wh/kg to about 1,500 Wh/kg, about 1,000 Wh/kg to about 1,750 Wh/kg, about 1,000 Wh/kg to about 2,000 Wh/kg, about 1,000 Wh/kg to about 2,250 Wh/kg, about 1,000 Wh/kg to about 2,500 Wh/kg, about 1,000 Wh/kg to about 2,750 Wh/kg, about 1,000 Wh/kg to about 3,000 Wh/kg, about 1,250 Wh/kg to about 1,500 Wh/kg, about 1,250 Wh/kg to about 1,750 Wh/kg, about 1,250 Wh/kg to about 2,000 Wh/kg, about 1,250 Wh/kg to about 2,250 Wh/kg, about 1,250 Wh/kg to about 2,500 Wh/kg, about 1,250 Wh/kg to about 2,750 Wh/kg, about 1,250 Wh/kg to about 3,000 Wh/kg, about 1,500 Wh/kg to about 1,750 Wh/kg, about 1,500 Wh/kg to about 2,000 Wh/kg, about 1,500 Wh/kg to about 2,250 Wh/kg, about 1,500 Wh/kg to about 2,500 Wh/kg, about 1,500 Wh/kg to about 2,750 Wh/kg, about 1,500 Wh/kg to about 3,000 Wh/kg, about 1,750 Wh/kg to about 2,000 Wh/kg, about 1,750 Wh/kg to about 2,250 Wh/kg, about 1,750 Wh/kg to about 2,500 Wh/kg, about 1,750 Wh/kg to about 2,750 Wh/kg, about 1,750 Wh/kg to about 3,000 Wh/kg, about 2,000 Wh/kg to about 2,250 Wh/kg, about 2,000 Wh/kg to about 2,500 Wh/kg, about 2,000 Wh/kg to about 2,750 Wh/kg, about 2,000 Wh/kg to about 3,000 Wh/kg, about 2,250 Wh/kg to about 2,500 Wh/kg, about 2,250 Wh/kg to about 2,750 Wh/kg, about 2,250 Wh/kg to about 3,000 Wh/kg, about 2,500 Wh/kg to about 2,750 Wh/kg, about 2,500 Wh/kg to about 3,000 Wh/kg, or about 2,750 Wh/kg to about 3,000 Wh/kg.

[0067] In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes, of about 100 Wh/L to about 2,000 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes, of at least about 100 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes, of at most about 2,000 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes, of about 500 Wh/L to about 625 Wh/L, about 500 Wh/L to about 750 Wh/L, about 500 Wh/L to about 875 Wh/L, about 500 Wh/L to about 100 Wh/L, about 500 Wh/L to about 1,125 Wh/L, about

500 Wh/L to about 1,250 Wh/L, about 500 Wh/L to about 1,375 Wh/L, about 500 Wh/L to about 1,500 Wh/L, about 500 Wh/L to about 1,750 Wh/L, about 500 Wh/L to about 2,000 Wh/L, about 625 Wh/L to about 750 Wh/L, about 625 Wh/L to about 875 Wh/L, about 625 Wh/L to about 100 Wh/L, about 625 Wh/L to about 1,125 Wh/L, about 625 Wh/L to about 1,250 Wh/L, about 625 Wh/L to about 1,375 Wh/L, about 625 Wh/L to about 1,500 Wh/L, about 625 Wh/L to about 1,750 Wh/L, about 625 Wh/L to about 2,000 Wh/L, about 750 Wh/L to about 875 Wh/L, about 750 Wh/L to about 100 Wh/L, about 750 Wh/L to about 1,125 Wh/L, about 750 Wh/L to about 1,250 Wh/L, about 750 Wh/L to about 1,375 Wh/L, about 750 Wh/L to about 1,500 Wh/L, about 750 Wh/L to about 1,750 Wh/L, about 750 Wh/L to about 2,000 Wh/L, about 875 Wh/L to about 100 Wh/L, about 875 Wh/L to about 1,125 Wh/L, about 875 Wh/L to about 1,250 Wh/L, about 875 Wh/L to about 1,375 Wh/L, about 875 Wh/L to about 1,500 Wh/L, about 875 Wh/L to about 1,750 Wh/L, about 875 Wh/L to about 2,000 Wh/L, about 100 Wh/L to about 1,125 Wh/L, about 100 Wh/L to about 1,250 Wh/L, about 100 Wh/L to about 1,375 Wh/L, about 100 Wh/L to about 1,500 Wh/L, about 100 Wh/L to about 1,750 Wh/L, about 100 Wh/L to about 2,000 Wh/L, about 1,125 Wh/L to about 1,250 Wh/L, about 1,125 Wh/L to about 1,375 Wh/L, about 1,125 Wh/L to about 1,500 Wh/L, about 1,125 Wh/L to about 1,750 Wh/L, about 1,125 Wh/L to about 2,000 Wh/L, about 1,250 Wh/L to about 1,375 Wh/L, about 1,250 Wh/L to about 1,500 Wh/L, about 1,250 Wh/L to about 1,750 Wh/L, about 1,250 Wh/L to about 2,000 Wh/L, about 1,375 Wh/L to about 1,500 Wh/L, about 1,375 Wh/L to about 1,750 Wh/L, about 1,375 Wh/L to about 2,000 Wh/L, about 1,500 Wh/L to about 1,750 Wh/L, about 1,500 Wh/L to about 2,000 Wh/L, or about 1,750 Wh/L to about 2,000 Wh/L.

[0068] In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of about 100 Wh/kg to about 2,000 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of at least about 100 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of at most about 2,000 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of about 500 Wh/kg to about 625 Wh/kg, about 500 Wh/kg to about 750 Wh/kg, about 500 Wh/kg to about 875 Wh/kg, about 500 Wh/kg to about 100 Wh/kg, about 500 Wh/kg to about 1,125 Wh/kg, about 500 Wh/kg to about 1,250 Wh/kg, about 500 Wh/kg to about 1,375 Wh/kg, about 500 Wh/kg to about 1,500 Wh/kg, about 500 Wh/kg to about

1,750 Wh/kg, about 500 Wh/kg to about 2,000 Wh/kg, about 625 Wh/kg to about 750 Wh/kg, about 625 Wh/kg to about 875 Wh/kg, about 625 Wh/kg to about 100 Wh/kg, about 625 Wh/kg to about 1,125 Wh/kg, about 625 Wh/kg to about 1,250 Wh/kg, about 625 Wh/kg to about 1,375 Wh/kg, about 625 Wh/kg to about 1,500 Wh/kg, about 625 Wh/kg to about 1,750 Wh/kg, about 625 Wh/kg to about 2,000 Wh/kg, about 750 Wh/kg to about 875 Wh/kg, about 750 Wh/kg to about 100 Wh/kg, about 750 Wh/kg to about 1,125 Wh/kg, about 750 Wh/kg to about 1,250 Wh/kg, about 750 Wh/kg to about 1,375 Wh/kg, about 750 Wh/kg to about 1,500 Wh/kg, about 750 Wh/kg to about 1,750 Wh/kg, about 750 Wh/kg to about 2,000 Wh/kg, about 875 Wh/kg to about 100 Wh/kg, about 875 Wh/kg to about 1,125 Wh/kg, about 875 Wh/kg to about 1,250 Wh/kg, about 875 Wh/kg to about 1,375 Wh/kg, about 875 Wh/kg to about 1,500 Wh/kg, about 875 Wh/kg to about 1,750 Wh/kg, about 875 Wh/kg to about 2,000 Wh/kg, about 100 Wh/kg to about 1,125 Wh/kg, about 100 Wh/kg to about 1,250 Wh/kg, about 100 Wh/kg to about 1,375 Wh/kg, about 100 Wh/kg to about 1,500 Wh/kg, about 100 Wh/kg to about 1,750 Wh/kg, about 100 Wh/kg to about 2,000 Wh/kg, about 1,125 Wh/kg to about 1,250 Wh/kg, about 1,125 Wh/kg to about 1,375 Wh/kg, about 1,125 Wh/kg to about 1,500 Wh/kg, about 1,125 Wh/kg to about 1,750 Wh/kg, about 1,125 Wh/kg to about 2,000 Wh/kg, about 1,250 Wh/kg to about 1,375 Wh/kg, about 1,250 Wh/kg to about 1,500 Wh/kg, about 1,250 Wh/kg to about 1,750 Wh/kg, about 1,250 Wh/kg to about 2,000 Wh/kg, about 1,375 Wh/kg to about 1,500 Wh/kg, about 1,375 Wh/kg to about 1,750 Wh/kg, about 1,375 Wh/kg to about 2,000 Wh/kg, about 1,500 Wh/kg to about 1,750 Wh/kg, about 1,500 Wh/kg to about 2,000 Wh/kg, or about 1,750 Wh/kg to about 2,000 Wh/kg.

[0069] In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of about 100 Wh/L to about 1,800 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of at least about 100 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of at most about 1,800 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the volume of the electrodes and the redox electrolyte, of about 400 Wh/L to about 600 Wh/L, about 400 Wh/L to about 800 Wh/L, about 400 Wh/L to about 100 Wh/L, about 400 Wh/L to about 1,200 Wh/L, about 400 Wh/L to about 1,400 Wh/L, about 400 Wh/L to about 1,600 Wh/L, about 400 Wh/L to about 1,800 Wh/L, about 600 Wh/L to about 800 Wh/L, about 600 Wh/L to about 100 Wh/L, about 600 Wh/L to about 1,200 Wh/L, about 600 Wh/L to about 1,400 Wh/L, about 600 Wh/L to about 1,600 Wh/L, about

600 Wh/L to about 1,800 Wh/L, about 800 Wh/L to about 100 Wh/L, about 800 Wh/L to about 1,200 Wh/L, about 800 Wh/L to about 1,400 Wh/L, about 800 Wh/L to about 1,600 Wh/L, about 800 Wh/L to about 1,800 Wh/L, about 100 Wh/L to about 1,200 Wh/L, about 100 Wh/L to about 1,400 Wh/L, about 100 Wh/L to about 1,600 Wh/L, about 100 Wh/L to about 1,800 Wh/L, about 1,200 Wh/L to about 1,400 Wh/L, about 1,200 Wh/L to about 1,600 Wh/L, about 1,200 Wh/L to about 1,800 Wh/L, about 1,400 Wh/L to about 1,600 Wh/L, about 1,400 Wh/L to about 1,800 Wh/L, or about 1,600 Wh/L to about 1,800 Wh/L.

[0070] In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of about 30 Wh/kg to about 120 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of at least about 30 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte, and the carbon cloth, of at most about 120 Wh/kg. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of about 30 Wh/kg to about 40 Wh/kg, about 30 Wh/kg to about 50 Wh/kg, about 30 Wh/kg to about 60 Wh/kg, about 30 Wh/kg to about 70 Wh/kg, about 30 Wh/kg to about 80 Wh/kg, about 30 Wh/kg to about 90 Wh/kg, about 30 Wh/kg to about 100 Wh/kg, about 30 Wh/kg to about 120 Wh/kg, about 40 Wh/kg to about 50 Wh/kg, about 40 Wh/kg to about 60 Wh/kg, about 40 Wh/kg to about 70 Wh/kg, about 40 Wh/kg to about 80 Wh/kg, about 40 Wh/kg to about 90 Wh/kg, about 40 Wh/kg to about 100 Wh/kg, about 40 Wh/kg to about 120 Wh/kg, about 50 Wh/kg to about 60 Wh/kg, about 50 Wh/kg to about 70 Wh/kg, about 50 Wh/kg to about 80 Wh/kg, about 50 Wh/kg to about 90 Wh/kg, about 50 Wh/kg to about 100 Wh/kg, about 50 Wh/kg to about 120 Wh/kg, about 60 Wh/kg to about 70 Wh/kg, about 60 Wh/kg to about 80 Wh/kg, about 60 Wh/kg to about 90 Wh/kg, about 60 Wh/kg to about 100 Wh/kg, about 60 Wh/kg to about 120 Wh/kg, about 70 Wh/kg to about 80 Wh/kg, about 70 Wh/kg to about 90 Wh/kg, about 70 Wh/kg to about 100 Wh/kg, about 70 Wh/kg to about 120 Wh/kg, about 80 Wh/kg to about 90 Wh/kg, about 80 Wh/kg to about 100 Wh/kg, about 80 Wh/kg to about 120 Wh/kg, about 90 Wh/kg to about 100 Wh/kg, about 90 Wh/kg to about 120 Wh/kg, or about 100 Wh/kg to about 120 Wh/kg.

[0071] In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of about

40 Wh/L to about 180 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of at least about 40 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of at most about 180 Wh/L. In those embodiments, the supercapacitor has a gravimetric energy density, as normalized by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth, of about 40 Wh/L to about 50 Wh/L, about 40 Wh/L to about 60 Wh/L, about 40 Wh/L to about 70 Wh/L, about 40 Wh/L to about 80 Wh/L, about 40 Wh/L to about 90 Wh/L, about 40 Wh/L to about 100 Wh/L, about 40 Wh/L to about 120 Wh/L, about 40 Wh/L to about 140 Wh/L, about 40 Wh/L to about 160 Wh/L, about 40 Wh/L to about 180 Wh/L, about 50 Wh/L to about 60 Wh/L, about 50 Wh/L to about 70 Wh/L, about 50 Wh/L to about 80 Wh/L, about 50 Wh/L to about 90 Wh/L, about 50 Wh/L to about 100 Wh/L, about 50 Wh/L to about 120 Wh/L, about 50 Wh/L to about 140 Wh/L, about 50 Wh/L to about 160 Wh/L, about 50 Wh/L to about 180 Wh/L, about 60 Wh/L to about 70 Wh/L, about 60 Wh/L to about 80 Wh/L, about 60 Wh/L to about 90 Wh/L, about 60 Wh/L to about 100 Wh/L, about 60 Wh/L to about 120 Wh/L, about 60 Wh/L to about 140 Wh/L, about 60 Wh/L to about 160 Wh/L, about 60 Wh/L to about 180 Wh/L, about 70 Wh/L to about 80 Wh/L, about 70 Wh/L to about 90 Wh/L, about 70 Wh/L to about 100 Wh/L, about 70 Wh/L to about 120 Wh/L, about 70 Wh/L to about 140 Wh/L, about 70 Wh/L to about 160 Wh/L, about 70 Wh/L to about 180 Wh/L, about 80 Wh/L to about 90 Wh/L, about 80 Wh/L to about 100 Wh/L, about 80 Wh/L to about 120 Wh/L, about 80 Wh/L to about 140 Wh/L, about 80 Wh/L to about 160 Wh/L, about 80 Wh/L to about 180 Wh/L, about 90 Wh/L to about 100 Wh/L, about 90 Wh/L to about 120 Wh/L, about 90 Wh/L to about 140 Wh/L, about 90 Wh/L to about 160 Wh/L, about 90 Wh/L to about 180 Wh/L, about 100 Wh/L to about 120 Wh/L, about 100 Wh/L to about 140 Wh/L, about 100 Wh/L to about 160 Wh/L, about 100 Wh/L to about 180 Wh/L, about 120 Wh/L to about 140 Wh/L, about 120 Wh/L to about 160 Wh/L, about 120 Wh/L to about 180 Wh/L, about 140 Wh/L to about 160 Wh/L, about 140 Wh/L to about 180 Wh/L, or about 160 Wh/L to about 180 Wh/L.

[0072] A fourth aspect disclosed herein is a supercapacitor comprising three electrodes, wherein each electrode comprises an activated carbon electrode, a current collector, and an electrolyte. In some embodiments, the current collector is metallic. In some embodiments, the current collector is ferritic. In some embodiments, the current collector comprises stainless steel, crucible steel, carbon

steel, spring steel, alloy steel, maraging steel, weathering steel, tool steel, or any combination thereof.

[0073] In some embodiments, the electrolyte is disposed between the electrodes. In some embodiments, the electrolyte comprises an acid. In some embodiments, the electrolyte comprises a solvent. In some embodiments, the electrolyte comprises an acid and a solvent. In some
5
embodiments, the acid is a strong acid. In some embodiments, the strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid, p-toluenesulfonic acid, methanesulfonic acid, or any combination thereof. In some embodiments, the solvent comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide,
10
nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof.

[0074] In some embodiments, the electrolyte is a gel electrolyte, wherein the gel electrolyte comprises a quinone. In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 1 millimolar. In those embodiments, the concentration of the quinone is at least
15
about 0.25 millimolar. In those embodiments, the concentration of the quinone is at most about 1 millimolar. In those embodiments, the concentration of the quinone is about 0.25 millimolar to about 0.375 millimolar, about 0.25 millimolar to about 0.5 millimolar, about 0.25 millimolar to about 0.625 millimolar, about 0.25 millimolar to about 0.75 millimolar, about 0.25 millimolar to about 1 millimolar, about 0.375 millimolar to about 0.5 millimolar, about 0.375 millimolar to about 0.625
20
millimolar, about 0.375 millimolar to about 0.75 millimolar, about 0.375 millimolar to about 1 millimolar, about 0.5 millimolar to about 0.625 millimolar, about 0.5 millimolar to about 0.75 millimolar, about 0.5 millimolar to about 1 millimolar, about 0.625 millimolar to about 0.75 millimolar, about 0.625 millimolar to about 1 millimolar, or about 0.75 millimolar to about 1 millimolar.

[0075] In those embodiments, the supercapacitor has a working potential of about 0.2 V to about 1.2 V. In those embodiments, the supercapacitor has a working potential of at least about 0.2 V. In those
25
embodiments, the supercapacitor has a working potential of at most about 1.2 V. In those embodiments, the supercapacitor has a working potential of about 0.2 V to about 0.3 V, about 0.2 V to about 0.4 V, about 0.2 V to about 0.6 V, about 0.2 V to about 0.8 V, about 0.2 V to about 1 V, about 0.2 V to about 1.2 V, about 0.3 V to about 0.4 V, about 0.3 V to about 0.6 V, about 0.3 V to
30
about 0.8 V, about 0.3 V to about 1 V, about 0.3 V to about 1.2 V, about 0.4 V to about 0.6 V, about 0.4 V to about 0.8 V, about 0.4 V to about 1 V, about 0.4 V to about 1.2 V, about 0.6 V to about

0.8 V, about 0.6 V to about 1 V, about 0.6 V to about 1.2 V, about 0.8 V to about 1 V, about 0.8 V to about 1.2 V, or about 1 V to about 1.2 V.

[0076] In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of about 1,000 F/g to about 8,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of at least about 1,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of at most about 8,000 F/g. In those embodiments, the supercapacitor has a gravimetric capacitance, in a current density of about 10 A/g, of about 7,000 F/g to about 8,000 F/g, about 7,000 F/g to about 1,000 F/g, about 7,000 F/g to about 1,250 F/g, about 7,000 F/g to about 1,500 F/g, about 7,000 F/g to about 2,000 F/g, about 7,000 F/g to about 2,250 F/g, about 7,000 F/g to about 2,500 F/g, about 7,000 F/g to about 2,800 F/g, about 8,000 F/g to about 1,000 F/g, about 8,000 F/g to about 1,250 F/g, about 8,000 F/g to about 1,500 F/g, about 8,000 F/g to about 2,000 F/g, about 8,000 F/g to about 2,250 F/g, about 8,000 F/g to about 2,500 F/g, about 8,000 F/g to about 2,800 F/g, about 1,000 F/g to about 1,250 F/g, about 1,000 F/g to about 1,500 F/g, about 1,000 F/g to about 2,000 F/g, about 1,000 F/g to about 2,250 F/g, about 1,000 F/g to about 2,500 F/g, about 1,000 F/g to about 2,800 F/g, about 1,250 F/g to about 1,500 F/g, about 1,250 F/g to about 2,000 F/g, about 1,250 F/g to about 2,250 F/g, about 1,250 F/g to about 2,500 F/g, about 1,250 F/g to about 2,800 F/g, about 1,500 F/g to about 2,000 F/g, about 1,500 F/g to about 2,250 F/g, about 1,500 F/g to about 2,500 F/g, about 1,500 F/g to about 2,800 F/g, about 2,000 F/g to about 2,250 F/g, about 2,000 F/g to about 2,500 F/g, about 2,000 F/g to about 2,800 F/g, about 2,250 F/g to about 2,500 F/g, about 2,250 F/g to about 2,800 F/g, or about 2,500 F/g to about 2,800 F/g.

[0077] A fifth aspect provided herein is a method of fabricating a functionalized carbon electrode comprising the steps of functionalizing a carbon substrate, preparing the functionalized carbon substrate, formulating a polymerization fluid, and synthesizing a nanotube on the functionalized carbon substrate.

[0078] In some embodiments, the functionalized carbon electrode is a polyaniline functionalized carbon electrode. In some embodiments, the nanotube is a polyaniline nanotube.

[0079] In some embodiments the step of functionalizing a carbon substrate comprises forming an functionalization solution, heating the functionalization solution, cooling the functionalization solution, displacing a piece of carbon substrate into the functionalization solution, and rinsing a piece of functionalized carbon substrate. In some embodiments the substrate is rinsed in water.

[0080] In some embodiments, the functionalization solution comprises a strong acid comprising perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid, p-toluenesulfonic acid, methanesulfonic acid, and nitric acid, chloric acid, or any combination thereof.

5 [0081] In some embodiments, the functionalization solution comprises a first strong acid and a second strong acid wherein the first strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid, p-toluenesulfonic acid, methanesulfonic acid, nitric acid chloric acid, or any combination thereof. In some embodiments, the second strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid,
10 p-toluenesulfonic acid, methanesulfonic acid, nitric acid chloric acid, or any combination thereof.

[0082] In some embodiments, the functionalization solution comprises a volume percentage of the first strong acid of about 15% to about 60%. In some embodiments, the functionalization solution comprises a volume percentage of the first strong acid of at least about 15%. In some embodiments, the functionalization solution comprises a volume percentage of the first strong acid of at most about
15 60%. In some embodiments, the functionalization solution comprises a volume percentage of the first strong acid of about 15% to about 20%, about 15% to about 25%, about 15% to about 30%, about 15% to about 35%, about 15% to about 40%, about 15% to about 45%, about 15% to about 50%, about 15% to about 55%, about 15% to about 60%, about 20% to about 25%, about 20% to about 30%, about 20% to about 35%, about 20% to about 40%, about 20% to about 45%, about 20%
20 to about 50%, about 20% to about 55%, about 20% to about 60%, about 25% to about 30%, about 25% to about 35%, about 25% to about 40%, about 25% to about 45%, about 25% to about 50%, about 25% to about 55%, about 25% to about 60%, about 30% to about 35%, about 30% to about 40%, about 30% to about 45%, about 30% to about 50%, about 30% to about 55%, about 30% to about 60%, about 35% to about 40%, about 35% to about 45%, about 35% to about 50%, about 35%
25 to about 55%, about 35% to about 60%, about 40% to about 45%, about 40% to about 50%, about 40% to about 55%, about 40% to about 60%, about 45% to about 50%, about 45% to about 55%, about 45% to about 60%, about 50% to about 55%, about 50% to about 60%, or about 55% to about 60%.

[0083] In some embodiments, the functionalization solution is heated to a temperature of about
30 30 °C to about 120 °C. In some embodiments, the functionalization solution is heated to a temperature of at least about 30 °C. In some embodiments, the functionalization solution is heated to a temperature of at most about 120 °C. In some embodiments, the functionalization solution is

heated to a temperature of about 30 °C to about 40 °C, about 30 °C to about 50 °C, about 30 °C to about 60 °C, about 30 °C to about 70 °C, about 30 °C to about 80 °C, about 30 °C to about 90 °C, about 30 °C to about 100 °C, about 30 °C to about 110 °C, about 30 °C to about 120 °C, about 40 °C to about 50 °C, about 40 °C to about 60 °C, about 40 °C to about 70 °C, about 40 °C to about 80 °C, about 40 °C to about 90 °C, about 40 °C to about 100 °C, about 40 °C to about 110 °C, about 40 °C to about 120 °C, about 50 °C to about 60 °C, about 50 °C to about 70 °C, about 50 °C to about 80 °C, about 50 °C to about 90 °C, about 50 °C to about 100 °C, about 50 °C to about 110 °C, about 50 °C to about 120 °C, about 60 °C to about 70 °C, about 60 °C to about 80 °C, about 60 °C to about 90 °C, about 60 °C to about 100 °C, about 60 °C to about 110 °C, about 60 °C to about 120 °C, about 70 °C to about 80 °C, about 70 °C to about 90 °C, about 70 °C to about 100 °C, about 70 °C to about 110 °C, about 70 °C to about 120 °C, about 80 °C to about 90 °C, about 80 °C to about 100 °C, about 80 °C to about 110 °C, about 80 °C to about 120 °C, about 90 °C to about 100 °C, about 90 °C to about 110 °C, about 90 °C to about 120 °C, about 100 °C to about 110 °C, about 100 °C to about 120 °C, or about 110 °C to about 120 °C.

[0084] In some embodiments, the functionalization solution is heated for a period of about 60 minutes to about 240 minutes. In some embodiments, the functionalization solution is heated for a period of at least about 60 minutes. In some embodiments, the functionalization solution is heated for a period of at most about 240 minutes. In some embodiments, the functionalization solution is heated for a period of about 60 minutes to about 80 minutes, about 60 minutes to about 100 minutes, about 60 minutes to about 120 minutes, about 60 minutes to about 140 minutes, about 60 minutes to about 160 minutes, about 60 minutes to about 180 minutes, about 60 minutes to about 200 minutes, about 60 minutes to about 220 minutes, about 60 minutes to about 240 minutes, about 80 minutes to about 100 minutes, about 80 minutes to about 120 minutes, about 80 minutes to about 140 minutes, about 80 minutes to about 160 minutes, about 80 minutes to about 180 minutes, about 80 minutes to about 200 minutes, about 80 minutes to about 220 minutes, about 80 minutes to about 240 minutes, about 100 minutes to about 120 minutes, about 100 minutes to about 140 minutes, about 100 minutes to about 160 minutes, about 100 minutes to about 180 minutes, about 100 minutes to about 200 minutes, about 100 minutes to about 220 minutes, about 100 minutes to about 240 minutes, about 120 minutes to about 140 minutes, about 120 minutes to about 160 minutes, about 120 minutes to about 180 minutes, about 120 minutes to about 200 minutes, about 120 minutes to about 220 minutes, about 120 minutes to about 240 minutes, about 140 minutes to about 160 minutes, about 140 minutes to about 180 minutes, about 140 minutes to about 200 minutes, about 140 minutes to

about 220 minutes, about 140 minutes to about 240 minutes, about 160 minutes to about 180 minutes, about 160 minutes to about 200 minutes, about 160 minutes to about 220 minutes, about 160 minutes to about 240 minutes, about 180 minutes to about 200 minutes, about 180 minutes to about 220 minutes, about 180 minutes to about 240 minutes, about 200 minutes to about 220 minutes, about 200 minutes to about 240 minutes, or about 220 minutes to about 240 minutes.

[0085] In some embodiments, the functionalization solution is cooled to room temperature. In some embodiments, the water is deionized.

[0086] In some embodiments, the water is heated to a temperature of about 5 °C to about 40 °C. In some embodiments, the water is heated to a temperature of at least about 5 °C. In some embodiments, the water is heated to a temperature of at most about 40 °C. In some embodiments, the water is heated to a temperature of about 5 °C to about 10 °C, about 5 °C to about 15 °C, about 5 °C to about 20 °C, about 5 °C to about 25 °C, about 5 °C to about 30 °C, about 5 °C to about 35 °C, about 5 °C to about 40 °C, about 10 °C to about 15 °C, about 10 °C to about 20 °C, about 10 °C to about 25 °C, about 10 °C to about 30 °C, about 10 °C to about 35 °C, about 10 °C to about 40 °C, about 15 °C to about 20 °C, about 15 °C to about 25 °C, about 15 °C to about 30 °C, about 15 °C to about 35 °C, about 15 °C to about 40 °C, about 20 °C to about 25 °C, about 20 °C to about 30 °C, about 20 °C to about 35 °C, about 20 °C to about 40 °C, about 25 °C to about 30 °C, about 25 °C to about 35 °C, about 25 °C to about 40 °C, about 30 °C to about 35 °C, about 30 °C to about 40 °C, or about 35 °C to about 40 °C.

[0087] In some embodiments, the volume of water is about 0.5 liters (L) to about 2 L. In some embodiments, the volume of water is at least about 0.5 L. In some embodiments, the volume of water is at most about 2 L. In some embodiments, the volume of water is about 0.5 L to about 0.625 L, about 0.5 L to about 0.75 L, about 0.5 L to about 0.875 L, about 0.5 L to about 1 L, about 0.5 L to about 1.25 L, about 0.5 L to about 1.5 L, about 0.5 L to about 1.75 L, about 0.5 L to about 2 L, about 0.625 L to about 0.75 L, about 0.625 L to about 0.875 L, about 0.625 L to about 1 L, about 0.625 L to about 1.25 L, about 0.625 L to about 1.5 L, about 0.625 L to about 1.75 L, about 0.625 L to about 2 L, about 0.75 L to about 0.875 L, about 0.75 L to about 1 L, about 0.75 L to about 1.25 L, about 0.75 L to about 1.5 L, about 0.75 L to about 1.75 L, about 0.75 L to about 2 L, about 0.875 L to about 1 L, about 0.875 L to about 1.25 L, about 0.875 L to about 1.5 L, about 0.875 L to about 1.75 L, about 0.875 L to about 2 L, about 1 L to about 1.25 L, about 1 L to about 1.5 L, about 1 L to about 1.75 L, about 1 L to about 2 L, about 1.25 L to about 1.5 L, about 1.25 L to about

1.75 L, about 1.25 L to about 2 L, about 1.5 L to about 1.75 L, about 1.5 L to about 2 L, or about 1.75 L to about 2 L.

[0088] In some embodiments, the carbon substrate is comprised of a carbon cloth, carbon fiber, amorphous carbon, glassy carbon, carbon nanofoam, carbon aerogel, or any combination thereof.

5 [0089] In some embodiments, the functionalized carbon substrate is annealed after functionalization.

[0090] In some embodiments, the annealing temperature is about 100 °C to about 400 °C. In some embodiments, the annealing temperature is at least about 100 °C. In some embodiments, the annealing temperature is at most about 400 °C. In some embodiments, the annealing temperature is
 10 about 100 °C to about 150 °C, about 100 °C to about 200 °C, about 100 °C to about 250 °C, about 100 °C to about 300 °C, about 100 °C to about 350 °C, about 100 °C to about 400 °C, about 150 °C to about 200 °C, about 150 °C to about 250 °C, about 150 °C to about 300 °C, about 150 °C to about 350 °C, about 150 °C to about 400 °C, about 200 °C to about 250 °C, about 200 °C to about 300 °C, about 200 °C to about 350 °C, about 200 °C to about 400 °C, about 250 °C to about 300 °C, about
 15 250 °C to about 350 °C, about 250 °C to about 400 °C, about 300 °C to about 350 °C, about 300 °C to about 400 °C, or about 350 °C to about 400 °C.

[0091] In some embodiments, the functionalized carbon substrate is annealed for a period of about 0.5 hours to about 14 hours. In some embodiments, the functionalized carbon substrate is annealed for a period of at least about 0.5 hours. In some embodiments, the functionalized carbon substrate is
 20 annealed for a period of at most about 14 hours. In some embodiments, the functionalized carbon substrate is annealed for a period of about 0.5 hours to about 1 hour, about 0.5 hours to about 2 hours, about 0.5 hours to about 5 hours, about 0.5 hours to about 7 hours, about 0.5 hours to about 9 hours, about 0.5 hours to about 11 hours, about 0.5 hours to about 14 hours, about 1 hour to about 2 hours, about 1 hour to about 5 hours, about 1 hour to about 7 hours, about 1 hour to about 9 hours,
 25 about 1 hour to about 11 hours, about 1 hour to about 14 hours, about 2 hours to about 5 hours, about 2 hours to about 7 hours, about 2 hours to about 9 hours, about 2 hours to about 11 hours, about 2 hours to about 14 hours, about 5 hours to about 7 hours, about 5 hours to about 9 hours, about 5 hours to about 11 hours, about 5 hours to about 14 hours, about 7 hours to about 9 hours, about 7 hours to about 11 hours, about 7 hours to about 14 hours, about 9 hours to about 11 hours, about 9
 30 hours to about 14 hours, or about 11 hours to about 14 hours.

[0092] In some embodiments, the step of preparing the functionalized carbon substrate comprises cutting a piece of functionalized carbon substrate, submerging the piece of functionalized carbon

substrate in a solvent solution, sonicating the piece functionalized carbon substrate in the solvent solution, and drying the piece of functionalized carbon substrate.

[0093] In some embodiments, the functionalized carbon substrate has a geometric area of about 0.1 square centimeters (cm²) to about 0.5 cm². In some embodiments, the functionalized carbon substrate has a geometric area of at least about 0.1 cm². In some embodiments, the functionalized carbon substrate has a geometric area of at most about 0.5 cm². In some embodiments, the functionalized carbon substrate has a geometric area of about 0.1 cm² to about 0.2 cm², about 0.1 cm² to about 0.3 cm², about 0.1 cm² to about 0.4 cm², about 0.1 cm² to about 0.5 cm², about 0.2 cm² to about 0.3 cm², about 0.2 cm² to about 0.4 cm², about 0.2 cm² to about 0.5 cm², about 0.3 cm² to about 0.4 cm², about 0.3 cm² to about 0.5 cm², or about 0.4 cm² to about 0.5 cm².

[0094] In some embodiments, the solvent solution comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide, nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof. In some embodiments, the solvent solution comprises a first solvent and a second solvent. In some embodiments, the first solvent solution comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide, nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof. In some embodiments, the second solvent solution comprises tetrahydrofuran, ethyl acetate, dimethylformamide, acetonitrile, acetone, dimethyl sulfoxide, nitromethane, propylene carbonate, ethanol, formic acid, n-butanol, methanol, acetic acid, water, or any combination thereof.

[0095] In some embodiments, the first solvent comprises a volume percentage of the solvent solution of about 25% to about 95%. In some embodiments, the first solvent comprises a volume percentage of the solvent solution of at least about 25%. In some embodiments, the first solvent comprises a volume percentage of the solvent solution of at most about 95%. In some embodiments, the first solvent comprises a volume percentage of the solvent solution of about 25% to about 35%, about 25% to about 45%, about 25% to about 55%, about 25% to about 65%, about 25% to about 75%, about 25% to about 85%, about 25% to about 95%, about 35% to about 45%, about 35% to about 55%, about 35% to about 65%, about 35% to about 75%, about 35% to about 85%, about 35% to about 95%, about 45% to about 55%, about 45% to about 65%, about 45% to about 75%, about 45% to about 85%, about 45% to about 95%, about 55% to about 65%, about 55% to about 75%, about 55% to about 85%, about 55% to about 95%, about 65% to about 75%, about 65% to about

85%, about 65% to about 95%, about 75% to about 85%, about 75% to about 95%, or about 85% to about 95%.

- 5 [0096] In some embodiments, the period of sonication is about 30 minutes to about 60 minutes. In some embodiments, the period of sonication is at least about 30 minutes. In some embodiments, the period of sonication is at most about 60 minutes. In some embodiments, the period of sonication is about 30 minutes to about 35 minutes, about 30 minutes to about 40 minutes, about 30 minutes to about 45 minutes, about 30 minutes to about 50 minutes, about 30 minutes to about 55 minutes, about 30 minutes to about 60 minutes, about 35 minutes to about 40 minutes, about 35 minutes to about 45 minutes, about 35 minutes to about 50 minutes, about 35 minutes to about 55 minutes, about 35 minutes to about 60 minutes, about 40 minutes to about 45 minutes, about 40 minutes to about 50 minutes, about 40 minutes to about 55 minutes, about 40 minutes to about 60 minutes, about 45 minutes to about 50 minutes, about 45 minutes to about 55 minutes, about 45 minutes to about 60 minutes, about 50 minutes to about 55 minutes, about 50 minutes to about 60 minutes, or about 55 minutes to about 60 minutes.
- 10 [0097] In some embodiments, the drying occurs at a temperature of about 30 °C to about 120 °C. In some embodiments, the drying occurs at a temperature of at least about 30 °C. In some embodiments, the drying occurs at a temperature of at most about 120 °C. In some embodiments, the drying occurs at a temperature of about 30 °C to about 40 °C, about 30 °C to about 50 °C, about 30 °C to about 60 °C, about 30 °C to about 70 °C, about 30 °C to about 80 °C, about 30 °C to about 90 °C, about 30 °C to about 100 °C, about 30 °C to about 110 °C, about 30 °C to about 120 °C, about 40 °C to about 50 °C, about 40 °C to about 60 °C, about 40 °C to about 70 °C, about 40 °C to about 80 °C, about 40 °C to about 90 °C, about 40 °C to about 100 °C, about 40 °C to about 110 °C, about 40 °C to about 120 °C, about 50 °C to about 60 °C, about 50 °C to about 70 °C, about 50 °C to about 80 °C, about 50 °C to about 90 °C, about 50 °C to about 100 °C, about 50 °C to about 110 °C, about 50 °C to about 120 °C, about 60 °C to about 70 °C, about 60 °C to about 80 °C, about 60 °C to about 90 °C, about 60 °C to about 100 °C, about 60 °C to about 110 °C, about 60 °C to about 120 °C, about 70 °C to about 80 °C, about 70 °C to about 90 °C, about 70 °C to about 100 °C, about 70 °C to about 110 °C, about 70 °C to about 120 °C, about 80 °C to about 90 °C, about 80 °C to about 100 °C, about 80 °C to about 110 °C, about 80 °C to about 120 °C, about 90 °C to about 100 °C, about 90 °C to about 110 °C, about 90 °C to about 120 °C, about 100 °C to about 110 °C, about 100 °C to about 120 °C, or about 110 °C to about 120 °C.
- 15
20
25
30

[0098] In some embodiments, the drying occurs over a period of time of about 3 hours to about 12 hours. In some embodiments, the drying occurs over a period of time of at least about 3 hours. In some embodiments, the drying occurs over a period of time of at most about 12 hours. In some embodiments, the drying occurs over a period of time of about 3 hours to about 4 hours, about 3 hours to about 5 hours, about 3 hours to about 6 hours, about 3 hours to about 7 hours, about 3 hours to about 8 hours, about 3 hours to about 9 hours, about 3 hours to about 10 hours, about 3 hours to about 11 hours, about 3 hours to about 12 hours, about 4 hours to about 5 hours, about 4 hours to about 6 hours, about 4 hours to about 7 hours, about 4 hours to about 8 hours, about 4 hours to about 9 hours, about 4 hours to about 10 hours, about 4 hours to about 11 hours, about 4 hours to about 12 hours, about 5 hours to about 6 hours, about 5 hours to about 7 hours, about 5 hours to about 8 hours, about 5 hours to about 9 hours, about 5 hours to about 10 hours, about 5 hours to about 11 hours, about 5 hours to about 12 hours, about 6 hours to about 7 hours, about 6 hours to about 8 hours, about 6 hours to about 9 hours, about 6 hours to about 10 hours, about 6 hours to about 11 hours, about 6 hours to about 12 hours, about 7 hours to about 8 hours, about 7 hours to about 9 hours, about 7 hours to about 10 hours, about 7 hours to about 11 hours, about 7 hours to about 12 hours, about 8 hours to about 9 hours, about 8 hours to about 10 hours, about 8 hours to about 11 hours, about 8 hours to about 12 hours, about 9 hours to about 10 hours, about 9 hours to about 11 hours, about 9 hours to about 12 hours, about 10 hours to about 11 hours, about 10 hours to about 12 hours, or about 11 hours to about 12 hours.

[0099] In some embodiments the step of formulating a polymerization fluid comprises forming a polymerization solution comprising a conducting polymer, an acid, a detergent, water, and an oxidizing agent and stirring the polymerization solution. In some embodiments, the conducting polymer comprises polyaniline, poly(p-phenylene oxide), poly(p-phenylene sulfide), poly(3,4-ethylenedioxythiophene), polypyrrole, polythiophene, poly(3-alkylthiophene), poly(3-methylthiophene), poly(3-hexylthiophene), or any combination thereof.

[00100] In some embodiments, the conducting polymer is distilled. In some embodiments, the conducting polymer is distilled by steam. In some embodiments, the steam comprises water, petroleum, oil, lipids, petrochemicals, or any combination thereof.

[00101] In some embodiments, the mass of the conducting polymer is about 20 milligrams (mg) to about 90 mg. In some embodiments, the mass of the conducting polymer is at least about 20 mg. In some embodiments, the mass of the conducting polymer is at most about 90 mg. In some embodiments, the mass of the conducting polymer is about 20 mg to about 30 mg, about 20 mg to

about 40 mg, about 20 mg to about 50 mg, about 20 mg to about 60 mg, about 20 mg to about 70 mg, about 20 mg to about 80 mg, about 20 mg to about 90 mg, about 30 mg to about 40 mg, about 30 mg to about 50 mg, about 30 mg to about 60 mg, about 30 mg to about 70 mg, about 30 mg to about 80 mg, about 30 mg to about 90 mg, about 40 mg to about 50 mg, about 40 mg to about 60 mg, about 40 mg to about 70 mg, about 40 mg to about 80 mg, about 40 mg to about 90 mg, about 50 mg to about 60 mg, about 50 mg to about 70 mg, about 50 mg to about 80 mg, about 50 mg to about 90 mg, about 60 mg to about 70 mg, about 60 mg to about 80 mg, about 60 mg to about 90 mg, about 70 mg to about 80 mg, about 70 mg to about 90 mg, or about 80 mg to about 90 mg.

[00102] In some embodiments, the acid is aqueous. In some embodiments, the acid comprises a strong acid. In some embodiments, the strong acid comprises perchloric acid, hydroiodic acid, hydrobromic acid, hydrochloric acid, sulfuric acid, p-toluenesulfonic acid, methanesulfonic acid, nitric acid, chloric acid, or any combination thereof.

[00103] In some embodiments, the concentration of the acid is about 0.1 M to about 0.5 M. In some embodiments, the concentration of the acid is at least about 0.1 M. In some embodiments, the concentration of the acid is at most about 0.5 M. In some embodiments, the concentration of the acid is about 0.1 M to about 0.2 M, about 0.1 M to about 0.3 M, about 0.1 M to about 0.4 M, about 0.1 M to about 0.5 M, about 0.2 M to about 0.3 M, about 0.2 M to about 0.4 M, about 0.2 M to about 0.5 M, about 0.3 M to about 0.4 M, about 0.3 M to about 0.5 M, or about 0.4 M to about 0.5 M.

[00104] In some embodiments, the volume of the acid is about 0.1 milliliters (ml) to about 0.6 ml.

In some embodiments, the volume of the acid is at least about 0.1 ml. In some embodiments, the volume of the acid is at most about 0.6 ml. In some embodiments, the volume of the acid is about 0.1 ml to about 0.2 ml, about 0.1 ml to about 0.3 ml, about 0.1 ml to about 0.4 ml, about 0.1 ml to about 0.5 ml, about 0.1 ml to about 0.6 ml, about 0.2 ml to about 0.3 ml, about 0.2 ml to about 0.4 ml, about 0.2 ml to about 0.5 ml, about 0.2 ml to about 0.6 ml, about 0.3 ml to about 0.4 ml, about 0.3 ml to about 0.5 ml, about 0.3 ml to about 0.6 ml, about 0.4 ml to about 0.5 ml, about 0.4 ml to about 0.6 ml, or about 0.5 ml to about 0.6 ml.

[00105] In some embodiments, the detergent comprises, dioctyl sodium sulfosuccinate, perfluorooctanesulfonate, perfluorobutanesulfonate, alkyl-aryl ether phosphates, alkyl ether phosphates, cetrimonium bromide, cetylpyridinium chloride, benzalkonium chloride, benzethonium chloride, dimethyldioctadecylammonium chloride, dioctadecyldimethylammonium bromide, octenidine dihydrochloride, octaethylene glycol monododecyl ether, pentaethylene glycol monododecyl ether, polypropylene glycol alkyl ethers, decyl glucoside, lauryl glucoside, octyl

glucoside, polyethylene glycol octylphenyl ethers, polyethylene glycol alkylphenyl ethers, nonoxynol-9, glycerol alkyl esters, glyceryl laurate, polyoxyethylene glycol sorbitan alkyl esters, polysorbate sorbitan alkyl esters, dodecyldimethylamine oxide, poloxamers, polyethoxylated tallow amine, or any combination thereof.

5 [00106] In some embodiments, the mass of the detergent is about 1 mg to about 10 mg. In some
embodiments, the mass of the detergent is at least about 1 mg. In some embodiments, the mass of the
detergent is at most about 10 mg. In some embodiments, the mass of the detergent is about 1 mg to
about 2 mg, about 1 mg to about 3 mg, about 1 mg to about 4 mg, about 1 mg to about 5 mg, about
1 mg to about 6 mg, about 1 mg to about 7 mg, about 1 mg to about 8 mg, about 1 mg to about 9 mg,
10 about 1 mg to about 10 mg, about 2 mg to about 3 mg, about 2 mg to about 4 mg, about 2 mg to
about 5 mg, about 2 mg to about 6 mg, about 2 mg to about 7 mg, about 2 mg to about 8 mg, about
2 mg to about 9 mg, about 2 mg to about 10 mg, about 3 mg to about 4 mg, about 3 mg to about
5 mg, about 3 mg to about 6 mg, about 3 mg to about 7 mg, about 3 mg to about 8 mg, about 3 mg to
15 about 9 mg, about 3 mg to about 10 mg, about 4 mg to about 5 mg, about 4 mg to about 6 mg, about
4 mg to about 7 mg, about 4 mg to about 8 mg, about 4 mg to about 9 mg, about 4 mg to about
10 mg, about 5 mg to about 6 mg, about 5 mg to about 7 mg, about 5 mg to about 8 mg, about 5 mg
to about 9 mg, about 5 mg to about 10 mg, about 6 mg to about 7 mg, about 6 mg to about 8 mg,
about 6 mg to about 9 mg, about 6 mg to about 10 mg, about 7 mg to about 8 mg, about 7 mg to
about 9 mg, about 7 mg to about 10 mg, about 8 mg to about 9 mg, about 8 mg to about 10 mg, or
20 about 9 mg to about 10 mg.

[00107] In some embodiments, the volume of the water is about 9 ml to about 40 ml. In some
embodiments, the volume of the water is at least about 9 ml. In some embodiments, the volume of
the water is at most about 40 ml. In some embodiments, the volume of the water is about 9 ml to
about 10 ml, about 9 ml to about 15 ml, about 9 ml to about 20 ml, about 9 ml to about 25 ml, about
25 9 ml to about 30 ml, about 9 ml to about 35 ml, about 9 ml to about 40 ml, about 10 ml to about
15 ml, about 10 ml to about 20 ml, about 10 ml to about 25 ml, about 10 ml to about 30 ml, about
10 ml to about 35 ml, about 10 ml to about 40 ml, about 15 ml to about 20 ml, about 15 ml to about
25 ml, about 15 ml to about 30 ml, about 15 ml to about 35 ml, about 15 ml to about 40 ml, about
20 ml to about 25 ml, about 20 ml to about 30 ml, about 20 ml to about 35 ml, about 20 ml to about
30 40 ml, about 25 ml to about 30 ml, about 25 ml to about 35 ml, about 25 ml to about 40 ml, about
30 ml to about 35 ml, about 30 ml to about 40 ml, or about 35 ml to about 40 ml.

[00108] In some embodiments, the oxidizing agent comprises ammonium persulfate and oxygen, ozone, hydrogen peroxide, fluorine, chlorine, halogens, nitric acid, sulfuric acid, peroxydisulfuric acid, peroxymonosulfuric acid, chlorite, perchlorate, hypochlorite, household bleach, chromic acid, dichromic acid, chromium trioxide, pyridinium chlorochromate, permanganate, sodium perborate, nitrous oxide, potassium nitrate, sodium bismuthate, or any combination thereof. In some
5
embodiments, the oxidizing agent is added in one portion.

[00109] In some embodiments, the concentration of the oxidizing agent is about 0.1 M to about 0.5 M. In some embodiments, the concentration of the oxidizing agent is at least about 0.1 M. In some
10
embodiments, the concentration of the oxidizing agent is at most about 0.5 M. In some
embodiments, the concentration of the oxidizing agent is about 0.1 M to about 0.2 M, about 0.1 M to about 0.3 M, about 0.1 M to about 0.4 M, about 0.1 M to about 0.5 M, about 0.2 M to about 0.3 M, about 0.2 M to about 0.4 M, about 0.2 M to about 0.5 M, about 0.3 M to about 0.4 M, about 0.3 M to about 0.5 M, or about 0.4 M to about 0.5 M.

[00110] In some embodiments, the mass of the oxidizing agent is about 1 mg to about 10 mg. In
15
some embodiments, the mass of the oxidizing agent is at least about 1 mg. In some embodiments, the mass of the oxidizing agent is at most about 10 mg. In some embodiments, the mass of the oxidizing agent is about 1 mg to about 2 mg, about 1 mg to about 3 mg, about 1 mg to about 4 mg, about 1 mg to about 5 mg, about 1 mg to about 6 mg, about 1 mg to about 7 mg, about 1 mg to about 8 mg, about 1 mg to about 9 mg, about 1 mg to about 10 mg, about 2 mg to about 3 mg, about 2 mg to
20
about 4 mg, about 2 mg to about 5 mg, about 2 mg to about 6 mg, about 2 mg to about 7 mg, about 2 mg to about 8 mg, about 2 mg to about 9 mg, about 2 mg to about 10 mg, about 3 mg to about 4 mg, about 3 mg to about 5 mg, about 3 mg to about 6 mg, about 3 mg to about 7 mg, about 3 mg to about 8 mg, about 3 mg to about 9 mg, about 3 mg to about 10 mg, about 4 mg to about 5 mg, about 4 mg to about 6 mg, about 4 mg to about 7 mg, about 4 mg to about 8 mg, about 4 mg to about 9 mg,
25
about 4 mg to about 10 mg, about 5 mg to about 6 mg, about 5 mg to about 7 mg, about 5 mg to about 8 mg, about 5 mg to about 9 mg, about 5 mg to about 10 mg, about 6 mg to about 7 mg, about 6 mg to about 8 mg, about 6 mg to about 9 mg, about 6 mg to about 10 mg, about 7 mg to about 8 mg, about 7 mg to about 9 mg, about 7 mg to about 10 mg, about 8 mg to about 9 mg, about 8 mg to about 10 mg, or about 9 mg to about 10 mg.

[00111] In some embodiments, the polymerization solution is stirred at room temperature.

[00112] In some embodiments, the polymerization solution is stirred for a period of time of about 10 minutes to about 40 minutes. In some embodiments, the polymerization solution is stirred for a

period of time of at least about 10 minutes. In some embodiments, the polymerization solution is stirred for a period of time of at most about 40 minutes. In some embodiments, the polymerization solution is stirred for a period of time of about 10 minutes to about 15 minutes, about 10 minutes to about 20 minutes, about 10 minutes to about 25 minutes, about 10 minutes to about 30 minutes, about 10 minutes to about 35 minutes, about 10 minutes to about 40 minutes, about 15 minutes to about 20 minutes, about 15 minutes to about 25 minutes, about 15 minutes to about 30 minutes, about 15 minutes to about 35 minutes, about 15 minutes to about 40 minutes, about 20 minutes to about 25 minutes, about 20 minutes to about 30 minutes, about 20 minutes to about 35 minutes, about 20 minutes to about 40 minutes, about 25 minutes to about 30 minutes, about 25 minutes to about 35 minutes, about 25 minutes to about 40 minutes, about 30 minutes to about 35 minutes, about 30 minutes to about 40 minutes, or about 35 minutes to about 40 minutes.

[00113] In some embodiments, the polymerization solution is stirred before the addition of the oxidizing agent. In some embodiments, the polymerization solution is stirred by a magnetic stirrer.

[00114] In some embodiments, the step of synthesizing a nanotube on the functionalized carbon substrate comprises stirring the polymerization fluid, immersing the functionalized carbon substrate in the polymerization fluid, storing the functionalized carbon substrate in the polymerization fluid, removing a functionalized carbon substrate from the polymerization fluid, washing the functionalized carbon substrate with water, and drying the functionalized carbon substrate. In some embodiments washing the functionalized carbon substrate with water removes excess polymerization fluid. In some embodiments, the functionalized carbon substrate is a polyaniline functionalized carbon substrate.

[00115] In some embodiments, polymerization fluid is stirred violently. In some embodiments, polymerization fluid is stirred non-violently. In some embodiments, the functionalized carbon substrate and the polymerization fluid are stored without agitation. In some embodiments, the functionalized carbon substrate and the polymerization fluid are stored with agitation.

[00116] In some embodiments, the polymerization fluid is stirred for a period of time of about 15 seconds to about 60 seconds. In some embodiments, the polymerization fluid is stirred for a period of time of at least about 15 seconds. In some embodiments, the polymerization fluid is stirred for a period of time of at most about 60 seconds. In some embodiments, the polymerization fluid is stirred for a period of time of about 15 seconds to about 20 seconds, about 15 seconds to about 25 seconds, about 15 seconds to about 30 seconds, about 15 seconds to about 35 seconds, about 15 seconds to about 40 seconds, about 15 seconds to about 45 seconds, about 15 seconds to about 50 seconds,

about 15 seconds to about 55 seconds, about 15 seconds to about 60 seconds, about 20 seconds to about 25 seconds, about 20 seconds to about 30 seconds, about 20 seconds to about 35 seconds, about 20 seconds to about 40 seconds, about 20 seconds to about 45 seconds, about 20 seconds to about 50 seconds, about 20 seconds to about 55 seconds, about 20 seconds to about 60 seconds, about 25 seconds to about 30 seconds, about 25 seconds to about 35 seconds, about 25 seconds to about 40 seconds, about 25 seconds to about 45 seconds, about 25 seconds to about 50 seconds, about 25 seconds to about 55 seconds, about 25 seconds to about 60 seconds, about 30 seconds to about 35 seconds, about 30 seconds to about 40 seconds, about 30 seconds to about 45 seconds, about 30 seconds to about 50 seconds, about 30 seconds to about 55 seconds, about 30 seconds to about 60 seconds, about 35 seconds to about 40 seconds, about 35 seconds to about 45 seconds, about 35 seconds to about 50 seconds, about 35 seconds to about 55 seconds, about 35 seconds to about 60 seconds, about 40 seconds to about 45 seconds, about 40 seconds to about 50 seconds, about 40 seconds to about 55 seconds, about 40 seconds to about 60 seconds, about 45 seconds to about 50 seconds, about 45 seconds to about 55 seconds, about 45 seconds to about 60 seconds, about 50 seconds to about 55 seconds, about 50 seconds to about 60 seconds, or about 55 seconds to about 60 seconds.

[00117] In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid at a temperature of about 10 °C to about 50 °C. In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid at a temperature of at least about 10 °C. In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid at a temperature of at most about 50 °C. In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid at a temperature of about 10 °C to about 15 °C, about 10 °C to about 20 °C, about 10 °C to about 25 °C, about 10 °C to about 30 °C, about 10 °C to about 35 °C, about 10 °C to about 40 °C, about 10 °C to about 45 °C, about 10 °C to about 50 °C, about 15 °C to about 20 °C, about 15 °C to about 25 °C, about 15 °C to about 30 °C, about 15 °C to about 35 °C, about 15 °C to about 40 °C, about 15 °C to about 45 °C, about 15 °C to about 50 °C, about 20 °C to about 25 °C, about 20 °C to about 30 °C, about 20 °C to about 35 °C, about 20 °C to about 40 °C, about 20 °C to about 45 °C, about 20 °C to about 50 °C, about 25 °C to about 30 °C, about 25 °C to about 35 °C, about 25 °C to about 40 °C, about 25 °C to about 45 °C, about 25 °C to about 50 °C, about 30 °C to about 35 °C, about 30 °C to about 40 °C, about 30 °C to about 45 °C, about 30 °C to about 50 °C, about 35 °C to about 40 °C, about 35 °C to about 45 °C, about 35 °C to about 50 °C, about 40 °C to about 45 °C, about 40 °C to about 50 °C, or about 45 °C to about 50 °C.

[00118] In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid for a period of time of about 8 hours to about 70 hours. In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid for a period of time of at least about 8 hours. In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid for a period of time of at most about 70 hours. In some embodiments, the functionalized carbon substrate is stored in the polymerization fluid for a period of time of about 8 hours to about 10 hours, about 8 hours to about 20 hours, about 8 hours to about 30 hours, about 8 hours to about 40 hours, about 8 hours to about 50 hours, about 8 hours to about 60 hours, about 8 hours to about 70 hours, about 10 hours to about 20 hours, about 10 hours to about 30 hours, about 10 hours to about 40 hours, about 10 hours to about 50 hours, about 10 hours to about 60 hours, about 10 hours to about 70 hours, about 20 hours to about 30 hours, about 20 hours to about 40 hours, about 20 hours to about 50 hours, about 20 hours to about 60 hours, about 20 hours to about 70 hours, about 30 hours to about 40 hours, about 30 hours to about 50 hours, about 30 hours to about 60 hours, about 30 hours to about 70 hours, about 40 hours to about 50 hours, about 40 hours to about 60 hours, about 40 hours to about 70 hours, about 50 hours to about 60 hours, about 50 hours to about 70 hours, or about 60 hours to about 70 hours.

[00119] In some embodiments, the functionalized carbon substrate is dried at a temperature of about 30 hours to about 120 hours. In some embodiments, the functionalized carbon substrate is dried at a temperature of at least about 30 hours. In some embodiments, the functionalized carbon substrate is dried at a temperature of at most about 120 hours. In some embodiments, the functionalized carbon substrate is dried at a temperature of about 30 hours to about 40 hours, about 30 hours to about 50 hours, about 30 hours to about 60 hours, about 30 hours to about 70 hours, about 30 hours to about 80 hours, about 30 hours to about 90 hours, about 30 hours to about 100 hours, about 30 hours to about 110 hours, about 30 hours to about 120 hours, about 40 hours to about 50 hours, about 40 hours to about 60 hours, about 40 hours to about 70 hours, about 40 hours to about 80 hours, about 40 hours to about 90 hours, about 40 hours to about 100 hours, about 40 hours to about 110 hours, about 40 hours to about 120 hours, about 50 hours to about 60 hours, about 50 hours to about 70 hours, about 50 hours to about 80 hours, about 50 hours to about 90 hours, about 50 hours to about 100 hours, about 50 hours to about 110 hours, about 50 hours to about 120 hours, about 60 hours to about 70 hours, about 60 hours to about 80 hours, about 60 hours to about 90 hours, about 60 hours to about 100 hours, about 60 hours to about 110 hours, about 60 hours to about 120 hours, about 70 hours to about 80 hours, about 70 hours to about 90 hours,

about 70 hours to about 100 hours, about 70 hours to about 110 hours, about 70 hours to about 120 hours, about 80 hours to about 90 hours, about 80 hours to about 100 hours, about 80 hours to about 110 hours, about 80 hours to about 120 hours, about 90 hours to about 100 hours, about 90 hours to about 110 hours, about 90 hours to about 120 hours, about 100 hours to about 110 hours, about 100 hours to about 120 hours, or about 110 hours to about 120 hours.

[00120] Other goals and advantages of the methods and devices taught herein will be further appreciated and understood when considered in conjunction with the following description and accompanying drawings. While the following description may contain specific details describing particular embodiments of the methods and devices taught herein, this should not be construed as limitations to the scope of the methods and devices taught herein but rather as an exemplification of preferable embodiments. For each aspect of the methods and devices taught herein, many variations are possible as suggested herein that are known to those of ordinary skill in the art. A variety of changes and modifications may be made within the scope of the methods and devices taught herein without departing from the spirit thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

[00121] The novel features of the methods and devices taught herein are set forth with particularity in the appended claims. A better understanding of the features and advantages of the present methods and devices taught herein will be obtained by reference to the following detailed description that sets forth illustrative embodiments, in which the principles of the methods and devices taught herein are utilized, and the accompanying drawings or figures (also “**FIG.**” and “**FIG.s**” herein), of which:

[00122] **FIG. 1A** illustratively depicts electron and ion transfer pathways in a nanofiber morphology of polyaniline, in accordance with some embodiments.

[00123] **FIG. 1B** illustratively depicts electron and ion transfer pathways in a nanosphere morphology of polyaniline (PANI), in accordance with some embodiments.

[00124] **FIG. 1C** illustratively depicts electron and ion transfer pathways in a nanotube morphology of polyaniline, in accordance with some embodiments.

[00125] **FIG. 2** illustratively depicts an exemplary asymmetric device, in accordance with some embodiments.

[00126] **FIG. 3** illustratively depicts an exemplary process of functionalizing carbon cloth, in accordance with some embodiments.

[00127] FIG. 4 illustratively depicts an example of the bonds that change through the connection between PANI and functionalized carbon cloth (FCC), in accordance with some embodiments.

[00128] FIG. 5A displays exemplary field emission scanning electron microscope (FESEM) images of PANI synthesized on carbon cloth (CC) in the presence of sodium dodecyl sulfate (SDS), in
5 accordance with some embodiments.

[00129] FIG. 5B displays exemplary FESEM images of PANI synthesized on CC in the presence of SDS, in accordance with some embodiments.

[00130] FIG. 6A displays an exemplary FESEM image of the surface structure of a CC, in accordance with some embodiments.

10 [00131] FIG. 6B displays an exemplary FESEM image of a 16-hour polymerized PANI-CC in high magnification, in accordance with some embodiments.

[00132] FIG. 6C displays an exemplary FESEM image of a 16-hour polymerized PANI-CC in low magnification, in accordance with some embodiments.

15 [00133] FIG. 6D displays an exemplary FESEM image of a 20-hour polymerized PANI-CC, in accordance with some embodiments.

[00134] FIG. 6E displays an exemplary FESEM image of a 24-hour polymerized PANI-CC in low magnification, in accordance with some embodiments.

[00135] FIG. 6F displays an exemplary FESEM image of a 24-hour polymerized PANI-CC in high magnification, in accordance with some embodiments.

20 [00136] FIG. 6G displays an exemplary FESEM image of a 28-hour polymerized PANI-CC, in accordance with some embodiments.

[00137] FIG. 6H displays an exemplary FESEM image of a 32-hour polymerized PANI-CC, in accordance with some embodiments.

25 [00138] FIG. 7 displays exemplary cyclic voltammetry (CV) graphs of exemplary CC and PANI-CC devices, in accordance with some embodiments.

[00139] FIG. 8 displays exemplary galvanostatic charge-discharge curves of an exemplary symmetric PANI-CC device, in accordance with some embodiments.

[00140] FIG. 9 displays exemplary CV curves of exemplary PANI-CC symmetric devices with different polymerization times, in accordance with some embodiments.

30 [00141] FIG. 10 displays exemplary galvanostatic charge-discharge curves of exemplary PANI-CC symmetric devices with different polymerization times, in accordance with some embodiments.

[00142] FIG. 11 displays exemplary powder x-ray diffraction (XRD) patterns of exemplary carbon cloth and functionalized carbon cloth, in accordance with some embodiments.

[00143] FIG. 12 displays exemplary Fourier transform infrared (FTIR) spectroscopy spectrum measurements of exemplary PANI-FCC and PANI-CC electrodes, in accordance with some
5 embodiments.

[00144] FIG. 13A displays exemplary CV curves of an exemplary PANI-FCC symmetric supercapacitor at a scan rate of 100 mV/s, in accordance with some embodiments.

[00145] FIG. 13B displays exemplary charge-discharge (CD) curves of an exemplary PANI-FCC symmetric supercapacitor at a current density of 1 A/g, in accordance with some embodiments.

10 [00146] FIG. 13C displays an exemplary Nyquist plot of CC, FCC, PANI-CC and PANI-FCC, in accordance with some embodiments.

[00147] FIG. 13D displays an exemplary Bode plot of CC, FCC, PANI-CC and PANI-FCC, in accordance with some embodiments.

15 [00148] FIG. 13E displays exemplary CV curves of an exemplary PANI-FCC symmetric supercapacitor under scan rates from 20mV/s to 1000 mV/s, in accordance with some embodiments.

[00149] FIG. 13F displays exemplary CD profiles of an exemplary PANI-FCC symmetric supercapacitor at various current densities ranging from 1 to 50 A/g, in accordance with some
embodiments.

20 [00150] FIG. 13G displays exemplary calculated capacitances as a function of current density of exemplary PANI-FCC and PANI-CC devices, in accordance with some embodiments.

[00151] FIG. 13H displays the exemplary cyclability of an exemplary PANI-FCC device at current densities of 1 to 20 A/g-1 over 5000 cycles, in accordance with some embodiments.

[00152] FIG. 14 displays exemplary CD curves of an exemplary PANI-FCC device at different currents, in accordance with some embodiments.

25 [00153] FIGs. 15A displays exemplary CD curves of an exemplary carbon cloth.

[00154] FIGs. 15B displays exemplary Nyquist plots of a PANI-FCC electrodes of various annealing times.

[00155] FIG. 16A displays an exemplary relationship between the resistance and the bending angle of an exemplary PANI-FCC device.

30 [00156] FIG. 16B displays an exemplary relationship between the resistance and the number of bending cycles of an exemplary PANI-FCC device, in accordance with some embodiments.

[00157] FIG. 16C displays exemplary CV curves of an exemplary bent, flat, and reopened PANI-FCC device, in accordance with some embodiments.

[00158] FIG. 17A displays exemplary CV curves of exemplary three-electrode PANI-FCC and AC-FCC devices at 20 mV/s, in accordance with some embodiments.

5 [00159] FIG. 17B displays an exemplary CV curve of an exemplary PANI-FCC asymmetric device at 50 mV/s, in accordance with some embodiments.

[00160] FIG. 17C displays exemplary CD curves of an exemplary asymmetric SC at various current densities, in accordance with some embodiments.

10 [00161] FIG. 17D displays exemplary Ragone plots of exemplary symmetric and asymmetric devices under various current densities, in accordance with some embodiments.

[00162] FIG. 18A displays exemplary CV curves of an exemplary PANI-FCC asymmetric device at different potential windows, in accordance with some embodiments.

[00163] FIG. 18B displays exemplary CV curves of an exemplary PANI-FCC asymmetric device at 50 mV/s and in H₂SO₄ and NQ gel electrolytes, in accordance with some embodiments.

15 [00164] FIG. 18C displays exemplary Nyquist plot of an exemplary PANI//AC device, in accordance with some embodiments.

[00165] FIG. 18D displays exemplary discharge curves of an exemplary PANI-FCC asymmetric device at different current densities from 2 to 50 A/g, in accordance with some embodiments.

20 [00166] FIG. 18E displays the calculated capacitance as a function of current density for an exemplary PANI//AC device from 5 to 50 A/g, in accordance with some embodiments.

[00167] FIG. 18F displays an exemplary Ragone plot of exemplary symmetric and asymmetric devices, in accordance with some embodiments.

[00168] FIG. 19A displays exemplary CV curves of exemplary PANI-FCC and AC-FCC electrodes, in accordance with some embodiments.

25 [00169] FIG 19B displays exemplary CD curves of exemplary PANI-FCC and AC-FCC electrodes in the presence of NQ at a current density of 10 A/g, in accordance with some embodiments.

[00170] FIG. 19C displays exemplary CD curves of exemplary AC-FCC//PANI-FCC devices in the presence of NQ at different current densities, in accordance with some embodiments.

30 [00171] FIG. 20A displays exemplary CV curves of an exemplary asymmetric AC-FCC//PANI-FCC device in an NQ gel electrolyte, in accordance with some embodiments.

[00172] FIG. 20B displays exemplary charge and discharge curves of an exemplary asymmetric AC-FCC//PANI-FCC device with and without NQ, in accordance with some embodiments.

[00173] FIG 20C displays the exemplary relationship between the current density and the specific capacitance of an exemplary AC-FCC//PANI-FCC device in the presence of NQ, in accordance with some embodiments.

[00174] FIG. 20D displays exemplary charge and discharge curves of an exemplary asymmetric AC-FCC//PANI-FCC device under a current density of about 47 A/g, in accordance with some
5 embodiments.

[00175] FIG. 21 displays the exemplary relationship between the power density and the energy density of exemplary symmetric and asymmetric devices, in accordance with some embodiments.

[00176] FIG. 22 displays the gravimetric and volumetric energy densities of the components of an
10 exemplary electrochemical cell, in accordance with some embodiments.

[00177] FIG. 23A illustratively displays an exemplary red LED powered by two exemplary asymmetric devices in series, in accordance with some embodiments.

[00178] FIG. 23B illustratively displays an exemplary a clock powered by two exemplary asymmetric devices in series, in accordance with some embodiments.

15

DETAILED DESCRIPTION

[00179] The market for flexible electronics such as solar cell arrays, flexible displays, and wearable electronics is rapidly growing and contributing to the design of future electronics, due to their portability, ruggedness, bendability, and rollability. The recent rapid progress in the production of flexible electronic devices over large areas, at the fraction of the cost of traditional semiconductors,
20 has led to the development of various energy storage and power storage devices, including a wide array of flexible semiconductors of varying sizes, shapes, and mechanical properties.

[00180] As such, there are growing demands for flexible, solid-state energy storage devices that are compatible with next-generation printed and flexible electronics. To this effect, the active layer and interfaces between flexible components must be redesigned to replace the rigid components of
25 traditional supercapacitors (SCs). As such, improving the energy density of SCs is necessary and will contribute to the technological advancement of energy storage devices.

[00181] Reducing the size, increasing the flexibility, and achieving a high energy density, integrated with the intrinsic high power density and cyclability of supercapacitors constitutes a major step forward toward more sustainable and efficient energy storage systems.

[00182] Therefore, a current unmet need exists for a battery device that is capable of recharging in seconds, that provides power over long periods of time, can be repeatedly bent without capability loss, and is as miniaturizable as other corresponding electronics components.

[00183] Provided herein are supercapacitor devices and methods for fabrication thereof. The supercapacitor devices may be electrochemical devices. The supercapacitor devices may be configured for high energy and power density. The supercapacitor devices may include an electrode composed of a rectangular-tube PANI that is chemically synthesized on a functionalized carbon cloth (FCC) substrate, and immobilized on a current collector. The supercapacitor devices may be arranged as symmetric, asymmetric, or 3D capacitors devices which contain an electrode immobilized on a current collector. The supercapacitor devices of the disclosure may comprise interconnected devices.

[00184] The present disclosure additionally provides systems and methods for growing polyaniline nanotubes on carbon cloth. The processing may include the manufacture (or synthesis) of functionalized carbon cloth and/or the manufacture (or synthesis) of polyaniline nanotubes and nanostructures. Some embodiments provide methods, devices, and systems for the manufacture (or synthesis) of functionalized carbon cloth and/or for the manufacture (or synthesis) of polyaniline nanotubes and nanostructures and/or for the manufacture (or synthesis) of electrolytes and/or for the manufacture (or synthesis) of supercapacitors. Various aspects of the disclosure described herein may be applied to any of the particular applications set forth below or in any other type of manufacturing, synthesis, or processing setting. Other manufacturing, synthesis, or processing of materials may equally benefit from features described herein. For example, the methods, devices, and systems herein may be advantageously applied to manufacture (or synthesis) of various forms of functionalized carbon. The methods and devices taught herein may be applied as a stand-alone method, device, or system, or as part of an integrated manufacturing or materials (e.g., chemicals) processing system. It shall be understood that different aspects of the methods and devices taught herein may be appreciated individually, collectively, or in combination with each other.

[00185] The present disclosure further provides an exemplary energy storage device fabricated from rectangular-tube polyaniline (PANI) that is chemically synthesized. The rectangular-tube PANI, as an active material, is synthesized on a functionalized carbon cloth (FCC) as a substrate, and the obtained composite is immobilized on a stainless steel mesh as a current collector. The present disclosure additionally presents a technique for the direct synthesis of PANI nanotubes, with rectangular pores, on chemically activated CC.

[00186] The supercapacitors described herein may play an important role in one or more applications or areas, such as, but not limited to, portable electronics (e.g., cellphones, computers, cameras, etc.), medical devices (e.g., life-sustaining and life-enhancing medical devices, including pacemakers, defibrillators, hearing aids, pain management devices, drug pumps), electric vehicles (e.g., batteries with long lifetime are needed to improve the electric vehicle industry), space (e.g., the batteries are used in space to power space systems including rovers, landers, spacesuits, and electronic equipment), military batteries (e.g., the military uses special batteries for powering a large number of electronics and equipment; reduced mass/volume of the batteries described herein are highly preferred), electric aircraft (e.g., an aircraft that runs on electric motors rather than internal combustion engines, with electricity coming from solar cells or batteries), grid scale energy storage (e.g., batteries are used to store electrical energy during times when production, from power plants, exceeds consumption and the stored energy are used at times when consumption exceeds production), renewable energy (e.g., since the sun does not shine at night and the wind does not blow at all times, batteries in off-the-grid power systems are capable of storing excess electricity from renewable energy sources for use during hours after sunset and when the wind is not blowing; high power batteries may harvest energy from solar cells with higher efficiency than current state-of-the-art batteries), power tools (e.g., the batteries described herein may enable fast-charging cordless power tools such as drills, screwdrivers, saws, wrenches, and grinders; current batteries have a long recharging time), or any combination thereof.

Supercapacitors

[00187] Supercapacitors are high-power energy storage devices with a much higher capacitance than normal capacitors. Supercapacitors (SCs) have recently attracted considerable attention as high power density energy storage resources, and have been increasingly employed energy storage resources in portable electronic devices, regenerative braking systems, voltage stabilization devices, hybrid buses, medical devices, and hybrid electric vehicles.

[00188] In some embodiments, supercapacitors or electrochemical capacitors are comprised of two or more electrodes separated by an ion-permeable membrane (separator) and an electrolyte ionically connecting the electrodes, whereas ions in the electrolyte form electric double layers of opposite polarity to the electrode's polarity when the electrodes are polarized by an applied voltage.

[00189] In some embodiments, an electrode in an electrochemical cell comprised of a substrate and an active material referred to as either an anode, whereas electrons leave the active material within

cell and oxidation occurs, or a cathode, whereas the electrons enter the active material within cell and reduction occurs. Each electrode may become either the anode or the cathode depending on the direction of current through the cell. In some embodiments, the supercapacitors may be symmetric or asymmetric, wherein the electrodes are identical or dissimilar, respectively. In some embodiments, the supercapacitors are configured with two or more electrodes.

[00190] Supercapacitors store energy via three main mechanisms (i) electric double-layer capacitance (EDLC), (ii) Faradaic capacitance, and (iii) capacitance directly from redox active electrolytes. Via the first two mechanisms, only solid-phase electrode materials contribute to charge storage, while the other cell components, including electrodes and electrolyte, are electrochemically inert. The addition of a redox active species to the electrolyte enhances the cell's capacitance through electrochemical reactions at the electrode/electrolyte interface.

[00191] In some embodiments, the devices herein (e.g., supercapacitors and/or microsupercapacitors) may be configured in different structures. In some embodiments, the devices may be configured in stacked structures (e.g., comprising stacked electrodes), planar structures (e.g., comprising interdigitated electrodes), spirally wound structures, or any combination thereof. In some embodiments, the devices may be configured in a sandwich structure or an interdigitated structure.

Electrodes

[00192] Materials commonly employed in supercapacitor electrodes include transition-metal oxides, conducting polymers, and high-surface carbons. Unfortunately, however, conventional supercapacitors based on these materials may exhibit low energy densities, and are limited by the mass loading of the electrode's active materials.

[00193] In some embodiments, faradaic materials are employed as electrodes because they store charge both on the surface and in the bulk, as opposed to EDLC materials, which only store charge through ion adsorption on the electrode's surface.

[00194] In some embodiments, high-surface-area electrodes are carbonaceous and comprise carbon cloth, carbon fiber, amorphous carbon, glassy carbon, carbon nanofoam, carbon aerogel, or activated carbon (AC).

[00195] In some embodiments, AC refers to carbon that has been treated to increase its surface area. In some embodiments, the crystalline density of AC is about 0.5 g/cm³.

[00196] The conducting polymer polyaniline serves as an ideal charge storage material due to its low-cost, ease of synthesis, controllable electrical conductivity, large specific capacitance, and environmental stability.

[00197] Among the vast majority of supercapacitive component materials, polyaniline (PANI), and its different morphologies, have been used as an active material because of its intrinsic high oxidation-reduction (redox) active-specific capacitance, flexibility, and ability to convert between multiple redox states accompanied by rapid doping and dedoping of counter ions during charge and discharge processes.

[00198] In some embodiments, polyaniline (PANI) is one example of a semi-flexible rod conducting polymer which is ease to synthesize, is environmentally stable, cheap, and exhibits a high electrical conductivity and specific pseudocapacitance. Additionally, PANI may be readily converted between multiple redox states accompanied by rapid doping and dedoping of counter ions during charge and discharge processes and, as such, electron transfer in PANI is accomplished through a conjugated double bond, passing of an electric current in a coherent wrap. Finally, in some embodiments, PANI exhibits an intrinsic high oxidation-reduction (redox) active-specific capacitance and flexibility. Therefore, developing PANI-based hybrid electrodes has been an attractive topic in the hope of improving its cycling stability.

[00199] Despite being a superior energy storage material, bulk PANI, in some embodiments, suffers from poor mechanical properties and mediocre cycling stability, whereas the large volume changes associated with doping and dedoping of the counter ions destroy the polymer backbone over cycling thus diminishing capacity and limiting the potential commercial applications of PANI pseudocapacitors. As electron transfer in PANI occurs through a conjugated double bond, however, passing an electric current in a coherent wrap may be easier than electron transfer between two independent parts.

[00200] In some embodiments, the structure and geometry of PANI is altered at the nanoscale to relax its internal strain by allowing the small surface features free space to flex. In some embodiments, the PANI is functionalized, wherein new functions, features, capabilities, or properties of a material are added by changing its surface chemistry and morphology.

[00201] In some embodiments, the morphology of a faradaic electrode's materials has a significant impact on the electrochemical performance. Some electrode structures facilitate electron transfer in the active materials and, therefore, increase the conductivity and capacity of their respective devices. Nanostructuring of electrode materials represents an effective strategy towards altering the

morphology of, and significantly improving the performance of, supercapacitor electrodes by increasing the interfacial area between the electrode and the electrolyte and by minimizing the ion diffusion pathway within the active materials. In some embodiments, electrode nanostructuring additionally minimizes the ion diffusion pathway within the active material.

5 [00202] In some embodiments, PANI has a crystalline density of about 1.3 g/cm³.

[00203] In some embodiments, the chemical and electrochemical properties of an electrode are enhanced through the addition of surface functional groups which increase charge storage capacity via the pseudocapacitive effect. In some embodiments, functionalization alters the features, capabilities, or properties of a material by changing its surface chemistry and morphology.

10 Functionalization synthesizes several forms of surface nanostructures such as nanospheres, nanodiscs, nanowire, nanofibers, nanotubes, nanoplates, and nanoflowers. Among these, nanotube structures with small diameters allow for better accommodation of volume changes, and direct one-dimensional electronic pathway from a substrate, to allow for efficient electron transport and, therefore, provide an increased electrical conductivity and capacity. Furthermore, the combined
15 electrolyte-exposed nanotube external and internal surface areas enable high charge storage capacities, and provide strain relief by increasing the free space available for surface flexing. This approach addresses the stability issues of silicon anodes in lithium ion batteries, which exhibit large volume changes during cycling.

[00204] In designing supercapacitor electrodes, special efforts may be made to provide a high
20 energy density and high power density, including the optimization of the preparation conditions to facilitate ionic and electronic transport within the electrodes, as illustrated in **FIGs. 1A-C**. As such, the design of high-performance hybrid supercapacitors requires high-energy-high-power hybrid supercapacitor electrodes.

[00205] **FIGs. 1A-C** schematically illustrate high-energy-high-power hybrid supercapacitor
25 electrode designs, with nanofiber **101**, nanosphere, **102** and nanotube morphologies **103**, respectively, whereas the electrode with a nanotube morphology of PANI schematically displayed in **FIG. 1C** is capable of improved facilitation of both the ionic current **102** (IC) and the electronic current (EC), and thus may be capable of forming a supercapacitor with a high energy and a high power.

30 [00206] In some embodiments, electrodes with nanostructured morphologies exhibit an increased performance, whereas per **FIGs. 1A-C**, the porous structure of these electrodes increases the exposure area between the active material and the electrolyte, and thus increase the discharge area

compared to a solid electrode surface. Particularly, electrodes with nanotube morphologies allow for increased charge storage capacity because both the external and internal surfaces of a nanotube are exposed to an electrolyte.

Substrates

- 5 [00207] In some embodiments, carbon cloth (CC) is used as a cell substrate. In some embodiments carbon cloth comprises a woven assembly of multiple carbon fibers. In some embodiments, carbon fiber and graphite fiber are fibers composed mostly of carbon atoms. Additionally, the good electrical conductivity and flexibility of carbon cloth enables devices with low internal resistance (by providing short pathways for electron transport) and mechanical flexibility.
- 10 [00208] In some embodiments, CC is an excellent three-dimensional conductive skeleton that supports a high electrolytic-accessible surface area, provides a direct path for electron transfer, improves conductivity of its composites, and relieves the degradation accompanied by volume changes during cycling. Further, CC acts as an ideal substrate for flexible energy storage system because of its mechanical flexibility, porous structure, high electrical conductivity, short electron
- 15 transport pathway, low internal resistance, high areal loading, and its ability to be easily packaged. [00209] In some embodiments, the chemical activation of carbon cloth is enhanced through hybridization, by synthesizing conductive polymer nanostructures on the surface of the electrode. In some embodiments, the chemical and electrochemical properties of carbon cloth are modified to enhance the properties of its composite hybrid, whereas the chemical activation of CC, via the
- 20 addition of functional groups onto the surface, enhances the charge storage capacity via the pseudocapacitive effect. Additionally, the functional groups on the surface of the functionalized carbon cloth allow for a stronger connection to the PANI, thus facilitating the passage of electrons from the polymer to the substrate. In some embodiments, chemical activation of a CC aids in situ polymerization by converting its naturally hydrophobic surface into a hydrophilic surface capable of
- 25 increased interaction with a, typically aqueous, polymerization or monomer feed solution. In some embodiments, the in situ polymerization of a conductive polymer ensures direct electrical contact with CC, thus eliminating the need for, and the extra weight of, binders and conductive additives. [00210] An exemplary image of the surface structure of a CC 602 displays, per FIG. 6A, a morphology comprising fibrous structures. The optimal 3D structure of CC enables high areal
- 30 loading of PANI, which is an important parameter for commercially viable electrodes. [00211] In some embodiments, carbon cloth has a crystalline density of about 1.6 g/cm³.

Electrolytes

[00212] The energy storage devices described herein may comprise an electrolyte. Electrolytes herein may include, for example but not limited to, aqueous, organic, and ionic liquid-based electrolytes, which may be in the form of a liquid, solid, or a gel. In some embodiments, an electrolyte is a solution with a uniform dispersion of cations and anions formed from an electrically conductive solute dissolved in a polar solvent.

[00213] Although electrolytes are neutral in charge, applying an electrical potential (voltage) to the solution draws the cations of the solution to the electrode with an abundance of electrons, and the anions to the electrode with an electron deficit. As such, the movement of anions and cations in opposite directions within the solution forms an energy current. Electrolytes described herein may comprise, for example, aqueous, organic, and/or ionic liquid-based electrolytes. The electrolyte may be a liquid, a solid, or a gel. An ionic liquid may be hybridized with another solid component such as, for example, polymer or silica (e.g., fumed silica), to form a gel-like electrolyte (also “ionogel” herein). An aqueous electrolyte may be hybridized with, for example, a polymer, to form a gel-like electrolyte (also “hydrogel” and “hydrogel-polymer” herein). In some cases, a hydrogel electrolyte solidifies during device fabrication, which binds the cell’s components together to improve the mechanical and electrical properties of an electrode. An organic electrolyte may be hybridized with, for example, a polymer, to form a gel-like electrolyte. In some embodiments, the electrolyte may also include a lithium salt (e.g., LiPF_6 , LiBF_4 , or LiClO_4). For example, the electrolyte may include a lithium salt (e.g., LiPF_6 , LiBF_4 , or LiClO_4) in an organic solution (e.g., ethylene carbonate (EC), dimethyl carbonate (DMC), or diethyl carbonate (DEC). The electrolyte may comprise one or more additional components (e.g., one or more additives) to form an electrolyte composition. In one example, a soft pack polymer LIB electrolyte comprises one or more of EC, ethyl methyl carbonate (EMC), DEC, LiPF_6 , and other additives. In another example, a high capacity LIB electrolyte may comprise one or more of EC, DEC, propylene carbonate (PC), LiPF_6 , and other additives.

[00214] Quinone electrolyte additives have been employed for their ability to store $2\text{ e}^-/2\text{ H}^+$ per quinone unit to enhance capacities in double-layer supercapacitors. During charge and discharge operations, quinone additives undergo redox processes at the electrodes. In some embodiments, quinone electrolytes are particularly excellent redox-active electrolytes because of their excellent electrochemical reversibility during charge and discharge, small size, high mobility, and an acidic pH compatible with the current family of acid-doped polymers.

Supercapacitor Device Design

[00215] In some embodiments, energy storage devices with ultrahigh energy densities are designed by selecting an electrode material in combination with an electrolyte to attain synergistic interactions among the device's components. Faradaic energy storage materials in current three-electrode devices
5 require aqueous electrolytes for their operation which are limited to about 1.0 V due to the decomposition of water at 1.23 V. Although symmetric devices exhibit a max theoretical voltage window of 1.0 V, asymmetric devices attain the voltage window of aqueous electrolytes by extending their operating voltage beyond the thermodynamic decomposition voltage of water.

[00216] In some embodiments, a supercapacitor device that comprises PANI, which is capable of
10 being converted between multiple redox states, as an electrochemically active material and a 1,4-naphthoquinone (NQ) redox couple electrolyte, forms a tunable double redox shuttle, whereas NQ provides pseudocapacitance through direct redox reactions on the electrode surfaces, catalyzes the regeneration of the oxidized form of PANI, and operates as a redox shuttle for the reversible oxidation/reduction of polyaniline, to considerably enhance the overall performance of the device.

[00217] The 3D nature of polyaniline rectangular tubes supported on a functionalized carbon cloth
15 offers efficient electron and ion transport pathways and provides sufficient space for the addition of NQ, thus forming a second redox system, and thus a tunable redox shuttle in the electrolyte that enhances electron-transfer processes on the surface of the electrode. Further, the addition of NQ not only increases the capacitance of polyaniline electrodes, but also improves the capacitance of EDLC
20 supercapacitor materials, such as activated carbons.


[00218] As such, the use of NQ, through an electrocatalytic mechanism as a redox additive, enables multiple charge transfer processes, provides Faradaic capacitance with direct redox reactions on the electrode surfaces, serves as the basis for a regenerative pathway towards long-term utilization of the electrode active materials, and enables a supercapacitor device with a much higher energy density. In
25 some embodiments, NQ has a crystalline density of about 1.4 g/cm³.

[00219] FIG. 2 shows the composition of an exemplary supercapacitor **200**, whereas the positive electrode **201** and the negative electrode **202** are separated by an ion-and-molecule-permeable membrane **203** that is soaked in an NQ electrolyte comprising sulfuric acid (H₂SO₄) and acetic acid (AcOH).

[00220] In some embodiments, the NQ comprises a polyvinyl alcohol (PVA) gel electrolyte in 1 M H₂SO₄ with 30% acetic acid (AcOH). In some embodiments a polyvinyl alcohol (PVA) gel
30

electrolyte is formed by dissolving 1 g of PVA in 10 mL of deionized water and AcOH, vigorously stirring for 30 minutes, adding a 0.56 mL stock of H₂SO₄ and adding 1.53 mg of NQ.

[00221] The NQ-promoted regeneration of polyaniline (PANI), which is capable of being reused in multiple redox reactions, plays an important role in a supercapacitor device. FIG. 4 displays the chemical process of converting a functionalized carbon cloth into a PANI functionalized carbon cloth, wherein per FIG. 2 and the equations below, PANI_{ox} is electrochemically reduced to PANI_{red} on the electrode surface, and NQ in the electrolyte oxidizes back the reduced form of the PANI via an EC' regenerative mechanism that may then re-undergo electron transfer reactions on the surface.



[00222] As such, the Faradaic capacitance of the device increases considerably due to the multiple reuse of the appropriate form (depending on the charge and discharge process) of polyaniline as a starting electroactive material. In addition to its electrocatalytic regenerative mechanism, NQ may undergo redox reactions on the substrate's surfaces. The combinatorial effect of NQ as both a tunable redox shuttle and a redox additive increases the performance of the supercapacitor, since energy is stored both on the polyaniline surfaces using a pseudo-capacitive mechanism and in the electrode-electrolyte interface via the redox reaction. There are several advantages as a result of the electrocatalytic reaction, which provides in situ regeneration of the electrode active materials. First, since $Q = mnF$, regeneration of the starting active materials increases the value of m , thus providing an additional charge in the cell. Additionally, because catalytic regeneration of the active material attains a higher current without increasing the initial mass of the active materials, reducing the mass of inactive components increases the specific energy and capacitance. Further, because additional mass is not required to increase capacitance, the system's equivalent series resistance (ESR) remains low. Moreover, because the regenerated active materials are firmly immobilized on the substrate surfaces, the ESR of the system does not increase. Also, since current is a function of the surface concentration of the active material (C_{AM}), the electrocatalytic regeneration of the electrode active material via an EC' mechanism remarkably increases the C_{AM} . Finally, the electrocatalytic reaction

eliminates the requirement to diffuse the electroactive materials from the bulk of the solution to the electrode surface.

Methods of Fabricating Electrodes

[00223] An exemplary process of fabricating a supercapacitor device **300** comprising fabricating a polyaniline functionalized electrode and packaging the electrode is shown in **FIG. 3**.

[00224] In exemplary embodiments, a method of fabricating a polyaniline functionalized electrode **305** comprises functionalizing a carbon substrate **301** to form a functionalized carbon substrate **303**, preparing the functionalized carbon substrate **303**, formulating a polymerization fluid **304**, and synthesizing a polyaniline nanotube **306** on the functionalized carbon substrate.

[00225] In exemplary embodiments, the step of functionalizing a carbon substrate **301** to form a functionalized carbon substrate **303** comprises forming a functionalization solution **302**, heating the functionalization solution **302**, cooling the functionalization solution **302**, displacing a piece of the carbon substrate **301** into the functionalization solution **302**, and rinsing a piece of functionalized carbon substrate **303**.

[00226] In an exemplary embodiment, the functionalization solution **302** comprises nitric acid (HNO_3) and sulfuric acid (H_2SO_4), wherein the volumetric percentage of nitric acid in the functionalization solution **302** is about 15% to about 60%. In an example, the functionalization solution **302** comprises a volumetric percentage of nitric acid of about 33%.

[00227] In an exemplary embodiment, the functionalization solution **302** is heated at a suitable temperature, such as, at about 30 °C to about 120 °C. In an example, the functionalization solution **302** is heated at a temperature of about 60°C. In an exemplary embodiment, the carbon substrate **301** is immersed in the functionalization solution **302** for a suitable period of time, such as, about 60 minutes to about 240 minutes. In an example, carbon substrate **301** is immersed in the functionalization solution **302** for a period of time of about 120 minutes.

[00228] In exemplary embodiments, the step of preparing the functionalized carbon substrate **303** comprises cutting a piece of the functionalized carbon substrate **303**, submerging the piece of functionalized carbon substrate **303** in a polymerization fluid **304**, sonicating the piece of functionalized carbon substrate **303** in the polymerization fluid **304**, and drying the piece of functionalized carbon substrate **303**.

[00229] In an exemplary embodiment, the functionalized carbon substrate **303** has a suitable geometric surface area, such as about 0.1 cm² to about 0.5 cm². In an example, the functionalized carbon substrate **303** has a suitable geometric surface area of about 0.25 cm².

[00230] In some embodiments, the polyaniline functionalized carbon substrate **305** is then annealed
5 in a furnace, in an air atmosphere, at 200° C. In an exemplary embodiment, the polyaniline functionalized carbon substrate **305** is annealed for a suitable period of time of about 0.5 hours to about 14 hours. In an example, the polyaniline functionalized carbon substrate **305** is annealed for a period of time of about 4 hours.

[00231] In an exemplary embodiment, the polymerization fluid **304** comprises acetone and ethanol.
10 In an exemplary embodiment, the polymerization fluid **304** comprises a suitable volume percentage of acetone, such as, about 25% to about 100%. In an example, the volumetric percentage of acetone in the polymerization fluid **304** is about 50%.

[00232] In an exemplary embodiment, the functionalized carbon substrate **303** is sonicated for a suitable period of time, such as, about 15 minutes to about 60 minutes. In an example, the
15 functionalized carbon substrate **303** is sonicated for a period of time of about 30 minutes.

[00233] In an exemplary embodiment, the functionalized carbon substrate **303** is dried at a suitable temperature, such as, at about 20 °C to about 120 °C. In an example, functionalized carbon substrate **303** is dried at a temperature of about 60 °C.

[00234] In an exemplary embodiment, the functionalized carbon substrate **303** is dried for a suitable
20 period of time of about 3 hours to about 12 hours. In an example, the functionalized carbon substrate **303** is dried for a period of time of about 6 hours.

[00235] In exemplary embodiments, the step of formulating a polymerization fluid **304** comprises mixing polyaniline, an acid, a detergent, water, and an oxidizing agent; and stirring the polymerization solution **304**. In an exemplary embodiment, the acid comprises hydrochloric acid
25 (HCl), the detergent comprises sodium dodecyl sulfate (SDS), and the oxidizing agent comprises ammonium persulfate (APS).

[00236] In an exemplary embodiment, the polymerization fluid **304** comprises a suitable mass of polyaniline of about 20 mg to about 90 mg. In an example, the mass of polyaniline in the polymerization fluid **304** is about 45 mg.

[00237] In an exemplary embodiment, the polymerization fluid **304** comprises a suitable
30 concentration of hydrochloric acid (HCl) of about 0.1 M to about 0.5 M. In an example, the concentration of HCl in the polymerization fluid **304** is about 0.25 M. In an exemplary embodiment,

the polymerization fluid **304** comprises a suitable volume of HCl of about 0.1 ml to about 0.6 ml. In an example, the volume of HCl in the polymerization fluid **304** is about 0.3 ml.

[00238] In an exemplary embodiment, the polymerization fluid **304** comprises a suitable mass of SDS of about 1 mg to about 10 mg. In an example, the concentration of SDS in the polymerization fluid **304** is about 5 mg.

[00239] In some embodiments the water comprises deionized water. In an exemplary embodiment, the polymerization fluid **304** comprises a suitable volume of water of about 9 ml to about 40 ml. In an example, the volume of water in the polymerization fluid **304** is about 18 ml.

[00240] In an exemplary embodiment, the polymerization fluid **304** comprises a suitable concentration of APS of about 0.1 M to about 0.5 M. In an example, the concentration of APS in the polymerization fluid **304** is about 0.24 M. In an exemplary embodiment, the polymerization fluid **304** comprises a suitable volume of APS of about 1 ml to about 4 ml. In an example, the concentration of APS in the polymerization fluid **304** is about 2 ml.

[00241] In an exemplary embodiment, the polymerization fluid **304** is stirred for a suitable amount of time of about 10 minutes to about 40 minutes. In an example, the polymerization fluid **304** may be stirred for a period of about 20 minutes.

[00242] In exemplary embodiments, the step of synthesizing a polyaniline nanotube **306** on the functionalized carbon substrate **303** comprises agitating the polymerization fluid **304**, immersing the functionalized carbon substrate **303** in the polymerization fluid **304**, storing the functionalized carbon substrate **303** in the polymerization fluid **304**, removing a polyaniline functionalized carbon substrate **305** from the polymerization fluid **304**, washing the polyaniline functionalized carbon substrate **305**, and drying the polyaniline functionalized carbon substrate **305**.

[00243] In an exemplary embodiment, the polymerization fluid **304** is agitated for a suitable amount of time of about 15 seconds to about 60 seconds. In an example, the polymerization fluid **304** may be agitated for a period of about 30 seconds.

[00244] In an exemplary embodiment, the functionalized carbon substrate **303** is stored in the polymerization fluid **304** at a suitable temperature of about 10 °C to about 50 °C. In an example, the functionalized carbon substrate **303** is stored in the polymerization fluid **304** at a temperature of about 25°C.

[00245] In an exemplary embodiment, the functionalized carbon substrate **303** is stored in the polymerization fluid **304** for a suitable polymerization time of about 8 hours to 70 hours. In an

example, the functionalized carbon substrate **303** is stored in the polymerization fluid **304** for a polymerization time of about 24 hours.

[00246] In an exemplary embodiment, the polyaniline functionalized carbon substrate **305** is dried at a suitable temperature of about 30 °C to about 120 °C. In an example, the polyaniline

5 functionalized carbon substrate **305** is dried at a temperature of about 60 °C.

[00247] In some embodiments, the polyaniline functionalized carbon substrate **305** is used directly as SC electrodes without the need for binders or conductive additives typically used in conventional devices.

[00248] Finally, in an exemplary embodiment, the polyaniline functionalized carbon substrate **305** 10 is packaged into a symmetric supercapacitor device **300** whereas a separator, soaked in an electrolyte, is sandwiched between the PANI faces of two polyaniline functionalized carbon substrates **305**.

[00249] The PANI functionalized cloths as electrodes, along with a stainless steel current collector and an electrolyte form symmetric (PANI-FCC//PANI-FCC or PANI-CC//PANI-CC) and 15 asymmetric (PANI-FCC//AC) supercapacitor devices.

Characterization and Measurements

[00250] The structure and morphology of the different electrode materials may be examined using field-emission scanning electron microscopy (Philips and JEOL-JSM-6700). The structural changes before and after functionalization of CC in the strong acid mixture may be characterized using an 20 x-ray powder diffraction (Philips X'pert diffractometer with Co K α radiation [$\lambda = 0.178$ nanometers] generated at 40 kV and 40 mA with a step size of $0.02^\circ \text{ s}^{-1}$). A spectrophotometer (Tensor 27 Bruker) may be used for performing Fourier transform infrared (FTIR) spectroscopy.

[00251] The exemplary devices are tested for their electrochemical performance using cyclic voltammetry (CV), galvanostatic charge-discharge (CD) curves, and electrochemical impedance 25 spectroscopy (EIS) experiments. A Biologic potentiostat (SP-300) may be used to acquire cyclic voltammetry and electrochemical impedance spectroscopy data for the different devices. A battery tester (Solartron) equipped with a Cell Test software may be used for the galvanostatic CD studies.

[00252] In some embodiments, the processes described herein employ a magnetic stirrer, which comprises a laboratory device, whereas an emitted rotating magnetic field quickly spins a 30 magnetized stir bar immersed in a liquid for quick, consistent mixing.

[00253] All the chemicals used herein are used directly as purchased, without further purification. Aniline is distilled by water steam before use.

Effect of SDS on Surface Morphology and Performance

[00254] In some embodiments, the anionic surfactant, sodium dodecyl sulfate (SDS), plays an important role as a soft template in doping, in the polymerization process upon the morphology of the synthesized PANI, and with the electrochemical properties and capacitance of the device. The SDS doping of the PANI structure generates a belt-like structure, the rolling up of which takes place subsequently, wherein further polymerization results in the formation of PANI with a rectangular-tube morphology. In some embodiments, the low concentration of HCl triggers PANI polymerization in the medium with low acidity, which slows the reaction processes and may allow for the formation of nanostructures.

[00255] In an example, **FIG. 5A** shows that the morphology of PANI synthesized on a CC in the presence of SDS, is formed of rectangular nanotubes **502** with PANI nanoparticles on their surfaces, wherein **FIG. 5B** shows that the morphology of PANI synthesized on the CC in the absence of SDS is comprised of irregular bulky nodules **503**. Therefore, the PANI produced in the presence of SDS has rectangular shape with nanostructures on its surface.

[00256] In an exemplary embodiment, the length of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is about 1 micrometers to 200 micrometers. In an example, the length of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is about 1 micrometers.

[00257] In an exemplary embodiment, the outer diameter of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is about 100 nanometers to 1,000 nanometers. In an example, the outer width of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is about 350 nanometers.

[00258] In an exemplary embodiment, the inner diameter of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is about 50 nanometers to 800 nanometers. In an example, the inner width of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is about 250 nanometers.

[00259] In an exemplary embodiment, a nanostructure on the surface of a rectangular nanotube **502** synthesized on a CC in the presence of SDS is a nanorod. In an exemplary embodiment, the nanorod on the surface of the rectangular nanotube **502** has a length of about 4 micrometers to 50

micrometers. In an example, the nanorod on the surface of the rectangular nanotube **502** has a length of about 9 micrometers.

[00260] In an exemplary embodiment, the nanorod on the surface of a rectangular nanotube **502** synthesized on a CC in the presence of SDS has a width of about 20 nanometers to 120 nanometers.

5 In an example, the nanorod on the surface of a rectangular nanotube **502** synthesized on a CC in the presence of SDS has a width of about 50 nanometers.

[00261] The regular hollow nanotube morphology increases electron transfer in the PANI structure synthesized in the presence of SDS. The rectangular hollow nanotube morphology of the synthesized PANI, and the nanoparticle morphology on its surface, enhances the electrochemical performance of
 10 an electrode. Per the cyclic voltammograms of the exemplary CC and PANI-CC devices in **FIG. 7**, the redox peaks at 0.4 V and at 0.2 V represent the reduction and oxidation, respectively, of PANI. The CV curve of PANI-CC displays its pseudocapacitive behavior and confirms the electric double-layer capacitance (EDLC) of CC in the exemplary device, and shows that the pseudocapacitance caused by PANI is dominant. The exemplary CD curves show two plateaus in the CD steps which
 15 correspond with the redox peaks of PANI in the exemplary CV curves. It is seen that the exemplary device, containing PANI synthesized in the presence SDS, exhibits a higher capacitance and rate capability per the areas under the exemplary CV curves, and the discharge times in **FIG.s 7 and 8**, respectively. As such, a PANI-FCC exhibits a significantly high charge/discharge current density and displays obvious redox peaks that are assigned to the redox additive.

20 **Effect of Polymerization Time on Surface Morphology and Performance**

[00262] Examples of surface morphologies exhibited by PANI synthesized on CC over different polymerization times (16, 20, 24, 28, and 32 hours) are shown in **FIGs. 6A-H**. A 16-hour polymerized PANI-CC **601a**, per **FIG. 6C** in low magnification, displays a morphology of hollow rectangularly cross-sectioned PANI nanotubes on the surface of a CC, with outer diameters of about
 25 200-500 nanometers, inner diameters of about 100-400nm, and lengths of several micrometers. Additionally, the 16-hour polymerized PANI-CC **601a**, per **FIG. 6B** in high magnification, displays a morphology of nanorods disorderly aligned in hierarchical structures on the surfaces of the PANI nanotubes, whose lengths and diameters range from about 100-200 nanometers and about 40-60 nanometers, respectively.

[00263] An image of an exemplary 20-hour polymerized PANI-CC **601b**, as shown in **FIG. 6D**, exhibits a morphology of larger nanotubes, whose surfaces contain a greater size and quantity of nanorods.

[00264] An image of an exemplary 24-hour polymerized PANI-CC **601c**, as shown in **FIGs. 6E**

5 and **6F** at low and high magnifications, respectively, exhibits a morphology of poriferous nanotubes, whose surfaces contain a uniform array of nanostructures that are 8-10 nanometers in size.

[00265] An image of an exemplary 28-hour polymerized PANI-CC **601d** and a 32-hour polymerized PANI-CC **601e**, per **FIGs. 6G** and **6H**, respectively, display that as the polymerization time increases, the nanostructures on the rectangular tubes may aggregate as they grow.

10 [00266] **FIGs. 9** and **10** display example CV and CD curves for the 16, 20, 24, 28, and 32-hour polymerized PANI-CCs in a symmetric PANI-CC device, whereas the exemplary device comprising two 24-hour polymerized PANI-CCs exhibits the highest capacitance, of about 341 F/g, and the greatest discharge time.

[00267] The increased capacitance of an exemplary device comprising a 24-hour polymerized

15 PANI-CC may be due to the fact that its rough surface, with multiple smaller nanostructures whose diameters are between 8 nanometers and 10 nanometers, exhibits a greater surface area and a reduced diffusion length.

Functionalization Characterization

[00268] Exemplary XRD patterns for CC and FCC are displayed in **FIG. 11**, whereas XRD patterns
20 of pristine CC exhibit two main characteristic diffraction peaks at 20° to 35° and 50° to 55° that are attributed to the (002) and (101) planes of the hexagonal CC structure. It is seen that CC's broad intensity peaks at 20° to 35° C may greatly reduce due to the destruction of the CC's ordered crystalline structure, and due to the increased bond strength between C=N and COO⁻ groups as their double bond is converted to a single bond during the functionalization process. The initial broad
25 peak may be related to the -OH group of carboxylic acid functional group on the FCC, and the peak shift between the CC and the FCC may be explained by the stretching vibrations of C=C in the quinonoid and benzenoid rings, and the interaction of positive PANI C-N band with the negative carboxylic acid.

[00269] Per **FIG. 12**, an example of Fourier transform infrared (FTIR) spectrums of CC and PANI-

30 FCC displays a strong and uniform connection between PANI and FCC, and thus provides evidence for a decreased equivalent series resistance and an increased conductance. As shown, after activation

of an exemplary CC, a broad peak appears between the range of $3,300\text{ cm}^{-1}$ to $3,650\text{ cm}^{-1}$, which may indicate the presence of exchangeable protons, typically from carboxylic acid, alcohol, and amine functional groups, on the FCC. The characteristic peaks of PANI may be modified by functionalizing the CC, whereas the bonds at $1,576\text{ cm}^{-1}$ and $1,503\text{ cm}^{-1}$ corresponding to the stretching vibrations of $\text{C}=\text{C}$ in the quinonoid and benzenoid rings, respectively, shifted slightly to $1,580\text{ cm}^{-1}$ and $1,507\text{ cm}^{-1}$. Additionally, the peak at $1,301\text{ cm}^{-1}$, associated with $\text{C}-\text{N}$ stretching vibrations, experienced a large shift to $1,261\text{ cm}^{-1}$ revealing a strong interaction of the positive PANI C-N band with the negative carboxylic acid. Finally, the band at $1,240\text{ cm}^{-1}$, associated with $\text{C}-\text{N}$ stretching vibrations of the exemplary device completely disappeared, which may indicate the formation of a covalent connection between the $\text{C}=\text{N}$ and the COO^- groups. Thus, FT-IR spectroscopy provides strong evidence for excellent connections between PANI and the FCC, and a decreased ESR, and thus an increased device conductance, which enables good power density at high rate charge-discharges, and improves the cycle life of a supercapacitor device.

Calculations

[00270] Capacitance is the ability of a body to store an electrical charge. Although any object may be electrically charged and exhibit capacitance, a body with a large capacitance holds more electric charge at a given voltage, than a body with a low capacitance. In some embodiments, capacitance is measured in Farads per gram (F/g).

[00271] The specific capacitance of the devices may be calculated through CD measurements using the following equation where C_{sp} is the specific capacitance, I is the discharge current density (A), Δt is the discharge duration (s), m is the mass loading (g), and ΔV is the potential range (V).

$$C_{sp} = \frac{I\Delta t}{m\Delta V}$$

[00272] The specific capacitance of a device with a non-linear CD curve, may be calculated using the following equation where C_{sp} is the specific capacitance, I is the discharge current density (A), Δt is the discharge duration (s), and V is the potential range (V).

$$C_{sp} = \frac{2I\int Vdt}{V^2}$$

[00273] To achieve the highest working potential range, the mass ratio of the negative electrode to the positive electrode is determined according to the charge balance theory ($q^+ = q^-$). The voltammetric charges (Q) may be calculated based on the following equations where C_{single} is the

specific capacitance (F/g) of each electrode measured in a three-electrode setup (calculated from cyclic voltammograms at a scan rate of 10 mV s⁻¹), ΔV is the potential window (V), and m is the mass of the electrode (g).

$$Q = C_{single} \times \Delta V \times m$$

[00274] To maintain a charge balance between the two electrodes, the mass ratio between the positive (m_+) and negative (m_-) electrodes needs to follow:

$$\frac{m_+}{m_-} = \frac{c_- \times \Delta V_-}{c_+ \times \Delta V_+}$$

[00275] Energy density (ED) may be derived from the galvanostatic discharge curves using the following equation where C_{sp} is specific capacitance (F/g), and ΔV is the potential range (V).

$$ED = \frac{C_{sp} \Delta V^2}{2}$$

[00276] The power density of the electrode is calculated from the following equation where ED is the energy density in Wh/kg, and Δt is the discharge time.

$$PD = \frac{ED}{\Delta t}$$

[00277] Areal capacitance is the capacitance of a body per unit area. In some embodiments, areal capacitance is measured in Farads per cubic centimeter (F/cm²)

[00278] Current density is the electric current per cross section area, defined as a vector whose magnitude is the electric current per cross-sectional area at a given point in space. In some embodiments, current density is measured in Amps per gram (A/g).

[00279] Energy density is a measure of the amount of energy that is stored per unit mass. In some embodiments, energy density is measured in Watt hours per kilogram (Wh/kg).

[00280] Power density is a measure of the amount of power that is stored per unit mass. In some embodiments, power density is measured in kilowatts per kilogram (kW/kg).

Device Performance Characteristics

[00281] Electrochemical performance characteristics of an exemplary PANI-FCC device are shown in **FIGs. 13A-H**. As seen per the CV graph in **FIG. 13A**, pristine CC exhibits a small rectangular curve with a very low capacitance. The FCC displays a rectangular CV shape, with a higher EDLC charge storage capability, possibly due to the fact that functionalizing the carbon cloth increases its

wettability, and thus facilitates the adsorption and desorption of charge. Additionally, the exemplary PANI-FCC device exhibits a more rectangularly shaped CV, and thus a higher capacitive performance, than the CV curve of the exemplary PANI-CC device, per **FIG. 13C**. This performance improvement is most likely related to the exemplary PANI-FCC's increased charge storage in its double-layer mechanism, the wettability of the FCC, and the absorption and desorption of charge. Additionally, it is clear that the redox peaks of the PANI that are responsible for the pseudocapacitance of the device are covered by a capacitive portion resulting from FCC, and that the redox peaks of PANI, which are responsible for the pseudocapacitance of the device, are considerably diminished by the electrical double-layer capacitance of the FCC.

[00282] As seen in **FIG. 13B**, an exemplary PANI-FCC device exhibits a more symmetrically shaped CD curve, and thus a higher capacitive performance, than the PANI-CC, whose CD curve is shown in **FIG. 13A**. Additionally, **FIG. 13B** displays that the infrared (IR) drop in the discharge step of the exemplary PANI-FCC device is much smaller than the infrared (IR) drop in the discharge step of the exemplary FCC and CC devices, most likely due to the increased wettability of the carbon substrate and the stronger connection between the PANI and the FCC. As functionalization of the CC may form some carboxylic acid groups with a negative charge, an electrostatic interaction may occur between the carboxylic acid groups and the anilinium ions while the FCC is immersed in the polymerization fluid. Thus, the connection between PANI and the FCC is stronger than the connection between the PANI and the CC, and more PANI is precipitated on FCC. This improvement in the capacity is most likely due to the increased interaction between PANIs and the functional groups present on the FCC substrate.

[00283] Considering the peak current densities, per **FIG. 13A**, and the exemplary capacitance values in **FIG. 13B**, the capacitance exhibited by the exemplary PANI-FCC device is about 667 F/g at a 1 A/g current density, whereas the capacitance of the exemplary PANI-CC device is about 341 F/g under the same condition. As acid treatment of the CC imposes negatively charged carboxylic group functionalities on the CC's surfaces, the immersion of the FCC into the polymerization fluid may create an electrostatic interaction between the carboxylic acid groups and the positively charged anilinium ions, which may lead to a stronger conjugation product. As such, the improvement in supercapacitive performance of the exemplary PANI-FCC device may be due to the combined effects of the better interaction between PANI and the functional groups present on the FCC substrate (i.e. the faster electron exchange between PANI and FCC), as well as the redox activity of the functional groups themselves.

[00284] Nyquist and Bode plots are shown in **FIG. 13C** and **13D**, respectively, for exemplary CC, FCC, PANI-CC, and PANI-FCC devices operated under an open circuit potential. Per **FIG. 13C**, the exemplary PANI-FCC device displays a lower equivalent series resistance, as evaluated from the x-intercept, than the exemplary PANI-CC, which confirms the low IR drop measurements shown in **FIG. 13B**. The Bode plot, per **FIG. 13D**, of the exemplary PANI-CC device also displays a larger phase angle, confirming the lower device resistance, as observed in the Nyquist plot in **FIG. 13C**.

[00285] Additionally, the scan rate measurements displayed in **FIG. 13E** from 10 mV/s to 1,000 mV/s, show that the exemplary PANI-FCC device retained a similar CV curve shape at a high scan rate of 200 mV/s, indicating a good rate capability, that is confirmed by the CD plots in **FIG. 13F**.

The large pore volumes which may be filled with a redox active electrolyte allow for charge storage through both adsorption and redox capacitance. As expected, the electrolyte species readily inserted and de-inserted into and out of the electrode surfaces and throughout the pores of the exemplary PANI-FCC device at low scan rates, resulting in the expected rectangular response curve. As the scan rate increases, the interaction between the electrolyte species and the electrode surfaces is theoretically limited by kinetic and mass transport parameters.

[00286] In such a case, a large proportion of the substrate surfaces have little dynamic interaction with the electrolyte, possibly resulting in the non-rectangular and tilted CV curve. The similar CD example plots at different current densities (1-50 A/g), as shown in **FIG. 13F** serve as an additional indication of the exemplary device's good rate capability.

[00287] The exemplary PANI-FCC device also maintained its electrochemical performance, even when operated at high CD rates. **FIG. 13G** shows the specific capacitances as a function of the current density of the exemplary PANI-FCC device, compared with the exemplary PANI-CC device. The rate capability of the exemplary symmetric device tested at different current densities from 1 to 50 A/g shows an excellent specific capacitance of 274 F/g at a current density of 50 A/g. The specific capacitance of the exemplary PANI-FCC device (upper curve) at 20 A/g and 50 A/g is as much as about 56% and about 41% of that at 1 A/g, respectively. These results demonstrate the good rate capability of the exemplary PANI-FCC device under high current densities, which is important for practical high rate SC applications.

[00288] The capacitance retention over the long-term charge/discharge cycles is indispensable for practical SC materials. The capacitance of the exemplary PANI-FCC device is measured during CD cycling at a range of current densities (1, 2, 5, 10, and 20 A/g) over 5,000 cycles, per **FIG. 13H**, whereas the capacitance of the exemplary device in a current density of 1 A/g increases during the

first 200 cycles, and whereas the capacitance of the exemplary device decreases during the period from 1,000 to 5,000 cycles. After 200 cycles at a current density of 1 A/g, the specific capacitance of the exemplary device decreases, and at the end of the 1,000th cycle, the exemplary device provides about 91% of its initial specific capacitance of 667 F/g. Finally, the exemplary device exhibits a capacitance retention of about 87% over 5,000 cycles, indicating very good cyclability. The inset in **FIG. 13H** additionally displays the 1st and 5,000th cycles of the exemplary PANI-FCC electrode at 1 A/g.

[00289] Per **FIG. 14**, examples of CD curves are shown for an exemplary PANI-FCC device in different currents to calculate its areal capacitance. The areal capacitance of exemplary stack is about 374 mF/cm² in 7 mA/cm² (equivalent to 1 A/g current).

[00290] After functionalization, an exemplary FCC is annealed in a furnace in an air atmosphere at 200° C for 1 hour, 4 hours, or 7 hours., the exemplary PANI-(*unannealed*)FCC device displays a much higher discharge time than the exemplary PANI-(*annealed*)FCC device. As shown in **FIG. 15A**, increasing the annealing time increases the discharge time of the exemplary PANI- FCC device, without effecting its capacitance, most likely due to the fact that annealing reduces the number, and thus the pseudocapacitance, of the functional groups present on the CC. Additionally, **FIG. 15B** depicts that increasing the annealing time decreases the semicircle in the high frequency region, indicating a reduction the charge transfer resistance, most likely due to the fact that as the functional groups on the FCC decrease during annealing, the FCC conductivity increases. As such, annealing the exemplary FCC device reduces the functional pseudocapacitance, increases conductivity, and decreases the exemplary device's resistance. The period of annealing does not seem to affect the capacitance of the exemplary devices.

[00291] The performance of an exemplary device under a constant mechanical stress displays its ability to act as a flexible energy storage device. **FIG. 16A** shows the resistance of the exemplary PANI-FCC device decreases under mechanical stress from a flat condition at 0° to a bent condition at 180°. Additionally, **FIG. 16B** displays that the device's resistance, per this example, is maintained within about 4%, as it is bent from its flat to its folded condition over 1,000 cycles. The as-prepared exemplary device exhibits a high flexibility and may be bent 180° without a loss in performance. Additionally, per **FIG. 16C**, the exemplary PANI-FCC device maintains its rectangularly shaped CV curve and capacitance in its folded condition. This excellent performance durability of the exemplary device may be attributed to the high mechanical flexibility of the electrodes and the strong connections between FCC and PANI, and proves that such a device is suitable for flexible use.

[00292] **FIGs. 17A-D** display the electrochemical performance of an exemplary asymmetric device comprising a PANI-FCC positive electrode, an activated carbon negative electrode, and a 1 M H_2SO_4 electrolyte. Per the example measurement shown in **FIG. 17A**, the AC electrode has a predefined voltage potential window of 1.2 V (-0.6 to 0.6 V) which is limited by the water redox range of H_2 evolution. **FIGs. 17B** and **17C** show the CV and CD of the above exemplary device at 50 mV/s and 1 A/g, respectively, whereas the potential window for the asymmetric device is extended to the aqueous electrolyte oxidation wall of 1.3 V, beyond the capabilities of the AC electrode.

[00293] Power density and energy density are the two main parameters used to evaluate a supercapacitor device's performance. **FIG. 17D** depicts a Ragone plot which compares the energy densities and the power densities of the exemplary PANI-FCC symmetric and asymmetric devices over a range of current densities from 1 A/g to 50 A/g. Per **FIG. 17D**, the maximum energy density of the exemplary symmetric device is about 59 Wh/Kg, which decreased to about 24 Wh/kg as the power density increased from about 0.4 kW/kg to about 20 kW/kg. The energy and power density of the exemplary asymmetric device increased to about 91 Wh/kg and 33 W/kg, respectively.

[00294] **FIGs. 23A** and **23B** display exemplary device applications, whereas two asymmetric PANI-FCC//AC devices connected in series, successfully powered a 5 mm diameter red LED **2101** indicator for about 47 minutes, and a clock **2102** for 1 h and 17 min, respectively.

[00295] NQ is an effective redox-active electrolyte which is capable of providing additional redox reactions. In one embodiment, the electrochemical performance of an exemplary PANI//AC asymmetric supercapacitor device with a 1 M H_2SO_4 + 10 millimolar NQ mixed gel electrolyte is shown in **FIGs. 18A-F**, whereas the addition of NQ extends the measured potential window. The CV curves of the exemplary asymmetric PANI//AC device with an NQ electrolyte at different voltage windows and at 100 mV/s are shown in **FIG. 18A**, whereas the potential windows are seen to extended to 1.7 V. The relationship between the potential window and the capacitance of the exemplary device is seen in the inset of **FIG. 18A**, whereas a 1.4 V potential window allows for the highest capacitance. **FIG. 18B** shows that the implementation of the H_2SO_4 + NQ mixed electrolyte in the exemplary device increases the integrated area of cyclic voltammetry compared with H_2SO_4 electrolyte. The Nyquist plots of the PANI//AC devices in the mixed and uniform electrolytes, per **FIG. 18C**, also proves that the exemplary PANI//AC device in the mixed electrolyte exhibits a lower equivalent series resistance of 2.5 Ω than in the uniform electrolyte (3.1 Ω) due to the high electrical conductivity of the electrolyte. As the exemplary PANI//AC device in the mixed electrolyte

additionally exhibits a smaller semicircle in the high frequency region, per the inset graph than the PANI//AC device in the H_2SO_4 electrolyte, the mixed electrode device exhibits a higher capacitance. Additionally, as the equivalent series resistance of the exemplary PANI//AC device in the H_2SO_4 + NQ electrolyte, per the measurements in **FIG. 18C**, is lower than the calculated equivalent series resistance of the exemplary PANI//AC device without NQ, the lower charge transfer resistance of the NQ may improve the capacitance of the device through increased electron transfer. The appearance of a plateau in the discharge curve of the exemplary mixed electrolyte device, at different current densities per **FIG. 18D**, confirms the contribution of NQ towards increasing the discharge time to about 2,000 seconds in a current density of 2 A/g. As calculated per the values in **FIG. 18D**, the addition of 10 millimolar 1,4-naphthoquinon (NQ) into the 1 M H_2SO_4 produces a mixed electrolyte and an exemplary device which exhibits a specific capacity of about 3,200 F/g, in a current density of 1 A/g, and an energy density of about 827 Wh/kg, performing more than 8 times better than the exemplary device in the absence of NQ.

[00296] The inset of **FIG. 18D**, and **FIG. 18E** display the CD curve of the exemplary mixed electrode device at a current density of 50 A/g, and the calculated capacitance as a function of current density, respectively, which highlight the high rate capability, and capacity of about 671 F/g. Finally, **FIG. 18F** shows the Ragone plots of an exemplary device, with and without the presence of NQ in the electrolyte, to highlight the 8 fold positive effect of NQ on energy density.

[00297] The addition of NQ is capable of not only increasing the capacitance of the PANI redox active electrodes, but also improves the capacitance of EDLC materials such as activated carbons. **FIG. 19A** shows the cyclic voltammogram of an exemplary device comprising an activated carbon electrode in PVA/ H_2SO_4 gel redox electrolyte, which demonstrates an outstanding capacitance of about 13,456 F/g. As activated carbon, with its high hydrogen evolution overpotential, may operate at more negative voltages without causing electrolyte decomposition, an exemplary asymmetric supercapacitor exhibits an extended voltage window and a controlled charge storage capacity, via a redox electrolyte that acts on the negative and positive electrodes simultaneously. **FIG. 19B** shows CD curves of exemplary asymmetric AC-FCC and PANI-FCC electrodes in a 3E cell (triple stacked) configuration at a current density of 10 A/g, the results of which agree with that of CV experiments. **FIG. 19C** depicts that the exemplary device exhibits a long discharge time of about 2,000 seconds under a current density of 2 A/g. The appearance of a new plateau in the discharge curve may confirm the contribution from NQ towards the capacitance of the exemplary device. The inset to

FIG. 19C demonstrates the CD curve of the device at a very high current density (100 A/g), revealing the high rate capability of the AC-FCC//PANI-FCC device in the presence of NQ.

DEVICE	ELECTROLYTE	CAPACITANCE (F/g)	ENERGY DENSITY (Wh/kg)	VOLTAGE (V)
CC//CC	H ₂ SO ₄	8	0.7	0.8
FCC//FCC	H ₂ SO ₄	126	11.2	0.8
PANI//PANI	H ₂ SO ₄	480	42.6	0.8
	0.5 mM NQ-in-H ₂ SO ₄ (liquid)	691	61.4	0.8
	10 mM NQ-in-H ₂ SO ₄ (gel)	710	63.1	0.8
PANI//AC	H ₂ SO ₄	276	64.8	1.3
	0.5 mM NQ-in-H ₂ SO ₄ (liquid)	383	76.6	1.2
	H ₂ SO ₄ (gel)	314	62.8	1.2
	10 mM NQ-in-H ₂ SO ₄ (gel)	5,661 @ 2 A/g	1,541	1.4
PANI//PANI//PANI	10 mM NQ-in-H ₂ SO ₄ (gel)	10,706 @ 10 A/g	-	-1
AC//AC//AC	10 mM NQ-in-H ₂ SO ₄ (gel)	13,456 @ 10 A/g	-	-1.1

- 5 **[00298]** **FIG 20A** shows the performance of an exemplary asymmetric supercapacitor comprising a PANI-FCC positive electrode and an AC-FCC negative electrode in an acidic polymer hydrogel electrolyte with and without the redox additive. This asymmetric supercapacitor bypasses the inherently low voltage of symmetric polyaniline devices (0.8 V) and extends the operation voltage window to 1.4 V. Furthermore, the integrated area of the cyclic voltammogram is obviously much
- 10 higher in the presence of the redox additive. The charge and discharge curves in **FIG 20B** show a discharge time of about 6,000 seconds under a current density of 1.88 A/g, whereas in the absence of NQ the same device discharges in only 185 seconds. In other words, the specific capacitance of the device in the presence of NQ is about 5,661 F/g (2.3 F/cm²) under a current density of 1.88 A/g, which is more than 20 times higher than that in the absence of NQ.
- 15 **[00299]** **FIG 20C** shows that the device maintains a high specific capacitance even at very high current densities of up to 94 A/g, revealing the high rate capability of the exemplary AC-FCC//PANI-FCC device in the presence of NQ.
- [00300]** Additionally, the charge/discharge (GCD) cycling of the AC-FCC//PANI-FCC device under a current density of 47 A/g, per **FIG 20D**, indicates an 84% capacitance retention over 7,000
- 20 cycles.
- [00301]** FIG. 21 displays an exemplary relationship between the power density and the energy density of exemplary symmetric and asymmetric devices, in accordance with some embodiments.

An exemplary redox supercapacitor constructed in accordance with the present disclosure demonstrates an outstanding energy density of 1,541 Wh/kg based on the mass of the active materials only.

Examples

- 5 [00302] In one example, an exemplary electrochemical cell has a footprint of about 1 cm² and a thickness of about 1 millimeter, thus encompassing a volume of 0.005 cm³. In this example, the composition of the exemplary electrochemical cell is shown below.

	Mass (g)	Density (g/cm ³)	Volume (cm ³)
CC	0.005	1.55	0.0032
PANI	0.0001	1.33	7.54 x10 ⁻⁵
AC	0.0001	0.5	0.0002
NQ	0.000085	1.42	5.99 x10 ⁻⁵

- 10 [00303] In this example of the electrochemical cell, as the SEM images, per Fig. 5A, display that the PANI nanotubes have a porosity of about 28.4%, the actual PANI volume is calculated to be about 1.05 x10⁻⁴ cm³. Additionally,

- 15 [00304] In this example, the exemplary electrochemical cell displays a capacitance, voltage, and energy of about 1.14 F, 1.4 V, and 0.0003 Wh, respectively. Additionally, FIG. 22, displays the gravimetric and volumetric densities of an asymmetric PANI//AC device with an NQ redox electrolyte and carbon cloth, as normalized by the mass and volume of the electrodes (1554 Wh/kg, 1019 Wh/L), by the mass and volume of the electrodes and the redox electrolyte (1091 Wh/kg, 851 Wh/L), and by the mass and volume of the electrodes, the redox electrolyte and the carbon cloth (59 Wh/kg. 87 Wh/L).

Terms and Definitions

- 20 [00305] Unless otherwise defined, all technical terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the device described herein belongs. As used in this specification and the appended claims, the singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise. Any reference to “or” herein is intended to encompass “and/or” unless otherwise stated.
- 25 [00306] As used herein, and unless otherwise specified, the term AC refers to activated carbon.
- [00307] As used herein, and unless otherwise specified, the term CC refers to carbon cloth.

[00308] As used herein, and unless otherwise specified, the term FCC refers to functionalized carbon cloth.

[00309] As used herein, and unless otherwise specified, the term PANI refers to Polyaniline.

[00310] As used herein, and unless otherwise specified, the term PANI-CC refers to a carbon cloth,
5 on which Polyaniline structures have been synthesized.

[00311] As used herein, and unless otherwise specified, the term PANI-FCC refers to a functionalized carbon cloth, on which polyaniline structures have been synthesized.

[00312] As used herein, and unless otherwise specified, the term SDS refers to sodium dodecyl sulfate.

10 [00313] As used herein, and unless otherwise specified, a CV chart refers to a cyclic voltammogram chart.

[00314] As used herein, and unless otherwise specified, a CD chart refers to a charge-discharge chart.

[00315] While preferable embodiments of the present methods and devices taught herein have been
15 shown and described herein, it will be obvious to those skilled in the art that such embodiments are provided by way of example only. Numerous variations, changes, and substitutions will now occur to those skilled in the art without departing from the methods and devices taught herein. It should be understood that various alternatives to the embodiments of the methods and devices taught herein described herein may be employed in practicing the methods and devices taught herein. It is intended
20 that the following claims define the scope of the methods and devices taught herein and that methods and structures within the scope of these claims and their equivalents be covered thereby.

[00316] As used herein, and unless otherwise specified, the term "about" or "approximately" means an acceptable error for a particular value as determined by one of ordinary skill in the art, which depends in part on how the value is measured or determined. In certain embodiments, the term
25 "about" or "approximately" means within 1, 2, 3, or 4 standard deviations. In certain embodiments, the term "about" or "approximately" means within 30%, 25%, 20%, 15%, 10%, 9%, 8%, 7%, 6%, 5%, 4%, 3%, 2%, 1%, 0.5%, 0.1%, or 0.05% of a given value or range.

[00317] In certain embodiments, the term "about" or "approximately" means within 100 nanometers, 90 nanometers, 80 nanometers, 70 nanometers, 60 nanometers, 50 nanometers, 40
30 nanometers, 30 nanometers, 20 nanometers, 10 nanometers, 9 nanometers, nanometers, 8 nanometers, 7 nanometers, 6 nanometers, 5 nanometers, 4 nanometers, 3 nanometers, 2 nanometers, or 1 nanometers of a given value or range. In certain embodiments, the term "about" or

"approximately" means within 100 mF/cm², 90 mF/cm², 80 mF/cm², 70 mF/cm², 60 mF/cm², 50 mF/cm², 40 mF/cm², 30 mF/cm², 20 mF/cm², 10 mF/cm², 9 mF/cm², mF/cm², 8 mF/cm², 7 mF/cm², 6 mF/cm², 5 mF/cm², 4 mF/cm², 3 mF/cm², 2 mF/cm², or 1 mF/cm² of a given value or range. In certain embodiments, the term "about" or "approximately" means within 5V, 4V, 3V, 2V, 1V, 0.5V, 0.1V, or 0.05V of a given value or range. In certain embodiments, the term "about" or "approximately" means within 100 F/g, 90 F/g, 80 F/g, 70 F/g, 60 F/g, 50 F/g, 40 F/g, 30 F/g, 20 F/g, 10 F/g, 9 F/g, F/g, 8 F/g, 7 F/g, 6 F/g, 5 F/g, 4 F/g, 3 F/g, 2 F/g, or 1 F/g of a given value or range. In certain embodiments, the term "about" or "approximately" means within 100 Wh/kg, 80 Wh/kg, 60 Wh/kg, 40 Wh/kg, 20 Wh/kg, 15 Wh/kg, 10 Wh/kg, 9 Wh/kg, 8 Wh/kg, 7 Wh/kg, 6 Wh/kg, 5 Wh/kg, 4 Wh/kg, 3 Wh/kg, 2 Wh/kg, 1 Wh/kg, 0.5 Wh/kg, 0.1 Wh/kg, or 0.05 Wh/kg of a given value or range. In certain embodiments, the term "about" or "approximately" means within 40 °C, 30 °C, 20 °C, 10 °C, 9 °C, °C, 8 °C, 7 °C, 6 °C, 5 °C, 4 °C, 3 °C, 2 °C, or 1 °C of a given value or range. In certain embodiments, the term "about" or "approximately" means within 60 minutes, 50 minutes, 40 minutes, 30 minutes, 20 minutes, 10 minutes, 9 minutes, minutes, 8 minutes, 7 minutes, 6 minutes, 5 minutes, 4 minutes, 3 minutes, 2 minutes, or 1 minute of a given value or range. In certain embodiments, the term "about" or "approximately" means within 60 hours, 50 hours, 40 hours, 30 hours, 20 hours, 10 hours, 9 hours, hours, 8 hours, 7 hours, 6 hours, 5 hours, 4 hours, 3 hours, 2 hours, or 1 hour of a given value or range. In certain embodiments, the term "about" or "approximately" means within 40.0 grams, 30.0 grams, 20.0 grams, 10.0 grams, 5.0 grams, 1.0 grams, 0.9 grams, 0.8 grams, 0.7 grams, 0.6 grams, 0.5 grams, 0.4 grams, 0.3 grams, 0.2 grams or 0.1 grams, 0.05 grams, or 0.01 grams of a given value or range. In certain embodiments, the term "about" or "approximately" means within 30.0 A/g, 20.0 A/g, 10.0A/g, 5.0 A/g, 1.0 A/g, 0.9 A/g, 0.8 A/g, 0.7 A/g, 0.6 A/g, 0.5 A/g, 0.4 A/g, 0.3 A/g, 0.2 A/g, or 0.1 A/g of a given value or range. In certain embodiments, the term "about" or "approximately" means within 20 kW/kg, 15 kW/kg, 10 kW/kg, 9 kW/kg, 8 kW/kg, 7 kW/kg, 6 kW/kg, 5 kW/kg, 4 kW/kg, 3 kW/kg, 2 kW/kg, 1 kW/kg, 0.5 kW/kg, 0.1 kW/kg, or 0.05 kW/kg of a given value or range. In certain embodiments, the term "about" or "approximately" means within 5 L, 4 L, 3 L, 2 L, 1 L, 0.5 L, 0.1 L, or 0.05 L. In certain embodiments, the term "about" or "approximately" means within 30.0 ml, 20.0 ml, 10.0 ml, 5.0 ml, 1.0 ml, 0.9 ml, 0.8 ml, 0.7 ml, 0.6 ml, 0.5 ml, 0.4 ml, 0.3 ml, 0.2 ml, or 0.1 ml of a given value or range. In certain embodiments, the term "about" or "approximately" means within 5 M, 4 M, 3 M, 2 M, 1 M, 0.5 M, 0.1 M, or 0.05 M of a given value or range.

CLAIMS

WHAT IS CLAIMED IS

- 5 1. A supercapacitor comprising:
 - two or more electrodes, wherein at least one electrode comprises a functionalized carbon electrode;
 - a current collector; and
 - a redox electrolyte.
- 10 2. The supercapacitor of claim 1, wherein the functionalized carbon electrode comprises:
 - a carbon substrate comprising carbon cloth, carbon fiber, amorphous carbon, glassy carbon, carbon nanofoam, carbon aerogel, graphene foam or any combination thereof;
 - and
 - a conducting polymer disposed on the carbon substrate, wherein the conducting polymer
 - 15 comprises polyaniline, poly(p-phenylene oxide), poly(p-phenylene sulfide), poly(3,4-ethylenedioxythiophene), polypyrrole, polythiophene, poly(3-alkythiophene), poly(3-methylthiophene), poly(3-hexylthiophene), or any combination thereof.
3. The supercapacitor of claim 2, wherein the conducting polymer has a morphology of one or more nanotubes.
- 20 4. The supercapacitor of claim 3, wherein a nanotube has a length of 100 nanometers to 10,000 nanometers.
5. The supercapacitor of claim 3, wherein a nanotube has an outer width of 10 nanometers to 1,000 nanometers.
6. The supercapacitor of claim 3, wherein a nanotube has an inner width of 50 nanometers to 800
- 25 nanometers.
7. The supercapacitor of claim 3, wherein a surface of a nanotube contains a nanostructure.

8. The supercapacitor of claim 7, wherein a nanostructure comprises a nanorod, nanochain, nanofiber, nanoflake, nanoflower, nanoparticle, nanoplatelet, nanoribbon, nanoring, nanosheet, or any combination thereof.
9. The supercapacitor of claim 7, wherein a nanostructure has a length of 4 nanometers to 50
5 nanometers.
10. The supercapacitor of claim 7, wherein a nanostructure has a width of 4 nanometers to 50 nanometers.
11. The supercapacitor of claim 2, wherein the functionalized carbon electrode has an areal capacitance of at least 150 mF/cm² to 750 mF/cm².
- 10 12. The supercapacitor of claim 2, wherein the functionalized carbon electrode has a resistance, which decreases after 1,000 cycles of bending by at most 8%.
13. The supercapacitor of claim 1, wherein the redox electrolyte comprises a quinone.
14. The supercapacitor of claim 1, wherein the supercapacitor has a working potential of 0.1 V to 1.7 V.
- 15 15. The supercapacitor of claim 1, wherein the supercapacitor has a gravimetric capacitance which, after 1,000 cycles of charging, decreases by at most 26%.
16. The supercapacitor of claim 1, wherein the supercapacitor has a gravimetric capacitance which is 125 F/g to 20,000 F/g.
17. The supercapacitor of claim 1, wherein the supercapacitor has a gravimetric energy density
20 which is 12 Wh/kg to 3,000 Wh/kg.
18. A method of fabricating a functionalized electrode comprising:
 - a) functionalizing a carbon substrate to form a functionalized carbon substrate;
 - b) preparing the functionalized carbon substrate;

- c) formulating a polymerization fluid; and
- d) synthesizing one or more nanotubes on the functionalized carbon substrate.

19. The method of claim 18, wherein the functionalizing of a carbon substrate to form a functionalized carbon substrate comprises:

- i) forming a functionalization solution;
- ii) heating the functionalization solution;
- iii) cooling the functionalization solution;
- iv) displacing a piece of carbon substrate into the functionalization solution; and
- v) rinsing a piece of functionalized carbon substrate.

20. The method of claim 19, wherein the heating of the functionalization solution occurs at a temperature of 30° C to 120° C.

21. The method of claim 19, wherein the heating of the functionalization solution occurs for a period of time of 60 minutes to 240 minutes.

22. The method of claim 18, further comprising a step of annealing the functionalized carbon substrate before the preparing of the functionalized carbon substrate.

23. The method of claim 22, wherein the functionalized carbon substrate is annealed at a temperature of 100° C to 400° C.

24. The method of claim 22, wherein the functionalized carbon substrate is annealed for a period of time of 0.5 hours to 14 hours.




25. The method of claim 18, wherein the preparing of the functionalized carbon substrate comprises:

- i) cutting a piece of the functionalized carbon substrate;
- ii) submerging the piece of functionalized carbon substrate in a solvent solution;
- iii) sonicating the piece of functionalized carbon substrate in the solvent solution; and
- iv) drying the piece of functionalized carbon substrate.

26. The method of claim 25, wherein the sonicating occurs for a period of time of 15 minutes to 60 minutes.
27. The method of claim 25, wherein the drying occurs at a temperature of 30° C to 120° C.
28. The method of claim 25, wherein the drying occurs over a period of time of 3 hours to 12 hours.
29. The method of claim 18, wherein the formulating of a polymerization fluid comprises:
- i) forming a polymerization solution comprising:
 - a conducting polymer;
 - an acid;
 - a detergent;
 - water; and
 - an oxidizing agent;
 - ii) stirring the polymerization solution to form the polymerization fluid.
30. The method of claim 29, wherein the conducting polymer comprises polyaniline, poly(p-phenylene oxide), poly(p-phenylene sulfide), poly(3,4-ethylenedioxythiophene), polypyrrole, polythiophene, poly(3-alkythiophene), poly(3-methylthiophene), poly(3-hexylthiophene), or any combination thereof.
31. The method of claim 29, wherein the stirring of the polymerization solution occurs for a period of time of 10 minutes to 40 minutes.
32. The method of claim 18, wherein the synthesizing of a nanotube on the functionalized carbon substrate comprises:
- i) agitating the polymerization fluid;
 - ii) immersing the functionalized carbon substrate in the polymerization fluid;
 - iii) storing the functionalized carbon substrate in the polymerization fluid;
 - iv) removing a functionalized carbon substrate from the polymerization fluid;
 - v) washing the functionalized carbon substrate; and
 - vi) drying the functionalized carbon substrate.

33. The method of claim 32, wherein the storing of the functionalized carbon substrate in the polymerization fluid occurs at a temperature of 10° C to 50° C.
34. The method of claim 32, wherein the storing of the functionalized carbon substrate in the polymerization fluid occurs for a period of time of at least 8 hours.
- 5 35. The method of claim 32, wherein the drying of the functionalized carbon substrate occurs at a temperature of 30° C to 120° C.

1/28



2/28




FIG. 2




FIG. 3

4/28




FIG. 4

5/28




FIG. 5A




FIG. 5B

6/28




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 6F




FIG. 6G




FIG. 6H




FIG. 7




FIG. 8

8/28




FIG. 9




FIG. 10

9/28




FIG. 11




FIG. 12

10/28




FIG. 13A




FIG. 13B

11/28




FIG. 13C




FIG. 13D

12/28




FIG. 13E




FIG. 13F

13/28




FIG. 13G




FIG. 13H

14/28




FIG. 14




FIG. 15A

15/28




FIG. 15B




FIG. 16A

16/28




FIG. 16B




FIG. 16C

17/28




FIG. 17A




FIG. 17B

18/28




FIG. 17C




FIG. 17D

19/28




FIG. 18A










FIG. 18B



**FIG. 18E****FIG. 18F**

**FIG. 19A****FIG. 19B**

23/28




FIG. 19C

24/28




FIG. 20A




FIG. 20B

25/28




FIG. 20C




FIG. 20D

26/28




FIG. 21

27/28




FIG. 22

28/28




FIG. 23A




FIG. 23B




FIG. 2