

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 December 2008 (18.12.2008)

PCT

(10) International Publication Number
WO 2008/154406 A1

- (51) International Patent Classification:
A61B 17/00 (2006.01)
 - (21) International Application Number:
PCT/US2008/066161
 - (22) International Filing Date: 6 June 2008 (06.06.2008)
 - (25) Filing Language: English
 - (26) Publication Language: English
 - (30) Priority Data:
60/942,788 8 June 2007 (08.06.2007) US
 - (71) Applicant (for all designated States except US): U.S. ENDOSCOPY GROUP, INC. [US/US]; 5976 Heisley Road, Mentor, OH 44060 (US).
 - (72) Inventors; and
 - (75) Inventors/Applicants (for US only): USPENSKI, Alexis [US/US]; 3617 Riverdale Road, Rock Creek, OH 44084 (US). BOYCE, Aaron [US/US]; 3655 Garretts Cove, Eastlake, OH 44095 (US). KAYE, Christopher, J. [US/US]; 7640 Kellogg Road, Concord, OH 44077 (US). RANALLO, Cynthia, Ann [US/US]; 1266 East 345th Street, Eastlake, OH 44095 (US).
 - (74) Agent: JOHNSTON, William, A.; Calfee, Halter & Griswold Llp, 800 Superior Avenue-Suite 1450, Cleveland, OH 44114-2688 (US).
 - (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
 - (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

(54) Title: RETRIEVAL DEVICE




Figure 17

(57) Abstract: An endoscopic device for retrieving an object from within a human body is disclosed. The device includes a support assembly, a transmitting assembly, a wire, and a net element. The support assembly has a base and a tubular member. The transmitting assembly includes a handle and a motion transmitting link fixed to the handle and extending through at least a portion of the tubular member. The wire defines a loop portion and two leg portions. A proximal end of each leg portion is secured to the link by a first connection and the two leg portions are secured to each other by at least a second connection distal from the first connection. The net element has a distal portion secured to the loop portion and a proximal portion secured relative to the leg portions. The loop portion is movable between an expanded position and a collapsed position.

WO 2008/154406 A1

RETRIEVAL DEVICE

Cross Reference to Related Applications

This non-provisional application claims the benefit of U.S. Provisional Patent Application No. 60/942,788, entitled "Retrieval Device," filed June 8, 2007, which is hereby incorporated in its entirety, to the extent that it is not conflicting with the present application.

Field of the Invention

The present invention relates to a retrieval device and to an endoscopic retrieval device for retrieving objects from within a human subject.

Background of the Invention

Endoscopic retrieval or removal devices are known in the art and are conventionally used to recover objects from inside a human subject. Such objects may include severed human tissue, foreign objects, or food bolus. Some typical devices include forceps or clasps to grab objects. Certain devices of this type are not well-suited for retrieving heavy, rounded or blunt objects such as large tissue masses, a food bolus, coins, marbles and batteries because the objects are difficult to hold secure. Further, if an object is dropped near the trachea during the removal process, the results can be catastrophic for the patient. Other devices include a variety of net support and net operating structures.

Many retrieval devices are used within an instrument channel of an endoscope during endoscopic medical procedures. These devices are generally expandable and collapsible relative to a tube inserted into the instrument channel. For example, a wire loop at the distal end of the device may expand and collapse relative to the tube by action of a handle at the proximal end of the device. Further, a net may be secured to the expandable and collapsible wire loop.

Summary of the Invention

In an illustrated embodiment of the invention, a device for retrieving objects, such as for example, impacted food bolus, foreign objects, and severed human tissue, is disclosed. The device is for use within an instrument channel of an endoscope during endoscopic medical procedures.

The device includes a body, a handle fixed to and movable relative to the body, an elongated tube fixed to the body, a link extending substantially through the tube and having a first end fixed to the handle and a second end remote from the body, and a net including a loop and a net element. The loop is expandable and collapsible by action of the handle relative to the body. The net is secured at distal and proximal locations relative to the handle. The device is more reliable, structurally simpler, and less costly to manufacture than prior devices.

Further features and advantages of the invention will become apparent from the following detailed description made with reference to the accompanying drawings.

Brief Description of the Drawings

Figure 1 is a perspective view of a retrieval device constructed in accordance with an embodiment of the present invention;

Figure 2 is a cross-sectional fragmentary view of the distal portion of the device illustrated in Figure 1, showing a retrieval net in a stored position within a tube;

Figure 3 is an alternative view of Figure 2, showing the retrieval net in a deployed position outside of the tube;

Figure 4 is an exploded perspective view of the designated circular section of Figure 1, showing detail of the net element and the distal end of the loop;

Figure 5 is an exploded fragmentary view of the net of a retrieval device, showing an alternative distal end of the loop;

Figure 6 is an exploded fragmentary view of the net of a retrieval device, showing yet another alternative distal end of the loop;

Figure 7 is a perspective view of a distal portion of the device illustrated in Figure 4, showing an exemplary food bolus captured within the retrieval net;

Figures 8-10 are views of a portion of the device of Figure 4, showing the portion during a variety of assembly steps;

Figure 11 is a front elevation view of a distal portion of the device of Figure 4;

Figures 12a-12b and 13 are enlarged views of the designated circular sections of Figure 11, showing a variety of structural detail;

Figure 14a is an enlarged sectional view of the device of Figure 4, showing a proximal net connection;

Figure 14b is an enlarged sectional view of the device of Figure 4, showing another proximal net connection;

Figure 15 is a top view of a net element according to another embodiment of the invention;

Figure 16 is a front elevation view of a distal portion of the device according to another embodiment of the invention;

Figure 17 is a cross-sectional fragmentary view of the distal portion of the device illustrated in Figure 16, showing a retrieval net in a deployed position; and

Figure 18 is a cross-sectional fragmentary view of the distal portion of the device illustrated in Figure 16, showing the retrieval net in a stored position.

Detailed Description of the Invention

The Detailed Description of the Invention merely describes preferred embodiments

of the invention and is not intended to limit the scope of the invention or claims in any way. Indeed, the invention as described by the claims is broader than and unlimited by the preferred embodiments, and the terms used have their full ordinary meaning.

A device for retrieving an object from within a human subject is disclosed. In discussing the device, the terms distal and proximal are used with respect to the operator's hand. In other words, when the device is used within the instrument channel of an endoscope or similar device, the proximal and distal orientation are relative to the position of the surgeon or operator of the device. Further, it should be noted that the terms first connection, second connection, third connection, and the like do not imply a manufacturing order.

It should also be noted that for the purposes of this application, the terms attach (attached), connect (connected), and link (linked) are not limited to direct attachment, connection, or linking but also include indirect attachment, connection, or linking with intermediate parts, components, or assemblies being located between the two parts being attached, connected, or linked to one another. In addition, the terms attach (attached), connect (connected), and link (linked) may include two parts integrally formed or unitarily constructed.

For exemplary purposes only, the invention will be discussed in regard to a device designed for use within an endoscope for retrieving objects within relatively tight passages, such as for example, impacted food bolus from the esophagus. It should be apparent to others with ordinary skill in the art that the discussion and Figures included in this application are by way of example only, and that the invention can be utilized with endoscopic retrieval devices having a wide variety of structures, shapes, strengths, or purposes. One of many other exemplary uses for the invention is to remove polyps from the colon.

Several exemplary devices for endoscopic retrieval of an object from within a subject are disclosed in U.S. Pat. No. 6,814,739 to Secrest et al.; Application No. 10/965,542, entitled "Retrieval Device" and filed July 28, 2005; and Application No.

11/137,763, entitled "Retrieval Device" and filed December 1, 2005, each of which incorporated herein by reference in its entirety, to the extent that any do not conflict with the present application.

As mentioned, devices using netting have been developed to capture rounded or blunt objects. In the use of devices having netting, and it is believed in the use of other devices, physicians have experienced difficulty in recovering certain objects, such as for example, impacted food bolus from the esophagus. A bolus is a mass of masticated or chewed food. In some cases, the bolus becomes impacted in the esophagus due to disease or other disorders and consequently does not pass into the stomach. It may be more difficult to position a net over an object of this type or the object may be heavier than the human tissue or foreign object for which a typical net device was originally designed. This problem is especially apparent when manipulating the device in relatively tight places within the body. As a result, netting support collapses and does not retain its shape in a deployed position when holding the captured object. Further, the netting may tear or net connections may fail causing reliability concerns.

To solve these and other problems, the retrieval device of the invention is more reliable, structurally simpler, and less costly to manufacture than prior devices. For example, in some embodiments, the proximal portion of the net element is secured to the wire that forms the loop and leg portions of the retrieval net using a shorter tether or anchor than previous designs which anchor the net element at a more proximal location. In other embodiments, no tether or anchor is used to secure the proximal portion of the net element and instead the net element is routed between welds, or other similar connections, connecting the leg portions of the wire together. Where no tether is used to secure the proximal portion of the net element, the chances of the net element breaking or tearing are reduced because the forces are distributed more evenly over a greater area instead of at an isolated point of contact.

Further, in some embodiments, the proximal portion of the net element at least partially surrounds the connection of the leg portions to the cable and/or the connection securing the leg portions together. As such, the proximal portion of the net element

inhibits damage to the connections and the inside of the tubular member. The proximal portion of the net element also provides a damping effect on the cable movement toward the distal end of the tubular member when the handle is activated. This also provides more control over the deployment of the net and cable and controls the portion of the device that exits the opening of the tubular member when the retrieval net is in the deployed position. The proximal portion of the net element also helps to center the leg portions of the wire and the cable within the tubular member.

The retrieval net generally collapses and expands relative to a tube inserted through the instrument channel of the endoscope. In the collapsed position, the retrieval net is small enough in diameter to fit inside at least the distal end of a lumen of the tubing. Further, any connection securing the net element to the loop should be small enough to fit within the lumen and allow the retrieval net to collapse and expand repeatedly. The connection should also be able to hold the net element in place relative to the loop during the expansion and collapse of the retrieval net. Further, the loop is generally connected to a motion transmitting link. The motion transmitting link allows the loop to be manipulated by a handle at the proximal end of the device. As such, any connection or connections securing the loop to the motion transmitting link must also be small enough to fit within the lumen and allow the retrieval net to collapse and expand repeatedly. If either of these connections is too large, the connection may drag or catch on the inside wall of the lumen. The friction between the connection and the inside wall of the lumen may prohibit essentially a 1:1 ratio between the movement of the handle and the movement of the distal end of the loop or retrieval net.

The net element is generally supported by the loop by threading, or weaving, the flat wire through the holes in the net element. However, the net element may be supported by the loop by any suitable method known in the art. For example, the net element may wrap around the loop, like a sleeve, or be tied to the loop. Further, the net element may be secured to the wire by tethers, anchors, adhesives, or the like such that the net element is held in place relative to the loop during the expansion and collapse of the retrieval net. For example, tethers or anchors may be used to secure the net element to the distal end and the

proximal end of the loop. In an embodiment of the invention, the proximal portion of the net element is attached adjacent a connection securing the two leg portions together, by a tether or anchor, such as for example, a string tie. The proximal portion of the net element may be attached using a tether or anchor to the proximal side of the connection securing the two leg portion together. The proximal portion of the net element may be attached using a tether or anchor to a 360 degree curved portion of at least one leg portion. The distal portion of the net element may also be attached using a tether or anchor to a 360 degree curved portion of the loop portion. In another embodiment, the proximal portion of the net element may be secured to the leg portions by routing the net element through connections securing the two leg portions together. The size and smooth or curved contour of these connections reduce the drag or friction on the inside wall of the lumen, permitting essentially a 1:1 ratio between the movement of the handle and the movement of the distal end of the loop or retrieval net.

Referring now to the drawings, Figure 1 is a perspective view of a retrieval device 10 constructed in accordance with an embodiment of the invention. The device 10 includes a support base or elongated body 14. The body 14 includes a ring 16 at a proximal end. The device 10 also includes a handle 18 having two rings 20. The handle 18 is mounted over an interior section 15 of the body 14 and is movable relative to the body in the direction A_1 as illustrated, or in an opposing direction. For example, an operator may place a finger in each of the rings 20 and thumb of the same hand in the body ring 16. By moving the two fingers in the direction A_1 , an operator can move the handle 18 relative to the body 14. In contrast, the handle 18 can be slid in a direction opposite A_1 by pulling one's fingers towards one's thumb.

The device 10 includes an elongated introducer member or tubular member 24 having a first end 26 fixed to the body 14 and a second end 28 remote from the body. The tubular member 24 and the body 14 are a fixed support assembly for the moving parts of the device 10. The tubular member 24 may be any suitable, small-diameter tube formed of a non-reactive low-friction flexible material, such as for example, polytetrafluorethylene. The tubular member 24 defines a lumen with an opening 30 at the tubular member second

end 28, as best seen in Figure 2 which shows a cross-sectional view of a distal portion of the device 10.

A motion transmitting link 34 is connected to the handle 18. The link can be a solid cable, a hollow tube, or any suitable elongated object or combination of objects for transferring axial motion from the handle 18 to other parts of the device. The link 34 has a first end 36 fixed to the handle 18 and a second end remote from the body 14. As shown in the drawings, the link extends substantially through the tubular member 24 lumen. The link may be constructed of any suitable rigid material. The link may be one piece or formed from a series of pieces and connections, such as for example, hypodermic tubes, swage connections, and cables.

Still referring to Figure 1, the device also includes a retrieval net 50. The retrieval net 50 is used by the operator to capture and retrieve objects from within a human subject. The retrieval net 50 includes a loop 52, or loop portion, and a net element 54 secured to the loop. The net element 54 is supported by the loop 52 by threading, or weaving, the loop through holes in the net element. However, the net element 54 may be supported by the loop 52 by any suitable method known in the art. Further, it should be apparent to others with ordinary skill in the art that a variety of net shapes and sizes can be utilized in the practice of this invention.

As shown in Figures 3 and 4, a tether or anchor 57a disposed at the distal portion of the net element 54 anchors the net element to the loop 52 at a distal end 53 of the loop. Other distal tether or anchor designs and distal net anchoring methods can be utilized in the practice of this invention.

As discussed, the retrieval net 50 is designed for movement between two positions. Figures 1 and 3 show the retrieval net 50 in a deployed position. In this position, the retrieval net 50 has a length L_1 and a width W_1 . Figure 2 is a cross-sectional view of a distal portion of the device 10, showing the retrieval net 50 in a stored position within the tube 24. In this position, the retrieval net 50 has a length L_2 which is considerably longer than L_1 . As shown in Figure 2, the retrieval net 50 is disposed within the tube 24 for

deployment and retrieval through the tubular member lumen opening 30. By movement of the handle 18 relative to the body 14, the retrieval net 50 is movable between either the deployed or stored positions.

Referring again to Figure 3, the retrieval net 50 is illustrated in a deployed position and fully expanded outside of the tube 24 second end 28. The net element 54 may be constructed of any suitable light weight material, such as for example, nylon mesh string 56, as best seen in Figure 4. The net element 54 has a centrally located object receiving pouch section 58. To be discussed further in greater detail, captured objects rest within this section as shown in Figure 7.

As discussed, the retrieval net 50 shown in Figure 3 includes a loop portion 52 formed by a wire. The loop 52 acts as a support for the net element 54 when the retrieval net is deployed. The loop 52 is resiliently movable between a collapsed position shown in Figure 2 to an expanded position shown in Figure 3 by operator action of the handle 18 relative to the body 14. A distal end 53 of the loop 52 includes structure to resist collapse of the loop during use.

Referring now to Figure 4, an exploded perspective view of the designated circular section of Figure 1 is shown. In the embodiment shown, the loop 52 is formed by a flat wire constructed of a resilient material, such as for example, 304 stainless steel. The loop 52 may be constructed from a material having a tensile strength greater than 300,000 psi. Again, it should be apparent to others with ordinary skill in the art that the present invention can be utilized with a loop 52 constructed from a wide variety of materials.

The device 10 as illustrated in Figures 3 and 4 includes several features that promote expansion and prohibit collapse when an object is held within the net element 54 or the device is used in a relatively tight passage of the body. The loop 52 includes several collapse-resistant bends 60. The location of the bends 60 act as memory points and are retained by the loop 52 through multiple deployments. These bends 60 are constructed such that the loop 52 forms a polygon shape when deployed. As shown, the loop 52 forms a general hexagon shape. It is believed that a polygon shape is more resilient and less

likely to collapse when an object is held within the net or when retrieving an object within a narrow passage. It should be understood by those with ordinary skill in the art that the polygon shape shown in Figure 3 is for exemplary purposes only, and other polygon or non-polygon shapes can be used in the practice of the invention, such as for example oval or round shapes.

As shown in Figure 4, the loop 52 further includes a 360 degree curved portion 64 disposed at a distal end 53 of the loop. This curved portion 64 acts as a spring tip to further prohibit collapse when an object is held within the retrieval net 50. This spring tip 64 also acts to promote polygon segments 65a, 65b to remain apart during deployment. This feature is beneficial in tight passages, such as for example, the esophagus. As mentioned, the tether or anchor 57a anchors the net element 54 to the curved portion 64 of the loop 52.

Several other embodiments include alternative shapes and structures of the distal end of the loop. Figure 5 shows the distal end of the support wire in an alternative shape. The loop 52 is bent to form a protruding tip 68. It is believed that this shape promotes polygon segments 69a, 69b to remain apart during deployment and use.

Referring to Figure 6, an exploded fragmentary view of other alternative structure of the distal end of the loop 52 is shown. As in the embodiment shown in Figure 5, the distal end of the loop 52 is bent into a protruding tip 68. Over the spring tip 68, a tip cap member 70 is press fit or connected by another suitable technique. The tip 70 may be constructed of plastic or any other suitable material. The tip 70 includes an aperture 72 therethrough as a distal end. As shown, the tether or anchor 57a is placed through the aperture and tied off to secure the net element 54 to the loop 52. To be discussed in greater detail, in one embodiment, a corresponding tether or anchor 57b can be used to secure the net element 54 on the proximal side of the retrieval net 50. The tether or anchor 57b is illustrated in Figures 14a-14b as a tie-off. It should be understood by those with ordinary skill in the art that the illustrated tethers or anchors 57a, 57b are for exemplary purposes only, and that other tether or anchor techniques and structure may be used in the practice of the invention.

Referring now to Figures 8-10, a portion of the device of Figure 4 is shown during a variety of assembly steps. The loop 52 of the wire is shown in Figure 8 in a polygon form prior to assembly within the tube 24. The wire extends back toward the proximal end of the device 10 and forms two adjacent, or leg, portions 100 and 102. The leg portions 100, 102 are secured to each other by a connection 104a, such as for example, with a weld or by crimping or twisting the portions together, having an axial length L_w of sufficient size to secure the portions together. As shown, the leg portions 100, 102 are joined by a weld 104a. The leg portions 100, 102 extend beyond the weld 104a a length L_3 . The extension lengths of the two leg portions 100, 102 may be mismatched by a length L_m , but this mismatch is not required. The mismatch in extension lengths of the two leg portions 100, 102 allows space to connect the two leg portions to the cable during manufacturing of the device.

The net element 54 is shown in Figures 8-10 in various stages of assembly. In Figure 8, the net element 54 is shown as it is just beginning to be woven around the flat wire loop 52. For purposes of perspective only, the net element 54 is shown in various positions in Figure 9. With the net element 54 in a first position, the net element has an outer edge 106. In this first position, the net element 54 is shown to have the outer edge 106 cooperatively shaped with the loop 52. It should be apparent to others with ordinary skill in the art that a variety of net shapes and sizes can be utilized in the practice of this invention. The outer edge 106 illustrates the size of the net element 54 in relation to the loop 52 prior to the net element being woven on the loop.

In a second position, the outer edge of the net element 54 now becomes line or outer edge 108. The second position shows net element 54 after it is woven on the loop 52. As can be seen, after the net element 54 is woven on the loop 52, the outer edge 106 of the net element 54 is now closer in position to the loop 52. This change in position creates the receiving pouch 58. As shown in Figure 9, the net element 54 in the second position or woven position includes an outer peripheral portion 109 that extends beyond the loop 52. As shown in Figure 10, this excess portion 109 can be trimmed or otherwise removed prior to final assembly.

Two tethers or anchors are shown anchoring the net element 54 to the loop 52 in Figure 10. A first distal tether or anchor 57a is shown, as previously described in regard to Figures 3 and 4. A second proximal tether or anchor 57b is shown and extends from the net element 54 to the proximal side of connection 104a securing the leg portions 100, 102 to each other. The second proximal tether or anchor 57b is shown in more detail in Figures 14a and 14b.

Figure 11 is a front elevation view of the device shown after subsequent assembly steps have been completed. A second connection 104b proximal to the first connection 104a is shown. As shown, the second connection 104b is a weld. The second connection 104b joins the leg portions 100, 102 with a cable 110. As best shown in Figure 12a, the leg portions 100, 102 are extended over the cable a length L_w . Also, as shown in Figure 8, the leg portions 100, 102 may be mismatched. The size and length of the proximal connection 104b may be the same or different than the length of the distal connection 104a. The connection 104b is of adequate strength to maintain correlating axial movement between the cable 110 and the leg portions 100, 102. In Figure 12b, a section of heat shrink material 112 is shown over the connection 104b to inhibit damage to the tubular member.

Referring now to Figure 13, the proximal end of the cable 110 is anchored axially in relation to the handle by a length of hypodermic tube 114. In Figure 13, the cable 110 is shown secured to the tube 114 by a swage connection 116 having a length L_s . The tube 114 extends distally beyond the swage connection 116 of length L_5 . The swage connection 116 is of adequate strength to maintain correlating axial movement between the tube 114 and the cable 110. As shown in Figure 11, the overall length of the motion transmitting link, which includes the tube 114 and the cable 110, is L_4 .

Figure 14a is an enlarged view of the distal portion 28 of the tube 24. As shown, the tether or anchor 57b anchors the proximal portion of the net element 54 and extends from the net element to the proximal side of the weld connection 104a. As shown, no internal connectors are used in this design to close the loop 52 or secure the loop 52 to the cable 110.

Figure 14b is another enlarged view of the distal portion 28 of the tube 24. As shown, the ends of the leg portions 100, 102 of the wire are connected to the cable 110. However, the leg portions 100, 102 of the wire may be connected, or secured, to each other, such as for example, with a weld or by crimping or twisting the portions together, but is not shown. In Figure 14b, the tether or anchor 57b anchors the proximal, or tail, portion of the net element 54 to a 360 curved portion 192 of leg portion 102 of the wire. It should be apparent to others with ordinary skill in the art that the curved portion may be included on either or both leg portions of the wire.

In the exemplary device shown in Figures 1-14b, the tube 114, cable 110, and connections thereof axially connect to form the transmitting link 34. However, other combinations of elements are possible.

A net element 254 is shown in Figure 15 according to another embodiment of the invention. As shown, the net element 254 has an outer edge 206 cooperatively shaped with the loop portion 252 of the device 200 shown in Figure 16. It should be apparent to others with ordinary skill in the art that a variety of net shapes and sizes can be utilized in the practice of this invention. The edge 206 is illustrated as the size of the net element 254 in relation to the loop 252 prior to the net element being woven on the loop. Further, as shown, the proximal portion of the net element 254 comprises a tail portion 290. As will be discussed, the tail portion 290 is used to secure the net element 254 to the wire.

Figures 16-18 show a device 200 according to another embodiment of the invention. As shown in Figure 16, the device 200 includes a retrieval net 250. The retrieval net 250 includes a wire forming a loop portion 252 and two adjacent leg portions 201, 202 and a net element 254 secured to the loop portion. The net element 254 is supported by the loop portion 252 by threading, or weaving, the wire through holes in the net element. As shown in Figure 16, a tether or anchor 257a disposed at the distal portion of the net element 254 anchors the net element to the loop portion 252 at a distal end of the loop portion.

The retrieval net 250 of device 200 is designed for movement between two

positions. Figure 16 shows the retrieval net 250 in a deployed position. Figures 17 and 18 are cross-sectional views of a distal portion of the device 200, showing the loop portion 252 of the retrieval net in a deployed position (Figure 17) and stored position within the tube 224 (Figure 18). As shown in Figure 18, the retrieval net is disposed within the tube 224 for deployment and retrieval through the tubular member lumen opening. By movement of the handle 218 relative to the body 214, the retrieval net 250 is movable between either the deployed or stored positions.

Referring again to Figures 16 and 17, the retrieval net 250 is illustrated in a deployed position and fully expanded outside of the tube 224 second end 228. The net element 254 may be constructed of any suitable light weight material, such as for example, nylon mesh string. The net element 254 has a centrally located object receiving pouch section 258. Further, as shown, the proximal portion of the net element 254 includes a tail portion 290.

As shown in Figures 16-18, the wire extends back toward the proximal end of the device 200 and forms two adjacent leg portions 201 and 202. The leg portions 201, 202 are secured to each other by two connections 204a, 204b. As shown, the leg portions 201, 202 are joined by two welds. However, the leg portions 201, 202 may be secured to each other by any suitable method known in the art, such as for example by crimping or twisting the portions together.

As shown in Figures 16-18, the tail portion 290 of the net element 254 is routed between the connections 204a, 204b to secure the proximal portion of the net element to the wire. As such, the tail portion 290 of the net element 254 is secured, or pinched, within the opening 292 defined by the connections 204a, 204b and the two leg portions 201, 202. Securing the proximal portion of the net element 254 between the connections 204a, 204b reduces the cost and complexity of manufacturing the retrieval device. Further, no tether or anchor is used to secure the proximal portion of the net element, reducing the chance of the net element tearing at the tether connection point, or the tether or anchor itself ripping.

Further, as shown in Figures 17-18, the tail portion 290 of the net element 254 at

least partially surrounds the connection 204c of the leg portions 201, 202 to the cable 210. The tail portion 290 of the net element 254 provides a damping effect on the cable 210 movement toward the distal end 228 of the tube 224 when the handle 218 is activated. This also provides more control over the deployment of the net and cable 210 and controls the portion of the device that exits the opening of the tubular member 224 when the retrieval net is in the deployed position. The mesh of the tail portion 290 of the net element 254 also helps to center the leg portions 201, 202 of the wire and the cable 210 within the tubular member 224. The mesh of the tail portion 290 of the net element 254 also inhibits damage to the connections 204a, 204b, and 204c and the inside of the tubular member 224.

In an exemplary operation using the device, the patient is intubated with an endoscope. The device 10 is inserted through an instrument channel of the endoscope, either before or after intubation. The device is inserted with the retrieval net in a stored position. The surgeon or operator utilizing the optical features of the endoscope will identify the object for removal. After identification of the object, the surgeon or operator will move the handle with respect to the base to deploy the retrieval net into the deployed position. The surgeon or operator will manipulate the object into the receiving pouch by one of a variety of techniques, including the use of additional endoscopic tools. For example, the surgeon or operator may manipulate the snare over the top of the object and enclose the net, or manipulate the snare under the object and enclose the net. Further, the surgeon or operator may use the net as a scoop, relying on the lateral stability of the device. Once the object is within the pouch, the surgeon or operator may manipulate the handle with respect to the body to slightly close the net around the object. Figure 7 is a perspective view of a distal portion of the device illustrated in Figure 4, showing a food bolus captured within the net. In this position, the loop retains an expanded configuration with an object 80 retained within the pouch section 58. The surgeon or operator may further close the loop to secure or hold the food bolus. The endoscope now may be removed from the patient with risk of loss of the food bolus greatly reduced as compared to prior art devices.

While several embodiments of the invention has been illustrated and described in considerable detail, the present invention is not to be considered limited to the precise construction disclosed. Various adaptations, modifications and uses of the invention may occur to those skilled in the arts to which the invention relates. It is the intention to cover all such adaptations, modifications and uses falling within the scope or spirit of the claims filed herewith.

We claim:

1. An endoscopic device for retrieving an object from within a human body, the device comprising:

a support assembly comprising a base and an elongated tubular member;

a transmitting assembly comprising a handle movable relative to the base, and a link having a first end fixed to the handle and a second end remote from the base, the link extending through at least a portion of the tubular member;

a wire defining a loop portion and two leg portions, wherein each leg portion is secured to the second end of the link by a first connection, and the two leg portions are secured to each other by at least a second connection;

a net element having a distal portion secured to the loop portion and a proximal portion; and

a means for securing the proximal portion of the net element adjacent the second connection;

wherein the loop portion is movable between an expanded position outside the tubular member and a collapsed position within the tubular member by action of the handle relative to the base.

2. The device of claim 1, wherein a proximal end of each leg portion is secured to the second end of the link by the first connection and the second connection is distal from the first connection.
3. The device of claim 1, wherein a tether attaches the proximal portion of the net element to a proximal side of the second connection.

4. The device of claim 3, wherein the second connection is a weld securing the two leg portions to each other.
5. The device of claim 1, wherein the two leg portions are secured to each other by the second connection and a third connection, each distal from the first connection with respect to the base.
6. The device of claim 5, wherein the proximal portion of the net element is routed between the second connection and the third connection.
7. The device of claim 6, wherein the second and third connections are welds securing the two leg portions of the wire to each other.
8. The device of claim 6, wherein the proximal portion of the net element is secured between the second connection, the third connection, and the two leg portions.
9. The device of claim 6, wherein the proximal portion of the net element at least partially surrounds the first connection to inhibit damage to the inside of the tubular member.
10. The device of claim 1, wherein bends in the loop portion promote expansion of the loop portion and prohibit collapse of the loop portion while retrieving the object from within the human body.
11. The device of claim 10, wherein segments of the loop portion between the bends form a polygonal shape.
12. The device of claim 1, wherein the wire further comprises a curved portion at a distal end of the loop portion forming a protruding tip that prohibits the collapse of the loop portion during use.
13. The device of claim 12, wherein the protruding tip includes a tip cap having an aperture and a tether secures the distal portion of the net element to the aperture in the tip cap.
14. The device of claim 1, wherein the wire further comprises a 360 degree curved portion at a distal end of the loop portion.

15. The device of claim 14, wherein a tether secures the distal portion of the net element to the 360 degree curved portion of the wire at the distal end of the loop portion.
16. The device of claim 1, wherein the motion transmitting link further comprises a tube attached to a cable by a swage connection.
17. The device of claim 16, wherein the cable is attached to the ends of the two leg portions of the wire by the first connection.
18. The device of claim 1, wherein a piece of heat shrink material at least partially surrounds the first connection to inhibit damage to the inside of the tubular member.
19. The device of claim 1, wherein the second end of the link is within the tubular member when the loop portion is in the expanded position.
20. An endoscopic device for retrieving an object from within a human body, the device comprising:
 - a support assembly comprising a base and an elongated tubular member;
 - a transmitting assembly comprising a handle movable relative to the base, and a link having a first end fixed to the handle and a second end remote from the base, the link extending through at least a portion of the tubular member;
 - a wire defining a loop portion and two leg portions, wherein each leg portion is secured to the second end of the link by a first connection, and the two leg portions are secured to each other by a second connection; and
 - a net element having a distal portion secured to the loop portion and a proximal portion secured relative to the second connection by a tether;wherein the loop portion is movable between an expanded position outside the tubular member and a collapsed position within the tubular member by action of the handle relative to the base.

21. The device of claim 20, wherein a proximal end of each leg portion is secured to the second end of the link by the first connection and the second connection is distal from the first connection.

22. The device of claim 20, wherein the tether is tied off at a location proximal to the second connection.

23. The device of claim 20, wherein the second connection is a weld.

24. The device of claim 20, wherein the tether is tied to a 360 degree curved portion of at least one leg portion.

25. An endoscopic device for retrieving an object from within a human body, the device comprising:

a support assembly comprising a base and an elongated tubular member;

a transmitting assembly comprising a handle movable relative to the base, and a link having a first end fixed to the handle and a second end remote from the base, the link extending through at least a portion of the tubular member;

a wire defining a loop portion and two leg portions, wherein each leg portion is secured to the second end of the link by a first connection, and the two leg portions are secured to each other by a second connection and a third connection; and

a net element having a distal portion secured to the loop portion and a proximal portion routed between the second and third connection;

wherein the loop portion is movable between an expanded position outside the tubular member and a collapsed position within the tubular member by action of the handle relative to the base.

26. The device of claim 25, wherein a proximal end of each leg portion is secured to the second end of the link by the first connection and the second and third connections are distal from the first connection.

27. The device of claim 25, wherein the second and third connections are welds securing the two leg portions of the wire to each other.
28. The device of claim 25, wherein the proximal portion of the net element is secured between the second connection, the third connection, and the two leg portions.
29. The device of claim 25, wherein the proximal portion of the net element at least partially surrounds the first connection to inhibit damage to the inside of the tubular member.
30. The device of claim 25, wherein the proximal portion of the net element extends beyond the first connection toward the base.
31. The device of claim 25, wherein the proximal portion of the net element has a tail.




Figure 1






Figure 2






Figure 5




Figure 6




Figure 7




Figure 10




Figure 9




Figure 8




Figure 14a




Figure 14b





Figure 15




Figure 16




Figure 17




Figure 18

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2008/066161

<p>A. CLASSIFICATION OF SUBJECT MATTER IPC(8) - A61B 17/00 (2008.04) USPC - 606/113 According to International Patent Classification (IPC) or to both national classification and IPC</p>																																									
<p>B. FIELDS SEARCHED</p> <p>Minimum documentation searched (classification system followed by classification symbols) IPC(8) - A61B 17/00 (2008.04) USPC - 606/113, 114, 119</p> <p>Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched</p> <p>Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) MicroPatent, DialogPro, IP.com</p>																																									
<p>C. DOCUMENTS CONSIDERED TO BE RELEVANT</p> <table border="1"> <thead> <tr> <th>Category*</th> <th>Citation of document, with indication, where appropriate, of the relevant passages</th> <th>Relevant to claim No.</th> </tr> </thead> <tbody> <tr> <td>Y</td> <td>US 2005/0267489 A1 (SECRET et al) 01 December 2005 (01.12.2005) entire document</td> <td>1-31</td> </tr> <tr> <td>Y</td> <td>US 5,906,621 A (SECRET et al) 25 May 1999 (25.05.1999) entire document</td> <td>4, 7, 16-17, 23, 27</td> </tr> <tr> <td>Y</td> <td>US 2003/0004538 A1 (SECRET et al) 02 January 2003 (02.01.2003) entire document</td> <td>18</td> </tr> <tr> <td>A</td> <td>US 460,940 A (BAUGH) 13 October 1891 (13.10.1891) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,098,441 A (WECHLER) 24 March 1992 (24.03.1992) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,147,371 A (WASHINGTON, deceased et al) 15 September 1992 (15.09.1992) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,190,542 A (NAKAO et al) 02 March 1993 (02.03.1993) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,192,286 A (PHAN et al) 09 March 1993 (09.03.1993) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,480,404 A (KAMMERER et al) 02 June 1996 (02.06.1996) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,496,330 A (BATES) 05 March 1996 (05.03.1996) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 5,643,283 A (YOUNKER) 01 July 1997 (01.07.1997) entire document</td> <td>1-31</td> </tr> <tr> <td>A</td> <td>US 6,500,182 B2 (FOSTER) 31 December 2002 (31.12.2002) entire document</td> <td>1-31</td> </tr> </tbody> </table>			Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	Y	US 2005/0267489 A1 (SECRET et al) 01 December 2005 (01.12.2005) entire document	1-31	Y	US 5,906,621 A (SECRET et al) 25 May 1999 (25.05.1999) entire document	4, 7, 16-17, 23, 27	Y	US 2003/0004538 A1 (SECRET et al) 02 January 2003 (02.01.2003) entire document	18	A	US 460,940 A (BAUGH) 13 October 1891 (13.10.1891) entire document	1-31	A	US 5,098,441 A (WECHLER) 24 March 1992 (24.03.1992) entire document	1-31	A	US 5,147,371 A (WASHINGTON, deceased et al) 15 September 1992 (15.09.1992) entire document	1-31	A	US 5,190,542 A (NAKAO et al) 02 March 1993 (02.03.1993) entire document	1-31	A	US 5,192,286 A (PHAN et al) 09 March 1993 (09.03.1993) entire document	1-31	A	US 5,480,404 A (KAMMERER et al) 02 June 1996 (02.06.1996) entire document	1-31	A	US 5,496,330 A (BATES) 05 March 1996 (05.03.1996) entire document	1-31	A	US 5,643,283 A (YOUNKER) 01 July 1997 (01.07.1997) entire document	1-31	A	US 6,500,182 B2 (FOSTER) 31 December 2002 (31.12.2002) entire document	1-31
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.																																							
Y	US 2005/0267489 A1 (SECRET et al) 01 December 2005 (01.12.2005) entire document	1-31																																							
Y	US 5,906,621 A (SECRET et al) 25 May 1999 (25.05.1999) entire document	4, 7, 16-17, 23, 27																																							
Y	US 2003/0004538 A1 (SECRET et al) 02 January 2003 (02.01.2003) entire document	18																																							
A	US 460,940 A (BAUGH) 13 October 1891 (13.10.1891) entire document	1-31																																							
A	US 5,098,441 A (WECHLER) 24 March 1992 (24.03.1992) entire document	1-31																																							
A	US 5,147,371 A (WASHINGTON, deceased et al) 15 September 1992 (15.09.1992) entire document	1-31																																							
A	US 5,190,542 A (NAKAO et al) 02 March 1993 (02.03.1993) entire document	1-31																																							
A	US 5,192,286 A (PHAN et al) 09 March 1993 (09.03.1993) entire document	1-31																																							
A	US 5,480,404 A (KAMMERER et al) 02 June 1996 (02.06.1996) entire document	1-31																																							
A	US 5,496,330 A (BATES) 05 March 1996 (05.03.1996) entire document	1-31																																							
A	US 5,643,283 A (YOUNKER) 01 July 1997 (01.07.1997) entire document	1-31																																							
A	US 6,500,182 B2 (FOSTER) 31 December 2002 (31.12.2002) entire document	1-31																																							
<p><input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/></p>																																									
<p>* Special categories of cited documents:</p> <table border="0"> <tr> <td style="vertical-align: top;"> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </td> <td style="vertical-align: top;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p> </td> </tr> </table>			<p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>																																					
<p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&" document member of the same patent family</p>																																								
<p>Date of the actual completion of the international search</p> <p>14 September 2008</p>		<p>Date of mailing of the international search report</p> <p>22 SEP 2008</p>																																							
<p>Name and mailing address of the ISA/US</p> <p>Mail Stop PCT, Attn: ISA/US, Commissioner for Patents P.O. Box 1450, Alexandria, Virginia 22313-1450 Facsimile No. 571-273-3201</p>		<p>Authorized officer:</p> <p>Blaine R. Copenheaver</p> <p>PCT Helpdesk: 571-272-4300 PCT OSP: 571-272-7774</p>																																							