





US 20180364614A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2018/0364614 A1**
Aruga et al. (43) **Pub. Date: Dec. 20, 2018**(54) **IMAGE FORMING APPARATUS HAVING
OPTICAL PRINT HEAD****Publication Classification**(71) Applicant: **CANON KABUSHIKI KAISHA,**
Tokyo (JP)(51) **Int. Cl.**
G03G 15/04 (2006.01)
G03G 15/043 (2006.01)
G03G 21/00 (2006.01)
G03G 21/16 (2006.01)(72) Inventors: **Daisuke Aruga**, Abiko-shi (JP);
Yasuaki Otaguro, Abiko-shi (JP); **Yuta Okada**,
Moriya-shi (JP); **Hitoshi Iwai**, Abiko-shi (JP);
Shinichiro Hosoi, Tokyo (JP); **Yuichiro Imai**, Tokyo (JP);
Toshiki Momoka, Tokyo (JP); **Yoshitaka Otsubo**, Tokyo (JP);
Saimon Gokyu, Tokyo (JP); **Takehiro Ishidate**, Tokyo (JP)(52) **U.S. Cl.**
CPC ... **G03G 15/04054** (2013.01); **G03G 15/0435**
(2013.01); **G03G 21/1671** (2013.01); **G03G 21/1666** (2013.01);
G03G 21/169 (2013.01); **G03G 21/0029** (2013.01)(21) Appl. No.: **16/001,409**(22) Filed: **Jun. 6, 2018**(30) **Foreign Application Priority Data**

Jun. 16, 2017 (JP) 2017-119004


(57) **ABSTRACT**

Provided are a first seating face and a second seating face, to which a lower side of a holding member of an optical print head being moved from an exposure position toward a retracted position by a movement mechanism strikes in the direction of movement thereof. A light emission face of a lens array of the holding member that has abutted the first seating face and second seating face is thereby positioned on a movement path of a rubbing portion provided on a cleaning member that is inserted from an opening.



DIRECTION TOWARD NEAR SIDE OF
PLANE OF DRAWING FROM FAR SIDE: FRONT
DIRECTION TOWARD FAR SIDE OF
PLANE OF DRAWING FROM NEAR SIDE: REAR

FIG. 1



DIRECTION TOWARD NEAR SIDE OF
PLANE OF DRAWING FROM FAR SIDE: FRONT
DIRECTION TOWARD FAR SIDE OF
PLANE OF DRAWING FROM NEAR SIDE: REAR

FIG. 2A




FIG. 2B




FIG. 4




FIG. 5A




FIG. 5B1




FIG. 5B2




FIG. 5C1




FIG. 5C2




FIG. 6A




FIG. 6B




FIG. 7A1




FIG. 7A2




FIG. 7B1




FIG. 7B2




FIG. 8




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A1




FIG. 15A2




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A




FIG. 18B




FIG. 18C




FIG. 18D




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 22A




FIG. 22B




FIG. 22C




FIG. 22D




FIG. 23A




FIG. 23B




FIG. 23C




FIG. 24A




FIG. 24B




FIG. 25A




FIG. 25B




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28




FIG. 29A1




FIG. 29A2




FIG. 29B




IMAGE FORMING APPARATUS HAVING OPTICAL PRINT HEAD

BACKGROUND OF THE INVENTION

Field of the Invention

[0001] The present invention relates to an image forming apparatus where a light emission faces of lenses that an optical print head has can be easily cleaned.

Description of the Related Art

[0002] Image forming apparatuses such as printers, copying machines, and so forth, have an optical print head that has multiple light-emitting elements for exposing a photosensitive drum. Some optical print heads use light-emitting diodes (LEDs) or organic electroluminescence (EL) devices or the like, which are examples of light-emitting elements. There are known arrangements where multiple such light-emitting elements are arrayed in one row or two staggered rows, for example, in the rotational axis direction of the photosensitive drum. Optical print heads also have multiple lenses for condensing light emitted from the multiple light-emitting elements onto the photosensitive drum. The multiple lenses are disposed facing the surface of the photosensitive drum, having been arrayed in the direction of array of the light-emitting elements, between the multiple light-emitting elements and the photosensitive drum. Light emitted from the multiple light-emitting elements is condensed on the surface of the photosensitive drum through the lenses, and an electrostatic latent image is formed on the photosensitive drum.

[0003] The photosensitive drum is a consumable item, and accordingly is periodically replaced. A worker performing the work of replacing a photosensitive drum or the like can perform maintenance of the image forming apparatus by replacing the replacement unit containing the photosensitive drum. The replacement unit has a configuration where it is detachably mountable to a main body of the image forming apparatus, by being extracted from and inserted to the apparatus main body from the side face of the image forming apparatus by sliding movement. The clearance between the lenses and the surface of the photosensitive drum is extremely narrow at an exposure position of the optical print head for when exposing the photosensitive drum (a position near to and facing the surface of the drum). Accordingly, the optical print head needs to be retracted from the exposure position when replacing the replacement unit, lest the optical print head and photosensitive drum or the like come into contact and the surface of the photosensitive drum and the lenses be damaged. Accordingly, a mechanism needs to be provided to the image forming apparatus where the optical print head is reciprocally moved between the exposure position and a retracted position where the optical print head is further distanced from the replacement unit than the exposure position, in order to mount/detach the replacement unit.

[0004] Now, an exposure unit such as an optical print head may be provided to the image forming apparatus between a charger and a developing unit. Maximally reducing the distances among the photosensitive drum, optical print head, charger, developing unit, and so forth, is an effective way to realize reduction in size of the apparatus. Accordingly, there has been a problem where the light emission faces of lenses

that the optical print head has are contaminated by toner falling from the photosensitive drum and developing unit. Contamination of the light emission faces of lenses can partially shield light emitted from light-emitting elements, and is a factor leading to deterioration in image quality of output images. A cleaning unit has been proposed to prevent such contamination of light emission faces of the optical print head in an optical print head that would lead to deterioration in image quality. One example of a cleaning unit is that described in Japanese Patent Laid-Open No. 2010-230954, for example.

[0005] An image forming unit **11** described in Japanese Patent Laid-Open No. 2010-230954 includes housing **19** as an example of a casing that holds a photosensitive drum **12**, a charger **13**, a light-emitting diode (LED) print head (LPH) **14**, and a developing unit **15**. A cleaning member **50** is inserted through an insertion opening **60** formed in the housing **19**, whereby a blade **52** provided to the cleaning member **50** rubs a light emission face of a rod lens array **43** that the LPH has. A structure is also disclosed where a protective member **53**, provided to the opposite side of the cleaning member **50** from the side where the blade **52** is provided, rubs the surface of the photosensitive drum **12**. The light emission face of the rod lens array **43** is cleaned by the blade **52** by operating the cleaning member **50**, by inserting into and extracting from the insertion opening **60**. Japanese Patent Laid-Open No. 2010-230954 also discloses a protruding guide portion **54** formed over the longitudinal direction of the cleaning member **50** fitting into a groove formed in the insertion opening **60**, thereby setting the direction of movement of the cleaning member to be in the X direction, at the time of passing the cleaning member **50** through the insertion opening **60** formed in the housing **19**. According to this structure, cases where the cleaning member **50** becomes caught on the edge portion of the photosensitive drum **12** or the like, for example, can be reduced, and smooth operation can be realized.

[0006] However, the configuration illustrated in Japanese Patent Laid-Open No. 2010-230954 is far from an ideal configuration regarding achieving a longer lifespan of the photosensitive drum **12**, since the protective member **53** rubs against the surface of the photosensitive drum **12** when the cleaning member **50** is operated. Now, an arrangement can be conceived where the image forming apparatus is provided with a configuration that retracts the LPH **14** from the photosensitive drum **12** to a position where the cleaning member **50** does not come into contact with the photosensitive drum **12** even when the cleaning member **50** is operated. One method to realize this configuration is to provide a movement mechanism that moves the LPH **14** so that spacing, formed between the photosensitive drum **12** and the light emission face of the rod lens array **43** at an exposure position where light-emitting elements that the LPH **14** has expose the photosensitive drum **12**, is increased.

[0007] According to this movement mechanism, in a case where the cleaning member **50** is inserted from the insertion opening **60** in a state where the LPH **14** is distanced from the photosensitive drum **12**, there is a possibility that the blade **52** will not sufficiently rub the light emission face if the light emission face of the rod lens array **43** is below the movement path of the blade **52**.

SUMMARY OF THE INVENTION

[0008] An image forming apparatus according to the present invention includes: a photosensitive drum configured to be capable of rotating as to an apparatus main body; an optical print head having a light emission face from which light to expose the photosensitive drum is emitted; a movement mechanism configured to move the optical print head from an exposure position, where the light emission face exposes the photosensitive drum, further away from the photosensitive drum than the exposure position; an insertion portion from which a rod-shaped cleaning member that rubs and cleans the light emission face is inserted by a worker from a side face of the apparatus main body, in the longitudinal direction of the optical print head; and a striking portion configured to be struck by the optical print head being moved from the exposure position by the movement mechanism, in the direction of the movement, and to stop movement of the optical print head so that the position of the light emission face is on a movement path of the cleaning member that is inserted through the insertion portion and is moved.

[0009] An image forming apparatus according to the present embodiment includes: a photosensitive drum configured to be capable of rotating as to an apparatus main body; an optical print head having a light emission face from which light to expose the photosensitive drum is emitted; a sliding portion configured to move by sliding in the longitudinal direction of the optical print head; a link portion of which one end side is pivotably attached to the sliding portion and an other end side is pivotably attached to the optical print head, and that is configured to pivot in conjunction with the sliding portion moving by sliding, to move the optical print head from an exposure position, where the light emission face exposes the photosensitive drum, further away from the photosensitive drum than the exposure position; an insertion portion from which a rod-shaped cleaning member that rubs and cleans the light emission face is inserted by a worker from a side face of the apparatus main body in the longitudinal direction; and a striking portion configured to stop sliding movement of the sliding portion and pivoting of the link portion, by the sliding portion moving by sliding striking in the direction of sliding movement. The light emission face is situated on a movement path of the cleaning member that is inserted through the insertion portion and is moved, in a state where the sliding portion has struck the striking portion.

[0010] An image forming apparatus according to the present invention includes: a photosensitive drum configured to be capable of rotating as to an apparatus main body; an optical print head having a light emission face from which light to expose the photosensitive drum is emitted; a sliding portion configured to move by sliding in the longitudinal direction of the optical print head; a link portion of which one end side is pivotably attached to the sliding portion and an other end side is pivotably attached to the optical print head, and that is configured to pivot in conjunction with the sliding portion moving by sliding, to move the optical print head from an exposure position, where the light emission face exposes the photosensitive drum, further away from the photosensitive drum than the exposure position; a guide portion from which a rod-shaped cleaning member that rubs and cleans the light emission face is inserted by a worker from a side face of the apparatus main body in the longitudinal direction, and that guides movement of the cleaning

member in the longitudinal direction; and a striking portion configured to stop the pivoting of the link portion and the sliding movement of the sliding portion, by the pivoting link portion striking in the direction of pivoting. The light emission face is situated on a movement path of the cleaning member that is inserted through the insertion portion and is moved, in a state where the link portion has struck the striking portion.

[0011] Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] FIG. 1 is a schematic cross-sectional diagram of an image forming apparatus.

[0013] FIGS. 2A and 2B are perspective views of around drum units in the image forming apparatus.

[0014] FIG. 3 is a schematic perspective view of an exposing unit.

[0015] FIG. 4 is a cross-sectional view of an optical print head, taken along a direction perpendicular to a rotational axis of an optical print head.

[0016] FIGS. 5A through 5C2 are schematic diagrams for describing a circuit board, LED chips, and lens array of an optical print head.

[0017] FIGS. 6A and 6B are side views of an optical print head.

[0018] FIGS. 7A1 through 7B2 are diagrams illustrating a state where an optical print head is in contact with a drum unit, and a retracted state.

[0019] FIG. 8 is a perspective view of a bushing attached to the rear side of a drum unit.

[0020] FIGS. 9A through 9C are perspective views of a first support portion and a third support portion.

[0021] FIGS. 10A through 10C are perspective views of a second support portion, a rear-side plate, and an exposing unit attached to the second support portion.

[0022] FIGS. 11A and 11B are perspective views of a movement mechanism, with the first support portion omitted from illustration.

[0023] FIGS. 12A and 12B are side views of a X-type first link mechanism.

[0024] FIGS. 13A and 13B are schematic perspective views of an exposing unit.

[0025] FIGS. 14A and 14B are diagrams describing a movement mechanism.

[0026] FIGS. 15A1 through 15B are diagrams describing an X-type movement mechanism.

[0027] FIGS. 16A and 16B are diagrams describing a movement mechanism using a cam mechanism.

[0028] FIGS. 17A through 17C are perspective views of a cover.

[0029] FIGS. 18A through 18D are perspective views of a cover, for description of operations when the cover is closed.

[0030] FIGS. 19A through 19D are perspective views of a cover, for description of operations when the cover is closed.

[0031] FIGS. 20A through 20D are perspective views of a cover, for description of operations when the cover is opened.

[0032] FIGS. 21A through 21D are side views of a cover, for description of operations when the cover is opened.

[0033] FIGS. 22A through 22D are perspective views for describing the structure of both ends of a holding member.

[0034] FIGS. 23A through 23C are side views for describing the structure of the other end of the holding member.

[0035] FIGS. 24A and 24B are diagrams for describing a cleaning member and a state in which the cleaning member is inserted into an opening.

[0036] FIGS. 25A and 25B are diagrams for describing the structure of a cleaning member.

[0037] FIG. 26 is a perspective view of a lens attaching portion of the holding member.

[0038] FIGS. 27A and 27B are diagrams for describing the way in which movement of the cleaning member is restricted by the opening and holding member.

[0039] FIG. 28 is a diagram for describing the positional relation of an abutting pin and lens array.

[0040] FIGS. 29A1 through 29B are diagrams for describing a striking portion (stopping mechanism) according to a second embodiment and a third embodiment.

DESCRIPTION OF THE EMBODIMENTS

First Embodiment

Image Forming Apparatus

[0041] First, a schematic configuration of an image forming apparatus 1 will be described. FIG. 1 is a schematic cross-sectional view of the image forming apparatus 1. Although the image forming apparatus 1 illustrated in FIG. 1 is a color printer (small function printer (SFP)) that does not have a reader, an embodiment may be a copying machine that has a reader. Also, an embodiment is not restricted to a color image forming apparatus having multiple photosensitive drums 103 as illustrated in FIG. 1, and may be a color image forming apparatus having one photosensitive drum 103 or an image forming apparatus that forms monochromatic images.

[0042] The image forming apparatus 1 illustrated in FIG. 1 has four image forming units 102Y, 102M, 102C, and 102K (hereinafter also collectively referred to simply as “image forming unit 102”) that form toner images of the yellow, magenta, cyan, and black colors. The image forming units 102Y, 102M, 102C, and 102K respectively have a photosensitive drum 103Y, 103M, 103C, and 103K (hereinafter also collectively referred to simply as “photosensitive drum 103”). The image forming units 102Y, 102M, 102C, and 102K also respectively have a charger 104Y, 104M, 104C, and 104K (hereinafter also collectively referred to simply as “charger 104”) for charging the photosensitive drums 103Y, 103M, 103C, and 103K, respectively. The image forming units 102Y, 102M, 102C, and 102K further respectively have a light-emitting diode (LED) exposing unit 500Y, 500M, 500C, and 500K (hereinafter also collectively referred to simply as “LED exposing unit 500”) serving as an exposure light source that emits light to expose the photosensitive drums 103Y, 103M, 103C, and 103K. Moreover, the image forming units 102Y, 102M, 102C, and 102K respectively have a developing unit 106Y, 106M, 106C, and 106K (hereinafter also collectively referred to simply as “developing unit 106”) that develops electrostatic latent images on the photosensitive drum 103 by toner, thereby developing toner images of the respective colors on the photosensitive drums 103. The Y, M, C, and K appended to the reference numerals indicate the color of the toner.

[0043] The image forming apparatus 1 is provided with an intermediate transfer belt 107 onto which toner images

formed on the photosensitive drums 103 are transferred, and primary transfer roller 108 (Y, M, C, K) that sequentially transfer the toner images formed on the photosensitive drums 103 of the image forming units 102 onto the intermediate transfer belt 107. The image forming apparatus 1 further is provided with a secondary transfer roller 109 that transfers the toner image on the intermediate transfer belt 107 onto a recording sheet P conveyed from a sheet feed unit 101, and a fixing unit 100 that fixes the secondary-transferred image onto the recording sheet P.

Drum Unit

[0044] Next, drum units 518 (Y, M, C, K), and developing units 641 (Y, M, C, K), which are an example of replacement units detachably mounted to the image forming apparatus 1 according to the present embodiment, will be described. FIG. 2A is a schematic perspective view around the drum units 518 and developing units 641 that the image forming apparatus 1 has. FIG. 2B is a diagram illustrating a drum unit 518 in a state partially inserted into the image forming apparatus 1 from the outer side of the apparatus main body. [0045] The image forming apparatus 1 has a front-side plate 642 and a rear-side plate 643 that are formed from sheet metal, as illustrated in FIG. 2A. The front-side plate 642 is a side wall provided to the front side of the image forming apparatus 1. The rear-side plate 643 is a side wall provided to the rear side of the image forming apparatus 1. The front-side plate 642 and rear-side plate 643 are disposed facing each other as illustrated in FIG. 2A, with sheet metal serving as beams that are omitted from illustration crossing therebetween. The front-side plate 642, rear-side plate 643, and unshown beams make up part of a frame of the image forming apparatus 1.

[0046] Openings are formed on the front-side plate 642, through which the drum units 518 and developing units 641 can be inserted and extracted from the front side of the image forming apparatus 1. The drum units 518 and developing units 641 are mounted through openings to predetermined positions in the main body of the image forming apparatus 1 (mounting positions). The image forming apparatus 1 also has covers 558 (Y, M, C, K) that cover the front side of the drum units 518 and developing units 641 mounted to the mounting positions. The covers 558 have one end thereof fixed integrally to the main body of the image forming apparatus 1 by a hinge, and are capable of pivoting as to the main body of the image forming apparatus 1 on the hinge. Unit replacement work is completed by a worker who performs maintenance opening a cover 558 and extracting a drum unit 518 or developing unit 641 within the main body, inserting a new drum unit 518 or developing unit 641, and closing the cover 558. The covers 558 will be described in detail later.

[0047] In the following description, the front-side plate 642 side is defined as the front side, and the rear-side plate 643 side as the rear side, as illustrated in FIGS. 2A and 2B. The side where the photosensitive drum 103Y that forms electrostatic latent images relating to yellow toner images is disposed is defined as the right side, with the photosensitive drum 103K that forms electrostatic latent images relating to black toner images as a reference. The side where the photosensitive drum 103K that forms electrostatic latent images relating to black toner images is disposed is defined as the left side, with the photosensitive drum 103Y that forms electrostatic latent images relating to yellow toner

images as a reference. Further, a direction that is perpendicular to the front-and-rear directions and left-and-right directions defined here, and is upward in the vertical direction is defined as the upward direction, and a direction that is perpendicular to the front-and-rear directions and left-and-right directions defined here, and is downward in the vertical direction is defined as the downward direction. The defined front direction, rear direction, right direction, left direction, upward direction, and downward direction, are illustrated in FIGS. 2A and 2B. The term “one end side of the photosensitive drum 103 in the rotational axis direction” as used in the present specification means the front side as defined here, and “other end side” means the rear side as defined here. The one end side and other end side in the front-and-rear direction here also correspond to the front side and rear side defined here. The one end side in the left-and-right direction means the right side as defined here, and the other end side means the left side as defined here.

[0048] Drum units 518 are attached to the image forming apparatus 1 according to the present embodiment. The drum units 518 are cartridges that are replaced. The drum units 518 according to the present embodiment have photosensitive drums 103 rotatably supported as to the casing of the drum units 518. The drum units 518 each have a photosensitive drum 103, charger 104, and cleaning device that is omitted from illustration. When the lifespan of a photosensitive drum 103 is expended due to wear by cleaning by the cleaning device for example, a worker who performs maintenance extracts the drum unit 518 from the apparatus main body, and replaces the photosensitive drum 103, as illustrated in FIG. 2B. Note that a configuration may be made where the drum unit 518 includes neither the charger 104 nor cleaning device, and only includes the photosensitive drum 103.

[0049] The developing units 641, which are separate from the drum units 518, are attached to the image forming apparatus 1 according to the present embodiment. The developing units 641 include the developing units 106 illustrated in FIG. 1. Each developing unit 106 is provided with a developing sleeve serving as a developing agent bearing member that bears a developing agent. Each developing unit 641 is provided with multiple gears for rotating a screw that agitates the toner and a carrier. When these gears deteriorate due to age or the like, a worker performing maintenance extracts the developing unit 641 from the apparatus main body of the image forming apparatus 1 and replaces it. The developing unit 641 according to the present embodiment is a cartridge where a developing unit 106 having a developing sleeve, and a toner container in which a screw is provided, have been integrated. An embodiment of the drum unit 518 and developing unit 641 may be a process cartridge where the drum unit 518 and developing unit 641 are integrated.

Image Forming Process

[0050] Next, an image forming process will be described. A later-described optical print head 105Y exposes the surface of the photosensitive drum 103Y that has been charged by the charger 104Y. Accordingly, an electrostatic latent image is formed on the photosensitive drum 103Y. Next, the developing unit 106Y develops the electrostatic latent image formed on the photosensitive drum 103Y by yellow toner. The yellow toner image developed on the surface of the photosensitive drum 103Y is transferred onto the interme-

mediate transfer belt 107 by the primary transfer roller 108Y at a primary transfer position Ty. Magenta, cyan, and black toner images are also transferred onto the intermediate transfer belt 107 by the same image forming process.

[0051] The toner images of each color transferred onto the intermediate transfer belt 107 are conveyed to a secondary transfer position T2 by the intermediate transfer belt 107. Transfer bias for transferring the toner images onto a recording sheet P is applied to the secondary transfer roller 109 disposed at the secondary transfer position T2. The toner images conveyed to the secondary transfer position T2 are transferred onto a recording sheet P conveyed from the sheet feed unit 101 by the transfer bias of the secondary transfer roller 109. The recording sheet P onto which the toner images have been transferred is conveyed to the fixing unit 100. The fixing unit 100 fixes the toner images onto the recording sheet P by heat and pressure. The recording sheet P subjected to fixing processing by the fixing unit 100 is discharged to a sheet discharge unit 111.

Exposing Unit

[0052] The exposing unit 500 including the optical print head 105 will be described. FIG. 3 is a schematic perspective view of the exposing unit 500 that the image forming apparatus 1 according to the present embodiment has. FIG. 4 is a schematic cross-sectional diagram where the exposing unit 500 illustrated in FIG. 3, and the photosensitive drum 103 disposed to the upper side of the exposing unit 500, have been cut away on a plane perpendicular to the rotational axis direction of the photosensitive drum 103. The exposing unit 500 has the optical print head 105 and a movement mechanism 640.

[0053] The optical print head 105 is provided with a holding member 505 that holds a lens array 506 (lenses) and circuit board 502, an abutting pin 514, and an abutting pin 515. The abutting pin 514 protrudes to the drum unit 518 side at one end side (front side) of the holding member 505 in the rotational axis direction of the photosensitive drum 103, which will be described in detail later. The abutting pin 515 also protrudes to the drum unit 518 side, at another end side (rear side) of the holding member 505 in the rotational axis direction of the photosensitive drum 103. The movement mechanism 640 has a first link mechanism 861, a second link mechanism 862, a sliding portion 525, a first support portion 527, a second support portion 528, and a third support portion 526 as an example of a slide supporting member. The first link mechanism 861 includes a link member 651 and link member 653, and the second link mechanism 862 includes a link member 652 and a link member 654. Although the abutting pin 514 and abutting pin 515 are described as being cylindrical pins in the present embodiment, the shape thereof is not restricted to being cylindrical, and may be polygonal posts, or conical shapes where the diameter is tapered toward the tip.

[0054] First, the holding member 505 will be described. The holding member 505 is a holder that holds the later-described circuit board 502, lens array 506, abutting pin 514, and abutting pin 515. As one example in the present embodiment, the length of the abutting pin 514 protruding from the upper face of the holding member 505 is 7 mm, the length of the abutting pin 515 protruding from the upper face of the holding member 505 is 11 mm, the length of the abutting pin 514 protruding from the lower face of the holding member 505 is 22 mm, and the length of the abutting pin 515

protruding from the lower face of the holding member 505 is 22 mm. The holding member 505 is provided with lens attaching portions 701 where the lens array 506 is attached, and circuit board attaching portions 702 where the circuit board 502 is attached, as illustrated in FIG. 4. The holding member 505 also has spring attaching portion 661, spring attaching portion 662, pin attaching portion 632, and pin attaching portion 633, which will be described later with reference to FIGS. 22A through 22D. The holding member 505 according to the present embodiment has the lens attaching portion 701, circuit board attaching portion 702, spring attaching portion 661, spring attaching portion 662, pin attaching portion 632, and pin attaching portion 633. The holding member 505 is a molded resin article, where the lens attaching portion 701, circuit board attaching portion 702, spring attaching portion 661, and spring attaching portion 662, have been integrally formed by injection molding. Note that the material of the holding member 505 is not restricted to resin, and may be metal or the like, for example.

[0055] The spring attaching portion 661 to which the link member 651 is attached is provided between the lens array 506 and the pin attaching portion 632 in the front-and-rear direction, as illustrated in FIG. 3. Also, the spring attaching portion 662 to which the link member 652 is attached is provided between the lens array 506 and the pin attaching portion 633 in the front-and-rear direction. That is to say, the holding member 505 is supported by the link member 651 between the lens array 506 and abutting pin 514 in the front-and-rear direction, and is supported by the link member 652 between the lens array 506 and abutting pin 515 in the front-and-rear direction, when the optical print head 105 moves between the exposure position and the retracted position. Portions where biasing force is applied to the holding member 505 by the link member 651 and link member 652 do not overlap the lens array 506 in the vertical direction, so warping of the lens array 506 due to this biasing force is reduced.

[0056] The lens attaching portion 701 has a first inner wall face 507 that extends in the longitudinal direction of the holding member 505, and a second inner wall face 508 that faces the first inner wall face 507 and also extends in the longitudinal direction of the holding member 505. The lens array 506 is inserted between the first inner wall face 507 and the second inner wall face 508 when assembling the optical print head 105. Adhesive agent is coated between the side face of the lens array 506 and the lens attaching portion 701, thereby fixing the lens array 506 to the holding member 505.

[0057] The circuit board attaching portion 702 has a cross-sectional open-box shape, and has a third inner wall face 900 extending in the longitudinal direction of the holding member 505, and a fourth inner wall face 901 that faces the third inner wall face 900 and extends in the longitudinal direction of the holding member 505, as illustrated in FIG. 4. A gap 910 into which the circuit board 502 is inserted is formed between the third inner wall face 900 and fourth inner wall face 901. The circuit board attaching portion 702 also includes circuit board abutting portions 911 where the circuit board 502 abuts. The circuit board 502 is inserted from the gap 910 when assembling the optical print head 105, and pressed as far as the circuit board abutting portions 911. Adhesive agent is coated on the boundary portion between the gap 910 side of the circuit board 502 and the third inner wall face 900 and fourth inner wall face

901 in a state where the circuit board 502 is abutted against the circuit board abutting portions 911, thereby fixing the circuit board 502 to the holding member 505. The exposing unit 500 is disposed on the lower side in the vertical direction from the rotational axis of the photosensitive drum 103, and LEDs 503 that the optical print head 105 has expose the photosensitive drum 103 from below.

[0058] Next, the circuit board 502 held by the holding member 505 will be described. FIG. 5A is a schematic perspective diagram of the circuit board 502. FIG. 5B1 illustrates an array of multiple LEDs 503 provided to the circuit board 502, and FIG. 5B2 is an enlarged view of FIG. 5B1.

[0059] LED chips 639 are mounted on the circuit board 502. The LED chips 639 are mounted on one face of the circuit board 502, while a connector 504 is provided to the rear face side, as illustrated in FIG. 5A. The circuit board 502 is provided with wiring to supply signals to the LED chips 639. One end of a flexible flat cable (FFC) that is omitted from illustration is connected to the connector 504. A circuit board is provided to the main unit of the image forming apparatus 1. The circuit board has a control unit and connector. The other end of the FFC is connected to this connector. Control signals are input to the circuit board 502 from the control unit of the main body of the image forming apparatus 1 via the FFC and connector 504. The LED chips 639 are driven by the control signals input to the circuit board 502.

[0060] The LED chips 639 mounted on the circuit board 502 will be described in further detail. Multiple (29) LED chips 639-1 through 639-29, on which multiple LEDs 503 are arrayed, are arrayed on one face of the circuit board 502, as illustrated in FIGS. 5B1 and 5B2. Each of the LED chips 639-1 through 639-29 has 516 LEDs (light-emitting elements) arrayed in a single row in the longitudinal direction thereof. The center-to-center distance k2 between LEDs adjacent in the longitudinal direction in the LED chips 639 corresponds to the resolution of the image forming apparatus 1. The resolution of the image forming apparatus 1 according to the present embodiment is 1200 dpi, so the LEDs are arrayed in a single row so that the center-to-center distance k2 between adjacent LEDs in the longitudinal direction of the LED chips 639-1 through 639-29 is 21.16 μm . Accordingly, the range of exposure of the optical print head 105 according to the present embodiment is 316 mm. The photosensitive layer of the photosensitive drum 103 is formed 316 mm or wider. The long side of an A4-size recording sheet and the short side of an A3-size recording sheet are 297 mm, so the optical print head 105 according to the present embodiment has an exposing range capable of forming images on A4-size recording sheets and A3-size recording sheets.

[0061] The LED chips 639-1 through 639-29 are alternately arrayed to form two rows in the rotational axis direction of the photosensitive drum 103. That is to say, odd-numbered LED chips 639-1, 639-3, and so on through 639-29, are arrayed on one line in the longitudinal direction of the circuit board 502 from the left, and even-numbered LED chips 639-2, 639-4, and so on through 639-28, are arrayed on one line in the longitudinal direction of the circuit board 502, as illustrated in FIG. 5B1. Arraying the LED chips 639 in this way enables the center-to-center distance k1 between the LEDs disposed on one end of one LED chip 639 and the other end of another LED chip 639 among

different adjacent LED chips 639 to be equal to the center-to-center distance k_2 of LEDs on the same LED chip 639, in the longitudinal direction of the LED chips 639, as illustrated in FIG. 5B2.

[0062] An example where the exposing light source is configured using LEDs is described in the present embodiment. However, organic electroluminescence (EL) devices may be used instead of the exposing light source.

[0063] Next, the lens array 506 will be described. FIG. 5C1 is a schematic diagram viewing the lens array 506 from the photosensitive drum 103 side. FIG. 5C2 is a schematic perspective view of the lens array 506. These multiple lenses are arrayed in two rows following the direction of array of the multiple LEDs 503, as illustrated in FIG. 5C1. The lenses are disposed in a staggered manner such that each lens in one row comes into contact with two lenses in the other row that are adjacent in the direction of array of the lenses. The lenses are cylindrical glass rod lenses. Note that the material of the lenses is not restricted to glass, and that plastic may be used. The shape of the lenses is not restricted to a cylindrical shape either, and may be polygonal posts such as hexagonal posts or the like, for example.

[0064] A dotted line Z in FIG. 5C2 indicates the optical axis of a lens. The optical print head 105 is moved by the above-described movement mechanism 140 in a direction generally following the optical axis of the lens indicated by the dotted line Z. The term optical axis of a lens here means a line that connects the center of the light emitting face of the lens and the focal point of this lens. The discharged light emitted from an LED enters a lens included in the lens array 506, as illustrated in FIG. 4. The lens functions to condense the discharged light entering the lens onto the surface of the photosensitive drum 103. The attachment position of the lens array 506 as to the lens attaching portion 701 is adjusted when assembling the optical print head 105, such that the distance between the light-emitting face of the LED and incoming light face of the lens, and the distance between the light-emitting face of the lens and the surface of the photosensitive drum 103, are generally equal.

[0065] Now, the necessity of moving the optical print head 105 will be described. When replacing a drum unit 518 in the image forming apparatus 1 according to the present embodiment, the drum unit 518 is moved by sliding in the rotational axis direction of the photosensitive drum 103 to the front side of the apparatus main body, as illustrated in FIG. 2B. Moving the drum unit 518 in a state where the optical print head 105 is situated near the surface of the photosensitive drum 103 results in the drum unit 518 coming into contact with the surface of the photosensitive drum 103 while moving by sliding, and the surface of the photosensitive drum 103 being mounted will be scratched. Also, the lens array 506 will come into contact with the frame of the drum unit 518 and the lens array 506 will be scratched. Accordingly, a structure is necessary where the optical print head 105 is reciprocally moved between an exposure position (FIG. 6A) where the photosensitive drum 103 is exposed, and a retracted position (FIG. 6B) retracted further from the replacement unit than this exposure position. When the sliding portion 525 moves by sliding in the direction of arrow A with the optical print head 105 at the exposure position (FIG. 6A), the optical print head 105 moves in a direction toward the retracted position (FIG. 6B). On the other hand, when the sliding portion 525 moves by sliding in the direction of arrow B with the optical print head 105

at the retracted position (FIG. 6B), the optical print head 105 moves in a direction toward the exposure position (FIG. 6A). This will be described in detail later.

[0066] FIG. 7A1 is a perspective view illustrating a bushing 671 provided to the rear side of the optical print head 105 situated in the exposure position and the rear side of the drum unit 518. FIG. 7A2 is a cross-sectional view illustrating the second support portion 528 and the bushing 671 provided to the rear side of the drum unit 518 when the optical print head 105 is situated in the exposure position. FIG. 7B1 is a perspective view illustrating the bushing 671 provided to the rear side of the optical print head 105 situated in the retracted position and the rear side of the drum unit 518. FIG. 7B2 is a cross-sectional view illustrating the second support portion 528 and the bushing 671 provided to the rear side of the drum unit 518 when the optical print head 105 is in the retracted position.

[0067] The way in which the abutting pin 515 provided to the rear side of the optical print head 105 abuts the bushing 671 provided to the drum unit 518 side will be described with reference to FIGS. 7A1 through 7B2. A part equivalent to the bushing 671 with which an abutting pin comes into contact is also provided on the front side of the drum unit 518, the structure thereof is the same as the structure of the bushing 671, and the function also is substantially the same. Just the way in which the abutting pin 515 comes into contact with the bushing 671 provided to the drum unit 518 side will be described here.

[0068] It can be seen from FIGS. 7A1 and 7B1 that the portion where the link member 652 is attached to the holding member 505 is closer to the photosensitive drum 103 side from the one of the ends of the abutting pin 515 that is opposite to the replacement unit side (the side where the drum unit 518 is disposed), in the vertical direction (the direction in which the optical print head 105 moves between the exposure position and the retracted position, i.e., in the direction of reciprocal movement). The spring attaching position 662 to which the link member 652 is attached is disposed so as to not intersect the abutting pin 515 in the vertical direction. The portion where the link member 651 is attached to the holding member 505 also is closer to the photosensitive drum 103 side from the one of the ends of the abutting pin 514 that is opposite to the replacement unit side (the side where the drum unit 518 is disposed), in the vertical direction (the direction in which the optical print head 105 moves between the exposure position and the retracted position, i.e., in the direction of reciprocal movement), although omitted from illustration here. The spring attaching portion 661 where the link member 651 is attached is disposed so as to not intersect the abutting pin 514 in the vertical direction. Accordingly, the size of the exposing unit 500 in the vertical direction can be suppressed.

[0069] The second support portion 528 has a second seating face 587, a restricting portion 128, a first wall face 588, and a second wall face 589, as illustrated in FIGS. 7A2 and 7B2. The second seating face 587 is provided to the lower side of the holding member 505. The lower side of the holding member 505 moving from the exposure position toward the retracted position abuts the second seating face 587 and the first seating face 586 of the later-described first support portion 527 from above in the vertical direction, and thus the optical print head 105 is at the retracted position. The restricting portion 128 is a recess formed in the second support portion 528 and having the shape of a box with one

side open, being opened toward the front side. The restricting portion 128 is formed to the opposite side of the holding member 505 from the side where the drum unit 518 is situated, and is fit further from the rear side than the abutting pin 515, so that the abutting pin 515 is capable of vertical movement. The abutting pin 515 that has protruded from the lower side of the holding member 505 moves through the gap formed by the restricting portion 128, and vertically moves along with the holding member 505. The first support portion 527 also has a restricting portion 127, though omitted from illustration here. The restricting portion 127 is a recess formed in the first support portion 527 and having the shape of a box with one side open, being opened toward the front side. The restricting portion 127 is formed to the opposite side of the holding member 505 from the side where the drum unit 518 is situated, and is fit further from the front side than the abutting pin 514, so that the abutting pin 514 is capable of vertical movement. The abutting pin 514 that has protruded from the lower side of the holding member 505 moves through the gap formed by the restricting portion 127, and vertically moves along with the holding member 505. The restricting portion 127 is formed tapered, to maximally reduce friction occurring due to contact with the abutting pin 514. Thus, the abutting pin 514 can smoothly move vertically in the gap at the restricting portion 127. Accordingly, movement of the holding member 505 that is integral with the abutting pin 515 and abutting pin 514 is restricted in directions intersecting both the front-and-rear direction (rotational axis direction of the photosensitive drum 103) and the vertical direction (the direction in which the optical print head 105 moves between the exposure position and the retracted position, i.e., in the direction of reciprocal movement). The restricting portion 127 may restrict the abutting pin 514 from moving from the rear side to the front side, and the restricting portion 128 may restrict the abutting pin 515 from moving from the front side to the rear side.

[0070] The first wall face 588 and second wall face 589 are disposed at positions facing each other in the left-and-right direction, with a gap formed. When the optical print head 105 reciprocally moves between the exposure position and the retracted position, the holding member 505 moves vertically through the gap formed by the first wall face 588 and second wall face 589. During this time, movement of the holding member 505 is restricted in directions intersecting both the front-and-rear direction (rotational axis direction of the photosensitive drum 103) and the vertical direction (the direction in which the optical print head 105 moves between the exposure position and the retracted position, i.e., in the direction of reciprocal movement), by the first wall face 588 and second wall face 589.

[0071] According to the above configuration, the optical print head 105 moves between the exposure position and retracted position in a state where movement is restricted in directions intersecting both the front-and-rear direction (rotational axis direction of the photosensitive drum 103) and the vertical direction (the direction in which the optical print head 105 moves between the exposure position and the retracted position, i.e., in the direction of reciprocal movement). Note that it is sufficient for at least one of the restricting portion 127 and restricting portion 128 to be provided to the first support portion 527 or second support portion 528. That is to say, it is sufficient for the restricting portion 127 to be provided to the first support portion 527

that is an example of a support portion, or the restricting portion 128 to be provided to the second support portion 528.

[0072] The position at which the abutting pin 515 comes into contact with the bushing 671 provided to the rear side of the drum unit 518, and the abutting pin 514 (omitted from illustration) comes into contact with the part equivalent to the bushing 671 that is provided to the front side of the drum unit 518, is the exposure position of the optical print head 105, as illustrated in FIGS. 7A1 and 7A2. The distance between the lens array 506 and the surface of the photosensitive drum 103 becomes the designed nominal distance by the abutting pin 514 and the abutting pin 515 abutting the bushing 671 and the part equivalent to the bushing 671.

[0073] On the other hand, the position where the abutting pin 515 is retracted from the bushing 671 provided to the rear side of the drum unit 518, as illustrated in FIGS. 7B1 and 7B2 is equivalent to the retracted position of the optical print head 105. The optical print head 105 is in a state where the drum unit 518 that moves by sliding for being replaced and the optical print head 105 do not come into contact, by the optical print head 105 being at the retracted position illustrated in FIGS. 7B1 and 7B2.

[0074] Now, the bushing 671 that the drum unit 518 has will be described. FIG. 8 illustrates a perspective view of the bushing 671. The bushing 671 is a member fixed to the casing of the drum unit 518 by screws or adhesive agent. An opening 916 is formed in the bushing 671, as illustrated in FIG. 8. A shaft member at the other end side of the photosensitive drum 103 is rotatably inserted into the opening 916. That is to say, the bushing 671 rotatably bears the photosensitive drum 103.

[0075] The photosensitive drum 103 has a photosensitive layer formed on an outer wall face of a hollow cylindrical aluminum tube. Flanges 673 are press-fitted to both ends of the aluminum tube. The flange 673 at the other end side of the photosensitive drum 103 is rotatably inserted into the opening 916 formed in the bushing 671. The flange 673 rotates while rubbing against the inner wall face of the opening 916 formed in the bushing 671. That is to say, the bushing 671 rotatably bears the photosensitive drum 103. An opening the same as that of the bushing 671 is also formed at the middle portion of the part equivalent to the bushing 671 provided to the front side of the drum unit 518, with which the abutting pin 514 comes into contact. The flange 673 of the one end side (front side) of the photosensitive drum 103 is rotatably inserted into the opening formed in the part equivalent to the bushing 671. The flange 673 rotates while rubbing against the inner wall face of this opening. That is to say, the part equivalent to the bushing 671 rotatably bears the photosensitive drum 103 at the front side, the same as the rear side of the drum unit 518.

[0076] The bushing 671 has a fitting portion 685 to which the abutting pin 515 fits. The fitting portion 685 is provided with an abutting face 551, a rear-side wall face 596, and a tapered portion 585. The fitting portion 685 may be recessed as to the bushing 671, or may be erected. The abutting pin 515 that moves in the direction from the retracted position toward the exposure position abuts the abutting face 551. The lower edge of the fitting portion 685 has the tapered portion 585 formed, that is tapered. The tapered portion 585 guides movement of the abutting pin 515 heading from the retracted position toward the exposure position, so as to abut

the abutting face **551**. Contact of the rear-side wall face **596** and the abutting pin **515** will be described later.

[0077] The movement of the abutting pin **515** that has abutted the abutting face **551** of the fitting portion **685** is restricted in directions intersecting both the front-and-rear direction (rotational axis direction of the photosensitive drum **103**) and the vertical direction (the direction in which the optical print head **105** moves between the exposure position and the retracted position, i.e., in the direction of reciprocal movement) by the fitting portion **685**. That is to say, movement of the upper end of the abutting pin **515** is restricted in directions intersecting both the front-and-rear direction and the vertical direction by the fitting portion **685**, and movement of the lower end of the abutting pin **515** is restricted in directions intersecting both the front-and-rear direction and the vertical direction by the restricting portion **128**, with regard to the optical print head **105** situated in the exposure position (FIG. 7A2). Now, the difference between the diameter of the fitting portion **685** in the left-and-right direction and the diameter of the upper end of the abutting pin **515** in the left-and-right direction, and the difference between the diameter of the restricting portion **128** in the left-and-right direction and the diameter of the lower end of the abutting pin **515** in the left-and-right direction, are smaller than the difference between the gap in the left-and-right direction between the first wall face **588** and second wall face **589** and holding member **505** situated between the first wall face **588** and second wall face **589**. Accordingly, when the optical print head **105** is in the exposure position, the first wall face **588** and second wall face **589** do not contribute to restriction of movement of the holding member **505** in directions intersecting either of the front-and-rear direction and the vertical direction.

Movement Mechanism

[0078] The movement mechanism **140** for moving the optical print head **105** will be described next. First, the first support portion **527** will be described. FIG. 9A is a schematic perspective view of the first support portion **527**. Formed on the first support portion **527** are the first seating face **586** that is an example of an abutting portion (stopping mechanism), an opening **700** serving as an example of an insertion portion, an abutting portion **529**, restricting portion **127**, protrusion **601**, screw hole **602**, positioning boss **603**, positioning boss **604**, and screw hole **605**. The first support portion **527** may be an article where the opening **700** and first seating face **586** have been integrally formed by injection molding, or these may be separate members.

[0079] The first seating face **586** is a portion where the lower side of the holding member **505** moving from the exposure position toward the retracted position abuts from above in the vertical direction, and is fixed to the main body of the image forming apparatus **1**. The lower side of the holding member **505** abuts the first seating face **586**, and the optical print head **105** is at the retracted position.

[0080] A cleaning member **572** for cleaning the light-emitting face of the lens array **506** contaminated by toner or the like is inserted through the opening **700** from the outer side of the main body of the image forming apparatus **1** by a worker such as a user or service staff or the like. The cleaning member **572** is inserted through the opening **700** along the longitudinal direction of the optical print head **105**. The cleaning member **572** is a slender rod-like member. Although a through hole which the cleaning member **572**

passes through in the front-and-rear direction is illustrated as an example of the opening **700** in the present embodiment, this is not restricted to being a hole, and a slit may be formed above, for example. The opening **700** is situated further to the downstream side than the optical print head **105**, in a direction heading from the other end side of the optical print head **105** in the longitudinal direction of the optical print head **105** toward the one end side (direction from the rear side toward the front side). In other words, the opening **700** is situated further to the front side than the optical print head **105**. The abutting portion **529** is a rear-side face of the first support portion **527**, as indicated by hatching in FIG. 9A, and is regions above and below the opening **700**. The function of the abutting portion **529** will be described later in detail.

[0081] The restricting portion **127** is a recess formed in the first support portion **527** and having the shape of a box with one side open, being opened toward the rear side, as illustrated in FIG. 9A. Part of the abutting pin **514** protruding from the lower side of the holding member **505** moves vertically along with the holding member **505** through the gap formed by the restricting portion **127**. The restricting portion **127** is formed tapered, with the thickness in the vertical direction being smaller the closer to the abutting pin **514**, to maximally reduce friction occurring due to contact with the abutting pin **514**. Accordingly, the abutting pin **514** can smoothly move vertically in the gap of the restricting portion **127**.

[0082] The first support portion **527** is fixed to the front-side face of the front-side plate **642**. Multiple holes (omitted from illustration), corresponding to the positioning boss **603**, positioning boss **604**, and fixing screws are formed in the front-side plate **642**. The positioning boss **603** and positioning boss **604** are inserted into respective holes of the multiple holes provided to the front-side plate **642**, and in this state, the first support portion **527** is fixed to the front-side plate **642** by screws passed through the screw holes of the first support portion **527**.

[0083] The third support portion **526**, which will be described later, is sheet metal folded into the shape of a box with one side opened. FIG. 9B is a diagram for describing the way in which one end portion of the third support portion **526** in the longitudinal direction is inserted into the portion surrounded by a dotted line in FIG. 9A. FIG. 9C is a diagram illustrating the one end portion of the third support portion **526** in the longitudinal direction having been inserted into the portion surrounded by the dotted line in FIG. 9A. A notch is provided at the one end portion of the third support portion **526** as illustrated in FIGS. 9B and 9C, with the protrusion **601** of the first support portion **527** side engaging the notch of the third support portion **526**. This engaging of the protrusion **601** with the notch in the third support portion **526** positions the third support portion **526** as to the first support portion **527** in the left-and-right direction. The third support portion **526** is pressed from the lower side in FIG. 9C by the screw inserted from the screw hole **602**, and is fixed to the first support portion **527** by abutting a contact face **681** of the first support portion **527**.

[0084] Next, the second support portion **528** will be described. FIG. 10A is a schematic perspective view of the second support portion **528**. The second seating face **587**, first wall face **588**, second wall face **589**, and restricting portion **128**, are formed on the second support portion **528**. The second seating face **587** is the portion that the lower side

of the holding member 505 moving from the exposure position toward the retracted position abuts, as described earlier. The second seating face 587 is fixed to the main body of the image forming apparatus 1. The lower side of the holding member 505 abuts the second seating face 587, and thus the optical print head 105 is at the retracted position.

[0085] The second support portion 528 is fixed to the front-side face of the rear-side plate 643, as illustrated in FIG. 10B. The second support portion 528 is fixed to the rear-side plate 643 by positioning bosses and screws, in the same way that the first support portion 527 is fixed to the front-side plate 642. FIG. 10C illustrates a state where the other end side (rear side) of the third support portion 526 in the longitudinal direction of the third support portion 526 is inserted into the portion surrounded by a dotted line in FIG. 10A. That is to say, one end portion of the third support portion 526 is supported by the first support portion 527, and the other end portion is supported by the second support portion 528, with the first support portion 527 and the second support portion 528 being fixed to the front-side plate 642 and rear-side plate 643, respectively. In other words, the third support portion 526 is fixed to the main body of the image forming apparatus 1.

[0086] Note that an arrangement may be made where the second support portion 528 is fixed to the third support portion 526 by screws or the like, and is not fastened to the rear-side plate 643 by screws. In this case, a structure is made, for example, where a recessed portion is formed in the second support portion 528, which fits with a protruding portion formed on the rear-side plate 643, thereby positioning the second support portion 528 as to the rear-side plate 643. The first wall face 588 and second wall face 589 of the second support portion 528 will be described later.

[0087] The restricting portion 128 is a recess formed in the second support portion 528 and having the shape of a box with one side open, being opened toward the front side, as illustrated in FIG. 10A. Part of the abutting pin 515 protruding from the lower side of the holding member 505 moves vertically along with the holding member 505 through the gap formed by the restricting portion 128. The restricting portion 128 is formed tapered, to maximally reduce friction occurring due to contact with the abutting pin 515 with the thickness in the vertical direction being thinner, the closer to the abutting pin 515. Accordingly, the abutting pin 515 can smoothly move vertically in the gap of the restricting portion 128.

[0088] Next, the third support portion 526 and sliding portion 525 will be described with reference to FIGS. 11A and 11B. The third support portion 526 and sliding portion 525 are disposed on the opposite side of the holding member 505 from the photosensitive drum 103.

[0089] FIG. 11A is a schematic perspective view of the front side of the movement mechanism 640 as viewed from the left side, with the first support portion 527 omitted from illustration. FIG. 11B is a schematic perspective view of the front side of the movement mechanism 640 as viewed from the right side, with the first support portion 527 omitted from illustration. The movement mechanism 640 has the link member 651, the sliding portion 525, and the third support portion 526. The third support portion 526 has a support shaft 531 and an E-type snap ring 533. It can be seen from FIGS. 11A and 11B that the support shaft 531 is inserted through openings formed in the opposing faces (left-side face and right-side face) of the third support portion 526 that

has been formed into the shape of a box with one side open. The support shaft 531 passes through the right-side face and the left-side face of the third support portion 526. The support shaft 531 is retained by the E-type snap ring 533 on the outer side of the left-side face, so as not to fall out from the openings of the third support portion 526. On the other hand, a slot 691 that is an elongated opening and that extends in the front-and-rear direction is formed in the sliding portion 525, as illustrated in FIG. 11A. The support shaft 531 is inserted through the slot 691 of the sliding portion 525, and is loosely fit with a gap of around 0.1 to 0.5 mm as to the slot 691 in the vertical direction, for example. Accordingly, movement of the sliding portion 525 in the vertical direction as to the third support portion 526 is restricted, and the sliding portion 525 can only move by sliding as to the third support portion 526 by the length of the slot 691 in the front-and-rear direction.

[0090] A slide aiding member 539 having an accommodation space 562 from the left side to the lower side is attached to one end side of the sliding portion 525. The slide aiding member 539 is fixed to the sliding portion 525 by being fastened by a screw from the left side. The accommodation space 562 accommodates a later-described pressing member 561 that the cover 558 has. The relation between the accommodation space 562 and the pressing member 561, and structural features thereof, will be described later along with description of the cover 558.

[0091] The movement mechanism 640 will be described with reference to FIGS. 3 and 11A through 12B. FIG. 3 is a schematic perspective view of the exposing unit 500 having the movement mechanism 640. The movement mechanism 640 has the first link mechanism 861, second link mechanism 862, sliding portion 525, first support portion 527, second support portion 528, and third support portion 526, as illustrated in FIG. 3. The first link mechanism 861 includes the link member 651 and link member 653, and the second link mechanism 862 includes the link member 652 and link member 654. The link member 651 and link member 653, and link member 652 and link member 654, each make up a J-type link mechanism, as illustrated in FIG. 3.

[0092] FIG. 11A is a schematic perspective view of the front side of the movement mechanism 640, as viewed from the left side, with the first support portion 527 omitted from illustration. FIG. 11B is a schematic perspective view of the front side of the movement mechanism 640, as viewed from the right side, with the first support portion 527 omitted from illustration.

[0093] The first link mechanism 861 will be described with reference to FIGS. 11A through 12B. FIG. 12A is a diagram where a cross-sectional view of the first link mechanism 861 taken along the rotational axis of the photosensitive drum 103 is viewed from the right side. The first link mechanism 861 has the link member 651 and link member 653. The link member 651 and link member 653 making up the first link mechanism 861 are each single link members, but may be configured by combining multiple link members. The length of the link member 653 in the longitudinal direction is shorter than the length of the link member 651 in the longitudinal direction, as illustrated in FIGS. 12A and 12B.

[0094] The link member 651 has a bearing 610, a protrusion 655, and a connecting shaft portion 538. The bearing 610 is provided to one end side in the longitudinal direction

of the link member 651. The protrusion 655 is a cylindrical protrusion erected in the pivoting axis direction of the link member 651 provided at the other end side in the longitudinal direction of the link member 651, for causing deformation of a spring provided to the holding member 505 side of the optical print head 105. The connecting shaft portion 538 is provided between the bearing 610 and protrusion 655 in the longitudinal direction of the link member 651. Although the protrusion 655 serves as a first moving portion, the first moving portion is not restricted to the protrusion 655, and may be a structure where one end side in the longitudinal direction of the link member 651 is bent in the pivoting axis direction.

[0095] A circular hollowed space that extends in the left-and-right direction in FIG. 12A is formed in the bearing 610, as a hole. A fitting shaft portion 534 is provided to the sliding portion 525. The fitting shaft portion 534 is a cylindrical protrusion erected from the sliding portion 525 to the left direction in FIG. 12A. The fitting shaft portion 534 forms a first connecting portion by being pivotably fit to the hole of the bearing 610. That is to say, the link member 651 is capable of pivoting as to the sliding portion 525, with the first connecting portion as the center of pivoting. Note that the fitting shaft portion 534 may be formed on the link member 651 side, and the bearing 610 formed on the sliding portion 525.

[0096] The link member 653 has a connecting shaft portion 530. The connecting shaft portion 530 is provided to one end side in the longitudinal direction of the link member 653. The connecting shaft portion 530 is a cylindrical protrusion erected from the link member 653 to the left side in FIG. 12A. The connecting shaft portion 530 is rotatably inserted into a hole formed in the third support portion 526, and thus forms a third connecting portion. The connecting shaft portion 530 may be formed to the third support portion 526 rather than the link member 653. That is to say, the connecting shaft portion 530 formed on the third support portion 526 may be inserted to a hole formed in the link member 653.

[0097] A circular hole that extends in the left-and-right direction in FIG. 12A is formed at the other end side in the longitudinal direction of the link member 653. The connecting shaft portion 538 of the abutting face 551 is pivotably inserted into this hole, whereby the connecting shaft portion 538 and the hole of the link member 653 make up a fourth connecting portion. That is to say, the link member 653 is capable of pivoting as to the third support portion 526 with the third connecting portion as a center of pivoting, and is capable of pivoting as to the link member 651 with the fourth connecting portion as a center of pivoting. Now, the connecting shaft portion 538 may be formed on the link member 653 rather than the link member 651. That is to say, the connecting shaft portion 538 formed on the link member 653 may be inserted into a hole formed in the link member 651.

[0098] Note that the configuration of the second link mechanism 862 is the same as the configuration of the first link mechanism 861 described above. The link member 652 and link member 654 that the second link mechanism 862 has correspond to the link member 651 and link member 653, respectively. The one end side in the longitudinal direction of the link member 652 and the connecting portion of the sliding portion 525 make up a second connecting portion, corresponding to the first connecting portion. Note

that one of the link member 653 and link member 654 may be omitted from the embodiment regarding the movement mechanism 640.

[0099] According to the above configuration, when the sliding portion 525 moves by sliding from the front side toward the rear side with regard to the third support portion 526, the bearing 610 to which the fitting shaft portion 534 has been fit moves by sliding from the front side toward the rear side as to the third support portion 526, along with the sliding portion 525. Accordingly, when viewing the first link mechanism 861 from the right side as illustrated in FIG. 12A, the link member 651 pivots in the clockwise direction with the fitting shaft portion 534 as the center of pivoting, and the link member 653 pivots in the counter-clockwise direction with the connecting shaft portion 530 as the center of pivoting. Accordingly, the protrusion 655 moves in a direction from the exposure position toward the retracted position.

[0100] On the other hand, when the sliding portion 525 moves by sliding from the rear side toward the front side as to the third support portion 526, the link member 651 and link member 653 move in the opposite directions as to the arrows in FIG. 12A. When the sliding portion 525 moves by sliding from the rear side toward the front side with regard to the third support portion 526, the bearing 610 to which the fitting shaft portion 534 has been fit moves by sliding from the rear side toward the front side as to the third support portion 526, along with the sliding portion 525. Accordingly, when viewing the first link mechanism 861 from the right side as illustrated in FIG. 12A, the link member 651 pivots in the counter-clockwise direction with the fitting shaft portion 534 as the center of pivoting, and the link member 653 pivots in the clockwise direction with the connecting shaft portion 530 as the center of pivoting. Accordingly, the protrusion 655 moves in a direction from the retracted position toward the exposure position.

[0101] Now,

[0102] (1) the distance between the pivoting center axis of the connecting shaft portion 538 and the pivoting center axis of the bearing 610 will be referred to as L1,

[0103] (2) the distance between the pivoting center axis of the connecting shaft portion 538 and the pivoting center axis of the connecting shaft portion 530 will be referred to as L2, and

[0104] (3) the distance between the pivoting center axis of the connecting shaft portion 538 and the pivoting center axis of the protrusion 655 will be referred to as L3. In the movement mechanism 640, the first link mechanism 861 forms a Scott Russel linkage where L1, L2, and L3 are equal (see FIG. 12B). The protrusion 655 moves perpendicular (along line A in FIG. 12B) to the direction of sliding movement of the fitting shaft portion 534 due to the distances L1, L2, and L3 being equal, so the optical print head 105 can be moved generally in the optical axis direction of the lens in the above-described link mechanism.

[0105] A configuration may be made where the front-and-rear directions of the first link mechanism 861 and second link mechanism 862 are opposite, so that when the sliding portion 525 is moved by sliding from the front side toward the rear side, the optical print head 105 moves from the retracted position toward the exposure position, and when the sliding portion 525 is moved by sliding from the rear side toward the front side, the optical print head 105 moves from the exposure position toward the retracted position. In this

case, the later-described cover **558** presses the sliding portion **525** from the front side toward the rear side when moving from an opened state to a closed state, and pulls the sliding portion **525** from the rear side toward the front side when moving from a closed state to an opened state.

[0106] The mechanism for moving optical print head **105** is not restricted to the movement mechanism **640**. A movement mechanism **140** illustrated in FIGS. **13A** and **13B** may be used. The movement mechanism **140** will be described below with reference to FIGS. **13A** through **14B**. Members which have substantially the same functions as the members making up the movement mechanism **640** are denoted by the same reference numerals, and redundant description may be omitted.

[0107] The arrangement by which the movement mechanism **140** moves the holding member **505** will be described with reference to FIGS. **13A** through **14B**. FIG. **14A** is a cross-sectional view of the holding member **505** and the movement mechanism **140** illustrated in FIG. **14B**, taken along the rotational axis of the photosensitive drum **103**.

[0108] The link member **151** has a bearing **110** and a protrusion **155**, as illustrated in FIGS. **13A** and **13B**. The bearing **110** is provided at the one end side of the link member **151** in the longitudinal direction. The protrusion **155** is, as illustrated in FIGS. **14A** and **14B**, a cylindrical protrusion that is provided on the other end side of the link member **151** in the longitudinal direction and that is erected in the pivoting axis direction of the link member **151**. The protrusion **155** is a protrusion for deforming a spring provided on the holding member **505** side of the optical print head **105**. Note that the first moving portion is not restricted to being the protrusion **155**, and may be a structure where the one end side in the longitudinal direction of the link member **151** is bent in the pivoting axis direction of the link member **151**.

[0109] A circular hollowed space that extends in the left-and-right direction is formed in the bearing **110**, as a hole. A fitting shaft portion **534** is provided to the sliding portion **525**, as illustrated in FIGS. **14A** and **14B**. The fitting shaft portion **534** is a cylindrical protrusion erected from the sliding portion **525** toward the left. The hole of the bearing **110** is fit with the fitting shaft portion **534** so as to be capable of pivoting, thereby forming a first connecting portion. That is to say, the link member **151** is pivotable as to the sliding portion **525**, with the first connecting portion as the center of pivoting. Note that an arrangement may be made where the fitting shaft portion **534** is formed on the link member **151** side, and the bearing **110** is formed on the sliding portion **525**.

[0110] Note that a shaft the same as the support shaft **531** is provided at the rear side of the third support portion **526**, a slot the same as the slot **691** is formed at the rear side of the sliding portion **525**, and the structure of the rear side of the movement mechanism **140** is the same as the front side. The structure of the link member **152** also is the same as the structure of the first moving member described above, with the link member **152** corresponding to the link member **151**. The connecting portion of the one end side in the longitudinal direction of the link member **152** and the sliding portion **525** make up the second connecting portion, corresponding to the first connecting portion.

[0111] The abutting portion **529** of the first support portion **527** (omitted from illustration in FIGS. **13A** through **14B**) is disposed further toward the front side as compared to the one

end of the holding member **505**. Accordingly, when the sliding portion **525** moves by sliding as to the third support portion **526** from the rear side to the front side, the bearing **110** to which the fitting shaft portion **534** is fit also moves by sliding as to the third support portion **526** from the rear side to the front side, along with the sliding portion **525**. The holding member **505** to which the protrusion **155** is attached also attempts to move forward in conjunction with this, but the one end of the holding member **505** is abutting the abutting portion **529**, and accordingly movement toward the front side is restricted. The link member **151** is disposed intersecting the rotational axis direction of the photosensitive drum **103** such that the one end side having the protrusion **155** is situated closer to the drum unit **518** side as compared to the other end side having the bearing **110**, and accordingly pivots in a counter-clockwise direction with the fitting shaft portion **534** as the center of pivoting, as viewed from the right side as illustrated in FIG. **14A**. Accordingly, the holding member **505** moves from the retracted position toward the exposure position with the one end of the holding member **505** abutting the abutting portion **529**.

[0112] On the other hand, when the sliding portion **525** moves by sliding as to the third support portion **526** from the front side to the rear side, the bearing **110** fit to the fitting shaft portion **534** moves by sliding as to the third support portion **526** from the rear side to the front side, along with the sliding portion **525**. Accordingly, the link member **151** pivots in a clockwise direction with the fitting shaft portion **534** as the center of pivoting, as viewed from the right side as illustrated in FIG. **14A**. Thus, the protrusion **155** moves in a direction from the exposure position toward the retracted position. The sliding portion **525** moves from the rear side to the front side in conjunction with a closing operation of the cover **558**, and moves from the front side to the rear side in conjunction with an opening operation of the cover **558**, which will be described in detail later. That is to say, when the cover **558** moves from an opened state to a closed state, the holding member **505** moves in a direction from the retracted position toward the exposure position, and when the cover **558** moves from the closed state to the opened state, the holding member **505** moves in a direction from the exposure position toward the retracted position.

[0113] When the optical print head **105** moves generally in the optical axis direction of the lens, the rear side of the holding member **505** moves through a gap formed by the first wall face **588** and the second wall face **589** of the second support portion **528**, as described earlier. This prevents the holding member **505** from tilting in the left or right directions.

[0114] Note that the link member **151** and link member **152** may be arranged such that the other end side is situated further toward the front side than the one end side, with the abutting portion **529** situated further toward the rear side than the other end of the holding member **505**. That is to say, when the sliding portion **525** moves by sliding as to the third support portion **526** from the front side to the rear side, the bearing **110** to which the fitting shaft portion **534** is fit also moves by sliding as to the third support portion **526** from the front side to the rear side, along with the sliding portion **525**. The holding member **505** to which the protrusion **155** is attached also attempts to move to the rear side in conjunction with this, but the other end of the holding member **505** is abutting the abutting portion **529**, and accordingly movement toward the rear side is restricted. Accordingly, the link

member **151** and link member **152** pivot in the clockwise direction as to the sliding portion **525** when viewing the link member **151** from the right side, and the holding member **505** moves from the retracted position toward the exposure position with the other end of the holding member **505** abutting the abutting portion **529**. In this case, the cover **558** presses the sliding portion **525** from the front side toward the rear side when moving from the opened state to the closed state, and pulls the sliding portion **525** from the rear side toward the front side when moving from the closed state to the opened state.

[0115] The mechanism for moving the optical print head **105** is not restricted to the movement mechanism **140** and movement mechanism **640**. A movement mechanism **840** illustrated in FIGS. **15A1** through **15B** may be used. The movement mechanism **840** will be described below with reference to FIGS. **15A1** through **15B**. Note that members having substantially the same functions as members making up the movement mechanism **140** (**640**) are denoted by the same reference numerals, and redundant description may be omitted.

[0116] FIGS. **15A1** and **15A2** illustrate the movement mechanism **840**. The movement mechanism **840** includes a first link mechanism **858**, a second link mechanism **859**, sliding portion **825**, and the third support portion **526**, as illustrated in FIGS. **15A1** and **15A2**. The first link mechanism **858** includes a link member **843** and a link member **844**, and the second link mechanism **859** includes a link member **845** and a link member **846**. The link member **843** and link member **844**, and the link member **845** and link member **846**, each pivotably intersect each other, making up an X-shaped link mechanism as illustrated in FIGS. **15A1** through **15B**. A protrusion **847** of the link member **843**, a protrusion **848** of the link member **844**, a protrusion **849** of the link member **845**, and a protrusion **850** of the link member **846**, are each pivotably attached to a holding member **805** that is omitted from illustration. When a sliding portion **825** is moved by sliding in the direction of the arrow A in FIG. **15A1**, the link members **843** through **846** pivot with regard to the sliding portion **825**, and the protrusions **847** through **850** move downwards (FIG. **15A2**). On the other hand, when the sliding portion **825** is moved by sliding in the direction of the arrow B in FIG. **15A2**, the link members **843** through **846** pivot with regard to the sliding portion **825**, and the protrusions **847** through **850** move upwards (FIG. **15A1**).

[0117] FIG. **15B** is a diagram illustrating the front side of the movement mechanism **840** with the front side of the holding member **805**. The arrangement by which the movement mechanism **840** moves the holding member **805** will be described below with reference to FIG. **15B**. Now, the operations of first link mechanism **858** and second link mechanism **859** are substantially the same, so the first link mechanism **858** will be described here with reference to FIG. **15B**. The first link mechanism **858** has the link member **843** and link member **844**. The link member **843** and link member **844** making up the first link mechanism **858** are single members, but may be configured by combining multiple members.

[0118] The movement mechanism **840** in FIG. **15B** has the first link mechanism **858** and sliding portion **825**. The sliding portion **825** has a slot **863** that is an elongated opening, passing through the sliding portion **825** in the

left-and-right direction and extending in the front-and-rear direction, as illustrated in FIG. **15B**.

[0119] The link member **843** has a protrusion **810**, the protrusion **847**, and the connecting shaft portion **538**. The protrusion **810** is provided to one end side in the longitudinal direction of the link member **843**. The protrusion **847** is a cylindrical protrusion erected to the right side in the pivoting axial direction of the link member **843**, provided to the other end side in the longitudinal direction of the link member **843**. The connecting shaft portion **538** is provided between the protrusion **810** and protrusion **847** in the longitudinal direction of the link member **843**. Although the protrusion **847** serves as a first moving portion, the first moving portion is not restricted to the protrusion **847**, and may be a structure where one end side in the longitudinal direction of the link member **843** is bent in the pivoting axis direction.

[0120] The protrusion **810** is pivotably loosely fit to the slot **863** of the sliding portion **825**, thereby forming the first connecting portion. That is to say, the link member **843** is pivotable as to the sliding portion **825** with the first connecting portion as the center of pivoting. The protrusion **810** is capable of moving in the slot **863** in the front-and-rear direction within the range of the slot **863** in the front-and-rear direction (within the opening). A coil spring **860** is disposed between the rear-side edge of the slot **863** and the protrusion **810**.

[0121] The link member **844** has the connecting shaft portion **530** and the protrusion **848**. The connecting shaft portion **530** is provided to one end side in the longitudinal direction of the link member **844**. The connecting shaft portion **530** is a cylindrical protrusion erected from the link member **844** to the right side in FIG. **15B**. The connecting shaft portion **530** is pivotably inserted into a hole formed in the third support portion **526**, thereby forming the third connecting portion. Now, the connecting shaft portion **530** may be formed on the third support portion **526** rather than the link member **844**. That is to say, the connecting shaft portion **530** formed on the third support portion **526** may be inserted into a hole formed in the link member **844**.

[0122] The protrusion **848** is a cylindrical protrusion provided to the other end side in the longitudinal direction of the link member **844**, erected to the right side in the pivoting axis direction of the link member **844**. A circular hole that extends in the left-and-right direction in FIG. **15B** is formed between the protrusion **848** of the link member **844** and the third connecting portion. The connecting shaft portion **538** of the link member **843** is pivotably inserted into this hole, whereby the connecting shaft portion **538** and the hole of the link member **844** make up the fourth connecting portion. That is to say, the link member **844** is capable of pivoting as to the third support portion **526** with the third connecting portion as a center of pivoting, and is capable of pivoting as to the link member **843** with the fourth connecting portion as a center of pivoting. Now, the connecting shaft portion **538** may be formed on the link member **844** rather than the link member **843**. That is to say, the connecting shaft portion **538** formed on the link member **844** may be inserted into a hole formed in the link member **843**. Note that one of the link member **843** and link member **844** may be omitted from the embodiment regarding the movement mechanism **840**.

[0123] The holding member **805** has the lens array **506**, a link attaching portion **851**, a link attaching portion **852**, and a pin attaching portion **855**. The link attaching portion **851** and link attaching portion **852** both are provided between

pins **514** attached to the lens array **506** and holding member **805**. Although omitted from illustration, a link attaching portion **853** and link attaching portion **854** to which the link member **845** and link member **846** making up the second link mechanism **859** are attached are both provided between pins **516** attached to the other end side of the lens array **506** and holding member **805**. The link attaching portion **851** is a hole formed to the holding member **805** between the lens array **506** and pin attaching portion **855**, passing through in the left-and-right direction. The link attaching portion **852** is a slot that is formed in the holding member **805** between the lens array **506** and the link attaching portion **851**, and that passes through in the left-and-right direction and extends in the front-and-rear direction.

[0124] The protrusion **847** of the link member **843** is pivotably attached to the link attaching portion **851**, and the protrusion **848** of the link member **844** is pivotably attached to the link attaching portion **852**. The protrusion **848** is attached to the link attaching portion **851** so as to be capable of moving in the front-and-rear direction. Accordingly, the link member **844** is capable of moving by sliding in the front-and-rear direction within the range of the link attaching portion **852** in the front-and-rear direction, while pivoting with the protrusion **848** as a center of pivoting.

[0125] According to the above-described configuration, when the sliding portion **825** moves by sliding from the front side to the rear side as to the third support portion **526**, the protrusion **810** moves by sliding from the front side to the rear side as to the third support portion **526** along with the sliding portion **825**. Accordingly, when viewing the first link mechanism **858** from the right side as illustrated in FIG. 15A1, the protrusion **848** moves from the front side to the rear side at the link attaching portion **852** with the link member **843** pivoting clockwise with the protrusion **810** as the center of pivoting and the link member **844** pivoting counter-clockwise with the connecting shaft portion **530** as the center of pivoting. Accordingly, the protrusion **847** and protrusion **848** move in the direction from the exposure position toward the retracted position.

[0126] On the other hand, when the sliding portion **825** moves by sliding from the rear side to the front side as to the third support portion **526**, the protrusion **810** moves by sliding from the rear side to the front side as to the third support portion **526** along with the sliding portion **825**. Accordingly, when viewing the first link mechanism **858** from the right side as illustrated in FIG. 15A2, the protrusion **848** moves from the rear side to the front side at the link attaching portion **852** with the link member **843** pivoting counter-clockwise with the protrusion **810** as the center of pivoting and the link member **844** pivoting clockwise with the connecting shaft portion **530** as the center of pivoting. Accordingly, the protrusion **847** and protrusion **848** move from the retracted position toward the exposure position. When the sliding portion **825** further moves by sliding to the front side in a state where the abutting pin **514** is in contact with an abutting face **550**, as illustrated in FIG. 15B, the coil spring **860** is compressed between the rear side edge of the slot **863** and the protrusion **810**. The protrusion **810** is biased to the front side by the restoration force of the compressed coil spring **860**. Accordingly, biasing force heading upwards is applied to the holding member **805**.

[0127] A configuration may be made where the front-and-rear directions of the first link mechanism **858** and second link mechanism **859** are opposite, so that when the sliding

portion **825** is moved by sliding from the front side toward the rear side, the optical print head **105** moves from the retracted position toward the exposure position, and when the sliding portion **825** is moved by sliding from the rear side toward the front side, the optical print head **105** moves from the exposure position toward the retracted position. In this case, the later-described cover **558** presses the sliding portion **825** from the front side toward the rear side when moving from an opened state to a closed state, and pulls the sliding portion **825** from the rear side toward the front side when moving from a closed state to an opened state.

[0128] The mechanism for moving the optical print head **105** is not restricted to the movement mechanism **140**, movement mechanism **640**, and movement mechanism **840**. A movement mechanism **940** illustrated in FIGS. 16A and 16B may be used. The movement mechanism **940** will be described below with reference to FIGS. 16A and 16B. Note that members having substantially the same functions as members making up the movement mechanism **140** (including **640** and **840**) are denoted by the same reference numerals, and redundant description may be omitted.

[0129] As illustrated in FIGS. 16A and 16B, a first cam portion **112** and a second cam portion **113** are provided to the front side and rear side of the sliding portion **525**. A movement support portion **114** and a movement support portion **115** are provided to the front side and rear side at the lower side of the holding member **905**. The first cam portion **112** and second cam portion **113** have a face inclined downwards from the rear side toward the front side as to the holding member **905** side.

[0130] FIG. 16A is a schematic diagram illustrating the optical print head **105** situated at the exposure position and the movement mechanism **940**, as viewed from the right side. When the sliding portion **525** moves by sliding from the front side to the rear side as to the third support portion **526** in a case where the optical print head **105** is at the exposure position, the first cam portion **112** and second cam portion **113** provided to the sliding portion **525** move by sliding from the front side to the rear side as to the third support portion **526**, along with the sliding portion **525**. Accordingly, the lower ends of the movement support portion **114** and movement support portion **115** provided to the holding member **905** about the first cam portion **112** and second cam portion **113**, and the movement support portion **114** and movement support portion **115** move along the first cam portion **112** and second cam portion **113** in a direction from the exposure position toward the retracted position.

[0131] FIG. 16B is a schematic diagram illustrating the optical print head **105** situated at the retracted position and the movement mechanism **940**, as viewed from the right side. When the sliding portion **525** moves by sliding from the rear side to the front side as to the third support portion **526** in a case where the optical print head **105** is at the retracted position, the first cam portion **112** and second cam portion **113** provided to the sliding portion **525** move by sliding from the rear side to the front side as to the third support portion **526**, along with the sliding portion **525**. Accordingly, the lower ends of the movement support portion **114** and movement support portion **115** provided to the holding member **905** are pressed upwards and move along the first cam portion **112** and second cam portion **113** in a direction from the retracted position toward the exposure position.

[0132] Now an arrangement may be made where the direction of inclination of the inclined faces that the first cam portion 112 and second cam portion 113 have is inclined downwards from the front side toward the rear side, with sliding movement of the sliding portion 525 from the front side to the rear side moving the optical print head 105 from the retracted position toward the exposure position, and sliding movement of the sliding portion 525 from the rear side to the front side moving the optical print head 105 from the exposure position toward the retracted position. In this case, the later-described cover 558 presses the sliding portion 525 from the front side toward the rear side when moving from an opened state to a closed state, and pulls the sliding portion 525 from the rear side toward the front side when moving from a closed state to an opened state.

[0133] Next, the cover 558 will be described with reference to FIGS. 17A through 17C. The cover 558 is a member for causing the sliding portion 525 to move by sliding as described above. Note that the configuration causing the sliding portion 525 to move by sliding is not restricted to the cover 558. For example, a configuration may be made where the sliding portion 525 moves by sliding in conjunction with opening/closing of an unshown front door. Alternatively, a configuration may be made where the sliding portion 525 moves by sliding in conjunction with turning of a turning member such as a lever or the like, rather than a covering member such as the cover 558 or a door.

[0134] FIG. 17A is a perspective view of the cover 558. The cover 558 has a pivoting shaft portion 559 and a pivoting shaft portion 560, as illustrated in FIG. 17A. The pivoting shaft portion 559 is a cylindrical protrusion protruding in the right-side direction of the cover 558, while the pivoting shaft portion 560 is a cylindrical protrusion protruding in the left-side direction of the cover 558.

[0135] FIG. 17B is an enlarged view of the portion where the cover 558 is attached to the front-side plate 642. FIG. 17C is a perspective view of the cover 558 that has been attached to the front-side plate 642. The front-side plate 642 has a bearing member 621 to which the pivoting shaft portion 559 of the cover 558 fits, and a bearing member 622 to which the pivoting shaft portion 560 fits, as illustrated in FIG. 17B. The pivoting shaft portion 559 of the cover 558 pivotably fits to the bearing member 621 of the front-side plate 642, and the pivoting shaft portion 560 pivotably fits to the bearing member 622 of the front-side plate 642, as illustrated in FIG. 17C. The pivoting axis of the pivoting shaft portion 559 and the pivoting axis of the pivoting shaft portion 560 are on a pivoting axis 563, as illustrated in FIG. 17A. The cover 558 opens and closes as to the main body of the image forming apparatus 1, with the pivoting axis 563 as the center of pivoting. The closed cover 558 is situated on the inserting/extracting path of the drum unit 518 and developing unit 641. Accordingly, when the cover 558 is in a closed state, replacement of the drum unit 518 and developing unit 641 cannot be performed by the worker. The worker can replace the drum unit 518 by opening the cover 558, and closes the cover 558 when the work is completed.

[0136] Next, the configuration by which the sliding portion 525 moves by sliding in the pivoting axis direction of the photosensitive drum 103 in conjunction with opening/closing operations of the cover 558 will be described in detail with reference to FIGS. 18A through 21D. FIGS. 18A through 18D are perspective diagrams illustrating the cover 558 pivoting from an opened state toward a closed state.

FIGS. 19A through 19D are cross-sectional views illustrating the cover 558 pivoting from the opened state toward the closed state. FIGS. 18A and 19A illustrate the opened state of the cover 558. FIGS. 18D and 19D illustrate the closed state of the cover 558. FIGS. 18B and 19B, and FIGS. 18C and 19C, are diagrams illustrating the cover 558 transitioning from the opened state to the closed state. Note that the closed state of the cover 558 in the closed state illustrated in FIGS. 18D and 19D is maintained by a snap fit mechanism for engaging to the main body, a stopper for preventing pivoting, or the like.

[0137] The cover 558 pivots as to the main body of the image forming apparatus 1 centered on the pivoting axis 563, as illustrated in FIGS. 18A through 18D. The pressing member 561 also turns centered on the pivoting axis 563 accordingly, as indicated by the movement path 564 in FIGS. 19A through 19D. The cover 558 has the cylindrical pressing member 561 protruding from the left side toward the right side. The pressing member 561 is situated within the accommodation space 562 provided to the one end of the sliding portion 525, as illustrated in FIGS. 18A through 18D.

[0138] The operations of the pressing member 561 on the sliding portion 525 will be described with reference to FIGS. 19A through 19D. When the cover 558 pivots in the clockwise direction from the state in FIG. 19A, the pressing member 561 is situated on the movement path 564, and abuts a first pressed portion 566 intersecting the movement path 564 (FIG. 19B). When the cover 558 further pivots in the clockwise direction from this state, the pressing member 561 presses the first pressed portion 566 to the front side while rubbing against the first pressed portion 566. Accordingly, the slide aiding member 539 moves toward the front side. The slide aiding member 539 is fixed to the sliding portion 525, so the sliding portion 525 also moves by sliding toward the front side, in conjunction with the movement of the slide aiding member 539.

[0139] Further, when the cover 558 pivots even more in the clockwise direction, the pressing member 561 moves from the first pressed portion 566 to a second pressed portion 567 (FIG. 19C). The second pressed portion 567 has a curved face that generally follows the movement path 564 of the pressing member 561. Accordingly, in a case where the cover 558 further pivots in the clockwise direction from the state in FIG. 19C, the pressing member 561 comes into contact with the second pressed portion 567 and moves upwards, but no force for further moving the slide aiding member 539 by sliding toward the front side is applied from the pressing member 561.

[0140] It can be seen from FIGS. 18C and 19C that when the cover 558 pivots from the opened state toward the closed state, the pressing member 561 abuts the second pressed portion 567 at the front side of the accommodation space 562 immediately after the holding member 505 has reached the exposure position. The second pressed portion 567 has a shape generally following the movement path 564 of the pressing member 561, which is an arc shape centered on the pivoting axis 563. Accordingly, in a case of further pivoting the cover 558 from the state in FIG. 19C in the clockwise direction, the pressing member 561 moves sliding over the second pressed portion 567 that it abuts. However, no force to further move the slide aiding member 539 toward the front side is applied from the pressing member 561. Accordingly, the slide aiding member 539 does not move from the rear side toward the front side while the pressing member

561 is moving over the second pressed portion **567**. That is to say, the movement mechanism **640** according to the present embodiment is configured such that when the cover **558** pivots in a state where the pressing member **561** is abutting the first pressed portion **566**, the sliding portion **525** moves by sliding in conjunction with the movement of the pressing member **561**, but the sliding portion **525** does not move by sliding even if the cover **558** pivots in a state where the pressing member **561** is abutting the second pressed portion **567**. By further pivoting the cover **558** from the state in FIG. 19C in the clockwise direction, the cover **558** reaches the closed state illustrated in FIG. 19D.

[0141] FIGS. 20A through 20D are perspective diagrams illustrating the cover **558** pivoting from the closed state toward the opened state. FIGS. 21A through 21D are cross-sectional views illustrating the cover **558** pivoting from the closed state toward the opened state. FIGS. 20A and 21A illustrate the closed state of the cover **558**. FIGS. 20D and 21D illustrate the opened state of the cover **558**. FIGS. 20B and 21B, and FIGS. 20C and 21C, are diagrams illustrating the cover **558** transitioning from the closed state to the opened state.

[0142] In the closed state of the cover **558** illustrated in FIG. 21A, force is placed on the sliding portion **525** via the first link mechanism **861** and second link mechanism **862** to slide from the front side toward the rear side, by the deadweight of the optical print head **105** and the restoring force of later-described springs. However, the cover **558** in the closed state is fixed to the main body of the image forming apparatus **1** so that the cover **558** does not pivot, and the pressing member **561** restricts movement of the slide aiding member **539** to the rear side, so the sliding portion **525** does not move by sliding to the rear side.

[0143] When the cover **558** pivots in the counter-clockwise direction from the state in FIG. 21A, the pressing member **561** abuts a third pressed portion **568**, as illustrated in FIG. 21B. Upon the cover **558** further pivoting in the counter-clockwise direction from the state in FIG. 21B, the pressing member **561** presses the third pressed portion **568** from the front side toward the rear side as illustrated in FIGS. 21B and 21C, and the sliding portion **525** moves toward the rear side. Thereafter, further pivoting of the cover **558** in the counter-clockwise direction brings the cover **558** to the opened state as illustrated in FIG. 21D.

[0144] The mechanism where the pressing member **561** presses the third pressed portion **568** is provided from the following reason. That is to say, a case can be conceived where the sliding portion **525** does not move to the rear side even if restriction on movement of the slide aiding member **539** by the pressing member **561** is released by the cover **558** being pivoted in the counter-clockwise direction from the state in FIG. 20A, if frictional force between the among the link members, frictional force between the link member **651** or link member **653** and the sliding portion **525**, and frictional force between the link member **652** or link member **654** and the third support portion **526**, are great. That is to say, a case can be conceived where the sliding portion **525** does not move by sliding even though the cover **558** has been opened. In order to deal with this, the movement mechanism according to the present embodiment includes the mechanism where the pressing member **561** presses the third pressed portion **568**, so that opening the cover **558** causes the sliding portion **525** to move toward the rear side. According to the configuration described above, a worker

performing maintenance opening and closing the cover **558** causes the sliding portion **525** to move by sliding with regard to the third support portion **526**, in conjunction with movement of the cover **558**.

[0145] Next, a connection mechanism between the holding member **505** and the link member **151** will be described. Note that the connection mechanism of the holding member **505** and link member **151** described below is substantially the same mechanism as the connection mechanism of the holding member **505** and link member **651**. FIGS. 22A and 22C are perspective views illustrating the one end side of the holding member **505** in the front-and-rear direction. FIGS. 22B and 22D are perspective views illustrating the other end side of the holding member **505** in the front-and-rear direction.

[0146] The holding member **505** is provided with the lens attaching portion **701** to which the lens array **506** is attached, the spring attaching portion **661** to which a coil spring **547** is attached, the spring attaching portion **662** to which a coil spring **548** is attached, the pin attaching portion **632** to which the abutting pin **514** is attached, and the pin attaching portion **633** to which the abutting pin **515** is attached, as illustrated in FIG. 22A. The holding member **505** is a resin molded article where the lens attaching portion **701**, circuit board attaching portion **702** (omitted from illustration), spring attaching portion **661**, and spring attaching portion **662**, have been integrally molded by injection molding. The spring attaching portion **661** is disposed to the one end side of the lens attaching portion **701** in the front-and-rear direction, and the pin attaching portion **632** is disposed further to the end side of the spring attaching portion **661** in the holding member **505**. The spring attaching portion **662** is disposed to the other end side of the lens attaching portion **701** in the front-and-rear direction, and the pin attaching portion **633** is disposed further to the other end side of the spring attaching portion **662** in the holding member **505**. The places where the lens attaching portion **701**, spring attaching portion **661**, and pin attaching portion **632** are formed in the holding member **505** are region C, region B, and region A in FIG. 22A. The holding member **505** that is a resin article integrally formed by injection molding is subjected to upwards biasing force from below, by the protrusion **155** of the link member **151** via the coil spring **547**, at a position to the front side of the lens array **506** but to the rear side of the abutting pin **514**. Also, the places where the lens attaching portion **701**, spring attaching portion **662**, and pin attaching portion **633** are formed in the holding member **505** are region C, region D, and region E in FIG. 22C. Biasing force is applied to the holding member **505** from the lower side toward the upper side by the protrusion **156** of the link member **152** via the coil spring **548**, at a position to the rear side from the lens array **506** but to the front side from the abutting pin **515**.

[0147] First, description will be made regarding the spring attaching portion **661**. The spring attaching portion **661** includes a first wall portion **751**, a second wall portion **752**, a first engaging portion **543**, and a second engaging portion **544**. The first wall portion **751** is disposed to the one end side of the holding member **505** in the left-and-right direction, and the second wall portion **752** is disposed to the other end side of the holding member **505** in the left-and-right direction. The first wall portion **751** and second wall portion **752** are disposed to both sides of the abutting pin **514** in the left-and-right direction, in the present embodiment. The first

wall portion 751 and second wall portion 752 each have an inner wall face facing each other, as illustrated in FIG. 22A. An opening 755 is formed in the first wall portion 751, and an opening 756 is formed in the second wall portion 752. The opening 755 and the opening 756 are slots extending in the vertical direction. The protrusion 155 is inserted to the opening 755 and opening 756. The protrusion 155 is not fit to the opening 755 and opening 756, and is inserted with a gap of around 0.5 mm even at the narrowest place in the front-and-rear direction. Accordingly, the direction of movement of the protrusion 155 is guided in the vertical direction by the opening 755 and opening 756, without any great frictional force being applied by the inner wall faces of the opening 755 and opening 756.

[0148] FIG. 22B is a diagram where the first wall portion 751 has been omitted from illustration in FIG. 22A. The first engaging portion 543 and second engaging portion 544 are disposed between the first wall portion 751 and second wall portion 752 in the left-and-right direction. This first engaging portion 543 and second engaging portion 544 also are respectively disposed on the front side and rear side of the opening 755 and opening 756 in the front-and-rear direction. The first engaging portion 543 is disposed further toward the end portion side of the holding member 505 than the second engaging portion 544 in the present embodiment. The first engaging portion 543 and second engaging portion 544 are protrusions that protrude downwards from connecting portions connecting the first wall portion 751 and second wall portion 752 of the holding member 505. One end of the coil spring 547 is engaged with the first engaging portion 543, and the other end of the coil spring 547 is engaged with the second engaging portion 544. The first engaging portion 543 and second engaging portion 544 are disposed at the spring attaching portion 661 such that the coil spring 547 that is engaged at the first engaging portion 543 and second engaging portion 544 traverses the opening 755 and opening 756.

[0149] The first engaging portion 543 and second engaging portion 544 are disposed at positions that are different from each other in the vertical direction. The first engaging portion 543 is disposed closer to the photosensitive drum 103 side than the second engaging portion 544 in the present embodiment. Note that an arrangement may be made where the first engaging portion 543 and second engaging portion 544 are generally the same in the vertical direction, and the second engaging portion 544 may be disposed closer to the photosensitive drum 103 side than the first engaging portion 543.

[0150] The protrusion 155 is inserted to the opening 756 of the second wall portion 752 from the outer wall face side thereof, passes beneath the coil spring 547 strung between the first engaging portion 543 and second engaging portion 544, and is inserted into the opening 755 of the first wall portion 751, as illustrated in FIG. 22B.

[0151] Next, description will be made regarding the spring attaching portion 662. The spring attaching portion 662 includes a third wall portion 753, a fourth wall portion 754, a third engaging portion 545, and a fourth engaging portion 546, as illustrated in FIG. 22C. The third wall portion 753 is disposed to the one end side of the holding member 505 in the left-and-right direction, and the fourth wall portion 754 is disposed to the other end side of the holding member 505 in the left-and-right direction. The third wall portion 753 and fourth wall portion 754 are disposed to both sides of the abutting pin 515 in the left-and-right direction, in the present

embodiment. The first wall portion 751 and the third wall portion 753 are disposed on the same side in the left-and-right direction, i.e., the first wall portion 751 and the third wall portion 753 are disposed on the right side of the holding member 505 in the left-and-right direction. The second wall portion 752 and the fourth wall portion 754 are disposed on the same side in the left-and-right direction, i.e., the second wall portion 752 and the fourth wall portion 754 are disposed on the left side of the holding member 505 in the left-and-right direction.

[0152] The third wall portion 753 and fourth wall portion 754 each have an inner wall face facing each other, as illustrated in FIG. 22C. An opening 757 is formed in the third wall portion 753, and an opening 758 is formed in the fourth wall portion 754. The opening 757 and the opening 758 are slots extending in the vertical direction. The protrusion 156 is inserted to the opening 757 and opening 758. The protrusion 156 is not fit to the opening 757 and opening 758, and is inserted with a gap of around 0.5 mm even at the narrowest place in the front-and-rear direction. Accordingly, the direction of movement of the protrusion 156 is guided in the vertical direction by the opening 757 and opening 758, without any great frictional force being applied by the inner wall faces of the opening 757 and opening 758.

[0153] FIG. 22D is a diagram where the third wall portion 753 has been omitted from illustration in FIG. 22C. The third engaging portion 545 and fourth engaging portion 546 are disposed between the third wall portion 753 and fourth wall portion 754 in the left-and-right direction. This third engaging portion 545 and fourth engaging portion 546 also are respectively disposed on the front side and rear side of the opening 757 and opening 758 in the front-and-rear direction. The fourth engaging portion 546 is disposed further toward the end portion side of the holding member 505 than the third engaging portion 545 in the present embodiment. The third engaging portion 545 and fourth engaging portion 546 are protrusions that protrude downwards from connecting portions connecting the third wall portion 753 and fourth wall portion 754 of the holding member 505. One end of the coil spring 548 is engaged with the third engaging portion 545, and the other end of the coil spring 548 is engaged with the fourth engaging portion 546. The third engaging portion 545 and fourth engaging portion 546 are disposed at the spring attaching portion 662 such that the coil spring 548 that is engaged at the third engaging portion 545 and fourth engaging portion 546 traverses the opening 757 and opening 758.

[0154] The third engaging portion 545 and fourth engaging portion 546 are disposed at positions that are different from each other in the vertical direction. The third engaging portion 545 is disposed closer to the photosensitive drum 103 side than the fourth engaging portion 546 in the present embodiment. Note that an arrangement may be made where the third engaging portion 545 and fourth engaging portion 546 are generally the same in the vertical direction, and the fourth engaging portion 546 may be disposed closer to the photosensitive drum 103 side than the third engaging portion 545.

[0155] The protrusion 156 is inserted to the opening 758 of the fourth wall portion 754 from the outer wall face side thereof, passes beneath the coil spring 548 strung between the third engaging portion 545 and fourth engaging portion 546, and is inserted into the opening 757 of the third wall portion 753, as illustrated in FIG. 22D. Although a coil

spring has been described as an example of the coil spring 547 and coil spring 548 in the present embodiment, plate springs may be used instead.

[0156] Next, the operations of the protrusion 155 provided to the link member 151 on the coil spring 547, and the operations of the protrusion 156 provided to the link member 152 on the coil spring 548, will be described with reference to FIGS. 23A through 23C. The operations of the protrusion 155 on the coil spring 547 and the operations of the protrusion 156 on the coil spring 548 are substantially the same, so the operations of the protrusion 156 on the coil spring 548 will be exemplified in FIGS. 23A through 23C.

[0157] FIG. 23A is a diagram illustrating a state where the abutting pin 515 provided to the holding member 505 is retracted from the abutting face 551 of the drum unit 518. FIG. 23B is a diagram illustrating the point of the abutting pin 515 abutting the abutting face 551 of the drum unit 518. FIG. 23C is a diagram illustrating a state where the link member 152 has pivoted in the counter-clockwise direction from the state in FIG. 23B.

[0158] Upon the sliding portion 525 moving by sliding in the state in FIG. 23A, the link member 152 pivots in the counter-clockwise direction in conjunction therewith, and the protrusion 156 moves upwards. At this time, the protrusion 156 presses the coil spring 548 upwards. The protrusion 156 pressing the coil spring 548 upwards causes upward force to be applied to the holding member 505 via the third engaging portion 545 and fourth engaging portion 546. The abutting pin 515 is not in contact with the drum unit 518, and there is no force countering the force of the protrusion 156 pressing the coil spring 548, other than the gravity acting on the optical print head 105. Accordingly, when the upward force acting on the third engaging portion 545 and the fourth engaging portion 546 exceeds the gravity acting on the optical print head 105, the holding member 505 moves upwards by the force acting on the third engaging portion 545 and fourth engaging portion 546. Now, an arrangement may be made where, when the holding member 505 is in the retracted position, the lower end of the abutting pin 515 (514) and the holding member 505 are supported by the apparatus main body, and the protrusion 156 (155) of the link member 152 (151) is not in contact with the coil spring 548 (547).

[0159] When the holding member 505 moves upwards, the abutting pin 515 abuts the abutting face 551 of the drum unit 518 as illustrated in FIG. 23B. In FIG. 23B, the optical print head 105 is situated at the exposure position, but the biasing force acting to the optical print head 105 to bias the optical print head 105 against the drum unit 518 is insufficient. Accordingly, the movement mechanism 140 according to the present embodiment has a configuration where the link member 152 is capable of further pivoting from the state in FIG. 23B, to apply the biasing force to the optical print head 105.

[0160] Further pivoting the link member 152 in the counter-clockwise direction from the state in FIG. 23B does not change the position of the holding member 505, since the abutting pin 515 is already abutting the abutting face 551 of the drum unit 518. On the other hand, the protrusion 156 moves upwards, so the coil spring 548 is pressed by the protrusion 156 passing between the third engaging portion 545 and fourth engaging portion 546, and flexes and stretches as illustrated in FIG. 23C.

[0161] The state in FIG. 23C corresponds to the state of the cover 558 in FIGS. 19C and 19D. That is to say, the sliding portion 525 is in a state where there is no further movement by sliding toward the front side. Accordingly, the link member 152 does not pivot further in the counter-clockwise direction from the state in FIG. 23C, since the sliding portion 525 does not move by sliding, and the protrusion 156 does not move upwards and is stationary at the position in FIG. 23C. The contracting force of the coil spring 548 acts on the third engaging portion 545 and fourth engaging portion 546 in this state. A force component of the contracting force of the coil spring 548 acting on the third engaging portion 545 and fourth engaging portion 546 is directed upwards, so biasing force acts on the holding member 505 to bias the holding member 505 toward the drum unit 518 side, and the holding member 505 is biased against the drum unit 518 via the abutting pin 515.

[0162] As described above, the third engaging portion 545 is disposed closer to the photosensitive drum 103 side than the fourth engaging portion 546, so normal force in the direction of the arrow N acts on the coil spring 548 from the protrusion 156. The force component of the normal force in the direction of the arrow N acts on the holding member 505. Accordingly, force toward the rear side in the front-and-rear direction acts on the abutting pin 515, and the abutting pin 515 abutting the abutting face 551 is biased against and abuts the rear-side wall face 596 at the deepest part of the fitting portion 685. The reason why the first engaging portion 543 is disposed closer to the photosensitive drum 103 side than the second engaging portion 544 is also the same.

Cleaning Mechanism

[0163] An exposing unit such as the optical print head 105, for example, is disposed between the charger 104 and developing unit 106 in the image forming apparatus 1. Accordingly, there are cases where the light emission faces of the lens array 506 that the optical print head 105 has are contaminated by toner falling from the photosensitive drum 103 or developing unit 106. Contamination of the light emission faces of the lens array 506 can partially shield light emitted from the light-emitting elements, and is a factor leading to deterioration in image quality of output images. Accordingly, the light emission faces of the optical print head 105 are preferably periodically cleaned.

[0164] FIG. 24A is a schematic perspective view of the cleaning member 572 used for cleaning the light emission faces of the lens array 506. The longitudinal direction and widthwise direction are defined as illustrated in FIG. 24A here. The cleaning member 572 has a gripping portion 575 at one end side (rear end side) of the cleaning member 572 in the longitudinal direction. A rubbing portion 574 is provided on the lower side of the cleaning member 572, at the other end side (tip side) in the longitudinal direction of the cleaning member 572, which will be described later. FIG. 24B illustrates a state in which the cleaning member 572 is inserted into the opening 700 provided to the first support portion 527, and the rubbing portion 574 is cleaning the light emission faces of the lens array 506. In this state, the longitudinal direction matches the front-and-rear direction along the rotational axis direction of the photosensitive drum 103, and the widthwise direction matches a direction orthogonal to the rotational axis direction of the photosensitive drum 103 and the optical axis direction of the lenses.

Cleaning of the light emission faces of the lens array 506 using the cleaning member 572 is performed in a case where the optical print head 105 is at the retracted position, as illustrated in FIG. 24B. That is to say, the term retracted position as used here means a cleaning position for cleaning the light emission faces of the lens array 506. The opening 700 guides rubbing portion 574 of the cleaning member 572 that has been inserted onto the light emission faces of the lens array 506 of the optical print head 105 at the retracted position. A worker such as a user or service staff or the like, for example, grips and operates the gripping portion 575 provided to the rear end side of the cleaning member 572 (extracting and inserting as to the opening 700).

[0165] FIG. 25A is a diagram viewing the cleaning member 572 from below, and FIG. 25B is a cross-sectional view where the cleaning member 572 has been cut along a plane perpendicular to the rotational axis of the photosensitive drum 103. FIG. 26 is a schematic perspective view of the front side of the optical print head 105. Protruding portions 580 that extend in the rotational axis direction of the photosensitive drum 103 and protrude to the right side and the left side (both directions intersecting the rotational axis direction of the photosensitive drum 103 and the lens optical axis direction) are formed to the upper side of the holding member 505, and the protruding portion 580 forms a gap 579, as illustrated in FIG. 26. The cleaning member 572 has the rubbing portion 574, engaging portions 576, lower-side protruding portions 577, and an upper-side protruding portion 578, as illustrated in FIGS. 25A and 25B.

[0166] The rubbing portion 574 is provided to the tip side (the other end side in the rotational axis direction of the photosensitive drum 103) of the cleaning member 572 at the lower side thereof. The rubbing portion 574 is an unwoven fabric formed of fibers of cotton, nylon, polyester, or the like, for example, and wipes off and cleans contamination of toner and so forth that has fallen onto the light emission faces of the lens array 506. The rubbing portion 574 is not restricted to unwoven fabric, and may be a rubber elastically deformable member such as a sponge or elastomer for example, which cleans by scraping off contamination of toner and so forth that has fallen onto the light emission faces of the lens array 506.

[0167] The engaging portions 576 of the cleaning member 572 inserted into the opening 700 protrude toward a position facing the lower side of the protruding portions 580 from the outer side of the protruding portions 580 in the widthwise direction, i.e., toward inside of the gaps 579, and engage the protruding portions 580. Tapered portions 581 are formed at the front end (the end portion at front side) of the protruding portions 580, and are inclined further downwards the closer to the gaps 579. These tapered portions 581 are the rear end (end portion at rear side) of the protruding portion 580, and serve to guide the engaging portions 576 of the cleaning member 572, inserted into the opening 700 and moving downstream in the insertion direction, into the gaps 579.

[0168] The lower-side protruding portions 577 that are an example of an abutting portion that the cleaning member 572 has is formed along the longitudinal direction, so as to face the upper side of the holding member 505 at the lower side of the cleaning member 572. FIG. 27A is a cross-sectional view taken at the opening 700 into which the cleaning member 572 has been inserted, in a direction perpendicular to the rotational axis of the photosensitive drum 103, in a state where the cleaning member 572 is

inserted to the opening 700. FIG. 27B is a cross-sectional view of the cleaning member 572 engaging the gaps 579 of the optical print head 105, taken along a direction perpendicular to the rotational axis of the photosensitive drum 103, as viewed from the front side.

[0169] Movement of the cleaning member 572 in directions orthogonal to the longitudinal direction is restricted by the cleaning member 572 being loosely fit to the inner side of the opening 700 with a gap of around 0.5 mm therebetween, as illustrated in FIG. 27A. That is to say, movement of the cleaning member 572 inserted into the opening 700 is restricted by the opening 700 to movement in the direction following the rotational axis direction of the photosensitive drum 103 (front-and-rear direction). Accordingly, the downstream-side end portions (end portion at tip side) of the engaging portions 576 of the cleaning member 572, which is inserted into the opening 700 and moves toward the downstream side in the insertion direction, engage upstream-side end portions (end portion at one end side) of the protruding portions 580 of the optical print head 105 situated at the retracted position, which is the cleaning position.

[0170] The position of the cleaning member 572 engaged with the optical print head 105 is a position where the rubbing portion 574 comes into contact with the light emission faces of the lens array 506. The optical print head 105 is situated at the retracted position at this time. The retracted position of the optical print head 105 is the position of the optical print head 105 in a state where the lower face of the holding member 505 (optical print head 105), moving toward the lower side from the exposure position, abuts from above in the vertical direction the first seating face 586 (serving as an example of a first abutting portion) and a second seating face 587 (serving as an example of a second abutting portion) that together serve as an example of a striking portion (stopping mechanism), as described earlier. That is to say, the light emission faces of the lens array 506 that the holding member 505 abutting the first seating face 586 and second seating face 587 has are positioned so as to be overlaid on the movement path of the rubbing portion 574 provided to the cleaning member 572 that is inserted to and extracted from the opening 700. Note that the first seating face 586 (and second seating face 587) preferably is integrally formed with the first support portion 527 (and second support portion 528), but may be formed as separate members. Note that for the striking portion (stopping mechanism) serving to bring the optical print head 105 to the retracted position, it is sufficient for the first support portion 527 to have the first seating face 586, at the least. That is to say, a configuration may be made where the first support portion 527 has the first seating face 586 and the second support portion 528 does not have the second seating face 587. The reason is that if the first support portion 527 does not have the first seating face 586, one end side of the holding member 505 may flex downward under its own weight, and the light emission face of the lens array 506 in close proximity with the opening 700 may not come into contact with the rubbing portion 574 of the cleaning member 572.

[0171] Another feature of the opening 700 and cleaning member 572 is that the opening 700 and the cleaning member 572 will not fit to each other if inserting the cleaning member 572 to the opening 700 is attempted in a state where the cleaning member 572 is vertically inverted, for example. That is to say, the opening 700 prevents the

worker such as the user, service staff, or the like, from erroneously inserting the cleaning member 572 into the opening 700 in a vertically inverted state.

[0172] It can be seen from FIG. 27B that the lower-side protruding portions 577 abut the upper face of the lens attaching portions 701 formed to the upper side of the holding member 505 when the cleaning member 572 is inserted from the opening 700. Accordingly, a gap is formed between the lower side of the cleaning member 572 inserted from the opening 700 and the light emission faces of the lens array 506. Thus, the only portion where the cleaning member 572 that has been inserted through the opening 700 and is engaging the optical print head 105 comes into contact with the light emission faces of the lens array 506 is the rubbing portion 574, thereby preventing contact between portions of the cleaning member 572 other than the rubbing portion 574 with the light emission faces of the lens array 506.

[0173] FIG. 28 is a cross-sectional view where the abutting pin 514 has been cut away in a direction perpendicular to the rotational axis direction of the photosensitive drum 103, illustrated along with the abutting pin 515. It can be seen in FIG. 28 that the length of the abutting pin 514 protruding from the upper side of the holding member 505 is shorter than the length of the abutting pin 515 protruding from the upper side of the holding member 505, and that the upper end of the abutting pin 514 is situated lower than the position of the light emission faces of the lens array 506. The reason why the position of the upper end of the abutting pin 514 is situated lower than the position of the light emission faces of the lens array 506 will be described with reference to FIG. 28.

[0174] One reason why the holding member 505 has the abutting pin 514 and abutting pin 515 is to form a gap between the light emission faces of the lens array 506 and the photosensitive drum 103, as described earlier. As for the structure of the abutting pin 514 and abutting pin 515 to achieve this, a structure may be made where the length of the abutting pin 514 protruding from the upper side of the holding member 505 is around the same as that of the abutting pin 515, i.e., the position of the upper end of the abutting pin 514 is above the light emission faces of the lens array 506. However, in a case of making this configuration, the abutting pin 514 exists on the movement path of the cleaning member 572 inserted into the opening 700 from the outer side of the main body of the image forming apparatus 1, and the cleaning member 572 and abutting pin 514 will come into contact when the cleaning member 572 is inserted into the opening 700 and moves to the downstream side in the direction of insertion. Accordingly, sufficiently cleaning the light emission faces of the lens array 506 will be difficult. It is from this reason that the length of the abutting pin 514 protruding from the upper side of the holding member 505 is shorter than that of the abutting pin 515 protruding from the upper side of the holding member 505, and that the upper end of the abutting pin 514 is situated lower than the position of the light emission faces of the lens array 506 as illustrated in FIG. 28.

[0175] As described above, the image forming apparatus 1 according to the first embodiment has the first seating face 586 and second seating face 587 serving as an example of a striking portion (stopping mechanism). The holding member 505 of the optical print head 105 that is moved from the exposure position toward the retracted position (cleaning

position) by the movement mechanism 140 (640, 840, 940) strikes the first seating face 586 and second seating face 587 from above in the vertical direction. Accordingly, the light emission faces of the lens array 506 that the holding member 505 abutting the first seating face 586 and second seating face 587 has, are situated overlaying the movement path of the rubbing portion 574 provided to the cleaning member 572 inserted into the opening 700. Accordingly, the light emission faces of the lens array 506 can be sufficiently cleaned by the cleaning member 572 being inserted into the opening 700.

Second Embodiment

[0176] The mechanism bringing the optical print head 105 to the retracted position (cleaning position) is not restricted to the above-described mechanism where the holding member 505 comes into contact with the first seating face 586 and second seating face 587 described earlier, thereby restricting downward movement of the holding member 505. A mechanism such as described next may be made.

[0177] FIG. 29A1 illustrates a structure using the slot 691, which is an elongated opening provided to the sliding portion 525, as an example of a striking portion (stopping mechanism). The mechanism illustrated in FIG. 29A1 is a mechanism that stops sliding movement of the sliding portion 525 that moves by sliding along with movement of the optical print head 105 from the exposure position toward the retracted position, thereby bringing the optical print head 105 to the retracted position. The sliding portion 525 in FIG. 29A1 has the slot 691. The slot 691 has an abutting portion 591. Out of the edges that the slot 691 has, the abutting portion 591 is formed to the edge at the front side.

[0178] The slot 691 is formed in the sliding portion 525, and accordingly moves along with the sliding movement of the sliding portion 525. The support shaft 531 and abutting portion 591 are disposed facing each other on the rotational axis of the photosensitive drum 103. The support shaft 531 is fixed to the third support portion 526 by the E-type snap ring 533, and is loosely fit to the slot 691 with a gap around 0.1 to 0.5 mm in the vertical direction, for example. That is to say, sliding movement of the sliding portion 525 is restricted by the support shaft 531, and movement by sliding can be performed within the range of the slot 691 (within the opening) in the front-and-rear direction. Note that support shaft 531 is disposed toward the rear side from the abutting portion 591 of the slot 691 when the cover 558 is in a closed state. Accordingly, the abutting portion 591 of the slot 691 and the support shaft 531 do not come into contact until the cover 558 is in an open state.

[0179] The range over which the sliding portion 525 can move by sliding can be changed by changing the range of the slot 691 in the rotational axis direction of the photosensitive drum 103 in the direction of the arrow X as illustrated in FIG. 29A2. For example, the range of the slot 691 in the front-and-rear direction is narrowed as illustrated in FIG. 29A2, so that the edge of the slot 691 toward the front side is closer to the support shaft 531 as compared with FIG. 29A1. Accordingly, the distance in the vertical direction from the third support portion 526 to the holding member 505 when the optical print head 105 is in the retracted position is greater than the distance in the vertical direction from the third support portion 526 to the holding member 505 when the optical print head 105 is in the retracted position before narrowing the range of the slot 691.

[0180] According to the above configuration, when the sliding portion 525 moves by sliding from the front side toward the rear side, the support shaft 531 abuts the end portion at the front side of the slot 691 in the opposite direction as to the direction of sliding movement (direction from rear side toward front side), sliding movement of the sliding portion 525 and pivoting of the link member 651 stop, and the holding member 505 is at the retracted position. Accordingly, the light emission faces of the lens array 506 that the holding member 505 has are situated overlaying the movement path of the rubbing portion 574 of the cleaning member 572 inserted through and extracted from the opening 700.

[0181] As described above, the image forming apparatus 1 according to the second embodiment uses the slot 691 of the sliding portion 525 as an example of the striking portion (stopping mechanism). The slot 691 functions to stop sliding movement of the sliding portion 525 moving the optical print head 105 from the exposure position to the retracted position, to bring the optical print head 105 to the retracted position. Accordingly, the light emission faces of the lens array 506 of the holding member 505 that has been brought to the retracted position that is the cleaning position, are situated on the movement path of the rubbing portion 574 provided to the cleaning member 572 that is inserted to and extracted from the opening 700. Accordingly, the light emission faces of the lens array 506 can be sufficiently cleaned by inserting and extracting the cleaning member 572 to and from the opening 700.

Third Embodiment

[0182] The mechanism bringing the optical print head 105 to the retracted position may be a mechanism where pivoting of the link member 651 serving as an example of a link portion is stopped using an abutting member 982 as an example of the striking portion (stopping mechanism), as illustrated in FIG. 29B. This mechanism will be described in detail with reference to FIG. 29B. FIG. 29B is a diagram for describing the striking portion (stopping mechanism) according to the third embodiment.

[0183] The abutting member 982 serving as an example of the striking portion (stopping mechanism) is fixed to the third support portion 526 as illustrated in FIG. 29B. The abutting member 982 is, for example, a cylindrical protrusion, erected on the sliding portion 525 side at the third support portion 526. The abutting member 982 is disposed facing the bearing 610 that the link member 651 has, in the rotational axis direction of the photosensitive drum 103. When the bearing 610 that the link member 651 has abuts the abutting member 982 due to movement of the sliding portion 525 from the front side toward the rear side, sliding movement of the sliding portion 525 and pivoting of the link member 651 stop, and the optical print head 105 is at the retracted position. Note that abutting member 982 is disposed further toward the rear side from the bearing 610 of the link member 651 when the cover 558 is in a closed state. Accordingly, the bearing 610 and the abutting member 982 do not come into contact until the cover 558 is in an open state.

[0184] Note that the farther to the front side the abutting member 982 is positioned on the third support portion 526, the greater the distance is in the vertical direction from the third support portion 526 to the holding member 505 when the optical print head 105 is in the retracted position. Also

note that while the abutting member 982 has been described as being fixed to the third support portion 526 here, the member to which the abutting member 982 is fixed is not restricted to the third support portion 526, and may be fixed to any member that does not move relative to the third support portion 526.

[0185] As described above, the image forming apparatus 1 according to the second modification has the abutting member 982 as an example of the striking portion (stopping mechanism). The abutting member 982 stops pivoting of the link member 651 that moves the holding member 505 from the exposure position to the retracted position while pivoting, and brings the holding member 505 to the retracted position. Accordingly, the light emission faces of the lens array 506 of the holding member 505 at the retracted position are situated being overlaid on the moving path of the rubbing portion 574 provided to the cleaning member 572 inserted from the opening 700. Accordingly, the light emission faces of the lens array 506 can be sufficiently cleaned by inserting and extracting the cleaning member 572 to and from the opening 700.

[0186] While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0187] This application claims the benefit of Japanese Patent Application No. 2017-119004, filed Jun. 16, 2017, which is hereby incorporated by reference herein in its entirety.

What is claimed is:

1. An image forming apparatus, comprising:
 - a photosensitive drum configured to be capable of rotating as to an apparatus main body;
 - an optical print head having a light emission face from which light to expose the photosensitive drum is emitted;
 - a movement mechanism configured to move the optical print head from an exposure position, where the light emission face exposes the photosensitive drum, further away from the photosensitive drum than the exposure position;
 - an insertion portion from which a rod-shaped cleaning member that rubs and cleans the light emission face is inserted by a worker from a side face of the apparatus main body, in the longitudinal direction of the optical print head; and
 - a striking portion configured to be struck by the optical print head being moved from the exposure position by the movement mechanism, in the direction of the movement, and to stop movement of the optical print head so that the position of the light emission face is on a movement path of the cleaning member that is inserted through the insertion portion and is moved.
2. The image forming apparatus according to claim 1, wherein the optical print head is provided on the lower side from the rotational axis direction of the photosensitive drum and exposes the photosensitive drum from below, and wherein the striking portion is disposed at one end of the optical print head in the longitudinal direction, at an

- opposite side of the optical print head from the side where the photosensitive drum is disposed.
3. The image forming apparatus according to claim 1, wherein the striking portion and the insertion portion are integrally-formed molded article.
 4. The image forming apparatus according to claim 1, wherein one end side of the movement mechanism in the longitudinal direction is attached to a support member where the insertion portion and the striking portion have been formed, and wherein the support member is fixed to a side plate disposed on a front face side of a casing making up the apparatus main body.
 5. The image forming apparatus according to claim 1, wherein the optical print head is disposed on the lower side from a rotational axis of the photosensitive drum, and exposes the photosensitive drum from below, wherein the striking portion includes a first striking portion that is situated at the lower side from one end of the optical print head in the longitudinal direction, and a second striking portion that is situated at the lower side from the other end of the optical print head in the longitudinal direction, and wherein the optical print head, moved by the movement mechanism from the exposure position, strikes the first striking portion and the second striking portion in the direction of movement.
 6. The image forming apparatus according to claim 1, wherein the insertion portion restricts movement of the cleaning member inserted into the insertion portion in a direction intersecting the longitudinal direction.
 7. The image forming apparatus according to claim 4, wherein the insertion portion is a through hole, passing through the support member in the longitudinal direction for insertion of the cleaning member.
 8. The image forming apparatus according to claim 5, wherein the first striking portion and the insertion portion are integrally-formed molded article.
 9. The image forming apparatus according to claim 5, further comprising:
 - a front-side plate disposed on the front face side of the casing making up the apparatus main body; and
 - a rear-side plate disposed on the rear face side of the casing making up the apparatus main body,
 wherein one end side of the movement mechanism in the longitudinal direction is attached to a first support member where the insertion portion and the first striking portion have been formed, wherein the other end side of the movement mechanism in the longitudinal direction is attached to a second support member where the second striking portion has been formed, and wherein the first support member is fixed to the front-side plate, and the second support member is fixed to the rear-side plate.
 10. An image forming apparatus, comprising:
 - a photosensitive drum configured to be capable of rotating as to an apparatus main body;
 - an optical print head having a light emission face from which light to expose the photosensitive drum is emitted;
 - a sliding portion configured to move by sliding in the longitudinal direction of the optical print head;
 - a link portion of which one end side is pivotably attached to the sliding portion and an other end side is pivotably attached to the optical print head, and that is configured to pivot in conjunction with the sliding portion moving by sliding, to move the optical print head from an exposure position, where the light emission face exposes the photosensitive drum, further away from the photosensitive drum than the exposure position;
 - an insertion portion from which a rod-shaped cleaning member that rubs and cleans the light emission face is inserted by a worker from a side face of the apparatus main body in the longitudinal direction; and
 - a striking portion configured to stop sliding movement of the sliding portion and pivoting of the link portion, by the sliding portion moving by sliding striking in the direction of sliding movement,
 wherein the light emission face is situated on a movement path of the cleaning member that is inserted through the insertion portion and is moved, in a state where the sliding portion has struck the striking portion.
 11. The image forming apparatus according to claim 10, further comprising:
 - a slide supporting portion configured to support the sliding portion so as to be capable of sliding movement, wherein an elongated hole is formed in the sliding portion, passing through in a perpendicular direction perpendicular to both the longitudinal direction and the direction of the optical print head being moved from the exposure position, and extending in the longitudinal direction,
 - wherein one end side of the slide supporting portion is fixed to a front-side plate provided to the front face side of the casing making up the apparatus main body and the other end side of the slide supporting portion is fixed to a rear-side plate disposed to the rear face side of the casing making up the apparatus main body, the slide supporting portion being configured to support the sliding portion so as to be capable of moving by sliding, via a shaft member passed through the opening,
 - and wherein the striking portion is formed on the shaft member, with the sliding motion of the sliding portion stopping by an edge of the opening striking the striking portion in the direction of sliding movement.
 12. The image forming apparatus according to claim 11, wherein the insertion portion is provided to one end side of the slide supporting portion in the longitudinal direction.
 13. The image forming apparatus according to claim 11, wherein the insertion portion restricts movement, in a direction intersecting the longitudinal direction, of the cleaning member inserted through the insertion portion.
 14. An image forming apparatus, comprising:
 - a photosensitive drum configured to be capable of rotating as to an apparatus main body;
 - an optical print head having a light emission face from which light to expose the photosensitive drum is emitted;
 - a sliding portion configured to move by sliding in the longitudinal direction of the optical print head;
 - a link portion of which one end side is pivotably attached to the sliding portion and an other end side is pivotably attached to the optical print head, and that is configured to pivot in conjunction with the sliding portion moving by sliding, to move the optical print head from an

exposure position, where the light emission face exposes the photosensitive drum, further away from the photosensitive drum than the exposure position;

a guide portion from which a rod-shaped cleaning member that rubs and cleans the light emission face is inserted by a worker from a side face of the apparatus main body in the longitudinal direction, and that guides movement of the cleaning member in the longitudinal direction; and

a striking portion configured to stop the pivoting of the link portion and the sliding movement of the sliding portion, by the pivoting link portion striking in the direction of pivoting,

wherein the light emission face is situated on a movement path of the cleaning member that is inserted through the insertion portion and is moved, in a state where the link portion has struck the striking portion.

15. The image forming apparatus according to claim **14**, further comprising:

a slide supporting portion configured to support the sliding portion so as to be capable of sliding movement, wherein an elongated hole is formed in the sliding portion, passing through in a perpendicular direction perpendicular to both the longitudinal direction and the direc-

tion of the optical print head being moved from the exposure position, and extending in the longitudinal direction,

wherein one end side of the slide supporting portion is fixed to a front-side plate provided to the front face side of the casing making up the apparatus main body and the other end side is fixed to a rear-side plate disposed to the rear face side of the casing making up the apparatus main body, the slide supporting portion being configured to support the sliding portion so as to be capable of moving by sliding, via a shaft member passed through the opening,

and wherein the striking portion is provided to the slide supporting portion, with the pivoting of the link portion and the sliding movement of the sliding portion stopping by the pivoting link portion striking in the pivoting direction.

16. The image forming apparatus according to claim **14**, wherein the insertion portion is provided to one end side of the slide supporting portion in the longitudinal direction.

17. The image forming apparatus according to claim **14**, wherein the insertion portion restricts movement, in a direction intersecting the longitudinal direction, of the cleaning member inserted through the insertion portion.

* * * * *