

(19)



(11) Publication number:

SG 187724 A1

(43) Publication date:

28.03.2013

(51) Int. Cl:

E21B 10/567, E21B 10/62;

(12)

Patent Application

(21) Application number: **2013008859**

(71) Applicant:

**BAKER HUGHES INCORPORATED
P.O.BOX 4740, HOUSTON, TX
77210-4740 UNITED STATES OF
AMERICA TX US**

(22) Date of filing: **05.08.2011**

(30) Priority: **US 61/371,554 06.08.2010**

(72) Inventor:

**LYONS, NICHOLAS, J. 808 PECORE
STREET HOUSTON, TX 77009 TX US**

(54) Title:

**SHAPED CUTTING ELEMENTS FOR EARTH-BORING
TOOLS, EARTH-BORING TOOLS INCLUDING SUCH
CUTTING ELEMENTS, AND RELATED METHODS**

(57) Abstract:

Cutting elements for earth-boring tools include a volume of polycrystalline diamond material on an end of a substrate base. The volume of polycrystalline diamond material comprises a generally conical surface, an apex, and flat cutting surface extending from a first point at least substantially proximate the apex to a second point more proximate a lateral side surface of the substrate base. A method of manufacturing such a cutting element is also disclosed.



(51) International Patent Classification:
E21B 10/567 (2006.01) *E21B 10/62* (2006.01)

(21) International Application Number:
PCT/US2011/046820

(22) International Filing Date:
5 August 2011 (05.08.2011)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/371,554 6 August 2010 (06.08.2010) US

(71) Applicant (for all designated States except US): **BAKER HUGHES INCORPORATED** [US/US]; P.O.Box 4740, Houston, TX 77210-4740 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **LYONS, Nicholas, J.** [US/US]; 808 Pecore Street, Houston, TX 77009 (US).

(74) Agents: **RIDDLE, J., Albert** et al.; Intellectual Property Counsel, Baker Hughes Incorporated, P.O.Box 4740, Houston, TX 77210-4740 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SHAPED CUTTING ELEMENTS FOR EARTH-BORING TOOLS, EARTH-BORING TOOLS INCLUDING SUCH CUTTING ELEMENTS, AND RELATED METHODS




FIG. 2

(57) Abstract: Cutting elements for earth-boring tools include a volume of polycrystalline diamond material on an end of a substrate base. The volume of polycrystalline diamond material comprises a generally conical surface, an apex, and flat cutting surface extending from a first point at least substantially proximate the apex to a second point more proximate a lateral side surface of the substrate base. A method of manufacturing such a cutting element is also disclosed.



Published:

- *without international search report and to be republished
upon receipt of that report (Rule 48.2(g))*

-1-

TITLE OF THE INVENTION

5 **SHAPED CUTTING ELEMENTS FOR EARTH-BORING TOOLS,
EARTH-BORING TOOLS INCLUDING SUCH CUTTING ELEMENTS, AND
RELATED METHODS**

PRIORITY CLAIM

 This application claims the benefit of the filing date of United States
Provisional Patent Application Serial Number 61/371,554 filed August 6, 2010, for
10 “SHAPED CUTTING ELEMENTS FOR EARTH-BORING TOOLS,
EARTH-BORING TOOLS INCLUDING SUCH CUTTING ELEMENTS, AND
RELATED METHODS.” The subject matter of this application is related to the
subject matter of co-pending provisional U.S. Patent Application Serial
No. 61/330,757, which was filed May 3, 2010 and entitled “Improved Gemotries For
15 Cutting Elements And Methods Of Forming Such Cutting Elements.”

TECHNICAL FIELD

 Embodiments of the present invention relate generally to cutting elements that
include a table of superabrasive material (e.g., polycrystalline diamond or cubic boron
20 nitride) formed on a substrate, to earth-boring tools including such cutting elements,
and to methods of forming and using such cutting elements and earth-boring tools.

BACKGROUND

 Earth-boring tools are commonly used for forming (e.g., drilling and
25 reaming) bore holes or wells (hereinafter “wellbores”) in earth formations.
Earth-boring tools include, for example, rotary drill bits, core bits, eccentric bits,
bicenter bits, reamers, underreamers, and mills.

 Different types of earth-boring rotary drill bits are known in the art including,
for example, fixed-cutter bits (which are often referred to in the art as “drag” bits),
30 rolling-cutter bits (which are often referred to in the art as “rock” bits),
diamond-impregnated bits, and hybrid bits (which may include, for example, both
fixed cutters and rolling cutters). The drill bit is rotated and advanced into the
subterranean formation. As the drill bit rotates, the cutters or abrasive structures

-2-

thereof cut, crush, shear, and/or abrade away the formation material to form the wellbore.

5 The drill bit is coupled, either directly or indirectly, to an end of what is referred to in the art as a “drill string,” which comprises a series of elongated tubular segments connected end-to-end that extends into the wellbore from the surface of the formation. Often various tools and components, including the drill bit, may be coupled together at the distal end of the drill string at the bottom of the wellbore being drilled. This assembly of tools and components is referred to in the art as a “bottom hole assembly” (BHA).

10 The drill bit may be rotated within the wellbore by rotating the drill string from the surface of the formation, or the drill bit may be rotated by coupling the drill bit to a downhole motor, which is also coupled to the drill string and disposed proximate the bottom of the wellbore. The downhole motor may comprise, for example, a hydraulic Moineau-type motor having a shaft, to which the drill bit is attached, that may be
15 caused to rotate by pumping fluid (e.g., drilling mud or fluid) from the surface of the formation down through the center of the drill string, through the hydraulic motor, out from nozzles in the drill bit, and back up to the surface of the formation through the annular space between the outer surface of the drill string and the exposed surface of the formation within the wellbore.

20 Rolling-cutter drill bits typically include three roller cones attached on supporting bit legs that extend from a bit body, which may be formed from, for example, three bit head sections that are welded together to form the bit body. Each bit leg may depend from one bit head section. Each roller cone is configured to spin or rotate on a bearing shaft that extends from a bit leg in a radially inward and downward
25 direction from the bit leg. The cones are typically formed from steel, but they also may be formed from a particle-matrix composite material (e.g., a cermet composite such as cemented tungsten carbide). Cutting teeth for cutting rock and other earth formations may be machined or otherwise formed in or on the outer surfaces of each cone. Alternatively, receptacles are formed in outer surfaces of each cone, and inserts formed
30 of hard, wear resistant material are secured within the receptacles to form the cutting elements of the cones. As the rolling-cutter drill bit is rotated within a wellbore, the

-3-

roller cones roll and slide across the surface of the formation, which causes the cutting elements to crush and scrape away the underlying formation.

Fixed-cutter drill bits typically include a plurality of cutting elements that are attached to a face of bit body. The bit body may include a plurality of wings or blades, which define fluid courses between the blades. The cutting elements may be secured to the bit body within pockets formed in outer surfaces of the blades. The cutting elements are attached to the bit body in a fixed manner, such that the cutting elements do not move relative to the bit body during drilling. The bit body may be formed from steel or a particle-matrix composite material (e.g., cobalt-cemented tungsten carbide). In embodiments in which the bit body comprises a particle-matrix composite material, the bit body may be attached to a metal alloy (e.g., steel) shank having a threaded end that may be used to attach the bit body and the shank to a drill string. As the fixed-cutter drill bit is rotated within a wellbore, the cutting elements scrape across the surface of the formation and shear away the underlying formation.

Impregnated diamond rotary drill bits may be used for drilling hard or abrasive rock formations such as sandstones. Typically, an impregnated diamond drill bit has a solid head or crown that is cast in a mold. The crown is attached to a steel shank that has a threaded end that may be used to attach the crown and steel shank to a drill string. The crown may have a variety of configurations and generally includes a cutting face comprising a plurality of cutting structures, which may comprise at least one of cutting segments, posts, and blades. The posts and blades may be integrally formed with the crown in the mold, or they may be separately formed and attached to the crown. Channels separate the posts and blades to allow drilling fluid to flow over the face of the bit.

Impregnated diamond bits may be formed such that the cutting face of the drill bit (including the posts and blades) comprises a particle-matrix composite material that includes diamond particles dispersed throughout a matrix material. The matrix material itself may comprise a particle-matrix composite material, such as particles of tungsten carbide, dispersed throughout a metal matrix material, such as a copper-based alloy.

It is known in the art to apply wear-resistant materials, such as "hardfacing" materials, to the formation-engaging surfaces of rotary drill bits to minimize wear of

those surfaces of the drill bits cause by abrasion. For example, abrasion occurs at the formation-engaging surfaces of an earth-boring tool when those surfaces are engaged with and sliding relative to the surfaces of a subterranean formation in the presence of the solid particulate material (e.g., formation cuttings and detritus) carried by conventional drilling fluid. For example, hardfacing may be applied to cutting teeth on the cones of roller cone bits, as well as to the gage surfaces of the cones. Hardfacing also may be applied to the exterior surfaces of the curved lower end or “shirttail” of each bit leg, and other exterior surfaces of the drill bit that are likely to engage a formation surface during drilling.

The cutting elements used in such earth-boring tools often include polycrystalline diamond cutters (often referred to as “PDCs”), which are cutting elements that include a polycrystalline diamond (PCD) material. Such polycrystalline diamond cutting elements are formed by sintering and bonding together relatively small diamond grains or crystals under conditions of high temperature and high pressure in the presence of a catalyst (such as, for example, cobalt, iron, nickel, or alloys and mixtures thereof) to form a layer of polycrystalline diamond material on a cutting element substrate. These processes are often referred to as high temperature/high pressure (or “HTHP”) processes. The cutting element substrate may comprise a cermet material (*i.e.*, a ceramic-metal composite material) such as, for example, cobalt-cemented tungsten carbide. In such instances, the cobalt (or other catalyst material) in the cutting element substrate may be drawn into the diamond grains or crystals during sintering and serve as a catalyst material for forming a diamond table from the diamond grains or crystals. In other methods, powdered catalyst material may be mixed with the diamond grains or crystals prior to sintering the grains or crystals together in an HTHP process.

Upon formation of a diamond table using an HTHP process, catalyst material may remain in interstitial spaces between the grains or crystals of diamond in the resulting polycrystalline diamond table. The presence of the catalyst material in the diamond table may contribute to thermal damage in the diamond table when the cutting element is heated during use due to friction at the contact point between the cutting element and the formation. Polycrystalline diamond cutting elements in which the catalyst material remains in the diamond table are generally thermally stable up to a

temperature of about 750° Celsius, although internal stress within the polycrystalline diamond table may begin to develop at temperatures exceeding about 350° Celsius. This internal stress is at least partially due to differences in the rates of thermal expansion between the diamond table and the cutting element substrate to which it is bonded. This differential in thermal expansion rates may result in relatively large compressive and tensile stresses at the interface between the diamond table and the substrate, and may cause the diamond table to delaminate from the substrate. At temperatures of about 750° Celsius and above, stresses within the diamond table may increase significantly due to differences in the coefficients of thermal expansion of the diamond material and the catalyst material within the diamond table itself. For example, cobalt thermally expands significantly faster than diamond, which may cause cracks to form and propagate within the diamond table, eventually leading to deterioration of the diamond table and ineffectiveness of the cutting element.

In order to reduce the problems associated with different rates of thermal expansion in polycrystalline diamond cutting elements, so-called “thermally stable” polycrystalline diamond (TSD) cutting elements have been developed. Such a thermally stable polycrystalline diamond cutting element may be formed by leaching the catalyst material (e.g., cobalt) out from interstitial spaces between the diamond grains in the diamond table using, for example, an acid. All of the catalyst material may be removed from the diamond table, or only a portion may be removed. Thermally stable polycrystalline diamond cutting elements in which substantially all catalyst material has been leached from the diamond table have been reported to be thermally stable up to a temperatures of about 1200° Celsius. It has also been reported, however, that such fully leached diamond tables are relatively more brittle and vulnerable to shear, compressive, and tensile stresses than are non-leached diamond tables. In an effort to provide cutting elements having diamond tables that are more thermally stable relative to non-leached diamond tables, but that are also relatively less brittle and vulnerable to shear, compressive, and tensile stresses relative to fully leached diamond tables, cutting elements have been provided that include a diamond table in which only a portion of the catalyst material has been leached from the diamond table.

BRIEF DESCRIPTION OF THE DRAWINGS

While the specification concludes with claims particularly pointing out and distinctly claiming what are regarded as embodiments of the present invention, various features and advantages of this invention may be more readily ascertained from the following description of example embodiments of the invention provided with reference to the accompanying drawings, in which:

FIG. 1 is a side perspective view of an embodiment of a cutting element of the invention;

FIG. 2 is a perspective view of the cutting element shown in FIG. 1, taken from a viewpoint approximately forty-five degrees (45°) clockwise of that of FIG. 1;

FIG. 3 is a front perspective view of the cutting element shown in FIG. 1, taken from a viewpoint approximately ninety degrees (90°) clockwise of that of FIG. 1;

FIG. 4 is a side perspective view of another embodiment of a cutting element of the invention;

FIG. 5 is a perspective view of the cutting element shown in FIG. 4, taken from a viewpoint approximately forty-five degrees (45°) clockwise of that of FIG. 4;

FIG. 6 is a front perspective view of the cutting element shown in FIG. 4, taken from a viewpoint approximately ninety degrees (90°) clockwise of that of FIG. 4;

FIG. 7 is a perspective view of an embodiment of a fixed-cutter earth-boring rotary drill bit of the invention that includes cutting elements as described herein;

FIG. 8 is a front view of an embodiment of a roller cone earth-boring rotary drill bit of the invention that includes cutting elements as described herein;

FIGS. 9 and 10 are side perspective views of different embodiments of cutting elements of the invention wherein the cutting elements are mounted on a drilling tool and provided with a negative physical back rake angle (e.g., physical forward rake) and a negative effective back rake angle (e.g., effective forward rake) relative to a formation surface;

FIGS. 11 and 12 are side perspective views of different embodiments of cutting elements of the invention wherein the cutting elements are mounted on a drilling tool and provided with a positive physical back rake angle (e.g., physical back rake) and a

-7-

positive effective back rake angle (e.g., effective back rake) relative to a formation surface;

FIGS. 13 and 14 are side perspective views of different embodiments of cutting elements of the invention wherein the cutting elements are mounted on a drilling tool and provided with a neutral physical back rake angle (e.g., physical neutral rake) and a positive effective back rake angle (e.g., effective back rake) relative to a formation surface;

FIGS. 15 and 16 are side perspective views of different embodiments of cutting elements of the invention wherein the cutting elements are mounted on a drilling tool and provided with a negative physical back rake angle (e.g., physical forward rake) and a positive effective back rake angle (e.g., effective back rake) relative to a formation surface; and

FIGS. 17 and 18 are side perspective views of different embodiments of cutting elements of the invention wherein the cutting elements are mounted on a drilling tool and provided with a negative physical back rake angle (e.g., physical forward rake) and a neutral effective back rake angle (e.g., effective neutral rake) relative to a formation surface.

MODE(S) FOR CARRYING OUT THE INVENTION

The illustrations presented herein are not meant to be actual views of any particular cutting element, earth-boring tool, or portion of a cutting element or tool, but are merely idealized representations which are employed to describe embodiments of the present invention. Additionally, elements common between figures may retain the same numerical designation.

As used herein, the term “earth-boring tool” means and includes any tool used to remove formation material and form a bore (e.g., a wellbore) through the formation by way of the removal of the formation material. Earth-boring tools include, for example, rotary drill bits (e.g., fixed-cutter or “drag” bits and roller cone or “rock” bits), hybrid bits including both fixed cutters and roller elements, coring bits, percussion bits, bi-center bits, reamers (including expandable reamers and fixed-wing reamers), and other so-called “hole-opening” tools.

As used herein, the term “apex,” when used in relation to a shaped cutting element, means and includes the most distant point on a cutting tip of a shaped cutting element relative to a center of a basal surface on an opposing side of the cutting element.

5 Referring FIGS. 1-3, an embodiment of the present disclosure includes a cutting element 10 having a longitudinal axis 11, a substrate base 12, and a cutting tip 13. The substrate base 12 may have a generally cylindrical shape. The longitudinal axis 11 may extend through a center of the substrate base 12 in an orientation that may be at least substantially parallel to a lateral side surface 14 of the substrate base 12 (e.g.,
10 in an orientation that may be perpendicular to a generally circular cross-section of the substrate base 12). The lateral side surface 14 of the substrate base may be coextensive and continuous with a generally cylindrical lateral side surface 15 of the cutting tip 13. The cutting tip 13 also includes a generally conical surface 16, an apex 17, and a flat cutting surface 18. A portion of the generally conical surface 16 may extend between
15 the edge of the flat cutting surface 18 and the generally cylindrical lateral side surface 15. The generally conical surface 16 may be defined by an angle ϕ_1 existing between the generally conical surface 16 and a phantom line extending from the generally cylindrical lateral side surface 15 of the cutting tip 13. The angle ϕ_1 may be within a range of from about thirty degrees (30°) to about sixty degrees (60°). The generally
20 conical surface 16 may extend from the generally cylindrical lateral side surface 15 to the apex 17, and may extend to the edges of the flat cutting surface 18. The location of the apex 17 may be centered about the longitudinal axis 11. The flat cutting surface 18 may extend from a location at least substantially proximate the apex 17 to a location on the cutting element 10 at a selected or predetermined distance from the apex 17, such
25 that an angle α_1 between the longitudinal axis 11 and the flat cutting surface 18 may be within a range of from about fifteen degrees (15°) to about ninety degrees (90°). Portions of the cutting tip 13, such as the flat cutting surface 18, may be polished.

In FIGS. 1-3, the angle ϕ_1 is about thirty degrees (30°), the apex 17 of the cutting tip 13 is centered about the longitudinal axis 11, and the flat cutting surface 18
30 extends from the apex 17 to the lateral side surface 14 of the substrate base 12. In turn, the angle α_1 is less than thirty degrees (30°). FIG. 1 illustrates a side perspective view of the cutting element 10 showing the non-symmetrical configuration of the cutting tip

13 about the longitudinal axis 11. FIG. 2, which is a perspective view of the cutting element 10 taken from a viewpoint approximately 45 degrees clockwise of that of FIG. 1, shows the flat cutting surface 18 of the cutting tip 13. FIG. 3 illustrates a front perspective view of the cutting element 10, taken from a viewpoint approximately ninety degrees (90°) clockwise of that of FIG. 1, in which the cutting tip 13 is symmetrical about the longitudinal axis 11.

Referring to FIGS. 4-6, another embodiment of the present disclosure includes a cutting element 20 having a longitudinal axis 21, a substrate base 22, and a cutting tip 23. The substrate base 22 may have a generally cylindrical shape. The longitudinal axis 21 may extend through a center of the substrate base 22 in an orientation that may be at least substantially parallel to a lateral side surface 24 of the substrate base 22 (e.g., in an orientation that may be perpendicular to a generally circular cross-section of the substrate base 22). The lateral side surface 24 of the substrate base 22 may be coextensive and continuous with a generally cylindrical lateral side surface 25 of the cutting tip 23. The cutting tip 23 also includes a generally conical surface 26, an apex 27, and a flat cutting surface 28. A portion of the generally conical surface 26 may extend between the edge of the flat cutting surface 28 and the generally cylindrical lateral side surface 25 of the cutting tip 23. The generally conical surface 26 may be defined by an angle ϕ_2 existing between the generally conical surface 26 and a phantom line extending from the generally cylindrical lateral side surface 25 of the cutting tip 23. The angle ϕ_2 may be within a range of from about thirty degrees (30°) to about sixty degrees (60°). The generally conical surface 26 may extend from the generally cylindrical lateral side surface 25 to the apex 27, and may extend to the edges of the flat cutting surface 28. The location of the apex 27 may be offset from the longitudinal axis 21. The flat cutting surface 28 may extend from a location at least substantially proximate the apex 27 to a location on the cutting element 20 at a selected or predetermined distance from the apex 27, such that an angle α_2 between the longitudinal axis 21 and the flat cutting surface 28 may be within a range of from about fifteen degrees (15°) to about ninety degrees (90°). Portions of the cutting tip 23, such as the flat cutting surface 28, may be polished.

In FIGS. 4-6 the angle ϕ_2 is about thirty degrees (30°), the apex 27 is offset from the longitudinal axis 21, and the flat cutting surface 28 extends from the apex 27

-10-

to a location on the generally conical surface 26 of the cutting tip 23. The angle α_2 is about sixty degrees (60°). The viewing angles represented by FIGS. 4-6 correspond, respectively, to those of FIGS. 1-3.

Each of the cutting tips 13 and 23 may comprise a polycrystalline diamond (PCD) material. Certain regions of the cutting tips 13 and 23, or the entire cutting tips 13 and 23, optionally may be processed (e.g., etched) to remove metal binder from between the interbonded diamond grains of the PCD material of each of the cutting tips 13 and 23, such that each of the cutting tips 13 and 23 are relatively more thermally stable. Each of the cutting tips 13 and 23 may be formed on their respective substrate bases 12 and 22, or each of the cutting tips 13 and 23 and their respective substrate bases 12 and 22 may be separately formed and subsequently attached together. Each of the substrate bases 12 and 22 may be formed from a material that is relatively hard and resistant to wear. As one non-limiting example, the substrate bases 12 and 22 may be at least substantially comprised of a cemented carbide material, such as cobalt-cemented tungsten carbide. Optionally, the cutting tips 13 and 23 may be formed for use without the respective substrate bases 12 and 22 (e.g., the substrate bases 12 and 22 may be omitted from the respective cutting elements 10 and 20). Optionally, an entirety of the cutting elements 10 and 20 (e.g., the cutting tips 13 and 23, and the substrate bases 12 and 22) may comprise a PCD material.

Each of the cutting elements 10 and 20 may be attached to an earth-boring tool such that the respective cutting tips 13 and 23 will contact a surface of a subterranean formation within a wellbore during a drilling or reaming process. FIG. 7 is a simplified perspective view of a fix-cutter rotary drill bit 100, which includes a plurality of the cutting elements 10 and 20 attached to blades 101 on the body of the drill bit 100. In additional embodiments, the drill bit 100 may include only cutting elements 10. In yet further embodiments, the drill bit 100 may include only cutting elements 20. FIG. 8 is a simplified front view of a roller cone rotary drill bit 200, which includes a plurality of the cutting elements 10 and 20 attached to roller cones 201 thereof. In additional embodiments, the drill bit 200 may include only cutting elements 10. In yet further embodiments, the drill bit 200 may include only cutting elements 20.

Referring to FIGS. 9-18, the cutting elements 10 and 20 may each be attached to a portion 400 of the earth-boring tool such that at least a portion of the respective flat

-11-

cutting surfaces 18 and 28 contact a surface 300 of the subterranean formation within the wellbore. The portion 400 of the earth-boring tool may be a portion of a fixed cutter earth-boring rotary drill bit, such as the drill bit 100 depicted in FIG. 7, or a portion of a roller cone earth-boring rotary drill bit, such as the drill bit 200 depicted in FIG. 8. A shape and configuration of each of the cutting elements 10 and 20 may enable versatility in orienting each of the cutting elements 10 and 20 relative to the surface 300 of the subterranean formation.

Referring to FIGS. 9-18, effective back rake angles θ_1 and θ_2 between the respective flat cutting surfaces 18 and 28 and a reference plane 500 at least substantially perpendicular to the surface 300 of the subterranean formation may be negative (i.e., effective forward rake), positive (i.e., effective back rake), or neutral (i.e., effective neutral rake). The effective back rake angles θ_1 and θ_2 may be considered negative where the corresponding flat cutting surfaces 18 and 28 are behind the reference plane 500 in the direction of cutter movement (i.e., the flat cutting surfaces 18 and 28 form an obtuse angle with the surface 300 of the subterranean formation), as depicted in FIGS. 9 and 10. The effective back rake angles θ_1 and θ_2 may be considered positive where the respective flat cutting surfaces 18 and 28 are ahead of the reference plane 500 in the direction of cutter movement (i.e., the flat cutting surfaces 18 and 28 form an acute angle with the surface of the subterranean formation 300), as depicted in FIGS. 11-16. The effective back rake angles θ_1 and θ_2 may be considered neutral where the respective flat cutting surfaces 18 and 28 are parallel with the reference plane 500 (i.e., the flat cutting surfaces 18 and 28 substantially form a right angle with the surface of subterranean formation 300), as depicted in FIGS. 17 and 18. In at least some embodiments, the effective back rake angles θ_1 and θ_2 of the corresponding cutting elements 10 and 20 may be within a range of from about thirty degrees (30°) negative back rake to about forty-five degrees (45°) positive back rake relative to the reference plane 500. Subterranean formation cuttings may be deflected over and across the flat cutting surfaces 18 and 28 in directions that may be up and away from the surface 300 of the subterranean formation.

A magnitude of each of the effective rake angles θ_1 and θ_2 may be at least partially determined by an orientation in which each of the respective cutting elements 10 and 20 is attached to the earth-boring tool. With continued reference to

FIGS. 9-18, each of the cutting elements 10 and 20 may be attached to the earth-boring tool as to include respective physical back rake angles π_1 and π_2 that may be negative (i.e., physical forward rake), positive (i.e., physical back rake), or neutral (i.e., physical neutral rake). The physical back rake angles π_1 and π_2 may be considered negative where at least a portion of the respective longitudinal axes 11 and 21 extending through the respective cutting elements 10 and 20 are behind the reference plane 500 (i.e., the longitudinal axes 11 and 21 form an obtuse angle with the surface of the subterranean formation 300), as in depicted in FIGS. 9, 10, and 15-18 (the vertically opposite physical back rake angles π_1 and π_2 being marked therein). The physical back rake angles π_1 and π_2 may be considered positive where at least a portion of the corresponding longitudinal axes 11 and 21 extending through the cutting elements 10 and 20 are ahead the reference plane 500 (i.e., the longitudinal axes form an acute angle with the surface of the subterranean formation 300), as depicted in FIGS. 11 and 12 (the vertically opposite physical back rake angles π_1 and π_2 being marked therein). The physical back rake angles π_1 and π_2 may be considered neutral where the corresponding longitudinal axes 11 and 21 are parallel with the reference plane 500, as depicted in FIGS. 13 and 14.

The magnitude of each of the effective back rake angles θ_1 and θ_2 may also be affected by the magnitudes of the angles α_1 and α_2 between the longitudinal axes 11 and 21 and the flat cutting surfaces 18 and 28, respectively. The magnitudes of the angles α_1 and α_2 may be influenced at least by the respective locations of the apex 17 and the apex 27 on the corresponding cutting tips 13 and 23, the length of the respective flat cutting surfaces 18 and 28, and the respective angles ϕ_1 and ϕ_2 between the corresponding generally conical surfaces 16 and 26 and the corresponding phantom lines extending from the generally cylindrical lateral side surfaces 15 and 25 of the cutting elements 10 and 20.

The physical back rake angles π_1 and π_2 , the size and shape of the flat cutting surfaces 18 and 28, and the effective back rake angles θ_1 and θ_2 of the cutting tips 13 and 23, respectively, may each be tailored to optimize the performance of the cutting elements 10 and 20 for the earth-boring tool being used and characteristics of the surface 300 of the subterranean formation 300. The non-limiting embodiments illustrated in FIGS. 9-18 include different combinations of these variables that may

result in effective back rake angles θ_1 and θ_2 of between about thirty degrees (30°) negative back rake and about forty-five degrees (45°) positive back rake of the reference plane 500.

FIGS. 9 and 10 illustrate that the cutting elements 10 and 20 may be formed and oriented on an earth-boring tool such that the corresponding physical back rake angles π_1 and π_2 are negative (i.e., physical forward rake) and the effective back rake angles θ_1 and θ_2 are negative (i.e., effective forward rake). FIG. 9 shows the side perspective view of the embodiment of the cutting element 10 illustrated in FIG. 1, as oriented on the earth-boring tool to include a physical back rake angle π_1 that is negative. FIG. 10 shows the side perspective view of the embodiment of the cutting element 20 illustrated in FIG. 4, as oriented on the earth-boring tool to include a physical back rake angle π_2 that is negative. In embodiments including relatively larger angles α_1 and α_2 , the corresponding effective back rake angles θ_1 and θ_2 may be closer to neutral. In embodiments including relatively larger angles α_1 and α_2 , the corresponding physical rake angles π_1 and π_2 may be more negative to facilitate effective back rake angles θ_1 and θ_2 that are negative. Conversely, in embodiments including relatively smaller angles α_1 and α_2 , the corresponding physical back rake angles π_1 and π_2 may be less negative (i.e., closer to zero degrees), while still including effective back rake angles θ_1 and θ_2 that are negative.

FIGS. 11 and 12 illustrate that the cutting elements 10 and 20 may be formed and oriented on an earth-boring tool such that the corresponding physical back rake angles π_1 and π_2 are positive (i.e., physical back rake) and the respective effective back rake angles θ_1 and θ_2 are positive (i.e., effective back rake). FIG. 11 shows the side perspective view of the embodiment of the cutting element 10 illustrated in FIG. 1, as oriented on the earth-boring tool to include a physical back rake angle π_1 that is positive. FIG. 12 shows the side perspective view of the embodiment of the cutting element 20 illustrated in FIG. 4, as oriented on the earth-boring tool to include a physical back rake angle π_2 that is positive. In embodiments including relatively larger angles α_1 and α_2 , the corresponding effective back rake angles θ_1 and θ_2 may be more positive. In embodiments including relatively larger angles α_1 and α_2 , the corresponding physical rake angles π_1 and π_2 may be more negative to facilitate effective back rake angles θ_1 and θ_2 that are within forty-five degrees (45°) of positive

back rake angle relative to the reference plane 500. Conversely, in embodiments including relatively smaller angles α_1 and α_2 , the corresponding physical rake angles π_1 and π_2 may be more positive while still including respective back rake angles θ_1 and θ_2 within forty-five degrees (45°) of positive back rake angle relative to the reference plane 500.

FIGS. 13 and 14 illustrate that cutting elements 10 and 20 may be formed and oriented on an earth-boring tool such that the corresponding effective back rake angles θ_1 and θ_2 are positive (i.e., effective back rake), and respective physical back rake angles π_1 and π_2 are neutral (i.e., physical neutral rake). FIG. 13 shows the side perspective view of the embodiment of the cutting element 10 illustrated in FIG. 1, as oriented on the earth-boring tool to include a physical back rake angle π_1 that is neutral. FIG. 14 shows the side perspective view of the embodiment of the cutting element 20 illustrated in FIG. 4, as oriented on the earth-boring tool to include a physical back rake angle π_2 that is neutral. The magnitudes of the angles α_1 and α_2 may affect the sign and magnitude of the effective back rake angles θ_1 and θ_2 . In embodiments including relatively larger angles α_1 and α_2 , the corresponding effective back rake angles θ_1 and θ_2 may be closer to forty-five degrees (45°) of positive back rake angle relative to the reference plane 500. In embodiments including relatively smaller angles α_1 and α_2 , the corresponding effective back rake angles θ_1 and θ_2 may be closer to neutral.

FIGS. 15 and 16 illustrate that cutting elements 10 and 20 may be formed and oriented on an earth-boring tool such that the corresponding the effective back rake angles θ_1 and θ_2 are positive (i.e., effective back rake), and the respective physical back rake angles π_1 and π_2 are negative (i.e., physical forward rake). FIG. 15 shows the side perspective view of the embodiment of the cutting element 10 illustrated in FIG. 1, as oriented on the earth-boring tool to include a physical back rake angle π_1 that is negative. FIG. 16 shows the side perspective view of the embodiment of the cutting element 20 illustrated in FIG. 4, as oriented on the earth-boring tool to include a physical back rake angle π_2 that is negative. In embodiments including relatively larger angles α_1 and α_2 , the corresponding effective back rake angles θ_1 and θ_2 may be more positive. In embodiments including relatively larger angles α_1 and α_2 , the corresponding physical rake angles π_1 and π_2 may be more negative to facilitate effective back rake angles θ_1 and θ_2 that are about forty-five degrees (45°) of positive

back rake to the reference plane 500 or less. Conversely, in embodiments including relatively smaller angles α_1 and α_2 , the effective back rake angles θ_1 and θ_2 may be closer to neutral. In at least some embodiments including relatively smaller angles α_1 and α_2 , the corresponding physical back rake angles π_1 and π_2 may be more positive to
5 facilitate effective back rake angles θ_1 and θ_2 that are negative.

FIGS. 17 and 18 illustrate that cutting elements 10 and 20 may be formed and oriented on an earth-boring tool such that the corresponding the effective back rake angles θ_1 and θ_2 are neutral (i.e., effective back rake), and the physical back rake angles π_1 and π_2 are negative (i.e., physical forward rake). FIG. 17 shows the side
10 perspective view of the embodiment of the cutting element 10 illustrated in FIG. 1, as oriented on the earth-boring tool to include a physical back rake angle π_1 that is negative. FIG. 18 shows the side perspective view of the embodiment of the cutting element 20 illustrated in FIG. 4, as oriented on the earth-boring tool to include a physical back rake angle π_2 that is negative. In embodiments including relatively larger
15 angles α_1 and α_2 , the corresponding physical back rake angles π_1 and π_2 may be more negative to facilitate corresponding effective back rake angles θ_1 and θ_2 that are neutral. Conversely, in embodiments including relatively smaller angles α_1 and α_2 , the corresponding physical back rake angles π_1 and π_2 may be more positive to facilitate corresponding effective back rake angles θ_1 and θ_2 that are neutral.

20 The enhanced shape of the cutting elements described herein may be used to improve the behavior and durability of the cutting elements when drilling in subterranean earth formations. The shape of the cutting elements may allow the cutting element to fracture and damage the formation, while also providing increased efficiency in the removal of the fractured formation material from the subterranean
25 surface of the wellbore. The shape of the cutting elements may be used to provide a positive, negative, or neutral effective back rake angle, regardless of whether the cutting element has a positive, negative, or neutral physical back rake angle.

While the present invention has been described herein with respect to certain embodiments, those of ordinary skill in the art will recognize and appreciate that it is
30 not so limited. Rather, many additions, deletions and modifications to the embodiments described herein may be made without departing from the scope of the invention as hereinafter claimed, including legal equivalents. In addition, features from

-16-

one embodiment may be combined with features of another embodiment while still being encompassed within the scope of the invention as contemplated by the inventor.

-17-

CLAIMS

What is claimed is:

- 5 1. A cutting element comprising:
a substrate base; and
a volume of polycrystalline diamond material on an end of the substrate base, the
volume of polycrystalline diamond material comprising:
a generally conical surface;
10 an apex; and
a flat cutting surface extending from a first point at least substantially
proximate the apex to a second point on the cutting element more
proximate a lateral side surface of the substrate base.
- 15 2. The cutting element of claim 1, wherein the apex is centered about a
longitudinal axis extending through a center of the substrate base.
3. The cutting element of claim 1, wherein the apex is offset from a
longitudinal axis extending through a center of the substrate base.
20 4. The cutting element from one of claims 2 and 3, wherein the second
point comprises a location on the volume of polycrystalline diamond material.
5. The cutting element from one of claims 2 and 3, wherein the second
25 point comprises a location on the lateral side surface substrate base.
6. The cutting element from one of claims 2 and 3, wherein an angle
within a range of from about thirty degrees (30°) to about sixty degrees (60°) exists
between the generally conical surface and a phantom line extending from the lateral
30 side surface of the substrate base.
7. The cutting element from one of claims 2 and 3, wherein an angle

-18-

within a range of from about fifteen degrees (15°) to about ninety degrees (90°) exists between the flat cutting surface and the longitudinal axis.

8. The cutting element from one of claims 2 and 3, wherein a first angle
5 within a range of from about thirty degrees (30°) to about sixty degrees (60°) exists between the generally conical surface and a phantom line extending from the lateral side surface of the substrate base, and wherein a second angle within a range of from about fifteen degrees (15°) to about ninety degrees (90°) exists between the flat cutting surface and the longitudinal axis.

10

9. A method of manufacturing a cutting element, comprising:
forming a base substrate; and
providing a volume of polycrystalline diamond material on an end of a substrate base,
the volume of polycrystalline diamond material comprising a generally conical
15 surface, an apex, and a flat cutting surface extending from the apex.

10. The method of claim 9, wherein providing the volume of
polycrystalline diamond material on an end of a substrate base comprises centering the
apex of the volume of polycrystalline diamond material about a longitudinal axis
20 extending through a center of the substrate base.

11. The method of claim 9, wherein providing the volume of
polycrystalline diamond material on an end of a substrate base comprises offsetting the
apex of the volume of polycrystalline diamond material from a longitudinal axis
25 extending through a center of the substrate base.

12. The method of one of claims 10 and 11, wherein providing the volume
of polycrystalline diamond material on an end of a substrate base further comprises
forming the generally conical surface of the volume of polycrystalline diamond
30 material at an angle within a range of from about thirty degrees (30°) to about sixty degrees (60°) relative a phantom line extending from a lateral side surface of the substrate base.

13. The method of one of claims 10 and 11, wherein providing the volume of polycrystalline diamond material on an end of a substrate base further comprises forming the flat cutting surface of the volume of polycrystalline diamond material at an angle within a range of from about fifteen degrees (15°) to about ninety degrees (90°) relative the longitudinal axis.

14. The method of one of claims 10 and 11, wherein providing the volume of polycrystalline diamond material further comprises:
10 forming the generally conical surface of the volume of polycrystalline diamond material at an angle within a range of from about thirty degrees (30°) to about sixty degrees (60°) relative a phantom line extending from a lateral side surface of the substrate base; and
forming the flat cutting surface of the volume of polycrystalline diamond material at an angle within a range of from about fifteen degrees (15°) to about ninety degrees (90°) relative the longitudinal axis.

15. The method of claim 9, wherein providing the volume of polycrystalline diamond material on the substrate base comprises attaching the volume of polycrystalline diamond material to the substrate base after forming at least one of the generally conical surface, the apex, and the flat cutting surface of the volume of polycrystalline diamond material.

16. The method of claim 9, wherein providing the volume of polycrystalline diamond material on the substrate base comprises forming at least one of the generally conical surface, the apex, and the flat cutting surface of the volume of polycrystalline diamond material while the volume of polycrystalline diamond material is attached to the substrate base.