

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2015/121371 A1

(43) International Publication Date
20 August 2015 (20.08.2015)

(51) International Patent Classification:
C10G 47/02 (2006.01)

(21) International Application Number:
PCT/EP2015/053010

(22) International Filing Date:
12 February 2015 (12.02.2015)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/939,100 12 February 2014 (12.02.2014) US

(71) Applicant: BP EUROPA SE [DE/DE]; Überseeallee 1, 20547 Hamburg (DE).

(72) Inventors; and

(71) Applicants (for US only): SCHLEIFFER, Andreas [DE/DE]; Wittener Strasse 45, 44789 Bochum (DE). YANG, Hong [CA/US]; 501 Westlake Park Boulevard, Houston, Texas 77079 (US).

(74) Agent: PEDLEY, Michael Ewan; BP INTERNATIONAL LIMITED, Global Patents & Technology Law, Chertsey Road, Sunbury-on-Thames, Middlesex TW16 7LN (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))



WO 2015/121371 A1

(54) Title: PROCESS FOR HYDROCRACKING HEAVY OIL AND OIL RESIDUE WITH A NON-METALLISED CARBONACEOUS ADDITIVE

(57) Abstract: A process for the hydroprocessing of heavy oils and/or oil residues, the process comprising the steps of contacting a non-metallised carbonaceous material with an oxygen-containing gas at a temperature of at least 120°C to form a non-metallised carbonaceous additive, and contacting the heavy oils and/or oil residues with the non-metallised carbonaceous additive in the presence of a hydrogen-containing gas at a temperature of from 250°C to 600°C.

**PROCESS FOR HYDROCRACKING HEAVY OIL AND OIL RESIDUE WITH A
NON-METALLISED CARBONACEOUS ADDITIVE**

FIELD OF THE INVENTION

5

This invention relates to processes for hydrocracking heavy oils and oil residues such as vacuum gas oil, atmospheric residue and vacuum residue into substances having smaller molecules of greater utility.

BACKGROUND OF THE INVENTION

10

Hydroprocessing (which may also be referred to as hydrocracking, hydrotreating, hydroconverting, hydroconversion or hydrogenative cracking / processing / converting / conversion / treating / treatment) of heavy oils and/or oil residues is a known process that may be used to form useful materials from crude oil components that have high initial boiling points (i.e. typically greater than about 385°C for atmospheric residue, greater than about 525°C for vacuum residue and between about 350°C and about 525°C for vacuum gas oil). In order to make hydroprocessing conditions more economically viable, metal catalysts may be used to facilitate the hydroprocessing. See e.g. US4770764, US 8372776 and US 20110017636. However, such metal catalysts are expensive and may be prone to deactivation. Alternatively, non-metallic (that is to say, non-metallised) carbonaceous materials such as lignite coke may be used as an additive instead of the metal catalysts. See US5064523. Such carbonaceous additives, however, are typically very inefficient at hydroprocessing larger hydrocarbon molecules, including molecules such as asphaltenes, which unfortunately leads to unconverted heavy oils and/or oil residues in the process, and incomplete hydroprocessing (including coke formation). To worsen matters, unprocessed asphaltenes (and coke) may also adhere to additive particles, thus preventing their further utility in the process.

There accordingly remains a need for a process for hydroprocessing heavy oils and oil residues such as vacuum gas oil, atmospheric residue and vacuum residue into substances having smaller molecules of greater utility that simultaneously offers the cost benefits of avoiding metal catalysts alongside improved process efficiency, especially when it comes to hydrocracking asphaltenes.

SUMMARY OF THE INVENTION

Surprisingly, the applicants have now found that the above problems may be addressed by providing a process for the hydroprocessing of heavy oils and/or oil residues, the process

5 comprising the steps of contacting a non-metallised carbonaceous material with an oxygen-containing gas at a temperature of at least 120°C to form a non-metallised carbonaceous additive, and contacting the heavy oils and/or oil residues with the non-metallised carbonaceous additive in the presence of a hydrogen-containing gas at a temperature of from 250°C to 600°C.

10 Also surprisingly, the applicants have found that the above problems may be addressed with a non-metallised carbonaceous additive for the hydroprocessing of heavy oils and/or oil residues wherein the non-metallised carbonaceous additive comprises, or consists of, a non-metallised carbonaceous material having been contacted with an oxygen-containing gas at a temperature of at least 120°C to form the non-metallised carbonaceous additive.

DETAILED DESCRIPTION OF THE INVENTION

The processes and materials of the present invention relate to the hydroprocessing of heavy oils and/or oil residues. Such processes are known in the art and usually involve reacting the heavy oil or oil residue in the presence of hydrogen at elevated temperature and pressure. Accordingly, the processes of the present invention comprise the step of contacting the heavy oils and/or oil residues with a non-metallised carbonaceous additive in the presence of a hydrogen-containing gas (i.e. as used herein, a gas comprising molecular hydrogen (H₂)) at a temperature of from about 250°C to about 600°C (preferably to about 500°C). As used herein “heavy oils or oil residues” refers to heavy and ultra-heavy crudes, including but not limited to residues, coals, bitumen, shale oils, tar sands and the like, and fractions thereof. The heavy oil may therefore be liquid, semi-solid and/or solid. Non-limiting examples of heavy oils that may be subjected to hydroprocessing include Canada Tar sands, vacuum residue from Brazilia Santos and Campos basins, Egyptia Gulf of Suez, Chad, Venezuelan Zulia, Malaysia and Indonesia Sumatra. Other examples of heavy oils and/or oil residues are described elsewhere herein and also include, without limitation, bottom of the barrel and residuum left over from refinery processes. Particular non-limiting examples include as atmospheric tower bottoms, which typically

have a boiling point of at least about 343°C, vacuum tower bottoms, which typically have a boiling point of at least about 524°C, and residue pitch and vacuum residue which may have a boiling point of about 524°C or greater.

The upgrade or treatment of heavy oils or oil residues in the presence of hydrogen 5 is generally referred to herein as “hydroprocessing.” Hydroprocessing includes any such process including without limitation hydrogenation, hydrotreating, hydroconversion, hydrocracking (including selective hydrocracking), hydroisomerisation, hydrodewaxing, hydrodearomatization, hydrodesulfurization, hydrodenitrogenation, hydrodemetallation. Of particular relevance to the present invention is where hydroprocessing is taken to mean 10 hydroconversion or hydrocracking, i.e. the treating of heavy oils and/or oil residues in order to lower the molecular weight and/or boiling point and/or concentration of asphaltenes in the heavy oils and/or oil residues. In the present process, a non-metallised carbonaceous material is used as an additive in the hydroprocessing.

As used herein the term “non-metallised” includes materials to which no metals 15 from group VB (5) (e.g. V, Nb, Ta), VIB (6) (e.g. Cr, Mo, W) and VIII (8) (e.g. Fe, Co, Ni, Ru, Rh, Pd, Os, Ir, Pt) have been added (e.g. loaded) from an external source, such as materials to which no transition metals have been added (e.g. loaded) from an external source, or such as materials to which no metals have been added (e.g. loaded) from an external source. As used herein, the heavy oils and/or oil residues being processed in the 20 present invention may be excluded from the reference to an external source, i.e. it is within the contemplation of the present invention that the additive may scavenge any of the categories of metals above from the heavy oils and/or oil residues e.g. in situ.

Commensurately, according to a definition of “non-metallised” as used herein, while the additive may comprise further materials, including metals, the non-metallised 25 carbonaceous material may not have had additional metal added to it (e.g. loaded on to it). It is thus understood and accepted that the raw carbonaceous material may contain metal (e.g. traces of metals such as iron, nickel or vanadium) in its natural state, comparable to a piece of fruit which while not inherently considered metallic or metallised, nonetheless may contain metal atoms (e.g. a banana in its natural state is not ordinarily considered to be 30 “metallised” but is however widely regarded as comprising potassium).

The non-metallised carbonaceous additive used according to the invention may be in any form, for example the additive may comprise, or be selected from one or more of

the group consisting of anthracite cokes, lignite cokes, carbon blacks, activated cokes, petroleum cokes, furnace dust, dusts from Winkler gasification of coal, red mud, electrostatic filter dusts, cyclone dusts, and mixtures thereof, while the non-metallised carbonaceous material preferably comprises, or is, a lignite coke. Although essentially 5 interchangeable herein, especially in respect of features or properties of the two species, the term “additive” typically refers to the species once prepared for use in a process according to the present invention, while “material” typically refers to either a substance of which the additive (once prepared) is composed, or to the additive prior to such preparation for a process according to the present invention.

10 In accordance with the present invention, the applicants have now found that heating the non-metallised carbonaceous material in the presence of an oxygen-containing gas (herein “heated oxidation”) increases the average pore size and broadens the pore size distribution, providing the benefits of the present invention. Advantageously, the heating is to a temperature above about 120°C, preferably from about 200°C to about 600°C, more 15 preferably from about 250°C to about 450°C, even more preferably from about 300°C to about 400°C and even more preferably still from about 330°C to about 370°C, and the duration of the heating in the presence of an oxygen containing gas is at least about 1 hour, preferably at least about 2 hours, more preferably at least about 3 hours and even more preferably at least about 4 hours, for example from about 1 hour to about 24 hours, from 20 about 2 hours to about 12 hours, from about 3 hours to about 10 hours or from about 4 hours to about 5 hours. Alternatively, the process step of heating the non-metallised carbonaceous material in the presence of an oxygen-containing gas may be continuous. The oxygen-containing gas may advantageously be oxygen, a nitrogen-oxygen mixture or air, and is preferably air. It should be noted that any combination of temperature range, 25 duration and oxygen-containing gas identity may be used and is intended to be included in the present disclosure. Without wishing to be bound by theory, the applicants understand that the heated oxidation according to the above description facilitates the removal of combustible material and/or ash from inside the pores of the non-metallised carbonaceous material, thus increasing the average pore size and increasing the availability of trace metals (for example iron) which may catalyse (either directly or via functioning as a pre-catalyst) the hydroprocessing step.

In accordance with some desirable embodiments, the pressure of the oxygen-containing gas during the heated oxidation may in principle be of any suitable level provided some oxygen-containing gas is present. Non-limiting examples of the pressures of the oxygen-containing gas that may be used include from about -999 mbarg to 20 barg,

5 from about -500 mbarg to about 10 barg, from about -250 mbarg to about 5 barg, from about -200 mbarg to about 2 barg, from about -150 mbarg to about 1 barg or from about -100 mbarg to about 500 mbarg. Ambient pressure (about 0 barg) may therefore be used. Alternatively, the pressures disclosed above may be partial pressures of the oxygen (O₂) present in the oxygen-containing gas.

10 Advantageously, the non-metallised carbonaceous additive has an average pore size of at least about 2nm, preferably at least about 2.25nm, more preferably at least about 2.5nm and even more preferably still at least about 3nm, for example from about 2nm to about 10nm, preferably from about 2.25nm to about 8nm, more preferably from about 2.5nm to about 6nm and even more preferably from about 3nm to about 5nm. As used 15 herein, the term "average pore size" refers to the average internal radius of the pores in the carbonaceous materials/additives. Correspondingly, "pore size" or "pore sizes" refers to an internal radius/internal radii respectively, for example as measured for a given pore or set of pores. Without wishing to be bound by theory, the applicants believe that adopting the pore sizes above facilitates access of asphaltene and other large hydrocarbons into the 20 additive in order to promote the hydroprocessing of these larger molecules. The ranges may also be bounded at the upper end because too big a pore size may reduce the overall surface area and physical strength of the additive, thus potentially may be detrimental to the efficacy of the non-metallised carbonaceous additive. Pore sizes as described herein may in turn enable the use of milder conditions for the hydroprocessing step. While large 25 hydrocarbon molecules such as asphaltenes may be cracked using severe conditions, the use of more severe conditions also results in a greater prevalence of small hydrocarbon molecules in the hydroprocessing product, which is undesirable on two counts. Firstly, the smaller molecules (e.g. methane and ethane) are undesirable per se for the reason that they lack value compared to larger hydrocarbon molecules (e.g. octane and decane) because of 30 the lower energy density, and secondly the hydrogen to carbon ratio is higher for smaller molecules, meaning that more hydrogen is consumed during the hydroprocessing process, hence being wasteful and increasing the costs associated with the process.

Pore sizes, including average pore size, (and specific surface area) of the non-metallised carbonaceous additive may be measured by the well established Brunauer-Emmett-Teller (BET) method (ASTM D3663 (e.g. version 03, reapproved 2008)), which evaluates the external surface area, pore sizes and surface area inside the pores of a porous material via the nitrogen multilayer adsorption/desorption isotherm at liquid nitrogen temperature (e.g. -196°C). As used herein, “total pore volume” is the overall pore volume measured for the material determined using the BET method. The Barrett-Joyner-Halenda (BJH) method is used to evaluate pore size distribution from the experimental desorption isotherms. As used herein “cumulative pore volume” is the aggregated pore volume for the material determined using the BJH method.

The presence of larger pores in the non-metallised carbonaceous additive is considered to be particularly advantageous. Without wishing to be bound by theory, the Applicants believe that increasing the proportion of larger pores increases the capability of the additive to process asphaltenes as they are able to enter additive particles rather than merely adhere to the surface where the large asphaltene molecules may simply block one or more pores. Accordingly, and this may be in combination with any of the average pore sizes disclosed above, the pore size distribution advantageously may extend up to about 50 nm or up to about 30 nm. So, for example, the pore size distribution may advantageously extend to about 40 nm, by which is meant the highest recorded value of a pore size is about 40 nm (and correspondingly for other values). Alternatively, the pore size distribution may extend between two values (i.e. the pore size distribution may have a lowest recorded value and a highest recorded value). Non-limiting examples of such advantageous pore size distributions may be those that extend from about 1.5 nm to about 50 nm, or preferably extending from about 2 nm to about 30 nm. A further advantageous aspect of the pore size distribution may be an increased proportion of larger pores, such as the presence of pores with a pore size of at least about 5 nm, or at least about 8 nm, or at least about 10 nm. The pore size distribution typically has at least one mode, and advantageously has at least two modes (i.e. maxima in the distribution located at particular pore sizes), for example 2, 3, 4, 5, 6, 7, 8, 9 or more modes.

Another way of considering pore size distribution is via the proportion of the pore volume in the material as a whole that arises from pores of certain sizes. Some examples according to the present invention include non-metallised carbonaceous additives wherein

at least about 80% of the cumulative pore volume arises from pores having a pore size of at least about 2nm, additionally or alternatively non-metallised carbonaceous additives wherein at least about 50% of the cumulative pore volume arises from pores having a pore size of at least about 5nm, additionally or alternatively non-metallised carbonaceous additives 5 wherein at least about 30% of the cumulative pore volume arises from pores having a pore size of at least about 10nm, and additionally or alternatively non-metallised carbonaceous additives wherein at least about 50% of the cumulative pore volume arises from pores having a pore size of at least about 10nm, or any combination thereof, based upon cumulative pore volume as measured by BJH (i.e. the sum of pore volume for all 10 pores as determined using this method).

By way of further non-limiting examples of pore size distributions, at least about 90% of the cumulative pore volume may arise from pores having a pore size of at least about 2nm, additionally or alternatively at least about 75% of the cumulative pore volume may arise from pores having a pore size of at least about 5nm, additionally or alternatively 15 about 50% of the cumulative pore volume may arise from pores having a pore size of at least about 10nm, or any combination thereof.

The various ranges described above in relation to pore sizes may also form any arithmetically sensible combination. So, to provide a non-limiting example of one such possible combination, a non-metallised carbonaceous additive according to the invention 20 may have a pore size distribution extending to 30nm, 30% of the cumulative pore volume arising from pores having a pore size of at least 10nm and 75% of the cumulative pore volume arising from pores having a pore size of at least 5nm.

The non-metallised carbonaceous additive as used in the present invention may advantageously have a total pore volume (measured according to the BET method (ASTM 25 D3663 (e.g. version 03, reapproved 2008))) greater than that of the carbonaceous material forming the non-metallised carbonaceous additive, i.e. greater than the total pore volume when the material is in its natural form. The total pore volume may range from about 0.1cm³/g to about 5cm³/g, preferably from about 0.2cm³/g to about 2cm³/g, more 30 preferably from about 0.3cm³/g to about 1.5cm³/g, even more preferably from about 0.5cm³/g to about 1.25cm³/g and even more preferably still from about 0.7cm³/g to about 1cm³/g. Without wishing to be bound by theory, the Applicants believe that such total pore

volumes provide more space for hydrocarbon molecules to diffuse into the additive, hence further improving efficacy.

Further, the non-metallised carbonaceous additive may advantageously have a specific surface area (measured according to the BET-method) greater than that of the carbonaceous material forming the non-metallised carbonaceous additive, i.e. greater than the specific surface area when the material is in its natural form. The specific surface area may range from about 100m²/g to about 3000m²/g, preferably from about 200m²/g to about 1000m²/g, more preferably from about 300m²/g to about 800m²/g, even more preferably from about 350m²/g to about 700m²/g, such as from about 400m²/g to about 650m²/g.

10 Without wishing to be bound by theory, such specific surface areas provide increased availability of additive surface to promote hydroprocessing of heavy oils and/or oil residues. High surface area may, particularly in combination with any of the aspects of pore size distribution described herein, also mean less additive is required for equivalent hydroprocessing efficiency.

15 The non-metallised carbonaceous additive used in the present invention is advantageously a powder. Within the present invention, this powder may in principle have any particle size. Desirably, the particle size is from about 1μm to about 100μm, preferably from about 10μm to about 90μm, more preferably from about 20μm to about 80μm, even more preferably from about 30μm to about 70μm and even more preferably 20 still from about 40μm to about 60μm.

As considered in the definition of “non-metallised” herein, the non-metallised carbonaceous additive may inherently comprise some metal. Without wishing to be bound by theory, the applicants believe that some metals, particularly transition metals such as iron may improve hydroprocessing by catalysing the cracking of hydrocarbons (either 25 directly or by acting as catalyst precursors). Accordingly, the non-metallised carbonaceous additive (especially coke and more especially lignite coke) thus advantageously comprises (e.g. inherently comprises) at least about 6000ppm of metal, such as from about 6000ppm to about 100000ppm, preferably from about 7000ppm to about 30000ppm, more preferably from about 8000ppm to about 20000ppm, even more preferably from about 9000ppm to 30 about 15000ppm and even more preferably still from about 10000ppm to about 13000ppm, all by weight of the non-metallised carbonaceous additive. Preferably, any of the ranges above may be applied to the non-metallised carbonaceous additive based only on the

amount of transition metals present, more preferably the amount of metals from group VB (5) (e.g. V, Nb, Ta), VIB (6) (e.g. Cr, Mo, W) and VIII (8) (e.g. Fe, Co, Ni, Ru, Rh, Pd, Os, Ir, Pt), even more preferably the amount of metals from group VIII (8) and even more preferably still the amount of iron present in the non-metallised carbonaceous additive, all

5 by weight of the non-metallised carbonaceous additive. These ranges may apply to the non-metallised carbonaceous additive without any metal being added (e.g. loaded) from an external source, e.g. in the non-metallised carbonaceous material's natural state.

Alternatively put, this may be achieved simply by selecting the material to be used for the non-metallised carbonaceous additive. Any scavenging of metals from the heavy oils

10 and/or oil residues may be in addition to these ranges or the ranges may describe the metal contents after such scavenging. The ranges may certainly describe the additive at the point of it being brought into contact with the heavy oils and/or oil residues, so for example, after other process steps such as heating in the presence of an oxygen-containing gas and/or treating with an acid described herein, have occurred. Without wishing to be bound 15 by theory, the Applicants believe that while combustible material is typically removed from the non-metallised carbonaceous additive in applying aspects of the present invention as described herein, metal is not, and therefore the proportion of potentially catalytic species in the additive is increased, thus promoting improved process efficiency.

Alternatively described, the process for the hydroprocessing of heavy oils and/or oil residues may comprise the steps of: contacting a non-metallised carbonaceous material with an oxygen-containing gas (i.e. a gas comprising molecular oxygen (O₂) at a temperature of at least about 120°C to form a non-metallised carbonaceous additive; and contacting the heavy oils and/or oil residues with the non-metallised carbonaceous additive in the presence of a hydrogen-containing gas at a temperature of from about 250°C to 25 about 600°C, under a hydrogen partial pressure of at least about 100 barg. Although the maximum pressure is practically dependent on the equipment used, the hydrogen partial pressure may be up to about 500 barg, up to about 400 barg or up to about 300 barg, for example from about 100 barg to about 500 barg, from about 150 barg to about 400 barg or from about 200 barg to about 300 barg. It is noted that a distinct heating process may have 30 been used in order to form the non-metallised carbonaceous material (i.e. a potential additive in an untreated form according to the present invention). A non-limiting example of this is that heating may be used to form a coke (a non-metallised carbonaceous

material), but then according to the present invention, a further heating step may be utilised in order to turn that coke into a non-metallised carbonaceous additive according to the invention. The heating step of the present invention (i.e. to form the non-metallised carbonaceous additive) may therefore be viewed as separate to any heating used to form 5 the non-metallised carbonaceous material (e.g. separated by a cooling step such as a step of cooling the non-metallised carbonaceous material to ambient temperature). By way of another non-limiting example, the heating step of the present invention may be co-located with the hydroprocessing step (e.g. on the same worksite).

It may be found that in its natural state, the average pore size of a non-metallised 10 carbonaceous material (e.g. lignite coke) is not only less than about 2nm but also accompanied by a narrow pore size distribution, such as a pore size distribution with few larger pores.

In some advantageous embodiments, the non-metallised carbonaceous material is treated with acid, i.e. the process may comprise a step of contacting the non-metallised 15 carbonaceous material/additive with an acid (herein “acid treatment”), such as in addition to a heated oxidation. Without wishing to be bound by theory, the applicants believe that acid treatment as described above may further remove ash, crystalline graphite and non-metal inorganic material from within the pores of the non-metallised carbonaceous material and may also remove basic metals (such as group 1 and 2 elements, e.g. Na, K, 20 Ca, Mg) which further increases the availability of potentially catalytic metals (e.g. transition metals such as iron) within the hydroprocessing step. The ash content may therefore be no more than (or less than) 20%, preferably no more than (or less than) 15%, more preferably no more than (or less than) 10% and even more preferably no more than (or less than) 5% by weight of the non-metallised carbonaceous additive. A further benefit 25 so arising may be that the additive is softened by the acid treatment, thus reducing erosion in processing equipment (such as the hydroprocessing reactor) that may occur as a result of using a carbonaceous additive.

An acid treatment step may occur before or after a heated oxidation described 30 herein, but is preferably before the heated oxidation as this allows the heated oxidation to additionally remove any residual moisture (i.e. drying the non-metallised carbonaceous additive) from the acid treatment at the same time as increasing the pore size.

In principle any acid may be used for the acid treatment step. Examples of suitable acids include inorganic acids such as tungstic acid, sulphuric acid, phosphoric acid, nitric acid, hydrochloric acid and mixtures thereof as well as organic acids such as citric acid, acetic acid, benzoic acid, salicylic acid and mixtures thereof. Preferably, the acid used for

5 the acid treatment step comprises, or is, an inorganic acid, more preferably the acid comprises, or is selected from sulphuric acid, phosphoric acid, nitric acid, hydrochloric acid and mixtures thereof and even more preferably the acid comprises, or is, nitric acid. Typically, the acid will be provided to the acid treatment as an aqueous solution. The concentration of the acid in such a solution may in principle be any value. For example,

10 the acid may be present in an amount of from about 1% to about 99% by weight of the solution, preferably from about 5% to about 95%, more preferably from about 10% to about 90%, even more preferably from about 20% to about 70%, even more preferably still from about 25% to about 50% and yet more preferably from about 30% to about 35%, all by weight of the solution.

15 The acid treatment may also be heated (e.g. a heated step), for example the acid treatment may occur at a temperature of from about 25°C to about 99°C, preferably from about 30°C to about 95°C, more preferably from about 40°C to about 90°C, even more preferably from about 50°C to about 88°C and even more preferably still from about 70°C to about 85°C or from about 75°C to about 85°C. Advantageously, an acid treatment may

20 also be agitated, e.g. by stirring.

Following the acid treatment step, it may be desirable to rinse the non-metallised carbonaceous additive in order to remove any excess acid that may be present. For example, the non-metallised carbonaceous additive may be rinsed with water (preferably de-ionised water), e.g. until such time as the pH of the rinse water (i.e. water sampled after

25 being used to rinse the additive) is stable.

A further drying step may also follow an acid treatment of the non-metallised carbonaceous additive which may be, for example, heating the non-metallised carbonaceous additive to a temperature of at least about 40°C for a period of at least about 2 hours. Preferably, the optional drying step may be conducted at about 120°C for about

30 12 hours.

It may also be desirable to manage the density of the non-metallised carbonaceous additive in order to improve its mobility within the hydroprocessing step (i.e. mobility

physically within a hydroprocessing reactor, as opposed to a tendency to settle) in order to improve overall process efficiency. In particular, and without wishing to be bound by theory, the Applicants understand that the removal of ash by heat and/or acid treatment may lower the density of the non-metallised carbonaceous additive and thus promote 5 overall process efficiency. Accordingly, the true density of the additive advantageously may be from about 1 g/cm³ to about 3g/cm³, preferably from about 1.7g/cm³ to about 2 g/cm³. The true density may be measured by He absorption, such as according to ASTM D2638 (e.g. version 10; ASTM D2638 – 10).

10 The present processes comprise a step of contacting the heavy oils and/or oil residues with a non-metallised carbonaceous additive in the presence of a hydrogen-containing gas i.e. the hydroprocessing step e.g hydrocracking step. This hydroprocessing step is typically conducted at a temperature of from about 250°C to about 600°C or 500°C, preferably from about 400°C to about 490°C, more preferably from about 425°C to about 485°C, even more preferably from about 440°C to about 480°C and even more preferably 15 still from about 450°C to about 475°C. It is also usual practice to utilise a hydrogen partial pressure of from about 50 barg to about 300 barg, preferably from about 100 barg to about 250 barg.

20 The non-metallised carbonaceous additive may be present in the hydroprocessing step in an amount of from about 0.1% to about 25% by weight of all solid and liquid materials present in the hydroprocessing step (e.g. not including any gas present). Advantageously, the non-metallised carbonaceous additive may be present in an amount of from about 0.5% to about 15%, preferably from about 0.8% to about 10% and even more preferably from about 1% to about 5%, by weight of the solid/liquid materials present in the hydroprocessing step.

25 Other additives and/or catalysts may be added in addition to the non-metallised carbonaceous additive according to the present invention. Such additives and/or catalysts may be any known in the art, for example metal catalysts. According to some embodiments of coal liquefaction for example, a catalyst precursor may be used to impregnate ground coal at a rate of about 0.25 to about 5 wt. % of metal to coal (on a dry, 30 ash-free basis or "daf" basis). After impregnation, the catalyst is then formed via in situ sulfidation. In some embodiments, the in situ sulfidation is carried out by mixing elemental sulfur with the catalyst impregnated coal and a solvent or diluent, (e.g. FCC-type

process oil(s), light catalytic cycle cracking oil(s) (LCCO), decanted oil(s) (DCO)), at a solvent to coal ratio ranging from about 0.25:1 to about 5:1 or from about 0.5 to about 3:1

The hydroprocessing step may be a plurality of individual hydroprocessing steps (i.e. 2 or more steps, for example 2, 3, 4, 5, 6, 7, 8, 9 or more steps) which may be identical or at least one of which may differ in one or more ways from at least one other.

5 The hydroprocessing step(s) may in principle be any of those known in the art and is/are in no way limited to particular approaches or equipment. The hydroprocessing may therefore be continuous, batch mode or combinations thereof (for example in the case of a plurality of hydroprocessing steps there may be one or more steps that are continuous and other(s) that operate in batch mode). Similarly one or more hydroprocessing steps may be carried out in a mixing tank and others in a fluidized bed reactor or slurry bed reactor.

10 Single-stage or multiple-stage reactors may also be used to create combinations of hydroprocessing processes and reactor types. In some embodiments, a batch process involving one reactor for multiple steps may be carried out with the steps carried out in sequence after completion of the previous step, or multiple reactors may be in series with each step being carried out in a separate reactor. Non-limiting continuous processes according to the invention include continuous processes in which the product stream from one reactor feeds the next step in the process, whether that is a further reactor, alternative step (e.g. distillation or condensing), or disposal (e.g. as a product stream or waste stream).

15 20 Any suitable apparatus known in the art may be used for the present processes. For example, the apparatus may be an ebullating bed reactor, a mixing tank reactor, a fluidized bed reactor, a slurry bed reactor or combinations thereof, including continuously stirred tank reactor variants of any of the foregoing. Stirring (which may be before, during and/or after hydroprocessing) may be achieved by any suitable means known in the art, for

25 example an in-line static mixer (e.g. utilising a plurality of internal baffles or other stirring elements), a dynamic high shear mixer (e.g. a vessel with a propeller for very highly turbulent, high shear mixing), or any combination of the above, in order to obtain turbulent mixing conditions. In some advantageous embodiments, high shear mixing is desirable in order to prevent the mixture from settling or thickening. Accordingly, it may be desirable 30 to obtain mixing conditions for a flow with a Reynolds number of at least about 2000. In some embodiments, the mixing is continuous in a high shear mode (e.g. from about 100 RPM to about 1600 RPM) and may last from about 10 minutes to about 24 hours with the

goal of obtaining a homogeneous slurry. The mixing may also be sufficient for a Reynolds number of at least about 3000, or from about 3100 to about 7200.

Any mixing may occur under an inert atmosphere, which may be, by way of non-limiting example: nitrogen, refinery gas, any other gas having little or no oxygen, and any mixtures thereof. The mixing may also be conducted under a hydrogen-containing gas pressure. It may be advantageous to add a surfactant to the heavy oils and/or oil residues (with or without the non-metallised carbonaceous additive) in order to improve processability, or to subject a mixture of non-metallised carbonaceous additive and heavy oil and/or oil residue to activation radiation, for example the mixture may be subjected to high intensity ultrasound or electromagnetic radiation to reduce the particle size of the non-metallised carbonaceous additive in situ.

The heavy oil and/or oil residue (with or without the non-metallised carbonaceous additive) may comprise water (e.g. free water) which may be removed to prevent it occupying space in a hydroprocessing reactor. For example, the heavy oil and/or oil residue (with or without the non-metallised carbonaceous additive) may be passed to a high pressure separator to remove water prior to hydroprocessing. Additionally or alternatively, the heavy oil and/or oil residue (with or without the non-metallised carbonaceous additive) may be pre-conditioned with hydrogen prior to hydroprocessing. The presence of free water may be particularly undesirable as this may lead to foaming in the reactor which then reduces the length of time for which a process may be run continuously.

The non-metallised carbonaceous additive is useful for hydroprocessing carbonaceous feedstocks which include without limitation atmospheric gas oils, vacuum gas oils (VGO), atmospheric residues, vacuum residues, deasphalting oils, olefins, oils derived from tar sands or bitumen, oils derived from coal, crude oils (e.g. heavy crude oils), synthetic oils from Fischer-Tropsch processes, and oils derived from recycled oil wastes and polymers. The non-metallised carbonaceous additive is useful for, but not limited to, hydrogenation upgrading processes such as thermal hydrocracking, hydrotreating, hydrodesulfurization, hydrodenitrification, and hydrodemetalization. In some further embodiments, the non-metallised carbonaceous additive may be used for pretreating a carbonaceous material and/or for liquefying a carbonaceous material such as coal or mixtures of coal with any other feedstocks mentioned above.

The non-metallised carbonaceous additive can be used to treat a plurality of feeds under wide-ranging reaction conditions such as temperatures of from about 200°C to about 600°C or to about 500°C, hydrogen pressures of from about 5 to about 300 barg or bara (72 to 4351 psi or 0.5 to 30 MPa), liquid hourly space velocities of from about 0.05 to 5 about 10 h⁻¹ and hydrogen treat gas rates of from about 35.6 to about 2670 m³/m³ (200 to 15000 SCF/B).

In some embodiments, the hydroprocessing pressure ranges from about 10 MPa (1,450 psi) to about 25 MPa (3,625 psi), from about 15 MPa (2,175 psi) to about 20 MPa (2,900 psi), less than 22 MPa (3,190 psi), or more than 14 MPa (2,030 psi). The liquid 10 hourly space velocity (LHSV) of the feed will generally range from about 0.05 h⁻¹ to about 30 h⁻¹, about 0.5 h⁻¹ to about 25 h⁻¹, about 1 h⁻¹ to about 20 h⁻¹, about 1.5 h⁻¹ to about 15 h⁻¹, or about 2 h⁻¹ to about 10 h⁻¹. In some embodiments, LHSV is at least about 5 h⁻¹, at least 15 about 11 h⁻¹, at least about 15 h⁻¹, or at least about 20 h⁻¹. In some embodiments, the LHSV ranges from about 0.25 h⁻¹ to about 0.9 h⁻¹. Also in some embodiments, the LHSV ranges 15 from about 0.1 h⁻¹ to about 3 h⁻¹. The hydroprocessing temperature may range from about 410°C (770°F) to about 600°C (1112°F), additionally or alternatively less than about 462°C (900°F) and/or more than about 425°C (797°F). The hydroprocessing can be practiced in one or more reaction zones and can be practiced in either counter-current flow or co-current flow mode. By counter-current flow mode is meant a process wherein the 20 feed stream flows counter-current to the flow of hydrogen-containing treat gas. By co-current flow mode is meant a process wherein the feed stream flows co-current with the flow of hydrogen-containing treat gas. The hydroprocessing may also include slurry and ebullated bed hydrotreating processes for the removal of sulfur and nitrogen compounds and the hydrogenation of aromatic molecules present in light fossil fuels such as petroleum 25 mid-distillates, e.g., hydrotreating a heavy oil employing a circulating non-metallised carbonaceous additive.

The feeds (i.e. heavy oils and/or oil residues) for use in hydroprocessing processes according to the invention may include but not necessarily be limited to petroleum and chemical feedstocks such as olefins, reduced crudes, hydrocrackates, raffinates, 30 hydrotreated oils, atmospheric and vacuum gas oils, coker gas oils, atmospheric and vacuum resids, deasphalted oils, dewaxed oils, slack waxes, Fischer-Tropsch waxes and mixtures thereof. Specific examples range from the relatively light distillate fractions up to

high boiling stocks such as whole crude petroleum, reduced crudes, vacuum tower residua, propane deasphalting residua, brightstock, cycle oils, fluid catalytic cracking (FCC) tower bottoms, gas oils including coker gas oils and vacuum gas oils, deasphalting residua and other heavy oils. In one embodiment, the feedstock is a C10+ feedstock. In another 5 embodiment, the feedstock is selected from distillate stocks, such as gas oils, kerosenes, jet fuels, lubricating oil stocks boiling above 230°C, heating oils, hydrotreated oil stock, furfural-extracted lubricating oil stock and other distillate fractions whose pour point and viscosity properties need to be maintained within certain specification limits. The non-metallised carbonaceous additive may be added directly to the feed before/during 10 hydroprocessing or may be first mixed into a solvent or diluent, (e.g. a petroleum fraction, FCC-type process oil(s), light catalytic cycle cracking oil(s) (LCCO), decanted oil(s) (DCO)).

In some embodiments, the heavy oils and/or oil residues may contain a substantial amount of nitrogen containing compounds, e.g. at least about 10 ppm nitrogen by weight, 15 particularly in the form of organic nitrogen compounds. The heavy oils and/or oil residues can also have a significant sulfur content, e.g. ranging from about 0.1 wt% to about 3 wt%, or higher. In some embodiments, the heavy oils and/or oil residues form a feed derived from crude oils, shale oils and tar sands as well as synthetic feeds such as those derived from Fischer-Tropsch processes, for example having initial boiling points of greater than 20 about 315°C or higher. Specific non-limiting examples include reduced crudes, hydrocrackates, raffinates, hydrotreated oils, atmospheric gas oils, vacuum gas oils, coker gas oils, atmospheric and vacuum residues, deasphalting oils, slack waxes and Fischer-Tropsch waxes, and mixtures thereof. In some embodiments, the feedstock is a mixture of gas oil from a coker and vacuum distillation from conventional crudes, derived from 25 distillation towers (atmospheric and vacuum), hydrocrackers, hydrotreaters and solvent extraction units, and may have wax contents of up to about 50% or more. Also in some embodiments, the heavy oils and/or oil residues may include mid-distillates from fossil fuels such as light catalytic cycle cracking oils (LCCO); distillates derived from petroleum, coal, bitumen, tar sands, or shale oil; heavy catalytic cracking cycle oils (HCCO), coker 30 gas oils, oils derived from recycled oil wastes and polymers, vacuum gas oils (VGO) and heavier residues, which for example may contain several percent (e.g. up to about 15%,

from about 1% to about 13%, from about 3% to about 10%, from about 5% to about 8% or from about 6% to about 7%) 3+ ring aromatics, particularly large asphaltenic molecules.

In a further aspect, the present invention provides a non-metallised carbonaceous additive for the hydroprocessing of heavy oils and/or oil residues wherein the non-metallised carbonaceous additive comprises, or consists of, a non-metallised carbonaceous material having been contacted with an oxygen-containing gas at a temperature of at least 120°C to form the non-metallised carbonaceous additive. As the additive according to this aspect of the invention is available for use in the processes also according to the invention, any feature or combination of features disclosed in respect of the non-metallised carbonaceous additive (including but not limited to the density, metal content, iron content, particle size, pore size distribution or any other aspect or combinations thereof) herein may be applied to this aspect of the present invention. Similarly, the present invention contemplates the use of such non-metallised carbonaceous additives as described herein for hydrocracking heavy oils and/or oil residues, and processes for the manufacture of such additives, whereby the processes for the manufacture of such additives comprise one or more steps described herein and pertaining to the non-metallised carbonaceous additive, such as the heated oxidation and/or acid treatment of a non-metallised carbonaceous material in order to form the non-metallised carbonaceous additive.

Examples

20 Comparative Example A

Powdered lignite coke (such as available from RWE as “reactivity-enhanced pulverized lignite coke”) having an average particle size <50µm was selected as the comparative example and the starting material for Inventive Examples 1 and 2 below.

Inventive Example 1

25 10g of powdered lignite coke (average particle size <50µm) was dried at a temperature of 110°C for 12 hours before being heat treated in a muff furnace at a temperature of 350°C for 4 hours under the flow of air.

Inventive Example 2

30 20g of powdered lignite coke (average particle size <50µm) was acid treated in a solution of 100ml of de-ionized water and 80ml of 70wt% nitric acid by stirring at a temperature of 80°C for a period of 6 hours. The solid was separated and washed with de-ionized water until the pH of the rinse water (sampled after rinsing) was stable. The washed solid was

left overnight then dried for 12 hours at 110°C before being heat treated at 350°C for 4 hours under the flow of air.

The three examples were each subjected to surface area, pore size and pore volume

measurements according to Brunauer-Emmett-Teller (BET) (ASTM D3663) method

5 mentioned above yielding the following results:

| Example | Average Pore Size (nm) | Surface area (m ² /g) | Total Pore volume (ml/g) |
|---------|------------------------|----------------------------------|--------------------------|
| A | 1.87 | 292.5 | 0.28 |
| 1 | 3.16 | 471.5 | 0.76 |
| 2 | 6.1 | 405 | 1.1 |

Analysis of the pore size distribution of the examples, based on the Barrett-Joyner-Halenda (BJH) method, yielded the following results:

| Example | Percentage of cumulative pore volume arising from pores | | |
|---------|---|-------------------------------------|--------------------------------------|
| | With average pore size at least 2nm | With average pore size at least 5nm | With average pore size at least 10nm |
| A | 56.7 | 37.8 | 23.9 |
| 1 | 81.3 | 58.2 | 31.3 |
| 2 | 90.1 | 77.3 | 52.6 |

10

Vacuum residue having the properties detailed in the table below was used to test the examples provided above:

| Properties of the vacuum residue | Unit | Value |
|----------------------------------|------|-------|
| API gravity | g/ml | 6.82 |
| Elemental composition | wt% | |
| C | | 84.08 |
| H | | 10.49 |
| N | | 0.48 |
| O | | 0.29 |
| S | | 4.5 |
| Asphaltene | wt% | 17.1 |
| Micro Carbon residue | wt% | 22.5 |
| SIMIDIST | | |
| 538° C ⁺ | wt% | 90 |

Comparative Example B

5 50±0.1 g of vacuum residue was first added to a 300 ml autoclave, and 1.2 g of the original untreated lignite coke (Example A) was then added to the residue. The autoclave was pressurized with pure hydrogen to 123.14 barg (1786 psig) at room temperature, then
10 the temperature was first increased to 120°C, where it was held under stirring for 30 minutes to disperse the additive. The temperature was then raised to 432°C (810°F) and held there for 2 hours under stirring. The extent of conversion (525°C+) resulting from these conditions was determined (via high temperature simulated distillation via gas chromatography) to be 75-80%. The reactor was then cooled to room temperature. After
15 removal of a smaller aliquot of the sample for simulated distillation analysis, the reactor content including liquid and solids was collected by washing with toluene. The mixture was filtered via a 0.45 µm Teflon filter at room temperature. The solid cake was put into 300 ml of toluene and the mixture was sonicated in a ultra-sonication bath for 45 min to remove any toluene soluble materials left on the solid. The toluene and solid mixture was
15 then filtered again. The coke collected from the filter paper was dried under N₂ flow at 120°C for at least 3 hours and the mass measured to obtain the final coke yield.

Inventive Example 3

The same procedure as Comparative Example B was used in Inventive Example 4.

20 However, lignite coke treated as described in Inventive Example 1 was used as the additive instead of the untreated lignite coke of Comparative Example A.

Inventive Example 4

The same procedure as Comparative Example B was used in Inventive Example 4.

However, lignite coke treated as described in Inventive Example 2 was used as the additive instead of the untreated lignite coke of Comparative Example A.

25 Results from Comparative Example B and Inventive Examples 3 and 4 are provided in the table below.

| Example | Additive used | Coke yield (wt%) |
|---------|---------------|------------------|
| B | A | 5.64 |
| 3 | 1 | 3.18 |
| 4 | 2 | 2.17 |

It is clearly demonstrated that the treated lignite coke additives of Inventive Examples 3 and 4 provide a significant advantage to the processes by reducing coke yield compared with Comparative Example B.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as "40 mm" is intended to mean "about 40 mm."

Every document cited herein, including any cross referenced or related patent or

10 application, is hereby incorporated herein by reference in its entirety unless expressly excluded or otherwise limited. The citation of any document is not an admission that it is prior art with respect to any invention disclosed or claimed herein or that it alone, or in any combination with any other reference or references, teaches, suggests or discloses any such invention. Further, to the extent that any meaning or definition of a term in this document

15 conflicts with any meaning or definition of the same term in a document incorporated by reference, the meaning or definition assigned to that term in this document shall govern.

While particular embodiments of the present invention have been illustrated and described, it would be obvious to those skilled in the art that various other changes and modifications can be made without departing from the spirit and scope of the invention. It is therefore 20 intended to cover in the appended claims all such changes and modifications that are within the scope and spirit of this invention.

CLAIMS

1. A process for the hydroprocessing of heavy oils and/or oil residues, the process comprising the steps of:

5 (a) contacting a non-metallised carbonaceous material with an oxygen-containing gas at a temperature of at least 120°C to form a non-metallised carbonaceous additive; and

(b) contacting the heavy oils and/or oil residues with the non-metallised carbonaceous additive in the presence of a hydrogen-containing gas at a temperature of from 250°C to 600°C.

10 2. A process according to claim 1, wherein the non-metallised carbonaceous additive has an average pore size of at least 2nm, preferably from 2nm to 10nm, more preferably from 2.25nm to 8nm, even more preferably from 2.5nm to 6nm and even more preferably still from 3nm to 5nm.

15 3. A process according to any preceding claim, wherein the non-metallised carbonaceous material is selected from the list consisting of: anthracite cokes, lignite cokes, carbon blacks, activated cokes, petroleum cokes, furnace dusts, dusts from Winkler gasification of coal, red mud, electrostatic filter dusts and cyclone dusts, preferably wherein the non-metallised carbonaceous material is a lignite coke.

20 4. A process according to any preceding claim wherein the non-metallised carbonaceous additive comprises one or more metals in a combined amount of at least 6000ppm, preferably from 6000ppm to 100000ppm, more preferably from 7000ppm to 30000ppm, even more preferably from 8000ppm to 20000ppm, even more preferably still from 9000ppm to 15000ppm and yet more preferably still from 10000ppm to 13000ppm, by weight of the non-metallised carbonaceous additive.

25 5. A process according to claim 4, wherein the one or more metals are selected from metals from group VB (5), VIB (6) and VIII (8), preferably from metals from group VIII (8) and more preferably the metal is iron.

6. A process according to any preceding claim, wherein the non-metallised carbonaceous additive comprises at least two modes in the pore size distribution.

30 7. least 90%, of the cumulative pore volume of the non-metallised carbonaceous additive arises from pores having a pore size of at least 2nm.

8. A process according to any preceding claim, wherein at least 50%, preferably at least 75% of the cumulative pore volume of the non-metallised carbonaceous additive arises from pores having a pore size of at least 5nm.

9. A process according to any preceding claim, wherein at least 30%, preferably at least 50% of the cumulative pore volume of the non-metallised carbonaceous additive arises from pores having a pore size of at least 10nm

10. A process according to any preceding claim, wherein the non-metallised carbonaceous additive has a surface area of from 100m²/g to 3000m²/g, preferably from 200m²/g to 1000m²/g, more preferably from 300m²/g to 800m²/g, even more preferably from 350m²/g to 700m²/g, such as from 400m²/g to 650m²/g.

11. A process according to any preceding claim, wherein the non-metallised carbonaceous additive has a total pore volume of from 0.1cm³/g to 5cm³/g, preferably from 0.2cm³/g to 2cm³/g, more preferably from 0.3cm³/g to 1.5cm³/g, even more preferably from 0.5cm³/g to 1.25cm³/g and even more preferably still from 0.7cm³/g to 1cm³/g.

15 12. A process according to any preceding claim, wherein the heavy oils and/or oil residues are contacting with the non-metallised carbonaceous additive in the presence of a hydrogen-containing gas at a temperature of from 250°C to 500°C, preferably from 400°C to 490°C, more preferably from 425°C to 485°C, even more preferably from 440°C to 480°C and even more preferably still from 450°C to 475°C.

20 13. A process according to any preceding claim, wherein the non-metallised carbonaceous material is contacted with the oxygen containing gas at a temperature of from 200°C to 600°C, preferably from 250°C to 450°C, more preferably from 300°C to 400°C and even more preferably from 330°C to 370°C.

25 14. A process according to any preceding claim wherein the non-metallised carbonaceous material is contacted with the oxygen containing gas in a batch process, preferably for a period of at least 1 hour, more preferably from 1 hour to 24 hours, even more preferably from 2 hours to 12 hours, even more preferably still from 3 hours to 10 hours and yet more preferably from 4 hours to 5 hours.

30 15. A process according to any preceding claim wherein the non-metallised carbonaceous material is contacted with the oxygen containing gas in a continuous process.

16. A process according to any preceding claim, wherein the partial pressure of oxygen in step (i) is from about -999 mbarg to about 20 barg, from about -500 mbarg to about 10

barg, from about -250 mbarg to about 5 barg, from about -200 mbarg to about 2 barg, from about -150 mbarg to about 1 barg or from about -100 mbarg to about 500 mbarg.

17. A process according to any preceding claim, further comprising the step of: contacting the non-metallised carbonaceous material and/or additive with an acid before step (b), preferably before step (a).

18. A process according to claim 17 wherein the acid is in the form of an aqueous solution in which the acid is present in an amount of from 1% to 99% by weight of the aqueous solution, preferably from 5% to 95%, more preferably from 10% to 90%, even more preferably from 20% to 70%, even more preferably still from 25% to 50% and yet more preferably from 30% to 35%, by weight of the aqueous solution.

19. A process according to either claim 17 or claim 18 wherein the acid is an inorganic acid, preferably wherein the acid is selected from tungstic acid, sulphuric acid, phosphoric acid, nitric acid, hydrochloric acid and mixtures thereof, more preferably wherein the acid is nitric acid.

15 20. A non-metallised carbonaceous additive for the hydroprocessing of heavy oils and/or oil residues wherein the non-metallised carbonaceous additive comprises, or consists of, a non-metallised carbonaceous material having been contacted with an oxygen-containing gas at a temperature of at least 120°C to form the non-metallised carbonaceous additive.

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2015/053010

A. CLASSIFICATION OF SUBJECT MATTER
INV. C10G47/02
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C10G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|-----------|--|-----------------------|
| X | US 3 617 505 A (COLE EDWARD L ET AL) 2 November 1971 (1971-11-02) column 1, lines 4-9 column 2, lines 25-35 column 3, lines 8-10,23-27 column 4, lines 53-57 examples I,II,VII ----- US 5 807 478 A (MYERS RONALD DAMIAN [CA] ET AL) 15 September 1998 (1998-09-15) column 1, lines 61-63 column 2, lines 15-20; table 1 ----- US 5 064 523 A (KRETSCHMAR KLAUS [DE] ET AL) 12 November 1991 (1991-11-12) cited in the application claims 1,8 ----- | 1-20 1-20 1-20 |



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

| | |
|--|--|
| Date of the actual completion of the international search | Date of mailing of the international search report |
| 11 May 2015 | 18/05/2015 |
| Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016 | Authorized officer Galleiske, Anke |

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/EP2015/053010

| Patent document cited in search report | Publication date | Patent family member(s) | | Publication date |
|--|------------------|--|--|------------------|
| US 3617505 | A 02-11-1971 | NONE | | |
| US 5807478 | A 15-09-1998 | NONE | | |
| US 5064523 | A 12-11-1991 | DD 283417 A5 10-10-1990 DE 3737370 C1 18-05-1989 EP 0314992 A2 10-05-1989 NO 884896 A 05-05-1989 SU 1739853 A3 07-06-1992 US 5064523 A 12-11-1991 | | |