



US 20150307029A1

(19) **United States**

(12) **Patent Application Publication**
Glovak

(10) **Pub. No.: US 2015/0307029 A1**

(43) **Pub. Date: Oct. 29, 2015**

(54) **STEP ASSEMBLY FOR A MOTOR VEHICLE HAVING A BED**

Publication Classification

(71) Applicant: **GM Global Technology Operations LLC, Detroit, MI (US)**

(51) **Int. Cl.**
B60R 3/00 (2006.01)

(72) Inventor: **Dan W. Glovak, Troy, MI (US)**

(52) **U.S. Cl.**
CPC **B60R 3/002** (2013.01)


(73) Assignee: **GM Global Technology Operations LLC, Detroit, MI (US)**

(57) **ABSTRACT**

(21) Appl. No.: **14/264,486**

A step assembly for a motor vehicle having a passenger compartment including a driver side and a passenger side and a cargo bed having first and second side portions includes a step member extending from a first end configured to be mounted at one of the driver side and the passenger side of the passenger compartment to a second end configured to be mounted at a corresponding one of the first and second side portions of the cargo bed.

(22) Filed: **Apr. 29, 2014**






FIG. 2




FIG. 3




FIG. 4





FIG. 5



STEP ASSEMBLY FOR A MOTOR VEHICLE HAVING A BED

FIELD OF THE INVENTION

[0001] The subject invention relates to the art of motor vehicles and, more particularly to a step assembly for a motor vehicle having a bed.

BACKGROUND

[0002] Motor vehicles, such as pick-up trucks, include a cargo bed and a passenger compartment. In most cases, the cargo bed is decoupled or isolated from the passenger compartment to enhance rideability and passenger comfort. Many pick-up trucks have a ground clearance that is greater than that of standard passenger vehicles. Accordingly, stepping into and out from the passenger compartment may be challenging. Also, accessing the cargo bed may prove challenging to certain individuals. Manufacturers have provided steps on either side of the passenger compartment to aid riders stepping into and alighting from the motor vehicle. Manufacturers have also provided tail gate steps that aid in stepping into and down from the cargo bed. Often times, it is desirable to access a side portion of a cargo bed. Accordingly, it is desirable to provide an assist step assembly for a motor vehicle having a bed that provides access to side portions of the cargo bed.

SUMMARY OF THE INVENTION

[0003] In accordance with one exemplary embodiment, a step assembly for a motor vehicle having a passenger compartment includes a driver side and a passenger side and a cargo bed having first and second side portions including a step member extending from a first end configured to be mounted at one of the driver side and the passenger side of the passenger compartment to a second end configured to be mounted at a corresponding one of the first and second side portions of the cargo bed.

[0004] In accordance with another exemplary embodiment, a motor vehicle includes a passenger compartment including a driver side and a passenger side. A cargo bed is mechanically isolated from the passenger compartment. The cargo bed includes a forward portion, a rear portion, and first and second side portions. A step assembly extends from the passenger compartment to the cargo bed. The step assembly includes a step member extending from a first end mounted at one of the driver side and the passenger side of the passenger compartment to a second end mounted at a corresponding one of the first and second side portions of the cargo bed.

[0005] The above features and advantages and other features and advantages of the invention are readily apparent from the following detailed description of the invention when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] Other features, advantages and details appear, by way of example only, in the following detailed description of embodiments, the detailed description referring to the drawings in which:

[0007] FIG. 1 is a perspective view of a motor vehicle having a cargo bed including a step assembly, in accordance with an exemplary embodiment;

[0008] FIG. 2 is a plan view of a flexible bracket assembly of the step assembly of FIG. 1;

[0009] FIG. 3 is a partially cut-away perspective view of a step assembly of FIG. 2, in accordance with an aspect of an exemplary embodiment

[0010] FIG. 4 is a plan view of a flexible bracket assembly, in accordance with another aspect of an exemplary embodiment; and

[0011] FIG. 5 is a plan view of a flexible bracket assembly, in accordance with yet another aspect of an exemplary embodiment.

DESCRIPTION OF THE EMBODIMENTS

[0012] The following description is merely exemplary in nature and is not intended to limit the present disclosure, its application or uses. It should be understood that throughout the drawings, corresponding reference numerals indicate like or corresponding parts and features.

[0013] With initial reference to FIG. 1, a motor vehicle, in accordance with an exemplary embodiment, is indicated generally at 2. Motor vehicle 2 includes a passenger compartment 6 and a cargo bed 10. Cargo bed 10 is mechanically isolated from passenger compartment 6. The term “mechanically isolated” should be understood to describe that movement/vibrations of cargo bed 10 do not translate to corresponding movement/vibrations in passenger compartment 6. Passenger compartment 6 includes a driver side 14 and a passenger side 16. Passenger compartment 6 may also include an additional rear seating/storage area 19. Passenger side 16 may include a cab body portion 24. Driver side 14 may include a corresponding frame member (not shown). Cargo bed 10 includes a forward portion 30, a rear portion 32 having a tailgate (not shown), a first or driver side portion 36 and a second or passenger side portion 38. Cargo bed 10 also includes an underside 40.

[0014] In accordance with an exemplary embodiment, motor vehicle 2 includes a step assembly 50 which, as will be detailed more fully below, extends along passenger compartment 6 and cargo bed 10. Step assembly 50 includes a step member 60 that extends from a first end 66 to a second end 67 through an intermediate portion 69 having a tread or step surface 71. Step member 60 includes a passenger compartment portion 74 that extends along passenger compartment 6 and a cargo bed portion 76 that extends along a portion of cargo bed 10.

[0015] In the exemplary embodiment shown, step assembly 50 includes a first fixed mounting bracket assembly 78, a second fixed mounting bracket assembly 79 and a third fixed mounting bracket assembly 80 that join passenger compartment portion 74 and passenger compartment 6 along passenger side 16. First, second, and third fixed mounting bracket assemblies 78-80 may join step member 60 to passenger compartment 6 through cab body 24. First, second, and third fixed mounting bracket assemblies 78-80 may also limit relative movement of step member 60 and passenger compartment 6. Step assembly 50 also includes a first flexible mounting bracket assembly 84 and a second flexible mounting bracket assembly 86. First and second flexible mounting bracket assemblies 84 and 86 provide a resilient interface between cargo bed portion 76 of step member 60 and cargo bed 10. Specifically, first and second flexible mounting bracket assemblies 84 and 86 allow for relative movement of cargo bed 10 and step member 60.

[0016] Reference will now follow to FIG. 2 in describing first flexible mounting bracket assembly 84 with an understanding that second flexible mounting bracket assembly 86

may include similar structure. First flexible mounting bracket assembly **84** includes a first member **92** extending from a base portion **94** to a cantilevered portion **95** having an opening **96** (FIG. 3). Base portion **94** may be secured to underside **40** of cargo bed **10** through a bracket **97**. Bracket **97** may also be secured to a frame member (not shown) coupled to cargo bed **10**. First flexible mounting bracket assembly **84** also includes a second member **98** that extends from a base section **100** to a cantilevered section **101** having an opening **102** (FIG. 3). Base section **100** is joined to cargo bed portion **76** of step member **60** through a member **104**. Cantilevered portion **95** of first member **92** is joined to cantilevered section **101** of second member **98** through a flexible member **106**.

[0017] In accordance with an aspect of an exemplary embodiment, flexible member **106** may extend from a first end section **110** having a first opening (not separately labeled) to a second end section **112** having a second opening (also not separately labeled). The first opening aligns with opening **96** in cantilevered portion **95** while the second opening aligns with opening **102** in cantilevered section **101**. A first mechanical fastener (not separately labeled) links first end section **110** to cantilevered portion **95**. A second mechanical fastener (also not separately labeled) links second end section **112** to cantilevered section **101**. In this manner, flexible member **106** provides a resilient interface between step member **60** and cargo bed **10**. At this point it should be understood that flexible member **106** may be formed from a first flexible member section **118** and a second flexible member section **119**. First and second flexible member sections **118** and **119** are aligned with one another to form a multi-component flexible member.

[0018] Reference will now be made to FIG. 4 in describing a flexible bracket assembly **124**, in accordance with another aspect of an exemplary embodiment. Flexible bracket assembly **124** includes a first member **128** extending from a base portion **130** to a cantilevered portion **131** having a first opening **132** and a second opening **133**. Base portion **130** may be joined to underside **40** of cargo bed **10** through bracket **97**. Flexible bracket assembly **124** also includes a second member **138** extending from a base section **140** to a cantilevered section **141** having a first opening **143** and a second opening **144**. Base section **141** may be joined to step member **60** through a member **146**.

[0019] In the exemplary embodiment shown, cantilevered portion **131** of first member **128** is joined to cantilevered section **141** of second member **138** by a flexible member **147**. Flexible member **147** includes a body **149** having a plurality of openings (not separately labeled). Two of the plurality of openings align with first and second openings **132** and **133** on first member **128** and another two of the plurality of openings align with first and second openings **143** and **144** on second member **138**. Mechanical fasteners (not shown) may join first and second members **128** and **138** with flexible member **147**. In the exemplary embodiment shown, flexible member **147** may be formed as a single body having multiple openings that join first and second members **128** and **138** to provide a resilient interface between step member **60** and cargo bed **10**. Of course it should be understood that first member **128** may be joined to second member **138** through more than a single flexible member such as shown in FIG. 5. In FIG. 5, a first flexible member **160** is mounted to first and second members **128** and **138** through first openings **132** and **144** and a second flexible member **162** is mounted to first and second members **128** and **138** through second openings **133** and **143**.

[0020] At this point, it should be understood that the flexible members, in accordance with various aspect of the exemplary embodiments, may be formed from an elastomeric material, a non-elastomeric material or a composite material including both elastomeric and non-elastomeric components. Thus, the flexible members may be formed from one or more materials having various degrees of flexibility. Further, it should be understood that the flexible members may take the form of a torsion bar (not shown), hydraulic actuators (also not shown) and the like that enable relative movement between the step member and the cargo bed.

[0021] While the invention has been described with reference to exemplary embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiments disclosed, but that the invention will include all embodiments falling within the scope of the application.

1. A step assembly for a motor vehicle having a passenger compartment including a driver side and a passenger side and a cargo bed having first and second side portions, the step assembly comprising:

- a first member fixedly mounted relative to the cargo bed;
- a step member extending from a first end configured to be mounted at one of the driver side and the passenger side of the passenger compartment to a second end configured to be mounted at a corresponding one of the first and second side portions of the cargo bed, the step member including a second member fixedly mounted at the second end; and

at least one flexible member linking the first member and the second member, the at least one flexible member defining each of a rotational axis and a translational axis of the step member relative to the cargo bed.

2. The step assembly according to claim 1, wherein the first end is fixedly mounted relative to the one of the driver side and the passenger side.

3. (canceled)

4. (canceled)

5. The step assembly according to claim 1, wherein the at least one flexible member extends from a first end section having a first opening to a second end section having a second opening, the first end section being joined to the first member through the first opening and the second end section being joined to the second member through the second opening.

6. The step assembly according to claim 4, wherein the at least one flexible member comprises a first flexible member and a second flexible member.

7. The step assembly according to claim 6, wherein the first flexible member extends from a first end section having a first opening to a second end section having a second opening, the first end section being joined to the first member through the first opening and the second end section being joined to the second member through the second opening.

8. The step assembly according to claim 7, wherein the second flexible member extends from a first end section having a first opening to a second end section having a second opening, the first end section being joined to the first member through the first opening and the second end section being joined to the second member through the second opening.

9. The step assembly according to claim 1, wherein the at least one flexible member comprises a first flexible member section and a second flexible member section abutting and aligned with the first flexible member section.

10. The step assembly according to claim 1, wherein the at least one flexible member comprises a single flexible member.

11. The step assembly according to claim 4, wherein the at least one flexible member includes four openings, the at least one flexible member being joined to the first member through two of the four openings and to the second member through another two of the four openings.

12. A motor vehicle comprising:

a passenger compartment including a driver side and a passenger side;

a cargo bed mounted in mechanical isolation from the passenger compartment, the cargo bed including a forward portion, a rear portion and first and second side portions, the cargo bed including a first member fixedly mounted at one of the first and second side portions;

a step assembly extending from the passenger compartment to the cargo bed, the step assembly including a step member extending from a first end mounted at one of the driver side and the passenger side of the passenger compartment to a second end mounted at a corresponding one of the first and second side portions of the cargo bed, the step member including a second member fixedly mounted at the second end; and

at least one flexible member linking the first member and the second member, the at least one flexible member

defining each of a rotational axis and a translational axis of the step member relative to the cargo bed.

13. The motor vehicle according to claim 12, wherein the first end is fixed relative to the one of the driver side and the passenger side.

14. (canceled)

15. (canceled)

16. The motor vehicle according to claim 12, wherein the at least one flexible member extends from a first end section having a first opening to a second end section having a second opening, the first end section being joined to the first member through the first opening and the second end section being joined to the second member through the second opening.

17. The motor vehicle according to claim 15, wherein the at least one flexible member comprises a first flexible member and a second flexible member.

18. The motor vehicle according to claim 17, wherein the first flexible member extends from a first end section having a first opening to a second end section having a second opening, the first end section being joined to the first member through the first opening and the second end section being joined to the second member through the second opening.

19. The motor vehicle according to claim 12, wherein the at least one flexible member comprises a single flexible member.

20. The motor vehicle according to claim 19 wherein the single flexible member includes four openings, the single flexible member being joined to the first member through two of the four openings and to the second member through another two of the four openings.

* * * * *