




(86) Date de dépôt PCT/PCT Filing Date: 2004/06/23
(87) Date publication PCT/PCT Publication Date: 2004/12/29
(45) Date de délivrance/Issue Date: 2014/01/21
(85) Entrée phase nationale/National Entry: 2005/12/21
(86) N° demande PCT/PCT Application No.: IL 2004/000559
(87) N° publication PCT/PCT Publication No.: 2004/114130
(30) Priorités/Priorities: 2003/06/23 (US60/480,225);
2004/02/23 (US60/546,163)

(51) Cl.Int./Int.Cl. *G06F 9/44* (2006.01),
G06F 9/445 (2006.01), *H03M 7/30* (2006.01)
(72) Inventeurs/Inventors:
MELLER, EVYATAR, IL;
PELEG, SHARON, IL
(73) Propriétaire/Owner:
RED BEND LTD., IL
(74) Agent: NORTON ROSE FULBRIGHT CANADA
LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : PROCÉDE ET SYSTÈME POUR LA MISE À JOUR DE VERSIONS DE CONTENU DANS UN DISPOSITIF DE STOCKAGE

(54) Title: METHOD AND SYSTEM FOR UPDATING VERSIONS OF CONTENT STORED IN A STORAGE DEVICE



(57) Abrégé/Abstract:

A system for generating a compact update package between an old version of content and a new version of content. The system includes a conversion element generator for generating a conversion element associated with the old version and new version. A



(57) **Abrégé(suite)/Abstract(continued):**

modified version generator for generating a modified version including applying the conversion element to the old versions. An update package generator for generating the compact update package. The compact update package includes the conversion element and a modified delta based on the modified version and the new version.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
29 December 2004 (29.12.2004)

PCT

(10) International Publication Number
WO 2004/114130 A3

(51) International Patent Classification⁷: **G06F 9/44**,
H03M 7/30, G06F 9/445

(72) Inventors; and

(21) International Application Number:
PCT/IL2004/000559

(75) Inventors/Applicants (for US only): **MELLER, Eviatar** [IL/IL]; 58/32 Menachem Begin Street, 49732 Petach-Tikva (IL). **PELEG, Sharon** [IL/IL]; 4 Ha'hagana Street, 47203 Ramat Hasharon (IL).

(22) International Filing Date: 23 June 2004 (23.06.2004)

(74) Agent: **REINHOLD COHN AND PARTNERS**; P.O.B. 4060, 61040 Tel-Aviv (IL).

(25) Filing Language: English

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(26) Publication Language: English


(30) Priority Data:
60/480,225 23 June 2003 (23.06.2003) US
60/546,163 23 February 2004 (23.02.2004) US

(71) Applicant (for all designated States except US): **RED BEND LTD.** [IL/IL]; 11 Haamal Street, Industrial Park Afek, 48092 Rosh Haayin (IL).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR UPDATING VERSIONS OF CONTENT STORED IN A STORAGE DEVICE



(57) Abstract: A system for generating a compact update package between an old version of content and a new version of content. The system includes a conversion element generator for generating a conversion element associated with the old version and new version. A modified version generator for generating a modified version including applying the conversion element to the old versions. An update package generator for generating the compact update package. The compact update package includes the conversion element and a modified delta based on the modified version and the new version.

WO 2004/114130 A3

WO 2004/114130 A3



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
14 April 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Method and System for Updating Versions of Content Stored in a Storage Device

FIELD OF THE INVENTION

This invention relates to creating compact updating versions of content stored in a storage device.

BACKGROUND OF THE INVENTION

US 6,546,552 discloses a method for generating a compact difference result between an old program and a new program. Each program including reference entries that contain reference that refers to other entries in the program. The method includes the steps of scanning the old program and for each reference entry perform steps that include replacing the reference of the entry by a distinct label mark, whereby a modified old program is generated. There is further provided the step of scanning the new program and for each reference entry perform steps that include replacing the reference of the entry by a distinct label mark whereby a modified new program is generated. There is still further provided the step of generating the specified difference result utilizing directly or indirectly the modified old program and modified new program.

There is a need in the art to provide for a new method and system for updating versions of content stored in a storage device.

SUMMARY OF THE INVENTION

The present invention provides a method of updating an old version of content on a storage device, comprising:

- (i) obtaining a compact update package, said compact update package includes: a conversion element, a modified delta, and an indication of one of forward

update and a backward update, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is a delta between one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta in the compact update package was generated by applying the conversion element to (1) the new version of content in the case of the modified delta being a delta between the old version of content and the modified version, and (2) the old version of content in the case of the modified delta being a delta between the modified version and the new version of content;

- (ii) determining whether the indication in the compact update package is one of a forward update indication and a backward update indication;
- (iii) in the case of the forward update indication:
 - a) generating the modified version by applying the conversion element to the old version of content on the storage device; and
 - b) generating the new version of content on the storage device by applying the modified delta to the modified version generated in (iii) (a), wherein the modified delta is the delta between the modified version and the new version of content;
- (iv) in the case of the backward update indication:
 - a) generating the modified version by applying the modified delta to the old version of content on the storage device, wherein the modified delta is the delta between the old version of content and the modified version; and

- b) generating the new version of content on the storage device by applying said conversion element to the modified version generated in (iv) (a).

The present invention further provides a program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform a method for updating an old version of content, comprising:

- (i) obtaining a compact update package, said compact update package includes: a conversion element, a modified delta, and an indication of one of forward update and a backward update, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is a delta between one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta in the compact update package was generated by applying the conversion element to (1) the new version of content in the case of the modified delta being a delta between the old version of content and the modified version, and (2) the old version of content in the case of the modified delta being a delta between the modified version and the new version of content;
- (ii) determining whether the indication in the compact update package is one of a forward update indication and a backward update indication;
- (iii) in the case of the forward update indication:
 - a) generating the modified version by applying the conversion element to the old version of content on the storage device; and

- b) generating the new version of content on the storage device by applying the modified delta to the modified version generated in (iii)(a), wherein the modified delta is the delta between the modified version and the new version of content;
- (iv) in the case of the backward update indication:
 - a) generating the modified version by applying the modified delta to the old version of content on the storage device, wherein the modified delta is the delta between the old version of content and the modified version; and
 - b) generating the new version of content on the storage device by applying said conversion element to the modified version generated in (iv) (a).

Yet still further the invention provides a system for updating an old version of content on a storage device, comprising: an input module configured to obtain a compact update package, said compact update package includes: a conversion element, a modified delta, and an indication of one of a forward update and a backward update, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is a delta between one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta of the compact update package was generated by applying the conversion element to (1) the new version of content in the case of the modified delta being a delta between the old version of content and the modified version, and (2) the old version of content in the case of the modified delta being a delta between the modified version and the new version of content; a processor configured to perform:

- (i) determining whether the indication in the compact update package is one of a forward update indication and a backward update indication;
- (ii) in the case of the forward update indication:
 - a) generating the modified version by applying the conversion element to said old version of content on the storage device; and
 - b) generating the new version of content on the storage device by applying the modified delta to the modified version generated in (ii)(a), wherein the modified delta is the delta between the modified version and the new version of content;
- (iii) in the case of the backward update indication:
 - a) generating the modified version by applying the modified delta to the old version of content on the storage device, wherein the modified delta is the delta between the old version of content and the modified version; and
 - b) generating the new version of content on the storage device by applying said conversion element to the modified version generated in (iii)(a).

The invention still further provides a method of updating an old version of content on a storage device, comprising: obtaining a compact update package comprising a modified delta and a conversion element, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is associated with one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta in the compact update package was generated by applying the conversion element to (1) the new version of content when the modified delta is

associated with the old version of content and the modified version, and (2) the old version of content when the modified delta is associated with the modified version and the new version of content; (a) when the modified delta in the compact update package is associated with the modified version and the new version of content: (i) applying the conversion element to the old version of content on the storage device thereby generating a modified version, and (ii) applying the modified delta on the modified version generated in (a)(i), thereby generating the new version of content on the storage device; (b) when the modified delta in the obtained compact update package is associated with the old version of content and the modified version: (i) applying the modified delta on the old version of content on the storage device thereby generating the modified version, and (ii) applying the conversion element on the modified version generated in (b)(i), thereby generating the new version of content on the storage device.

Yet still further the invention provides a method for generating a compact update package between an old version of content and a new version of content, comprising:

- (i) generating a conversion element associated with said old version of content and new version of content and including at least one shift rule that can be applied while updating said old version of content to said new version of content;
- (ii) generating a modified version including applying the conversion element to one of said old and new versions of content; and
- (iii) generating, in a specifically programmed computer, said compact update package, wherein the compact update package includes said conversion element and a modified delta based on a comparison of one of:

said modified version and the new version, when said conversion element is applied to the old version; and

the old version and said modified version, when said conversion element is applied to the new version.

By another aspect the invention provides a system for generating a compact update package between an old version of content and a new version of content, comprising:

a conversion element generator for generating a conversion element associated with said old version and said new version and including at least one shift rule that can be applied while updating said old version to said new version;

a modified version generator for generating a modified version including applying the conversion element to one of said old version and said old version; and

an update package generator of a specifically programmed computer for generating said compact update package, wherein the compact update package includes said conversion element and a modified delta based on a comparison of one of:

said modified version and the new version, when said conversion element is applied to the old version; and

the old version and said modified version, when said conversion element is applied to the new version.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the invention and to see how it may be carried out in practice, a preferred embodiment will now be described, by way of non- limiting example only, with reference to the accompanying drawings, in which:

Fig. 1 is a schematic illustration of a system providing update of versions in a cellular network, in accordance with one embodiment of the invention;

Fig 2 is a schematic illustration of an update package adapted to update an old version of content into a new version;

Fig. 3 is a schematic illustration of an integer value representing an item, in accordance with one embodiment of the invention;

Fig. 4 illustrates a portion of the update package of **Fig. 2** using integer notation, in accordance with one embodiment of the invention;

Fig. 5 is a schematic illustration of an old version and a new version received from update thereof, in accordance with one embodiment of the invention;

Fig. 6 illustrates a portion of the update package used to update the old version of **Fig. 5** to the new version thereof;

- 6 -

Fig. 7 is a flowchart describing in detail the generation of numeral shift rules in an update package, in accordance with one embodiment of the invention;

Fig. 8 illustrates exemplary content and associated meta-data, in accordance with one embodiment of the invention;

Fig. 9 is a schematic illustration of an old version and a new version received from update thereof, in accordance with one embodiment of the invention;

Fig. 9A is a schematic illustration of meta-data associated with the old and new versions of **Fig. 9**, in accordance with one embodiment of the invention;

Fig. 10 illustrates a difference table and its corresponding reference shift rules in accordance with the example of **Fig. 9**, according to an embodiment of the invention;

Fig. 11 is a schematic illustration of partial meta-data associated with the old and new versions of **Fig. 9**, in accordance with one embodiment of the invention;

Fig. 12 illustrates a difference table and its corresponding reference shift rules in accordance with the example of **Figs. 9** and **11**, according to an embodiment of the invention;

Fig. 13 is a flowchart describing in detail the generation of reference shift rules in an update package, in accordance with one embodiment of the invention;

Fig. 14 is a schematic illustration of iterations updating versions of content, according to an iterations embodiment of the invention;

Fig. 15 is a flowchart describing in detail the iterations embodiment of the invention;

Fig. 16 is a flowchart describing an update of an old version of content giving rise to a new version of content;

Fig. 17 illustrates a system for generating a compact update package between an old version of content and a new version of content, in accordance with one embodiment of the invention; and

- 7 -

Fig. 18 illustrates a system for updating an old version of content giving rise to a new version of content, in accordance with one embodiment of the invention.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Fig. 1 is a schematic illustration of a system **101** providing update of versions in a cellular network, in accordance with one embodiment of the invention. Cellular telephones **102** that are coupled to memory devices, execute programs that enable their operation. The version of the program currently executing on the cellular telephones is referred to, hereinafter, as old version. Sometimes there is a need to update the programs in order for the telephones **102** to execute a new version thereof. The new version is generated on a version generator **105**, such as a personal computer (PC). The new version is stored on a server **103** and transmitted, via a transmitter **104** to the cellular telephones **102**.

It should be noted that the system **101** illustrated in **Fig. 1** is a non-binding example and the invention is not limited to cellular networks or to update of programs. Many other types of content require update, such as data stored in storage devices. For example, a Personal Computer (PC), or any other computer, can store files including data required for its operation or for operation of programs executing thereon (such as "info files" known for those versed in the art). Sometimes it is required to update this data via communications lines, for example, via the internet.

Therefore, hereinafter the term "content" will be used instead of "program". In the same way, the term "storage device" will be used instead of the cellular telephones' memory devices in **Fig. 1**.

In order to update content stored in the storage devices, update packages are generated and stored in the server and transmitted to the storage devices or to other devices coupled therewith.

It should be noted that a storage device can be associated with an embedded device. The embedded device can, for example, be a member in a

- 8 -

group that includes, e.g., cellular telephones and/or consumer electronic devices. Alternatively, the storage device can be associated with a computer.

Fig. 2 is a schematic illustration of an update package **201** adapted to update an old version of content **202** into a new version **203**. An old version of content (such as old version **202**) is also referred to, shortly, as “old version”. Likewise, a new version of content (such as the new version **203**) is referred to, shortly, as “new version”.

It is noted that the update package **201** can be generated in accordance with methods known *per se* to those versed in the art. Similarly, the ways to apply this update package in order to update the old version **202** to the new version **203** are also known.

It should also be noted that an update package is sometimes referred to as “delta file”, “difference file” or shortly as “delta” or “difference”, wherein the delta is a collections of modifications occurring while updating an old version to a new version. Thus, a person versed in the art can appreciated that an update package can be a delta file or alternatively, it can include a delta file and perhaps additional information.

The old version **202** includes a block **204** of five items, each item can be the size of at least one word, the size of one or more bytes, or any other applicable measurement. The block **204** is followed by a second block **205** of, e.g., five hundred items. Next, the old version **202** includes an item **206** that includes at least a reference (such as a pointer) to a certain item **207** in the second block **205**. Items including at least one reference are referred to, hereinafter, as “reference items”. For example, a reference item **206** can include an instruction associated with an absolute reference to **207**, such as “jump to the absolute address of item **207**”.

It should be appreciated that if the content represented by the old and new versions (such as **202** and **203**) is a computer program, for example, a block can represent a program function, as known to those versed in the art.

- 9 -

Reference item **206** is followed by another reference item **208**, including a reference to a different item **209** in the second block **205**. The reference item **208** is followed by other reference items, all include references to items within the second block **205**, the last of them is reference item **210**. Whilst not shown in the figure, according to the example there are, e.g. one hundred reference items between reference item **206** and reference item **210**.

It is appreciated that the old version **202** can include also non-reference items, i.e., items that include no reference. The item **211** is an example to a non-reference item. Unless specifically noted, the term “item” refers, hereinafter, both to reference and non-reference items.

In addition, the old version **202** can include reference items to other items that are not included in the old version **202**, i.e., references to items being external to the content. For example, if the old version represents a computer program that is loaded to a computer's RAM (Random Access Memory) during execution, such a reference item can refer to another item that is stored in an area of the RAM which is outside the area used to store the program.

Hereinafter, reference items that include at least a reference to an item included in the content are referred to as “explicit reference items”, while reference items that include at least a reference to an item that is external to the content are referred to as “implicit reference items”.

Back to **Fig. 2**, whilst not shown in the figure, following the last reference item **210** there are seventy items. For the matter of convenience, these seventy items (including item **211**) are referred to, hereinafter, as “terminating items” **212**. The seventy items include non-reference items (such as item **211**) and/or implicit reference items (such as item **213**). It should be clarified that the size of any content being updated according to this example is not limited and accordingly any size of any block along this content is non-limited too.

Although not shown in **Fig. 2**, non-reference items can exist between reference items, and there is no requirement that reference items be continuous.

- 10 -

For example, there could be one or more non-reference items somewhere between the reference items **206**, **208**, ..., **210**.

The update package **201** is adapted to modify the old version **202** of the content, generating a new version **203** of the content. An update process operates in accordance with the update package **201** to generate this new version **203**.

One difference between old version **202** and new version **203** in the example, is the absence of block **204** from the new version **203**, where the second block **205** shifts backwards and occupies the block **204** on the storage device. According to the example, block **204** includes five items, and therefore the second block **205** shifts five items backwards. It can be appreciated, thus, that further to block **205**'s shift backwards, all the items included therein are shifted correspondingly (by five items). Such is the case, e.g., also with items **207** and **209** (and their corresponding items **207'** and **209'** in the new version). It is noted that item **206** includes a reference to item **207**. After shifting item **206** backwards to generate item **206'**, this item still references item **207**, i.e., it references the address of **207** in the old version. It is required to replace the content of item **206'** so it will reference item **207'** in its new location in the new version.

It should be noted that the content of the non-reference item **211** that includes no reference and the content of the implicit reference item **213** do not require modification in this case, although their location is also shifted up by five items. It should also be noted that throughout the description, examples applied to explicit reference items are also applicable with reference to implicit reference items, unless specifically noted otherwise.

Reverting now to the update package **201**, it includes commands for updating the old version **202** to the new version **203**. It should be considered that in the current example commands are illustrated as string characters representing one or more operation to be performed by updating the old content (such as "copy", "replace" etc.). However, other ways to represent commands are also applicable, such as using operation codes (shortly referred to as op-codes), wherein each command has a predetermined op-code assigned to it. In addition,

- 11 -

sometimes commands are represented by alternative ways to those illustrated in **201**. For example, a “replace” command can be represented by an insert command, where the inserted content replaces the existing content.

As shown, the first command included in package **201** is to delete five items, thereby deleting the first five items in **102**, being block **204**. Next, the update package includes a command to copy five hundreds items to the beginning of the new version, thereby shifting the block **205** five items backwards, giving rise to block **205'**.

After copying block **205**, *prima facie* it would be required to copy items **206**, **208**, ..., **210**, while shifting their location five blocks up, giving rise to the corresponding items **206'**, **208'**, ..., **210'**. However, as explained before, the included references of items **206'**, **208'**, ..., **210'** needs to be updated to reference **207'**, **209'**, ... instead of **207**, **209**, ... That is, these reference items or at least part of them need to be replaced. Instead of copying a reference item and then replacing it by a shifted reference, it is possible to replace the item on the first hand, saving the copy operation. The update package **201** includes therefore a hundred replacement commands, one for each reference item **206**, **208**, ..., **210**, for replacing them by a reference to the corresponding shifted item (**206'**, **208'**, ..., **210'**).

Following the hundred replacement commands, the update package **201** includes a copy command that copies the seventy terminating items **212** to follow the replaced hundred reference items in the new version **203**, i.e., the seventy items (including item **211** and **213** that gives rise to items **211'** and **213'**) shifted five items backwards in the new version **203**.

A person versed in the art can appreciate that the update package **201** in the example above includes, amongst others, a hundred replacement commands wherein each command includes a replacing item. That is, the update package **201** includes a hundred replacing items. Bearing in mind that update packages can be transferred over limited bandwidth communication lines, such as internet

- 12 -

or mobile (cellular) networks, reducing the size of update packages would be beneficial.

Thus, unlike the existing method in the art for generating and applying update packages, the invention discloses other methods that can produce more efficient update packages, or “compact update packages” as referred to hereinafter. One embodiment for generating such efficient update packages is referred to, hereinafter, as ‘integer notation embodiment’, wherein this embodiment generates ‘integer shift rules’. The background for explaining integer shift rules is exemplified below, with reference to Figs. 2 and 3.

It should be appreciated that according to some embodiments of the invention it is possible to use integer values for representing items in the old and new content (202 and 203 respectively). It can be appreciated that items are data stored on a storage device such as disk or memory. If the size of an item is four bytes, it is possible to visualize the data stored in an item as an integer number occupying the four bytes. Fig. 3 is a schematic illustration of an integer representation of a four-byte item 301, according to one embodiment of the invention. The most significant byte (left-most byte) 302 is occupied by the binary value 00001011 (0x0B in hexadecimal), the second byte 303 is occupied by the binary value 10011101 (0x9D in hexadecimal), the third 304 by the value 11110111 (0xF7 in hexadecimal) and the least significant byte 305 by the value 10000101 (0x85 in hexadecimal). The four bytes can thus be interpreted as one integer having the hexadecimal value 0x0B9DF785. That is, the integer 0x0B9DF785 is the integer representation of item 301, or *int*(301) as referenced hereinafter. It should be noted that ‘*int*’ stands for ‘integer’.

It should be noted that any item, including non-reference items, can be represented by integers as well, and therefore *int*(211), for example, is the integer representation of item 211.

Reverting now to Fig. 2, the explicit reference item 206, for example, can include a program instruction “jump to the absolute address of item 207”. If the absolute address of item 207 is 0x9DF785, then the instruction included in item

- 13 -

206 is equivalent to "jump to 0x9DF785". Program instructions can be represented by predetermined op-codes. Hence, the op-code for "jump to" can be, for example the decimal integer '11' (or 0xB in hex). As was explained before with reference to **Fig. 3**, the integer representation of item **206** according to this example is 0x0B9DF785. The op-code in this case is represented by byte **302**, while the bytes **303**, **304** and **305** are indicatives to the referenced item. That is, the bytes **303**, **304** and **305** together are indicative of the referenced item, or *ind(207)* as referred to hereinafter. It should be noted that '*ind*' stands for 'indicative'.

Alternatively, it is possible to view the whole integer as indicative of the referenced item. According to this example, if item **206** includes the instruction "jump to item **207**" then the integer 0x0B9DF785 can be considered as *ind(207)*, unlike the previous embodiment, where only 0x9DF785 was considered as the indicative value. It should be appreciated that there may be another reference item (although not shown in **Fig. 2**) that can include an instruction such as "call item **207**" wherein the op-code for the call instruction is the decimal integer 27 (or 0x1B in hex). According to this example, *int(reference item)* is 0x1B9DF785. In addition, 0x1B9DF785 can be referenced in this case as *ind(referenced item)* or *ind(207)*. That is, according to this embodiment there can be more than one indicative value to an address of a referenced item.

It can be further appreciated that indicative values can be any part of (including the whole) an integer representation of an item. Also, the example referred to a four-byte size of an item. This size was used here (and will be used again below) only as an example, and any applicable item size can be used. Note also that representing numbers as integers is only a non limiting example; and other known *per se* number representations are applicable.

Bearing in mind that an item (including a reference item and/or a non-reference item) can be represented by an integer value, and reverting back to **Fig. 2**, it is possible to express replacement commands in update package **201** in

- 14 -

terms of integers. For example, "Replace int(206), int (206')"' is equivalent to "Replace 206, 206'" that is part of the update package 201.

Fig. 4 illustrates a portion of the update package of Fig. 2 using integer notation, according to one embodiment of the invention. Portion 401 is the portion of the update package 201 that includes replacement commands. It is noted that portion 401 is in accordance with the prior art. It should be noted that any replacement command in this example is associated with two reference items, one in the old version and one in the new version. The two reference items are referred to, hereinafter, as a "replacement pair".

A person versed in the art can appreciate that 402 is equivalent to portion 401, wherein the replacement commands are expressed using the integer notation, in accordance with one embodiment of the invention. When using the integer notation, there are two integers associated with each replacement command. The two integers are referred to, hereinafter, as an "integer replacement pair". One integer in an integer replacement pair is referred to as a "pre-modification integer" (representing the item in the old version) and the second is a "post-modification integer" (representing the item in the new version).

Looking at the integer replacement pairs for the explicit reference items in the old version 202, i.e., looking at the integer replacement pairs in 402, it is possible to see that the integer values reflect the shift of the referenced items. For example, it is possible to view the integer replacement pair <int(208), int(208')>, when items 208 and 208' references items 209 and 209' respectively. If the item 209 was originally located at address 0x9DF785, wherein the size of an item is four bytes, then after shifting the content of item 209 five items backward (i.e., 20 bytes backward) to yield item 209', this item 209' will be located at address 0x9DF771. Bearing in mind that the least significant bytes of the reference item include a value indicative of the referenced item's address, it can be understood that the least significant bytes of the integer representing reference item 208 are 0x9DF785 (that is, item 208 references item 209), and the least significant bytes

- 15 -

of the reference item **208'** are 0x9DF771 (i.e., item **208'** references item **209'**). The difference between the two integers comprising together an integer replacement pair reflects, therefore, the shift that is performed while updating old version **202** to new version **203**. This difference is referred to, hereinafter, as "modification difference". Modification difference is represented by *diff* together with the integer modified, such as *diff(208)*.

Thus, instead of associating a pre-modification integer and a post-modification integer in an integer replacement pair, it is possible to associate a pre-modification integer or a post-modification integer with a modification difference. A pair associating a pre-modification integer together with a modification difference is referred to, hereinafter, as "integer shift pair".

Back to **Fig. 4**, **403** is a portion equivalent to the portions **401** and **402** that is using integer shift pairs notation.

The description with reference to **Figs. 3** and **4** provides a background for understanding an embodiment of the invention that utilizes the integer notation, hereinafter, the 'integer notation embodiment'.

Fig. 5 illustrates a more complex example of old and new versions (compared to the old and new versions illustrated in **Fig. 2**) in order to exemplify and explain the integer notation embodiment. In the figure, an old version **501** is updated to give rise to a new version **502**. Thus, the old version **501** includes a block **503**, deleted while generating the new version **502**. The size of the deleted block is referred to, hereinafter, as *size(503)*. Following the example of **Fig. 2**, it can be understood that further to the deletion of block **503**, the items in the new version are expected to be shifted backwards by *size(503)* items backwards.

In the old version, block **504** follows block **503**. Six items (**505**, **506**, **507**, **508**, **509** and **510**) are marked within block **504**. The addresses where the items begin are marked, hereinafter, as *addr(item)*, e.g., *addr(505)*, *addr(506)* and *addr(507)* etc. The blocks **508**, **509** and **510** are explicit reference items. The item **509** references item **507**, and items **508**, **510** reference items **511** and **512** respectively. It is noted that items **511** and **512** are part of the old version, and are

- 16 -

located forward to block **504**. Thus, the explicit reference items **508**, **509** and **510**, include values indicative of *addr(511)*, *addr(507)* and *addr(512)* respectively.

In the new version **502** the block **504'** corresponds to block **504**. As expected, the block **504'** is shifted backwards by *size(503)*. The items **505'**, **506'**, **507'**, **508'**, **509'** and **510'** correspond to items **505**, **506**, **507**, **508**, **509** and **510** respectively. Like block **504'**, the items **505'**, **506'**, **507'**, **508'**, **509'** and **510'** are also shifted backwards by *size(503)*.

Following block **504** the old version **501** includes a block **513** having one item **514** marked therewith. The item **514** is an explicit reference item that references item **506**, i.e., the reference item **514** includes a value indicative of the address *addr(506)*. In the new version, block **513'** corresponds to block **513** and item **514'** corresponds to item **514**. However, a new block **515** of one or more items is inserted into block **513'**, before item **514'**. That is, *size(513') > size(513)*. According to this example, *size(515)* is smaller than the *size(503)* and therefore it can be appreciated that item **514'** is shifted backwards by (*size(503) – size(515)*).

Back to the old version **501**, there is a third block **516** following block **513**. Five items are marked within this block, specifically these are items **517**, **518**, **519**, **511** and **512**. Items **517** and **518** are explicit reference items referencing items **519** and **505**, that is, items **517** and **518** include values indicative of the referenced items **519** and **505** or, in other words, indicative of *addr(519)* and *addr(505)* respectively.

In the new version, block **516'** corresponds to block **516**. Likewise, items **517'**, **518'**, **519'**, **511'** and **512'** correspond to items **517**, **518**, **519**, **511** and **512** respectively. Following the insertion of block **515** to block **513'** it can be appreciated that the items in block **516'** are shifted backwards by (*size(503) – size(515)*) items.

The example of **Fig. 5** illustrates also the existence of a terminating block **517** in the old version, corresponding to block **517'** in the new version. The

- 17 -

update process inserts a new block **520** of one or more items to block **517'**. According to the example the size of the new block **520** is ($size(503) - size(515)$), and therefore the total size of the new version **502** is substantially similar to this of the old version **501**.

It should be noted that the example provided with reference to **Fig. 5** is by no means binding. An old or new version of any content can be comprised by any number of blocks, each including any number of items as applicable to the case. Similarly, while updating an old version to a new version, the update process can insert, delete, replace and/or perform any required operation, as many times as required, wherein the size of items or blocks may vary, depending upon the particular application.

It should also be noted that the size of an item is non-limited as well, but hereinafter, the size of an item in the content illustrated in **Fig. 5** is demonstrated as four bytes.

A person versed in the art can appreciate that for updating the old version **501** to new version **502**, according to one embodiment it is possible to copy block **504** and a first portion of block **514** to the new version, insert the new block **515**, and then copy the second portion of block **514** together with blocks **516** and **517** to the new version. However, as was already explained with reference to **Fig. 2**, doing so, the explicit reference items in the new version will reference items in their original addresses, as were in the old version. For example, in the old version the explicit reference item **508** references item **511** and therefore the least significant bytes of item **508** include a value indicative of $addr(511)$. In the old version item **508** is located at $addr(508)$. After copying block **504** to the new version, it is appreciated that item **508** is located at $addr(508')$ which is backward to $addr(508)$ in this example. However, item **508** still includes reference to item **511**, that is, it includes a value indicative of $addr(511)$, where it is expected to include a reference to item **511'** by including a value indicative of $addr(511')$. Therefore, according to the embodiment, after copying content from the old version to the new one and after inserting new

- 18 -

blocks (such as block **515**) the update package can include commands for replacing reference items, such as “in **508**’ replace the value indicative of *addr(511)* with a value indicative of *addr(511)*’”, or shortly, “Replace **508**, **508**”.

Having provided a background discussion of the integer notation embodiment (with reference to **Figs. 3** and **4** above) and exemplary old and new versions (**Fig. 5**), there follows a description (with reference to **Fig. 6**) exemplifying how to obtain a portion of the update package in accordance with the integer notation embodiment, compared with an equivalent portion of the update package obtained in accordance with the prior art. As will be evident from the description the portion obtained in accordance with this embodiment of the invention can be considerably smaller than that obtained in accordance with methods known in the prior art.

Turning now to **Fig. 6**, portion **601** contains replacement instructions for updating the explicit reference items illustrated in **Fig. 5**. It is noted that portion **601** is generated by applying a conventional diff methods on the old and new versions of **Fig. 5**. It is also noted that **601** is a portion of the complete update package used to update the old version **501** to the new version **502** (the complete update package is not illustrated). The portion includes only replacement commands, while other commands such as insert and/or delete are omitted. It should be noted that in the example of **Fig. 5** there are six reference items, and therefore there are six replacement commands in the portion **601**. Portion **602** is an equivalent portion to **601**, expressed in terms of integer replacement pairs, where in light of the description of **Figs. 3** and **4** it can be understood that for a reference item the term ‘*int(item)*’ reflects the address reference thereby.

It was further explained, with reference to **Fig. 4**, that instead of using integer replacement pairs’ notation it is possible to express a replacement command in terms of integer shift pairs. That is, instead of replacing a reference item, it is possible to modify the reference included therein, regardless of other

- 19 -

information stored therewith such as an op-code, to reflect the shift in the referenced item's location.

From **Fig. 5** it arises that the modification difference of some of the items in the example is *size(503)*, while other items are characterized by a modification difference of $(size(503) - size(515))$. Therefore, it is possible to change portion **602**, while instead of using replacement commands, it is possible to use modification commands using pre-modification integer shift pairs notation, as illustrated in **603**.

It should be noted that the modification difference in an integer shift pair is indicative of the referenced item's shift, and not of the reference item's shift.

In **604** the same portion of the update package is illustrated, where the modification commands are sorted according to the modification differences. It should be noticed that the sorted portion **604** includes two groups. One group includes commands for modifying *int(509)*, *int(514)* and *int(518)*, wherein the modification difference is *size(503)*. The second group includes commands for modifying *int(508)*, *int(510)* and *int(517)*, wherein the modification difference is $(size(503) - size(515))$.

It should be recalled that an integer or part thereof is indicative of a referenced item's address. It should also be considered that while updating a reference item the reference needs to be modified regardless of the op-code or any other information being associated with it. Therefore, in an integer shift pair, instead of referring to an integer it is possible to refer to the value indicative of the referenced item, or to '*ind*(referenced item)'. A pair of *ind*(referenced item) and its associated modification difference is referred to, hereinafter, as an "indicative shift pair".

It should be noted that although not shown in Figs. 5 and 6, sometimes there are more than one reference item referencing the same referenced item. If the referenced items' indicative values are part of the referencing items' integer representation, all these referencing items can sometimes be represented by a similar indicative value. If the entire integer is used as the referenced item's

- 20 -

indicative value, there may be more than one indicative value representing the referencing items.

For example, a referenced item's address is 0x5F8B23. Four reference items reference this item by designating its address. The first has an op-code 0xA2, the second has an op-code 0x0F and the third, 0x1B. The fourth reference item has an op-code similar to the first (i.e., 0xA2). If the indicative value is represented by the three least significant bytes then all four reference items will be represented as *ind*(0x5F8B23). On the contrary, when the whole integer is used as an indicative value, there will be three different indicative values representing the four reference items. The first and the fourth reference items will be presented as *ind*(0xA25F8B23), the second will be represented as *ind*(0x0F5F8B23), and the third as *ind*(0x1B5F8B23).

Reverting back to **Fig. 6**, in **605** a sorted portion equivalent to **604** is illustrated, using the indicative shift pairs notation. **605** illustrates that when shifting reference items referencing items in block **504**, the indicative values therein should be modified to reflect a shift of *size*(**503**). When shifting reference items referencing items in block **516**, the indicative values therein should be modified to reflect a shift of (*size*(**503**) – *size*(**515**)).

Seeing that the two groups exist also in **605**, it is possible to sort each group internally according to the *ind*(referenced item), and consequently generating **606**. Instead of having three modification commands for modifying reference items having values indicative of items in block **504**, it is possible to generate one composite modification command to update all the values indicative of items in block **504** to reflect a shift of *size*(**503**). In other words, if a reference item includes a value indicative of an item that is between **505** and **507**, included, this value should be modified to reflect a shift of *size*(**503**). In the same way, instead of having three modification commands for modifying reference items having values indicative of items in block **516**, it is possible to generate one composite modification command to update all the values indicative of items in block **516** to reflect a shift of (*size*(**503**) – *size*(**515**)). In other words, if a

- 21 -

reference item includes a value indicative of an item that is between 511 and 519, included, this value should be modified to reflect a shift of ($size(503) - size(515)$), as illustrated in 607. Such a composite modification command is referenced, hereinafter, as an integer shift rule. That is, 607 demonstrates two integer shift rules that can be applied in order to update the explicit reference items in the example of Fig. 5.

Thus, it can be appreciated that the portion 607, using integer shift rules is equivalent to portion 601, using replacement commands. Yet, portion 607 includes only two integer shift rules, instead of six replacement commands that are included in 601. Hence the update package including portion 607 is equivalent to an update package including portion 601. If the space required for storing an integer shift rule is smaller than the space required for storing its equivalent replacement commands, it is possible to reduce the size of an update package by using the equivalent integer shift rule.

The reduction in the update package size can be significant. Considering, for example, a non limiting application of updating version of software on cellular telephones, an integer shift rule can sometimes save even tens of thousands replacement commands.

It should also be noted that instead of using integer shift rules, any numeral shift rule can apply as well, therefore, hereinafter, the term 'numeral shift rule' is used.

Fig. 7 is a flowchart describing in detail the generation of numeral shift rules in an update package, in accordance with one embodiment of the invention. It should be appreciated that in order to create an update package and numeral shift rules, diff should be utilized (701, in any method known *per se*) between an old version and a new version in order to detect differences between the two versions. There are many tools available today for detecting differences between versions, such as the UNIX diff program. The diff generates pairs of differences between the old and new versions, amongst can be replacement pairs. If the diff includes replacement pairs (702), at least some of them are grouped together

- 22 -

(703) to form a portion of the diff, thus creating, for example, a portion like the portion 601 of Fig. 6. Next (704), the replacement pairs are converted to form integer replacement pairs, using the integer notation as was exemplified before with reference to Figs. 4 and 6 (see 402 and 602 therein).

After converting the replacement pairs to integer replacement pairs the integer replacement pairs are converted (705) to be integer shift pairs, by associating the pre-modification integers together with their modification difference, a stage that was previously exemplified with reference to Figs. 4 (403) and 6 (603). The integer shift pairs are sorted (706) according to the modification differences as in Fig. 6, block 604.

After sorting, the pre-modification integers in the integer shift pairs are replaced (707) by the respective referenced items' indicative values to form indicative shift pairs, a stage exemplified before with reference to Fig. 6 (605). It should be noted that in those cases when there are several indicative shift pairs having the same modification difference(708), these indicative shift pairs are sorted (709) in accordance with their indicative value. In those cases when the whole integer is considered as the referenced items' indicative value, it is appreciated that the block 707 is redundant and can be skipped, while the *int* value serves instead of the *ind* throughout the rules' generation process. The blocks 606 of Fig. 6 is an example to block 709 in the current figure.

If there are groups including more than one indicative shift pairs having the same modification difference, the indicative shift pairs in a group can be joined (710) to form a numeral shift rule indicating the first and last referenced items' indicative values in the group and the modification difference characterizing them, as was previously exemplified with reference to Fig. 6 (see 607).

It is noted that sometimes further optimizations are applicable. For example, if there are two numeral shift rules having the same modification difference, wherein the last referenced item's indicative value of the first rule and the first referenced item's indicative value of the second rule are close enough,

- 23 -

the two rules can be joined to form one joined numeral shift rule. The joined numeral shift rule indicates the first referenced items' indicative value of the first numeral shift rule and the last referenced items' indicative value of the second numeral shift rule, together with the modification difference that characterizes them. It should be noted that when two non-adjusting numeral shift rules are joined, the numeral shift rule (or indicative shift pairs) between them are swallowed by the joined rule, and therefore their pre-modification reference items are susceptible to erroneous update (that is, they may be updated to reflect an erroneous shift).

It should be noted that the invention is not bound to the specific sequence of operation and manner of obtaining the integer shift rules as described in **Fig. 7**, or to the integer shift rule terminology used in portion **607** of **Fig. 6**.

In addition, the embodiments illustrated so far reduce the size of an update package by using numeral shift rules, thus generating a compact update package. It is noted that in those cases using different terminologies to describe an update package such as "delta" or "difference" or "diff", the compact update package could be named also, e.g., "compact difference results".

According to a different embodiment, sometimes content can be accompanied by associated descriptive data referred to, hereinafter, as 'meta-data'. Common forms for providing meta-data are symbol tables, debug tables and linker map used to describe computer programs. However, meta-data is not limited to computer programs and other types of content can have meta-data as well. It should also be noted that associated meta-data can be separated from the content, for example by storing it in a different file or by storing it in a database. Alternatively, the meta-data can be stored as part of the content, as applicable to the case.

Fig. 8 illustrates exemplary content and associated meta-data. Content **801** includes four blocks **802**, **803**, **804** and **805**. Block **803** starts at address *addr(803)*, block **804** starts at *addr(804)*, and block **805** starts at *addr(805)*. The associated meta-data **806** describes the content and the blocks thereof, wherein

- 24 -

for each block the meta-data **806** provides a start address and the length of the block. It should be notified, however, that this is a non-limiting example and meta-data can include other data instead of the start address and length of each block.

When generating an update package intended to update an old version of content to a new version thereof, if meta-data is associated with the content, it is possible to use the meta-data in order to encode modifications to references as will be explained below with reference to **Figs. 9 and 10**.

The example and description of **Fig. 8** will serve as a basis for understanding how to obtain a so called 'reference shift rule' in accordance with another embodiment of the invention, as will be explained with further detail with ref to **Fig. 9**, which is a schematic illustration of an old version **901** and a new version **902** received from update thereof, and with reference to **Fig. 9A** that is a schematic illustration of meta-data and a difference table (**9A01**, **9A02** and **9A03** respectively) associated with the old and new versions of **Fig. 9**, in accordance with one embodiment of the invention.

The old version **901** includes four blocks (**905**, **906**, **907** and **708**), their respective start addresses are *addr(905)*, *addr(906)*, *addr(907)* and *addr(908)*. In the new version, a new block **909** of at least one item was added to block **905**, thus generating the corresponding block **905'**. It can be appreciated that the size of block **905'** is thus bigger than the size of the block **905** by *size(909)*. In addition, unless additional insertions of items to the content or deletions of items from the content further occur during the update process, items forward to the new block **909** are expected to shift forward by *size(909)*.

Forward to block **905'**, block **906'** corresponds to block **906**, block **907'** corresponds to block **907** and block **908'** corresponds to block **708**. A new block **910** of one or more items is inserted also into block **907'**. The size of this new block is *size(910)*. Thus, item forward to the new item **910** are shifted forward by (*size(909) + size(910)*).

- 25 -

In the old version, block 906 includes at least three explicit reference items 911, 912 and 913, referencing items 914, 915 and 916 correspondingly. The referenced item 914 is in block 908, the referenced item 915 is in block 907, and the referenced item 916 is in block 906. In addition, block 908 includes at least one explicit reference item 917 that references item 918. Like the referenced item 915, the referenced item 918 is also in block 907.

The meta-data 9A01 in association with the old version 901 describes the four blocks, their respective start address and their length. The meta-data 9A02 in association with the new version 902 describes the blocks included therein. By comparing meta-data 9A01 with meta-data 9A02 it can be demonstrated that the start address of block 905' in this case is similar to this of block 905 of the old version. However, the start address of block 906' equals to $(addr(906) + size(909))$. Likewise, the start address of block 907, when compared to the start address of block 907 of the old version also reflects a shift of $size(909)$, that is, $addr(907') = addr(907) + size(909)$. On the other hand, the start address of block 908' demonstrates a shift of $(size(909) + size(910))$, that is, $addr(908') = addr(908) + size(909) + size(910)$.

Whereas the description how to obtain reference shift rules will be described below with respect to the specific example of Fig. 9, it should be noted, incidentally, that the example of Figs. 9, 9A and 10 is non-limiting. The old and new versions can have any applicable number of blocks, new blocks and items can be inserted at any location or deleted while updating the old version to a new version. It should also be appreciated that it is possible to indicate the meta-data 9A02 of the new version by using addresses in the old version, and adding the sizes of the inserted blocks when applicable. The result, together with the modification difference (that is, the shift that characterizes the start address of each block in the old version and its corresponding block in the new version) is referred to as a "difference tables". This is illustrated in 1000 (see Fig. 10), which is the difference table corresponding to meta-data 9A01 and 9A02.

- 26 -

It can be appreciated that reference shift rules can be generated in accordance with the difference table 1000. If a reference item references another item in block 906' for example, and following the information in the difference table, it is possible to appreciate that in the new version its corresponding reference item should be modified to reflect a shift of $size(909)$ in the referenced items location. In the same way if a second reference item references another item in block 908', it is possible to appreciate that in the new version its corresponding reference item should be modified to reflect a shift of $size(909) + size(910)$ in the referenced items location.

Generally speaking, the difference table reflects therefore reference shift rules. For example, for each referenced item in block 906' the characteristic shift is $size(909)$. In the same way for each referenced item in block 907' the characteristic shift is also $size(909)$ whereas for each referenced item in block 908' the characteristic shift is $size(909) + size(910)$.

It is possible to determine whether a reference item references another item in a certain block in accordance with the blocks' start address and length as indicated in the difference table. Therefore a reference shift rule may be represented by the exemplary notation "Modify $\langle addr(\text{referenced block}), size(\text{referenced block}) \rangle$, shift".

In the example of Fig. 9A, it can be seen that blocks 906' and 907' both are characterized by the same shift. Seeing that blocks 906' and 907' are consecutive, it can be appreciated that their two reference shift rules can be joined to form one reference shift rule saying "Modify $\langle addr(906'), size(906') + size(907') \rangle$, $size(909)$ ".

In Fig. 10, block 1001 exemplifies the reference shift rules based on the difference table 1000. In this case three reference shift rules (1002, 1003 and 1004) are illustrated.

Yet, sometimes, as is known *per se*, the meta-data does not describe one or more blocks of the content. See for example, Figs. 9 and 11. In Fig. 11, the meta-data 1101 of the old version 901 of Fig. 9 and the meta-data 1102 of the

- 27 -

new version **902** of **Fig. 9** are illustrated. It is noted that the meta-data **1101** and **1102** are partial, that is, block **907** and its corresponding block **907'** are not described. It can be appreciated therefore, that in the difference table **1201** of **Fig. 12**, the differences for block **907'** are not described as well. This affects the generation of reference shift rules illustrated in **1202**. Like the previous example of **Figs. 9** and **10** in the current example, there are also three reference shift rules **1203**, **1204** and **1205**. However, because block **907'** is not described, the second rule **1204** corresponds to a smaller block compared to the second rule **1003** of the previous example. Therefore, a reference item referencing another item in block **907'** cannot be modified in accordance with the reference shift rules in this case.

Nevertheless, following the description of the numeral shift rules with reference to **Figs. 5, 6** and **7** above, a person versed in the art can appreciate that it is possible to try and apply numeral shift rules wherever reference shift rules are non applicable. As it may be recalled, the method for utilizing numeral shift rules does not require meta-data and therefore utilizing numeral shift rules is applicable in this case.

Fig. 13 is a flowchart describing in detail the generation of reference shift rules in an update package, in accordance with one embodiment of the invention. After receiving meta-data (**1301**) respective of an old and a new version, a difference table (such as difference table **1000** of **Fig. 10**) is created (**1302**). The difference table includes at least information about blocks (such as their start addresses) in the old version associated with information about their respective corresponding blocks (such as their start addresses) in the new version. Alternatively, the difference table can include at least information about blocks in the old version associated with information about their respective modification differences (i.e., their shift value). It is noted that other alternatives are allowed as well, such as including at least information about blocks in the new version associated with information about their respective modification differences.

For each block described in the difference table a reference shift rule is being generated (**1304**). Next reference shift rules referring to adjacent blocks are

- 28 -

joined. It should be noted that the invention is not bound to the specific sequence of operation and manner of obtaining the reference shift rules as described in **Fig. 13**.

It should also be noted that the notation used to describe a reference shift rules is non binding and other notations are applicable as well. For example, instead of designating the first item and the length of the block or blocks covered by the rule (in other words, a “section”), it is possible to designate the first and the last items in the section. Note that the latter applies also to numeral shift rules described with reference to **Fig. 7**, *mutatis mutandis*.

The description above describes embodiments for generating numeral and reference shift rules for updating references in reference items during update of an old version to a new version. It should be noted that the invention is not bound by the specific numeral shift rules and reference shift rules described above. More generally, the term “shift rule” refers to updating of reference items to reflect the shift of reference items in the new version.

Hereinafter, a ‘conversion element’ is the term used to refer to a collection of shift rules associated with an update package. That is, a conversion element can include at least one numeral shift rule, and/or at least one reference shift rule, and/or any other shift rule that can be applied while updating an old version to a new version. Thus, according to the description above, a person versed in the art can appreciate that an update package that contains at least one conversion element is a compact update package.

When applying a conversion element to an old version, it should be appreciated that sometimes reference items can be updated erroneously. For example, consider the example illustrated in **Fig. 9**, wherein the inserted item **910** is inserted into block **907** backwards to item **915'**. This change in the example will not affect the difference table **1000** and the reference shift rules will be similar to those described in **Fig. 10** (see **1001**). However, it can be appreciated that items **915'** and **918'** are shifted forward by $(size(909) + size(910))$, and not by $size(909)$ as predicted by the difference table **1000**. Therefore, unlike what is

- 29 -

indicated by the reference shift rules of **1001**, the reference items **912'** and **917'** should be modified to reflect a shift of ($size(909) + size(910)$) instead of $size(909)$.

According to an embodiment of the invention referred to, hereinafter, as “one modified” embodiment of the invention and it is possible to apply the conversion element including the reference shift rules of **1001** of **Fig. 10**, generating a modified version thereby, and afterwards provide remedy to the erroneous reference items affected by this conversion element by applying a diff utility between the modified version and the new version. This diff procedure, sometimes referred shortly as “diff”, comparing between a modified and a new version is referred to hereinafter as “modified diff”, wherein the first diff (comparing between an old and a new version), utilized in order to generate the conversion element is referred to, hereinafter, as “complete diff”. The output of the complete diff is referred to as a “complete delta”, while the output of the modified diff is referred to as a “modified delta”.

Generally speaking, it is possible to appreciate that while the complete diff detects all the variations that exist between the old and the new versions, including for example, replacement pairs (i.e., shifted explicit reference items as explained above) and other variations such as inserted items and deleted items, the modified diff detects substantially less replacements together with possibly erroneous replacement pairs and together with the other variations. Thus, modified delta is smaller in size compared to the complete delta.

Yet, the modified delta together with the conversion element can constitute together an update package that can update the old version and create a new version thereof. Such an output package, constituted of at least one conversion element and a modified delta, is referred to, hereinafter as a “composite update package”, unlike a “simple update package” that includes a complete delta and no conversion element. Bearing in mind that the conversion element can be smaller in size compared to its equivalent replacement commands, the resulting composite update package is usually smaller in size

- 30 -

compared to the simple update package known *per se*. Therefore, a composite update package is considered hereinafter as a compact update package. According to an embodiment of the invention a compact update package includes at least a conversion element and a modified delta associated therewith.

It is appreciated that by applying the conversion element, and afterwards the modified diff associated with it (“forward conversion order” or in other words, “forward update indicator”) in a compact update package, a new version will be generated wherein items that were erroneously modified by the conversion element will be replaced by the modified delta and amended in a way that their proper content in the new version is received (the procedures for applying update packages are discussed in detail below). However it should be noted that sometimes the modified diff should be applied before the conversion element referred to hereinafter as “backward conversion order”. Backward conversion order shall be explained in detail below.

Yet, it can be illustrated that instead of joining the modified delta to the conversion element to form a compact update package, it is possible to extract additional conversion elements from the modified delta, contributing to the previous conversion element or generating an additional conversion element to be associated together with the previous one and with a delta to form an even smaller compact update package. Thus, another embodiment of the invention, referred to as an “iterations embodiment” is described below, with reference to Fig. 14.

Fig. 14 is an exemplary schematic illustration of iterations for updating versions of content, according to an iterations embodiment of the invention. The version 1401 is an old version, while the version 1402 is the new version. The figure illustrates generation of a compact update package for updating old version 1401 to new version 1402 according to the iterations embodiment of the invention. The old version 1401 includes a block 1403. Further to block 1403 there is another block 1404 including at least some explicit reference items 1405,

- 31 -

1406, 1407, 1408, 1409, 1410, 1411, 1412, 1413 and 1414. The block 1404 includes also a non reference item 1415.

In the new version 1402, the blocks 1403' and 1404' correspond to blocks 1403 and 1404, while the items 1405', 1406', 1407', 1408', 1409', 1410', 1411', 1412', 1413', 1414' and 1415' correspond to items 1406, 1407, 1408, 1409, 1410, 1411, 1412, 1413, 1414 and 1415 respectively. At least one item 1416 was inserted into block 1403', thus enlarging its size by *size(1416)*, and at least one item 1417, of *size(1417)* was inserted into block 1404' backwards to item 1405'.

It should be noted that the content of reference items 1405, 1411 and 1414 are substantially identical, and therefore the content of the corresponding reference items 1405', 1411' and 1414' are substantially identical as well. Similarly, the content of 1406, 1412 and 1414 are substantially identical, and therefore the content of the corresponding reference items 1406', 1412' and 1414' are substantially identical as well.

The items 1405', 1406', ..., 1410' are explicit reference items, whose content was modified (i.e., their referenced items were shifted) in the new version compared to the old version. The same applies also to the explicit reference items 1411', 1412', 1413' and 1414'. Yet, a diff utility known per se can not recognize that item 1417 is a new item inserted into the new version 1402 while items 1405', 1406', ..., 1410', ... are shifted items, and therefore, the diff utility erroneously detects that item 1417 replaces item 1405. Further on the diff utility identifies that item 1415' is identical to item 1415 (and therefore a copy thereof), and synchronizes to detect (correctly, this time) that item 1411' replaces item 1411 and so on.

Thus, following a complete diff, a complete delta is generated, indicating (partially erroneously) the following:

1417 replaces 1405;

1405' replaces 1406;

1406' replaces 1407;

1407' replaces 1408;

- 32 -

1408' replaces **1409**;
1409' replaces **1410**;
1415' is a copy of **1415**;
1411' replaces **1411**;
1412' replaces **1412**;
1413' replaces **1413**; and
1414' replaces **1414**.

Based on this complete delta a conversion element is generated, for example in accordance with the methods illustrated in **Figs. 7 and 13** above.

Recalling that items **1405**, **1411** and **1414** are substantially identical (and so are their corresponding items), as well as items **1406**, **1412** and **1414** that are substantially identical (and so are their corresponding items too), and upon detecting that **1411'** replaces **1411** and that **1413'** replaces **1413**, the conversion element can estimate that **1405** should be replaced by **1405'**. Similarly, by detecting that **1412'** replaces **1412** and **1414'** replaces **1414**, the conversion element can estimate that **1406** should be replaced by **1406'**.

This conversion element is applied to the old version **1401**, generating modified version **1418**. It should be noted that the conversion element modified (or converts) several items in the old version, but it does handle any other variation such as deleting and/or inserting items. Therefore, the modified version **1418** is not shifted in relation to the old version **1401**.

According to the one modified embodiment of the invention, a modified diff can be utilized, comparing between the modified version **1418** and the new version **1402**. The resultant modified delta would recognize the insertion of additional elements, deletion of others and replacement of the rest (amongst are the items **1407**, **1408**, **1409** and **1410** that were not handled by the conversion element. This modified delta, together with the conversion element, will serve as the basis for generating the compact update package.

Alternatively, according to the iterations embodiment of the invention, instead of generating a compact update package, the modified delta should serve

- 33 -

as a basis for generation of additional new conversion elements, for example in accordance with the methods illustrated in **Figs. 7 and 13** above. This new conversion element, together with the one generated in the previous iteration will constitute together a compound conversion element. The new conversion element can be applied to the modified version **1418** to generate another modified version (not shown) to be compared by a modified diff against the new version **1402**, and so on. One exemplary terminating condition for stopping the iterations is when the size of the modified delta produced by an iteration together with the size of the new conversion element is larger or equal to the size of the previous modified delta together with the size of the previous compound conversion element. When the iterations are stopped the compact update package is generated based on the compound conversion element and the modified delta.

Whereas the iterations embodiment will be describe in general terms below with respect to the flow chart of **Fig. 15**, it should be noted, incidentally, that the example of **Fig. 14** is non-limiting. The old and new versions can have any applicable number of blocks, new blocks and items can be inserted at any location or deleted while updating the old version to a new version, any number of iterations can be performed and any applicable terminating condition (or “stop criterion”) can be used to stop the iterations. That is, the process proceeds to the next iteration if the stop criterion is not met.

Fig. 15 is a flowchart describing in detail the iterations embodiment of the invention. It is noted that the update package generated in accordance with this flowchart is in forward conversion order.

Upon start, the method described receives at least an old and a new version of the content to be updated, and meta-data, if available. The two versions and the meta-data serve as the basis for the generation (**1501**) of a conversion element and for determining (**1502**) the initial delta size, wherein it can be appreciated that initially the compound conversion element is identical (**1503**) to the conversion element generated in **1501**. The conversion element is applied (**1504**) to the old version, generating a modified version thereby. Next a

- 34 -

modified delta is generated (1505) while utilizing a modified diff on the modified and new version, and the modified delta serves as a basis for generation (1506) of a new conversion element. The size of this new conversion element is determined (1507).

The new conversion element is merged (1508) into the compound conversion element. The size of the new conversion element is determined (1509) and the size of the modified delta (1510).

If the size of the compound conversion element together with the delta size is smaller than the size of the new conversion element together with the size of the modified delta (1511) the new conversion element becomes the conversion element (1512), the delta size becomes the new delta size (1513) and the new conversion element is applied to the modified version (1514) creating a new modified version thereby. Returning to 1505 a new modified delta is created.

However, if on 1511 it is determined that the size of the conversion element together with the size of the modified delta is equal or larger than the size of the compound conversion element together with the delta size, an update package is generated (1515) on the basis of the compound conversion element and the modified delta. Alternatively, on 1511 the stop criterion is met if the compact update package is larger than the compact update package generated in the previous iteration.

It should be appreciated that the iterations embodiment can operate also in the backward conversion order, that is the complete diff is applied between the old version and the new version for generating an initial conversion element, wherein the modified version is created by applying the conversion element on the new version. Next a modified delta is generated between the old version and the modified version for generating a new conversion element and so on.

An update package is marked to indicate the conversion order in accordance with the update package was generated.

- 35 -

It should be noted that the invention is not bound to the specific sequence of operation and manner of generating the update package as described in **Fig. 15**.

Having described the generation of an update package in accordance with various non-limiting embodiments of the invention, there follows a description of using the update package for updating an old version giving rise to a new version. By way of non-limiting example the update package is transmitted through a wireless communication medium and received by cellular telephone device. The cellular telephone device includes a processor configured to process the so received updated package and to update an old version of program and/or data stored therein giving rise to a new version that is stored and operable in the cellular telephone device.

Bearing this in mind, attention is drawn to **Fig. 16** illustrating a flowchart describing an update of an old version of content giving rise to a new version of content, in accordance with one embodiment of the invention. An update package in accordance with this embodiment includes a conversion element and a modified delta. It should be noted that an update package includes either a forward update indicator or a backward update indicator.

After obtaining a compact update package (1601) the conversion element included therein is extracted (1602).

If the update package includes a forward update indicator, as detected on 1603, the conversion element is applied (1604) to the old version, generating a modified version. Then the modified delta is extracted (1605) from the update package and applied (1606) to the modified version. On the other hand, if it is found on 1603 and 1607 that the update package includes a backward update indicator, the modified delta is first extracted (1605) and applied (1606) to the old version generating a modified version on which the conversion element is then applied (1608). In both cases the result is the new version.

Fig. 17 illustrates a system 1701 for generating a compact update package between an old version of content and a new version of content, in accordance

- 36 -

with one embodiment of the invention. The system includes a conversion element generator **1702** for generating a conversion element associated with the old version and new version. A modified version generator **1703** for generating a modified version including applying the conversion element to the old versions. An update package generator **1704** for generating the compact update package. The compact update package includes the conversion element and a modified delta based on the modified version and the new version.

Fig. 18 illustrates a system **1801** for updating an old version of content giving rise to a new version of content, in accordance with one embodiment of the invention. The system includes an input module **1802** and a processor **1803**. The input module is configured to obtaining a compact update package that includes a conversion element associated with said old version and new version, a modified delta, and indication of forward update or backward update. In the case of forward update indication the processor is configured to generate the modified version including applying the conversion element to the old version. The processor is also configured to generate the new version including applying the modified delta to the modified version. In the case of backward update indication the processor is configured to generate a modified version including applying the modified delta to the old version. The processor is also configured to generate the new version including applying the conversion element to the modified version.

It will also be understood that the system according to the invention may be a suitably programmed computer. Likewise, the invention contemplates a computer program being readable by a computer for executing the method of the invention. The invention further contemplates a machine-readable memory tangibly embodying a program of instructions executable by the machine for executing the method of the invention.

The present invention has been described with a certain degree of particularity, but those versed in the art will readily appreciate that various

- 37 -

alterations and modifications may be carried out, without departing from the scope of the following Claims:

CLAIMS:

1. A method of updating an old version of content on a storage device, comprising:
 - (i) obtaining a compact update package, said compact update package includes: a conversion element, a modified delta, and an indication of one of forward update and a backward update, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is a delta between one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta in the compact update package was generated by applying the conversion element to (1) the new version of content in the case of the modified delta being a delta between the old version of content and the modified version, and (2) the old version of content in the case of the modified delta being a delta between the modified version and the new version of content;
 - (ii) determining whether the indication in the compact update package is one of a forward update indication and a backward update indication;
 - (iii) in the case of the forward update indication:
 - a) generating the modified version by applying the conversion element to the old version of content on the storage device; and
 - b) generating the new version of content on the storage device by applying the modified delta to the modified version generated

in (iii) (a), wherein the modified delta is the delta between the modified version and the new version of content;

(iv) in the case of the backward update indication:

a) generating the modified version by applying the modified delta to the old version of content on the storage device, wherein the modified delta is the delta between the old version of content and the modified version; and

b) generating the new version of content on the storage device by applying said conversion element to the modified version generated in (iv) (a).

2. The method according to Claim 1, wherein said conversion element is a compound conversion element.
3. The method according to Claim 1, wherein said (i) comprises: receiving said compact update package.
4. The method according to Claim 1, wherein said shift rule is numerical shift rule.
5. The method according to Claim 4, wherein said numerical shift rule is an integer shift rule.
6. The method according to Claim 1, wherein said shift rule is a reference shift rule.
7. The method according to Claim 1, wherein said content comprises a computer program.
8. The method according to Claim 7, wherein said computer program is an executable program.
9. The method according to Claim 1, wherein said content comprises data.

10. The method according to Claim 1, wherein said storage device is associated with an embedded device.
11. The method according to Claim 10, wherein said embedded device is a member of a group that includes: cellular telephone and consumer electronic device.
12. The method according to Claim 1, wherein said storage device is associated with a computer.
13. A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform a method for updating an old version of content, comprising:
 - (i) obtaining a compact update package, said compact update package includes: a conversion element, a modified delta, and an indication of one of forward update and a backward update, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is a delta between one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta in the compact update package was generated by applying the conversion element to (1) the new version of content in the case of the modified delta being a delta between the old version of content and the modified version, and (2) the old version of content in the case of the modified delta being a delta between the modified version and the new version of content;

- (ii) determining whether the indication in the compact update package is one of a forward update indication and a backward update indication;
 - (iii) in the case of the forward update indication:
 - a) generating the modified version by applying the conversion element to the old version of content on the storage device; and
 - b) generating the new version of content on the storage device by applying the modified delta to the modified version generated in (iii)(a), wherein the modified delta is the delta between the modified version and the new version of content;
 - (iv) in the case of the backward update indication:
 - a) generating the modified version by applying the modified delta to the old version of content on the storage device, wherein the modified delta is the delta between the old version of content and the modified version; and
 - b) generating the new version of content on the storage device by applying said conversion element to the modified version generated in (iv) (a).
14. A system for updating an old version of content on a storage device, comprising: an input module configured to obtain a compact update package, said compact update package includes: a conversion element, a modified delta, and an indication of one of a forward update and a backward update, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is a delta between one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content,

and wherein the modified version used to produce the modified delta of the compact update package was generated by applying the conversion element to (1) the new version of content in the case of the modified delta being a delta between the old version of content and the modified version, and (2) the old version of content in the case of the modified delta being a delta between the modified version and the new version of content; a processor configured to perform:

- (i) determining whether the indication in the compact update package is one of a forward update indication and a backward update indication;
- (ii) in the case of the forward update indication:
 - a) generating the modified version by applying the conversion element to said old version of content on the storage device; and
 - b) generating the new version of content on the storage device by applying the modified delta to the modified version generated in (ii)(a), wherein the modified delta is the delta between the modified version and the new version of content;
- (iii) in the case of the backward update indication:
 - a) generating the modified version by applying the modified delta to the old version of content on the storage device, wherein the modified delta is the delta between the old version of content and the modified version; and
 - b) generating the new version of content on the storage device by applying said conversion element to the modified version generated in (iii)(a).

15. The system according to Claim 14, wherein said storage device is associated with an embedded device.
16. The system according to claim 15, wherein said embedded device is a member of a group that includes: cellular telephone and consumer electronic device.
17. The system according to Claim 14, wherein said storage device is associated with a computer.
18. A method of updating an old version of content on a storage device, comprising: obtaining a compact update package comprising a modified delta and a conversion element, wherein the conversion element comprises a shift rule reflecting differences between the old version of content and a new version of content, wherein the modified delta is associated with one of: (1) the old version of content and a modified version and (2) the modified version and the new version of content, and wherein the modified version used to produce the modified delta in the compact update package was generated by applying the conversion element to (1) the new version of content when the modified delta is associated with the old version of content and the modified version, and (2) the old version of content when the modified delta is associated with the modified version and the new version of content; (a) when the modified delta in the compact update package is associated with the modified version and the new version of content: (i) applying the conversion element to the old version of content on the storage device thereby generating a modified version, and (ii) applying the modified delta on the modified version generated in (a)(i), thereby generating the new version of content on the storage device; (b) when the modified delta in the obtained

compact update package is associated with the old version of content and the modified version: (i) applying the modified delta on the old version of content on the storage device thereby generating the modified version, and (ii) applying the conversion element on the modified version generated in (b)(i), thereby generating the new version of content on the storage device.

19. The method according to Claim 18, wherein said conversion element is a compound conversion element.
20. The method according to Claim 18, wherein said obtaining comprises: receiving said compact update package.
21. The method according to Claim 18, wherein said shift rule is a numerical shift rule.
22. The method according to Claim 21, wherein said numerical shift rule is an integer shift rule.
23. The method according to Claim 18, wherein said shift rule is a reference shift rule.
24. The method according to Claim 18, wherein said content comprises a computer program.
25. The method according to Claim 24, wherein said computer program is an executable program.
26. The method according to Claim 18, wherein said content comprises data.
27. The method according to Claim 18, wherein said storage device is associated with an embedded device.
28. The method according to Claim 27, wherein said embedded device is a member in a group that comprises: cellular telephone and consumer electronic device.

29. The method according to Claim 18, wherein said storage device is associated with a computer.
30. A method for generating a compact update package between an old version of content and a new version of content, comprising:
- (i) generating a conversion element associated with said old version of content and new version of content and including at least one shift rule that can be applied while updating said old version of content to said new version of content;
 - (ii) generating a modified version including applying the conversion element to one of said old and new versions of content; and
 - (iii) generating, in a specifically programmed computer, said compact update package, wherein the compact update package includes said conversion element and a modified delta based on a comparison of one of:
 - said modified version and the new version, when said conversion element is applied to the old version;
 - and
 - the old version and said modified version, when said conversion element is applied to the new version.
31. The method according to Claim 30, wherein said conversion element is applied to the old version of content and the comparison is of the old version and the modified version.
32. The method according to Claim 30, wherein said conversion element is applied to the new version of content and the comparison is of the modified version and the new version.

33. The method according to Claim 30, wherein said shift rules comprise a numerical shift rule.
34. The method according to Claim 33, wherein said numerical shift rule is an integer shift rule.
35. The method according to Claim 30, wherein said shift rules comprise a reference shift rule.
36. The method according to Claim 35, wherein said reference shift rule is associated with a difference table.
37. The method according to Claim 36, wherein said difference table is based on at least meta-data associated with said old version of content and said new version of content.
38. The method according to Claim 37, wherein said meta-data is content description data.
39. The method according to Claim 38, wherein said content description data is a member in a group that comprises map files, symbol tables, and debug tables.
40. The method according to Claim 30, wherein said content includes a computer program.
41. The method according to Claim 30, wherein said content includes data.
42. The method according to Claim 30, including the following steps, which are repeatedly applied as iterations:
 - a. generating the conversion element associated with the modified version as one of the old version for a first iteration and as obtained in a previous iteration and said new version of content;

- b. generating the modified version including applying the conversion element obtained in (a) to the modified version obtained in the previous iteration;
 - c. generating the compact update package, the compact update package including a compound conversion element that includes conversion elements generated in all preceding iterations, and the modified delta based on at least the modified version stipulated in (b) and said new version of content; and
 - d. proceeding to a next iteration if a stop criterion is not met; otherwise, selecting the compact update package of smallest size from among a plurality of compact update packages generated during the preceding iterations.
43. The method according to Claim 42, wherein said stop criterion is met if the compact update package is larger than another compact update package generated in the previous iteration.
44. A method of updating an old version of content to a new version of content, comprising:

using a compact update package on said old version of content to update it to be said new version of content, wherein said compact update package is generated according to the method according to Claim 30.
45. A computer program product comprising a computer readable memory storing computer executable instructions thereon that when executed by a computer perform the method according to Claim 30.
46. A system for generating a compact update package between an old version of content and a new version of content, comprising:

a conversion element generator for generating a conversion element associated with said old version and said new version and including at least one shift rule that can be applied while updating said old version to said new version;

a modified version generator for generating a modified version including applying the conversion element to one of said old version and said old version; and

an update package generator of a specifically programmed computer for generating said compact update package, wherein the compact update package includes said conversion element and a modified delta based on a comparison of one of:

said modified version and the new version, when said conversion element is applied to the old version;

and

the old version and said modified version, when said conversion element is applied to the new version.

47. A compact update package stored on a tangible medium comprising a program of instructions executable by a machine obtainable according to the method of Claim 30.
48. A method of using an update package, said use comprising one or more of:
storing said update package,
transmitting said update package, and
performing an update of an old version of content to a new version of content, wherein said update package is generated using the method according to Claim 30.

49. The method according to Claim 30, including the following steps, which are repeated applied as iterations:
- a. generating the conversion element associated with the modified version as one of the old version for a first iteration and as obtained in a previous iteration;
 - b. generating the modified version including applying the conversion element obtained in (a) to the modified version obtained in the previous iteration;
 - c. generating the compact update package, the compact update package including a compound conversion element that includes conversion elements generated in all preceding iterations, and the modified delta based on at least the modified version stipulated in (b) and said old version of content; and
 - d. proceeding to a next iteration if a stop criterion is not met; otherwise, selecting the compact update package of smallest size from among a plurality of compact update packages generated during the preceding iterations.
50. The method according to Claim 49, wherein said stop criterion is met if the compact update package is larger than another compact update package generated in the previous iteration.

1/13




FIG. 1

2/13




FIG. 2

3/13




FIG. 3




FIG. 4

4/13




FIG. 5

5/13




FIG. 6

6/13




FIG. 7

7/13




FIG. 8

8/13




FIG. 9

9/13




FIG. 9A




FIG. 10

10/13




FIG. 11






FIG. 12

11/13



12/13




FIG. 15

13/13




FIG. 16




FIG. 17




FIG. 18

