



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 1 319 059 B1**

(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention
of the grant of the patent:
10.11.2004 Bulletin 2004/46

(21) Application number: **01970847.8**

(22) Date of filing: **13.09.2001**

(51) Int Cl.7: **C11D 3/12, C11D 3/00**

(86) International application number:
PCT/US2001/028476

(87) International publication number:
WO 2002/024850 (28.03.2002 Gazette 2002/12)

(54) **DETERGENT COMPOSITIONS**
WASCHMITTELZUSAMMENSETZUNGEN
COMPOSITIONS DETERGENTES

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**

(30) Priority: **19.09.2000 GB 0022906**

(43) Date of publication of application:
18.06.2003 Bulletin 2003/25

(73) Proprietor: **The Procter & Gamble Company
Cincinnati, Ohio 45202 (US)**

(72) Inventors:
• **HARTSHORN, Richard, Timothy
Lawrenceburg, IN 47025 (US)**
• **MAIN, Alison, Lesley
Whitley Bay, Tyne and Wear NE25 8RG (GB)**

• **LETZELTER, Nathalie, Sophie
Newcastle upon Tyne NE13 7AL (GB)**
• **INGRAM, Barry, Thomas
Whitley Bay, Tyne and Wear NE26 1JE (GB)**

(74) Representative: **Brooks, Maxim Courtney et al
Procter & Gamble Technical Centres Limited,
Whitley Road,
Longbenton
Newcastle upon Tyne NE12 9TS (GB)**

(56) References cited:
EP-A- 0 026 529 EP-A- 0 297 673
GB-A- 2 179 971 US-A- 3 862 058
US-A- 3 993 573 US-A- 4 062 647
US-A- 4 196 104 US-A- 4 444 674
US-A- 5 234 620

EP 1 319 059 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

DescriptionTechnical Field

5 **[0001]** The present invention relates to solid fabric or cleaning compositions, especially laundry detergent compositions that provide fabric softening benefits during the washing process.

Background of the Invention

10 **[0002]** There is a consumer demand for solid laundry detergents that provide fabric softening benefits during the washing process. To meet this demand, the laundry industry typically adds a softening agent to solid detergent products. These softening agents do not always efficiently deposit onto fabric, they do not disperse well or do not deposit evenly on to the fabric surface, and are removed from the wash liquor during the washing cycle, hence the softening benefit they provide during the washing cycle still needs to be improved. Currently, the laundry industry typically adds flocculating aids to solid detergent compositions comprising clay, to improve clay deposition onto fabric. However, there is still a need to further improve the efficiency of clay deposition onto fabric in such a manner that an improved fabric softening benefit is achieved.

15 **[0003]** The Inventors have surprisingly found that by using a combination of specific clays, these clays provide an improved fabric softening benefit over several washing cycles, compared to when the same amount of a single clay type is used.

20 **[0004]** Moreover, it is believed that a combination of specific types of clay, acts in such a manner as to disperse better and more readily deposit onto fabric in such a manner so that the fabric softening benefit over several washing cycles is improved, compared to when only one clay type is used.

25 **[0005]** Furthermore, the Inventors have found that when the two clay types are present in a solid detergent composition in the form of an agglomerate, then the fabric softening benefit provided by the solid detergent composition during the washing cycle is further improved. Granular fabric softening compositions are already known in the art, see for example US-4 062 647-A, which discloses compositions comprising hectorite and smectite type clays. The Inventors have also found that when the two clay types are present in the same agglomerate, then the fabric softening benefit provided is further improved, compared to two separate clay agglomerates being used.

30 **[0006]** The Inventors have also found that adding a hydrophobically modified cellulosic based polymer to a solid detergent composition comprising specific types of clay, further improves the fabric softening benefit provided and also provides a fabric anti-wrinkling benefit, over several washing cycles.

Summary of the Invention


35 **[0007]** In a first embodiment of the present invention, a solid detergent composition is provided which comprises hectorite clay and dioctahedral smectite clay, wherein the weight ratio of said hectorite clay to said dioctahedral smectite clay is less than 1:1, wherein said hectorite clay and said dioctahedral smectite clay are present in said composition in the form of agglomerate particles, and wherein further said hectorite clay and said dioctahedral smectite clay are present in the same agglomerate particle.

40 **[0008]** In a second embodiment of the present invention, the use of a solid detergent composition comprising hectorite clay and dioctahedral smectite clay, wherein the weight ratio of said hectorite clay to said dioctahedral smectite clay is less than 1:1 wherein said hectorite clay and said dioctahedral smectite clay are present in said composition in the form of agglomerate particles, and wherein further said hectorite clay and said dioctahedral smectite clay are present in the same agglomerate particle, to provide fabric softening benefits to fabric, is provided.

45 **[0009]** In a third embodiment of the present invention, the use of a solid detergent composition comprising hectorite clay, dioctahedral smectite clay and a hydrophobically modified cellulosic based polymer, wherein the weight ratio of said hectorite clay to said dioctahedral smectite clay is less than 1:1 wherein said hectorite clay and said dioctahedral smectite clay are present in said composition in the form of agglomerate particles, and wherein further said hectorite clay and said dioctahedral smectite clay are present in the same agglomerate particle. to provide fabric softening benefits and fabric anti-wrinkling benefits to fabric, is provided.

Detailed description of the invention55 Hectorite clay

[0010] The composition herein comprises hectorite clay. Typical hectorite clay for use herein has the general formula



wherein $y=0$ to 0.4 , if $y>0$ then Me^{III} is Al, Fe or B, preferably $y=0$; M^{n+} is a monovalent ($n=1$) or a divalent ($n=2$) metal ion, preferably selected from Na, K, Mg, Ca and Sr. x is a number from 0.1 to 0.5 , preferably from 0.2 to 0.4 , more preferably from 0.25 to 0.35 . z is a number from 0 to 2 . The value of $(x+y)$ is the layer charge of said first clay, preferably the value of $(x+y)$ is in the range of from 0.1 to 0.5 , preferably from 0.2 to 0.4 , more preferably from 0.25 to 0.35 .

[0011] The Inventors have found that a specific volume weight mean particle size of hectorite clay, typically from 5 micrometers to 20 micrometers, further improves the fabric softening benefit provided. Therefore, the hectorite clay for use herein preferably has a volume weight mean particle size of from 5 micrometers to 20 micrometers, preferably from 7 micrometers to 19 micrometers, more preferably from 10 micrometers to 18 micrometers, more preferably from 12 micrometers to 17 micrometers, more preferably from 14 micrometers to 16 micrometers. The method for determining said volume weight mean particle size of said first clay is described in more detail hereinafter

[0012] Also, the inventors have found that when the hectorite clay has a lath like primary platelet shape, typically defined by an aspect ratio of greater than $3:1$, then the fabric softening benefit provided is further improved. Therefore the hectorite clay, especially the primary platelets of said hectorite clay, has an aspect ratio of greater than $3:1$, more preferably greater than $5:1$, more preferably greater than $7:1$, or preferably from $7:1$ to $15:1$. The aspect ratio of the primary platelets is typically defined as the ratio of the average length of the primary platelets to the average width of the primary platelets. It is believed that the small particles of the hectorite clay which have primary platelets that are more elongated in structure, more easily fit into the crevices of the fabric and give an improved softening benefit during the washing process.


[0013] Preferred hectorite clays for use herein are those having a cationic exchange capacity of at least 90 meq/ 100 g. The cationic exchange capacity of clays can be measured using the method described in Grimshaw, The Chemistry and Physics of Clays, Interscience Publishers, Inc., pp. $264-265$ (1971).

[0014] An especially preferred hectorite clay is that supplied by Rheox under the trade name Bentone HC. Other preferred hectorite clays for use herein are those hectorite clays supplied by CSM Materials under the trade name Hectorite U and Hectorite R, respectively.


Diocahedral smectite clay

[0015] The composition herein comprises a diocahedral smectite clay. Any diocahedral smectite clay can be used herein, preferred diocahedral smectite clays for use herein are montmorillonite clays.

[0016] Diocahedral smectite clays for use herein typically have the general formula



or



wherein x is a number from 0.1 to 0.5 , preferably from 0.2 to 0.4 .

[0017] Preferred diocahedral smectite clays are low charge montmorillonite clays (also known as a sodium montmorillonite clay or Wyoming type montmorillonite clay) which have a general formula corresponding to formula (II) above, or high charge montmorillonite clays (also known as a calcium montmorillonite clay or Cheto type montmorillonite clay) which have a general formula corresponding to formula (III).

[0018] The Inventors have found that when the diocahedral smectite clay has a specific volume weight mean particle size, typically of more than 20 micrometers, then the fabric softening benefit provided is further improved. Therefore, preferably the diocahedral smectite clay has a volume weight mean particle size of more than 20 micrometers, preferably more than 23 micrometers, preferably more than 25 micrometers, or preferably from 21 micrometers to 60 micrometers, more preferably from 22 micrometers to 50 micrometers, more preferably from 23 micrometers to 40 micrometers, more preferably from 24 micrometers to 30 micrometers, more preferably from 25 micrometers to 28 micrometers. The method for determining said volume weight mean particle size of said second clay is described in more detail hereinafter.

Method For Determining The Volume Weight Mean Particle Size Of The First Clay and Second Clay


[0019] The volume weight mean particle size of the hectorite clay and dioctahedral smectite clay, respectively, is determined using the following method:

[0020] 12g clay is placed in a glass beaker containing 250ml distilled water and vigorously stirred for 5 minutes to form a clay solution. The clay is not sonicated, or microfluidised in a high pressure microfluidizer processor, but is added to said beaker of water in an unprocessed form (i.e. it's raw form). 1ml clay solution is added to the reservoir volume of an Accusizer 780 single-particle optical sizer (SPOS) using a micropipette. The clay solution that is added to the reservoir volume of said Accusizer 780 SPOS is diluted in more distilled water to form a diluted clay solution, this dilution occurs in the reservoir volume of said Accusizer 780 SPOS and is an automated process that is controlled by said Accusizer 780 SPOS which determines the optimum concentration of said diluted clay solution, for determining the volume weight mean particle size of the clay particles in the diluted clay solution. The diluted clay solution is left in the reservoir volume of said Accusizer 780 SPOS for 3 minutes. The clay solution is vigorously stirred for the whole period of time that it is in the reservoir volume of said Accusizer 780 SPOS. The diluted clay solution is then sucked through the sensors of said Accusizer 780 SPOS, this is an automated process that is controlled by said Accusizer 780 SPOS which determines the optimum flow rate of the diluted clay solution through the sensors, for determining the volume weight mean particle size of the clay particles in the diluted clay solution. All of the steps of this method are carried out at a temperature of 20°C. This method is carried out in triplicate and the mean of these results determined.

Hydrophobically Modified Cellulosic Based Polymers


[0021] The composition herein preferably comprises (by weight of said composition) from 0.01% to 50%, preferably from 0.05% to 20%, more preferably from 0.05% to 15%, more preferably from 0.05% to 10%, more preferably from 0.05% to 5%, more preferably from 0.05% to 3%, more preferably from 0.1% to 2% a hydrophobically modified cellulosic based polymer. The hydrophobically modified cellulosic based polymers herein include polymers, oligomers, copolymers and also cross-linked polymers, oligomers and copolymers. The term "hydrophobically modified cellulosic based polymer" is herein referred to as "cellulosic based polymer". As will be apparent to those skilled in the art, an oligomer is a molecule consisting of only a few monomer units while polymers comprise considerably more monomer units. For the present invention, oligomers are defined as molecules having a weight average molecular weight of below 1,000 and polymers are molecules having a weight average molecular weight of greater than 1,000. One suitable type of cellulosic based polymer herein has a weight average molecular weight of from about 5,000 to about 2,000,000, preferably from about 50,000 to about 1,000,000.

[0022] The cellulosic based polymer for use herein is preferably of the following formula:



wherein each R is selected from the group consisting of R₂, R_c, and

5




wherein:

10

- each R₂ is independently selected from the group consisting of H and C₁-C₄ alkyl;
- each R_C is

15




20

wherein each Z is independently selected from the group consisting of M, R₂, R_C, and R_H;

- each R_H is independently selected from the group consisting of C₅-C₂₀ alkyl, C₅-C₇ cycloalkyl, C₇-C₂₀ alkylaryl, C₇-C₂₀ arylalkyl, substituted alkyl, hydroxyalkyl, C₁-C₂₀ alkoxy-2-hydroxyalkyl, C₇-C₂₀ alkylaryloxy-2-hydroxyalkyl, (R₄)₂N-alkyl, (R₄)₂N-2-hydroxyalkyl, (R₄)₃N-alkyl, (R₄)₃N-2-hydroxyalkyl, C₆-C₁₂ aryloxy-2-hydroxyalkyl,


25



30

and

35



40

- each R₄ is independently selected from the group consisting of H, C₁-C₂₀ alkyl, C₅-C₇ cycloalkyl, C₇-C₂₀ alkylaryl, C₇-C₂₀ arylalkyl, aminoalkyl, alkylaminoalkyl, dialkylaminoalkyl, piperidinoalkyl, morpholinoalkyl, cycloalkylaminoalkyl and hydroxyalkyl;
- each R₅ is independently selected from the group consisting of H, C₁-C₂₀ alkyl, C₅-C₇ cycloalkyl, C₇-C₂₀ alkylaryl, C₇-C₂₀ arylalkyl, substituted alkyl, hydroxyalkyl, (R₄)₂N-alkyl, and (R₄)₃N-alkyl;

wherein:

45

M is a suitable cation selected from the group consisting of Na, K, 1/2Ca, and 1/2Mg;

each x is from 0 to about 5;

each y is from about 1 to about 5; and

50

provided that:

55

- the Degree of Substitution for group R_H is between about 0.001 and 0.1, more preferably between about 0.005 and 0.05, and most preferably between about 0.01 and 0.05;
- the Degree of Substitution for group R_C wherein Z is H or M is between about 0.2 and 2.0, more preferably between about 0.3 and 1.0, and most preferably between about 0.4 and 0.7;
- if any R_H bears a positive charge, it is balanced by a suitable anion; and
- two R₄'s on the same nitrogen can together form a ring structure selected from the group consisting of piperidine and morpholine.

[0023] The "Degree of Substitution" for group R_H, which is sometimes abbreviated herein "DS_{RH}", means the number of moles of group R_H components that are substituted per anhydrous glucose unit, wherein an anhydrous glucose unit is a six membered ring as shown in the repeating unit of the general structure above.

[0024] The "Degree of Substitution" for group R_C, which is sometimes abbreviated herein "DS_{RC}", means the number of moles of group R_C components, wherein Z is H or M, that are substituted per anhydrous glucose unit, wherein an anhydrous glucose unit is a six membered ring as shown in the repeating unit of the general structure above. The requirement that Z be H or M is necessary to insure that there are a sufficient number of carboxy methyl groups such that the resulting polymer is soluble. It is understood that in addition to the required number of R_C components wherein Z is H or M, there can be, and most preferably are, additional R_C components wherein Z is a group other than H or M.


Flocculation Agent

[0025] The composition herein may preferably comprise a flocculation agent, preferably present at a level of from 0.005% to 10%, more preferably from 0.01% to 5%, more preferably from 0.05% or even 0.1% to 1% by weight of said composition. The flocculation agent may be present in said composition as part of the detergent base granule, or if the clay system is present in said composition as a separate pre-formed particle, the flocculation agent may be present in the composition as part of said separate pre-formed particle. Preferred flocculation agents herein are organic polymeric materials having a weight average molecular weight of from 100000 to 10000000, preferably from 150000 to 5000000, more preferably from 200000 to 2000000. Suitable organic polymeric materials comprise homopolymers or copolymers containing monomeric units selected from alkylene oxide, particularly ethylene oxide, acrylamide, acrylic acid, vinyl alcohol, vinyl pyrrolidone and ethylene imine. Homopolymers of ethylene oxide, acrylamide and acrylic acid are preferred. European patents no.s EP-A-299,575 and EP-A-313146 in the name of The Procter and Gamble Company describe preferred organic polymeric flocculation agents for use herein. Highly preferred are polyethylene oxides of a weight average molecular weight of from 150000 to 3000000. Inorganic flocculation agents may also be suitable for use herein, typical examples of which include lime and alum.

Cyclic Amine Based Polymer Materials


[0026] It may be preferred that the composition herein comprises one or more cyclic amine based polymer. The composition herein may comprise (by weight of said composition) from 0.05% to 10%, preferably from 0.05% to 5% or even from 0.05% to 3% or even 0.1% to 2% cyclic amine based polymer. When used herein, 'polymers' include not only polymers, but also oligomers, co-polymers, co-oligomers, present in any structural arrangement, also including cross-linked arrangements. As will be apparent to those skilled in the art, an oligomer is a molecule consisting of only a few monomer units while polymers comprise considerably more monomer units. For the present invention, oligomers are defined as molecules having an average molecular weight below 1,000 and polymers are molecules having an average molecular weight of greater than 1,000; copolymers or co-oligomers are materials wherein two or more dissimilar monomers have been simultaneously or sequentially polymerized. Copolymers or co-oligomers for use herein can include, for example, polymers or oligomers polymerized from a mixture of a primary cyclic amine based monomer, e.g., piperadine, and a secondary cyclic amine monomer, e.g., morpholine.

[0027] The preferred cyclic amine based polymers herein can be characterized by the following general formula:




wherein;


each T is independently selected from the group consisting of H, C₁-C₁₂ alkyl, substituted alkyl, C₇-C₁₂ alkylaryl, -(CH₂)_nCOOM, -(CH₂)_nSO₃M, CH₂CH(OH)SO₃M, -(CH₂)_nOSO₃M,



10



20 - wherein W comprises at least one cyclic constituent selected from the group consisting of:



30

and



40

in addition to the at least one cyclic constituent, W may also comprise an aliphatic or substituted aliphatic moiety of the general structure;


45




- 55
- each B is independently C₁-C₁₂ alkylene, C₁-C₁₂ substituted alkylene, C₃-C₁₂ alkenylene, C₈-C₁₂ dialkylarylene, C₈-C₁₂ dialkylarylenediyl, and -(R₅O)_nR₅-;
 - each D is independently C₂-C₆ alkylene;
 - each Q is independently selected from the group consisting of hydroxy, C₁-C₁₈ alkoxy, C₂-C₁₈ hydroxyalkoxy,

amino, C₁-C₁₈ alkylamino, dialkylamino, trialkylamino groups, heterocyclic monoamino groups and diamino groups;

- each R₁ is independently selected from the group consisting of H, C₁-C₈ alkyl and C₁-C₈ hydroxyalkyl;
- each R₂ is independently selected from the group consisting of C₁-C₁₂ alkylene, C₁-C₁₂ alkenylene, -CH₂-CH(O_{R1})-CH₂, C₈-C₁₂ alkarylene, C₄-C₁₂ dihydroxyalkylene, poly(C₂-C₄ alkyleneoxy)alkylene, H₂CH(OH)CH₂OR₂OCH₂CH(OH)CH₂-, and C₃-C₁₂ hydrocarbyl moieties; provided that when R₂ is a C₃-C₁₂ hydrocarbyl moiety the hydrocarbyl moiety can comprise from about 2 to about 4 branching moieties of the general structure:



- each R₃ is independently selected from the group consisting of H, O, R₂, C₁-C₂₀ hydroxyalkyl, C₁-C₂₀ alkyl, substituted alkyl, C₆-C₁₁ aryl, substituted aryl, C₇-C₁₁ alkylaryl, C₁-C₂₀ aminoalkyl, -(CH₂)_hCOOM, -(CH₂)_hSO₃M, CH₂CH(OH)SO₃M, -(CH₂)_hOSO₃M,



- each R₄ is independently selected from the group consisting of H, C₁-C₂₂ alkyl, C₁-C₂₂ hydroxyalkyl, aryl and C₇-C₂₂ alkylaryl;
- each R₅ is independently selected from the group consisting of C₂-C₈ alkylene, C₂-C₈ alkyl substituted alkylene; and

A is a compatible monovalent or di or polyvalent anion;

M is a compatible cation;

b = number necessary to balance the charge;

each x is independently from 3 to about 1000;

each c is independently 0 or 1;

each h is independently from about 1 to about 8;

each q is independently from 0 to about 6;

each n is independently from 1 to about 20;

each r is independently from 0 to about 20; and


each t is independently from 0 to 1.

[0028] The cyclic amine based polymer may comprise combinations of these cyclic amine based materials. For example, a mixture of piperadine and epihalohydrin condensates can be combined with a mixture of morpholine and epihalohydrin condensates to achieve the desired fabric treatment results. Moreover, the molecular weight of the cyclic polymers can vary as is illustrated herein.

[0029] Preferred cyclic amine based polymers that fall within this general structure include compounds:


- wherein each R₁ is H; and
- at least one W is selected from the group consisting of:

5




10

15



20

25




30

[0030] Even more preferred compounds are those:

- wherein each R_1 is H; and
- at least one W is selected from the group consisting of:

35


40



45

and

50




55

[0031] And most preferred compounds are those:

- wherein each R_1 is H; and

- at least one W is selected from the group consisting of:




[0032] Preferred compounds to be used as the linking group R_2 include, but are not limited to: polyepoxides, ethylenecarbonate, propylenecarbonate, urea, α , β -unsaturated carboxylic acids, esters of α , β -unsaturated carboxylic acids, amides of α , β -unsaturated carboxylic acids, anhydrides of α , β -unsaturated carboxylic acids, di- or polycarboxylic acids, esters of di- or polycarboxylic acids, amides of di- or polycarboxylic acids, anhydrides of di- or polycarboxylic acids, glycidylhalogens, chloroformic esters, chloroacetic esters, derivatives of chloroformic esters, derivatives of chloroacetic esters, epihalohydrins, glycerol dichlorohydrins, bis-(halohydrins), polyetherdihalo-compounds, phosgene, polyhalogens, functionalized glycidyl ethers and mixtures thereof. Moreover, R_2 can also comprise a reaction product formed by reacting one or more of polyetherdiamines, alkylenediamines, polyalkylenepolyamines, alcohols, alkylene glycols and polyalkyleneglycols with α , β -unsaturated carboxylic acids, esters of α , β -unsaturated carboxylic acids, amides of α , β -unsaturated carboxylic acids and anhydrides of α , β -unsaturated carboxylic acids provided that the reaction products contain at least two double bonds, two carboxylic groups, two amide groups or two ester groups.

[0033] Also preferred cyclic amine based polymers for use herein include adducts of two or more compounds selected from the group consisting of piperazine, piperadine, epichlorohydrin, epichlorohydrin benzyl quat, epichlorohydrin methyl quat, morpholine and mixtures thereof.

[0034] Highly preferred cyclic amine based polymers herein are referred to as Imidazole-epi chlorohydrin copolymers.

[0035] These cyclic amine based polymers can be linear or branched. One specific type of branching can be introduced using a polyfunctional crosslinking agent. An example of such a polymer is exemplified below.



Optional Detergent Ingredients

[0036] The composition herein may comprise the following detergent ingredients:

Surfactant

[0037] The composition herein preferably contains one or more surfactants selected from anionic, nonionic, cationic, ampholytic, amphoteric and zwitterionic surfactants and mixtures thereof.

[0038] A typical listing of anionic, nonionic, ampholytic, and zwitterionic classes, and species of these surfactants, is given in U.S.P. 3,929,678 issued to Laughlin and Heuring on December 30, 1975. Further examples are given in "Surface Active Agents and Detergents" (Vol. I and II by Schwartz, Perry and Berch). A list of suitable cationic surfactants is given in U.S.P. 4,259,217 issued to Murphy on March 31, 1981.

[0039] Where present, ampholytic, amphoteric and zwitterionic surfactants are generally used in combination with one or more anionic and/or nonionic surfactants.

Anionic Surfactant

[0040] The composition herein preferably comprise an additional anionic surfactant. Essentially any anionic surfactants useful for deterative purposes can be comprised in the composition herein. These can include salts (including, for example, sodium, potassium, ammonium, and substituted ammonium salts such as mono-, di- and triethanolamine salts) of the anionic sulfate, sulfonate, carboxylate and sarcosinate surfactants. Anionic sulfate and sulfonate surfactants are preferred.

[0041] Highly preferred are surfactants systems comprising a sulfonate and a sulfate surfactant, preferably a linear or branched alkyl benzene sulfonate and alkyl ethoxysulfates, as described herein, preferably combined with a cationic surfactants as described herein.

[0042] Other anionic surfactants include the isethionates such as the acyl isethionates, N-acyl taurates, fatty acid amides of methyl tauride, alkyl succinates and sulfosuccinates, monoesters of sulfosuccinate (especially saturated and unsaturated C₁₂-C₁₈ monoesters) diesters of sulfosuccinate (especially saturated and unsaturated C₆-C₁₄ diesters), N-acyl sarcosinates. Resin acids and hydrogenated resin acids are also suitable, such as rosin, hydrogenated rosin, and resin acids and hydrogenated resin acids present in or derived from tallow oil.

Anionic Sulfate Surfactant

[0043] Anionic sulfate surfactants suitable for use herein include the linear and branched primary and secondary alkyl sulfates, alkyl ethoxysulfates, fatty oleoyl glycerol sulfates, alkyl phenol ethylene oxide ether sulfates, the C₅-C₁₇ acyl-N-(C₁-C₄ alkyl) and -N-(C₁-C₂ hydroxyalkyl) glucamine sulfates, and sulfates of alkylpolysaccharides such as the sulfates of alkylpolyglucoside (the nonionic nonsulfated compounds described herein).

[0044] Alkyl sulfate surfactants are preferably selected from the linear and branched primary C₁₀-C₁₈ alkyl sulfates, more preferably the C₁₁-C₁₅ branched chain alkyl sulfates and the C₁₂-C₁₄ linear chain alkyl sulfates.

[0045] Alkyl ethoxysulfate surfactants are preferably selected from the group consisting of the C₁₀-C₁₈ alkyl sulfates which have been ethoxylated with from 0.5 to 20 moles of ethylene oxide per molecule. More preferably, the alkyl ethoxysulfate surfactant is a C₁₁-C₁₈, most preferably C₁₁-C₁₅ alkyl sulfate which has been ethoxylated with from 0.5 to 7, preferably from 1 to 5, moles of ethylene oxide per molecule.

Anionic Sulfonate Surfactant

[0046] Anionic sulfonate surfactants suitable for use herein include the salts of C₅-C₂₀ linear alkylbenzene sulfonates, alkyl ester sulfonates, C₆-C₂₂ primary or secondary alkane sulfonates, C₆-C₂₄ olefin sulfonates, sulfonated polycarboxylic acids, alkyl glycerol sulfonates, fatty acyl glycerol sulfonates, fatty oleyl glycerol sulfonates, and any mixtures thereof.

Anionic Carboxylate Surfactant

[0047] Suitable anionic carboxylate surfactants include the alkyl ethoxy carboxylates, the alkyl polyethoxy polycarboxylate surfactants and the soaps ('alkyl carboxyls'), especially certain secondary soaps as described herein.

[0048] Suitable alkyl ethoxy carboxylates include those with the formula RO(CH₂CH₂O)_xCH₂COO-M⁺ wherein R is a C₆ to C₁₈ alkyl group, x ranges from 0 to 10, and the ethoxylate distribution is such that, on a weight basis, the amount of material where x is 0 is less than 20 % and M is a cation. Suitable alkyl polyethoxy polycarboxylate surfactants include those having the formula RO-(CHR₁-CHR₂-O)-R₃ wherein R is a C₆ to C₁₈ alkyl group, x is from 1 to 25, R₁ and R₂ are selected from the group consisting of hydrogen, methyl acid radical, succinic acid radical, hydroxysuccinic acid radical, and mixtures thereof, and R₃ is selected from the group consisting of hydrogen, substituted or unsubstituted hydrocarbon having between 1 and 8 carbon atoms, and mixtures thereof.

[0049] Suitable soap surfactants include the secondary soap surfactants which contain a carboxyl unit connected to a secondary carbon. Preferred secondary soap surfactants for use herein are water-soluble members selected from the group consisting of the water-soluble salts of 2-methyl-1-undecanoic acid, 2-ethyl-1-decanoic acid, 2-propyl-1-nonanoic acid, 2-butyl-1-octanoic acid and 2-pentyl-1-heptanoic acid. Certain soaps may also be included as suds suppressers.

Alkali Metal Sarcosinate Surfactant

[0050] Other suitable anionic surfactants are the alkali metal sarcosinates of formula R-CON(R¹)CH₂COOM, wherein R is a C₅-C₁₇ linear or branched alkyl or alkenyl group, R¹ is a C₁-C₄ alkyl group and M is an alkali metal ion. Preferred examples are the myristyl and oleoyl methyl sarcosinates in the form of their sodium salts.

Alkoxyated Nonionic Surfactant

[0051] Essentially any alkoxyated nonionic surfactants are suitable herein. The ethoxyated and propoxyated nonionic surfactants are preferred.

[0052] Preferred alkoxyated surfactants can be selected from the classes of the nonionic condensates of alkyl phenols, nonionic ethoxyated alcohols, nonionic ethoxyated/propoxyated fatty alcohols, nonionic ethoxyate/propoxyate condensates with propylene glycol, and the nonionic ethoxyate condensation products with propylene oxide/ethylene diamine adducts.

Nonionic Alkoxyated Alcohol Surfactant

[0053] The condensation products of aliphatic alcohols with from 1 to 25 moles of alkylene oxide, particularly ethylene oxide and/or propylene oxide, are suitable for use herein. The alkyl chain of the aliphatic alcohol can either be straight or branched, primary or secondary, and generally contains from 6 to 22 carbon atoms. Particularly preferred are the condensation products of alcohols having an alkyl group containing from 8 to 20 carbon atoms with from 2 to 10 moles of ethylene oxide per mole of alcohol.

Nonionic Polyhydroxy Fatty Acid Amide Surfactant

[0054] Polyhydroxy fatty acid amides suitable for use herein are those having the structural formula R^2CONR^1Z wherein: R^1 is H, C_1 - C_4 hydrocarbyl, 2-hydroxy ethyl, 2-hydroxy propyl, ethoxy, propoxy, or a mixture thereof, preferably C_1 - C_4 alkyl, more preferably C_1 or C_2 alkyl, most preferably C_1 alkyl (i.e., methyl); and R^2 is a C_5 - C_{31} hydrocarbyl, preferably straight-chain C_5 - C_{19} alkyl or alkenyl, more preferably straight-chain C_9 - C_{17} alkyl or alkenyl, most preferably straight-chain C_{11} - C_{17} alkyl or alkenyl, or mixture thereof; and Z is a polyhydroxyhydrocarbyl having a linear hydrocarbyl chain with at least 3 hydroxyls directly connected to the chain, or an alkoxyated derivative (preferably ethoxyated or propoxyated) thereof. Z preferably will be derived from a reducing sugar in a reductive amination reaction; more preferably Z is a glyceryl.


Nonionic Fatty Acid Amide Surfactant

[0055] Suitable fatty acid amide surfactants include those having the formula: $R^6CON(R^7)_2$ wherein R^6 is an alkyl group containing from 7 to 21, preferably from 9 to 17 carbon atoms and each R^7 is selected from the group consisting of hydrogen, C_1 - C_4 alkyl, C_1 - C_4 hydroxyalkyl, and $-(C_2H_4O)_xH$, where x is in the range of from 1 to 3.

Nonionic Alkylpolysaccharide Surfactant

[0056] Suitable alkylpolysaccharides for use herein are disclosed in U.S. Patent 4,565,647, Llenado, issued January 21, 1986, having a hydrophobic group containing from 6 to 30 carbon atoms and a polysaccharide, e.g., a polyglycoside, hydrophilic group containing from 1.3 to 10 saccharide units.

[0057] Preferred alkylpolyglycosides have the formula:



wherein R^2 is selected from the group consisting of alkyl, alkylphenyl, hydroxyalkyl, hydroxyalkylphenyl, and mixtures thereof in which the alkyl groups contain from 10 to 18 carbon atoms; n is 2 or 3; t is from 0 to 10, and x is from 1.3 to 8. The glycosyl is preferably derived from glucose.

Amphoteric Surfactant

[0058] Suitable amphoteric surfactants for use herein include the amine oxide surfactants and the alkyl amphocarboxylic acids.

[0059] Suitable amine oxides include those compounds having the formula $R^3(OR^4)_xN^0(R^5)_2$ wherein R^3 is selected from an alkyl, hydroxyalkyl, acylamidopropoyl and alkyl phenyl group, or mixtures thereof, containing from 8 to 26 carbon atoms; R^4 is an alkylene or hydroxyalkylene group containing from 2 to 3 carbon atoms, or mixtures thereof; x is from 0 to 5, preferably from 0 to 3; and each R^5 is an alkyl or hydroxyalkyl group containing from 1 to 3, or a polyethylene oxide group containing from 1 to 3 ethylene oxide groups. Preferred are C_{10} - C_{18} alkyl dimethylamine oxide, and C_{10-18} acylamido alkyl dimethylamine oxide.

[0060] A suitable example of an alkyl aphodicarboxylic acid is Miranol(TM) C2M Conc. manufactured by Miranol, Inc., Dayton, NJ.

Zwitterionic Surfactant

[0061] Zwitterionic surfactants can also be incorporated into the composition herein. These surfactants can be broadly described as derivatives of secondary and tertiary amines, derivatives of heterocyclic secondary and tertiary amines, or derivatives of quaternary ammonium, quaternary phosphonium or tertiary sulfonium compounds. Betaine and sultaine surfactants are exemplary zwitterionic surfactants for use herein.

[0062] Suitable betaines are those compounds having the formula $R(R^1)_2N^+R^2COO^-$ wherein R is a C_6-C_{18} hydrocarbyl group, each R^1 is typically C_1-C_3 alkyl, and R^2 is a C_1-C_5 hydrocarbyl group. Preferred betaines are C_{12-18} dimethyl-ammonio hexanoate and the C_{10-18} acylamidopropane (or ethane) dimethyl (or diethyl) betaines. Complex betaine surfactants are also suitable for use herein.

Cationic Surfactants

[0063] Suitable cationic surfactants to be used in the composition herein include the quaternary ammonium surfactants. Preferably the quaternary ammonium surfactant is a mono C_6-C_{16} , preferably C_6-C_{10} N-alkyl or alkenyl ammonium surfactants wherein the remaining N positions are substituted by methyl, hydroxyethyl or hydroxypropyl groups. Preferred are also the mono-alkoxylated and bis-alkoxylated amine surfactants.

[0064] Another suitable group of cationic surfactants which can be used in the composition herein are cationic ester surfactants.


The cationic ester surfactant is a, preferably water dispersible, compound having surfactant properties comprising at least one ester (i.e. -COO-) linkage and at least one cationically charged group.

[0065] Suitable cationic ester surfactants, including choline ester surfactants, have for example been disclosed in US Patents No.s 4228042, 4239660 and 4260529.

[0066] In one preferred aspect the ester linkage and cationically charged group are separated from each other in the surfactant molecule by a spacer group consisting of a chain comprising at least three atoms (i.e. of three atoms chain length), preferably from three to eight atoms, more preferably from three to five atoms, most preferably three atoms. The atoms forming the spacer group chain are selected from the group consisting of carbon, nitrogen and oxygen atoms and any mixtures thereof, with the proviso that any nitrogen or oxygen atom in said chain connects only with carbon atoms in the chain. Thus spacer groups having, for example, -O-O- (i.e. peroxide), -N-N-, and -N-O-linkages are excluded, whilst spacer groups having, for example -CH₂-O-CH₂- and -CH₂-NH-CH₂- linkages are included. In a preferred aspect, the spacer group chain comprises only carbon atoms, most preferably the chain is a hydrocarbyl chain.

Cationic mono-alkoxylated amine surfactants

[0067] Highly preferred herein are cationic mono-alkoxylated amine surfactant preferably of the general formula I:




wherein R^1 is an alkyl or alkenyl moiety containing from about 6 to about 18 carbon atoms, preferably 6 to about 16 carbon atoms, most preferably from about 6 to about 14 carbon atoms; R^2 and R^3 are each independently alkyl groups containing from one to about three carbon atoms, preferably methyl, most preferably both R^2 and R^3 are methyl groups; R^4 is selected from hydrogen (preferred), methyl and ethyl; X^- is an anion such as chloride, bromide, methylsulfate, sulfate, or the like, to provide electrical neutrality; A is an alkoxy group, especially an ethoxy, propoxy or butoxy group; and p is from 0 to about 30, preferably 2 to about 15, most preferably 2 to about 8.

[0068] Preferably the ApR^4 group in formula I has $p=1$ and is a hydroxyalkyl group, having no greater than 6 carbon

atoms whereby the —OH group is separated from the quaternary ammonium nitrogen atom by no more than 3 carbon atoms. Particularly preferred ApR⁴ groups are —CH₂CH₂OH, —CH₂CH₂CH₂OH, —CH₂CH(CH₃)OH and -CH(CH₃)CH₂OH, with —CH₂CH₂OH being particularly preferred. Preferred R¹ groups are linear alkyl groups. Linear R¹ groups having from 8 to 14 carbon atoms are preferred.

[0069] Another highly preferred cationic mono-alkoxylated amine surfactants for use herein are of the formula




wherein R¹ is C₁₀-C₁₈ hydrocarbonyl and mixtures thereof, especially C₁₀-C₁₄ alkyl, preferably C₁₀ and C₁₂ alkyl, and X is any convenient anion to provide charge balance, preferably chloride or bromide.

[0070] As noted, compounds of the foregoing type include those wherein the ethoxy (CH₂CH₂O) units (EO) are replaced by butoxy, isopropoxy [CH(CH₃)CH₂O] and [CH₂CH(CH₃O)] units (i-Pr) or n-propoxy units (Pr), or mixtures of EO and/or Pr and/or i-Pr units.

[0071] The levels of the cationic mono-alkoxylated amine surfactants used in the composition herein is preferably from 0.1% to 20%, more preferably from 0.2% to 7%, most preferably from 0.3% to 3.0% by weight of said composition.


Cationic bis-alkoxylated amine surfactant

[0072] The cationic bis-alkoxylated amine surfactant preferably has the general formula II:



wherein R¹ is an alkyl or alkenyl moiety containing from about 8 to about 18 carbon atoms, preferably 10 to about 16 carbon atoms, most preferably from about 10 to about 14 carbon atoms; R² is an alkyl group containing from one to three carbon atoms, preferably methyl; R³ and R⁴ can vary independently and are selected from hydrogen (preferred), methyl and ethyl, X⁻ is an anion such as chloride, bromide, methylsulfate, sulfate, or the like, sufficient to provide electrical neutrality. A and A' can vary independently and are each selected from C₁-C₄ alkoxy, especially ethoxy, (i. e., -CH₂CH₂O-), propoxy, butoxy and mixtures thereof; p is from 1 to about 30, preferably 1 to about 4 and q is from 1 to about 30, preferably 1 to about 4, and most preferably both p and q are 1.


[0073] Highly preferred cationic bis-alkoxylated amine surfactants for use herein are of the formula



wherein R¹ is C₁₀-C₁₈ hydrocarbonyl and mixtures thereof, preferably C₁₀, C₁₂, C₁₄ alkyl and mixtures thereof. X is any convenient anion to provide charge balance, preferably chloride. With reference to the general cationic bis-alkoxylated amine structure noted above, since in a preferred compound R¹ is derived from (coconut) C₁₂-C₁₄ alkyl fraction fatty

acids, R² is methyl and ApR³ and A^qR⁴ are each monoethoxy.

[0074] Other cationic bis-alkoxylated amine surfactants useful herein include compounds of the formula:



wherein R¹ is C₁₀-C₁₈ hydrocarbyl, preferably C₁₀-C₁₄ alkyl, independently p is 1 to about 3 and q is 1 to about 3, R² is C₁-C₃ alkyl, preferably methyl, and X is an anion, especially chloride or bromide.

[0075] Other compounds of the foregoing type include those wherein the ethoxy (CH₂CH₂O) units (EO) are replaced by butoxy (Bu) isopropoxy [CH(CH₃)CH₂O] and [CH₂CH(CH₃O)] units (i-Pr) or n-propoxy units (Pr), or mixtures of EO and/or Pr and/or i-Pr units.

Building Agent

[0076] The composition herein may comprise one or more building agents. Preferred building agents are described in more detail hereinafter. These building agents may be water-soluble building compounds, also herein referred to as water-soluble builder compounds, or water-insoluble or partially water-insoluble building agents, also herein referred to as insoluble builder compounds or partially soluble builder compounds.

Water-Soluble Builder Compound

[0077] The composition herein may preferably contain a water-soluble builder compound, typically present in said compositions at a level of from 1% to 80% by weight, preferably from 10% to 60% by weight, most preferably from 15% to 40% by weight of the composition.

[0078] The composition herein may preferably comprise phosphate-containing builder material. Preferably present at a level of from 0.5% to 60%, more preferably from 5% to 50%, more preferably from 8% to 40% by weight of the composition.

[0079] The phosphate-containing builder material preferably comprises tetrasodium pyrophosphate or even more preferably anhydrous sodium tripolyphosphate.

[0080] Suitable water-soluble builder compounds include the water soluble monomeric polycarboxylates, or their acid forms, homo or copolymeric polycarboxylic acids or their salts in which the polycarboxylic acid comprises at least two carboxylic radicals separated from each other by not more than two carbon atoms, borates, and mixtures of any of the foregoing.

[0081] The carboxylate or polycarboxylate builder can be monomeric or oligomeric in type although monomeric polycarboxylates are generally preferred for reasons of cost and performance.

[0082] Suitable carboxylates containing one carboxy group include the water soluble salts of lactic acid, glycolic acid and ether derivatives thereof. Polycarboxylates containing two carboxy groups include the water-soluble salts of succinic acid, malonic acid, (ethylenedioxy) diacetic acid, maleic acid, diglycolic acid, tartaric acid, tartronic acid and fumaric acid, as well as the ether carboxylates and the sulfanyl carboxylates.

[0083] Polycarboxylates or their acids containing three carboxy groups include, in particular, water-soluble citrates, aconitrates and citraconates as well as succinate derivatives such as the carboxymethyloxysuccinates described in British Patent No. 1,379,241, lactoxysuccinates described in British Patent No. 1,389,732, and aminosuccinates described in Netherlands Application 7205873, and the oxypolycarboxylate materials such as 2-oxa-1,1,3-propane tricarboxylates described in British Patent No. 1,387,447. The most preferred polycarboxylic acid containing three carboxy groups is citric acid, preferably present at a level of from 0.1% to 15%, more preferably from 0.5% to 8% by weight of the composition.

[0084] Polycarboxylates containing four carboxy groups include oxydisuccinates disclosed in British Patent No. 1,261,829, 1,1,2,2-ethane tetracarboxylates, 1,1,3,3-propane tetracarboxylates and 1,1,2,3-propane tetracarboxylates. Polycarboxylates containing sulfo substituents include the sulfosuccinate derivatives disclosed in British Patent Nos. 1,398,421 and 1,398,422 and in U.S. Patent No. 3,936,448, and the sulfonated pyrolysed citrates described in British Patent No. 1,439,000. Preferred polycarboxylates are hydroxycarboxylates containing up to three carboxy groups per molecule, more particularly citrates.

[0085] The parent acids of the monomeric or oligomeric polycarboxylate chelating agents or mixtures thereof with their salts, e.g. citric acid or citrate/citric acid mixtures are also contemplated as useful builder components.

[0086] Borate builders, as well as builders containing borate-forming materials that can produce borate under detergent storage or wash conditions are useful water-soluble builders herein.

[0087] Suitable examples of water-soluble phosphate builders are the alkali metal triphosphates, sodium, potassium and ammonium pyrophosphate, sodium and potassium and ammonium pyrophosphate, sodium and potassium orthophosphate, sodium polymeta/phosphate in which the degree of polymerization ranges from about 6 to 21, and salts of phytic acid.


Partially Soluble or Insoluble Builder Compound

[0088] The compositions herein may contain a partially soluble or insoluble builder compound, typically present at a level of from 0.5% to 60% by weight, preferably from 5% to 50% by weight, most preferably from 8% to 40% by weight of the composition.

[0089] Examples of largely water insoluble builders include the sodium aluminosilicates.

[0090] Suitable aluminosilicate zeolites have the unit cell formula $\text{Na}_x[(\text{AlO}_2)_z(\text{SiO}_2)_y] \cdot x\text{H}_2\text{O}$ wherein z and y are at least 6; the molar ratio of z to y is from 1.0 to 0.5 and x is at least 5, preferably from 7.5 to 276, more preferably from 10 to 264. The aluminosilicate material are in hydrated form and are preferably crystalline, containing from 10% to 28%, more preferably from 18% to 22% water in bound form.

[0091] The aluminosilicate zeolites can be naturally occurring materials, but are preferably synthetically derived. Synthetic crystalline aluminosilicate ion exchange materials are available under the designations Zeolite A, Zeolite B, Zeolite P, Zeolite X, Zeolite HS and mixtures thereof. Zeolite A has the formula:



wherein x is from 20 to 30, especially 27. Zeolite X has the formula $\text{Na}_{86}[(\text{AlO}_2)_{86}(\text{SiO}_2)_{106}] \cdot 276 \text{H}_2\text{O}$.

[0092] Another preferred aluminosilicate zeolite is zeolite MAP builder.

The zeolite MAP can be present at a level of from 1% to 80%, more preferably from 15% to 40% by weight of the composition.

[0093] Zeolite MAP is described in EP 384070A (Unilever). It is defined as an alkali metal aluminosilicate of the zeolite P type having a silicon to aluminium ratio not greater than 1.33, preferably within the range from 0.9 to 1.33 and more preferably within the range of from 0.9 to 1.2.

[0094] Of particular interest is zeolite MAP having a silicon to aluminium ratio not greater than 1.15 and, more particularly, not greater than 1.07.

[0095] In a preferred aspect the zeolite MAP detergent builder has a particle size, expressed as a d_{50} value of from 1.0 to 10.0 micrometres, more preferably from 2.0 to 7.0 micrometres, most preferably from 2.5 to 5.0 micrometres.

[0096] The d_{50} value indicates that 50% by weight of the particles have a diameter smaller than that figure. The particle size may, in particular be determined by conventional analytical techniques such as microscopic determination using a scanning electron microscope or by means of a laser granulometer. Other methods of establishing d_{50} values are disclosed in EP 384070A.

Chelating Agent

[0097] The composition herein may comprise one or more chelating agents, also herein referred to as heavy metal ion sequestrant. Preferred chelating agents are described in more detail hereinafter.

Heavy metal ion sequestrant

[0098] The compositions herein preferably contain as an optional component a heavy metal ion sequestrant. By heavy metal ion sequestrant it is meant herein components which act to sequester (chelate) heavy metal ions. These components may also have calcium and magnesium chelation capacity, but preferentially they show selectivity to binding heavy metal ions such as iron, manganese and copper.

[0099] Heavy metal ion sequestrants are generally present at a level of from 0.005% to 10%, preferably from 0.1% to 5%, more preferably from 0.25% to 7.5% and most preferably from 0.3% to 2% by weight of the composition.

[0100] Suitable heavy metal ion sequestrants for use herein include organic phosphonates, such as the amino alkylene poly (alkylene phosphonates), alkali metal ethane 1-hydroxy disphosphonates and nitrilo trimethylene phosphonates.

[0101] Preferred among the above species are diethylene triamine penta (methylene phosphonate), ethylene diamine tri (methylene phosphonate) hexamethylene diamine tetra (methylene phosphonate) and hydroxy-ethylene 1,1 diphos-

phonate, 1,1 hydroxyethane diphosphonic acid and 1,1 hydroxyethane dimethylene phosphonic acid.

[0102] Other suitable heavy metal ion sequestrant for use herein include nitrilotriacetic acid and polyaminocarboxylic acids such as ethylenediaminetetracetic acid, ethylenediamine disuccinic acid, ethylenediamine diglutamic acid, 2-hydroxypropylenediamine disuccinic acid or any salts thereof.

[0103] Other suitable heavy metal ion sequestrants for use herein are iminodiacetic acid derivatives such as 2-hydroxyethyl diacetic acid or glyceryl imino diacetic acid, described in EP-A-317,542 and EP-A-399,133. The iminodiacetic acid-N-2-hydroxypropyl sulfonic acid and aspartic acid N-carboxymethyl N-2-hydroxypropyl-3-sulfonic acid sequestrants described in EP-A-516,102 are also suitable herein. The β -alanine-N,N'-diacetic acid, aspartic acid-N,N'-diacetic acid, aspartic acid-N-monoacetic acid and iminodisuccinic acid sequestrants described in EP-A-509,382 are also suitable.

[0104] EP-A-476,257 describes suitable amino based sequestrants. EP-A-510,331 describes suitable sequestrants derived from collagen, keratin or casein. EP-A-528,859 describes a suitable alkyl iminodiacetic acid sequestrant. Dipicolinic acid and 2-phosphonobutane-1,2,4-tricarboxylic acid are also suitable. Glycinamide-N,N'-disuccinic acid (GADS), ethylenediamine-N,N'-diglutamic acid (EDDG) and 2-hydroxypropylenediamine-N,N'-disuccinic acid (HPDDS) are also suitable.

[0105] Especially preferred are diethylenetriamine pentacetic acid, ethylenediamine-N,N'-disuccinic acid (EDDS) and 1,1 hydroxyethane diphosphonic acid or the alkali metal, alkaline earth metal, ammonium, or substituted ammonium salts thereof, or mixtures thereof.

Bleaching Agent

[0106] The composition herein may comprise one or bleaching agents. Preferred bleaching agents for use herein are described in more detail hereinafter.

Perhydrate Bleaches

[0107] A preferred additional bleaching agent is a perhydrate bleach, such as metal perborates, metal percarbonates, particularly the sodium salts. Perborate can be mono or tetra hydrated. Sodium percarbonate has the formula corresponding to $2\text{Na}_2\text{CO}_3 \cdot 3\text{H}_2\text{O}_2$, and is available commercially as a crystalline solid.


[0108] Potassium peroxymonopersulfate, sodium per is another optional inorganic perhydrate salt of use in the composition herein.

Organic Peroxyacid Bleaching System


[0109] A preferred feature of the composition herein is an organic peroxyacid bleaching system. In one preferred execution the bleaching system contains a hydrogen peroxide source and an organic peroxyacid bleach precursor compound. The production of the organic peroxyacid occurs by an in situ reaction of the precursor with a source of hydrogen peroxide. Preferred sources of hydrogen peroxide include inorganic perhydrate bleaches, such as the perborate bleach. In an alternative preferred execution a preformed organic peroxyacid is incorporated directly into the composition herein. The composition herein may contain mixtures of a hydrogen peroxide source and organic peroxyacid precursor in combination with a preformed organic peroxyacid.

Peroxyacid Bleach Precursor

[0110] Peroxyacid bleach precursors are compounds which react with hydrogen peroxide in a perhydrolysis reaction to produce a peroxyacid. Generally peroxyacid bleach precursors may be represented as



where L is a leaving group and X is essentially any functionality, such that on perhydrolysis the structure of the peroxyacid produced is



5

Peroxyacid bleach precursor compounds are preferably incorporated at a level of from 0.5% to 20% by weight, more preferably from 1% to 15% by weight, most preferably from 1.5% to 10% by weight of the composition herein.


10 **[0111]** Suitable peroxyacid bleach precursor compounds typically contain one or more N- or O-acyl groups, which precursors can be selected from a wide range of classes. Suitable classes include anhydrides, esters, imides, lactams and acylated derivatives of imidazoles and oximes. Examples of useful materials within these classes are disclosed in GB-A-1586789. Suitable esters are disclosed in GB-A-836988, 864798, 1147871, 2143231 and EP-A-0170386.

15 Leaving Groups


[0112] The leaving group, hereinafter L group, must be sufficiently reactive for the perhydrolysis reaction to occur within the optimum time frame (e.g., a wash cycle). However, if L is too reactive, this activator will be difficult to stabilize for use herein.

20 **[0113]** Preferred L groups are selected from the group consisting of:

25



30



35


40


45



50

55





5
10 and mixtures thereof, wherein R¹ is an alkyl, aryl, or alkaryl group containing from 1 to 14 carbon atoms, R³ is an alkyl chain containing from 1 to 8 carbon atoms, R⁴ is H or R³, and Y is H or a solubilizing group. Any of R¹, R³ and R⁴ may be substituted by essentially any functional group including, for example alkyl, hydroxy, alkoxy, halogen, amine, nitrosyl, amide and ammonium or alkyl ammonium groups.

15 **[0114]** The preferred solubilizing groups are -SO₃⁻M⁺, -CO₂⁻M⁺, -SO₄⁻M⁺, -N⁺(R³)₄X⁻ and O⁻-N(R³)₃ and most preferably -SO₃⁻M⁺ and -CO₂⁻M⁺ wherein R³ is an alkyl chain containing from 1 to 4 carbon atoms, M is a cation which provides solubility to the bleach activator and X is an anion which provides solubility to the bleach activator. Preferably, M is an alkali metal, ammonium or substituted ammonium cation, with sodium and potassium being most preferred, and X is a halide, hydroxide, methylsulfate or acetate anion.

20 Alkyl Percarboxylic Acid Bleach Precursors


[0115] Alkyl percarboxylic acid bleach precursors form percarboxylic acids on perhydrolysis. Preferred precursors of this type provide peracetic acid on perhydrolysis.

25 **[0116]** Preferred alkyl percarboxylic precursor compounds of the imide type include the N-,N,N¹N¹ tetra acetylated alkylene diamines wherein the alkylene group contains from 1 to 6 carbon atoms, particularly those compounds in which the alkylene group contains 1, 2 and 6 carbon atoms. Tetraacetyl ethylene diamine (TAED) is particularly preferred.

30 **[0117]** Other preferred alkyl percarboxylic acid precursors include sodium 3,5,5-tri-methyl hexanoyloxybenzene sulfonate (iso-NOBS), sodium nonanoyloxybenzene sulfonate (NOBS), sodium acetoxybenzene sulfonate (ABS) and pentaacetyl glucose.

Amide Substituted Alkyl Peroxyacid Precursors

35 **[0118]** Amide substituted alkyl peroxyacid precursor compounds are suitable for use herein, including those of the following general formulae:




45 wherein R¹ is an alkyl group with from 1 to 14 carbon atoms, R² is an alkylene group containing from 1 to 14 carbon atoms, and R⁵ is H or an alkyl group containing 1 to 10 carbon atoms and L can be essentially any leaving group. Amide substituted bleach activator compounds of this type are described in EPA-0170386.

50 Preformed Organic Peroxyacid

[0119] The composition herein may contain, in addition to, or as an alternative to, an organic peroxyacid bleach precursor compound, a preformed organic peroxyacid, typically at a level of from 1% to 15% by weight, more preferably from 1% to 10% by weight of the composition.

55 **[0120]** A preferred class of organic peroxyacid compounds are the amide substituted compounds of the following general formulae:



wherein R¹ is an alkyl, aryl or alkaryl group with from 1 to 14 carbon atoms, R² is an alkylene, arylene, and alkarylene group containing from 1 to 14 carbon atoms, and R⁵ is H or an alkyl, aryl, or alkaryl group containing 1 to 10 carbon atoms. Amide substituted organic peroxyacid compounds of this type are described in EP-A-0170386.

[0121] Other organic peroxyacids include diacyl and tetraacylperoxides, especially diperoxydodecanedioic acid, diperoxytetradecanedioic acid and diperoxyhexadecanedioic acid. Mono- and diperazelaic acid, mono- and diperbrassylic acid and N-phthaloylaminoperoxicaproic acid are also suitable herein.

Enzyme

[0122] Another preferred ingredient useful in the composition herein is one or more additional enzymes.

[0123] Preferred additional enzymatic materials include the commercially available lipases, cutinases, amylases, neutral and alkaline proteases, cellulases, endolases, esterases, pectinases, lactases and peroxidases conventionally incorporated into the composition herein. Suitable enzymes are discussed in US Patents 3,519,570 and 3,533,139.

[0124] Preferred commercially available protease enzymes include those sold under the tradenames Alcalase, Savinase, Primase, Durazym, and Esperase by Novo Industries A/S (Denmark), those sold under the tradename Maxatase, Maxacal and Maxapem by Gist-Brocades, those sold by Genencor International, and those sold under the tradename Opticlean and Optimase by Solvay Enzymes. Protease enzyme may be incorporated into the composition herein at a level of from 0.0001% to 4% active enzyme by weight of the composition.

[0125] Preferred amylases include, for example, α -amylases obtained from a special strain of *B licheniformis*, described in more detail in GB-1,269,839 (Novo). Preferred commercially available amylases include for example, those sold under the tradename Rapidase by Gist-Brocades, and those sold under the tradename Termamyl, Duramyl and BAN by Novo Industries A/S. Highly preferred amylase enzymes maybe those described in PCT/US 9703635, and in WO95/26397 and WO96/23873.

[0126] Amylase enzyme may be incorporated into the composition herein at a level of from 0.0001% to 2% active enzyme by weight of the composition.

[0127] Lipolytic enzyme may be present at levels of active lipolytic enzyme of from 0.0001% to 2% by weight, preferably 0.001% to 1% by weight, most preferably from 0.001% to 0.5% by weight of the composition.

[0128] The lipase may be fungal or bacterial in origin being obtained, for example, from a lipase producing strain of *Humicola* sp., *Thermomyces* sp. or *Pseudomonas* sp. including *Pseudomonas pseudoalcaligenes* or *Pseudomas fluorescens*. Lipase from chemically or genetically modified mutants of these strains are also useful herein. A preferred lipase is derived from *Pseudomonas pseudoalcaligenes*, which is described in Granted European Patent, EP-B-0218272.

[0129] Another preferred lipase herein is obtained by cloning the gene from *Humicola lanuginosa* and expressing the gene in *Aspergillus oryza*, as host, as described in European Patent Application, EP-A-0258 068, which is commercially available from Novo Industri A/S, Bagsvaerd, Denmark, under the trade name Lipolase. This lipase is also described in U.S. Patent 4,810,414, Huger-Jensen et al, issued March 7, 1989.

Suds Suppressing System

[0130] The composition herein, when formulated for use in machine washing compositions, may comprise a suds suppressing system present at a level of from 0.01% to 15%, preferably from 0.02% to 10%, most preferably from 0.05% to 3% by weight of the composition.

[0131] Suitable suds suppressing systems for use herein may comprise essentially any known antifoam compound, including, for example silicone antifoam compounds and 2-alkyl alcanol antifoam compounds.

[0132] By antifoam compound it is meant herein any compound or mixtures of compounds which act such as to depress the foaming or sudsing produced by a solution of a detergent composition, particularly in the presence of agitation of that solution.

[0133] Particularly preferred antifoam compounds for use herein are silicone antifoam compounds defined herein as any antifoam compound including a silicone component. Such silicone antifoam compounds also typically contain

a silica component. The term "silicone" as used herein, and in general throughout the industry, encompasses a variety of relatively high molecular weight polymers containing siloxane units and hydrocarbyl group of various types. Preferred silicone antifoam compounds are the siloxanes, particularly the polydimethylsiloxanes having trimethylsilyl end blocking units.

5 **[0134]** Other suitable antifoam compounds include the monocarboxylic fatty acids and soluble salts thereof. These materials are described in US Patent 2,954,347, issued September 27, 1960 to Wayne St. John. The monocarboxylic fatty acids, and salts thereof, for use as suds suppressor typically have hydrocarbyl chains of 10 to 24 carbon atoms, preferably 12 to 18 carbon atoms. Suitable salts include the alkali metal salts such as sodium, potassium, and lithium salts, and ammonium and alkanolammonium salts.

10 **[0135]** Other suitable antifoam compounds include, for example, high molecular weight fatty esters (e.g. fatty acid triglycerides), fatty acid esters of monovalent alcohols, aliphatic C₁₈-C₄₀ ketones (e.g. stearone) N-alkylated amino triazines such as tri- to hexaalkylmelamines or di- to tetra alkyldiamine chlortriazines formed as products of cyanuric chloride with two or three moles of a primary or secondary amine containing 1 to 24 carbon atoms, propylene oxide, bis stearic acid amide and monostearyl di-alkali metal (e.g. sodium, potassium, lithium) phosphates and phosphate esters.

15 **[0136]** A preferred suds suppressing system comprises:

(a) antifoam compound, preferably silicone antifoam compound, most preferably a silicone antifoam compound comprising in combination

20 (i) polydimethyl siloxane, at a level of from 50% to 99%, preferably 75% to 95% by weight of the silicone antifoam compound; and

(ii) silica, at a level of from 1% to 50%, preferably 5% to 25% by weight of the silicone/silica antifoam compound;

25 wherein said silica/silicone antifoam compound is incorporated at a level of from 5% to 50%, preferably 10% to 40% by weight;

30 (b) a dispersant compound, most preferably comprising a silicone glycol rake copolymer with a polyoxyalkylene content of 72-78% and an ethylene oxide to propylene oxide ratio of from 1:0.9 to 1:1.1, at a level of from 0.5% to 10%, preferably 1% to 10% by weight; a particularly preferred silicone glycol rake copolymer of this type is DCO544, commercially available from DOW Corning under the tradename DCO544;

35 (c) an inert carrier fluid compound, most preferably comprising a C₁₆-C₁₈ ethoxylated alcohol with a degree of ethoxylation of from 5 to 50, preferably 8 to 15, at a level of from 5% to 80%, preferably 10% to 70%, by weight;

40 **[0137]** A highly preferred particulate suds suppressing system is described in EP-A-0210731 and comprises a silicone antifoam compound and an organic carrier material having a melting point in the range 50°C to 85°C, wherein the organic carrier material comprises a monoester of glycerol and a fatty acid having a carbon chain containing from 12 to 20 carbon atoms. EP-A-0210721 discloses other preferred particulate suds suppressing systems wherein the organic carrier material is a fatty acid or alcohol having a carbon chain containing from 12 to 20 carbon atoms, or a mixture thereof, with a melting point of from 45°C to 80°C.

45 **[0138]** Other highly preferred suds suppressing systems comprise polydimethylsiloxane or mixtures of silicone, such as polydimethylsiloxane, aluminosilicate and polycarboxylic polymers, such as copolymers of laic and acrylic acid.

Polymeric Dye Transfer Inhibiting Agents


50 **[0139]** The composition herein may also comprise from 0.01% to 10 %, preferably from 0.05% to 0.5% by weight of polymeric dye transfer inhibiting agents.

[0140] The polymeric dye transfer inhibiting agents are preferably selected from polyamine N-oxide polymers, copolymers of N-vinylpyrrolidone and N-vinylimidazole, polyvinylpyrrolidone polymers or combinations thereof, whereby these polymers can be cross-linked polymers.

Optical Brightener

55 **[0141]** The composition herein also optionally contain from about 0.005% to 5% by weight of certain types of hydrophilic optical brighteners.

[0142] Hydrophilic optical brighteners useful herein include those having the structural formula:



wherein R_1 is selected from anilino, N-2-bis-hydroxyethyl and NH-2-hydroxyethyl; R_2 is selected from N-2-bis-hydroxyethyl, N-2-hydroxyethyl-N-methylamino, morphilino, chloro and amino; and M is a salt-forming cation such as sodium or potassium.

[0143] When in the above formula, R_1 is anilino, R_2 is N-2-bis-hydroxyethyl and M is a cation such as sodium, the brightener is 4,4'-bis[(4-anilino-6-(N-2-bis-hydroxyethyl)-s-triazine-2-yl)amino]-2,2'-stilbenedisulfonic acid and disodium salt. This particular brightener species is commercially marketed under the tradename Tinopal-UNPA-GX by Ciba-Geigy Corporation. Tinopal-CBS-X and Tinopal-UNPA-GX is the preferred hydrophilic optical brightener useful in the composition herein.

[0144] When in the above formula, R_1 is anilino, R_2 is N-2-hydroxyethyl-N-2-methylamino and M is a cation such as sodium, the brightener is 4,4'-bis[(4-anilino-6-(N-2-hydroxyethyl-N-methylamino)-s-triazine-2-yl)amino]-2,2'-stilbenedisulfonic acid disodium salt. This particular brightener species is commercially marketed under the tradename Tinopal 5BM-GX by Ciba-Geigy Corporation.

[0145] When in the above formula, R_1 is anilino, R_2 is morphilino and M is a cation such as sodium, the brightener is 4,4'-bis[(4-anilino-6-morphilino-s-triazine-2-yl)amino]-2,2'-stilbenedisulfonic acid, sodium salt. This particular brightener species are commercially marketed under the tradename Tinopal-DMS-X and Tinopal AMS-GX by Ciba Geigy Corporation.

Other Optional Ingredients

[0146] Other optional ingredients suitable for use herein include perfumes, colours and filler salts, with sodium sulfate being a preferred filler salt.

[0147] Preferably, the composition herein may contain from about 2% to about 10% by weight of an organic acid, preferably citric acid. Also, preferably combined with a carbonate salt, minor amounts (e.g., less than about 20% by weight) of neutralizing agents, buffering agents, phase regulants, hydrotropes, enzyme stabilizing agents, polyacids, suds regulants, opacifiers, anti-oxidants, bactericides and dyes, such as those described in US Patent 4,285,841 to Barrat et al., issued August 25, 1981, can be present.

Composition

[0148] The composition herein is a solid detergent composition. The composition herein is in solid form, such as a granular composition or, agglomerate or granule containing composition. The composition herein can be made by methods such as dry-mixing, agglomerating, compaction, spray drying of various ingredients comprised in the composition herein, or a combination thereof. The composition herein preferably has a bulk density of from 300g/litre or even 350g/litre or 450g/litre to preferably 1500g/litre or 1000g/litre or even to 850g/litre.

[0149] The composition herein comprises a hectorite clay and a dioctrahedral smectite clay. The ratio of said hectorite clay to said dioctrahedral smectite clay is less than 1:1, preferably less than 0.8:1, more preferably less than 0.6:1, or preferably from 0.1:1 to 0.9:1, more preferably from 0.2:1 to 0.7:1, more preferably from 0.2:1 to 0.5:1.

[0150] Preferably, said composition comprises (by weight of said composition) an amount of clay of no more than 10%, or preferably from 1% to 10%, preferably from 5% to 15%, more preferably from 7% to 10%. Preferably, said clay comprises (by weight of said clay) no more than 35%, preferably less than 35% impurities such as mineral impurities, typical mineral impurities include calcite.

[0151] Preferably, the clay is present in said composition as a separate preformed particle.

[0152] Preferably, said preformed particle has a weight average particle size of from 250 micrometers to 1500 micrometers, more preferably from 500 micrometers to 1350 micrometers, more preferably from 600 micrometers to 1200 micrometers, more preferably from 800 micrometers to 1000 micrometers. Said hectorite clay and said dioctrahedral smectite clay are present in the same separate preformed particle.

[0153] Said preformed particle may comprise additional detergent ingredients such as surfactant, building agent, chelating agent, bleaching agent, filler agent or combination thereof. Preferably, said preformed particle comprises one

or more binding agents. Typical binding agents for use herein include humectant and/or hydrophobic compounds, preferably a wax or oil such as paraffin oil. Preferred binding agents are organic compounds, including propylene glycol, ethylene glycol, dimers or trimers of glycol, most preferably glycerol. Another preferred binding agent is water. It may also be preferred that the preformed particle comprises a flocculation agent, said flocculation agent is described in more detail herein, said preformed particle is in the form of an agglomerate. Preferably, said preformed particle is in the form of an agglomerate and comprises a binding agent.

Laundry Washing Method

[0154] Laundry washing methods herein typically comprise treating soiled laundry with an aqueous wash solution for washing by machine or for washing by hand, having dissolved or dispensed therein an effective amount of the composition herein. By an effective amount of the composition it is meant from 40g to 300g of said composition dissolved or dispersed in a wash solution of volume from 1 to 65 litres, as are typical product dosages and wash solution volumes commonly employed in conventional laundry methods. Other laundry washing processes known in the art can also be used.

EXAMPLES

Example I

[0155] 150g hectorite clay powder supplied by Rheox under the trade name Bentone HC and 300g montmorillonite clay powder supplied by CSM under the trade name "**AP base**" is added to a food mixer and mixed at half speed for 10 seconds to form a clay mixture. 22.5g glycerol is slowly added to the clay mixture which is being constantly mixed at half speed during the period of glycerol addition to form a glycerol-clay mixture. 90g distilled water is slowly added to the glycerol-clay mixture which is being constantly mixed at full speed during the period of water addition to form moist clay agglomerates. 15g molten paraffin wax at a temperature of 70°C is added to the moist clay agglomerates and the agglomerates are mixed at full speed in the food mixer for 5 seconds.

[0156] The moist clay agglomerates are then transferred to a Sherwood fluidised bed dryer and dried for 5 minutes to form clay agglomerates. The air temperature in the drier is 60°C and the air flow rate in the drier is 1.2meter/second during the drying period. The moisture content of the clay agglomerates after the drying step is 5% by weight of the agglomerates. The clay agglomerates are then sieved using a ROTAP sieve with mesh sizes of 250 micrometers and 1180 micrometers, and the clay agglomerates having a particle size of from 250 micrometers to 1180 micrometers are collected. 15g clay agglomerates are added to 120g base detergent powder comprising ester carboxymethyl cellulose, polyethylene oxide, surfactant, sodium carbonate, sodium sulphate, zeolite, enzymes and suds suppressor, to form a solid detergent composition in accord with the present invention.

Example II

[0157] 450g hectorite clay powder supplied by Rheox under the trade name Bentone is added to a food mixer. 22.5g glycerol is slowly added to the clay mixture which is being constantly mixed at half speed during the period of glycerol addition to form a glycerol-clay mixture. 120g distilled water is slowly added to the glycerol-clay mixture which is being constantly mixed at full speed during the period of water addition to form moist hectorite clay agglomerates. 15g molten paraffin wax at a temperature of 70°C is added to the moist hectorite clay agglomerates and the agglomerates are mixed at full speed in the food mixer for 5 seconds. The moist hectorite clay agglomerates are then transferred to a Sherwood fluidised bed dryer and dried for 6 minutes to form hectorite clay agglomerates. The air temperature in the drier is 60°C and the air flow rate in the drier is 1.2meter/second during the drying period. The moisture content of the hectorite clay agglomerates after the drying step is 5% by weight of the agglomerates. The hectorite clay agglomerates are then sieved using a ROTAP sieve with mesh sizes of 250 micrometers and 1180 micrometers, and the hectorite clay agglomerates having a particle size of from 250 micrometers to 1180 micrometers are collected.

[0158] Then, 450g montmorillonite clay powder supplied by CSM under the trade name "**AP base**" is added to a food mixer. 22.5g glycerol is slowly added to the clay mixture which is being constantly mixed at half speed during the period of glycerol addition to form a glycerol-clay mixture. 70g distilled water is slowly added to the glycerol-clay mixture which is being constantly mixed at full speed during the period of water addition to form moist montmorillonite clay agglomerates. 15g molten paraffin wax at a temperature of 70°C is added to the moist montmorillonite clay agglomerates and the agglomerates are mixed at full speed in the food mixer for 5 seconds. The moist montmorillonite clay agglomerates are then transferred to a Sherwood fluidised bed dryer and dried for 4 minutes to form montmorillonite clay agglomerates. The air temperature in the drier is 60°C and the air flow rate in the drier is 1.2meter/second during the drying period. The moisture content of the montmorillonite clay agglomerates after the drying step is 5% by weight

of the agglomerates. The montmorillonite clay agglomerates are then sieved using a ROTAP sieve with mesh sizes of 250 micrometers and 1180 micrometers, and the montmorillonite clay agglomerates having a particle size of from 250 micrometers to 1180 micrometers are collected.

[0159] 5g hectorite clay agglomerates and 10g montmorillonite clay agglomerates are added to 120g base detergent powder comprising, ester carboxymethyl cellulose, polyethylene oxide, surfactant, sodium carbonate, sodium sulphate, zeolite, enzymes and suds suppressor, to form a solid detergent composition in accord with the present invention.

Example III

[0160] 3g hectorite clay powder supplied by Rheox under the trade name Bentone HC and 7g montmorillonite clay powder supplied by CSM under the trade name "AP base" are added to and dry mixed with 125g base detergent powder comprising ester carboxymethyl cellulose, polyethylene oxide, surfactant, sodium carbonate, sodium sulphate, zeolite, enzymes and suds suppressor, to form a solid detergent composition in accord with the present invention.

Example IV


[0161] The following compositions are solid detergent compositions in accord with the present invention. The amounts of the detergent ingredients are shown as % by weight of said composition.

	A	B	C	D	E
Hectorite clay	3	3	3	4	1
Montmorillonite clay	6	5	7	7	8
Ester carboxymethyl cellulose	0.1	0.2	1	2	
Polyethylene oxide		0.2		0.1	1
Imidazole-epi chlorohydrin - copolymer	1		0.1		0.5
Nonionic surfactant	10	20	15	20	5
Anionic Surfactant	5			5	17
Cationic Surfactant	5		5		
Sodium tripolyphosphate		5	10		20
Zeolite	15	10	5	20	
Chelating agent			0.4		1
Bleaching agent			10		8
Suds Suppressor	0.4	0.05		0.1	0.2
Carbonate	15	10	15	30	25
Sulphate	25	20	15	10	25
Enzyme	0.1		0.4		
Minors and water	to 100	to 100	to 100	to 100	to 100

Claims

1. A solid detergent composition comprising a hectorite clay and a dioctahedral smectite clay, wherein, the weight ratio of said hectorite clay to said dioctahedral smectite clay is less than 1:1, wherein said hectorite clay and said dioctahedral smectite clay are present in said composition in the form of agglomerate particles, and wherein further said hectorite clay and said dioctahedral smectite clay are present in the same agglomerate particle.


2. A composition according to claim 1, whereby said hectorite clay has the general formula




wherein y=0 to 0.4, and whereby if y>0 then Me^{III} is Al, Fe or B, preferably y=0; Mⁿ⁺ is a monovalent (n=1) or a divalent (n=2) metal ion, preferably selected from Na, K, Mg, Ca and Sr; x is a number from 0.1 to 0.5, preferably from 0.2 to 0.4, more preferably from 0.25 to 0.35; z is a number from 0 to 2, preferably the value of (x+y) is in the

range of from 0.1 to 0.5, preferably from 0.2 to 0.4, more preferably from 0.25 to 0.35.

3. A composition according to claims 1 or 2, whereby said dioctahedral smectite clay is a montmorillonite clay, said montmorillonite clay has the general formula



or




wherein x is a number from 0.1 to 0.5, preferably from 0.2 to 0.4.

4. A composition according to any preceding claim, whereby said hectorite clay has an aspect ratio of greater than 3:1.
5. A composition according to any preceding claim, whereby said hectorite clay has a volume weight mean particle size of from 5 micrometers to 20 micrometers, and/or said dioctahedral clay has a volume weight mean particle size of more than 20 micrometers.
6. A composition according to any preceding claim, whereby said composition comprises (by weight) an amount of clay of no more than 10%.
7. A composition according to any preceding claim, whereby said composition comprises (by weight) from 0.01% to 50% a hydrophobically modified cellulosic based polymer, preferably an ester carboxymethyl cellulose, said hydrophobically modified cellulosic based polymer has a weight average molecular weight of from 50000 to 2000000.
8. A composition according to any preceding claim, whereby said composition comprises a flocculating agent, preferably said flocculating agent comprises a polyethylene oxide.
9. A composition according to any preceding claim, whereby said composition comprises a cyclic amine based polymer.
10. Use of a composition of claims 1-6 and 8-9, to provide softening benefits to fabric.
11. Use of a composition of claim 7, to provide softening benefits and anti-wrinkling benefits to fabric.

Patentansprüche


1. Feste Detergenezusammensetzung, umfassend einen Hektorit-Ton und einen dioktaedrischen Smektit-Ton, worin das Gewichtsverhältnis von dem Hektorit-Ton zu dem dioktaedrischen Smektit-Ton geringer als 1:1 ist, worin der Hektorit-Ton und der dioktaedrische Smektit-Ton in der Zusammensetzung in der Form von Agglomerat-Teilchen vorliegen, und worin weiterhin der Hektorit-Ton und der dioktaedrische Smektit-Ton in dem selben Agglomeratteilchen vorliegen.
2. Zusammensetzung nach Anspruch 1, worin der Hektorit-Ton die allgemeine Formel aufweist




worin y=0 bis 0,4 ist und worin, wenn y≥0 ist, Me^{III} Al, Fe oder B ist, und worin vorzugsweise y=0 ist; Mⁿ⁺ ein monovalentes (n=1) oder divalentes (n=2) Metallion darstellt, vorzugsweise ausgewählt aus Na, K, Mg, Ca und Sr; x eine Zahl von 0,1 bis 0,5, vorzugsweise von 0,2 bis 0,4, besonders bevorzugt von 0,25 bis 0,35 ist; z eine Zahl von 0 bis 2 ist, wobei der Wert von (x+y) in dem Bereich von 0.1 bis 0,5, vorzugsweise von 0,2 bis 0,4, besonders bevorzugt von 0,25 bis 0,35 liegt.

EP 1 319 059 B1

3. Zusammensetzung nach Anspruch 1 oder 2, worin der dioctaédrische Smektit-Ton ein Montmorillonit-Ton ist, wobei der Montmorillonit-Ton die allgemeine Formel



oder




worin x eine Zahl von 0,1 bis 0,5, vorzugsweise von 0,2 bis 0,4 ist, aufweist.

4. Zusammensetzung nach einem der vorangehenden Ansprüche, worin der Hektorit-Ton ein Längenverhältnis von größer als 3:1 aufweist.
5. Zusammensetzung nach einem der vorangehenden Ansprüche, worin der Hektorit-Ton eine volumengewichtsmittlere Teilchengröße von 5 µm bis 20 µm aufweist und/oder der dioctaédrische Ton eine volumengewichtsmittlere Teilchengröße von mehr als 20 µm aufweist.
6. Zusammensetzung nach einem der vorangehenden Ansprüche, worin die Zusammensetzung eine Tonmenge von nicht mehr als 10 Gew.-% umfasst.
7. Zusammensetzung nach einem der vorangehenden Ansprüche, worin die Zusammensetzung 0,01 Gew.-% bis 50 Gew.-% eines hydrophob-modifizierten Cellulose-basierten Polymers, vorzugsweise einer Ester-carboxymethyl-cellulose umfasst, wobei das hydrophob-modifizierte Cellulose-basierte Polymer ein gewichtsmittleres Molekulargewicht von 50.000 bis 2.000.000 aufweist.
8. Zusammensetzung nach einem der vorangehenden Ansprüche, worin die Zusammensetzung ein Ausflockungsmittel umfasst, wobei das Ausflockungsmittel bevorzugt ein Polyethylenoxid umfasst.
9. Zusammensetzung nach einem der vorangehenden Ansprüche, worin die Zusammensetzung ein Polymer auf der Basis eines cyclischen Amins umfasst.
10. Verwendung einer Zusammensetzung gemäß den Ansprüchen 1 bis 6 und 8 bis 9 zur Vermittlung von Textilweichmachervorteilen.
11. Verwendung nach Anspruch 7 zur Vermittlung von Textilweichmachervorteilen und Antifalten-Vorteilen.

Revendications


1. Composition détergente solide comprenant une argile hectorite et une argile smectite dioctaédrique, dans laquelle le rapport en poids de ladite argile hectorite à ladite smectite dioctaédrique est inférieur à 1 : 1, dans laquelle ladite argile hectorite et ladite argile smectite dioctaédrique sont présentes dans ladite composition sous forme de particules d'agglomérat, et dans laquelle en outre ladite argile hectorite et ladite argile smectite dioctaédrique sont présentes dans la même particule d'agglomérat.
2. Composition selon la revendication 1, où ladite argile hectorite a la formule générale




dans laquelle $y = 0$ à $0,4$, et où si $y > 0$, alors Me^{III} est Al, Fe ou B, de préférence $y = 0$; M^{n+} est un ion métallique monovalent ($n = 1$) ou divalent ($n = 2$); de préférence choisi parmi Na, K, Mg, Ca et Sr; x est un nombre de $0,1$ à $0,5$, de préférence de $0,2$ à $0,4$, plus préférentiellement de $0,25$ à $0,35$; z est un nombre de 0 à 2 , de préférence la valeur de $(x + y)$ est dans la plage de $0,1$ à $0,5$, de préférence de $0,2$ à $0,4$; plus préférentiellement de $0,25$ à $0,35$.

EP 1 319 059 B1

3. Composition selon les revendications 1 ou 2, où ladite argile smectite dioctaédrique est une argile montmorillonite, ladite argile montmorillonite ayant la formule générale :



ou



où x est un nombre de 0,1 à 0,5. de préférence de 0,2 à 0,4.

4. Composition selon l'une quelconque des revendications précédentes, où ladite argile hectorite a un rapport d'aspect supérieur à 3 : 1.
5. Composition selon l'une quelconque des revendications précédentes, où ladite argile hectorite a une taille particulière moyenne en masse volumique de 5 micromètres à 20 micromètres, et/ou ladite argile dioctaédrique a une taille particulière moyenne en masse volumique de plus de 20 micromètres.
6. Composition selon l'une quelconque des revendications précédentes, où ladite composition comprend une quantité (en poids) d'argile non supérieure à 10 %.
7. Composition selon l'une quelconque des revendications précédentes, où ladite composition comprend (en poids) de 0,01 % à 50 % d'un polymère à base de cellulose modifiée de manière hydrophobe, de préférence un ester de carboxyméthylcellulose, ledit polymère à base de cellulose modifiée de manière hydrophobe ayant une masse moléculaire moyenne en poids de 50 000 à 2 000 000.
8. Composition selon l'une quelconque des revendications précédentes, où ladite composition comprend un agent de floculation, de préférence ledit agent de floculation comprend un polyoxyde d'éthylène.
9. Composition selon l'une quelconque des revendications précédentes, où ladite composition comprend un polymère à base d'amine cyclique.
10. Utilisation d'une composition des revendications 1 - 6 et 8 - 9, pour procurer des avantages d'adoucissement à un textile.
11. Utilisation d'une composition de la revendication 7, pour procurer des avantages d'adoucissement et des avantages d'anti-froissement à un textile.