

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2014/007846 A1

(43) International Publication Date
9 January 2014 (09.01.2014)

WIPO | PCT

(51) International Patent Classification:
C12Q 1/00 (2006.01) *C12Q 1/66* (2006.01)

(72) Inventors; and

(71) Applicants : **DRISCOLL, Mark B.** [GB/GB]; 3M Centre, Cain Road, Bracknell Berkshire RG12 8HT (GB). **EVANS, Rachel E.** [GB/GB]; 3M Centre, Cain Road, Bracknell Berkshire RG12 8HT (GB). **RAMSAY, Catherine M.** [GB/GB]; 3M Centre, Cain Road, Bracknell Berkshire RG12 8HT (GB). **PERCY, Neil** [GB/US]; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).

(21) International Application Number:
PCT/US2013/027631

(22) International Filing Date:
25 February 2013 (25.02.2013)

(25) Filing Language: English

(74) Agents: **WILLIAMS, Michael G.** et al.; 3M Center, Office of Intellectual Property Counsel, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).

(26) Publication Language: English

(30) Priority Data:
61/668,526 6 July 2012 (06.07.2012) US

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,

(71) Applicant: **3M INNOVATIVE PROPERTIES COMPANY** [US/US]; 3M Center, Post Office Box 33427, Saint Paul, Minnesota 55133-3427 (US).

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR DETECTING ATP IN A LIQUID SAMPLE

(57) **Abstract:** Apparatuses and kits for the detection of ATP in a liquid sample are provided. The apparatuses and kits comprise a liquid reagent composition comprising luciferin and a sampling device having a sampling portion and a handling portion. The sampling portion comprises a fibrous or a foam material and is adapted to acquire and releasably retain a predetermined volume of a liquid sample or a sample of residue from a surface. The sampling device comprises a dry coating or a liquid coating, the coating including an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher. Methods of use of the apparatus or kit are also provided.




Fig. 5



BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,

EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))

APPARATUS AND METHODS FOR DETECTING ATP IN A LIQUID SAMPLE

Cross Reference to Related Applications

[0001] This application claims the benefit of U.S. Provisional Patent Application No. 61/668,526, filed July 6, 2012, which is incorporated herein by reference in its entirety.

Background

[0002] Sampling programs are used to monitor critical raw materials, in-process materials, finished goods, and processing environments in the food and beverage industry. Routine sampling and testing can allow quality assurance personnel to detect undesirable materials, such as microorganisms, at a very early stage and take steps to prevent subsequent contamination of equipment and/or products. A variety of tests can be performed to detect the unwanted materials. Examples of such tests include chemical residue tests (e.g., Adenosine triphosphate (ATP) bioluminescence tests and protein colorimetric tests), culture methods, genetic tests (e.g., PCR), immunodiagnostic tests, and bioluminescent tests.

[0003] Sample-collection devices typically are used to collect surface samples for environmental tests. Commercially-available sample-collection devices include absorbent devices such as sponges, swabs, and the like. In addition, certain sample-collection devices are capable of collecting a predetermined volume of a liquid sample.

[0004] ATP is used routinely to detect a presence or absence of microorganisms in a sample. The chemical energy produced from the breakdown of ATP is converted into light energy. Each molecule of ATP consumed in the reaction produces one photon of light. This light output can be quantified in a luminometer. The presence of ATP in a sample may be a direct indicator of the presence of a microorganism (i.e., the ATP is derived from a microorganism) or the ATP may be an indirect indicator of the presence of a microorganism (i.e., the ATP is derived from vegetative or animal matter and indicates that nutrients that support the growth of microorganisms may be present in the sample). In addition, the presence or absence of ATP in a sample is used routinely to assess the efficacy of cleaning processes in food, beverage, other industrial processed, healthcare (e.g. endoscopes) and for such as cooling and process waters and/or to determine whether biocide treatment has been effective in reducing the level of microorganisms.

Summary

[0005] The present disclosure generally relates to the detection of ATP in a sample using luciferase enzyme. In particular, in one aspect, the disclosure relates to a multi-purpose sampling device that comprises a dry coating comprising a pH-adjusting reagent. The pH-adjusting reagent is capable of causing a pH change when contacted with a liquid reagent

composition comprising luciferin. The pH change can facilitate the achievement of a substantially steady-state light-emitting reaction in a shorter period of time than at a lower pH. Surprisingly, the sampling device can be contacted with a liquid sample and, even though the dry coating may be soluble in the liquid sample, an effective amount of the pH-adjusting reagent is retained on and/or in the sampling device and the effective amount can be transferred to the liquid reagent composition where it effects the aforementioned pH change. In addition, the sampling device obtains a predetermined volume of a liquid sample, thereby permitting the operator to detect and, optionally, quantitate the amount of ATP in the liquid sample.

[0006] In another aspect, the disclosure relates to a multi-purpose sampling device that comprises a liquid coating comprising a pH-adjusting reagent. The pH-adjusting reagent is capable of causing a pH change when contacted with a liquid reagent composition comprising luciferin. The pH change can facilitate the achievement of a substantially steady-state light-emitting reaction in a shorter period of time than at a lower pH. The sampling device can be contacted with a surface that may comprise liquid and/or solid residue. Surprisingly, after contact with the surface, an effective amount of the pH-adjusting reagent is retained on and/or in the sampling device and the effective amount can be transferred (with the residue collected by the sampling device) to the liquid reagent composition where the effective amount of pH-adjusting reagent effects the aforementioned pH change. After transferring the pH-adjusting reagent and the residue to the liquid reagent composition, the operator can detect and, optionally, quantitate the amount of ATP in the residue.

[0007] In one aspect, the present disclosure provides a kit. The kit can comprise a container with an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer, a liquid reagent composition comprising luciferin, and a sampling device having a sampling portion. The liquid reagent composition can be disposed in a closed compartment. The pH of the liquid reagent composition is about 6.8 or lower. The sampling portion of the sampling device is adapted to acquire and releasably retain a sample. The sampling portion comprises a fibrous or a foam material. The sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher.

[0008] In another aspect, the present disclosure provides an apparatus. The apparatus can comprise a container with an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer, a liquid reagent composition comprising luciferin, and a sampling device having a sampling portion. The liquid reagent composition can be disposed in a closed compartment. The pH of the liquid reagent composition is about 6.8 or lower. The sampling portion of the sampling device is adapted to acquire and releasably retain a sample. The sampling portion comprises a fibrous or a foam material. The sampling device comprises a

coating that includes an effective amount of a pH-adjusting reagent that, when contacted with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher.

[0009] In any of the above embodiments of the kits or apparatuses, the sampling portion can be adapted to obtain a predetermined volume of liquid. In any of the above embodiments of the kits or apparatuses, at least a portion of the coating can be disposed on the sampling portion of the sampling device. In any of the above embodiments of the kits or apparatuses, the pH-adjusting reagent can comprise a water-soluble reagent. In any of the above embodiments of the kits or apparatuses, the coating can comprise a dry coating or a liquid coating. In any of the above embodiments of the kits or the apparatuses, the closed compartment can comprise a frangible wall. In any of the above embodiments, the frangible wall can be disposed in the container between the opening and the cuvette portion. In any of the above embodiments of the kits or apparatuses, the pH-adjusting reagent can comprise a buffer component selected from the group consisting of N-[2-hydroxyethyl] piperazine-N'-[2-ethanesulfonic acid] (HEPES), N-[tris(hydroxymethyl)methyl]glycine (TRICINE), and combinations thereof. In any of the above embodiments of the kits or apparatuses, the coating further can comprise an effective amount of a cell extractant. In any of the above embodiments of the kits or methods, the luciferase enzyme can comprise or consist essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme. In any of the above embodiments of the kits or apparatuses, the predetermined volume can be about 0.01 milliliters to about 0.25 milliliters.

[0010] In yet another aspect, the present disclosure provides a method. The method can comprise using a sampling device to obtain a predetermined volume of sample, contacting the predetermined volume of sample with the pH-adjusting reagent and the liquid reagent composition in a container to form a reaction mixture, and using a luminometer to detect light emitted from the reaction mixture. The sampling device can comprise a sampling portion that comprises a fibrous material or a foam material. The sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH of about 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher. The liquid reagent composition comprises a luciferin. The container comprises a cuvette portion adapted to be operationally coupled to the luminometer.

[0011] In yet another aspect, the present disclosure provides a method. The method can comprise using a sampling device with a surface to obtain a sample of residue from a surface; after obtaining the sample of residue, contacting the sample and the pH-adjusting reagent with the liquid reagent composition in a container to form a reaction mixture; and using a

luminometer to detect light emitted from the reaction mixture. The sampling portion can comprise a fibrous material or a foam material. The sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH of about 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher. The container can comprise a cuvette portion adapted to be operationally coupled to the luminometer.

[0012] In any of the above embodiments of the methods, the coating can comprise a dry coating or a liquid coating. In any of the above embodiments of the methods, the liquid reagent composition further can comprise a luciferase enzyme. In any of the above embodiments of the methods, the luciferase enzyme can consist essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme. In any of the above embodiments of the methods, contacting the sampling device comprising the sample with liquid reagent composition can comprise contacting the sampling device with the liquid reagent composition at a temperature within a range of 10° C and 35° C, inclusive. In any of the above embodiments of the methods, after contacting the sampling device with liquid reagent composition, a substantially steady-state amount of light can be emitted from the composition in less than 20 seconds.

[0013] The words “preferred” and “preferably” refer to embodiments of the invention that may afford certain benefits, under certain circumstances. However, other embodiments may also be preferred, under the same or other circumstances. Furthermore, the recitation of one or more preferred embodiments does not imply that other embodiments are not useful, and is not intended to exclude other embodiments from the scope of the invention.

[0014] The terms “comprises” and variations thereof do not have a limiting meaning where these terms appear in the description and claims.

[0015] As used herein, “a,” “an,” “the,” “at least one,” and “one or more” are used interchangeably. Thus, for example, a cell extractant can be interpreted to mean “one or more” cell extractants.

[0016] The term “and/or” means one or all of the listed elements or a combination of any two or more of the listed elements.

[0017] Also herein, the recitations of numerical ranges by endpoints include all numbers subsumed within that range (e.g., 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, 5, etc.).

[0018] The above summary of the present invention is not intended to describe each disclosed embodiment or every implementation of the present invention. The description that follows more particularly exemplifies illustrative embodiments. In several places throughout the application, guidance is provided through lists of examples, which examples can be used in

various combinations. In each instance, the recited list serves only as a representative group and should not be interpreted as an exclusive list.

[0019] Additional details of these and other embodiments are set forth in the accompanying drawings and the description below. Other features, objects and advantages will become apparent from the description and drawings, and from the claims.

Brief Description of Drawings

[0020] FIG. 1 is a side view of one embodiment of a sampling device according to the present disclosure.

[0021] FIG. 2 is a side view of an alternative embodiment of a sampling device according to the present disclosure.

[0022] FIG. 3 is an exploded view, partially in section, of one embodiment of an apparatus according to the present disclosure.

[0023] FIG. 4 is a side view, partially in section, of the assembled apparatus of FIG. 3 showing the sampling device and the container in a first operational position with respect to each other.

[0024] FIG. 5 is a side view, partially in section, of the assembled apparatus of FIG. 3 showing the sampling device and the container in a second operational position with respect to each other.

Detailed Description

[0025] Before any embodiments of the present disclosure are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of "including," "comprising," or "having" and variations thereof herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Unless specified or limited otherwise, the terms "connected" and "coupled" and variations thereof are used broadly and encompass both direct and indirect connections and couplings. Further, "connected" and "coupled" are not restricted to physical or mechanical connections or couplings. It is to be understood that other embodiments may be utilized and structural or logical changes may be made without departing from the scope of the present disclosure. Furthermore, terms such as "front," "rear," "top," "bottom," and the like are only used to describe elements as they relate to one another, but are in no way meant to recite

specific orientations of the apparatus, to indicate or imply necessary or required orientations of the apparatus, or to specify how the invention described herein will be used, mounted, displayed, or positioned in use.

[0026] The present disclosure generally relates to an apparatus and method for detecting ATP from organic residues and/or cells in a sample. According to the present disclosure, the ATP from cells is detected by contacting the sample with a cell extractant to release ATP and detecting the released ATP using an enzymatic reaction that involves the reaction of the released ATP with luciferase enzyme activity in the presence of luciferin and results in the production of measurable light.

[0027] In particular, the present disclosure provides an apparatus and/or a kit with a sampling device that is adapted such that it 1) can acquire and releasably retain a predetermined volume of liquid sample, 2) can use the liquid sample to rehydrate an effective amount of dry, rehydratable pH-adjusting reagent, and 3) can deliver the liquid sample and effective amount of pH-adjusting reagent into a container in order to facilitate a luciferase-catalyzed light-emitting reaction. Advantageously, the present disclosure provides kits and apparatuses that can be used to store aqueous mixtures comprising luciferin for extended periods of time and instantly to adjust the pH of the mixtures in order to reduce the lag time required for a glow-type luciferase enzyme activity to achieve stable light output (e.g., maximum light output) in the presence of ATP and luciferin, particularly at lower temperatures (e.g., temperatures less than or equal to 20° C).

[0028] FIG. 1 shows one embodiment of a sampling device that can be used in an apparatus, kit and/or method according to the present disclosure. The sampling device 100 comprises a handling portion 20 and a sampling portion 30. In the illustrated embodiment, the sampling portion 30 is coupled to the handling portion 20 via an optional stem 15. Typically, the sampling device 100 is shaped and dimensioned to be received in a corresponding container (not shown). The handling portion 20 can be made from a variety of materials (e.g., wood, metal, plastic, glass) using processes known in the art and the handling portion 20 functions as a location at which the sampling device 100 can be grasped and/or manipulated during use. Optionally, the handling portion comprises a handle 24 that is shaped and/or textured to facilitate manual or mechanical gripping of the sampling device 100.

[0029] The sampling portion 30 includes fibrous materials or foam materials capable of obtaining (e.g., via contact, capillary pressure and/or absorption) and retaining a sample from a sample source. In any embodiment, the sampling portion 30 can retain a liquid sample. In any embodiment, the sampling portion may comprise an applicator shaft (e.g., a solid molded plastic applicator shaft) having a tip coated with short fibers (e.g., nylon fibers) that are arranged in a perpendicular fashion such as, for example, the flocked swabs described in U.S.

Patent No. 8,114,027, which is incorporated herein by reference in its entirety. In any embodiment, the sampling portion may comprise an applicator shaft (e.g., a solid molded plastic applicator shaft) having a tip coated with a fibrous material such as, for example, the sea-island bicomponent fibers (e.g., polyester/polyester conjugated fiber yarn or polyester/nylon conjugated fiber yarn) described in U.S. Patent Publication Nos. 2011/0262951 and 2011/0262952, which are incorporated herein by reference in their entirety.

[0030] In any embodiment, the liquid sample may comprise a liquid sample having a predetermined maximum sample volume. The sampling portion 30 can be adapted to obtain and retain a predetermined volume of sample by selecting fibrous or foam materials having the appropriate composition, dimensions, porosity, hydrophilicity and combinations thereof. The maximum sample volume may be selected, for example, based on the desired sensitivity of the test performed with the sample. In any embodiment, the sampling portion may obtain (e.g., via contact capillary pressure and/or absorption) and retain residue (e.g., liquid and/or solid residue) from a surface.

[0031] In general, sampling portion 30 is comprised of a material that achieves the desired sample acquisition characteristics, which may depend upon the type of sample acquired (e.g., some liquid samples may include dissolved or suspended solids that affect the surface tension of the liquid). Material properties that may affect the ability of sampling portion 30 to acquire and retain a sample include, for example, surface energy. For example, the material may be selected to have a particular surface energy in order to draw the sample by capillary force or absorption, for example, into one or more spaces between the plurality of fibers disposed in the sampling portion 30. Other characteristics of the material from which the sampling portion is made may include substantial inertness relative to the sample or a relatively low rate of elution of chemicals or other contaminants that may affect luciferase enzyme activity, e.g., when the sample is released from sampling portion 30.

[0032] Foam articles (e.g., sponges, sponges mounted on a handle) for obtaining samples from environmental surfaces are known in the art. FIG. 2 shows a sampling device 100' comprising a sampling portion 30 that comprises a foam material. The foam material comprises individual cells or void spaces that are capable of obtaining and retaining a liquid sample. Sampling devices of the present disclosure may comprise a sampling portion that includes a foam material. Suitable foam materials for use in a sampling device of the present disclosure include, for example, polyurethane foams, polyethylene foams, and polystyrene foams. In some embodiments, the foams may be treated (e.g., corona-treated or electron beam-treated) in order to make the surface of the polymer more hydrophilic. The foam material can be coupled to a stem 15 and/or a handling portion 20 using materials (e.g., adhesives,

mechanical fasteners, or the like) and processes known in the art. Optionally, the sampling device 100 further can comprise a piercing tip 40.

[0033] Optionally, any sampling device according to the present disclosure further may comprise a coating area (not shown) on which a coating comprising a pH-adjusting reagent according to the present disclosure can be disposed. The coating area may be located, for example, on a portion of the stem and/or the optional piercing tip of the sampling device.

[0034] A sampling device of the present disclosure comprises a dry coating. In any embodiment, the dry coating can be disposed on and/or in (e.g., in the interstitial spaces between fibers of a fibrous material or in the individual cells of a foam material) the sampling portion of the device so that, when the device is dipped into the liquid sample, the coating is contacted with the liquid sample. The dry coating includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition of the present disclosure, changes the pH of the liquid reagent composition having an initial pH of about 6.8 or lower to an adjusted pH of about 6.9 or higher. In any embodiment, the pH-adjusting reagent comprises a water-soluble reagent. In any embodiment, the pH-adjusting reagent comprises a buffer component (e.g., N-[2-hydroxyethyl] piperazine-N'-[2-ethanesulfonic acid] (HEPES), N-[tris(hydroxymethyl)methyl]glycine (TRICINE), and combinations thereof). In some embodiments, the pH-adjusting reagent does not comprise an effective amount of a buffer component comprising phosphate. A buffer component comprising an amount of phosphate effective to change the pH of the liquid reagent composition from an initial pH 6.8 or lower to an adjusted pH of 6.9 or higher may also be sufficient to at least partially inhibit luciferase enzyme activity. In any embodiment, the pH-adjusting reagent further comprises a metallic base (e.g., sodium hydroxide, potassium hydroxide).

[0035] In any embodiment, the coating further can comprise a cell lysis agent that does not substantially inhibit luciferase enzyme activity. Examples of suitable cell lysis agents include, but are not limited to, chlorhexidine digluconate, TRITON X-100, lysozyme, lysostaphin, bacteriophage lysin, a quaternary ammonium compound (e.g., benzalkonium chloride, benzethonium chloride), cetyl trimethylammonium chloride (CTAB), dodecyltrimethylammonium chloride (DTAB), TWEEN 20, TWEEN 80, and a combination of any two or more of the foregoing.

[0036] The amount of pH-adjusting reagent coated onto the sampling device should be enough to change the pH of the liquid reagent composition from an initial (i.e., before contact with the pH-adjusting reagent) pH of 6.8 or lower to an adjusted pH of about 6.9 or higher (i.e., after contact with the pH-adjusting reagent). Preferably, the amount of pH-adjusting reagent coated on the sampling device should be enough to change the pH of the liquid reagent composition from an initial pH of 6.8 or lower to a pH about 7.2 or higher.

[0037] A non-limiting example of a coating solution that can be used to prepare sampling devices of the present disclosure is shown in Table 1. The coating can be applied to the sampling device using any suitable coating method. In any embodiment, the coating initially can be applied to the sampling device as a liquid coating (i.e., the pH-adjusting reagent is dissolved or suspended in a solvent such as water, for example). The solvent is subsequently dried to leave the substantially dry pH-adjusting reagent coated on the sampling device. In any embodiment, the liquid coating is applied by dipping the sampling device (e.g., the sampling portion of the sampling device) into a liquid comprising the pH-adjusting reagent. While immersed in the coating liquid, the sampling device can be agitated to facilitate movement of the coating liquid into the one or more cavity of the sampling portion. After coating the device, the coated portion can be dried (e.g., in a stream of air, a convection oven, or the like) under conditions (e.g., ambient or above-ambient (warm) temperatures) sufficient to evaporate the solvent without substantially degrading the pH-adjusting reagent and/or cell lysis agent.

[0038] In an alternative embodiment of the sampling device of the present disclosure, the coating can be applied to the sampling device as a liquid coating and held in a substantially liquid state (e.g., by packaging the device in a sealed container made from substantially moisture-resistant material) until use. Optionally, the liquid coating can comprise a humectant (e.g., propylene glycol) at a concentration that substantially does not leave a perdurable residue on a surface, as described in International Publication No. WO 2009/140356, which is incorporated herein by reference in its entirety. In some embodiments, the humectant comprises about 1 weight percent to about 50 weight percent of the liquid coating. Preferably, the humectant comprises about 2 weight percent to about 10 weight percent of the liquid coating. Sampling devices having a liquid coating may be used in any kit of the present disclosure.

[0039] Kits and apparatuses of the present disclosure further comprise a container. The container functions as a vessel in which to contact a sample with the liquid reagent composition described herein. The container comprises an opening and is configured (e.g., shaped and dimensioned) to receive at least a portion (e.g., the sampling portion) of the sampling device. FIG. 3 shows an exploded view, partially in section, of one embodiment of an apparatus comprising a container according to the present disclosure. The apparatus 1000 comprises a sampling device 100 comprising a handling portion 20 with a handle 24 and a sampling portion 30 according to any of the embodiments described herein. The apparatus 1000 further comprises a container 200, shown in cross-section in FIG. 3.

[0040] The container comprises at least one wall 50 and an opening 52, the opening configured to receive the sampling device 100. As discussed below, the apparatus 1000 with the opening 52 shown in the illustrated embodiment of FIG. 3 is shaped and dimensioned to

receive the entire sampling device 100. The container further comprises a cuvette portion 54 that is adapted to be operationally coupled to a luminometer. Typically, the cuvette portion 54 is operationally coupled to a luminometer by placing the cuvette portion 54 of the container 200, or the entire container 200, into a complementary-shaped receiving compartment of the luminometer. The cuvette portion 54 is fabricated from optically-transmissible material (e.g., glass or a polymeric material such as polyethylene, polypropylene, polycarbonate, or polystyrene, for example) that permits the transmission there through of light emitted as a product of a reaction catalyzed by luciferase enzyme.

[0041] The container 200 may be fabricated as a unitary article (not shown), for example, using extrusion and/or molding processes known in the art. Alternatively, portions of the container 200, such as the cylindrically-shaped sleeve 56 and the cuvette 55 of the illustrated embodiment of FIG. 3, may be fabricated separately and coupled together using suitable means (e.g., an adhesive, a heat sealing process, a sonic weld, and/or by press-fitting the sleeve 56 and cuvette 55 together). The sleeve 56 may be fabricated via a molding or extrusion process, for example, using a plastic polymer such as polypropylene or polyethylene, for example. The cuvette 55 can be formed in a variety of geometric shapes, such as cubic, cuboid, cylindrical, conical, frusto-conical, other suitable geometric shapes, and combinations thereof. Preferably, the walls of the cuvette 55 are configured to allow the passage of light (e.g., visible light) into and/or out of the cuvette 55. Optionally, the container further may comprise a lamina 60. The lamina 60 can hold the cuvette 55 firmly together with the sleeve 56. The lamina 60 can be made from paper or a plastic film, for example, and may be used as a label.

[0042] Kits and apparatuses of the present disclosure further comprise a liquid reagent composition (liquid reagent composition 70 shown in FIGS. 3-5). The liquid reagent composition comprises luciferin at a concentration (e.g., 0.3-0.4 mg/L luciferin) sufficient to facilitate a light-emitting reaction in the presence of luciferase; preferably, a glow-type luciferase; and a source of ATP. In a method of the present disclosure, the source of ATP can be a sample as disclosed herein or a solution containing a predefined amount or concentration of ATP (i.e., a positive control or an ATP standard). In any embodiment, the liquid reagent composition can comprise an aqueous solution. The liquid reagent composition used in the apparatus or kit of the present disclosure has an initial (i.e., before contact with the pH-adjusting reagent) pH of 6.8 or lower. Preferably, liquid reagent composition has an initial (i.e., before contact with the pH-adjusting reagent) pH of 6.4 or lower.

[0043] A non-limiting example of a liquid composition according to the present disclosure is listed in Table 2 of the Examples.

[0044] In any embodiment of a kit or apparatus according to the present disclosure, the liquid reagent composition optionally may comprise a buffering agent. Suitable buffering

agents have a pKa that is effective to maintain the pH of the liquid reagent composition at a pH of 6.8 or lower, preferably at a pH of 6.4 or lower. N-(2-acetamido)-iminodiacetic acid (ADA) is a nonlimiting example of a suitable buffering agent. The buffering agent should be present in the liquid reagent composition in an amount (e.g., about 16 mM ADA in 425 microliters of liquid reagent composition at pH 6.4-6.8) that is high enough to effectively maintain the pH of the liquid reagent composition, yet low enough so that it does not substantially resist a change in the pH of the liquid reagent composition mediated by the pH-adjusting reagent coated on the sampling portion of the sampling device. In any embodiment, the liquid reagent composition further may comprise a luciferase enzyme. In any embodiment, the luciferase enzyme can consist essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme. The luciferase enzyme can be present in the liquid reagent composition at a concentration of about 9 mg/L, for example. In any embodiment, the liquid reagent composition further can comprise a source of magnesium ions (e.g., magnesium diacetate tetrahydrate). The source of magnesium ions can be present at a concentration (e.g., about 3 mM, for example) that does not substantially interfere with luciferase enzyme activity when the liquid reagent composition is mixed with the liquid sample. In any embodiment, the liquid reagent composition further can comprise a protein (e.g., bovine serum albumin). Without being bound by theory, the protein may stabilize the luciferase enzyme during prolonged storage and/or make the luciferase enzyme less susceptible to protease enzyme activities. At its working concentration, the protein should not substantially interfere with luciferase enzyme activity when the liquid reagent composition is mixed with the liquid sample. The protein may be present in the liquid reagent composition at a concentration of about 0.046 weight percent, for example. In any embodiment, the liquid reagent composition further can comprise a preservative (e.g., 0.046 weight percent sodium azide) at a concentration that does not substantially interfere with luciferase enzyme activity when the liquid reagent composition is mixed with the liquid sample. In any embodiment, the liquid reagent composition further may comprise ethylenediamine tetraacetic acid (EDTA). Without being bound by theory, the EDTA can act as a preservative in the liquid reagent composition and may also function to chelate ions present in the liquid reagent composition and/or the liquid sample.

[0045] In any embodiment of a kit or apparatus according to the present disclosure, the liquid reagent composition can be disposed in a closed compartment. In some embodiments, the closed compartment comprises a frangible wall. In the illustrated embodiment of FIG. 4, the container further comprises a liquid-resistant frangible wall 65 disposed proximate the cuvette 55 that forms a compartment 67. The frangible wall 65 can be made from a water-

resistant material, such as plastic film, metal foil, or a metal-coated plastic film, for example. The frangible wall 65 can be coupled to the cuvette 55 and/or the sleeve 56 via an adhesive, a heat seal, a sonic weld, or other means known in the art to form a liquid-resistant seal to retain the liquid reagent composition 70 in the compartment 67.

[0046] In an alternative embodiment (not shown) of a kit or apparatus according to the present disclosure, the liquid reagent composition may be disposed in a frangible ampoule (e.g., a glass or polymeric ampoule) which is disposed in the container. The liquid reagent composition can be released from the frangible ampoule by squeezing the container with enough force to fracture the ampoule or by urging the sampling device (e.g., the piercing tip of the sampling device) against the ampoule with enough force to fracture the ampoule.

[0047] In yet another embodiment (not shown) of a kit or apparatus according to the present disclosure, the liquid reagent composition may be disposed in a compartment disposed in the sampling device. Nason (U.S. Patent No. 5,266,266, which is incorporated herein by reference in its entirety) discloses a swab device comprising a hollow stem and a liquid-containing closed compartment with an actuatable valve (break-off nib) that releases the liquid into the hollow stem for delivery into tube in which at least a portion of the swab is disposed. Any sampling device of the present disclosure may be modified to include the hollow stem and reagent chamber of Nason. The reagent chamber can contain the liquid reagent composition of the present disclosure and the liquid reagent composition can be transferred into the container of the present disclosure using the technique described by Nason. The liquid reagent composition can be transferred to the container before or after the liquid sample is acquired using the sampling device according to the present disclosure. Other compartments for temporarily storing liquid reagent compositions to be used in a reaction (e.g., a chemical and/or enzymatic reaction) are known in the art and a person of ordinary skill in the art will recognize such compartments can be used to temporarily contain the liquid reagent composition of the present disclosure. Non-limiting examples of such compartments can be found in U.S. Patent No. 7,399,984; U.S. Patent No. 6,548,018; U.S. Patent No. 5,965,453; and U.S. Patent No. 6,524,530, which are all incorporated herein by reference in their entirety.

[0048] The present disclosure provides a kit. The kit may be used, for example, to detect a presence or absence of ATP in a liquid sample according the method described herein. In any embodiment, the kit may comprise instructions disclosing an embodiment of the method disclosed herein.

[0049] Kits of the present disclosure comprise a container according to any of the embodiments disclosed herein. The container comprises an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer. Kits of the present disclosure further comprise a liquid reagent composition comprising luciferin according to any of the

embodiments disclosed herein. The initial pH (i.e., before contact with a pH-adjusting reagent of the present disclosure) of the liquid reagent composition is about pH 6.8 or lower; preferably, about pH 6.4 or lower. Kits of the present disclosure further comprise a sampling device having a sampling portion and a handling portion according to any of the embodiments disclosed herein. The liquid reagent composition is disposed in a closed compartment disposed in the container or the sampling device, as disclosed herein. The sampling portion of the sampling device comprises fibrous materials or foam materials and is configured to obtain (e.g., via capillary pressure or absorption) and retain a predetermined volume of liquid sample from a sample source. The sampling portion of the sampling device comprises a dry coating that includes an effective amount of a pH-adjusting reagent that, when contacted (e.g., mixed) with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher, preferably to about pH 7.2 - 8.0, more preferably to about pH 7.2 - 7.8. In any embodiment, the pH-adjusting reagent comprises a water-soluble reagent.

[0050] Kits and apparatuses of the present disclosure can be used methods of detecting a presence or an absence of ATP in a liquid sample. The presence of ATP in a sample can indicate a possible presence of organic residues and/or microorganisms (e.g., pathogenic microorganisms) in the sample. Moreover, the quantity of ATP in the sample can be an indicator of the relative number of microorganisms in the sample.

[0051] In one method of the present disclosure, a sampling device is used to obtain a liquid sample which is subsequently tested to detect a presence or an absence of ATP in the liquid sample. Because the amount of ATP in a sample can be an indicator of the cleanliness of the sample and/or the presence of microorganisms in the sample, it may be desirable to calculate the absolute or relative quantity of ATP in the sample. Therefore, it is desirable to test a predetermined volume of sample, so that the amount of ATP per unit volume of sample can be determined. The amount of ATP per unit volume of sample can be compared to a predetermined value to determine whether the sample is acceptable for use in a particular application (e.g., food or beverage production), whether a cleaning process has been effective in removing organic residues, and/or whether a biocide treatment has been effective in reducing the number of microorganisms.

[0052] Thus, a first method of the present disclosure comprises using a sampling device to obtain a predetermined volume of liquid sample, contacting the predetermined volume of sample with a liquid reagent composition in a container to form a reaction mixture, and using a luminometer to detect light emitted from the reaction mixture. The predetermined volume of liquid sample can be about 10 microliters to about 250 microliters. In some embodiments, the predetermined volume of liquid sample can be about 100 microliters to about 200 microliters.

In some embodiments, the predetermined volume of liquid sample can be about 125 microliters to about 175 microliters.

[0053] According to the first method of the present disclosure, the sample comprises a liquid. The liquid may comprise water. The sample further may comprise solids that are dissolved, dispersed, and/or suspended in the liquid. Nonlimiting examples of suitable samples include clean-in-place (CIP) rinse-water samples, process and cooling water samples, and endoscope rinse water samples.

[0054] The sampling device used in the first method of the present disclosure can be any sampling device disclosed herein. The sampling device comprises a sampling portion and a handling portion. The sampling portion is adapted to acquire and releasably retain a predetermined volume of liquid sample. The sampling portion includes fibrous materials or foam materials capable of obtaining (e.g., via capillary pressure or absorption) and retaining a liquid sample from a sample source. The sampling portion retains a predetermined maximum sample volume. In any embodiment of the first method, the sampling portion of the device comprises a dry coating that includes an effective amount of a pH-adjusting reagent that, when contacted (e.g., mixed) with a liquid reagent composition having an initial pH of 6.8 or lower (i.e., before contacting the pH-adjusting reagent), adjusts the pH of the liquid reagent composition to 6.9 or higher. In some embodiments of the first method, the sampling portion of the device comprises a moist (i.e., liquid) coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having an initial pH of 6.8 or lower, adjusts the pH of the liquid reagent composition to 6.9 or higher.

[0055] The present disclosure further provides a second method of detecting ATP in a sample. The second method is used to detect ATP that is present in residue on a surface (e.g., liquid and/or solid residue found on a solid surface. The second method is particularly useful, for example, to detect the efficacy of a process that is used to clean the surface. In many environments (e.g., food-processing facilities, hospitals), a cleaning process should substantially reduce or remove detectable ATP from the surface that is to be tested. Suitable samples for the second method of the present disclosure include, but are not limited to, processing equipment (e.g., food-handling surfaces, tubes, drains, conveyors, storage containers), environmental surfaces (e.g., sinks, countertops, drawers, floors, walls, ceilings, doors, bedrails, linens, computer touch screens, keyboards, monitors), and medical equipment or devices (e.g., endoscopes, retractors, trocars, scalpels, trays). According to the second method of the present disclosure, the sample may comprise liquid and/or solid residue present on a surface.

[0056] The sampling device used in the second method of the present disclosure can be any sampling device disclosed herein. The sampling device comprises a sampling portion and a

handling portion. The sampling portion is adapted to acquire a sample of surface residue. The sampling portion includes fibrous materials or foam materials capable of obtaining and retaining the surface residue. In any embodiment of the second method, the sampling portion of the device comprises a dry coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having an initial pH of 6.8 or lower, adjusts the pH of the liquid reagent composition to 6.9 or higher. In some embodiments of the second method, the sampling portion of the device comprises a moist (i.e., liquid) coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having an initial pH of 6.8 or lower, adjusts the pH of the liquid reagent composition to 6.9 or higher.

[0057] The liquid reagent composition used in any embodiment of the first or second method of the present disclosure comprises a luciferin (e.g., firefly luciferin). Luciferin is a compound that undergoes oxidation by luciferase enzyme activity to produce oxyluciferin and light. Luciferin compounds can be unstable when stored for extended periods of time in liquid solutions at a pH above 6.8. Thus, the liquid reagent composition used in the method of the present disclosure has an initial pH of 6.8 or lower. Preferably, liquid reagent composition has an initial pH of 6.4 or lower.

[0058] In any embodiment, the liquid reagent composition may further comprise a luciferase enzyme. In a preferred embodiment, the luciferase enzyme comprises a recombinant luciferase enzyme having luciferase activity that is less sensitive than a corresponding non-recombinant luciferase enzyme to variations in temperature, ionic detergents, and reducing agents. In some embodiments, the luciferase enzyme consists essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme.

[0059] In any embodiment, the liquid reagent composition optionally may comprise a buffering agent. The buffering agent can be used to maintain the liquid reagent composition at an initial pH (e.g., ≤ 6.8) that is suitable to store a liquid solution containing luciferin. N-(2-acetamido)-iminodiacetic acid (ADA) is a nonlimiting example of a suitable buffering agent. The buffering agent should be present in the liquid reagent composition in an amount (e.g., about 16 mM ADA in 425 microliters of liquid reagent composition at pH 6.4-6.8) that is high enough to effectively maintain the pH of the liquid reagent composition, yet low enough so that it does not substantially resist a change in the pH of the liquid reagent composition mediated by the pH-adjusting reagent coated on the sampling portion of the sampling device.

[0060] The container used in any embodiment of the first or second method of the present disclosure comprises a cuvette portion. The cuvette portion permits the transmission there through of light emitted as a product of the reaction catalyzed by luciferase enzyme. The

cuvette portion is adapted (e.g., shaped and dimensioned) to be operationally coupled to the luminometer. In some embodiments, using a luminometer to detect light emitted from the reaction mixture comprises detecting a presence or an absence of ATP in the liquid sample. In some embodiments, using a luminometer to detect light emitted from the reaction mixture comprises measuring a quantity (e.g., a relative quantity or an absolute quantity) of ATP present in the liquid sample.

[0061] In any embodiment of the first or second method of the present disclosure, contacting the predetermined volume of sample with a liquid reagent composition in a container to form a reaction mixture comprises bringing the sampling portion of the sampling device into contact with the liquid reagent composition in a container. The contact may be achieved, for example, by immersing at least a part; preferably, the entire sampling portion; of the sampling device in the liquid reagent composition. The contact forms a reaction mixture (e.g., by diffusion of at least part of the liquid sample into the liquid reagent composition). If it is not already present in the liquid reagent composition, luciferase can be added to the reaction mixture. Thus, if ATP is present in the liquid sample, the ATP can facilitate a light-emitting reaction catalyzed by luciferase enzyme. The light-emitting reaction can be detected in the aforementioned luminometer.

[0062] FIGS. 4 and 5 illustrate one embodiment of a process of contacting a predetermined volume of sample with a liquid reagent composition in a container to form a reaction mixture. After obtaining the sample using the sampling device 100, the sampling device is inserted into the container 200. FIG. 4 shows the sampling device 100 with the stem 15 and sampling portion 30 in the container. In this configuration, the sampling device 100 and container 200 are disposed in a first operational position with respect to one another and the apparatus 1000 is ready to bring the sample into contact with the liquid reagent composition 70 located in the compartment 67. Using manual or mechanical pressure against the handle 24 of the sampling device 100, the sampling portion 30 is urged toward the compartment 67 until it ruptures the frangible wall 65 and brings the liquid sample (not shown) associated with the sampling portion 30 into contact with the liquid reagent composition 70, as shown in FIG. 5. In the illustrated embodiment of FIG. 5, the sampling device 100 and container 200 are disposed in a second operational position with respect to each other. In this embodiment, the sampling device 100 is fully-inserted into the container 200 and the sampling portion 30 of the sampling device is contacting the liquid reagent composition 70.

[0063] In any embodiment of the first or second method according to the present disclosure, contacting the predetermined volume of sample with a liquid reagent composition in a container to form a reaction mixture further can comprise the step of agitating the sample and the liquid reagent composition in the container. This may be done manually or mechanically,

for example, by rapidly shaking the container in a swirling motion, a pendulum-like motion, or by contacting the container with a machine that vibrates the container.

[0064] In any embodiment of the first or second method of the present disclosure, the cuvette portion of the container is operationally coupled to the luminometer in order to detect the light emission resulting from luciferase enzyme activity. Commercially-available luminometers are suitable for use in any embodiment of the method of the present disclosure. A non-limiting example of a suitable luminometer is the 3M™ Clean-Trace™ NG Luminometer commercially available from 3M Company, St. Paul, MN. Typically, the cuvette is operationally coupled by placing a portion (e.g., the cuvette portion) of the container or the entire container into a corresponding receiving compartment of the luminometer. The cuvette portion may be operationally coupled to the luminometer before or after forming the reaction mixture. Typically, the cuvette portion is operationally coupled to the luminometer after the reaction mix is formed. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 5 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 10 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 15 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 20 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 30 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 45 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 60 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 90 seconds after forming the reaction mixture. In some embodiments the cuvette portion is operationally coupled to the luminometer up to 2 minutes after forming the reaction mixture. Preferably, the cuvette is operationally coupled to the luminometer within about 5 to 10 seconds after forming the reaction mixture.

[0065] In any embodiment of the first or second method of the present disclosure, after operationally coupling the cuvette portion to the luminometer, the light-emission is monitored by the luminometer. After the reaction mixture is formed, it may take a period of time for the reaction to reach a relatively stable quantity of light emission.

[0066] In any embodiment of the first or second method of the present disclosure, the liquid reagent composition comprises luciferin at a concentration (e.g., about 0.3-0.4 mg/L luciferin) sufficient to facilitate a light-emitting reaction in the presence of luciferase and a source of ATP. In the method of the present disclosure, the source of ATP can be a liquid sample as

disclosed herein or a solution containing a predefined amount or concentration of ATP (i.e., a positive control or an ATP standard). In any embodiment, the liquid reagent composition can comprise an aqueous solution. The liquid reagent composition used in the apparatus or kit of the present disclosure has an initial pH of 6.8 or lower. Preferably, liquid reagent composition has an initial pH of 6.4 or lower.

[0067] In any embodiment of the first or second method of the present disclosure, the liquid reagent composition optionally may comprise a buffer component. Suitable buffer components have a pKa that is effective to maintain the initial pH of the liquid reagent composition at a pH of 6.8 or lower, preferably at a pH of 6.4 or lower. N-(2-acetamido)-iminodiacetic acid (ADA) is a nonlimiting example of a suitable buffering agent. The buffer component should be present in the liquid reagent composition in an amount (e.g., about 16 mM ADA in 425 microliters of liquid reagent composition at pH 6.4-6.8) that is high enough to effectively maintain the pH of the liquid reagent composition, yet low enough so that it does not substantially resist a change in the pH of the liquid reagent composition mediated by the pH-adjusting reagent coated on the sampling portion of the sampling device. In any embodiment of the first or second method, the liquid reagent composition further may comprise a luciferase enzyme. In any embodiment of the first or second method, the luciferase enzyme can consist essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme. The luciferase enzyme can be present in the liquid reagent composition at a concentration of about 9 mg/L, for example. In any embodiment of the first or second method, the liquid reagent composition further can comprise a source of magnesium ions (e.g., magnesium diacetate tetrahydrate). The source of magnesium ions can be present at a concentration (e.g., about 3 mM, for example) that does not substantially interfere with luciferase enzyme activity when the liquid reagent composition is mixed with the liquid sample. In any embodiment of the first or second method, the liquid reagent composition further can comprise a protein (e.g., bovine serum albumin). The protein may be present in the liquid reagent composition at a concentration of about 0.046 weight percent, for example. In any embodiment of the first or second method, the liquid reagent composition further can comprise a preservative (e.g., 0.046 weight percent sodium azide) at a concentration that does not substantially interfere with luciferase enzyme activity when the liquid reagent composition is mixed with the liquid sample.

[0068] In any embodiment of the first or second method of the present disclosure, contacting the sampling device comprising the liquid sample with liquid reagent composition comprises contacting the sampling device with the liquid reagent composition at a particular temperature (e.g. ambient temperature). In general, when the contact occurs at lower temperatures, a longer

period of time is required for the light-emitting reaction to reach a relatively stable amount of light emission. Conversely, when the contact occurs at higher temperatures, a shorter period of time is required for the light-emitting reaction to reach a relatively stable amount of light emission. In any embodiment of the method of the present disclosure, contacting the sampling device comprising the liquid sample with liquid reagent composition comprises contacting the liquid sample with the liquid reagent composition at temperature within a range of 10° C and 35° C, inclusive. Preferably, contacting the sampling device comprising the liquid sample with liquid reagent composition comprises contacting the liquid sample with the liquid reagent composition at temperature within a range of 15° C and 30° C, inclusive.

[0069] In any embodiment of the first or second method, after contacting the sampling device with the liquid reagent composition, a substantially steady-state amount of light is emitted from the composition after a period of time. As discussed above, the period of time may be affected by the temperature at which the contact occurs. In any embodiment of the first or second method of the present disclosure, a substantially steady-state amount of light is emitted from the composition in less than 25 seconds (e.g., when contact occurs at a temperature of about 10° C to about 20° C). In any embodiment of the first or second method of the present disclosure, a substantially steady-state amount of light is emitted from the composition in about 22 seconds or less (e.g., when contact occurs at a temperature of about 10° C to about 20° C). In some embodiments, a substantially steady-state amount of light is emitted from the composition in less than 20 seconds (e.g., when contact occurs at a temperature of about 14° C to about 20° C). In some embodiments, a substantially steady-state amount of light is emitted from the composition in about 10 seconds or less (e.g., when contact occurs at a temperature of about 20° C).

[0070] The methods of the present invention substantially reduces the amount of time necessary for a luciferase enzyme, in contact with a sample comprising ATP and a liquid reagent composition according to the present disclosure, to catalyze a light-emitting reaction that is substantially steady state.

Embodiments

[0071] Embodiment A is a kit, comprising:

 a container with an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer;

 a liquid reagent composition comprising luciferin, wherein the liquid reagent composition is disposed in a closed compartment, wherein the pH of the liquid reagent composition is about 6.8 or lower; and

 a sampling device having a sampling portion;

wherein the sampling portion is adapted to acquire and releasably retain a sample;

wherein the sampling portion comprises a fibrous material or a foam material;

wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher.

[0072] Embodiment B is an apparatus, comprising:

a container with an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer;

a liquid reagent composition comprising luciferin, wherein the liquid reagent composition is disposed in a closed compartment, wherein the pH of the liquid reagent composition is about 6.8 or lower; and

a sampling device having a sampling portion;

wherein the sampling portion is adapted to acquire and releasably retain a sample;

wherein the sampling portion comprises a fibrous material or a foam material;

wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher.

[0073] Embodiment C is the kit of Embodiment A or the apparatus of Embodiment B, wherein the sampling portion is adapted to obtain a predetermined volume of a liquid.

[0074] Embodiment D is the kit or the apparatus of any one of the preceding Embodiments, wherein at least a portion of the coating is disposed on the sampling portion of the sampling device.

[0075] Embodiment E is the kit or the apparatus of any one of the preceding Embodiments, wherein the pH-adjusting reagent comprises a water-soluble reagent.

[0076] Embodiment F is the kit or the apparatus of any one of the preceding Embodiments, wherein the coating comprises a dry coating.

[0077] Embodiment G is the kit or the apparatus of any one of Embodiments A through E, wherein the coating comprises a liquid coating.

[0078] Embodiment H is the kit or the apparatus of Embodiment G, wherein the liquid coating comprises a humectant.

[0079] Embodiment I is the kit or the apparatus of any one of the preceding Embodiments, wherein the closed compartment comprises a frangible wall.

[0080] Embodiment J is the kit or the apparatus of Embodiment I, wherein the frangible wall is disposed in the container between the opening and the cuvette portion.

[0081] Embodiment K is the kit or the apparatus of any one of Embodiments A through H, wherein the sampling device comprises the closed compartment, wherein the sampling device further comprises a structure that selectively releases the fluid composition from the container.

[0082] Embodiment L is the kit or the apparatus of any one of the preceding Embodiments, wherein the pH-adjusting reagent comprises a buffer component selected from the group consisting of N-[2-hydroxyethyl] piperazine-N'-[2-ethanesulfonic acid] (HEPES), N-[tris(hydroxymethyl)methyl]glycine (TRICINE), and combinations thereof.

[0083] Embodiment M is the kit or the apparatus of any one of the preceding Embodiments, wherein the coating further comprises an effective amount of a cell extractant.

[0084] Embodiment N is the kit or the apparatus of any one of the preceding Embodiments, wherein the luciferase enzyme comprises a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme.

[0085] Embodiment O is the kit or the apparatus of any one of Embodiments A through M, wherein the luciferase enzyme consists essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme.

[0086] Embodiment P is the kit or the apparatus of any one of the preceding Embodiments, wherein the coating does not comprise an effective amount of a buffer component comprising phosphate.

[0087] Embodiment Q is the kit or the apparatus of any one of the preceding Embodiments, wherein the predetermined volume is about 0.01 milliliters to about 0.25 milliliters.

[0088] Embodiment R is a method, comprising:

using a sampling device to obtain a predetermined volume of liquid sample;

wherein the sampling device comprises a sampling portion that comprises a fibrous material or a foam material;

wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH of about 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher;

wherein the liquid reagent composition comprises a luciferin;

contacting the predetermined volume of sample with the pH-adjusting reagent and the liquid reagent composition in a container to form a reaction mixture; and

using a luminometer to detect light emitted from the reaction mixture;

wherein the container comprises a cuvette portion adapted to be operationally coupled to the luminometer.

[0089] Embodiment S is a method, comprising:

using a sampling device to obtain a sample of residue from a surface;

wherein the sampling device comprises a sampling portion that comprises a fibrous material or a foam material;

wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH of about 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher;

wherein the liquid reagent composition comprises a luciferin;

after obtaining the sample of residue, contacting the sample and the pH-adjusting reagent with the liquid reagent composition in a container to form a reaction mixture; and

using a luminometer to detect light emitted from the reaction mixture;

wherein the container comprises a cuvette portion adapted to be operationally coupled to the luminometer.

[0090] Embodiment T is the method of Embodiment R or Embodiment S, wherein the coating comprises a dry coating.

[0091] Embodiment U is the method of Embodiment R or Embodiment S, wherein the coating comprises a liquid coating.

[0092] Embodiment V is the method of any one of Embodiments Q through T, further comprising the step of agitating the sampling portion and the liquid reagent composition in the container.

[0093] Embodiment W is the method of any one of Embodiments R through V, wherein the liquid reagent composition further comprises a luciferase enzyme.

[0094] Embodiment X is the method of Embodiment W, wherein the luciferase enzyme consists essentially of a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme.

[0095] Embodiment Y is the method of any one of Embodiments R through X, wherein contacting the sampling device comprising the sample with liquid reagent composition comprises contacting the sampling device with the liquid reagent composition at a temperature within a range of 10° C and 35° C, inclusive.

[0096] Embodiment Z is the method of any one of Embodiments R through Y wherein, after contacting the sampling device with liquid reagent composition, a substantially steady-state amount of light is emitted from the composition in less than 20 seconds.

[0097] Objects and advantages of this invention are further illustrated by the following examples, but the particular materials and amounts thereof recited in these examples, as well as other conditions and details, should not be construed to unduly limit this invention.

Examples

[0098] **Coating Formulation 1:**

[0099] Coating Formulation 1 was prepared as a solution from the components listed in Table 1 and was used to coat the fibrous sampling portions of the sampling devices in Examples 1-5 and 8-12. The pH of Coating Formulation 1 was about 8.5.

[00100] Table 1. Coating Formulation 1

Component	Weight Percentage of Component in the Formulation	Source
Water (from a Milli Q water purification system)	96.33 %	EMD Millipore Corp. (Billerica, MA)
Chlorhexidine digluconate (20% in water) [CAS No. 18472-51-0]	0.32 %	Sigma-Aldrich Co. (St. Louis, MO)
Triton X100 [CAS No. 9002-93-1]	0.19 %	Sigma-Aldrich Co. (St. Louis, MO)
Tricine [CAS No. 5704-04-1]	1.72 %	Sigma-Aldrich Co. (St. Louis, MO)
Sodium Hydroxide (4N)	1.44 %	VWR Corp. (Radnor, PA)

[00101] **Liquid Reagent Composition:**

[00102] The liquid reagent composition described herein comprises luciferin and a luciferase enzyme. The liquid reagent composition was prepared as a solution using the components listed in Table 2. The pH of the formulation was about 6.4. The total volume of liquid reagent composition contained in the sealed cuvette portion of each container of the present disclosure was about 425 microliters.

[00103] Table 2. Liquid reagent composition

Component	Weight Percentage of Component in the Formulation	Source
Water (from a Milli Q water purification system)	77.6099 %	EMD Millipore Corp. (Billerica, MA)
ADA Free Acid [CAS No. 26239-55-4]	0.0283 %	Sigma-Aldrich Co. (St. Louis, MO)
ADA Disodium Salt [CAS No. 41689-31-0]	0.3081 %	Sigma-Aldrich Co. (St. Louis, MO)
EDTA Disodium Salt Dihydrate [CAS No. 6381-92-6]	0.0646 %	Sigma-Aldrich Co. (St. Louis, MO)
Magnesium Acetate Tetrahydrate [CAS No. 16674-78-5]	0.1862 %	Sigma-Aldrich Co. (St. Louis, MO)
Sodium Azide [CAS No. 26628-22-8]	0.0457 %	Sigma-Aldrich Co. (St. Louis, MO)
D-Sorbitol [CAS No. 50-70-4]	21.7106 %	Molekula LTD (Gillingham, UK)
Bovine Serum Albumin [CAS No. 9048-46-8]	0.0457 %	Sigma-Aldrich Co. (St. Louis, MO)
UltraGlo Luciferase (Type E140X)	0.0009% (9 mg/L)	Promega Corp. (Madison, WI)
Luciferin (Type XE160X)	0.00003-0.00004% (0.3-0.4 mg/L)	Promega Corp. (Madison, WI)

[00104] Coating Formulation 2:

[00105] Coating Formulation 2 was prepared as a solution from the components listed in Table 3 and was used to coat the fibrous sampling portions of the sampling devices in Comparative Examples 1-5 and 8-12. The pH of Coating Formulation 2 was about 7.2.

[00106] Table 3. Coating Formulation 2

Component	Weight Percentage of Component in the Formulation	Source
Water (from a Milli Q water purification system)	99.47 %	EMD Millipore Corp. (Billerica, MA)
Chlorhexidine digluconate (20% in water) [CAS No. 18472-51-0]	0.32 %	Sigma-Aldrich Co. (St. Louis, MO)
Triton X100 [CAS No. 9002-93-1]	0.21 %	Sigma-Aldrich Co. (St. Louis, MO)

[00107] Preparation of ATP Test Apparatus 1 :

[00108] An apparatus similar to the design described in FIG. 4 was used. The apparatus was prepared by combining components (sampling device component and container component) from two different commercially available products.

[00109] The container component of the apparatus was obtained from a 3M Clean-TraceTM Water Plus-Total ATP Test Device (product number AQT200, 3M Company, St. Paul, MN). The sampling device component was removed from the device and discarded, while the container component was saved. The cuvette portion of the container contained the liquid reagent composition described in Table 2.

[00110] The sampling device with a fibrous sampling portion was obtained from a 3M Clean-TraceTM Surface ATP Test Device (product number UXL-100, 3M Company, St. Paul, MN). The fibrous sampling portion was prepared from polyethylene terephthalate fibers. The sampling device component was removed from the test device and the rest of the test device (i.e. the container component) was discarded. The sampling device was then coated using Coating Formulation 1 (Table 1). The sampling device was coated by holding the handling portion of the sampling device and dipping the opposite end of the device into a vessel containing Coating Formulation 1 to a point where the entire fibrous sampling portion was immersed in the coating formulation for a period of 15 seconds. The sampling device was withdrawn from the coating formulation. Excess coating formulation was removed from the fibrous sampling portion by gently tapping the stem portion of the sampling device against the side of the container. The sampling device retained about 170 microliters of the formulation. The coated sampling device was immediately combined with the container portion of the 3M Clean-TraceTM Water Plus-Total ATP Test Device so that the sampling device and container were assembled in the first operational position with respect to each other (FIG. 4).

[00111] Preparation of ATP Test Apparatus 2 :

[00112] The ATP Test Apparatus 2 was prepared in the same manner as ATP Test Apparatus 1 except for the procedure used to coat the sampling device. For ATP Test Apparatus 2, the sampling device was coated by holding the handling portion of the sampling device and dipping the opposite end of the device into a vessel containing Coating Formulation 1 to a point where the entire fibrous sampling portion was immersed in the coating formulation for a period of 15 seconds. The sampling device was withdrawn from the coating formulation. Excess coating formulation was removed from the fibrous sampling portion by gently tapping the stem portion of the sampling device against the side of the container. The sampling device was then placed in a laminar flow cabinet and air dried at 20° C for a period of at least 3 hours. After the drying step, the coated sampling device was combined with the container portion of the 3M Clean-Trace™ Water Plus-Total ATP Test Device so that the sampling device and container were assembled in the first operational position with respect to each other (FIG. 4).

[00113] Example 1

[00114] The ATP Test Apparatus 1 described above was used. The sampling device was removed from the ATP test apparatus and 10 microliters of a 1×10^{-7} M aqueous solution of adenosine triphosphate (ATP) was added to the midsection of the fibrous sampling portion using a micropipette. The sampling device was reinserted into the container. The handle of the sampling device was pressed in order to move the sampling device from the first operational position to the second operational position. The movement of the sampling device in the container caused the frangible seal to be broken and the fibrous sampling portion to be positioned in direct contact with the liquid reagent composition. The container was held in the vertical position and shaken rapidly from side to side (pendulum motion) for about 5 seconds. After shaking the container, the cuvette portion of the apparatus was immediately inserted into a 3M Clean-Trace™ NG Luminometer (commercially available from 3M Company, St. Paul, MN) and measurements were recorded in relative light units (RLU). The RLU measurements were taken approximately every 10 seconds over a 70 second time period. This was accomplished by initiating a new reading for the luminometer immediately after the previous reading. Because the instrument takes approximately 10 seconds to obtain and present each new reading, this resulted in RLU measurements taken about every 10 seconds. All testing was conducted in an environmental chamber at 10° C. All materials and equipment were equilibrated in the chamber prior to testing. A total of five replicate samples were tested and the results are presented in Table 4.

[00115] Movement of the sampling device from the first operational position to the second operational position resulted in the pH of the liquid reagent composition in the cuvette increasing from a pH of approximately 6.4 to a pH of approximately 7.2 to 7.6.

[00116] Comparative Example 1

[00117] The same procedure was used as in Example 1 with the exception that the sampling device was coated with Coating Formulation 2 instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 5.

[00118] Table 4. Sampling Device of Example 1

Time (seconds)	RLU Measurement at 10°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	8,378	11,204	8,818	7,394	9,054
20	8,899	12,192	9,727	8,881	9,771
30	9,044	12,350	9,877	9,274	9,882
40	8,996	12,386	9,891	9,365	9,893
50	8,963	12,304	9,785	9,394	9,838
60	8,950	12,250	9,752	9,348	9,830
70	8,904	12,200	9,662	9,344	9,788

[00119] Table 5. Sampling Device of Comparative Example 1

Time (seconds)	RLU Measurement at 10°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	6,372	4,568	5,153	5,470	3,511
20	12,290	8,813	9,815	8,934	8,093
30	14,360	11,809	12,803	11,182	10,876
40	15,745	13,466	14,853	12,358	12,908
50	16,312	14,435	16,454	13,409	13,999
60	16,672	15,025	16,236	13,936	14,647
70	16,748	15,357	16,020	14,250	15,114

[00120] Example 2

[00121] The same procedure as described in Example 1 was followed with the exception that the tests were conducted at 15°C. A total of five replicate samples were tested and the results are presented in Table 6.

[00122] Comparative Example 2

[00123] The same procedure was used as in Example 2 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU

measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 7.

[00124] Table 6. Sampling Device of Example 2

Time (seconds)	RLU Measurement at 15°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	9,629	12,535	11,779	11,755	14,367
20	10,383	12,866	12,242	12,444	15,399
30	10,487	12,827	12,237	12,531	15,488
40	10,466	12,746	12,208	12,498	15,499
50	10,459	12,728	12,232	12,555	15,413
60	10,411	12,630	12,156	12,533	15,340
70	10,392	12,505	12,124	12,483	15,343

[00125] Table 7. Sampling Device of Comparative Example 2

Time (seconds)	RLU Measurement at 15°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	7,407	13,021	10,849	12,489	13,096
20	13,037	19,286	15,282	18,494	18,839
30	16,492	22,020	18,163	21,665	20,809
40	18,239	23,348	19,247	23,395	21,738
50	19,091	24,235	19,820	24,344	22,089
60	19,350	24,564	20,024	24,590	22,196
70	19,561	24,823	20,122	24,615	22,179

[00126] Example 3

[00127] The same procedure as described in Example 1 was followed with the exception that the tests were conducted at 20°C. A total of five replicate samples were tested and the results are presented in Table 8.

[00128] Comparative Example 3

[00129] The same procedure was used as in Example 3 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 9.

[00130] Table 8. Sampling Device of Example 3

Time (seconds)	RLU Measurement at 20°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	14,752	13,300	14,890	14,485	16,509
20	14,822	13,357	14,884	14,514	16,505
30	14,712	13,362	14,826	14,462	16,380
40	14,664	13,239	14,818	14,357	16,283
50	14,568	13,182	14,712	14,222	16,157
60	14,485	13,076	14,638	14,130	16,027
70	14,455	13,037	14,571	14,026	16,021

[00131] Table 9. Sampling Device of Comparative Example 3

Time (seconds)	RLU Measurement at 20°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	11,225	16,660	19,057	20,198	15,015
20	15,786	21,247	27,159	24,820	18,001
30	17,533	23,152	29,535	26,544	18,717
40	18,175	23,570	30,294	26,975	18,702
50	18,304	23,378	30,529	26,922	18,669
60	18,240	23,078	30,441	26,813	18,552
70	18,075	22,844	30,347	26,685	18,464

[00132] Example 4

[00133] The same procedure as described in Example 1 was followed with the exception that the tests were conducted at 25°C. A total of five replicate samples were tested and the results are presented in Table 10.

[00134] Comparative Example 4

[00135] The same procedure was used as in Example 4 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 11.

[00136] Table 10. Sampling Device of Example 4

Time (seconds)	RLU Measurement at 25°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	12,725	19,302	16,148	20,779	18,069
20	12,675	19,544	16,122	20,747	17,974
30	12,558	19,483	16,084	20,601	17,826
40	12,485	19,429	16,022	20,425	17,710
50	12,448	19,419	15,974	20,227	17,594
60	12,344	19,306	15,891	20,136	17,455
70	12,298	19,166	15,796	19,994	17,392

[00137] Table 11. Sampling Device of Comparative Example 4

Time (seconds)	RLU Measurement at 25°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	24,357	20,166	21,459	20,427	20,324
20	30,040	24,776	28,527	25,149	23,024
30	31,347	25,415	30,221	25,961	23,405
40	31,356	26,013	30,668	26,054	23,252
50	30,878	25,899	30,920	25,894	23,122
60	30,619	25,447	30,520	25,703	22,906
70	30,221	25,265	30,340	25,511	22,628

[00138] Example 5

[00139] The same procedure as described in Example 1 was followed with the exception that the tests were conducted at 30°C. A total of five replicate samples were tested and the results are presented in Table 12.

[00140] Comparative Example 5

[00141] The same procedure was used as in Example 5 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 13.

[00142] Table 12. Sampling Device of Example 5

Time (seconds)	RLU Measurement at 30°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	16,634	16,453	17,311	11,700	15,280
20	16,594	16,359	17,292	11,610	15,250
30	16,459	16,230	17,281	11,563	15,204
40	16,355	16,134	17,166	11,531	15,103
50	16,267	15,983	17,139	11,438	14,996
60	16,131	15,918	17,003	11,436	14,928
70	16,009	15,793	16,871	11,386	14,813

[00143] Table 13. Sampling Device of Comparative Example 5

Time (seconds)	RLU Measurement at 30°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	24,231	25,726	22,401	19,166	25,295
20	27,766	28,186	26,480	19,039	27,983
30	28,301	28,536	26,703	18,855	27,961
40	28,182	28,429	26,562	18,699	27,672
50	27,935	28,185	26,269	18,510	27,502
60	27,699	27,977	26,002	18,349	27,106
70	27,389	27,726	25,749	18,176	27,000

[00144] Example 6

[00145] For the test samples of Examples 1-5 and the corresponding Comparative Examples 1-5, the percent increase in the RLU measurement between the first time point (10 seconds) and the second time point (20 seconds) was calculated using the following equation:

$$\% \text{ Increase in RLU} = \{[(\text{RLU at 20 sec}) - (\text{RLU at 10 sec})] / (\text{RLU at 10 sec})\} \times 100$$

[00146] The mean percent increase (n=5) in the RLU measurement is reported in Table 14.

[00147] Table 14.

Example Number	Mean Percent Increase in the RLU Measurement (n=5)	Standard Deviation
Example 1	10.7	5.5
Comparative Example 1	93.8	21.3

Example 2	5.5	2.2
Comparative Example 2	51.4	14.1
Example 3	0.2	0.2
Comparative Example 3	31.2	10.4
Example 4	-0.02	0.02
Comparative Example 4	23.0	7.1
Example 5	-0.4	0.3
Comparative Example 5	10.7	7.1

[00148] Example 7

[00149] For the test samples of Examples 1-5 and the corresponding Comparative Examples 1-5, the mean time (n=5) to reach the maximum RLU measurement was determined. The results are reported in Table 15.

[00150] Table 15.

Example Number	Mean Time to the Maximum RLU Measurement in seconds (n=5)
Example 1	40
Comparative Example 1	66
Example 2	32
Comparative Example 2	68
Example 3	18
Comparative Example 3	42
Example 4	12
Comparative Example 4	40
Example 5	10
Comparative Example 5	24

[00151] Example 8

[00152] The same procedure as described in Example 1 was followed with the exception that ATP Test Apparatus 2 was used instead of ATP Test apparatus 1. A total of five replicate samples were tested and the results are presented in Table 16.

[00153] Comparative Example 8

[00154] The same procedure was used as in Example 8 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU

measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 17.

[00155] Table 16. Sampling Device of Example 8

Time (seconds)	RLU Measurement at 10°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	7,582	7,920	8,377	13,883	4,142
20	7796	9,053	9,278	15,017	4,286
30	8,010	9,398	9,428	15,221	4,607
40	7,995	9,445	9,377	15,108	4,630
50	7,987	9,398	9,294	14,952	4,665
60	7,944	9,354	9,184	14,806	4,654
70	7,966	9,306	9,075	14,642	4,694

[00156] Table 17. Sampling Device of Comparative Example 8

Time (seconds)	RLU Measurement at 10°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	4,426	4,053	5,864	3,969	4,366
20	6,182	6,637	8,268	5,093	5,912
30	6,482	7,371	8,940	5,572	6,910
40	7,153	7,498	9,217	5,820	7,457
50	7,275	7,506	9,245	5,997	7,784
60	7,270	7,492	9,215	6,071	7,960
70	7,284	7,428	9,121	6,159	8,052

[00157] Example 9

[00158] The same procedure as described in Example 8 was followed with the exception that the tests were conducted at 15°C. A total of five replicate samples were tested and the results are presented in Table 18.

[00159] Comparative Example 9

[00160] The same procedure was used as in Example 9 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 19.

[00161] Table 18. Sampling Device of Example 9

Time (seconds)	RLU Measurement at 15°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	15,025	8,107	6,458	12,972	8,773
20	15,109	8,434	8,206	13,081	9,419
30	15,248	8,478	8,679	13,201	9,550
40	15,271	8,385	8,843	13,282	9,546
50	15,202	8,322	8,884	13,368	9,547
60	15,189	8,302	8,881	13,417	9,524
70	15,148	8,212	8,697	13,419	9,532

[00162] Table 19. Sampling Device of Comparative Example 9

Time (seconds)	RLU Measurement at 15°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	11,468	10,729	11,779	11,755	14,367
20	15,593	14,629	12,242	12,444	15,399
30	17,395	16,396	12,237	12,531	15,488
40	18,193	17,261	12,208	12,498	15,499
50	18,533	17,616	12,232	12,555	15,413
60	18,589	17,789	12,156	12,533	15,340
70	18,613	17,831	12,124	12,483	15,343

[00163] Example 10

[00164] The same procedure as described in Example 8 was followed with the exception that the tests were conducted at 20°C. A total of five replicate samples were tested and the results are presented in Table 20.

[00165] Comparative Example 10

[00166] The same procedure was used as in Example 10 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 21.

[00167] Table 20. Sampling Device of Example 10

Time (seconds)	RLU Measurement at 20°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	11,902	11,196	16,438	18,096	9,417
20	12,214	11,307	16,112	17,877	9,496
30	12,167	11,402	15,837	17,502	9,523
40	12,208	11,469	15,587	17,372	9,549
50	12,238	11,514	15,331	17,176	9,533
60	12,239	11,541	15,143	17,049	9,562
70	12,255	11,559	14,948	16,867	9,564

[00168] Table 21. Sampling Device of Comparative Example 10

Time (seconds)	RLU Measurement at 20°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	22,170	20,178	10,403	13,474	16,213
20	25,171	24,350	12,549	16,670	18,496
30	26,019	25,627	13,465	17,505	19,090
40	26,203	25,860	13,676	17,754	19,188
50	26,052	25,793	16,844	17,737	19,154
60	25,829	25,664	13,905	17,713	19,094
70	25,593	25,566	13,876	17,635	19,071

[00169] Example 11

[00170] The same procedure as described in Example 8 was followed with the exception that the tests were conducted at 25°C. A total of five replicate samples were tested and the results are presented in Table 22.

[00171] Comparative Example 11

[00172] The same procedure was used as in Example 11 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 23.

[00173] Table 22. Sampling Device of Example 11

Time (seconds)	RLU Measurement at 25°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	17,794	10,518	18,097	10,069	16,054
20	17,586	10,450	17,697	10,427	16,035
30	17,421	10,404	17,503	10,730	15,824
40	17,272	10,349	17,363	10,936	15,775
50	17,143	10,323	17,147	10,980	15,679
60	17,030	10,230	16,893	11,081	15,517
70	16,915	10,136	16,666	11,060	15,432

[00174] Table 23. Sampling Device of Comparative Example 11

Time (seconds)	RLU Measurement at 25°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	28,554	22,254	27,263	22,646	15,920
20	33,683	25,660	32,905	23,686	18,535
30	34,131	26,048	33,842	24,117	18,893
40	34,082	25,904	33,749	24,443	18,822
50	33,774	25,726	33,408	24,540	18,656
60	33,559	25,530	33,040	24,636	18,430
70	33,318	25,330	32,625	24,717	18,274

[00175] Example 12

[00176] The same procedure as described in Example 8 was followed with the exception that the tests were conducted at 30°C. A total of five replicate samples were tested and the results are presented in Table 24.

[00177] Comparative Example 12

[00178] The same procedure was used as in Example 12 with the exception that the sampling device was coated with Coating Formulation 2, instead of Coating Formulation 1. The RLU measurements were taken every 10 seconds over a 70 second time period. A total of five replicate samples were tested and the results are presented in Table 25.

[00179] Table 24. Sampling Device of Example 12

Time (seconds)	RLU Measurement at 30°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	11,951	15,440	16,488	10,797	12,971
20	11,896	15,130	16,466	10,846	12,948
30	11,870	14,920	16,374	10,778	12,921
40	11,832	14,827	16,375	10,751	12,835
50	11,800	14,702	16,283	10,660	12,813
60	11,783	14,557	16,220	10,605	12,733
70	11,700	14,438	16,135	10,513	12,655

[00180] Table 25. Sampling Device of Comparative Example 12

Time (seconds)	RLU Measurement at 30°C				
	Sample 1	Sample 2	Sample 3	Sample 4	Sample 5
10	19,871	19,145	23,539	22,318	19,116
20	21,523	20,781	25,727	24,087	20,417
30	21,499	21,001	25,837	24,132	20,291
40	21,322	21,047	25,717	24,039	20,154
50	21,233	20,995	25,435	23,809	19,985
60	21,038	20,990	25,164	23,638	19,878
70	20,926	20,949	24,993	23,557	19,784

[00181] Example 13

[00182] For the test samples of Examples 8-12 and the corresponding Comparative Examples 8-12, the percent increase in the RLU measurement between the first time point (10 seconds) and the second time point (20 seconds) was calculated using the following equation:

$$\% \text{ Increase in RLU} = \{[(\text{RLU at 20 sec}) - (\text{RLU at 10 sec})] / (\text{RLU at 10 sec})\} \times 100$$

[00183] The mean percent increase (n=5) in the RLU measurement is reported in Table 26.

[00184] Table 26.

Example Number	Mean Percent Increase in the RLU Measurement (n=5)	Standard Deviation
Example 8	7.9	4.8
Comparative Example 8	41.6	13.3

Example 9	7.9	11.0
Comparative Example 9	17.9	16.8
Example 10	0.2	1.8
Comparative Example 10	18.5	4.5
Example 11	-0.1	2.2
Comparative Example 11	15.0	6.2
Example 12	-0.5	0.9
Comparative Example 12	8.2	0.9

[00185] Example 14

[00186] For the test samples of Examples 8-12 and the corresponding Comparative Examples 8-12, the mean time (n=5) to reach the maximum RLU measurement was determined. The results are reported in Table 27.

[00187] Table 27.

Example Number	Mean Time to the Maximum RLU Measurement in seconds (n=5)
Example 8	40
Comparative Example 8	62
Example 9	44
Comparative Example 9	50
Example 10	46
Comparative Example 10	42
Example 11	20
Comparative Example 11	38
Example 12	12
Comparative Example 12	28

[00188] The complete disclosure of all patents, patent applications, and publications, and electronically available material cited herein are incorporated by reference. In the event that any inconsistency exists between the disclosure of the present application and the disclosure(s) of any document incorporated herein by reference, the disclosure of the present application shall govern. The foregoing detailed description and examples have been given for clarity of understanding only. No unnecessary limitations are to be understood therefrom. The invention

is not limited to the exact details shown and described, for variations obvious to one skilled in the art will be included within the invention defined by the claims.

[00189] All headings are for the convenience of the reader and should not be used to limit the meaning of the text that follows the heading, unless so specified.

[00190] Various modifications may be made without departing from the spirit and scope of the invention. These and **other** embodiments are within the scope of the following claims.

What is claimed is:

1. A method, comprising:
 - using a sampling device to obtain a predetermined volume of sample;
 - wherein the sampling device comprises a sampling portion that comprises a fibrous material or a foam material;
 - wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH of about 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher;
 - wherein the liquid reagent composition comprises a luciferin;
 - contacting the predetermined volume of sample with the pH-adjusting reagent and the liquid reagent composition in a container to form a reaction mixture; and
 - using a luminometer to detect light emitted from the reaction mixture;
 - wherein the container comprises a cuvette portion adapted to be operationally coupled to the luminometer.
2. A method, comprising:
 - using a sampling device with a surface to obtain a sample of residue from a surface;
 - wherein the sampling portion comprises a fibrous material or a foam material;
 - wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with a liquid reagent composition having a pH of about 6.8 or lower, changes the pH of the liquid reagent composition to 6.9 or higher;
 - wherein the liquid reagent composition comprises a luciferin;
 - after obtaining the sample of residue, contacting the sample and the pH-adjusting reagent with the liquid reagent composition in a container to form a reaction mixture; and
 - using a luminometer to detect light emitted from the reaction mixture;
 - wherein the container comprises a cuvette portion adapted to be operationally coupled to the luminometer.
3. The method of claim 1 or claim 2, further comprising the step of agitating the sampling portion and the liquid reagent composition in the container.
4. The method of any one of claims 1 through 3, wherein the liquid reagent composition further comprises a luciferase enzyme.

5. The method of any one of claims 1 through 4, wherein contacting the sampling device comprising the sample with liquid reagent composition comprises contacting the sampling device with the liquid reagent composition at a temperature within a range of 10° C and 35° C, inclusive.

6. The method of any one of claims 1 though 5 wherein, after contacting the sampling device with liquid reagent composition, a substantially steady-state amount of light is emitted from the composition in less than 20 seconds.

7. An apparatus, comprising:

a container with an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer;

a liquid reagent composition comprising luciferin, wherein the liquid reagent composition is disposed in a closed compartment, wherein the pH of the liquid reagent composition is about 6.8 or lower; and

a sampling device having a sampling portion;

wherein the sampling portion is adapted to acquire and releasably retain a sample;

wherein the sampling portion comprises a fibrous or a foam material;

wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher.

8. A kit, comprising:

a container with an opening and a cuvette portion that is adapted to be operationally coupled to a luminometer;

a liquid reagent composition comprising luciferin, wherein the liquid reagent composition is disposed in a closed compartment, wherein the pH of the liquid reagent composition is about 6.8 or lower; and

a sampling device having a sampling portion;

wherein the sampling portion is adapted to acquire and releasably retain a sample;

wherein the sampling portion comprises a fibrous or a foam material;

wherein the sampling device comprises a coating that includes an effective amount of a pH-adjusting reagent that, when contacted with the liquid reagent composition, changes the pH of the liquid reagent composition to 6.9 or higher.

9. The apparatus of claim 7 or the kit of claim 8, wherein the sampling portion is adapted to obtain a predetermined volume of liquid.

10. The apparatus or the kit of any one of claims 7 through 9, wherein at least a portion of the coating is disposed on the sampling portion of the sampling device.

11. The apparatus or the kit of any one of claims 7 through 10, wherein the pH-adjusting reagent comprises a water-soluble reagent.

12. The apparatus or the kit of any one of claims 7 through 11, wherein the coating comprises a dry coating.

13. The apparatus or the kit of any one of claims 7 through 11, wherein the coating comprises a liquid coating.

14. The apparatus or the kit of claim 13, wherein the liquid coating comprises a humectant.

15. The apparatus or the kit of any one of claims 7 through 14, wherein the pH-adjusting reagent comprises a buffer component selected from the group consisting of N-[2-hydroxyethyl] piperazine-N'-[2-ethanesulfonic acid] (HEPES), N-[tris(hydroxymethyl)methyl]glycine (TRICINE), and combinations thereof.

16. The apparatus or the kit of any one of claims 7 through 15, wherein the coating further comprises an effective amount of a cell extractant.

17. The apparatus or the kit of any one of claims 7 through 9, wherein the luciferase enzyme comprises a recombinant luciferase enzyme having luciferase activity that is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme.

18. The apparatus or the kit of any one of claims 7 through 16, wherein the luciferase enzyme consists essentially of a recombinant luciferase enzyme having luciferase activity that

is less sensitive to variations in temperature, ionic detergents, and reducing agents than a corresponding non-recombinant luciferase enzyme.

19. The apparatus or the kit of any one of claims 7 through 18, wherein the coating does not comprise an effective amount of a buffer component comprising phosphate.

20. The apparatus or the kit of any one of claims 7 through 19, wherein the predetermined volume is about 0.01 milliliters to about 0.25 milliliters.




Fig. 1

Fig. 2





Fig. 3

*Fig. 4**Fig. 5*

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2013/027631

A. CLASSIFICATION OF SUBJECT MATTER
INV. C12Q1/00 C12Q1/66
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
C12Q G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, BIOSIS, EMBASE, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>WO 2009/140356 A1 (3M INNOVATIVE PROPERTIES CO [US]; BENNION NERYS [GB]; WATKIN JAMES [GB]) 19 November 2009 (2009-11-19) page 3, line 10 - line 17 page 7, line 13 - page 8, line 14 page 8, line 21 - page 9, line 7 page 13, line 21 - page 16, line 11 page 18, line 8 - line 28 page 19, line 6 - line 13 example 3 figures 1,2</p> <p style="text-align: center;">-----</p> <p style="text-align: center;">-/-</p>	1-20

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
14 May 2013	23/05/2013

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Chrétien, Eva Maria

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2013/027631

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	Sigma: "BIOLUMINESCENT DETERMINATION OF ATP WITH LUCIFERASE-LUCIFERIN", 1 November 1991 (1991-11-01), pages 1-6, XP055062780, Retrieved from the Internet: URL: http://www.sigmaldrich.com/etc/media/documents/Sigma/Bulletin/10633bul.Par.0001.File.tmp/10633bul.pdf [retrieved on 2013-05-14] page 4, paragraph 1 -----	1-20
Y	WO 97/03209 A1 (CHARM SCIENCES INC [US]; SKIFFINGTON RICHARD [US]; ZOMER ELIEZER [US]) 30 January 1997 (1997-01-30) page 24, line 12 - line 15 -----	1-20
X	US 7 494 781 B1 (CHARM STANLEY E [US] ET AL) 24 February 2009 (2009-02-24) column 2, line 64 - column 5, line 12 column 5, line 38 - line 50 column 14, line 9 - line 40 figures 1, 2 examples 1, 2 -----	1-20
Y	US 4 036 212 A (KARUHN RICHARD F) 19 July 1977 (1977-07-19) column 6, line 60 - column 7, line 1 claims 1-3 -----	1-20
Y	US 2006/073537 A1 (CAIRNS JAMES E [CA] ET AL CAIRNS JAMES C [CA] ET AL) 6 April 2006 (2006-04-06) paragraph [0018] - paragraph [0026] -----	1-20
A	WO 2010/129726 A1 (3M INNOVATIVE PROPERTIES CO [US]; RAJAGOPAL RAJ [US]; WRIGHT ROBIN E [I]) 11 November 2010 (2010-11-11) the whole document -----	1-20
A	WO 03/050513 A2 (BIOCONTROL SYSTEMS INC [US]) 19 June 2003 (2003-06-19) the whole document -----	1-20
A	WO 97/23596 A1 (BIOTRACE LTD [GB]; GOODFIELD CLIVE [GB]; MILLER ANNE TREGONING [GB]; P) 3 July 1997 (1997-07-03) the whole document -----	1-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2013/027631

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
WO 2009140356	A1	19-11-2009		CA 2724087 A1 CN 102083955 A EP 2276828 A1 JP 2011523358 A US 2012329081 A1 WO 2009140356 A1		19-11-2009 01-06-2011 26-01-2011 11-08-2011 27-12-2012 19-11-2009
WO 9703209	A1	30-01-1997		AU 713409 B2 AU 4756896 A CA 2226857 A1 DE 69629582 D1 DE 69629582 T2 EP 0861330 A1 JP H11514849 A US 5965453 A US 6180395 B1 WO 9703209 A1		02-12-1999 10-02-1997 30-01-1997 25-09-2003 24-06-2004 02-09-1998 21-12-1999 12-10-1999 30-01-2001 30-01-1997
US 7494781	B1	24-02-2009		US 7494781 B1 US 2009148852 A1 US 2011065116 A1		24-02-2009 11-06-2009 17-03-2011
US 4036212	A	19-07-1977		NONE		
US 2006073537	A1	06-04-2006		NONE		
WO 2010129726	A1	11-11-2010		US 2012082977 A1 WO 2010129726 A1		05-04-2012 11-11-2010
WO 03050513	A2	19-06-2003		AU 2002357107 A1 BR 0214680 A CA 2469025 A1 EP 1451560 A2 JP 4467304 B2 JP 2006502376 A JP 2009092668 A MX PA04005416 A NZ 533051 A US 2003143752 A1 US 2006139631 A1 US 2008272283 A1 WO 03050513 A2		23-06-2003 30-05-2006 19-06-2003 01-09-2004 26-05-2010 19-01-2006 30-04-2009 11-10-2004 27-10-2006 31-07-2003 29-06-2006 06-11-2008 19-06-2003
WO 9723596	A1	03-07-1997		AU 1165097 A WO 9723596 A1		17-07-1997 03-07-1997