



US008330789B2

(12) **United States Patent**  
**Karnalkar et al.**

(10) **Patent No.:** **US 8,330,789 B2**

(45) **Date of Patent:** **Dec. 11, 2012**

(54) **INTEGRATED DEVICES FOR MULTIMEDIA  
CONTENT DELIVERY AND VIDEO  
CONFERENCING**

(75) Inventors: **Anup D. Karnalkar**, Allen, TX (US);  
**Jyotindra N. Shah**, Austin, TX (US)

(73) Assignee: **AT&T Intellectual Property I, L.P.**,  
Atlanta, GA (US)

(\* ) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 1350 days.

(21) Appl. No.: **11/932,514**

(22) Filed: **Oct. 31, 2007**

(65) **Prior Publication Data**

US 2009/0109278 A1 Apr. 30, 2009

(51) **Int. Cl.**  
**H04N 7/14** (2006.01)

(52) **U.S. Cl.** ..... **348/14.04**; 348/14.01

(58) **Field of Classification Search** ..... 348/14.01,  
348/14.02, 14.03, 14.04; 725/37-61, 131,  
725/133, 139, 141, 151, 153

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,724,106	A *	3/1998	Autry et al.	348/734
5,999,207	A	12/1999	Rodriguez et al.	
6,791,974	B1 *	9/2004	Greenberg	370/352
7,142,230	B2	11/2006	Novak et al.	
7,164,435	B2	1/2007	Wang et al.	
2006/0020960	A1 *	1/2006	Relan et al.	725/141

\* cited by examiner


*Primary Examiner* — Brian Ensey

(74) *Attorney, Agent, or Firm* — Jackson Walker L.L.P.

(57) **ABSTRACT**

A receiver device for use in conjunction with an MCDN includes a computer readable storage resource, a controller to execute stored instructions, a network interface coupling the device to the MCDN, and a decoder to decode streaming multimedia content received via the network interface. The receiver includes a remote control interface to detect a remote control command from a remote control device and a handset interface to communicate audio data with a handset device. A local video interface receives video data from a camera or other local video resource. The stored instructions include, a remote control application to execute remote control commands, a handset module to communicate audio data with the handset device, and a session initiation module to establish a video conferencing session. A video conferencing module integrates the audio data and the video data and communicates the integrated data via the video conferencing session.

**17 Claims, 4 Drawing Sheets**








FIG. 2




FIG. 3




FIG. 4

# INTEGRATED DEVICES FOR MULTIMEDIA CONTENT DELIVERY AND VIDEO CONFERENCING

## BACKGROUND

### 1. Field of the Invention

The present disclosure relates to multimedia communication networks.

### 2. Description of the Related Art

Conventional videophone technology involves a stand-alone transceiver, a display device, and a camera. Because each of these units occupy space and may be relatively expensive, conventional video conferencing implementations are not ideally suited, especially in the consumer market.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram of an implementation of a multimedia content distribution network according to one embodiment;

FIG. 2 is a block diagram of selected elements of a set top box suitable for use in the network of FIG. 1;

FIG. 3 is a block diagram of an embodiment of the set top box of FIG. 2 emphasizing video conferencing functionality; and

FIG. 4 is a block diagram of an embodiment of a remote control/handset device emphasizing video conferencing functionality.

## DESCRIPTION OF THE EMBODIMENT(S)

In one aspect, a receiver device for use in conjunction with a multimedia content distribution network (MCDN) is disclosed. The receiver device includes a computer readable storage resource, a controller to execute stored instructions, a network interface coupling the device to the MCDN, and a decoder to decode streaming multimedia content received via the network interface. The receiver includes a remote control interface to detect a remote control command from a remote control device and a handset interface to communicate audio data with a handset device. The remote control device and the handset device may be integrated within a single physical device. A local video interface receives video data from a camera or other local video resource. The stored instructions include, a remote control application to execute remote control commands, a handset module to communicate audio data with the handset device, and a session initiation module to establish a video conferencing session. A video conferencing module integrates the audio data and the video data and communicates the integrated data via the video conferencing session. The handset module may be operable to communicate digital audio data with the handset device. For example, the handset module may be operable to support a digital enhanced cordless telecommunication (DECT) compliant communication with the handset device. The session initiation module may be implemented with a session initiation protocol (SIP) compliant client. The receiver device may be implemented as a set top box (STB). In these embodiments, the STB is operable to communicate with a residential gateway via a local area network connection. The remote control interface comprises an infrared interface operable to detect infrared signals from the remote control device.

In another aspect, a portable communication device suitable for use in conjunction with an STB is disclosed, where the STB is operably coupled to the MCDN. The communication device includes a set of one or more remote control buttons, a button interface to generate remote control com-

mands responsive to assertion of remote control buttons, a remote control interface to transmit remote control commands to the STB, and a handset interface to communicate audio data with the STB. The portable communication device further includes a microphone operable to convert sound to audio data and to provide the audio data to the handset interface and a speaker operable to convert audio data from the handset interface to sound. The handset interface may be operable to support a DECT compliant connection, or another digital and/or wireless connection with the STB. The portable device may include a small display to display, for example, CallerID information.

In another aspect, a disclosed multimedia service includes providing a subscriber with a STB to receive multimedia content and providing the subscriber with a remote control operable to transmit remote control commands to the STB. The remote control includes a speaker to generate sound and a microphone to receive sound. The STB and the remote control are operable to communicate audio data with each other. The STB is operable to establish a multimedia conferencing session and further operable to transmit and receive video conferencing content via the established session.

In the following description, details are set forth by way of example to facilitate discussion of the disclosed subject matter. It should be apparent to a person of ordinary skill in the field, however, that the disclosed embodiments are exemplary and not exhaustive of all possible embodiments. Throughout this disclosure, a hyphenated form of a reference numeral refers to a specific instance of an element and the un-hyphenated form of the reference numeral refers to the element generically or collectively. Thus, for example, widget **102-1** refers to an instance of a widget class, which may be referred to collectively as widgets **102** and any one of which may be referred to generically as a widget **102**.

Before describing details of applications, disclosed herein, for use in conjunction with a multimedia content distribution network, selected aspects of one embodiment of the network and selected devices used to implement the network are described to provide context.

Referring now to the drawings, FIG. 1 illustrates selected aspects of an embodiment of a multimedia content distribution network (MCDN) **100**. MCDN **100** is operable for distributing television programs, video on demand content including movies, radio programs including music content, and a variety of other types of multimedia content to multiple subscribers. MCDN **100** as shown includes a client side **101** and a service provider side **102**, sometimes referred to herein simply as server side **102**. Client side **101** and server side **102** are linked by an access network **130**.

Access network **130** connects client side **101** and server side **102**. In embodiments of MCDN **100** that leverage telephony hardware and infrastructure, access network **130** may include a "local loop" or "last mile," which refers to the physical connection between a subscriber's home or business and a local exchange. In these embodiments, the physical layer of access network **130** may include twisted pair copper cables, fiber optics cables employed either as fiber to the curb (FTTC) or fiber to the home (FTTH), or another suitable broadband capable medium.

As shown in FIG. 1, client side **101** depicts two of a potentially large number of client(s) **120**, each of which may represent a subscriber or subscriber household. Each client **120** as shown in FIG. 1 includes a display **124**, a client-side receiver operable to receive and process a multimedia signal, a remote control device **126** operable to communicate with the client-side receiver, and a residential gateway (RG) **122** for interfacing the receiver to access network **130**.

In the embodiment depicted in FIG. 1, the client-side receiver is implemented as an STB 121, which is described in greater detail below. In some embodiments, RG 122 may include elements of a broadband modem such as a DSL modem as well as elements of a router and/or access point for a local area network (LAN) 127. In some embodiments, LAN 127 is a wired or wireless Ethernet LAN.

In some embodiments, display 124 is an NTSC and/or PAL compliant display device. STB 121, display 124, or both may include a frequency tuner for use in systems where one or more channels of multimedia content are modulated onto an RF carrier signal and delivered to RG 122. In other embodiments where, for example, multimedia content is delivered to client side 101 as a packet-based stream, frequency tuners may not be required. In these embodiments, clients 120 may support or comply with various network protocols including, as examples, streaming protocols such as RDP (reliable datagram protocol) over UDP/IP (user datagram protocol/internet protocol) as well as more conventional web protocols such as HTTP (hypertext transport protocol) over TCP/IP (transport control protocol).

The elements of server side 102 as depicted in FIG. 1 emphasize various broad categories or “tiers” of devices and/or services desirable for acquiring and delivering multimedia content to a networked base of subscribers. As depicted in FIG. 1, for example, server side 102 includes a multimedia content acquisition tier 106, a multimedia content delivery tier 107, an application tier 105, a database tier 109, and an operations system support (OSS) and business systems support (BSS) tier 108. In the depicted embodiment, each tier 105 through 109 is demarcated by a corresponding routing and switching device 115 through 119, respectively. Routing and switching devices 115 through 119 are referred to herein simply as a switches 115 through 119.

In addition to providing routing and switching functions, switches 115 through 119 may implement hardware and/or software firewalls and/or other security functions (not depicted explicitly) that define at least some of the boundaries of a private network 110. Private network 110 may support any of various existing or future protocols for providing reliable real-time streaming multimedia content including, as examples, real-time transport protocol (RTP), real-time control protocol (RTCP), file transfer protocol (FTP), and real-time streaming protocol (RTSP). In addition, the depicted implementation of MCDN 100 includes switches that connect some of the server-side tiers to a public network 112. As suggested by their names, private network 110 is a restricted access network while public network 112 is a freely accessible network. In some embodiments, public network 112 represents or includes an IP-based network, e.g., the Internet, and private network 110 is another IP-based network. In other embodiments, private network 110 may be any network suitable for transmitting digital video content including, for example, a digital cable-based network, a digital satellite network, and or another suitable network.

Acquisition tier 106 encompasses various devices and/or services to acquire multimedia content, reformat it when necessary, and process it for delivery to subscribers over private network 110 and access network 130. Acquisition tier 106 may include, for example, systems for capturing analog and/or digital content feeds, either directly from a content provider or from a content aggregation facility. Content feeds transmitted via VHF/UHF broadcast signals may be captured by an antenna 141 and delivered to live acquisition server 140. Similarly, live acquisition server 140 may capture down linked signals transmitted by a satellite 142 and received by a parabolic dish 144. In addition, live acquisition server 140

may acquire programming feeds transmitted via high-speed fiber feeds or other suitable transmission means. VoD acquisition server 150 receives content from one or more VoD sources that may be external to the MCDN 100 including, as examples, discs represented by a DVD player 151, or transmitted feeds (not shown). Acquisition resources 106 may further include signal conditioning systems and content preparation systems for encoding content.

After acquiring multimedia content, acquisition tier 106 may transmit acquired content over private network 110, for example, to one or more servers in content delivery tier 107 via content delivery switch 117. The content may be compressed and/or encrypted prior to transmission. In the depicted implementation, content delivery tier 107 includes a content delivery server 155 in communication with a live or real-time content server 156 and a VoD delivery server 158. For purposes of this disclosure, the use of the term “live” or “real-time” in connection with content server 156 is intended primarily to distinguish the applicable content from the content provided by VoD delivery server 158. The content provided by a VoD server is sometimes referred to as time-shifted content to emphasize the ability to obtain and view VoD content substantially without regard to the time of day or day of week.

Content delivery tier 107 includes devices and/or services that are, in some embodiments, responsible for creating video streams, e.g., MPEG-2 video streams, suitable for transmission over private network 110 and/or access network 130 to clients 120. The video streams may be “packetized” video streams comprised of multiple network data packets. Content delivery server 155 may employ unicast and broadcast techniques when making content available to a subscriber.

Client-facing switch 113 as shown is further coupled to a client gateway 153 and a terminal server 154 that is operable to provide terminal devices with a connection point to the private network 110. Client gateway 153 may provide subscriber access to private network 110 and the resources coupled thereto. Client gateway 153 may also prevent unauthorized devices, such as hacker computers or stolen set-top boxes, from accessing the private network 110. Accordingly, in some embodiments, when an STB 121 accesses MCDN 100, client gateway 153 verifies subscriber information by communicating with user store 172 via the private network 110.

MCDN 100 as depicted includes application resources 105, which communicate with private network 110 via application switch 115. Application resources 105 as shown include an application server 160 operable to host or otherwise facilitate one or more subscriber applications 165 that may be made available to system subscribers. For example, subscriber applications 165 as shown include an electronic programming guide (EPG) application 163.

Application server 160 as shown also hosts an application referred to generically as user application 164. User application 164 represents or encompasses an application that may deliver a value added feature to subscribers. User application 164 is included in FIG. 1 to emphasize the ability to extend the network’s functionality via network hosted applications.

As shown in FIG. 1, a database switch 119 connects database tier 109 to private network 110 and to public network 112. Database tier 109 as shown includes a database server 170 that manages a system storage resource 172, also referred to herein as user store 172. User store 172 as shown includes one or more user profiles 174. In some embodiments, user profiles 174 include account information and subscriber preference information pertaining to a corresponding subscriber. User profiles 174 may be accessed by applications executing

on application server **160** and/or applications executing locally on a client **120**, e.g., executing on STB **121**.

MCDN **100** as shown includes OSS/BSS tier **108** connected to public network **112** via OSS/BSS switch **118**. OSS/BSS tier **108** as shown includes an OSS/BSS server **181** that

hosts operations support services including remote management via a management server **182**. OSS/BSS resources **108** may include a monitoring server (not depicted) that monitors network devices within or coupled to MCDN **100** via, for example, a simple network management protocol (SNMP).

Turning now to FIG. 2, selected components of one embodiment of the STB **121** depicted in FIG. 1 are illustrated. Some embodiments of STB **121** include hardware and/or software functionality to receive streaming multimedia data from an IP-based network and process the data to produce video and audio signals suitable for delivery to an NTSC, PAL, or other type of display **124**. In addition, some embodiments of STB **121** may include resources to store multimedia content locally and resources to play back locally stored multimedia content when requested.

In the embodiment depicted in FIG. 2, STB **121** includes a general purpose processing core represented as controller **260** in communication with various special purpose multimedia modules. These modules may include a transport/de-multiplexer module **205**, an A/V decoder **210**, a video encoder **220**, an audio DAC **230**, and an RF modulator **235**. Although FIG. 2 depicts each of these modules discretely, STB **121** may be implemented with a system on chip (SoC) device that integrates controller **260** and each of these multimedia modules. In still other embodiments, STB **121** may include an embedded processor serving as controller **260** and at least some of the multimedia modules may be implemented with a general purpose digital signal processor (DSP) and supporting software.

Regardless of the implementation details of the multimedia processing hardware, STB **121** as shown in FIG. 2 includes a network interface **202** that enables STB **121** to communicate with an external network such as LAN **127**. Network interface **202** may share many characteristics with conventional network interface cards (NICs) used in personal computer platforms. For embodiments in which LAN **127** is an Ethernet LAN, for example, network interface **202** implements level 1 (physical) and level 2 (data link) layers of a standard communication protocol stack by enabling access to twisted pair, fiber, or other form of physical network medium and by supporting low level addressing using MAC addressing. In these embodiments, every network interface **202** includes a globally unique 48-bit MAC address **203** stored in a ROM or other persistent storage element of network interface **202**. Similarly, at the other end of the LAN connection **127**, RG **122** has a network interface (not depicted) with its own globally unique MAC address.

Network interface **202** may further include or support software or firmware providing one or more complete network communication protocol stacks. Where network interface **202** is tasked with receiving streaming multimedia communications, for example, network interface **202** may include a streaming video protocol stack such as an RTP/UDP stack. In these embodiments, network interface **202** is operable to receive a series of streaming multimedia packets and process them to generate a digital multimedia stream **204** that is provided to transport/demux **205**.

The digital multimedia stream **204** is a sequence of digital information that may include video data streams interlaced with audio data streams. The video and audio data contained in digital multimedia stream **204** may be referred to as “in-band” data. Multimedia stream **204** may also include “out-

of-band” data, which might include, for example, billing data, decryption data, and data enabling the IPTV service provider to manage IPTV client **120** remotely.

Transport/demux **205** as shown is operable to segregate and, if needed, decrypt the audio, video, and any out-of-band data in digital multimedia stream **204**. Transport/demux **205** outputs a digital audio stream **206**, a digital video stream **207**, and an out-of-band digital stream **208** to A/V decoder **210**. Transport/demux **205** may also, in some embodiments, support or communicate with various peripheral interfaces of STB **121** including an IR interface **250** suitable for use with an IR remote control unit (not shown) and a front panel interface (not shown).

A/V decoder **210** processes digital audio, video, and out-of-band streams **206**, **207**, and **208** to produce a native format digital audio stream **211** and a native format digital video stream **212**. A/V decoder **210** processing may include decompression of digital audio stream **206** and/or digital video stream **207**, which are generally delivered to STB **121** as compressed data streams. In some embodiments, digital audio stream **206** and digital video stream **207** are MPEG compliant streams and, in these embodiments, A/V decoder **210** is an MPEG decoder.

The native format digital audio stream **211** as shown in FIG. 2 is routed to an audio DAC **230** to produce an audio output signal **231**. The native format digital video stream **212** is routed to an NTSC/PAL or other suitable video encoder **220**, which generates digital video output signals suitable for presentation to an NTSC or PAL compliant display device **204**. In the depicted embodiment, for example, video encoder **220** generates a composite video output signal **221** and an S video output signal **222**. An RF modulator **235** receives the audio and composite video outputs signals **231** and **221** respectively and generates an RF output signal **221** suitable for providing to an analog input of display **204**.

In addition to the multimedia modules described, STB **121** as shown includes various peripheral interfaces. STB **121** as shown includes, for example, a USB interface **240**, an interface **255** for communicating with a telephony handset, and a local video interface **256** for receiving video data from a camera **258** or another source of local video data. The illustrated embodiment of STB **121** includes storage resources **270** that are accessible to controller **260** and possibly one or more of the multimedia modules. Storage **270** may include DRAM or another type of volatile storage identified as memory **275** as well as various forms of persistent or non-volatile storage including flash memory **280** and/or other suitable types of persistent memory devices including ROMs, EPROMs, and EEPROMs. In addition, the depicted embodiment of STB **121** includes a mass storage device in the form of one or more magnetic hard disks **295** supported by an IDE compliant or other type of disk drive **290**. Embodiments of STB **121** employing mass storage devices may be operable to store content locally and play back stored content when desired.

Turning now to FIG. 3, selected elements of an embodiment of STB **121** are depicted to emphasize video conferencing functionality. As depicted in FIG. 3, STB **121** includes various software modules **302** through **310** to support video conferencing functionality. The software modules represent computer executable instructions embedded in one or more of the storage components of storage **270**. As shown in FIG. 3, the software modules include a remote control application **302**, a SIP client application **304**, a handset module **306**, a video conferencing module **308**, and a camera module **310**.

Remote control application **302** represents code operable to execute a remote control initiated function in response to a

subscriber or other user asserting a remote control button on the remote control device **126**. Remote control application **126** may include or have access to a table indicating procedures to execute in response to assertion of applicable remote control buttons. In some embodiments, remote control commands are received by STB **121** via its RC interface **250**, which may be an infrared or other form of wireless communication interface.

In the depicted embodiment, STB **121** is operable, not only to participate in a multimedia conferencing session, but also to establish the session for itself and one or more external devices. STB **121** as depicted in FIG. 3, for example, includes a SIP client application **304**. SIP is a protocol for establishing a multimedia session and SIP client application **304** is compliant with the SIP protocol. Integrating the SIP client application **304** into STB **121** beneficially simplifies the implementation of hardware needed to support video conferencing.

Handset module **306** enables STB **121** to communicate video conferencing audio data with a handset device. In some embodiments, the handset device is integrated within the remote control device **126** so that the STB **121** and remote control device **126** are operable to communicate audio data with each other. In some embodiments, the audio data is communicate wirelessly and/or digitally between STB **121** and remote control device **126**. Camera module **310** is executed by controller **260** to process video information received from local video input interface **256**. Video conferencing module **308** supports video conferencing functionality by being operable to integrate audio data from remote control device **126** and video data from camera **258** into multimedia data and being further operable to transmit and received multimedia data via the established video conferencing session.

Referring now to FIG. 4, selected elements of an embodiment of remote control **126** are depicted to emphasize the dual functionality of remote control device **126** as a remote and a video conferencing handset. In the depicted embodiment, remote control device **126** includes a remote control interface **323**, a handset interface **322**, a speaker **324**, an LCD **326**, a controller **328**, button interface **330**, a set of buttons **331**, which are shown with dashed lines and transposed relative to remote control device **126** for the sake of clarity, a cordless module **332**, and a microphone **334**. Microphone **334** converts sound to audio data for transmission while speaker **324** converts received audio data to sound. Button I/F **330** and RC interface **323** enable remote control device **126** to transmit remote control commands wirelessly to STB **121** via an infrared or other wireless signal.

Handset interface **322**, in conjunction with cordless module **332**, is operable to communicate audio data with STB **121**. In one embodiment, cordless module **332** is a DECT compliant module that enables remote control device **126** to communicate audio data using DECT compliant connections with STB **121** serving as the DECT base station. LCD **326** may be used in conjunction with this embodiment to display DECT information including, for example, CallerID information.

In one particular implementation, STB **121** is operable as a DECT base station and remote control **126** is operable as a DECT handset. DECT functionality enables the implementation of beneficial features. For example, multiple DECT handsets can register with a single DECT base station and thereby communicate audio data to a designated base station. A subscriber with multiple STBs could designate one of the STBs as the video conferencing STB, establish that STB as the DECT base station, and register all of his or her remote controls with the designated STB for telecommunications purposes. In addition, DECT supports the transmission of

information including CallerID information between a base station and a handset. If remote control device **126** is implemented within a display device such as a liquid crystal display, it could display CallerID information when an incoming call is received.

The above disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover all such modifications, enhancements, and other embodiments which fall within the true spirit and scope of the present invention. Thus, to the maximum extent allowed by law, the scope of the present invention is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

What is claimed is:

**1.** A receiver device for use in conjunction with a multimedia content distribution network, the receiver device comprising:

- a computer readable storage resource;
- a controller operable to execute instructions stored in the storage resource;
- a network interface to couple the receiver device to the multimedia content distribution network;
- a decoder to decode streaming multimedia content via the network interface;
- a remote control interface to detect a remote control command from a remote control device;
- a handset interface to communicate audio data with a handset device;
- a local video interface to receive video data from a local video resource;

wherein the instructions stored in the storage resource include:

- a remote control application to execute remote control commands received via the remote control interface;
- a handset module operable to support a telephony connection using the handset interface;
- a session initiation module operable to establish a video conferencing session; and
- a video conferencing module operable to generate integrated data by integrating the audio data and the video data and communicate the integrated data via the video conferencing session;

wherein the handset module supports digital enhanced cordless telecommunication compliant communication with the handset device.

**2.** The device of claim **1**, wherein the handset module is operable to communicate digital audio data with the handset device.

**3.** The device of claim **1**, wherein the session initiation module comprises a session initiation protocol compliant client.

**4.** The device of claim **1**, wherein the receiver device comprises a set top box.

**5.** The device of claim **4**, wherein the set top box is to communicate with a residential gateway via a local area network connection.

**6.** The device of claim **1**, wherein the remote control interface includes an infrared interface to detect infrared signals from the remote control device.

**7.** A portable communication device suitable for use in conjunction with a set top box operably coupled to a multimedia content distribution network, the communication device comprising:

- a plurality of remote control buttons;

9

a button interface to generate a remote control command responsive to assertion of a selected remote control button;

a remote control interface to transmit the remote control command to the set top box;

a handset interface to communicate audio data with the set top box, wherein the handset interface supports digital enhanced cordless telecommunication compliant communication with the set top box;

a microphone to convert sound to audio data and to provide the audio data to the handset interface; and

a speaker to convert audio data from the handset interface to sound.

8. The device of claim 7, wherein the handset interface communicates the audio data and the remote control command wirelessly.

9. The device of claim 7, wherein the handset interface communicates digital audio data with the set top box.

10. The device of claim 7, further comprising a display operable to display information communicated via a digital enhanced cordless telecommunication compliant connection with the set top box.

11. The device of claim 10, wherein the information includes CallerID information associated with a video call.

12. The device of claim 7, wherein the remote control interface comprises an infrared interface.

13. A multimedia service comprising:  
providing a subscriber with a set top box to receive multimedia content;

10

providing the subscriber with a remote control to transmit remote control commands to the set top box;

wherein the remote control includes a speaker to generate sound and a microphone to receive sound;

wherein the set top box and the remote control communicates audio data;

wherein the set top box establishes a multimedia conferencing session and further operable to transmit and receive multimedia conference content via the established session; and

wherein the set top box and the remote control communicate via a digital enhanced cordless telecommunications compliant connection.

14. The service of claim 13, wherein the set top box and the remote control communicate audio data with each other digitally.

15. The service of claim 13, wherein the remote control device includes a liquid crystal display and displays digital enhanced cordless telecommunication information in the display.

16. The service of claim 13, wherein the set top box comprises a session initiation protocol client to establish the multimedia conference session.

17. The service of claim 13, further comprising providing the subscriber with a second set top box and a second remote control wherein the second remote control communicates remote control commands to the second set top box and wherein the second remote control communicates audio data to the first set top box.

\* \* \* \* \*